

GDCM
2.2.4

Generated by Doxygen 1.8.4

Mon Nov 4 2013 10:59:18

Contents

1	GDCM Documentation	1
2	off-screen rendering of DICOM images	3
2.1	SYNOPSIS	3
2.2	DESCRIPTION	3
2.3	PARAMETERS	3
2.4	options	3
2.4.1	options	3
2.4.2	general options	3
2.5	Simple usage	4
2.6	SEE ALSO	4
2.7	COPYRIGHT	4
3	Convert a file supported by VTK into DICOM.	5
3.1	SYNOPSIS	5
3.2	DESCRIPTION	5
3.3	PARAMETERS	5
3.4	options	5
3.4.1	options	5
3.4.2	compression options	6
3.4.3	general options	6
3.4.4	environment variable	6
3.5	DESCRIPTION	6
3.5.1	CONVERT Metalmage (mhd, mha)	6
3.5.2	CONVERT MHA/MHD	7
3.5.3	CONVERT VTI	7
3.5.4	CONVERT VTK	7
3.6	CONVERT DICOM	7
3.7	RoundTrip DICOM to MHD to DICOM	7

3.8	gdcm2vtk notes	7
3.9	SEE ALSO	8
3.10	COPYRIGHT	8
4	Tool to anonymize a DICOM file.	9
4.1	SYNOPSIS	9
4.2	DESCRIPTION	9
4.3	PARAMETERS	9
4.4	options	10
4.4.1	Required parameters	10
4.4.2	options	10
4.4.3	encryption options	10
4.4.4	dumb mode options	10
4.4.5	general options	10
4.4.6	environment variable	11
4.5	Typical usage	11
4.5.1	De-identification (anonymization, encrypt)	11
4.5.2	Re-identification (de-anonymization, decrypt)	11
4.5.3	Multiple files caveat	11
4.5.4	Dumb mode	11
4.5.4.1	Irreversible Anonymization	12
4.6	OpenSSL	12
4.6.1	Generating a Private Key	12
4.6.2	Generating a Certificate	13
4.7	DICOM Standard:	13
4.8	Warnings	13
4.9	SEE ALSO	13
4.10	COPYRIGHT	13
5	Tool to convert DICOM to DICOM.	15
5.1	SYNOPSIS	15
5.2	DESCRIPTION	15
5.3	PARAMETERS	15
5.4	options	15
5.4.1	PARAMETERS	15
5.4.2	options	15
5.4.3	image options	16
5.4.4	JPEG options	16

5.4.5	JPEG-LS options	16
5.4.6	J2K options	16
5.4.7	general options	16
5.4.8	special options	16
5.4.9	environment variable	17
5.5	Simple usage	17
5.6	Typical usage	17
5.6.1	File Meta Header	17
5.6.2	Conversion to Explicit Transfer Syntax	18
5.6.3	Compressing to lossless JPEG	18
5.6.4	Compressing to lossy JPEG	18
5.6.5	Compressing to lossless JPEG-LS	18
5.6.6	Compressing to lossy JPEG-LS	18
5.6.7	Compressing to lossless J2K	18
5.6.8	Compressing to lossy J2K	18
5.6.9	Compressing to lossless RLE	19
5.6.10	Split encapsulated DICOM:	19
5.6.11	Forcing (re)compression	19
5.6.12	Decompressing a Compressed DICOM	19
5.6.13	Compressing an uncompressed Icon	19
5.6.14	Generating an Icon	20
5.6.15	Changing the planar Configuration	20
5.7	Lossless Conversion	20
5.8	Quality Control	20
5.8.1	DCMTK / dicom3tools	20
5.8.2	VIM: vimdiff	21
5.8.3	vbindiff	21
5.9	SEE ALSO	21
5.10	COPYRIGHT	21
6	dumps differences of two DICOM files	23
6.1	SYNOPSIS	23
6.2	DESCRIPTION	23
6.3	PARAMETERS	23
6.4	options	23
6.4.1	options	23
6.4.2	general options	23

6.5	Simple usage	24
6.6	SEE ALSO	24
6.7	COPYRIGHT	24
7	dumps a DICOM file, it will display the structure and values contained in the specified DICOM file.	25
7.1	SYNOPSIS	25
7.2	DESCRIPTION	25
7.3	PARAMETERS	25
7.4	options	25
7.4.1	options	25
7.4.2	general options	26
7.4.3	special options	26
7.5	Typical usage	26
7.5.1	Printing Implicit Transfer Syntax	26
7.5.2	Print Private Attributes	27
7.5.3	SIEMENS CSA Header	27
7.5.4	GEMS Protocol Data Block	27
7.5.5	ELSCINT Protocol Information	28
7.5.6	VEPRO Protocol Information	28
7.5.7	Philips Private MR Series Data Storage (1.3.46.670589.11.0.0.12.2)	29
7.5.8	Encapsulated ASN1 Structure	30
7.6	SEE ALSO	31
7.7	COPYRIGHT	31
8	Tool to generate a DICOMDIR file from a File-Set.	33
8.1	SYNOPSIS	33
8.2	DESCRIPTION	33
8.3	PARAMETERS	33
8.4	options	33
8.4.1	Parameters	33
8.4.2	options	33
8.4.3	general options	33
8.4.4	environment variable	34
8.5	Typical usage	34
8.6	NOTE	34
8.7	SEE ALSO	34
8.8	COPYRIGHT	34

9	Manipulate DICOM image file.	35
9.1	SYNOPSIS	35
9.2	DESCRIPTION	35
9.3	PARAMETERS	35
9.4	options	35
9.4.1	PARAMETERS	35
9.4.2	options	35
9.4.3	fill options	36
9.4.4	general options	36
9.4.5	environment variable	36
9.5	Supported File Format (appropriate file extension) <code>gdcmimg</code>	36
9.6	Typical usage	37
9.6.1	Remove a rectangular part of the image	37
9.6.2	Convert RAW to DICOM	37
9.6.3	Convert PGM/PNM/PPM to DICOM	37
9.6.4	Convert RLE to DICOM	38
9.6.5	Convert JPEG to DICOM	38
9.6.6	Convert J2K to DICOM	38
9.6.7	Specifying a SOP Class UID	38
9.7	Multiple Files	38
9.8	Start Offset	38
9.9	Warning	39
9.10	SEE ALSO	39
9.11	COPYRIGHT	39
10	Display meta info about the input DICOM file.	41
10.1	SYNOPSIS	41
10.2	DESCRIPTION	41
10.3	PARAMETERS	41
10.4	options	41
10.4.1	options	41
10.4.2	general options	41
10.4.3	environment variable	42
10.5	Simple usage	42
10.5.1	<code>gdcmData</code>	42
10.5.2	Davie Clunie datasets:	42
10.5.3	Checking the md5sum of the Pixel Data	43

10.5.4 Checking if Pixel Data is lossless	43
10.6 SEE ALSO	43
10.7 COPYRIGHT	43
11 Tool to convert PDF to PDF/DICOM.	45
11.1 SYNOPSIS	45
11.2 DESCRIPTION	45
11.3 PARAMETERS	45
11.4 options	45
11.4.1 general options	45
11.5 Usage Example	46
11.6 PDF Info Mapping	46
11.7 SEE ALSO	47
11.8 COPYRIGHT	47
12 Extract Data Element Value Field.	49
12.1 SYNOPSIS	49
12.2 DESCRIPTION	49
12.3 PARAMETERS	49
12.4 options	49
12.4.1 PARAMETERS	49
12.4.2 options	49
12.4.3 general options	49
12.5 Typical usage	50
12.5.1 Copy Attribute Value to file	50
12.5.2 Extract Pixel Data	50
12.5.3 Encapsulated Syntax	50
12.5.4 Extract fragments as single file	51
12.6 Footnote about JPEG files	52
12.7 SEE ALSO	52
12.8 COPYRIGHT	52
13 Scan a directory containing DICOM files.	53
13.1 SYNOPSIS	53
13.2 DESCRIPTION	53
13.2.1 PARAMETERS	53
13.2.2 options	53
13.2.3 general options	53

13.3 Typical usage	54
13.4 Simple usage	54
13.5 Complex usage	54
13.6 SEE ALSO	54
13.7 COPYRIGHT	54
14 Tool to execute a DICOM Query/Retrieve operation	55
14.1 SYNOPSIS	55
14.2 DESCRIPTION	55
14.3 PARAMETERS	55
14.4 options	55
14.4.1 options	55
14.4.2 mode options	55
14.4.3 C-STORE options	56
14.4.4 C-FIND/C-MOVE options	56
14.4.5 C-MOVE options	56
14.4.6 general options	56
14.4.7 environment variable	56
14.5 C-ECHO usage	57
14.6 C-STORE usage	57
14.7 C-FIND usage	57
14.8 C-MOVE usage	58
14.9 patientroot notes	58
14.10Debugging	58
14.11Port Warning	58
14.12C-STORE Warnings	59
14.13C-MOVE Warnings	59
14.14C-FIND IMAGE level (Composite Object Instance)	59
14.15Storing the Query	59
14.16DICOM Public Servers	60
14.17SEE ALSO	60
14.18COPYRIGHT	60
15 Concatenate/Extract DICOM files.	61
15.1 SYNOPSIS	61
15.2 DESCRIPTION	61
15.3 PARAMETERS	61
15.4 options	61

15.4.1 options	61
15.4.2 general options	61
15.4.3 environment variable	62
15.5 Typical usage	62
15.5.1 SIEMENS Mosaic	62
15.6 SEE ALSO	63
15.7 COPYRIGHT	63
16 Simple DICOM viewer.	65
16.1 SYNOPSIS	65
16.2 DESCRIPTION	65
16.3 PARAMETERS	65
16.4 options	65
16.4.1 options	65
16.4.2 general options	65
16.5 Typical usage	66
16.6 Simple usage	66
16.7 Wiki Link	66
16.8 SEE ALSO	66
16.9 COPYRIGHT	66
17 Todo List	67
18 Deprecated List	69
19 Bug List	71
20 Namespace Index	73
20.1 Namespace List	73
21 Hierarchical Index	75
21.1 Class Hierarchy	75
22 Class Index	83
22.1 Class List	83
23 File Index	97
23.1 File List	97
24 Namespace Documentation	103
24.1 gdcm Namespace Reference	103

24.1.1	Detailed Description	117
24.1.2	Typedef Documentation	117
24.1.2.1	AEComp	117
24.1.2.2	ASComp	117
24.1.2.3	BOOL_FUNCTION_PFILE_PFILE_POINTER	117
24.1.2.4	CSComp	117
24.1.2.5	DAComp	117
24.1.2.6	DTComp	117
24.1.2.7	FileList	117
24.1.2.8	IconImage	118
24.1.2.9	LOComp	118
24.1.2.10	LTComp	118
24.1.2.11	MacroEntry	118
24.1.2.12	NestedMacroEntries	118
24.1.2.13	PNComp	118
24.1.2.14	SHComp	118
24.1.2.15	STComp	118
24.1.2.16	TMComp	118
24.1.2.17	UIComp	118
24.1.2.18	UTComp	118
24.1.3	Enumeration Type Documentation	118
24.1.3.1	CompOperators	118
24.1.3.2	ECharSet	118
24.1.3.3	EQueryLevel	119
24.1.3.4	EQueryType	119
24.1.3.5	ERootType	119
24.1.3.6	LodModeType	119
24.1.4	Function Documentation	119
24.1.4.1	backslash	119
24.1.4.2	GetVRFromTag	120
24.1.4.3	operator!=	120
24.1.4.4	operator!=	120
24.1.4.5	operator<<	120
24.1.4.6	operator<<	120
24.1.4.7	operator<<	120
24.1.4.8	operator<<	120
24.1.4.9	operator<<	120

24.1.4.10 operator<<	120
24.1.4.11 operator<<	120
24.1.4.12 operator<<	120
24.1.4.13 operator<<	120
24.1.4.14 operator<<	120
24.1.4.15 operator<<	121
24.1.4.16 operator<<	121
24.1.4.17 operator<<	121
24.1.4.18 operator<<	121
24.1.4.19 operator<<	121
24.1.4.20 operator<<	121
24.1.4.21 operator<<	121
24.1.4.22 operator<<	121
24.1.4.23 operator<<	121
24.1.4.24 operator<<	121
24.1.4.25 operator<<	121
24.1.4.26 operator<<	121
24.1.4.27 operator<<	121
24.1.4.28 operator<<	121
24.1.4.29 operator<<	121
24.1.4.30 operator<<	121
24.1.4.31 operator<<	121
24.1.4.32 operator<<	122
24.1.4.33 operator<<	122
24.1.4.34 operator<<	122
24.1.4.35 operator<<	122
24.1.4.36 operator<<	122
24.1.4.37 operator<<	122
24.1.4.38 operator<<	122
24.1.4.39 operator<<	122
24.1.4.40 operator<<	122
24.1.4.41 operator<<	122
24.1.4.42 operator<<	122
24.1.4.43 operator<<	122
24.1.4.44 operator<<	122
24.1.4.45 operator<<	122
24.1.4.46 operator<<	123

24.1.4.47 operator<<	123
24.1.4.48 operator<<	123
24.1.4.49 operator<<	123
24.1.4.50 operator<<	123
24.1.4.51 operator<<	123
24.1.4.52 operator<<	123
24.1.4.53 operator<<	123
24.1.4.54 operator<<	123
24.1.4.55 operator<<	123
24.1.4.56 operator<<	123
24.1.4.57 operator<<	123
24.1.4.58 operator<<	123
24.1.4.59 operator==	124
24.1.4.60 operator>>	124
24.1.4.61 operator>>	124
24.1.4.62 operator>>	124
24.1.4.63 to_string	124
24.1.4.64 TYPETOENCODING	124
24.1.5 Variable Documentation	124
24.1.5.1 GlobalInstance	124
24.1.5.2 VRBINARY	124
24.2 gdcm::network Namespace Reference	124
24.2.1 Enumeration Type Documentation	128
24.2.1.1 EEventID	128
24.2.1.2 EStateID	129
24.2.2 Function Documentation	129
24.2.2.1 GetStateIndex	129
24.2.3 Variable Documentation	129
24.2.3.1 cMaxEventID	129
24.2.3.2 cMaxStateID	129
24.3 gdcm::SegmentHelper Namespace Reference	130
24.4 gdcm::terminal Namespace Reference	130
24.4.1 Detailed Description	130
24.4.2 Enumeration Type Documentation	131
24.4.2.1 Attribute	131
24.4.2.2 Color	131
24.4.2.3 Mode	131

24.4.3	Function Documentation	131
24.4.3.1	setattribute	131
24.4.3.2	setbgcolor	131
24.4.3.3	setfgcolor	131
24.4.3.4	setmode	131
25	Class Documentation	133
25.1	gdcmm::network::AAabortPDU Class Reference	133
25.1.1	Detailed Description	134
25.1.2	Constructor & Destructor Documentation	134
25.1.2.1	AAabortPDU	134
25.1.3	Member Function Documentation	134
25.1.3.1	IsLastFragment	134
25.1.3.2	Print	134
25.1.3.3	Read	134
25.1.3.4	SetReason	135
25.1.3.5	SetSource	135
25.1.3.6	Size	135
25.1.3.7	Write	135
25.2	gdcmm::network::AAssociateACPDU Class Reference	135
25.2.1	Detailed Description	136
25.2.2	Member Typedef Documentation	137
25.2.2.1	SizeType	137
25.2.3	Constructor & Destructor Documentation	137
25.2.3.1	AAssociateACPDU	137
25.2.4	Member Function Documentation	137
25.2.4.1	AddPresentationContextAC	137
25.2.4.2	GetNumberOfPresentationContextAC	137
25.2.4.3	GetPresentationContextAC	137
25.2.4.4	GetUserInformation	137
25.2.4.5	InitFromRQ	137
25.2.4.6	IsLastFragment	137
25.2.4.7	Print	137
25.2.4.8	Read	137
25.2.4.9	SetCalledAETitle	137
25.2.4.10	SetCallingAETitle	137
25.2.4.11	Size	137

25.2.4.12 Write	137
25.2.5 Friends And Related Function Documentation	137
25.2.5.1 AAssociateRQPDU	138
25.3 gdcm::network::AAssociateRJPDU Class Reference	138
25.3.1 Detailed Description	139
25.3.2 Constructor & Destructor Documentation	139
25.3.2.1 AAssociateRJPDU	139
25.3.3 Member Function Documentation	139
25.3.3.1 IsLastFragment	139
25.3.3.2 Print	139
25.3.3.3 Read	139
25.3.3.4 Size	139
25.3.3.5 Write	139
25.4 gdcm::network::AAssociateRQPDU Class Reference	139
25.4.1 Detailed Description	141
25.4.2 Member Typedef Documentation	141
25.4.2.1 PresentationContextArrayType	141
25.4.2.2 SizeType	141
25.4.3 Constructor & Destructor Documentation	141
25.4.3.1 AAssociateRQPDU	141
25.4.3.2 AAssociateRQPDU	141
25.4.4 Member Function Documentation	142
25.4.4.1 AddPresentationContext	142
25.4.4.2 GetCalledAETitle	142
25.4.4.3 GetCallingAETitle	142
25.4.4.4 GetNumberOfPresentationContext	142
25.4.4.5 GetPresentationContext	142
25.4.4.6 GetPresentationContextByAbstractSyntax	142
25.4.4.7 GetPresentationContextByID	142
25.4.4.8 GetPresentationContexts	142
25.4.4.9 GetReserved43_74	142
25.4.4.10 GetUserInfoation	142
25.4.4.11 IsAETitleValid	142
25.4.4.12 IsLastFragment	142
25.4.4.13 Print	142
25.4.4.14 Read	142
25.4.4.15 SetCalledAETitle	142

25.4.4.16 SetCallingAETitle	142
25.4.4.17 SetUserInfoInformation	143
25.4.4.18 Size	143
25.4.4.19 Write	143
25.4.5 Friends And Related Function Documentation	143
25.4.5.1 AAssociateACPDU	143
25.5 gdcm::AbortEvent Class Reference	143
25.6 gdcm::network::AbstractSyntax Class Reference	144
25.6.1 Detailed Description	144
25.6.2 Constructor & Destructor Documentation	145
25.6.2.1 AbstractSyntax	145
25.6.3 Member Function Documentation	145
25.6.3.1 GetAsDataElement	145
25.6.3.2 GetName	145
25.6.3.3 operator==	145
25.6.3.4 Print	145
25.6.3.5 Read	145
25.6.3.6 SetName	145
25.6.3.7 SetNameFromUID	145
25.6.3.8 Size	145
25.6.3.9 Write	145
25.7 gdcm::AnonymizeEvent Class Reference	145
25.7.1 Detailed Description	147
25.7.2 Member Typedef Documentation	147
25.7.2.1 Self	147
25.7.2.2 Superclass	147
25.7.3 Constructor & Destructor Documentation	147
25.7.3.1 AnonymizeEvent	147
25.7.3.2 ~AnonymizeEvent	147
25.7.3.3 AnonymizeEvent	147
25.7.4 Member Function Documentation	147
25.7.4.1 CheckEvent	147
25.7.4.2 GetEventName	147
25.7.4.3 GetTag	147
25.7.4.4 MakeObject	147
25.7.4.5 SetTag	147
25.8 gdcm::Anonymizer Class Reference	148

25.8.1 Detailed Description	149
25.8.2 Constructor & Destructor Documentation	150
25.8.2.1 Anonymizer	150
25.8.2.2 ~Anonymizer	150
25.8.3 Member Function Documentation	150
25.8.3.1 BALCPPProtect	150
25.8.3.2 BasicApplicationLevelConfidentialityProfile	151
25.8.3.3 CanEmptyTag	151
25.8.3.4 Empty	151
25.8.3.5 GetBasicApplicationLevelConfidentialityProfileAttributes	151
25.8.3.6 GetCryptographicMessageSyntax	151
25.8.3.7 GetFile	151
25.8.3.8 New	151
25.8.3.9 RecurseDataSet	151
25.8.3.10 Remove	151
25.8.3.11 RemoveGroupLength	151
25.8.3.12 RemovePrivateTags	152
25.8.3.13 RemoveRetired	152
25.8.3.14 Replace	152
25.8.3.15 Replace	152
25.8.3.16 SetCryptographicMessageSyntax	152
25.8.3.17 SetFile	152
25.9 gdcm::AnyEvent Class Reference	152
25.10gdcm::network::ApplicationContext Class Reference	154
25.10.1 Detailed Description	154
25.10.2 Constructor & Destructor Documentation	154
25.10.2.1 ApplicationContext	154
25.10.3 Member Function Documentation	154
25.10.3.1 GetName	154
25.10.3.2 Print	154
25.10.3.3 Read	154
25.10.3.4 SetName	154
25.10.3.5 Size	154
25.10.3.6 Write	154
25.11gdcm::ApplicationEntity Class Reference	155
25.11.1 Detailed Description	155
25.11.2 Member Function Documentation	156

25.11.2.1 IsValid	156
25.11.2.2 Print	156
25.11.2.3 SetBlob	156
25.11.2.4 Squeeze	156
25.11.3 Member Data Documentation	156
25.11.3.1 Internal	156
25.11.3.2 MaxLength	156
25.11.3.3 MaxNumberOfComponents	156
25.11.3.4 Padding	156
25.11.3.5 Separator	156
25.12gdcmm::network::AReleaseRPPDU Class Reference	156
25.12.1 Detailed Description	157
25.12.2 Constructor & Destructor Documentation	157
25.12.2.1 AReleaseRPPDU	158
25.12.3 Member Function Documentation	158
25.12.3.1 IsLastFragment	158
25.12.3.2 Print	158
25.12.3.3 Read	158
25.12.3.4 Size	158
25.12.3.5 Write	158
25.13gdcmm::network::AReleaseRQPDU Class Reference	158
25.13.1 Detailed Description	159
25.13.2 Constructor & Destructor Documentation	159
25.13.2.1 AReleaseRQPDU	159
25.13.3 Member Function Documentation	159
25.13.3.1 IsLastFragment	159
25.13.3.2 Print	159
25.13.3.3 Read	159
25.13.3.4 Size	160
25.13.3.5 Write	160
25.14gdcmm::network::ARTIMTimer Class Reference	160
25.14.1 Detailed Description	160
25.14.2 Constructor & Destructor Documentation	160
25.14.2.1 ARTIMTimer	160
25.14.3 Member Function Documentation	160
25.14.3.1 GetElapsedTime	160
25.14.3.2 GetHasExpired	160

25.14.3.3 GetTimeout	161
25.14.3.4 SetTimeout	161
25.14.3.5 Start	161
25.14.3.6 Stop	161
25.15gdcmm::ASN1 Class Reference	161
25.15.1 Detailed Description	161
25.15.2 Constructor & Destructor Documentation	161
25.15.2.1 ASN1	161
25.15.2.2 ~ASN1	161
25.15.3 Member Function Documentation	161
25.15.3.1 ParseDump	161
25.15.3.2 ParseDumpFile	161
25.15.3.3 TestPBKDF2	162
25.16gdcmm::network::AsynchronousOperationsWindowSub Class Reference	162
25.16.1 Detailed Description	162
25.16.2 Constructor & Destructor Documentation	162
25.16.2.1 AsynchronousOperationsWindowSub	162
25.16.3 Member Function Documentation	162
25.16.3.1 Print	162
25.16.3.2 Read	162
25.16.3.3 Size	162
25.16.3.4 Write	162
25.17gdcmm::Attribute< Group, Element, TVR, TVM > Class Template Reference	162
25.17.1 Detailed Description	164
25.17.2 Member Typedef Documentation	164
25.17.2.1 ArrayType	164
25.17.3 Member Enumeration Documentation	164
25.17.3.1 anonymous enum	165
25.17.4 Member Function Documentation	165
25.17.4.1 GDCM_STATIC_ASSERT	165
25.17.4.2 GDCM_STATIC_ASSERT	165
25.17.4.3 GDCM_STATIC_ASSERT	165
25.17.4.4 GetAsDataElement	165
25.17.4.5 GetDictVM	165
25.17.4.6 GetDictVR	165
25.17.4.7 GetNumberOfValues	165
25.17.4.8 GetTag	166

25.17.4.9 GetValue	166
25.17.4.10GetValue	166
25.17.4.11GetValues	166
25.17.4.12GetVM	167
25.17.4.13GetVR	167
25.17.4.14operator!=	167
25.17.4.15operator<	167
25.17.4.16operator==	167
25.17.4.17operator[]	167
25.17.4.18operator[]	167
25.17.4.19Print	168
25.17.4.20Set	168
25.17.4.21SetByteValue	168
25.17.4.22SetByteValueNoSwap	168
25.17.4.23SetFromDataElement	168
25.17.4.24SetFromDataSet	169
25.17.4.25SetValue	169
25.17.4.26SetValues	169
25.17.5 Member Data Documentation	169
25.17.5.1 Internal	169
25.18gdcmm::Attribute< Group, Element, TVR, VM::VM1 > Class Template Reference	170
25.18.1 Member Typedef Documentation	171
25.18.1.1 ArrayType	171
25.18.2 Member Enumeration Documentation	171
25.18.2.1 anonymous enum	171
25.18.3 Member Function Documentation	171
25.18.3.1 GDCM_STATIC_ASSERT	171
25.18.3.2 GDCM_STATIC_ASSERT	171
25.18.3.3 GDCM_STATIC_ASSERT	172
25.18.3.4 GDCM_STATIC_ASSERT	172
25.18.3.5 GetAsDataElement	172
25.18.3.6 GetDictVM	172
25.18.3.7 GetDictVR	172
25.18.3.8 GetNumberOfValues	172
25.18.3.9 GetTag	172
25.18.3.10GetValue	172
25.18.3.11GetValue	172

25.18.3.12	GetValues	172
25.18.3.13	GetVM	172
25.18.3.14	GetVR	173
25.18.3.15	operator!=	173
25.18.3.16	operator<	173
25.18.3.17	operator==	173
25.18.3.18	Print	173
25.18.3.19	Set	173
25.18.3.20	SetByteValue	173
25.18.3.21	SetByteValueNoSwap	173
25.18.3.22	SetFromDataElement	174
25.18.3.23	SetFromDataSet	174
25.18.3.24	SetValue	174
25.18.4	Member Data Documentation	174
25.18.4.1	Internal	174
25.19	gdcmm::Attribute< Group, Element, TVR, VM::VM1_3 > Class Template Reference	174
25.19.1	Member Function Documentation	175
25.19.1.1	GetVM	175
25.20	gdcmm::Attribute< Group, Element, TVR, VM::VM1_8 > Class Template Reference	176
25.20.1	Member Function Documentation	177
25.20.1.1	GetVM	177
25.21	gdcmm::Attribute< Group, Element, TVR, VM::VM1_n > Class Template Reference	177
25.21.1	Member Typedef Documentation	178
25.21.1.1	ArrayType	178
25.21.2	Constructor & Destructor Documentation	178
25.21.2.1	Attribute	178
25.21.2.2	~Attribute	178
25.21.3	Member Function Documentation	178
25.21.3.1	GDCM_STATIC_ASSERT	178
25.21.3.2	GDCM_STATIC_ASSERT	178
25.21.3.3	GDCM_STATIC_ASSERT	179
25.21.3.4	GetAsDataElement	179
25.21.3.5	GetDictVM	179
25.21.3.6	GetDictVR	179
25.21.3.7	GetNumberOfValues	179
25.21.3.8	GetTag	179
25.21.3.9	GetValue	179

25.21.3.10GetValue	179
25.21.3.11GetValues	179
25.21.3.12GetVM	179
25.21.3.13GetVR	180
25.21.3.14operator[]	180
25.21.3.15operator[]	180
25.21.3.16Print	180
25.21.3.17Set	180
25.21.3.18SetByteValue	180
25.21.3.19SetFromDataElement	180
25.21.3.20SetFromDataSet	180
25.21.3.21SetNumberOfValues	181
25.21.3.22SetValue	181
25.21.3.23SetValue	181
25.21.3.24SetValues	181
25.22gdcM::Attribute< Group, Element, TVR, VM::VM2_n > Class Template Reference	181
25.22.1 Member Function Documentation	183
25.22.1.1 GetVM	183
25.23gdcM::Attribute< Group, Element, TVR, VM::VM2_n > Class Template Reference	183
25.23.1 Member Function Documentation	184
25.23.1.1 GetVM	184
25.24gdcM::Attribute< Group, Element, TVR, VM::VM3_3n > Class Template Reference	184
25.24.1 Member Function Documentation	186
25.24.1.1 GetVM	186
25.25gdcM::Attribute< Group, Element, TVR, VM::VM3_n > Class Template Reference	186
25.25.1 Member Function Documentation	187
25.25.1.1 GetVM	187
25.26gdcM::AudioCodec Class Reference	187
25.26.1 Detailed Description	189
25.26.2 Constructor & Destructor Documentation	189
25.26.2.1 AudioCodec	189
25.26.2.2 ~AudioCodec	189
25.26.3 Member Function Documentation	189
25.26.3.1 CanCode	189
25.26.3.2 CanDecode	189
25.26.3.3 Decode	189
25.27gdcM::Base64 Class Reference	189

25.27.1 Detailed Description	190
25.27.2 Constructor & Destructor Documentation	190
25.27.2.1 Base64	190
25.27.2.2 ~Base64	190
25.27.3 Member Function Documentation	190
25.27.3.1 Decode	190
25.27.3.2 Encode	190
25.27.3.3 GetDecodeLength	191
25.27.3.4 GetEncodeLength	191
25.28gdcm::network::BaseCompositeMessage Class Reference	191
25.28.1 Detailed Description	192
25.28.2 Member Function Documentation	192
25.28.2.1 ConstructPDV	192
25.29gdcm::network::BasePDU Class Reference	192
25.29.1 Detailed Description	193
25.29.2 Constructor & Destructor Documentation	194
25.29.2.1 ~BasePDU	194
25.29.3 Member Function Documentation	194
25.29.3.1 IsLastFragment	194
25.29.3.2 Print	194
25.29.3.3 Read	194
25.29.3.4 Size	194
25.29.3.5 Write	194
25.30gdcm::BaseRootQuery Class Reference	194
25.30.1 Detailed Description	196
25.30.2 Constructor & Destructor Documentation	196
25.30.2.1 BaseRootQuery	196
25.30.2.2 ~BaseRootQuery	196
25.30.3 Member Function Documentation	196
25.30.3.1 AddQueryDataSet	197
25.30.3.2 Construct	197
25.30.3.3 GetAbstractSyntaxUID	197
25.30.3.4 GetQueryDataSet	197
25.30.3.5 GetQueryDataSet	197
25.30.3.6 GetQueryLevelFromQueryRoot	197
25.30.3.7 GetQueryLevelFromString	197
25.30.3.8 GetQueryLevelString	197

25.30.3.9 GetTagListByLevel	197
25.30.3.10 InitializeDataSet	197
25.30.3.11 Print	197
25.30.3.12 SetSearchParameter	197
25.30.3.13 SetSearchParameter	197
25.30.3.14 SetSearchParameter	197
25.30.3.15 ValidateQuery	198
25.30.3.16 WriteHelpFile	198
25.30.3.17 WriteQuery	198
25.30.4 Friends And Related Function Documentation	198
25.30.4.1 QueryFactory	198
25.30.5 Member Data Documentation	198
25.30.5.1 mDataSet	198
25.30.5.2 mHelpDescription	198
25.30.5.3 mImage	198
25.30.5.4 mPatient	198
25.30.5.5 mRootType	198
25.30.5.6 mSeries	198
25.30.5.7 mStudy	198
25.31 gdcmm::SegmentHelper::BasicCodedEntry Struct Reference	198
25.31.1 Detailed Description	200
25.31.2 Constructor & Destructor Documentation	200
25.31.2.1 BasicCodedEntry	200
25.31.2.2 BasicCodedEntry	200
25.31.2.3 BasicCodedEntry	200
25.31.3 Member Function Documentation	200
25.31.3.1 IsEmpty	200
25.31.4 Member Data Documentation	200
25.31.4.1 CM	200
25.31.4.2 CSD	200
25.31.4.3 CSV	200
25.31.4.4 CV	201
25.32 gdcmm::BasicOffsetTable Class Reference	201
25.32.1 Detailed Description	202
25.32.2 Constructor & Destructor Documentation	202
25.32.2.1 BasicOffsetTable	202
25.32.3 Member Function Documentation	202

25.32.3.1 Read	203
25.32.4 Friends And Related Function Documentation	203
25.32.4.1 operator<<	203
25.33gdcm::Bitmap Class Reference	203
25.33.1 Detailed Description	206
25.33.2 Member Typedef Documentation	206
25.33.2.1 LUTPtr	206
25.33.3 Constructor & Destructor Documentation	206
25.33.3.1 Bitmap	206
25.33.3.2 ~Bitmap	206
25.33.4 Member Function Documentation	206
25.33.4.1 AreOverlaysInPixelData	206
25.33.4.2 Clear	206
25.33.4.3 ComputeLossyFlag	206
25.33.4.4 GetBuffer	206
25.33.4.5 GetBuffer2	206
25.33.4.6 GetBufferLength	206
25.33.4.7 GetColumns	207
25.33.4.8 GetDataElement	207
25.33.4.9 GetDataElement	207
25.33.4.10GetDimension	207
25.33.4.11GetDimensions	207
25.33.4.12GetLUT	207
25.33.4.13GetLUT	207
25.33.4.14GetNeedByteSwap	207
25.33.4.15GetNumberOfDimensions	207
25.33.4.16GetPhotometricInterpretation	207
25.33.4.17GetPixelFormat	208
25.33.4.18GetPixelFormat	208
25.33.4.19GetPlanarConfiguration	208
25.33.4.20GetRows	208
25.33.4.21GetTransferSyntax	208
25.33.4.22IsEmpty	208
25.33.4.23IsLossy	208
25.33.4.24IsTransferSyntaxCompatible	208
25.33.4.25Print	208
25.33.4.26SetColumns	208

25.33.4.27SetDataElement	208
25.33.4.28SetDimension	209
25.33.4.29SetDimensions	209
25.33.4.30SetLossyFlag	209
25.33.4.31SetLUT	209
25.33.4.32SetNeedByteSwap	209
25.33.4.33SetNumberOfDimensions	209
25.33.4.34SetPhotometricInterpretation	209
25.33.4.35SetPixelFormat	209
25.33.4.36SetPlanarConfiguration	209
25.33.4.37SetRows	210
25.33.4.38SetTransferSyntax	210
25.33.4.39TryJPEG2000Codec	210
25.33.4.40TryJPEG2000Codec2	210
25.33.4.41TryJPEGCodec	210
25.33.4.42TryJPEGCodec2	210
25.33.4.43TryJPEGLSCodec	210
25.33.4.44TryKAKADUCodec	210
25.33.4.45TryPVRGCodec	210
25.33.4.46TryRAWCodec	210
25.33.4.47TryRLECodec	210
25.33.5 Friends And Related Function Documentation	210
25.33.5.1 ImageChangeTransferSyntax	210
25.33.5.2 PixmapReader	210
25.33.6 Member Data Documentation	210
25.33.6.1 Dimensions	210
25.33.6.2 LossyFlag	210
25.33.6.3 LUT	210
25.33.6.4 NeedByteSwap	210
25.33.6.5 NumberOfDimensions	210
25.33.6.6 PF	210
25.33.6.7 PI	210
25.33.6.8 PixelData	210
25.33.6.9 PlanarConfiguration	211
25.33.6.10TS	211
25.34gdcm::BitmapToBitmapFilter Class Reference	211
25.34.1 Detailed Description	212

25.34.2 Constructor & Destructor Documentation	212
25.34.2.1 BitmapToBitmapFilter	212
25.34.2.2 ~BitmapToBitmapFilter	212
25.34.3 Member Function Documentation	212
25.34.3.1 GetOutput	212
25.34.3.2 GetOutputAsBitmap	212
25.34.3.3 SetInput	212
25.34.4 Member Data Documentation	212
25.34.4.1 Input	212
25.34.4.2 Output	212
25.35gdcmm::BoxRegion Class Reference	213
25.35.1 Detailed Description	214
25.35.2 Constructor & Destructor Documentation	214
25.35.2.1 BoxRegion	214
25.35.2.2 ~BoxRegion	214
25.35.2.3 BoxRegion	214
25.35.3 Member Function Documentation	214
25.35.3.1 Area	214
25.35.3.2 BoundingBox	215
25.35.3.3 Clone	215
25.35.3.4 ComputeBoundingBox	215
25.35.3.5 Empty	215
25.35.3.6 GetXMax	215
25.35.3.7 GetXMin	215
25.35.3.8 GetYMax	215
25.35.3.9 GetYMin	215
25.35.3.10GetZMax	215
25.35.3.11GetZMin	215
25.35.3.12IsValid	215
25.35.3.13operator=	215
25.35.3.14Print	215
25.35.3.15SetDomain	216
25.36gdcmm::ByteBuffer Class Reference	216
25.36.1 Detailed Description	216
25.36.2 Constructor & Destructor Documentation	216
25.36.2.1 ByteBuffer	216
25.36.3 Member Function Documentation	216

25.36.3.1	Get	216
25.36.3.2	GetStart	216
25.36.3.3	ShiftEnd	216
25.36.3.4	UpdatePosition	216
25.37	gdcmm::ByteSwap< T > Class Template Reference	217
25.37.1	Detailed Description	217
25.37.2	Member Function Documentation	217
25.37.2.1	Swap	217
25.37.2.2	SwapFromSwapCodeIntoSystem	217
25.37.2.3	SwapRange	217
25.37.2.4	SwapRangeFromSwapCodeIntoSystem	217
25.37.2.5	SystemIsBigEndian	217
25.37.2.6	SystemIsLittleEndian	218
25.38	gdcmm::ByteSwapFilter Class Reference	218
25.38.1	Detailed Description	218
25.38.2	Constructor & Destructor Documentation	218
25.38.2.1	ByteSwapFilter	218
25.38.2.2	~ByteSwapFilter	218
25.38.3	Member Function Documentation	218
25.38.3.1	ByteSwap	218
25.38.3.2	SetByteSwapTag	218
25.39	gdcmm::ByteValue Class Reference	218
25.39.1	Detailed Description	220
25.39.2	Constructor & Destructor Documentation	220
25.39.2.1	ByteValue	220
25.39.2.2	ByteValue	221
25.39.2.3	~ByteValue	221
25.39.3	Member Function Documentation	221
25.39.3.1	Clear	221
25.39.3.2	Fill	221
25.39.3.3	GetBuffer	221
25.39.3.4	GetLength	221
25.39.3.5	GetPointer	221
25.39.3.6	IsEmpty	222
25.39.3.7	IsPrintable	222
25.39.3.8	operator const std::vector< char > &	222
25.39.3.9	operator=	222

25.39.3.10operator==	222
25.39.3.11operator==	222
25.39.3.12Print	222
25.39.3.13PrintASCII	222
25.39.3.14PrintGroupLength	222
25.39.3.15PrintHex	222
25.39.3.16Read	222
25.39.3.17Read	222
25.39.3.18SetLength	222
25.39.3.19Write	222
25.39.3.20Write	223
25.39.3.21WriteBuffer	223
25.40gdcm::network::CEchoRQ Class Reference	223
25.40.1 Detailed Description	224
25.40.2 Member Function Documentation	224
25.40.2.1 ConstructPDV	224
25.40.3 Member Data Documentation	224
25.40.3.1 AffectedSOPClassUID	224
25.40.3.2 MessageID	224
25.41gdcm::network::CEchoRSP Class Reference	224
25.41.1 Detailed Description	225
25.41.2 Member Function Documentation	225
25.41.2.1 ConstructPDVByDataSet	225
25.42gdcm::network::CFind Class Reference	226
25.42.1 Detailed Description	226
25.43gdcm::network::CFindCancelRQ Class Reference	226
25.43.1 Detailed Description	227
25.43.2 Member Function Documentation	227
25.43.2.1 ConstructPDVByDataSet	227
25.44gdcm::network::CFindRQ Class Reference	227
25.44.1 Detailed Description	228
25.44.2 Member Function Documentation	228
25.44.2.1 ConstructPDV	229
25.45gdcm::network::CFindRSP Class Reference	229
25.45.1 Detailed Description	230
25.45.2 Member Function Documentation	230
25.45.2.1 ConstructPDVByDataSet	230

25.46gdcmm::network::CMoveCancelRq Class Reference	230
25.46.1 Member Function Documentation	231
25.46.1.1 ConstructPDVByDataSet	231
25.47gdcmm::network::CMoveRQ Class Reference	231
25.47.1 Detailed Description	232
25.47.2 Member Function Documentation	232
25.47.2.1 ConstructPDV	233
25.48gdcmm::network::CMoveRSP Class Reference	233
25.48.1 Detailed Description	234
25.48.2 Member Function Documentation	234
25.48.2.1 ConstructPDVByDataSet	234
25.49gdcmm::Codec Class Reference	234
25.49.1 Detailed Description	235
25.50gdcmm::Coder Class Reference	235
25.50.1 Detailed Description	236
25.50.2 Constructor & Destructor Documentation	236
25.50.2.1 ~Coder	236
25.50.3 Member Function Documentation	236
25.50.3.1 CanCode	236
25.50.3.2 Code	236
25.50.3.3 InternalCode	236
25.51gdcmm::CodeString Class Reference	237
25.51.1 Detailed Description	238
25.51.2 Member Typedef Documentation	238
25.51.2.1 const_iterator	238
25.51.2.2 const_reference	238
25.51.2.3 const_reverse_iterator	238
25.51.2.4 difference_type	238
25.51.2.5 iterator	238
25.51.2.6 pointer	238
25.51.2.7 reference	238
25.51.2.8 reverse_iterator	238
25.51.2.9 size_type	238
25.51.2.10value_type	238
25.51.3 Constructor & Destructor Documentation	238
25.51.3.1 CodeString	238
25.51.3.2 CodeString	238

25.51.3.3 CodeString	238
25.51.3.4 CodeString	238
25.51.4 Member Function Documentation	239
25.51.4.1 GetAsString	239
25.51.4.2 IsValid	239
25.51.4.3 Size	239
25.51.4.4 TrimInternal	239
25.51.5 Friends And Related Function Documentation	239
25.51.5.1 operator!=	239
25.51.5.2 operator<<	239
25.51.5.3 operator==	239
25.52gdcM::Command Class Reference	239
25.52.1 Detailed Description	241
25.52.2 Constructor & Destructor Documentation	241
25.52.2.1 Command	241
25.52.2.2 ~Command	241
25.52.3 Member Function Documentation	241
25.52.3.1 Execute	241
25.52.3.2 Execute	241
25.53gdcM::CommandDataSet Class Reference	241
25.53.1 Detailed Description	243
25.53.2 Constructor & Destructor Documentation	243
25.53.2.1 CommandDataSet	243
25.53.2.2 ~CommandDataSet	243
25.53.3 Member Function Documentation	243
25.53.3.1 Insert	243
25.53.3.2 Read	243
25.53.3.3 Replace	243
25.53.3.4 Write	243
25.53.4 Friends And Related Function Documentation	243
25.53.4.1 operator<<	243
25.54gdcM::network::CompositeMessageFactory Class Reference	243
25.54.1 Detailed Description	244
25.54.2 Member Function Documentation	244
25.54.2.1 ConstructCEchoRQ	244
25.54.2.2 ConstructCFindRQ	244
25.54.2.3 ConstructCMoveRQ	244

25.54.2.4 ConstructCStoreRQ	244
25.54.2.5 ConstructCStoreRSP	244
25.55gdcmm::CompositeNetworkFunctions Class Reference	244
25.55.1 Detailed Description	245
25.55.2 Member Typedef Documentation	245
25.55.2.1 KeyValuePairArrayType	245
25.55.2.2 KeyValuePairType	246
25.55.3 Member Function Documentation	246
25.55.3.1 CEcho	246
25.55.3.2 CFind	246
25.55.3.3 CMove	246
25.55.3.4 ConstructQuery	247
25.55.3.5 ConstructQuery	247
25.55.3.6 CStore	247
25.56gdcmm::ConstCharWrapper Class Reference	247
25.56.1 Detailed Description	248
25.56.2 Constructor & Destructor Documentation	248
25.56.2.1 ConstCharWrapper	248
25.56.3 Member Function Documentation	248
25.56.3.1 operator const char *	248
25.57gdcmm::CP246ExplicitDataElement Class Reference	248
25.57.1 Detailed Description	249
25.57.2 Member Function Documentation	249
25.57.2.1 GetLength	249
25.57.2.2 Read	250
25.57.2.3 ReadPreValue	250
25.57.2.4 ReadValue	250
25.57.2.5 ReadWithLength	250
25.58gdcmm::CryptographicMessageSyntax Class Reference	250
25.58.1 Detailed Description	250
25.58.2 Member Enumeration Documentation	251
25.58.2.1 CipherTypes	251
25.58.3 Constructor & Destructor Documentation	251
25.58.3.1 CryptographicMessageSyntax	251
25.58.3.2 ~CryptographicMessageSyntax	251
25.58.4 Member Function Documentation	251
25.58.4.1 Decrypt	251

25.58.4.2 Encrypt	251
25.58.4.3 GetCipherType	251
25.58.4.4 ParseCertificateFile	251
25.58.4.5 ParseKeyFile	251
25.58.4.6 SetCipherType	251
25.59gdcmm::CSAElement Class Reference	251
25.59.1 Detailed Description	253
25.59.2 Member Typedef Documentation	253
25.59.2.1 DataPtr	253
25.59.3 Constructor & Destructor Documentation	253
25.59.3.1 CSAElement	253
25.59.3.2 CSAElement	253
25.59.4 Member Function Documentation	253
25.59.4.1 GetByteValue	253
25.59.4.2 GetKey	254
25.59.4.3 GetName	254
25.59.4.4 GetNoOfItems	254
25.59.4.5 GetSyngoDT	254
25.59.4.6 GetValue	254
25.59.4.7 GetValue	254
25.59.4.8 GetVM	254
25.59.4.9 GetVR	254
25.59.4.10IsEmpty	254
25.59.4.11operator<	255
25.59.4.12operator=	255
25.59.4.13operator==	255
25.59.4.14SetByteValue	255
25.59.4.15SetKey	255
25.59.4.16SetName	255
25.59.4.17SetNoOfItems	255
25.59.4.18SetSyngoDT	255
25.59.4.19SetValue	255
25.59.4.20SetVM	255
25.59.4.21SetVR	255
25.59.5 Friends And Related Function Documentation	255
25.59.5.1 operator<<	255
25.59.6 Member Data Documentation	255

25.59.6.1 DataField	255
25.59.6.2 KeyField	255
25.59.6.3 NameField	256
25.59.6.4 NoOfItemsField	256
25.59.6.5 SyngoDTField	256
25.59.6.6 ValueMultiplicityField	256
25.59.6.7 VRField	256
25.60gdcm::CSAHeader Class Reference	256
25.60.1 Detailed Description	257
25.60.2 Member Enumeration Documentation	258
25.60.2.1 CSAHeaderType	258
25.60.3 Constructor & Destructor Documentation	258
25.60.3.1 CSAHeader	258
25.60.3.2 ~CSAHeader	258
25.60.4 Member Function Documentation	258
25.60.4.1 FindCSAElementByName	258
25.60.4.2 GetCSADataInfo	258
25.60.4.3 GetCSAEEnd	259
25.60.4.4 GetCSAElementByName	259
25.60.4.5 GetCSAImageHeaderInfoTag	259
25.60.4.6 GetCSASeriesHeaderInfoTag	259
25.60.4.7 GetDataSet	259
25.60.4.8 GetFormat	259
25.60.4.9 GetInterfile	259
25.60.4.10LoadFromDataElement	259
25.60.4.11Print	260
25.60.4.12Read	260
25.60.4.13Write	260
25.60.5 Friends And Related Function Documentation	260
25.60.5.1 operator<<	260
25.61gdcm::CSAHeaderDict Class Reference	260
25.61.1 Detailed Description	261
25.61.2 Member Typedef Documentation	261
25.61.2.1 ConstIterator	261
25.61.2.2 Iterator	261
25.61.2.3 MapCSAHeaderDictEntry	261
25.61.3 Constructor & Destructor Documentation	261

25.61.3.1 CSAHeaderDict	261
25.61.4 Member Function Documentation	261
25.61.4.1 AddCSAHeaderDictEntry	261
25.61.4.2 Begin	261
25.61.4.3 End	261
25.61.4.4 GetCSAHeaderDictEntry	261
25.61.4.5 IsEmpty	261
25.61.4.6 LoadDefault	261
25.61.5 Friends And Related Function Documentation	261
25.61.5.1 Dicts	261
25.61.5.2 operator<<	261
25.62gdcmm::CSAHeaderDictEntry Class Reference	262
25.62.1 Detailed Description	262
25.62.2 Constructor & Destructor Documentation	263
25.62.2.1 CSAHeaderDictEntry	263
25.62.3 Member Function Documentation	263
25.62.3.1 GetDescription	263
25.62.3.2 GetName	263
25.62.3.3 GetVM	263
25.62.3.4 GetVR	263
25.62.3.5 operator<	263
25.62.3.6 SetDescription	263
25.62.3.7 SetName	263
25.62.3.8 SetVM	263
25.62.3.9 SetVR	263
25.62.4 Friends And Related Function Documentation	263
25.62.4.1 operator<<	263
25.63gdcmm::CSAHeaderDictException Class Reference	263
25.64gdcmm::network::CStoreRQ Class Reference	264
25.64.1 Detailed Description	265
25.64.2 Member Function Documentation	265
25.64.2.1 ConstructPDV	265
25.65gdcmm::network::CStoreRSP Class Reference	266
25.65.1 Detailed Description	267
25.65.2 Member Function Documentation	267
25.65.2.1 ConstructPDV	267
25.66gdcmm::Curve Class Reference	267

25.66.1 Detailed Description	269
25.66.2 Constructor & Destructor Documentation	269
25.66.2.1 Curve	269
25.66.2.2 ~Curve	269
25.66.2.3 Curve	269
25.66.3 Member Function Documentation	269
25.66.3.1 Decode	269
25.66.3.2 GetAsPoints	269
25.66.3.3 GetCurveDataDescriptor	269
25.66.3.4 GetDataValueRepresentation	269
25.66.3.5 GetDimensions	269
25.66.3.6 GetGroup	269
25.66.3.7 GetNumberOfCurves	269
25.66.3.8 GetNumberOfPoints	269
25.66.3.9 GetTypeOfData	269
25.66.3.10GetTypeOfDataDescription	269
25.66.3.11IsEmpty	269
25.66.3.12Print	269
25.66.3.13SetCoordinateStartValue	270
25.66.3.14SetCoordinateStepValue	270
25.66.3.15SetCurve	270
25.66.3.16SetCurveDataDescriptor	270
25.66.3.17SetCurveDescription	270
25.66.3.18SetDataValueRepresentation	270
25.66.3.19SetDimensions	270
25.66.3.20SetGroup	270
25.66.3.21SetNumberOfPoints	270
25.66.3.22SetTypeOfData	270
25.66.3.23Update	270
25.67gdcmm::DataElement Class Reference	270
25.67.1 Detailed Description	273
25.67.2 Member Typedef Documentation	273
25.67.2.1 ValuePtr	273
25.67.3 Constructor & Destructor Documentation	273
25.67.3.1 DataElement	273
25.67.3.2 DataElement	274
25.67.4 Member Function Documentation	274

25.67.4.1 Clear	274
25.67.4.2 Empty	274
25.67.4.3 GetByteValue	274
25.67.4.4 GetLength	274
25.67.4.5 GetSequenceOfFragments	274
25.67.4.6 GetSequenceOfItems	274
25.67.4.7 GetSequenceOfItems	275
25.67.4.8 GetTag	275
25.67.4.9 GetTag	275
25.67.4.10 GetValue	275
25.67.4.11 GetValue	275
25.67.4.12 GetValueAsSQ	275
25.67.4.13 GetVL	276
25.67.4.14 GetVL	276
25.67.4.15 GetVR	276
25.67.4.16 IsEmpty	276
25.67.4.17 IsUndefinedLength	276
25.67.4.18 operator<	276
25.67.4.19 operator=	277
25.67.4.20 operator==	277
25.67.4.21 Read	277
25.67.4.22 ReadOrSkip	277
25.67.4.23 ReadPreValue	277
25.67.4.24 ReadValue	277
25.67.4.25 ReadWithLength	277
25.67.4.26 SetByteValue	277
25.67.4.27 SetTag	277
25.67.4.28 SetValue	278
25.67.4.29 SetVL	278
25.67.4.30 SetVLToUndefined	278
25.67.4.31 SetVR	278
25.67.4.32 Write	279
25.67.5 Friends And Related Function Documentation	279
25.67.5.1 operator<<	279
25.67.6 Member Data Documentation	279
25.67.6.1 TagField	279
25.67.6.2 ValueField	279

25.67.6.3 ValueLengthField	279
25.67.6.4 VRField	279
25.68gdcmm::DataElementException Class Reference	279
25.69gdcmm::DataEvent Class Reference	280
25.69.1 Detailed Description	281
25.69.2 Member Typedef Documentation	281
25.69.2.1 Self	281
25.69.2.2 Superclass	281
25.69.3 Constructor & Destructor Documentation	282
25.69.3.1 DataEvent	282
25.69.3.2 ~DataEvent	282
25.69.3.3 DataEvent	282
25.69.4 Member Function Documentation	282
25.69.4.1 CheckEvent	282
25.69.4.2 GetData	282
25.69.4.3 GetDataLength	282
25.69.4.4 GetEventName	282
25.69.4.5 MakeObject	282
25.69.4.6 SetData	282
25.70gdcmm::DataSet Class Reference	282
25.70.1 Detailed Description	284
25.70.2 Member Typedef Documentation	285
25.70.2.1 ConstIterator	285
25.70.2.2 DataElementSet	285
25.70.2.3 Iterator	285
25.70.2.4 SizeType	285
25.70.3 Member Function Documentation	285
25.70.3.1 Begin	285
25.70.3.2 Begin	285
25.70.3.3 Clear	285
25.70.3.4 ComputeDataElement	285
25.70.3.5 ComputeGroupLength	286
25.70.3.6 End	286
25.70.3.7 End	286
25.70.3.8 FindDataElement	286
25.70.3.9 FindDataElement	286
25.70.3.10FindNextDataElement	286

25.70.3.11GetDataElement	286
25.70.3.12GetDataElement	287
25.70.3.13GetDEEnd	287
25.70.3.14GetDES	287
25.70.3.15GetDES	287
25.70.3.16GetLength	287
25.70.3.17GetMediaStorage	287
25.70.3.18GetPrivateCreator	287
25.70.3.19Insert	287
25.70.3.20InsertDataElement	287
25.70.3.21IsEmpty	288
25.70.3.22operator()	288
25.70.3.23operator=	288
25.70.3.24operator[]	288
25.70.3.25Print	288
25.70.3.26Read	288
25.70.3.27ReadNested	288
25.70.3.28ReadSelectedTags	288
25.70.3.29ReadSelectedTagsWithLength	288
25.70.3.30ReadUpToTag	288
25.70.3.31ReadUpToTagWithLength	288
25.70.3.32ReadWithLength	288
25.70.3.33Remove	288
25.70.3.34Replace	288
25.70.3.35ReplaceEmpty	289
25.70.3.36Size	289
25.70.3.37Write	289
25.70.4 Friends And Related Function Documentation	289
25.70.4.1 CSAHeader	289
25.70.4.2 operator<<	289
25.71gdcm::DataSetEvent Class Reference	289
25.71.1 Detailed Description	290
25.71.2 Member Typedef Documentation	290
25.71.2.1 Self	290
25.71.2.2 Superclass	290
25.71.3 Constructor & Destructor Documentation	291
25.71.3.1 DataSetEvent	291

25.71.3.2 ~DataSetEvent	291
25.71.3.3 DataSetEvent	291
25.71.4 Member Function Documentation	291
25.71.4.1 CheckEvent	291
25.71.4.2 GetDataSet	291
25.71.4.3 GetEventName	291
25.71.4.4 MakeObject	291
25.72gdcmm::DataSetHelper Class Reference	291
25.72.1 Detailed Description	291
25.72.2 Member Function Documentation	291
25.72.2.1 ComputeVR	291
25.73gdcmm::Decoder Class Reference	292
25.73.1 Detailed Description	292
25.73.2 Constructor & Destructor Documentation	292
25.73.2.1 ~Decoder	292
25.73.3 Member Function Documentation	293
25.73.3.1 CanDecode	293
25.73.3.2 Decode	293
25.73.3.3 DecodeByStreams	293
25.74gdcmm::DefinedTerms Class Reference	293
25.74.1 Detailed Description	293
25.74.2 Constructor & Destructor Documentation	294
25.74.2.1 DefinedTerms	294
25.75gdcmm::Defs Class Reference	294
25.75.1 Detailed Description	295
25.75.2 Constructor & Destructor Documentation	295
25.75.2.1 Defs	295
25.75.2.2 ~Defs	295
25.75.3 Member Function Documentation	295
25.75.3.1 GetIODFromFile	295
25.75.3.2 GetIODNameFromMediaStorage	295
25.75.3.3 GetIODs	295
25.75.3.4 GetIODs	295
25.75.3.5 GetMacros	295
25.75.3.6 GetMacros	295
25.75.3.7 GetModules	295
25.75.3.8 GetModules	295

25.75.3.9 GetTypeFromTag	295
25.75.3.10IsEmpty	295
25.75.3.11LoadDefaults	295
25.75.3.12LoadFromFile	295
25.75.3.13Verify	296
25.75.3.14Verify	296
25.75.4 Friends And Related Function Documentation	296
25.75.4.1 Global	296
25.76gdcm::DeltaEncodingCodec Class Reference	296
25.76.1 Detailed Description	297
25.76.2 Constructor & Destructor Documentation	297
25.76.2.1 DeltaEncodingCodec	297
25.76.2.2 ~DeltaEncodingCodec	297
25.76.3 Member Function Documentation	297
25.76.3.1 CanDecode	297
25.76.3.2 Decode	297
25.76.3.3 Decode	298
25.77gdcm::DICOMDIR Class Reference	298
25.77.1 Detailed Description	298
25.77.2 Constructor & Destructor Documentation	298
25.77.2.1 DICOMDIR	298
25.77.2.2 DICOMDIR	298
25.78gdcm::DICOMDIRGenerator Class Reference	298
25.78.1 Detailed Description	299
25.78.2 Member Typedef Documentation	300
25.78.2.1 FilenamesType	300
25.78.2.2 FilenameType	300
25.78.3 Constructor & Destructor Documentation	300
25.78.3.1 DICOMDIRGenerator	300
25.78.3.2 ~DICOMDIRGenerator	300
25.78.4 Member Function Documentation	300
25.78.4.1 AddImageDirectoryRecord	300
25.78.4.2 AddPatientDirectoryRecord	300
25.78.4.3 AddSeriesDirectoryRecord	300
25.78.4.4 AddStudyDirectoryRecord	300
25.78.4.5 Generate	300
25.78.4.6 GetFile	300

25.78.4.7 GetScanner	300
25.78.4.8 SetDescriptor	300
25.78.4.9 SetFile	300
25.78.4.10SetFilenames	300
25.78.4.11SetRootDirectory	300
25.79gdcmm::Dict Class Reference	301
25.79.1 Detailed Description	301
25.79.2 Member Typedef Documentation	302
25.79.2.1 ConstIterator	302
25.79.2.2 Iterator	302
25.79.2.3 MapDictEntry	302
25.79.3 Constructor & Destructor Documentation	302
25.79.3.1 Dict	302
25.79.4 Member Function Documentation	302
25.79.4.1 AddDictEntry	302
25.79.4.2 Begin	302
25.79.4.3 End	302
25.79.4.4 GetDictEntry	302
25.79.4.5 GetDictEntryByKeyword	302
25.79.4.6 GetDictEntryByName	302
25.79.4.7 GetKeywordFromTag	303
25.79.4.8 IsEmpty	303
25.79.4.9 LoadDefault	303
25.79.5 Friends And Related Function Documentation	303
25.79.5.1 Dicts	303
25.79.5.2 operator<<	303
25.80gdcmm::DictConverter Class Reference	303
25.80.1 Detailed Description	304
25.80.2 Member Enumeration Documentation	304
25.80.2.1 OutputTypes	304
25.80.3 Constructor & Destructor Documentation	304
25.80.3.1 DictConverter	304
25.80.3.2 ~DictConverter	304
25.80.4 Member Function Documentation	304
25.80.4.1 AddGroupLength	304
25.80.4.2 Convert	304
25.80.4.3 ConvertToCXX	304

25.80.4.4 ConvertToXML	305
25.80.4.5 GetDictName	305
25.80.4.6 GetInputFilename	305
25.80.4.7 GetOutputFilename	305
25.80.4.8 GetOutputType	305
25.80.4.9 Readuint16	305
25.80.4.10ReadVM	305
25.80.4.11ReadVR	305
25.80.4.12SetDictName	305
25.80.4.13SetInputFileName	305
25.80.4.14SetOutputFileName	305
25.80.4.15SetOutputType	305
25.80.4.16WriteFooter	305
25.80.4.17WriteHeader	305
25.81gdcmm::DictEntry Class Reference	305
25.81.1 Detailed Description	306
25.81.2 Constructor & Destructor Documentation	306
25.81.2.1 DictEntry	306
25.81.3 Member Function Documentation	306
25.81.3.1 GetKeyword	306
25.81.3.2 GetName	306
25.81.3.3 GetRetired	307
25.81.3.4 GetVM	307
25.81.3.5 GetVR	307
25.81.3.6 IsUnique	307
25.81.3.7 SetElementXX	307
25.81.3.8 SetGroupXX	307
25.81.3.9 SetKeyword	307
25.81.3.10SetName	307
25.81.3.11SetRetired	307
25.81.3.12SetVM	307
25.81.3.13SetVR	307
25.81.4 Friends And Related Function Documentation	308
25.81.4.1 operator<<	308
25.82gdcmm::DictPrinter Class Reference	308
25.82.1 Detailed Description	309
25.82.2 Constructor & Destructor Documentation	309

25.82.2.1 DictPrinter	309
25.82.2.2 ~DictPrinter	310
25.82.3 Member Function Documentation	310
25.82.3.1 Print	310
25.82.3.2 PrintDataElement2	310
25.82.3.3 PrintDataSet2	310
25.83gdcmm::Dicts Class Reference	310
25.83.1 Detailed Description	311
25.83.2 Member Enumeration Documentation	311
25.83.2.1 ConstructorType	311
25.83.3 Constructor & Destructor Documentation	311
25.83.3.1 Dicts	311
25.83.3.2 ~Dicts	311
25.83.4 Member Function Documentation	311
25.83.4.1 GetConstructorString	311
25.83.4.2 GetCSAHeaderDict	311
25.83.4.3 GetDictEntry	311
25.83.4.4 GetDictEntry	312
25.83.4.5 GetPrivateDict	312
25.83.4.6 GetPrivateDict	312
25.83.4.7 GetPublicDict	312
25.83.4.8 IsEmpty	312
25.83.4.9 LoadDefaults	312
25.83.5 Friends And Related Function Documentation	312
25.83.5.1 Global	312
25.83.5.2 operator<<	312
25.84gdcmm::network::DIMSE Class Reference	312
25.84.1 Detailed Description	313
25.84.2 Member Enumeration Documentation	313
25.84.2.1 CommandTypes	313
25.85gdcmm::DirectionCosines Class Reference	314
25.85.1 Detailed Description	315
25.85.2 Constructor & Destructor Documentation	315
25.85.2.1 DirectionCosines	315
25.85.2.2 DirectionCosines	315
25.85.2.3 ~DirectionCosines	315
25.85.3 Member Function Documentation	315

25.85.3.1 ComputeDistAlongNormal	315
25.85.3.2 Cross	315
25.85.3.3 CrossDot	315
25.85.3.4 Dot	315
25.85.3.5 IsValid	315
25.85.3.6 Normalize	315
25.85.3.7 operator const double *	315
25.85.3.8 Print	316
25.85.3.9 SetFromString	316
25.86gdcmm::Directory Class Reference	316
25.86.1 Detailed Description	317
25.86.2 Member Typedef Documentation	317
25.86.2.1 FilenamesType	317
25.86.2.2 FilenameType	317
25.86.3 Constructor & Destructor Documentation	317
25.86.3.1 Directory	317
25.86.3.2 ~Directory	317
25.86.4 Member Function Documentation	317
25.86.4.1 Explore	317
25.86.4.2 GetDirectories	317
25.86.4.3 GetFilenames	318
25.86.4.4 GetToplevel	318
25.86.4.5 Load	318
25.86.4.6 Print	318
25.86.5 Friends And Related Function Documentation	318
25.86.5.1 operator<<	318
25.87gdcmm::DirectoryHelper Class Reference	318
25.87.1 Detailed Description	319
25.87.2 Member Function Documentation	319
25.87.2.1 GetCTImageSeriesUIDs	319
25.87.2.2 GetFilenamesFromSeriesUIDs	319
25.87.2.3 GetFrameOfReference	319
25.87.2.4 GetMRImageSeriesUIDs	319
25.87.2.5 GetRTStructSeriesUIDs	320
25.87.2.6 GetSeriesUIDsBySOPClassUID	320
25.87.2.7 GetSOPClassUID	320
25.87.2.8 GetStringValueFromTag	320

25.87.2.9 LoadImageFromFiles	320
25.87.2.10 RetrieveSOPInstanceUIDFromIndex	320
25.87.2.11 RetrieveSOPInstanceUIDFromZPosition	320
25.88gdcmm::DummyValueGenerator Class Reference	320
25.88.1 Detailed Description	320
25.88.2 Member Function Documentation	320
25.88.2.1 Generate	321
25.89gdcmm::Dumper Class Reference	321
25.89.1 Detailed Description	322
25.89.2 Constructor & Destructor Documentation	322
25.89.2.1 Dumper	322
25.89.2.2 ~Dumper	322
25.90gdcmm::Element< TVR, TVM > Class Template Reference	323
25.90.1 Detailed Description	324
25.90.2 Member Typedef Documentation	325
25.90.2.1 Type	325
25.90.3 Member Function Documentation	325
25.90.3.1 GetAsDataElement	325
25.90.3.2 GetLength	325
25.90.3.3 GetValue	325
25.90.3.4 GetValue	325
25.90.3.5 GetValues	325
25.90.3.6 GetVM	325
25.90.3.7 GetVR	325
25.90.3.8 operator[]	325
25.90.3.9 Print	325
25.90.3.10 Read	325
25.90.3.11 Set	325
25.90.3.12 SetFromDataElement	325
25.90.3.13 SetNoSwap	325
25.90.3.14 SetValue	325
25.90.3.15 Write	325
25.90.4 Member Data Documentation	325
25.90.4.1 Internal	325
25.91gdcmm::Element< TVR, VM::VM1_2 > Class Template Reference	326
25.91.1 Member Typedef Documentation	327
25.91.1.1 Parent	327

25.91.2 Member Function Documentation	327
25.91.2.1 SetLength	327
25.92gdcmm::Element< TVR, VM::VM1_n > Class Template Reference	327
25.92.1 Member Typedef Documentation	328
25.92.1.1 Type	328
25.92.2 Constructor & Destructor Documentation	328
25.92.2.1 Element	328
25.92.2.2 ~Element	328
25.92.2.3 Element	328
25.92.3 Member Function Documentation	328
25.92.3.1 GetAsDataElement	328
25.92.3.2 GetLength	328
25.92.3.3 GetValue	328
25.92.3.4 GetValue	328
25.92.3.5 GetVM	328
25.92.3.6 GetVR	329
25.92.3.7 operator=	329
25.92.3.8 operator[]	329
25.92.3.9 Print	329
25.92.3.10Read	329
25.92.3.11Set	329
25.92.3.12SetArray	329
25.92.3.13SetFromDataElement	329
25.92.3.14SetLength	329
25.92.3.15SetNoSwap	329
25.92.3.16SetValue	329
25.92.3.17Write	329
25.92.3.18WriteASCII	329
25.93gdcmm::Element< TVR, VM::VM2_n > Class Template Reference	329
25.93.1 Member Typedef Documentation	331
25.93.1.1 Parent	331
25.93.2 Member Function Documentation	331
25.93.2.1 SetLength	331
25.94gdcmm::Element< TVR, VM::VM2_n > Class Template Reference	331
25.94.1 Member Typedef Documentation	332
25.94.1.1 Parent	332
25.94.2 Member Function Documentation	332

25.94.2.1 SetLength	332
25.95gdcmm::Element< TVR, VM::VM3_3n > Class Template Reference	332
25.95.1 Member Typedef Documentation	334
25.95.1.1 Parent	334
25.95.2 Member Function Documentation	334
25.95.2.1 SetLength	334
25.96gdcmm::Element< TVR, VM::VM3_n > Class Template Reference	334
25.96.1 Member Typedef Documentation	335
25.96.1.1 Parent	335
25.96.2 Member Function Documentation	335
25.96.2.1 SetLength	335
25.97gdcmm::Element< VR::AS, VM::VM5 > Class Template Reference	335
25.97.1 Member Function Documentation	336
25.97.1.1 GetLength	336
25.97.1.2 Print	336
25.97.2 Member Data Documentation	336
25.97.2.1 Internal	336
25.98gdcmm::Element< VR::OB, VM::VM1 > Class Template Reference	336
25.99gdcmm::Element< VR::OW, VM::VM1 > Class Template Reference	337
25.100gdcmm::ElementDisableCombinations< TVR, TVM > Class Template Reference	339
25.100. Detailed Description	339
25.101gdcmm::ElementDisableCombinations< VR::OB, VM::VM1_n > Class Template Reference	340
25.102gdcmm::ElementDisableCombinations< VR::OW, VM::VM1_n > Class Template Reference	340
25.103gdcmm::EncapsulatedDocument Class Reference	340
25.103. Detailed Description	340
25.103.2 Constructor & Destructor Documentation	340
25.103.2.1 EncapsulatedDocument	340
25.104gdcmm::EncodingImplementation< T > Class Template Reference	341
25.104. Detailed Description	341
25.105gdcmm::EncodingImplementation< VR::VRASCII > Class Template Reference	341
25.105. Member Function Documentation	341
25.105.1.1 Read	341
25.105.1.2 ReadComputeLength	342
25.105.1.3 ReadNoSwap	342
25.105.1.4 Write	342
25.105.1.5 Write	342
25.105.1.6 Write	342

25.106	dcm::EncodingImplementation< VR::VRBINARY > Class Template Reference	342
25.106.1	Member Function Documentation	342
25.106.1.1	Read	342
25.106.1.2	ReadComputeLength	343
25.106.1.3	ReadNoSwap	343
25.106.1.4	Write	343
25.107	dcm::EndEvent Class Reference	343
25.108	dcm::EnumeratedValues Class Reference	344
25.108.1	Detailed Description	344
25.108.2	Constructor & Destructor Documentation	345
25.108.2.1	EnumeratedValues	345
25.109	dcm::Event Class Reference	345
25.109.1	Detailed Description	346
25.109.2	Constructor & Destructor Documentation	346
25.109.2.1	Event	346
25.109.2.2	~Event	346
25.109.2.3	~Event	346
25.109.3	Member Function Documentation	346
25.109.3.1	CheckEvent	346
25.109.3.2	GetEventName	346
25.109.3.3	MakeObject	346
25.109.3.4	Print	346
25.110	dcm::Exception Class Reference	347
25.110.1	Detailed Description	348
25.110.2	Constructor & Destructor Documentation	348
25.110.2.1	Exception	348
25.110.2.2	~Exception	348
25.110.3	Member Function Documentation	348
25.110.3.1	GetDescription	348
25.110.3.2	what	348
25.111	dcm::ExitEvent Class Reference	348
25.112	dcm::ExplicitDataElement Class Reference	350
25.112.1	Detailed Description	351
25.112.2	Member Function Documentation	351
25.112.2.1	GetLength	351
25.112.2.2	Read	351
25.112.2.3	ReadPreValue	351

25.112.2.4	ReadValue	351
25.112.2.5	ReadWithLength	351
25.112.2.6	Write	351
25.113	gdcm::ExplicitImplicitDataElement Class Reference	351
25.113.1	Detailed Description	353
25.113.2	Member Function Documentation	353
25.113.2.1	GetLength	353
25.113.2.2	Read	353
25.113.2.3	ReadPreValue	353
25.113.2.4	ReadValue	353
25.113.2.5	ReadWithLength	353
25.114	gdcm::Fiducials Class Reference	353
25.114.1	Detailed Description	353
25.114.2	Constructor & Destructor Documentation	354
25.114.2.1	Fiducials	354
25.115	gdcm::File Class Reference	354
25.115.1	Detailed Description	355
25.115.2	Constructor & Destructor Documentation	356
25.115.2.1	File	356
25.115.2.2	~File	356
25.115.3	Member Function Documentation	356
25.115.3.1	GetDataSet	356
25.115.3.2	GetDataSet	356
25.115.3.3	GetHeader	356
25.115.3.4	GetHeader	357
25.115.3.5	Read	357
25.115.3.6	SetDataSet	357
25.115.3.7	SetHeader	357
25.115.3.8	Write	357
25.115.4	Friends And Related Function Documentation	357
25.115.4.1	operator<<	357
25.116	gdcm::FileAnonymizer Class Reference	357
25.116.1	Detailed Description	359
25.116.2	Constructor & Destructor Documentation	359
25.116.2.1	FileAnonymizer	359
25.116.2.2	~FileAnonymizer	359
25.116.3	Member Function Documentation	359

25.116.3.1Empty	359
25.116.3.2Remove	359
25.116.3.3Replace	359
25.116.3.4Replace	359
25.116.3.5SetInputFileName	360
25.116.3.6SetOutputFileName	360
25.116.3.7Write	360
25.117dcm::FileDerivation Class Reference	360
25.117.1Detailed Description	361
25.117.2Constructor & Destructor Documentation	361
25.117.2.1FileDerivation	361
25.117.2.2~FileDerivation	361
25.117.3Member Function Documentation	361
25.117.3.1AddDerivationDescription	361
25.117.3.2AddPurposeOfReferenceCodeSequence	361
25.117.3.3AddReference	361
25.117.3.4AddSourceImageSequence	361
25.117.3.5Derive	361
25.117.3.6GetFile	362
25.117.3.7GetFile	362
25.117.3.8SetDerivationCodeSequenceCodeValue	362
25.117.3.9SetDerivationDescription	362
25.117.3.10SetFile	362
25.117.3.11SetPurposeOfReferenceCodeSequenceCodeValue	362
25.118dcm::FileExplicitFilter Class Reference	362
25.118.1Detailed Description	363
25.118.2Constructor & Destructor Documentation	363
25.118.2.1FileExplicitFilter	363
25.118.2.2~FileExplicitFilter	363
25.118.3Member Function Documentation	363
25.118.3.1Change	364
25.118.3.2ChangeFMI	364
25.118.3.3GetFile	364
25.118.3.4ProcessDataSet	364
25.118.3.5SetChangePrivateTags	364
25.118.3.6SetFile	364
25.118.3.7SetRecomputeItemLength	364

25.118.3.8SetRecomputeSequenceLength	364
25.118.3.9SetUseVRUN	364
25.119.1gdcmm::FileMetaInformation Class Reference	364
25.119.1Detailed Description	367
25.119.2Constructor & Destructor Documentation	367
25.119.2.1FileMetaInformation	367
25.119.2.2~FileMetaInformation	367
25.119.2.3FileMetaInformation	367
25.119.3Member Function Documentation	367
25.119.3.1AppendImplementationClassUID	367
25.119.3.2ComputeDataSetMediaStorageSOPClass	367
25.119.3.3ComputeDataSetTransferSyntax	367
25.119.3.4Default	367
25.119.3.5FillFromDataSet	367
25.119.3.6GetDataSetTransferSyntax	367
25.119.3.7GetFileMetaInformationVersion	368
25.119.3.8GetFullLength	368
25.119.3.9GetGDCMImplementationClassUID	368
25.119.3.10GetGDCMImplementationVersionName	368
25.119.3.11GetGDCMSourceApplicationEntityTitle	368
25.119.3.12GetImplementationClassUID	368
25.119.3.13GetImplementationVersionName	368
25.119.3.14GetMediaStorage	368
25.119.3.15GetMetaInformationTS	368
25.119.3.16GetPreamble	368
25.119.3.17GetPreamble	368
25.119.3.18GetSourceApplicationEntityTitle	368
25.119.3.19Insert	368
25.119.3.20Valid	368
25.119.3.21Read	368
25.119.3.22ReadCompat	368
25.119.3.23ReadCompatInternal	368
25.119.3.24Replace	369
25.119.3.25SetDataSetTransferSyntax	369
25.119.3.26SetImplementationClassUID	369
25.119.3.27SetImplementationVersionName	369
25.119.3.28SetPreamble	369

25.119.3.2	SetSourceApplicationEntityTitle	369
25.119.3.3	Write	369
25.119.4	Friends And Related Function Documentation	369
25.119.4.1	operator<<	369
25.119.5	Member Data Documentation	369
25.119.5.1	DataSetMS	369
25.119.5.2	DataSetTS	369
25.119.5.3	MetaInformationTS	370
25.120	dcm::Filename Class Reference	370
25.120.1	Detailed Description	370
25.120.2	Constructor & Destructor Documentation	371
25.120.2.1	Filename	371
25.120.3	Member Function Documentation	371
25.120.3.1	EndWith	371
25.120.3.2	GetExtension	371
25.120.3.3	GetFileName	371
25.120.3.4	GetName	371
25.120.3.5	GetPath	371
25.120.3.6	IsEmpty	371
25.120.3.7	IsIdentical	371
25.120.3.8	Join	371
25.120.3.9	operator const char *	371
25.120.3.10	ToUnixSlashes	371
25.120.3.11	ToWindowsSlashes	372
25.121	dcm::FilenameGenerator Class Reference	372
25.121.1	Detailed Description	372
25.121.2	Member Typedef Documentation	373
25.121.2.1	FileNamesType	373
25.121.2.2	FilenameType	373
25.121.2.3	SizeType	373
25.121.3	Constructor & Destructor Documentation	373
25.121.3.1	FilenameGenerator	373
25.121.3.2	~FilenameGenerator	373
25.121.4	Member Function Documentation	373
25.121.4.1	Generate	373
25.121.4.2	GetFilename	373
25.121.4.3	GetFileNames	373

25.121.4.4	GetNumberOfFileNames	373
25.121.4.5	GetPattern	374
25.121.4.6	GetPrefix	374
25.121.4.7	SetNumberOfFileNames	374
25.121.4.8	SetPattern	374
25.121.4.9	SetPrefix	374
25.122	gdcm::FileSet Class Reference	374
25.122.1	Detailed Description	375
25.122.2	Member Typedef Documentation	375
25.122.2.1	FileType	375
25.122.2.2	FileType	375
25.122.3	Constructor & Destructor Documentation	375
25.122.3.1	FileSet	375
25.122.4	Member Function Documentation	375
25.122.4.1	AddFile	375
25.122.4.2	AddFile	375
25.122.4.3	GetFiles	375
25.122.4.4	SetFiles	375
25.122.5	Friends And Related Function Documentation	375
25.122.5.1	operator<<	375
25.123	gdcm::FileWithName Class Reference	375
25.123.1	Detailed Description	377
25.123.2	Constructor & Destructor Documentation	377
25.123.2.1	FileWithName	377
25.123.3	Member Data Documentation	377
25.123.3.1	filename	377
25.124	gdcm::FindPatientRootQuery Class Reference	377
25.124.1	Detailed Description	378
25.124.2	Constructor & Destructor Documentation	378
25.124.2.1	FindPatientRootQuery	378
25.124.3	Member Function Documentation	378
25.124.3.1	GetAbstractSyntaxUID	378
25.124.3.2	GetTagListByLevel	378
25.124.3.3	InitializeDataSet	379
25.124.3.4	ValidateQuery	379
25.124.4	Friends And Related Function Documentation	379
25.124.4.1	QueryFactory	379

25.125	dcm::FindStudyRootQuery Class Reference	379
25.125.1	Detailed Description	381
25.125.2	Constructor & Destructor Documentation	381
25.125.2.1	FindStudyRootQuery	381
25.125.3	Member Function Documentation	381
25.125.3.1	GetAbstractSyntaxUID	381
25.125.3.2	GetTagListByLevel	381
25.125.3.3	InitializeDataSet	381
25.125.3.4	ValidateQuery	381
25.125.4	Friends And Related Function Documentation	381
25.125.4.1	QueryFactory	381
25.126	dcm::Fragment Class Reference	381
25.126.1	Detailed Description	383
25.126.2	Constructor & Destructor Documentation	383
25.126.2.1	Fragment	383
25.126.3	Member Function Documentation	383
25.126.3.1	GetLength	383
25.126.3.2	Read	383
25.126.3.3	ReadBacktrack	383
25.126.3.4	ReadPreValue	383
25.126.3.5	ReadValue	383
25.126.3.6	Write	384
25.126.4	Friends And Related Function Documentation	384
25.126.4.1	operator<<	384
25.127	dcm::Global Class Reference	384
25.127.1	Detailed Description	385
25.127.2	Constructor & Destructor Documentation	385
25.127.2.1	Global	385
25.127.2.2	~Global	385
25.127.3	Member Function Documentation	385
25.127.3.1	Append	385
25.127.3.2	GetDefs	385
25.127.3.3	GetDicts	385
25.127.3.4	GetDicts	385
25.127.3.5	GetInstance	385
25.127.3.6	LoadResourcesFiles	386
25.127.3.7	Locate	386

25.127.3.8Prepend	386
25.127.4Friends And Related Function Documentation	386
25.127.4.1operator<<	386
25.128gdcmm::GroupDict Class Reference	386
25.128.1Detailed Description	387
25.128.2Member Typedef Documentation	387
25.128.2.1GroupStringVector	387
25.128.3Constructor & Destructor Documentation	387
25.128.3.1GroupDict	387
25.128.3.2~GroupDict	387
25.128.4Member Function Documentation	387
25.128.4.1Add	387
25.128.4.2GetAbbreviation	387
25.128.4.3GetName	387
25.128.4.4Insert	388
25.128.4.5Size	388
25.128.5Friends And Related Function Documentation	388
25.128.5.1operator<<	388
25.129gdcmm::IconImageFilter Class Reference	388
25.129.1Detailed Description	388
25.129.2Constructor & Destructor Documentation	389
25.129.2.1IconImageFilter	389
25.129.2.2~IconImageFilter	389
25.129.3Member Function Documentation	389
25.129.3.1Extract	389
25.129.3.2ExtractIconImages	389
25.129.3.3ExtractVeprolIconImages	389
25.129.3.4GetFile	389
25.129.3.5GetFile	389
25.129.3.6GetIconImage	390
25.129.3.7GetNumberOfIconImages	390
25.129.3.8SetFile	390
25.130gdcmm::IconImageGenerator Class Reference	390
25.130.1Detailed Description	391
25.130.2Constructor & Destructor Documentation	391
25.130.2.1IconImageGenerator	391
25.130.2.2~IconImageGenerator	391

25.130.3	Member Function Documentation	391
25.130.3.1	AutoPixelMinMax	391
25.130.3.2	ConvertRGBToPaletteColor	391
25.130.3.3	Generate	391
25.130.3.4	GetIconImage	392
25.130.3.5	GetPixmap	392
25.130.3.6	GetPixmap	392
25.130.3.7	SetOutputDimensions	392
25.130.3.8	SetOutsideValuePixel	392
25.130.3.9	SetPixelMinMax	392
25.130.3.10	SetPixmap	392
25.130	gdcm::ignore_char Struct Reference	392
25.131.1	Constructor & Destructor Documentation	393
25.131.1.1	ignore_char	393
25.131.2	Member Data Documentation	393
25.131.2.1	m_char	393
25.132	gdcm::Image Class Reference	393
25.132.1	Detailed Description	394
25.132.2	Constructor & Destructor Documentation	395
25.132.2.1	Image	395
25.132.2.2	~Image	395
25.132.3	Member Function Documentation	395
25.132.3.1	GetDirectionCosines	395
25.132.3.2	GetDirectionCosines	395
25.132.3.3	GetIntercept	395
25.132.3.4	GetOrigin	395
25.132.3.5	GetOrigin	396
25.132.3.6	GetSlope	396
25.132.3.7	GetSpacing	396
25.132.3.8	GetSpacing	396
25.132.3.9	Print	396
25.132.3.10	SetDirectionCosines	396
25.132.3.11	SetDirectionCosines	396
25.132.3.12	SetDirectionCosines	396
25.132.3.13	SetIntercept	396
25.132.3.14	SetOrigin	396
25.132.3.15	SetOrigin	396

25.132.3.1	SetOrigin	396
25.132.3.1	SetSlope	396
25.132.3.1	SetSpacing	396
25.132.3.1	SetSpacing	397
25.133	dcm::ImageApplyLookupTable Class Reference	397
25.133.1	Detailed Description	399
25.133.2	Constructor & Destructor Documentation	399
25.133.2.1	ImageApplyLookupTable	399
25.133.2.2	~ImageApplyLookupTable	399
25.133.3	Member Function Documentation	399
25.133.3.1	Apply	399
25.134	dcm::ImageChangePhotometricInterpretation Class Reference	399
25.134.1	Detailed Description	402
25.134.2	Constructor & Destructor Documentation	402
25.134.2.1	ImageChangePhotometricInterpretation	402
25.134.2.2	~ImageChangePhotometricInterpretation	402
25.134.3	Member Function Documentation	402
25.134.3.1	Change	402
25.134.3.2	ChangeMonochrome	402
25.134.3.3	GetPhotometricInterpretation	402
25.134.3.4	RGB2YBR	402
25.134.3.5	RGB2YBR	402
25.134.3.6	SetPhotometricInterpretation	403
25.134.3.7	YBR2RGB	403
25.134.3.8	YBR2RGB	403
25.135	dcm::ImageChangePlanarConfiguration Class Reference	403
25.135.1	Detailed Description	405
25.135.2	Constructor & Destructor Documentation	405
25.135.2.1	ImageChangePlanarConfiguration	405
25.135.2.2	~ImageChangePlanarConfiguration	405
25.135.3	Member Function Documentation	405
25.135.3.1	Change	405
25.135.3.2	GetPlanarConfiguration	405
25.135.3.3	RGBPixelsToRGBPlanes	405
25.135.3.4	RGBPixelsToRGBPlanes	405
25.135.3.5	RGBPlanesToRGBPixels	405
25.135.3.6	RGBPlanesToRGBPixels	406

25.135.3.7SetPlanarConfiguration	406
25.136.0dcm::ImageChangeTransferSyntax Class Reference	406
25.136.1Detailed Description	408
25.136.2Constructor & Destructor Documentation	408
25.136.2.1ImageChangeTransferSyntax	408
25.136.2.2~ImageChangeTransferSyntax	408
25.136.3Member Function Documentation	408
25.136.3.1Change	408
25.136.3.2GetTransferSyntax	408
25.136.3.3SetCompressIconImage	409
25.136.3.4SetForce	409
25.136.3.5SetTransferSyntax	409
25.136.3.6SetUserCodec	409
25.136.3.7TryJPEG2000Codec	409
25.136.3.8TryJPEGCodec	409
25.136.3.9TryJPEGLSCodec	409
25.136.3.10TryRAWCodec	409
25.136.3.11TryRLECodec	409
25.137.0dcm::ImageCodec Class Reference	410
25.137.1Detailed Description	412
25.137.2Member Typedef Documentation	412
25.137.2.1LUTPtr	412
25.137.3Constructor & Destructor Documentation	412
25.137.3.1ImageCodec	412
25.137.3.2~ImageCodec	412
25.137.4Member Function Documentation	412
25.137.4.1CanCode	412
25.137.4.2CanDecode	412
25.137.4.3Decode	412
25.137.4.4DecodeByStreams	413
25.137.4.5DoByteSwap	413
25.137.4.6DoInvertMonochrome	413
25.137.4.7DoOverlayCleanup	413
25.137.4.8DoPaddedCompositePixelCode	413
25.137.4.9DoPlanarConfiguration	413
25.137.4.10DoSimpleCopy	413
25.137.4.11DoYBR	413

25.137.4.10	GetDimensions	413
25.137.4.10	GetHeaderInfo	413
25.137.4.10	GetLossyFlag	413
25.137.4.10	GetLUT	413
25.137.4.10	GetNeedByteSwap	413
25.137.4.10	GetNumberOfDimensions	413
25.137.4.10	GetPhotometricInterpretation	413
25.137.4.10	GetPixelFormat	413
25.137.4.20	GetPixelFormat	413
25.137.4.20	GetPlanarConfiguration	413
25.137.4.20	Lossy	413
25.137.4.20	Valid	414
25.137.4.20	SetDimensions	414
25.137.4.20	SetDimensions	414
25.137.4.20	SetLossyFlag	414
25.137.4.20	SetLUT	414
25.137.4.20	SetNeedByteSwap	414
25.137.4.20	SetNeedOverlayCleanup	414
25.137.4.30	SetNumberOfDimensions	414
25.137.4.30	SetPhotometricInterpretation	414
25.137.4.30	SetPixelFormat	414
25.137.4.30	SetPlanarConfiguration	414
25.137.5	Friends And Related Function Documentation	414
25.137.5.1	ImageChangePhotometricInterpretation	414
25.137.6	Member Data Documentation	414
25.137.6.1	Dimensions	415
25.137.6.2	LossyFlag	415
25.137.6.3	LUT	415
25.137.6.4	NeedByteSwap	415
25.137.6.5	NeedOverlayCleanup	415
25.137.6.6	NumberOfDimensions	415
25.137.6.7	PF	415
25.137.6.8	PI	415
25.137.6.9	PlanarConfiguration	415
25.137.6.10	RequestPaddedCompositePixelCode	415
25.137.6.10	RequestPlanarConfiguration	415
25.137.6	dcm::ImageConverter Class Reference	415

25.138.1	Detailed Description	415
25.138.2	Constructor & Destructor Documentation	416
25.138.2.1	ImageConverter	416
25.138.2.2	~ImageConverter	416
25.138.3	Member Function Documentation	416
25.138.3.1	Convert	416
25.138.3.2	GetOutput	416
25.138.3.3	SetInput	416
25.139	gdcm::ImageFragmentSplitter Class Reference	416
25.139.1	Detailed Description	418
25.139.2	Constructor & Destructor Documentation	418
25.139.2.1	ImageFragmentSplitter	418
25.139.2.2	~ImageFragmentSplitter	418
25.139.3	Member Function Documentation	418
25.139.3.1	GetFragmentSizeMax	418
25.139.3.2	SetForce	418
25.139.3.3	SetFragmentSizeMax	418
25.139.3.4	Split	418
25.140	gdcm::ImageHelper Class Reference	418
25.140.1	Detailed Description	419
25.140.2	Member Function Documentation	419
25.140.2.1	ComputeSpacingFromImagePositionPatient	419
25.140.2.2	GetDimensionsValue	420
25.140.2.3	GetDirectionCosinesFromDataSet	420
25.140.2.4	GetDirectionCosinesValue	420
25.140.2.5	GetForcePixelSpacing	420
25.140.2.6	GetForceRescaleInterceptSlope	420
25.140.2.7	GetLUT	420
25.140.2.8	GetOriginValue	420
25.140.2.9	GetPhotometricInterpretationValue	420
25.140.2.10	GetPixelFormatValue	420
25.140.2.11	GetPlanarConfigurationValue	420
25.140.2.12	GetPointerFromElement	420
25.140.2.13	GetRescaleInterceptSlopeValue	420
25.140.2.14	GetSpacingTagFromMediaStorage	421
25.140.2.15	GetSpacingValue	421
25.140.2.16	GetZSpacingTagFromMediaStorage	421

25.140.2.1	SetDimensionsValue	421
25.140.2.1	SetDirectionCosinesValue	421
25.140.2.1	SetForcePixelSpacing	421
25.140.2.2	SetForceRescaleInterceptSlope	421
25.140.2.2	SetOriginValue	421
25.140.2.2	SetRescaleInterceptSlopeValue	421
25.140.2.2	SetSpacingValue	421
25.141	gdcm::ImageReader Class Reference	421
25.141.1	Detailed Description	424
25.141.2	Constructor & Destructor Documentation	424
25.141.2.1	ImageReader	424
25.141.2.2	~ImageReader	424
25.141.3	Member Function Documentation	424
25.141.3.1	GetImage	424
25.141.3.2	GetImage	424
25.141.3.3	Read	424
25.141.3.4	ReadACRNEMAIImage	425
25.141.3.5	ReadImage	425
25.142	gdcm::ImageRegionReader Class Reference	425
25.142.1	Detailed Description	427
25.142.2	Constructor & Destructor Documentation	427
25.142.2.1	ImageRegionReader	427
25.142.2.2	~ImageRegionReader	427
25.142.3	Member Function Documentation	427
25.142.3.1	ComputeBufferLength	427
25.142.3.2	GetRegion	427
25.142.3.3	Read	427
25.142.3.4	ReadInformation	427
25.142.3.5	ReadIntoBuffer	428
25.142.3.6	SetRegion	428
25.143	gdcm::ImageToImageFilter Class Reference	428
25.143.1	Detailed Description	429
25.143.2	Constructor & Destructor Documentation	430
25.143.2.1	ImageToImageFilter	430
25.143.2.2	~ImageToImageFilter	430
25.143.3	Member Function Documentation	430
25.143.3.1	GetInput	430

25.143.3.2	GetOutput	430
25.144	dcm::ImageWriter Class Reference	430
25.144.1	Detailed Description	432
25.144.2	Constructor & Destructor Documentation	432
25.144.2.1	ImageWriter	432
25.144.2.2	~ImageWriter	432
25.144.3	Member Function Documentation	432
25.144.3.1	GetImage	432
25.144.3.2	GetImage	432
25.144.3.3	Write	432
25.145	dcm::network::ImplementationClassUIDSub Class Reference	433
25.145.1	Detailed Description	433
25.145.2	Constructor & Destructor Documentation	433
25.145.2.1	ImplementationClassUIDSub	433
25.145.3	Member Function Documentation	433
25.145.3.1	Print	433
25.145.3.2	Read	433
25.145.3.3	Size	433
25.145.3.4	Write	433
25.146	dcm::network::ImplementationUIDSub Class Reference	433
25.146.1	Detailed Description	434
25.146.2	Constructor & Destructor Documentation	434
25.146.2.1	ImplementationUIDSub	434
25.146.3	Member Function Documentation	434
25.146.3.1	Write	434
25.147	dcm::network::ImplementationVersionNameSub Class Reference	434
25.147.1	Detailed Description	434
25.147.2	Constructor & Destructor Documentation	434
25.147.2.1	ImplementationVersionNameSub	434
25.147.3	Member Function Documentation	434
25.147.3.1	Print	434
25.147.3.2	Read	434
25.147.3.3	Size	434
25.147.3.4	Write	435
25.148	dcm::ImplicitDataElement Class Reference	435
25.148.1	Detailed Description	436
25.148.2	Member Function Documentation	436

25.148.2.1	GetLength	436
25.148.2.2	Read	436
25.148.2.3	ReadPreValue	436
25.148.2.4	ReadValue	436
25.148.2.5	ReadWithLength	436
25.148.2.6	Write	436
25.149	dcm::InitializeEvent Class Reference	436
25.150	dcm::IOD Class Reference	438
25.150.1	Detailed Description	438
25.150.2	Member Typedef Documentation	438
25.150.2.1	MapIODEntry	438
25.150.2.2	SizeType	438
25.150.3	Constructor & Destructor Documentation	438
25.150.3.1	IOD	438
25.150.4	Member Function Documentation	439
25.150.4.1	AddIODEntry	439
25.150.4.2	Clear	439
25.150.4.3	GetIODEntry	439
25.150.4.4	GetNumberOfIODs	439
25.150.4.5	GetTypeFromTag	439
25.150.5	Friends And Related Function Documentation	439
25.150.5.1	operator<<	439
25.151	dcm::IODEntry Class Reference	439
25.151.1	Detailed Description	440
25.151.2	Constructor & Destructor Documentation	440
25.151.2.1	IODEntry	440
25.151.3	Member Function Documentation	440
25.151.3.1	GetIE	440
25.151.3.2	GetName	440
25.151.3.3	GetRef	440
25.151.3.4	GetUsage	441
25.151.3.5	GetUsageType	441
25.151.3.6	SetIE	441
25.151.3.7	SetName	441
25.151.3.8	SetRef	441
25.151.3.9	SetUsage	441
25.151.4	Friends And Related Function Documentation	441

25.151.4.1operator<<	441
25.152gdcmm::IODs Class Reference	441
25.152.1Detailed Description	442
25.152.2Member Typedef Documentation	442
25.152.2.1IODMapType	442
25.152.2.2IODMapTypeConstIterator	442
25.152.2.3IODName	442
25.152.3Constructor & Destructor Documentation	442
25.152.3.1IODs	442
25.152.4Member Function Documentation	442
25.152.4.1AddIOD	442
25.152.4.2Begin	442
25.152.4.3Clear	442
25.152.4.4End	442
25.152.4.5GetIOD	442
25.152.5Friends And Related Function Documentation	442
25.152.5.1operator<<	442
25.153gdcmm::IPPSorter Class Reference	442
25.153.1Detailed Description	444
25.153.2Constructor & Destructor Documentation	444
25.153.2.1IPPSorter	444
25.153.2.2~IPPSorter	444
25.153.3Member Function Documentation	444
25.153.3.1GetDirectionCosinesTolerance	444
25.153.3.2GetZSpacing	444
25.153.3.3GetZSpacingTolerance	445
25.153.3.4SetComputeZSpacing	445
25.153.3.5SetDirectionCosinesTolerance	445
25.153.3.6SetDropDuplicatePositions	445
25.153.3.7SetZSpacingTolerance	445
25.153.3.8Sort	445
25.153.4Member Data Documentation	446
25.153.4.1ComputeZSpacing	446
25.153.4.2DirCosTolerance	446
25.153.4.3DropDuplicatePositions	446
25.153.4.4ZSpacing	446
25.153.4.5ZTolerance	446

25.154	dcm::Item Class Reference	446
25.154.1	Detailed Description	448
25.154.2	Constructor & Destructor Documentation	448
25.154.2.1	Item	448
25.154.2.2	Item	448
25.154.3	Member Function Documentation	448
25.154.3.1	Clear	448
25.154.3.2	FindDataElement	448
25.154.3.3	GetDataElement	448
25.154.3.4	GetLength	448
25.154.3.5	GetNestedDataSet	448
25.154.3.6	GetNestedDataSet	449
25.154.3.7	InsertDataElement	449
25.154.3.8	Read	449
25.154.3.9	SetNestedDataSet	449
25.154.3.10	Write	449
25.154.4	Friends And Related Function Documentation	449
25.154.4.1	operator<<	449
25.155	dcm::IterationEvent Class Reference	449
25.156	dcm::JPEG12Codec Class Reference	451
25.156.1	Detailed Description	452
25.156.2	Constructor & Destructor Documentation	452
25.156.2.1	JPEG12Codec	452
25.156.2.2	~JPEG12Codec	452
25.156.3	Member Function Documentation	452
25.156.3.1	DecodeByStreams	452
25.156.3.2	GetHeaderInfo	452
25.156.3.3	InternalCode	452
25.156.3.4	IsStateSuspension	452
25.157	dcm::JPEG16Codec Class Reference	453
25.157.1	Detailed Description	454
25.157.2	Constructor & Destructor Documentation	454
25.157.2.1	JPEG16Codec	454
25.157.2.2	~JPEG16Codec	454
25.157.3	Member Function Documentation	454
25.157.3.1	DecodeByStreams	454
25.157.3.2	GetHeaderInfo	454

25.157.3.3InternalCode	454
25.157.3.4IsStateSuspension	454
25.158dcm::JPEG2000Codec Class Reference	455
25.158.1Detailed Description	456
25.158.2Constructor & Destructor Documentation	456
25.158.2.1JPEG2000Codec	456
25.158.2.2~JPEG2000Codec	456
25.158.3Member Function Documentation	456
25.158.3.1CanCode	456
25.158.3.2CanDecode	457
25.158.3.3Code	457
25.158.3.4Decode	457
25.158.3.5DecodeByStreams	457
25.158.3.6DecodeExtent	457
25.158.3.7GetHeaderInfo	457
25.158.3.8GetQuality	457
25.158.3.9GetRate	457
25.158.3.10SetNumberOfResolutions	457
25.158.3.11SetQuality	457
25.158.3.12SetRate	457
25.158.3.13SetReversible	457
25.158.3.14SetTileSize	457
25.158.4Friends And Related Function Documentation	457
25.158.4.1Bitmap	457
25.158.4.2ImageRegionReader	457
25.159dcm::JPEG8Codec Class Reference	458
25.159.1Detailed Description	459
25.159.2Constructor & Destructor Documentation	459
25.159.2.1JPEG8Codec	459
25.159.2.2~JPEG8Codec	459
25.159.3Member Function Documentation	459
25.159.3.1DecodeByStreams	459
25.159.3.2GetHeaderInfo	459
25.159.3.3InternalCode	459
25.159.3.4IsStateSuspension	459
25.160dcm::JPEGCodec Class Reference	460
25.160.1Detailed Description	461

25.160.2	Constructor & Destructor Documentation	. 462
25.160.2.1	JPEGCodec	. 462
25.160.2.2	~JPEGCodec	. 462
25.160.3	Member Function Documentation	. 462
25.160.3.1	CanCode	. 462
25.160.3.2	CanDecode	. 462
25.160.3.3	Code	. 462
25.160.3.4	ComputeOffsetTable	. 462
25.160.3.5	Decode	. 462
25.160.3.6	DecodeByStreams	. 462
25.160.3.7	DecodeExtent	. 463
25.160.3.8	GetHeaderInfo	. 463
25.160.3.9	GetLossless	. 463
25.160.3.10	GetQuality	. 463
25.160.3.11	StateSuspension	. 463
25.160.3.12	Valid	. 463
25.160.3.13	SetBitSample	. 463
25.160.3.14	SetLossless	. 463
25.160.3.15	SetPixelFormat	. 463
25.160.3.16	SetQuality	. 463
25.160.4	Friends And Related Function Documentation	. 463
25.160.4.1	ImageRegionReader	. 463
25.160.5	Member Data Documentation	. 463
25.160.5.1	BitSample	. 463
25.160.5.2	Lossless	. 463
25.160.5.3	Quality	. 464
25.160.6	gdcm::JPEGLSCodec Class Reference	. 464
25.161.1	Detailed Description	. 465
25.161.2	Constructor & Destructor Documentation	. 466
25.161.2.1	JPEGLSCodec	. 466
25.161.2.2	~JPEGLSCodec	. 466
25.161.3	Member Function Documentation	. 466
25.161.3.1	CanCode	. 466
25.161.3.2	CanDecode	. 466
25.161.3.3	Code	. 466
25.161.3.4	Decode	. 466
25.161.3.5	Decode	. 466

25.161.3.6	DecodeExtent	466
25.161.3.7	GetBufferLength	466
25.161.3.8	GetHeaderInfo	466
25.161.3.9	GetLossless	466
25.161.3.10	SetBufferLength	466
25.161.3.11	SetLossless	466
25.161.3.12	SetLossyError	467
25.161.4	Friends And Related Function Documentation	467
25.161.4.1	ImageRegionReader	467
25.162	gdcm::KAKADUCodec Class Reference	467
25.162.1	Detailed Description	468
25.162.2	Constructor & Destructor Documentation	468
25.162.2.1	KAKADUCodec	468
25.162.2.2	~KAKADUCodec	468
25.162.3	Member Function Documentation	468
25.162.3.1	CanCode	468
25.162.3.2	CanDecode	468
25.162.3.3	Code	469
25.162.3.4	Decode	469
25.163	gdcm::LO Class Reference	469
25.163.1	Detailed Description	470
25.163.2	Member Typedef Documentation	471
25.163.2.1	const_iterator	471
25.163.2.2	const_reference	471
25.163.2.3	const_reverse_iterator	471
25.163.2.4	difference_type	471
25.163.2.5	iterator	471
25.163.2.6	pointer	471
25.163.2.7	reference	471
25.163.2.8	reverse_iterator	471
25.163.2.9	size_type	471
25.163.2.10	Superclass	471
25.163.2.11	value_type	471
25.163.3	Constructor & Destructor Documentation	471
25.163.3.1	LO	471
25.163.3.2	LO	471
25.163.3.3	LO	471

25.163.3.4LO	. 471
25.163.4Member Function Documentation	. 471
25.163.4.1IsValid	. 471
25.164dcm::LookupTable Class Reference	. 471
25.164.1Detailed Description	. 473
25.164.2Member Enumeration Documentation	. 474
25.164.2.1LookupTableType	. 474
25.164.3Constructor & Destructor Documentation	. 474
25.164.3.1LookupTable	. 474
25.164.3.2~LookupTable	. 474
25.164.3.3LookupTable	. 474
25.164.4Member Function Documentation	. 474
25.164.4.1Allocate	. 474
25.164.4.2Clear	. 474
25.164.4.3Decode	. 474
25.164.4.4Decode	. 474
25.164.4.5GetBitSample	. 474
25.164.4.6GetBufferAsRGBA	. 474
25.164.4.7GetLUT	. 475
25.164.4.8GetLUTDescriptor	. 475
25.164.4.9GetLUTLength	. 475
25.164.4.10GetPointer	. 475
25.164.4.11InitializeBlueLUT	. 475
25.164.4.12Initialized	. 475
25.164.4.13InitializeGreenLUT	. 475
25.164.4.14InitializeLUT	. 475
25.164.4.15InitializeRedLUT	. 475
25.164.4.16Print	. 475
25.164.4.17SetBlueLUT	. 475
25.164.4.18SetGreenLUT	. 475
25.164.4.19SetLUT	. 475
25.164.4.20SetRedLUT	. 475
25.164.4.21WriteBufferAsRGBA	. 475
25.164.5Member Data Documentation	. 476
25.164.5.1BitSample	. 476
25.164.5.2IncompleteLUT	. 476
25.164.5.3Internal	. 476

25.165	dcm::Scanner::Itstr Struct Reference	476
25.165.1	Member Function Documentation	476
25.165.1.1	operator()	476
25.166	dcm::Macro Class Reference	476
25.166.1	Detailed Description	477
25.166.2	Member Typedef Documentation	477
25.166.2.1	ArrayIncludeMacrosType	477
25.166.2.2	MapModuleEntry	477
25.166.3	Constructor & Destructor Documentation	477
25.166.3.1	Macro	477
25.166.4	Member Function Documentation	477
25.166.4.1	AddMacroEntry	477
25.166.4.2	Clear	477
25.166.4.3	FindMacroEntry	477
25.166.4.4	GetMacroEntry	477
25.166.4.5	GetName	477
25.166.4.6	SetName	477
25.166.4.7	Verify	478
25.166.5	Friends And Related Function Documentation	478
25.166.5.1	operator<<	478
25.167	dcm::Macros Class Reference	478
25.167.1	Detailed Description	478
25.167.2	Member Typedef Documentation	479
25.167.2.1	ModuleMapType	479
25.167.3	Constructor & Destructor Documentation	479
25.167.3.1	Macros	479
25.167.4	Member Function Documentation	479
25.167.4.1	AddMacro	479
25.167.4.2	Clear	479
25.167.4.3	GetMacro	479
25.167.4.4	IsEmpty	479
25.167.5	Friends And Related Function Documentation	479
25.167.5.1	operator<<	479
25.168	dcm::network::MaximumLengthSub Class Reference	479
25.168.1	Detailed Description	479
25.168.2	Constructor & Destructor Documentation	480
25.168.2.1	MaximumLengthSub	480

25.168.3	Member Function Documentation	480
25.168.3.1	GetMaximumLength	480
25.168.3.2	Print	480
25.168.3.3	Read	480
25.168.3.4	SetMaximumLength	480
25.168.3.5	Size	480
25.168.3.6	Write	480
25.169	dcm::MD5 Class Reference	480
25.169.1	Detailed Description	480
25.169.2	Constructor & Destructor Documentation	481
25.169.2.1	MD5	481
25.169.2.2	~MD5	481
25.169.3	Member Function Documentation	481
25.169.3.1	Compute	481
25.169.3.2	ComputeFile	481
25.170	dcm::MediaStorage Class Reference	481
25.170.1	Detailed Description	484
25.170.2	Member Enumeration Documentation	484
25.170.2.1	MSType	484
25.170.2.2	ObjectType	486
25.170.3	Constructor & Destructor Documentation	487
25.170.3.1	MediaStorage	487
25.170.4	Member Function Documentation	487
25.170.4.1	GetModality	487
25.170.4.2	GetModalityDimension	487
25.170.4.3	GetMSString	487
25.170.4.4	GetMSType	487
25.170.4.5	GetNumberOfModality	487
25.170.4.6	GetNumberOfMSString	487
25.170.4.7	GetNumberOfMSType	487
25.170.4.8	GetString	487
25.170.4.9	GuessFromModality	487
25.170.4.10	Image	487
25.170.4.11	Undefined	488
25.170.4.12	operator MSType	488
25.170.4.13	SetFromDataSet	488
25.170.4.14	SetFromFile	488

25.170.4.1	SetFromHeader	488
25.170.4.1	SetFromModality	488
25.170.4.1	SetFromSourceImageSequence	488
25.170.5	Friends And Related Function Documentation	488
25.170.5.1	operator<<	488
25.171	gdcm::MemberCommand< T > Class Template Reference	488
25.171.1	Detailed Description	490
25.171.2	Member Typedef Documentation	490
25.171.2.1	Self	490
25.171.2.2	TConstMemberFunctionPointer	491
25.171.2.3	TMemberFunctionPointer	491
25.171.3	Constructor & Destructor Documentation	491
25.171.3.1	MemberCommand	491
25.171.3.2	~MemberCommand	491
25.171.4	Member Function Documentation	491
25.171.4.1	Execute	491
25.171.4.2	~Execute	491
25.171.4.3	New	491
25.171.4.4	SetCallbackFunction	491
25.171.4.5	SetCallbackFunction	492
25.171.5	Member Data Documentation	492
25.171.5.1	m_ConstMemberFunction	492
25.171.5.2	m_MemberFunction	492
25.171.5.3	m_This	492
25.172	gdcm::MeshPrimitive Class Reference	492
25.172.1	Detailed Description	494
25.172.2	Member Typedef Documentation	494
25.172.2.1	PrimitivesData	494
25.172.3	Member Enumeration Documentation	494
25.172.3.1	MPType	494
25.172.4	Constructor & Destructor Documentation	495
25.172.4.1	MeshPrimitive	495
25.172.4.2	~MeshPrimitive	495
25.172.5	Member Function Documentation	495
25.172.5.1	AddPrimitiveData	495
25.172.5.2	GetMPType	495
25.172.5.3	GetMPTypeString	495

25.172.5.4	GetNumberOfPrimitivesData	495
25.172.5.5	GetPrimitiveData	495
25.172.5.6	GetPrimitiveData	495
25.172.5.7	GetPrimitiveData	495
25.172.5.8	GetPrimitiveData	495
25.172.5.9	GetPrimitivesData	495
25.172.5.10	GetPrimitivesData	495
25.172.5.10	GetPrimitiveType	495
25.172.5.12	SetPrimitiveData	495
25.172.5.13	SetPrimitiveData	495
25.172.5.13	SetPrimitivesData	495
25.172.5.13	SetPrimitiveType	495
25.172.6	Member Data Documentation	495
25.172.6.1	PrimitiveData	495
25.172.6.2	PrimitiveType	495
25.173	dcm::ModifiedEvent Class Reference	495
25.174	dcm::Module Class Reference	497
25.174.1	Detailed Description	497
25.174.2	Member Typedef Documentation	498
25.174.2.1	ArrayIncludeMacrosType	498
25.174.2.2	MapModuleEntry	498
25.174.3	Constructor & Destructor Documentation	498
25.174.3.1	Module	498
25.174.4	Member Function Documentation	498
25.174.4.1	AddMacro	498
25.174.4.2	AddModuleEntry	498
25.174.4.3	Clear	498
25.174.4.4	FindModuleEntryInMacros	498
25.174.4.5	GetModuleEntryInMacros	498
25.174.4.6	GetName	498
25.174.4.7	SetName	498
25.174.4.8	Verify	498
25.174.5	Friends And Related Function Documentation	498
25.174.5.1	operator<<	498
25.175	dcm::ModuleEntry Class Reference	499
25.175.1	Detailed Description	500
25.175.2	Member Typedef Documentation	500

25.175.2.1Description	500
25.175.3Constructor & Destructor Documentation	500
25.175.3.1ModuleEntry	500
25.175.3.2~ModuleEntry	501
25.175.4Member Function Documentation	501
25.175.4.1GetDescription	501
25.175.4.2GetName	501
25.175.4.3GetType	501
25.175.4.4SetDescription	501
25.175.4.5SetName	501
25.175.4.6SetType	501
25.175.5Friends And Related Function Documentation	501
25.175.5.1operator<<	501
25.175.6Member Data Documentation	501
25.175.6.1DataElementType	501
25.175.6.2DescriptionField	501
25.175.6.3Name	501
25.176dcm::Modules Class Reference	501
25.176.1Detailed Description	502
25.176.2Member Typedef Documentation	502
25.176.2.1ModuleMapType	502
25.176.3Constructor & Destructor Documentation	502
25.176.3.1Modules	502
25.176.4Member Function Documentation	502
25.176.4.1AddModule	502
25.176.4.2Clear	502
25.176.4.3GetModule	502
25.176.4.4IsEmpty	502
25.176.5Friends And Related Function Documentation	503
25.176.5.1operator<<	503
25.177dcm::MovePatientRootQuery Class Reference	503
25.177.1Detailed Description	504
25.177.2Constructor & Destructor Documentation	504
25.177.2.1MovePatientRootQuery	504
25.177.3Member Function Documentation	504
25.177.3.1GetAbstractSyntaxUID	504
25.177.3.2GetTagListByLevel	504

25.177.3.3InitializeDataSet	504
25.177.3.4ValidateQuery	504
25.177.4Friends And Related Function Documentation	505
25.177.4.1QueryFactory	505
25.178dcm::MoveStudyRootQuery Class Reference	505
25.178.1Detailed Description	506
25.178.2Constructor & Destructor Documentation	506
25.178.2.1MoveStudyRootQuery	506
25.178.3Member Function Documentation	506
25.178.3.1GetAbstractSyntaxUID	506
25.178.3.2GetTagListByLevel	506
25.178.3.3InitializeDataSet	507
25.178.3.4ValidateQuery	507
25.178.4Friends And Related Function Documentation	507
25.178.4.1QueryFactory	507
25.179dcm::NestedModuleEntries Class Reference	507
25.179.1Detailed Description	509
25.179.2Member Typedef Documentation	509
25.179.2.1SizeType	509
25.179.3Constructor & Destructor Documentation	509
25.179.3.1NestedModuleEntries	509
25.179.4Member Function Documentation	509
25.179.4.1AddModuleEntry	509
25.179.4.2GetModuleEntry	509
25.179.4.3GetModuleEntry	509
25.179.4.4GetNumberOfModuleEntries	509
25.179.5Friends And Related Function Documentation	509
25.179.5.1operator<<	509
25.180dcm::NoEvent Class Reference	509
25.180.1Detailed Description	510
25.181dcm::Object Class Reference	510
25.181.1Detailed Description	512
25.181.2Constructor & Destructor Documentation	512
25.181.2.1Object	512
25.181.2.2~Object	512
25.181.2.3Object	512
25.181.3Member Function Documentation	512

25.181.3.1operator=	512
25.181.3.2Print	512
25.181.3.3Register	512
25.181.3.4UnRegister	512
25.181.4Friends And Related Function Documentation	512
25.181.4.1operator<<	512
25.181.4.2SmartPointer	512
25.182dcm::Orientation Class Reference	513
25.182.1Detailed Description	513
25.182.2Member Enumeration Documentation	514
25.182.2.1OrientationType	514
25.182.3Constructor & Destructor Documentation	514
25.182.3.1Orientation	514
25.182.3.2~Orientation	514
25.182.4Member Function Documentation	514
25.182.4.1GetLabel	514
25.182.4.2GetMajorAxisFromPatientRelativeDirectionCosine	514
25.182.4.3GetObliquityThresholdCosineValue	514
25.182.4.4GetType	514
25.182.4.5Print	514
25.182.4.6SetObliquityThresholdCosineValue	514
25.182.5Friends And Related Function Documentation	514
25.182.5.1operator<<	514
25.183dcm::Overlay Class Reference	515
25.183.1Detailed Description	517
25.183.2Member Enumeration Documentation	517
25.183.2.1OverlayType	517
25.183.3Constructor & Destructor Documentation	518
25.183.3.1Overlay	518
25.183.3.2~Overlay	518
25.183.3.3Overlay	518
25.183.4Member Function Documentation	518
25.183.4.1Decode	518
25.183.4.2Decompress	518
25.183.4.3GetBitPosition	518
25.183.4.4GetBitsAllocated	518
25.183.4.5GetBuffer	518

25.183.4.6	GetColumns	518
25.183.4.7	GetDescription	518
25.183.4.8	GetGroup	518
25.183.4.9	GetOrigin	518
25.183.4.10	GetOverlayData	519
25.183.4.10	GetOverlayTypeAsString	519
25.183.4.10	GetOverlayTypeFromString	519
25.183.4.10	GetRows	519
25.183.4.10	GetType	519
25.183.4.10	GetTypeAsEnum	519
25.183.4.10	GetUnpackBuffer	519
25.183.4.10	GetUnpackBuffer	519
25.183.4.10	GetUnpackBufferLength	519
25.183.4.10	GrabOverlayFromPixelData	519
25.183.4.20	Empty	519
25.183.4.21	InPixelData	519
25.183.4.21	InPixelData	519
25.183.4.21	Zero	519
25.183.4.24	Print	520
25.183.4.25	SetBitPosition	520
25.183.4.26	SetBitsAllocated	520
25.183.4.27	SetColumns	520
25.183.4.28	SetDescription	520
25.183.4.29	SetFrameOrigin	520
25.183.4.30	SetGroup	520
25.183.4.30	SetNumberOfFrames	520
25.183.4.30	SetOrigin	520
25.183.4.30	SetOverlay	520
25.183.4.30	SetRows	520
25.183.4.30	SetType	521
25.183.4.30	Update	521
25.184	dcm::ParseException Class Reference	521
25.184.1	Detailed Description	522
25.184.2	Constructor & Destructor Documentation	522
25.184.2.1	ParseException	522
25.184.2.2	~ParseException	522
25.184.3	Member Function Documentation	522

25.184.3.1	GetLastElement	522
25.184.3.2	operator=	522
25.184.3.3	SetLastElement	523
25.185	dcm::Parser Class Reference	523
25.185.1	Detailed Description	524
25.185.2	Member Typedef Documentation	524
25.185.2.1	EndElementHandler	524
25.185.2.2	StartElementHandler	524
25.185.3	Member Enumeration Documentation	524
25.185.3.1	ErrorType	524
25.185.4	Constructor & Destructor Documentation	524
25.185.4.1	Parser	524
25.185.4.2	~Parser	524
25.185.5	Member Function Documentation	524
25.185.5.1	GetBuffer	524
25.185.5.2	GetCurrentByteIndex	524
25.185.5.3	GetErrorCode	524
25.185.5.4	GetErrorString	524
25.185.5.5	GetUserData	524
25.185.5.6	Parse	525
25.185.5.7	ParseBuffer	525
25.185.5.8	Process	525
25.185.5.9	SetElementHandler	525
25.185.5.10	SetUserData	525
25.186	dcm::Patient Class Reference	525
25.186.1	Detailed Description	525
25.186.2	Constructor & Destructor Documentation	525
25.186.2.1	Patient	525
25.187	dcm::network::PDataTFPDU Class Reference	525
25.187.1	Detailed Description	527
25.187.2	Member Typedef Documentation	527
25.187.2.1	SizeType	527
25.187.3	Constructor & Destructor Documentation	527
25.187.3.1	PDataTFPDU	527
25.187.4	Member Function Documentation	527
25.187.4.1	AddPresentationDataValue	527
25.187.4.2	GetNumberOfPresentationDataValues	527

25.187.4.3	GetPresentationDataValue	527
25.187.4.4	IsLastFragment	527
25.187.4.5	Print	527
25.187.4.6	Read	527
25.187.4.7	ReadInto	527
25.187.4.8	Size	527
25.187.4.9	Write	527
25.188	dcm::PDBElement Class Reference	528
25.188.1	Detailed Description	529
25.188.2	Constructor & Destructor Documentation	529
25.188.2.1	PDBElement	529
25.188.3	Member Function Documentation	529
25.188.3.1	GetName	529
25.188.3.2	GetValue	529
25.188.3.3	operator==	529
25.188.3.4	SetName	529
25.188.3.5	SetValue	529
25.188.4	Friends And Related Function Documentation	529
25.188.4.1	operator<<	529
25.188.5	Member Data Documentation	529
25.188.5.1	NameField	529
25.188.5.2	ValueField	529
25.189	dcm::PDBHeader Class Reference	530
25.189.1	Detailed Description	530
25.189.2	Constructor & Destructor Documentation	531
25.189.2.1	PDBHeader	531
25.189.2.2	~PDBHeader	531
25.189.3	Member Function Documentation	531
25.189.3.1	FindPDBElementByName	531
25.189.3.2	GetPDBEEnd	531
25.189.3.3	GetPDBElementByName	531
25.189.3.4	GetPDBInfoTag	531
25.189.3.5	LoadFromDataElement	531
25.189.3.6	Print	531
25.189.4	Friends And Related Function Documentation	531
25.189.4.1	operator<<	531
25.190	dcm::PDFCodec Class Reference	532

25.190.1	Detailed Description	533
25.190.2	Constructor & Destructor Documentation	533
25.190.2.1	PDFCodec	533
25.190.2.2	PDFCodec	533
25.190.3	Member Function Documentation	533
25.190.3.1	CanCode	533
25.190.3.2	CanDecode	533
25.190.3.3	Decode	533
25.190	gdcmm::network::PDUFactory Class Reference	533
25.191.1	Detailed Description	534
25.191.2	Member Function Documentation	534
25.191.2.1	ConstructAbortPDU	534
25.191.2.2	ConstructPDU	534
25.191.2.3	ConstructReleasePDU	534
25.191.2.4	CreateCEchoPDU	534
25.191.2.5	CreateCFindPDU	534
25.191.2.6	CreateCMovePDU	534
25.191.2.7	CreateCStoreRQPDU	534
25.191.2.8	CreateCStoreRSPPDU	534
25.191.2.9	DetermineEventByPDU	534
25.191.2.10	GetPDVs	534
25.190	gdcmm::PersonName Class Reference	535
25.192.1	Detailed Description	535
25.192.2	Member Function Documentation	535
25.192.2.1	GetMaxLength	535
25.192.2.2	GetNumberOfComponents	535
25.192.2.3	Print	535
25.192.2.4	SetBlob	535
25.192.2.5	SetComponents	535
25.192.2.6	SetComponents	535
25.192.3	Member Data Documentation	535
25.192.3.1	Component	536
25.192.3.2	MaxLength	536
25.192.3.3	MaxNumberOfComponents	536
25.192.3.4	Padding	536
25.192.3.5	Separator	536
25.190	gdcmm::PGXCodec Class Reference	536

25.193.1Detailed Description	537
25.193.2Constructor & Destructor Documentation	537
25.193.2.1PGXCodec	537
25.193.2.2~PGXCodec	537
25.193.3Member Function Documentation	537
25.193.3.1CanCode	537
25.193.3.2CanDecode	537
25.193.3.3GetHeaderInfo	538
25.193.3.4Read	538
25.193.3.5Write	538
25.194dcm::PhotometricInterpretation Class Reference	538
25.194.1Detailed Description	539
25.194.2Member Enumeration Documentation	539
25.194.2.1PIType	539
25.194.3Constructor & Destructor Documentation	539
25.194.3.1PhotometricInterpretation	539
25.194.4Member Function Documentation	539
25.194.4.1GetPIString	539
25.194.4.2GetPIType	540
25.194.4.3GetSamplesPerPixel	540
25.194.4.4GetString	540
25.194.4.5GetType	540
25.194.4.6IsLossless	540
25.194.4.7IsLossy	540
25.194.4.8IsRetired	540
25.194.4.9IsSameColorSpace	540
25.194.4.10operator PIType	540
25.194.5Friends And Related Function Documentation	540
25.194.5.1operator<<	540
25.195dcm::PixelFormat Class Reference	540
25.195.1Detailed Description	542
25.195.2Member Enumeration Documentation	542
25.195.2.1ScalarType	542
25.195.3Constructor & Destructor Documentation	542
25.195.3.1PixelFormat	542
25.195.3.2PixelFormat	542
25.195.3.3~PixelFormat	542

25.195.4	Member Function Documentation	542
25.195.4.1	GetBitsAllocated	543
25.195.4.2	GetBitsStored	543
25.195.4.3	GetHighBit	543
25.195.4.4	GetMax	543
25.195.4.5	GetMin	543
25.195.4.6	GetPixelRepresentation	543
25.195.4.7	GetPixelSize	543
25.195.4.8	GetSamplesPerPixel	544
25.195.4.9	GetScalarType	544
25.195.4.10	GetScalarTypeAsString	544
25.195.4.11	IsValid	544
25.195.4.12	operator ScalarType	544
25.195.4.13	operator!=	544
25.195.4.14	operator!=	544
25.195.4.15	operator==	544
25.195.4.16	operator==	544
25.195.4.17	Print	544
25.195.4.18	SetBitsAllocated	544
25.195.4.19	SetBitsStored	544
25.195.4.20	SetHighBit	544
25.195.4.21	SetPixelRepresentation	544
25.195.4.22	SetSamplesPerPixel	544
25.195.4.23	SetScalarType	545
25.195.4.24	Validate	545
25.195.5	Friends And Related Function Documentation	545
25.195.5.1	Bitmap	545
25.195.5.2	operator<<	545
25.196	dcm::Pixmap Class Reference	545
25.196.1	Detailed Description	547
25.196.2	Constructor & Destructor Documentation	547
25.196.2.1	Pixmap	547
25.196.2.2	~Pixmap	547
25.196.3	Member Function Documentation	547
25.196.3.1	AreOverlaysInPixelData	547
25.196.3.2	GetCurve	547
25.196.3.3	GetCurve	548

25.196.3.4	GetIconImage	548
25.196.3.5	GetIconImage	548
25.196.3.6	GetNumberOfCurves	548
25.196.3.7	GetNumberOfOverlays	548
25.196.3.8	GetOverlay	548
25.196.3.9	GetOverlay	548
25.196.3.10	Print	548
25.196.3.11	RemoveOverlay	548
25.196.3.12	SetIconImage	548
25.196.3.13	SetNumberOfCurves	548
25.196.3.14	SetNumberOfOverlays	548
25.196.4	Member Data Documentation	548
25.196.4.1	Curves	548
25.196.4.2	Icon	548
25.196.4.3	Overlays	548
25.197	dcm::PixmapReader Class Reference	548
25.197.1	Detailed Description	551
25.197.2	Constructor & Destructor Documentation	551
25.197.2.1	PixmapReader	551
25.197.2.2	~PixmapReader	551
25.197.3	Member Function Documentation	551
25.197.3.1	GetPixmap	551
25.197.3.2	GetPixmap	551
25.197.3.3	Read	551
25.197.3.4	ReadACRNEMAIImage	551
25.197.3.5	ReadImage	551
25.197.3.6	ReadImageInternal	552
25.197.4	Member Data Documentation	552
25.197.4.1	PixelData	552
25.198	dcm::PixmapToPixmapFilter Class Reference	552
25.198.1	Detailed Description	553
25.198.2	Constructor & Destructor Documentation	553
25.198.2.1	PixmapToPixmapFilter	553
25.198.2.2	~PixmapToPixmapFilter	554
25.198.3	Member Function Documentation	554
25.198.3.1	GetInput	554
25.198.3.2	GetOutput	554

25.198.3.3GetOutputAsPixmap	554
25.199dcm::PixmapWriter Class Reference	554
25.199.1Detailed Description	556
25.199.2Constructor & Destructor Documentation	556
25.199.2.1PixmapWriter	556
25.199.2.2~PixmapWriter	556
25.199.3Member Function Documentation	556
25.199.3.1DolconImage	556
25.199.3.2GetImage	556
25.199.3.3GetImage	556
25.199.3.4GetPixmap	556
25.199.3.5GetPixmap	556
25.199.3.6PrepareWrite	556
25.199.3.7SetImage	557
25.199.3.8SetPixmap	557
25.199.3.9Write	557
25.199.4Member Data Documentation	557
25.199.4.1PixelData	557
25.200dcm::PNMCodec Class Reference	557
25.200.1Detailed Description	559
25.200.2Constructor & Destructor Documentation	559
25.200.2.1PNMCodec	559
25.200.2.2~PNMCodec	559
25.200.3Member Function Documentation	559
25.200.3.1CanCode	559
25.200.3.2CanDecode	559
25.200.3.3GetBufferLength	559
25.200.3.4GetHeaderInfo	559
25.200.3.5Read	559
25.200.3.6SetBufferLength	559
25.200.3.7Write	559
25.201dcm::Preamble Class Reference	560
25.201.1Detailed Description	560
25.201.2Constructor & Destructor Documentation	560
25.201.2.1Preamble	560
25.201.2.2~Preamble	560
25.201.2.3Preamble	560

25.201.3	Member Function Documentation	560
25.201.3.1	Clear	561
25.201.3.2	Create	561
25.201.3.3	GetInternal	561
25.201.3.4	GetLength	561
25.201.3.5	IsEmpty	561
25.201.3.6	IsValid	561
25.201.3.7	operator=	561
25.201.3.8	Print	561
25.201.3.9	Read	561
25.201.3.10	Remove	561
25.201.3.11	Valid	561
25.201.3.12	Write	561
25.201.4	Friends And Related Function Documentation	561
25.201.4.1	operator<<	561
25.202	gdcmm::PresentationContext Class Reference	561
25.202.1	Detailed Description	562
25.202.2	Member Typedef Documentation	562
25.202.2.1	SizeType	562
25.202.2.2	TransferSyntaxArrayType	562
25.202.3	Constructor & Destructor Documentation	562
25.202.3.1	PresentationContext	562
25.202.3.2	PresentationContext	562
25.202.4	Member Function Documentation	562
25.202.4.1	AddTransferSyntax	562
25.202.4.2	GetAbstractSyntax	562
25.202.4.3	GetNumberOfTransferSyntaxes	562
25.202.4.4	GetPresentationContextID	562
25.202.4.5	GetTransferSyntax	562
25.202.4.6	operator==	562
25.202.4.7	Print	562
25.202.4.8	SetAbstractSyntax	562
25.202.4.9	SetPresentationContextID	563
25.203	gdcmm::network::PresentationContextAC Class Reference	563
25.203.1	Detailed Description	563
25.203.2	Constructor & Destructor Documentation	563
25.203.2.1	PresentationContextAC	563

25.203.3	Member Function Documentation	563
25.203.3.1	GetPresentationContextID	563
25.203.3.2	GetReason	563
25.203.3.3	GetTransferSyntax	563
25.203.3.4	Print	563
25.203.3.5	Read	563
25.203.3.6	SetPresentationContextID	564
25.203.3.7	SetReason	564
25.203.3.8	SetTransferSyntax	564
25.203.3.9	Size	564
25.203.3.10	Write	564
25.204	dcm::PresentationContextGenerator Class Reference	564
25.204.1	Detailed Description	565
25.204.2	Member Typedef Documentation	565
25.204.2.1	PresentationContextArrayType	565
25.204.2.2	SizeType	565
25.204.3	Constructor & Destructor Documentation	565
25.204.3.1	PresentationContextGenerator	565
25.204.4	Member Function Documentation	565
25.204.4.1	AddPresentationContext	565
25.204.4.2	GenerateFromFilenames	565
25.204.4.3	GenerateFromUID	565
25.204.4.4	GetDefaultTransferSyntax	566
25.204.4.5	GetPresentationContexts	566
25.204.4.6	SetDefaultTransferSyntax	566
25.204.4.7	SetMergeModeToAbstractSyntax	566
25.204.4.8	SetMergeModeToTransferSyntax	566
25.205	dcm::network::PresentationContextRQ Class Reference	566
25.205.1	Detailed Description	567
25.205.2	Member Typedef Documentation	567
25.205.2.1	SizeType	567
25.205.3	Constructor & Destructor Documentation	567
25.205.3.1	PresentationContextRQ	567
25.205.3.2	PresentationContextRQ	567
25.205.3.3	PresentationContextRQ	567
25.205.4	Member Function Documentation	567
25.205.4.1	AddTransferSyntax	567

25.205.4.2GetAbstractSyntax	567
25.205.4.3GetAbstractSyntax	567
25.205.4.4GetNumberOfTransferSyntaxes	567
25.205.4.5GetPresentationContextID	567
25.205.4.6GetTransferSyntax	567
25.205.4.7GetTransferSyntax	567
25.205.4.8GetTransferSyntaxes	567
25.205.4.9operator==	568
25.205.4.10Print	568
25.205.4.11Read	568
25.205.4.12SetAbstractSyntax	568
25.205.4.13SetPresentationContextID	568
25.205.4.14Size	568
25.205.4.15Write	568
25.206dcm::network::PresentationDataValue Class Reference	568
25.206.1Detailed Description	569
25.206.2Constructor & Destructor Documentation	569
25.206.2.1PresentationDataValue	569
25.206.3Member Function Documentation	569
25.206.3.1ConcatenatePDVBlobs	569
25.206.3.2GetBlob	569
25.206.3.3GetIsCommand	569
25.206.3.4GetIsLastFragment	569
25.206.3.5GetMessageHeader	569
25.206.3.6GetPresentationContextID	569
25.206.3.7Print	569
25.206.3.8Read	569
25.206.3.9ReadInto	569
25.206.3.10SetBlob	569
25.206.3.11SetCommand	569
25.206.3.12DataSet	569
25.206.3.13SetLastFragment	569
25.206.3.14SetMessageHeader	569
25.206.3.15SetPresentationContextID	570
25.206.3.16Size	570
25.206.3.17Write	570
25.207dcm::Printer Class Reference	570

25.207.1Detailed Description	572
25.207.2Member Enumeration Documentation	572
25.207.2.1PrintStyles	572
25.207.3Constructor & Destructor Documentation	572
25.207.3.1Printer	572
25.207.3.2~Printer	572
25.207.4Member Function Documentation	572
25.207.4.1GetPrintStyle	572
25.207.4.2Print	572
25.207.4.3PrintDataElement	572
25.207.4.4PrintDataSet	572
25.207.4.5PrintSQ	573
25.207.4.6SetColor	573
25.207.4.7SetFile	573
25.207.4.8SetStyle	573
25.207.5Member Data Documentation	573
25.207.5.1F	573
25.207.5.2MaxPrintLength	573
25.207.5.3PrintStyle	573
25.208dcm::PrivateDict Class Reference	573
25.208.1Detailed Description	574
25.208.2Constructor & Destructor Documentation	574
25.208.2.1PrivateDict	574
25.208.2.2~PrivateDict	574
25.208.3Member Function Documentation	574
25.208.3.1AddDictEntry	574
25.208.3.2FindDictEntry	574
25.208.3.3GetDictEntry	574
25.208.3.4IsEmpty	574
25.208.3.5LoadDefault	574
25.208.3.6PrintXML	574
25.208.3.7RemoveDictEntry	574
25.208.4Friends And Related Function Documentation	574
25.208.4.1Dicts	574
25.208.4.2operator<<	574
25.209dcm::PrivateTag Class Reference	575
25.209.1Detailed Description	576

25.209.2	Constructor & Destructor Documentation	576
25.209.2.1	PrivateTag	576
25.209.3	Member Function Documentation	576
25.209.3.1	GetOwner	576
25.209.3.2	operator<	576
25.209.3.3	ReadFromCommaSeparatedString	576
25.209.3.4	SetOwner	576
25.209.4	Friends And Related Function Documentation	576
25.209.4.1	operator<<	576
25.210	dcm::ProgressEvent Class Reference	576
25.210.1	Detailed Description	578
25.210.2	Member Typedef Documentation	578
25.210.2.1	Self	578
25.210.2.2	Superclass	578
25.210.3	Constructor & Destructor Documentation	578
25.210.3.1	ProgressEvent	578
25.210.3.2	~ProgressEvent	578
25.210.3.3	ProgressEvent	578
25.210.4	Member Function Documentation	578
25.210.4.1	CheckEvent	578
25.210.4.2	GetEventName	578
25.210.4.3	GetProgress	578
25.210.4.4	MakeObject	578
25.210.4.5	SetProgress	578
25.211	dcm::PVRGCodec Class Reference	579
25.211.1	Detailed Description	580
25.211.2	Constructor & Destructor Documentation	580
25.211.2.1	PVRGCodec	580
25.211.2.2	~PVRGCodec	580
25.211.3	Member Function Documentation	580
25.211.3.1	CanCode	580
25.211.3.2	CanDecode	580
25.211.3.3	Code	580
25.211.3.4	Decode	581
25.212	dcm::PythonFilter Class Reference	581
25.212.1	Detailed Description	581
25.212.2	Constructor & Destructor Documentation	581

25.212.2.1PythonFilter	581
25.212.2.2~PythonFilter	581
25.212.3Member Function Documentation	581
25.212.3.1GetFile	581
25.212.3.2GetFile	581
25.212.3.3SetDicts	581
25.212.3.4SetFile	581
25.212.3.5ToPyObject	581
25.212.3.6UseDictAlways	582
25.213dcm::QueryBase Class Reference	582
25.213.1Detailed Description	582
25.213.2Constructor & Destructor Documentation	583
25.213.2.1~QueryBase	583
25.213.3Member Function Documentation	583
25.213.3.1GetAllRequiredTags	583
25.213.3.2GetAllTags	583
25.213.3.3GetHierachicalSearchTags	583
25.213.3.4GetName	583
25.213.3.5GetOptionalTags	583
25.213.3.6GetQueryLevel	583
25.213.3.7GetRequiredTags	583
25.213.3.8GetUniqueTags	584
25.214dcm::QueryFactory Class Reference	584
25.214.1Detailed Description	584
25.214.2Member Function Documentation	584
25.214.2.1GetCharacterFromCurrentLocale	584
25.214.2.2ListCharSets	584
25.214.2.3ProduceCharacterSetDataElement	585
25.214.2.4ProduceQuery	585
25.215dcm::QueryImage Class Reference	585
25.215.1Detailed Description	586
25.215.2Member Function Documentation	586
25.215.2.1GetHierachicalSearchTags	586
25.215.2.2GetName	586
25.215.2.3GetOptionalTags	586
25.215.2.4GetQueryLevel	587
25.215.2.5GetRequiredTags	587

25.215.2.6GetUniqueTags	587
25.216dcm::QueryPatient Class Reference	587
25.216.1Detailed Description	588
25.216.2Member Function Documentation	588
25.216.2.1GetHierachicalSearchTags	588
25.216.2.2GetName	588
25.216.2.3GetOptionalTags	588
25.216.2.4GetQueryLevel	589
25.216.2.5GetRequiredTags	589
25.216.2.6GetUniqueTags	589
25.217dcm::QuerySeries Class Reference	589
25.217.1Detailed Description	590
25.217.2Member Function Documentation	590
25.217.2.1GetHierachicalSearchTags	590
25.217.2.2GetName	590
25.217.2.3GetOptionalTags	590
25.217.2.4GetQueryLevel	591
25.217.2.5GetRequiredTags	591
25.217.2.6GetUniqueTags	591
25.218dcm::QueryStudy Class Reference	591
25.218.1Detailed Description	592
25.218.2Member Function Documentation	592
25.218.2.1GetHierachicalSearchTags	592
25.218.2.2GetName	592
25.218.2.3GetOptionalTags	592
25.218.2.4GetQueryLevel	593
25.218.2.5GetRequiredTags	593
25.218.2.6GetUniqueTags	593
25.219dcm::RAWCodec Class Reference	593
25.219.1Detailed Description	594
25.219.2Constructor & Destructor Documentation	594
25.219.2.1RAWCodec	594
25.219.2.2~RAWCodec	594
25.219.3Member Function Documentation	594
25.219.3.1CanCode	594
25.219.3.2CanDecode	595
25.219.3.3Code	595

25.219.3.4	Decode	595
25.219.3.5	DecodeByStreams	595
25.219.3.6	DecodeBytes	595
25.219.3.7	GetHeaderInfo	595
25.220	dcm::Reader Class Reference	595
25.220.1	Detailed Description	597
25.220.2	Constructor & Destructor Documentation	598
25.220.2.1	Reader	598
25.220.2.2	~Reader	598
25.220.3	Member Function Documentation	598
25.220.3.1	CanRead	598
25.220.3.2	GetFile	598
25.220.3.3	GetFile	599
25.220.3.4	GetStreamPtr	599
25.220.3.5	Read	599
25.220.3.6	ReadDataSet	599
25.220.3.7	ReadMetaInformation	599
25.220.3.8	ReadPreamble	599
25.220.3.9	ReadSelectedTags	599
25.220.3.10	ReadUpToTag	599
25.220.3.11	SetFile	599
25.220.3.12	SetFileName	599
25.220.3.13	SetStream	600
25.220.4	Friends And Related Function Documentation	600
25.220.4.1	StreamImageReader	600
25.220.5	Member Data Documentation	600
25.220.5.1	F	600
25.221	dcm::Region Class Reference	600
25.221.1	Detailed Description	601
25.221.2	Constructor & Destructor Documentation	601
25.221.2.1	Region	601
25.221.2.2	~Region	601
25.221.3	Member Function Documentation	601
25.221.3.1	Area	601
25.221.3.2	Clone	602
25.221.3.3	ComputeBoundingBox	602
25.221.3.4	Empty	602

25.221.3.5IsValid	602
25.221.3.6Print	602
25.222dcm::Rescaler Class Reference	602
25.222.1Detailed Description	603
25.222.2Constructor & Destructor Documentation	604
25.222.2.1Rescaler	604
25.222.2.2~Rescaler	604
25.222.3Member Function Documentation	604
25.222.3.1ComputeInterceptSlopePixelType	604
25.222.3.2ComputePixelTypeFromMinMax	604
25.222.3.3GetIntercept	604
25.222.3.4GetSlope	604
25.222.3.5InverseRescale	604
25.222.3.6InverseRescaleFunctionIntoBestFit	604
25.222.3.7Rescale	604
25.222.3.8RescaleFunctionIntoBestFit	604
25.222.3.9SetIntercept	604
25.222.3.10SetMinMaxForPixelType	604
25.222.3.11SetPixelFormat	605
25.222.3.12SetSlope	605
25.222.3.13SetTargetPixelType	605
25.222.3.14SetUseTargetPixelType	605
25.223dcm::RLECodec Class Reference	605
25.223.1Detailed Description	607
25.223.2Constructor & Destructor Documentation	607
25.223.2.1RLECodec	607
25.223.2.2~RLECodec	607
25.223.3Member Function Documentation	607
25.223.3.1CanCode	607
25.223.3.2CanDecode	607
25.223.3.3Code	608
25.223.3.4Decode	608
25.223.3.5DecodeByStreams	608
25.223.3.6DecodeExtent	608
25.223.3.7GetBufferLength	608
25.223.3.8GetHeaderInfo	608
25.223.3.9SetBufferLength	608

25.223.3.1	SetLength	608
25.223.4	Friends And Related Function Documentation	608
25.223.4.1	ImageRegionReader	608
25.224	dcm::network::RoleSelectionSub Class Reference	608
25.224.1	Detailed Description	609
25.224.2	Constructor & Destructor Documentation	609
25.224.2.1	RoleSelectionSub	609
25.224.3	Member Function Documentation	609
25.224.3.1	Print	609
25.224.3.2	Read	609
25.224.3.3	SetTuple	609
25.224.3.4	Size	609
25.224.3.5	Write	609
25.225	dcm::SerieHelper::Rule Struct Reference	609
25.225.1	Member Data Documentation	610
25.225.1.1	elem	610
25.225.1.2	group	610
25.225.1.3	op	610
25.225.1.4	value	610
25.226	dcm::Scanner Class Reference	610
25.226.1	Detailed Description	613
25.226.2	Member Typedef Documentation	613
25.226.2.1	ConstIterator	613
25.226.2.2	MappingType	613
25.226.2.3	TagToValue	613
25.226.2.4	TagToValueValueType	614
25.226.2.5	ValuesType	614
25.226.3	Constructor & Destructor Documentation	614
25.226.3.1	Scanner	614
25.226.3.2	~Scanner	614
25.226.4	Member Function Documentation	614
25.226.4.1	AddPrivateTag	614
25.226.4.2	AddSkipTag	614
25.226.4.3	AddTag	614
25.226.4.4	Begin	614
25.226.4.5	ClearSkipTags	614
25.226.4.6	ClearTags	614

25.226.4.7End	614
25.226.4.8GetAllFileNamesFromTagToValue	614
25.226.4.9GetFilenameFromTagToValue	614
25.226.4.10GetFileNames	614
25.226.4.11GetKeys	614
25.226.4.12GetMapping	615
25.226.4.13GetMappingFromTagToValue	615
25.226.4.14GetMappings	615
25.226.4.15GetOrderedValues	615
25.226.4.16GetValue	615
25.226.4.17GetValues	615
25.226.4.18GetValues	615
25.226.4.19Key	616
25.226.4.20New	616
25.226.4.21Print	616
25.226.4.22ProcessPublicTag	616
25.226.4.23Scan	616
25.226.5Friends And Related Function Documentation	616
25.226.5.1operator<<	616
25.227gdcmm::Segment Class Reference	616
25.227.1Detailed Description	618
25.227.2Member Typedef Documentation	619
25.227.2.1SurfaceVector	619
25.227.3Member Enumeration Documentation	619
25.227.3.1ALGOType	619
25.227.4Constructor & Destructor Documentation	619
25.227.4.1Segment	619
25.227.4.2~Segment	619
25.227.5Member Function Documentation	619
25.227.5.1AddSurface	619
25.227.5.2GetALGOType	619
25.227.5.3GetALGOTypeString	619
25.227.5.4GetAnatomicRegion	619
25.227.5.5GetAnatomicRegion	619
25.227.5.6GetPropertyCategory	619
25.227.5.7GetPropertyCategory	619
25.227.5.8GetPropertyType	619

25.227.5.9	GetPropertyType	619
25.227.5.10	GetSegmentAlgorithmName	619
25.227.5.11	GetSegmentAlgorithmType	619
25.227.5.12	GetSegmentDescription	619
25.227.5.13	GetSegmentLabel	619
25.227.5.14	GetSegmentNumber	619
25.227.5.15	GetSurface	619
25.227.5.16	GetSurfaceCount	620
25.227.5.17	GetSurfaces	620
25.227.5.18	GetSurfaces	620
25.227.5.19	SetAnatomicRegion	620
25.227.5.20	SetPropertyCategory	620
25.227.5.21	SetPropertyType	620
25.227.5.22	SetSegmentAlgorithmName	620
25.227.5.23	SetSegmentAlgorithmType	620
25.227.5.24	SetSegmentAlgorithmType	620
25.227.5.25	SetSegmentDescription	620
25.227.5.26	SetSegmentLabel	620
25.227.5.27	SetSegmentNumber	620
25.227.5.28	SetSurfaceCount	620
25.227.6	Member Data Documentation	620
25.227.6.1	AnatomicRegion	620
25.227.6.2	PropertyCategory	620
25.227.6.3	PropertyType	620
25.227.6.4	SegmentAlgorithmName	620
25.227.6.5	SegmentAlgorithmType	620
25.227.6.6	SegmentDescription	620
25.227.6.7	SegmentLabel	620
25.227.6.8	SegmentNumber	620
25.227.6.9	SurfaceCount	620
25.227.6.10	Surfaces	620
25.228	dcm::SegmentedPaletteColorLookupTable Class Reference	621
25.228.1	Detailed Description	622
25.228.2	Constructor & Destructor Documentation	622
25.228.2.1	SegmentedPaletteColorLookupTable	622
25.228.2.2	~SegmentedPaletteColorLookupTable	622
25.228.3	Member Function Documentation	622

25.228.3.1Print	622
25.228.3.2SetLUT	622
25.229dcm::SegmentReader Class Reference	622
25.229.1Detailed Description	624
25.229.2Member Typedef Documentation	624
25.229.2.1SegmentMap	624
25.229.2.2SegmentVector	624
25.229.3Constructor & Destructor Documentation	624
25.229.3.1SegmentReader	624
25.229.3.2~SegmentReader	624
25.229.4Member Function Documentation	624
25.229.4.1GetSegments	624
25.229.4.2GetSegments	625
25.229.4.3Read	625
25.229.4.4ReadSegment	625
25.229.4.5ReadSegments	625
25.229.5Member Data Documentation	625
25.229.5.1Segments	625
25.230dcm::SegmentWriter Class Reference	625
25.230.1Detailed Description	626
25.230.2Member Typedef Documentation	627
25.230.2.1SegmentVector	627
25.230.3Constructor & Destructor Documentation	627
25.230.3.1SegmentWriter	627
25.230.3.2~SegmentWriter	627
25.230.4Member Function Documentation	627
25.230.4.1AddSegment	627
25.230.4.2GetNumberOfSegments	627
25.230.4.3GetSegment	627
25.230.4.4GetSegments	627
25.230.4.5GetSegments	627
25.230.4.6PrepareWrite	627
25.230.4.7SetNumberOfSegments	627
25.230.4.8SetSegments	627
25.230.4.9Write	627
25.230.5Member Data Documentation	627
25.230.5.1Segments	627

25.231.0 dcm::SequenceOfFragments Class Reference	627
25.231.1 Detailed Description	629
25.231.2 Member Typedef Documentation	630
25.231.2.1 ConstIterator	630
25.231.2.2 FragmentVector	630
25.231.2.3 Iterator	630
25.231.2.4 SizeType	630
25.231.3 Constructor & Destructor Documentation	630
25.231.3.1 SequenceOfFragments	630
25.231.4 Member Function Documentation	630
25.231.4.1 AddFragment	630
25.231.4.2 Begin	630
25.231.4.3 Begin	630
25.231.4.4 Clear	630
25.231.4.5 ComputeByteLength	630
25.231.4.6 ComputeLength	630
25.231.4.7 End	630
25.231.4.8 End	630
25.231.4.9 GetBuffer	630
25.231.4.10 GetFragBuffer	630
25.231.4.11 GetFragment	631
25.231.4.12 GetLength	631
25.231.4.13 GetNumberOfFragments	631
25.231.4.14 GetTable	631
25.231.4.15 GetTable	631
25.231.4.16 New	631
25.231.4.17 operator==	631
25.231.4.18 Print	631
25.231.4.19 Read	631
25.231.4.20 ReadPreValue	631
25.231.4.21 ReadValue	631
25.231.4.22 SetLength	632
25.231.4.23 Write	632
25.231.4.24 WriteBuffer	632
25.232.0 dcm::SequenceOfItems Class Reference	632
25.232.1 Detailed Description	634
25.232.2 Member Typedef Documentation	635

25.232.2.1ConstIterator	635
25.232.2.2ItemVector	635
25.232.2.3Iterator	635
25.232.2.4SizeType	635
25.232.3Constructor & Destructor Documentation	635
25.232.3.1SequenceOfItems	635
25.232.4Member Function Documentation	635
25.232.4.1AddItem	635
25.232.4.2Begin	635
25.232.4.3Begin	635
25.232.4.4Clear	635
25.232.4.5ComputeLength	635
25.232.4.6End	635
25.232.4.7End	636
25.232.4.8FindDataElement	636
25.232.4.9GetItem	636
25.232.4.10GetItem	636
25.232.4.11GetLength	636
25.232.4.12GetNumberOfItems	636
25.232.4.13UndefinedLength	636
25.232.4.14New	636
25.232.4.15operator=	636
25.232.4.16operator==	636
25.232.4.17Print	636
25.232.4.18Read	637
25.232.4.19SetLength	637
25.232.4.20SetLengthToUndefined	637
25.232.4.21SetNumberOfItems	637
25.232.4.22Write	637
25.232.5Member Data Documentation	637
25.232.5.1Items	637
25.232.5.2SequenceLengthField	637
25.233gdcmm::SerieHelper Class Reference	638
25.233.1Detailed Description	639
25.233.2Member Typedef Documentation	639
25.233.2.1SerieRestrictions	639
25.233.2.2SingleSerieUIDFileSetmap	639

25.233.3	Constructor & Destructor Documentation	639
25.233.3.1	SerieHelper	639
25.233.3.2	~SerieHelper	639
25.233.4	Member Function Documentation	639
25.233.4.1	AddFile	639
25.233.4.2	AddFileName	640
25.233.4.3	AddRestriction	640
25.233.4.4	AddRestriction	640
25.233.4.5	AddRestriction	640
25.233.4.6	Clear	640
25.233.4.7	CreateDefaultUniqueSeriesIdentifier	640
25.233.4.8	CreateUniqueSeriesIdentifier	640
25.233.4.9	FileNameOrdering	640
25.233.4.10	GetFirstSingleSerieUIDFileSet	640
25.233.4.11	GetNextSingleSerieUIDFileSet	640
25.233.4.12	ImagePositionPatientOrdering	640
25.233.4.13	OrderFileList	640
25.233.4.14	SetDirectory	640
25.233.4.15	SetLoadMode	640
25.233.4.16	SetUseSeriesDetails	640
25.233.4.17	UserOrdering	640
25.233.5	Member Data Documentation	640
25.233.5.1	ItFileSetHt	640
25.233.5.2	SingleSerieUIDFileSetHT	640
25.234	dcm::Series Class Reference	640
25.234.1	Detailed Description	641
25.234.2	Constructor & Destructor Documentation	641
25.234.2.1	Series	641
25.235	dcm::network::ServiceClassApplicationInformation Class Reference	641
25.235.1	Detailed Description	641
25.235.2	Constructor & Destructor Documentation	641
25.235.2.1	ServiceClassApplicationInformation	641
25.235.3	Member Function Documentation	641
25.235.3.1	Print	641
25.235.3.2	Read	641
25.235.3.3	SetTuple	641
25.235.3.4	Size	641

25.235.3.5Write	641
25.236dcm::ServiceClassUser Class Reference	642
25.236.1Detailed Description	643
25.236.2Constructor & Destructor Documentation	644
25.236.2.1ServiceClassUser	644
25.236.2.2~ServiceClassUser	644
25.236.3Member Function Documentation	644
25.236.3.1GetAETitle	644
25.236.3.2GetCalledAETitle	644
25.236.3.3GetTimeout	644
25.236.3.4InitializeConnection	644
25.236.3.5IsPresentationContextAccepted	644
25.236.3.6SendEcho	644
25.236.3.7SendFind	644
25.236.3.8SendMove	644
25.236.3.9SendMove	644
25.236.3.10SendMove	645
25.236.3.11SendStore	645
25.236.3.12SendStore	645
25.236.3.13SendStore	645
25.236.3.14SetAETitle	645
25.236.3.15SetCalledAETitle	645
25.236.3.16SetHostname	645
25.236.3.17SetPort	645
25.236.3.18SetPortSCP	646
25.236.3.19SetPresentationContexts	646
25.236.3.20SetTimeout	646
25.236.3.21StartAssociation	646
25.236.3.22StopAssociation	646
25.237dcm::SHA1 Class Reference	646
25.237.1Detailed Description	647
25.237.2Constructor & Destructor Documentation	647
25.237.2.1SHA1	647
25.237.2.2~SHA1	647
25.237.3Member Function Documentation	647
25.237.3.1Compute	647
25.237.3.2ComputeFile	647

25.238	dcm::SimpleMemberCommand< T > Class Template Reference	647
25.238.1	Detailed Description	649
25.238.2	Member Typedef Documentation	649
25.238.2.1	Self	649
25.238.2.2	MemberFunctionPointer	649
25.238.3	Constructor & Destructor Documentation	650
25.238.3.1	SimpleMemberCommand	650
25.238.3.2	~SimpleMemberCommand	650
25.238.4	Member Function Documentation	650
25.238.4.1	Execute	650
25.238.4.2	Execute	650
25.238.4.3	New	650
25.238.4.4	SetCallbackFunction	650
25.238.5	Member Data Documentation	650
25.238.5.1	m_MemberFunction	650
25.238.5.2	m_This	651
25.239	dcm::SimpleSubjectWatcher Class Reference	651
25.239.1	Detailed Description	651
25.239.2	Constructor & Destructor Documentation	651
25.239.2.1	SimpleSubjectWatcher	651
25.239.2.2	~SimpleSubjectWatcher	651
25.239.3	Member Function Documentation	651
25.239.3.1	EndFilter	651
25.239.3.2	ShowAbort	651
25.239.3.3	ShowAnonymization	652
25.239.3.4	ShowData	652
25.239.3.5	ShowDataSet	652
25.239.3.6	ShowIteration	652
25.239.3.7	ShowProgress	652
25.239.3.8	StartFilter	652
25.239.3.9	TestAbortOff	652
25.239.3.10	TestAbortOn	652
25.240	dcm::SmartPointer< ObjectType > Class Template Reference	652
25.240.1	Detailed Description	654
25.240.2	Constructor & Destructor Documentation	654
25.240.2.1	SmartPointer	654
25.240.2.2	SmartPointer	654

25.240.2.3SmartPointer	654
25.240.2.4SmartPointer	654
25.240.2.5~SmartPointer	654
25.240.3Member Function Documentation	654
25.240.3.1GetPointer	654
25.240.3.2operator ObjectType *	655
25.240.3.3operator*	655
25.240.3.4operator->	655
25.240.3.5operator=	655
25.240.3.6operator=	655
25.240.3.7operator=	655
25.240gdcmm::network::SOPClassExtendedNegociationSub Class Reference	655
25.241.1Detailed Description	656
25.241.2Constructor & Destructor Documentation	656
25.241.2.1SOPClassExtendedNegociationSub	656
25.241.3Member Function Documentation	656
25.241.3.1Print	656
25.241.3.2Read	656
25.241.3.3SetTuple	656
25.241.3.4Size	656
25.241.3.5Write	656
25.240gdcmm::SOPClassUIDToIOD Class Reference	656
25.242.1Detailed Description	657
25.242.2Member Typedef Documentation	657
25.242.2.1const	657
25.242.3Member Function Documentation	657
25.242.3.1GetIOD	657
25.242.3.2GetIODFromSOPClassUID	657
25.242.3.3GetNumberOfSOPClassToIOD	657
25.242.3.4GetSOPClassUIDFromIOD	657
25.242.3.5GetSOPClassUIDToIOD	657
25.242.3.6GetSOPClassUIDToIODs	657
25.240gdcmm::Sorter Class Reference	657
25.243.1Detailed Description	659
25.243.2Member Typedef Documentation	659
25.243.2.1SelectionMap	659
25.243.2.2SortFunction	659

25.243.3	Constructor & Destructor Documentation	660
25.243.3.1	Sorter	660
25.243.3.2	~Sorter	660
25.243.4	Member Function Documentation	660
25.243.4.1	AddSelect	660
25.243.4.2	GetFileNames	660
25.243.4.3	Print	660
25.243.4.4	SetSortFunction	660
25.243.4.5	Sort	660
25.243.4.6	StableSort	660
25.243.5	Friends And Related Function Documentation	661
25.243.5.1	operator<<	661
25.243.6	Member Data Documentation	661
25.243.6.1	FileNames	661
25.243.6.2	Selection	661
25.243.6.3	SortFunc	661
25.244	dcm::Spacing Class Reference	661
25.244.1	Detailed Description	661
25.244.2	Member Enumeration Documentation	662
25.244.2.1	SpacingType	662
25.244.3	Constructor & Destructor Documentation	662
25.244.3.1	Spacing	662
25.244.3.2	~Spacing	662
25.244.4	Member Function Documentation	662
25.244.4.1	ComputePixelAspectRatioFromPixelSpacing	662
25.245	dcm::Spectroscopy Class Reference	663
25.245.1	Detailed Description	663
25.245.2	Constructor & Destructor Documentation	663
25.245.2.1	Spectroscopy	663
25.246	dcm::SplitMosaicFilter Class Reference	663
25.246.1	Detailed Description	664
25.246.2	Constructor & Destructor Documentation	664
25.246.2.1	SplitMosaicFilter	664
25.246.2.2	~SplitMosaicFilter	664
25.246.3	Member Function Documentation	664
25.246.3.1	ComputeMOSAICDimensions	664
25.246.3.2	GetFile	664

25.246.3.3	GetFile	664
25.246.3.4	GetImage	664
25.246.3.5	GetImage	664
25.246.3.6	SetFile	664
25.246.3.7	SetImage	664
25.246.3.8	Split	664
25.247	dcm::StartEvent Class Reference	664
25.248	dcm::static_assert_test< x > Struct Template Reference	666
25.249	dcm::STATIC_ASSERTION_FAILURE< x > Struct Template Reference	666
25.250	dcm::STATIC_ASSERTION_FAILURE< true > Struct Template Reference	666
25.250.1	Member Enumeration Documentation	666
25.250.1.1	anonymous enum	666
25.251	dcm::StreamImageReader Class Reference	666
25.251.1	Detailed Description	667
25.251.2	Constructor & Destructor Documentation	667
25.251.2.1	StreamImageReader	667
25.251.2.2	~StreamImageReader	667
25.251.3	Member Function Documentation	667
25.251.3.1	CanReadImage	667
25.251.3.2	DefinePixelExtent	667
25.251.3.3	DefineProperBufferLength	668
25.251.3.4	GetDimensionsValueForResolution	668
25.251.3.5	GetFile	668
25.251.3.6	Read	668
25.251.3.7	ReadImageInformation	668
25.251.3.8	SetFileName	669
25.251.3.9	SetStream	669
25.252	dcm::StreamImageWriter Class Reference	669
25.252.1	Detailed Description	671
25.252.2	Constructor & Destructor Documentation	671
25.252.2.1	StreamImageWriter	671
25.252.2.2	~StreamImageWriter	671
25.252.3	Member Function Documentation	671
25.252.3.1	CanWriteFile	672
25.252.3.2	DefinePixelExtent	672
25.252.3.3	DefineProperBufferLength	672
25.252.3.4	SetFile	672

25.252.3.5SetFileName	672
25.252.3.6SetStream	672
25.252.3.7Write	673
25.252.3.8WriteImageInformation	673
25.252.3.9WriteImageSubregionRAW	673
25.252.3.10WriteRawHeader	673
25.252.4Member Data Documentation	673
25.252.4.1mElementOffsets	673
25.252.4.2mElementOffsets1	674
25.252.4.3mspFile	674
25.252.4.4mWriter	674
25.252.4.5mXMax	674
25.252.4.6mXMin	674
25.252.4.7mYMax	674
25.252.4.8mYMin	674
25.252.4.9mZMax	674
25.252.4.10mZMin	674
25.253dcm::String< TDelimiter, TMaxLength, TPadChar > Class Template Reference	674
25.253.1Detailed Description	676
25.253.2Member Typedef Documentation	676
25.253.2.1const_iterator	676
25.253.2.2const_reference	676
25.253.2.3const_reverse_iterator	676
25.253.2.4difference_type	676
25.253.2.5iterator	676
25.253.2.6pointer	676
25.253.2.7reference	676
25.253.2.8reverse_iterator	676
25.253.2.9size_type	676
25.253.2.10value_type	677
25.253.3Constructor & Destructor Documentation	677
25.253.3.1String	677
25.253.3.2String	677
25.253.3.3String	677
25.253.3.4String	677
25.253.4Member Function Documentation	677
25.253.4.1IsValid	677

25.253.4.2operator const char *	. 677
25.253.4.3Trim	. 677
25.253.4.4Trim	. 677
25.253.4.5Truncate	. 677
25.254dcm::StringFilter Class Reference	. 678
25.254.1Detailed Description	. 678
25.254.2Constructor & Destructor Documentation	. 678
25.254.2.1StringFilter	. 678
25.254.2.2~StringFilter	. 678
25.254.3Member Function Documentation	. 678
25.254.3.1ExecuteQuery	. 679
25.254.3.2ExecuteQuery	. 679
25.254.3.3FromString	. 679
25.254.3.4FromString	. 679
25.254.3.5GetFile	. 679
25.254.3.6GetFile	. 679
25.254.3.7SetDicts	. 679
25.254.3.8SetFile	. 679
25.254.3.9ToString	. 679
25.254.3.10bStringPair	. 679
25.254.3.11bStringPair	. 680
25.254.3.12UseDictAlways	. 680
25.255dcm::Study Class Reference	. 680
25.255.1Detailed Description	. 680
25.255.2Constructor & Destructor Documentation	. 680
25.255.2.1Study	. 680
25.256dcm::Subject Class Reference	. 680
25.256.1Detailed Description	. 681
25.256.2Constructor & Destructor Documentation	. 682
25.256.2.1Subject	. 682
25.256.2.2~Subject	. 682
25.256.3Member Function Documentation	. 682
25.256.3.1AddObserver	. 682
25.256.3.2AddObserver	. 682
25.256.3.3GetCommand	. 682
25.256.3.4HasObserver	. 682
25.256.3.5InvokeEvent	. 682

25.256.3.6InvokeEvent	682
25.256.3.7RemoveAllObservers	682
25.256.3.8RemoveObserver	682
25.257dcm::Surface Class Reference	683
25.257.1Detailed Description	685
25.257.2Member Enumeration Documentation	686
25.257.2.1STATES	686
25.257.2.2VIEWType	686
25.257.3Constructor & Destructor Documentation	686
25.257.3.1Surface	686
25.257.3.2~Surface	686
25.257.4Member Function Documentation	686
25.257.4.1GetAlgorithmFamily	686
25.257.4.2GetAlgorithmFamily	686
25.257.4.3GetAlgorithmName	686
25.257.4.4GetAlgorithmVersion	686
25.257.4.5GetAxisOfRotation	686
25.257.4.6GetCenterOfRotation	687
25.257.4.7GetFiniteVolume	687
25.257.4.8GetManifold	687
25.257.4.9GetMaximumPointDistance	687
25.257.4.10GetMeanPointDistance	687
25.257.4.11GetMeshPrimitive	687
25.257.4.12GetMeshPrimitive	687
25.257.4.13GetNumberOfSurfacePoints	687
25.257.4.14GetNumberOfVectors	687
25.257.4.15GetPointCoordinatesData	687
25.257.4.16GetPointCoordinatesData	687
25.257.4.17GetPointPositionAccuracy	687
25.257.4.18GetPointsBoundingBoxCoordinates	687
25.257.4.19GetProcessingAlgorithm	687
25.257.4.20GetProcessingAlgorithm	687
25.257.4.21GetRecommendedDisplayCIELabValue	687
25.257.4.22GetRecommendedDisplayCIELabValue	687
25.257.4.23GetRecommendedDisplayGrayscaleValue	687
25.257.4.24GetRecommendedPresentationOpacity	687
25.257.4.25GetRecommendedPresentationType	688

25.257.4.26	GetSTATES	688
25.257.4.27	GetSTATESString	688
25.257.4.28	GetSurfaceComments	688
25.257.4.29	GetSurfaceNumber	688
25.257.4.30	GetSurfaceProcessing	688
25.257.4.31	GetSurfaceProcessingDescription	688
25.257.4.32	GetSurfaceProcessingRatio	688
25.257.4.33	GetVectorAccuracy	688
25.257.4.34	GetVectorCoordinateData	688
25.257.4.35	GetVectorCoordinateData	688
25.257.4.36	GetVectorDimensionality	688
25.257.4.37	GetVIEWType	688
25.257.4.38	GetVIEWTypeString	688
25.257.4.39	GetAlgorithmFamily	688
25.257.4.40	GetAlgorithmName	688
25.257.4.41	GetAlgorithmVersion	688
25.257.4.42	GetAxisOfRotation	688
25.257.4.43	GetCenterOfRotation	688
25.257.4.44	GetFiniteVolume	688
25.257.4.45	GetManifold	688
25.257.4.46	GetMaximumPointDistance	688
25.257.4.47	GetMeanPointDistance	688
25.257.4.48	GetMeshPrimitive	688
25.257.4.49	GetNumberOfSurfacePoints	688
25.257.4.50	GetNumberOfVectors	688
25.257.4.51	GetPointCoordinatesData	689
25.257.4.52	GetPointPositionAccuracy	689
25.257.4.53	GetPointsBoundingBoxCoordinates	689
25.257.4.54	GetProcessingAlgorithm	689
25.257.4.55	GetRecommendedDisplayCIELabValue	689
25.257.4.56	GetRecommendedDisplayCIELabValue	689
25.257.4.57	GetRecommendedDisplayCIELabValue	689
25.257.4.58	GetRecommendedDisplayGrayscaleValue	689
25.257.4.59	GetRecommendedPresentationOpacity	689
25.257.4.60	GetRecommendedPresentationType	689
25.257.4.61	GetSurfaceComments	689
25.257.4.62	GetSurfaceNumber	689

25.257.4.63	SetSurfaceProcessing	689
25.257.4.63	SetSurfaceProcessingDescription	689
25.257.4.65	SetSurfaceProcessingRatio	689
25.257.4.66	SetVectorAccuracy	689
25.257.4.67	SetVectorCoordinateData	689
25.257.4.68	SetVectorDimensionality	689
25.258	dcm::SurfaceHelper Class Reference	689
25.258.1	Detailed Description	690
25.258.2	Member Typedef Documentation	690
25.258.2.1	ColorArray	690
25.258.3	Member Function Documentation	690
25.258.3.1	RecommendedDisplayCIELabToRGB	690
25.258.3.2	RecommendedDisplayCIELabToRGB	691
25.258.3.3	RecommendedDisplayCIELabToRGB	691
25.258.3.4	RecommendedDisplayCIELabToRGB	691
25.258.3.5	RGBToRecommendedDisplayCIELab	691
25.258.3.6	RGBToRecommendedDisplayCIELab	692
25.258.3.7	RGBToRecommendedDisplayGrayscale	692
25.258.3.8	RGBToRecommendedDisplayGrayscale	692
25.259	dcm::SurfaceReader Class Reference	692
25.259.1	Detailed Description	694
25.259.2	Constructor & Destructor Documentation	694
25.259.2.1	SurfaceReader	694
25.259.2.2	~SurfaceReader	694
25.259.3	Member Function Documentation	694
25.259.3.1	GetNumberOfSurfaces	694
25.259.3.2	Read	694
25.259.3.3	ReadPointMacro	694
25.259.3.4	ReadSurface	694
25.259.3.5	ReadSurfaces	694
25.260	dcm::SurfaceWriter Class Reference	695
25.260.1	Detailed Description	696
25.260.2	Constructor & Destructor Documentation	696
25.260.2.1	SurfaceWriter	696
25.260.2.2	~SurfaceWriter	696
25.260.3	Member Function Documentation	696
25.260.3.1	ComputeNumberOfSurfaces	696

25.260.3.2GetNumberOfSurfaces	696
25.260.3.3PrepareWrite	696
25.260.3.4PrepareWritePointMacro	696
25.260.3.5SetNumberOfSurfaces	696
25.260.3.6Write	696
25.260.4Member Data Documentation	696
25.260.4.1NumberOfSurfaces	696
25.261gdcmm::SwapCode Class Reference	696
25.261.1Detailed Description	697
25.261.2Member Enumeration Documentation	697
25.261.2.1SwapCodeType	697
25.261.3Constructor & Destructor Documentation	698
25.261.3.1SwapCode	698
25.261.4Member Function Documentation	698
25.261.4.1GetIndex	698
25.261.4.2GetSwapCodeString	698
25.261.4.3operator SwapCode::SwapCodeType	698
25.261.5Friends And Related Function Documentation	698
25.261.5.1operator<<	698
25.262gdcmm::SwapperDoOp Class Reference	698
25.262.1Member Function Documentation	698
25.262.1.1Swap	698
25.262.1.2SwapArray	698
25.263gdcmm::SwapperNoOp Class Reference	699
25.263.1Detailed Description	699
25.263.2Member Function Documentation	699
25.263.2.1Swap	699
25.263.2.2SwapArray	699
25.264gdcmm::System Class Reference	699
25.264.1Detailed Description	700
25.264.2Member Function Documentation	700
25.264.2.1DeleteDirectory	700
25.264.2.2EncodeBytes	700
25.264.2.3FileExists	701
25.264.2.4FileIsDirectory	701
25.264.2.5FileIsSymlink	701
25.264.2.6FileSize	701

25.264.2.7	FileTime	701
25.264.2.8	FormatDateTime	701
25.264.2.9	GetCurrentDateTime	701
25.264.2.10	GetCurrentModuleFileName	702
25.264.2.11	GetCurrentProcessFileName	702
25.264.2.12	GetCurrentResourcesDirectory	702
25.264.2.13	GetCurrentCWD	702
25.264.2.14	GetHostName	702
25.264.2.15	GetLastError	702
25.264.2.16	GetLocaleCharset	702
25.264.2.17	GetPermissions	702
25.264.2.18	GetTimezoneOffsetFromUTC	702
25.264.2.19	MakeDirectory	702
25.264.2.20	ParseDateTime	703
25.264.2.21	ParseDateTime	703
25.264.2.22	RemoveFile	703
25.264.2.23	SetPermissions	703
25.264.2.24	StrCaseCmp	703
25.264.2.25	StrNCaseCmp	703
25.264.2.26	StrTokR	703
25.265	dcm::Table Class Reference	703
25.265.1	Detailed Description	704
25.265.2	Member Typedef Documentation	704
25.265.2.1	MapTableEntry	704
25.265.3	Constructor & Destructor Documentation	704
25.265.3.1	Table	704
25.265.3.2	~Table	704
25.265.4	Member Function Documentation	704
25.265.4.1	GetTableEntry	704
25.265.4.2	InsertEntry	704
25.265.5	Friends And Related Function Documentation	704
25.265.5.1	operator<<	704
25.266	dcm::TableEntry Class Reference	704
25.266.1	Detailed Description	705
25.266.2	Constructor & Destructor Documentation	705
25.266.2.1	TableEntry	705
25.266.2.2	~TableEntry	705

25.267	gdcm::TableReader Class Reference	705
25.267.1	Detailed Description	706
25.267.2	Constructor & Destructor Documentation	706
25.267.2.1	TableReader	706
25.267.2.2	~TableReader	706
25.267.3	Member Function Documentation	706
25.267.3.1	CharacterDataHandler	706
25.267.3.2	EndElement	706
25.267.3.3	GetDefs	706
25.267.3.4	GetFilename	706
25.267.3.5	HandleIOD	706
25.267.3.6	HandleIODEntry	706
25.267.3.7	HandleMacro	706
25.267.3.8	HandleMacroEntry	706
25.267.3.9	HandleMacroEntryDescription	706
25.267.3.10	HandleModule	706
25.267.3.11	HandleModuleEntry	706
25.267.3.12	HandleModuleEntryDescription	707
25.267.3.13	HandleModuleInclude	707
25.267.3.14	Read	707
25.267.3.15	SetFilename	707
25.267.3.16	StartElement	707
25.268	gdcm::network::TableRow Class Reference	707
25.268.1	Constructor & Destructor Documentation	708
25.268.1.1	TableRow	708
25.268.1.2	~TableRow	708
25.268.2	Member Data Documentation	708
25.268.2.1	transitions	708
25.269	gdcm::Tag Class Reference	708
25.269.1	Detailed Description	710
25.269.2	Constructor & Destructor Documentation	710
25.269.2.1	Tag	710
25.269.2.2	Tag	710
25.269.2.3	Tag	710
25.269.3	Member Function Documentation	710
25.269.3.1	GetElement	710
25.269.3.2	GetElementTag	711

25.269.3.3	GetGroup	. 711
25.269.3.4	GetLength	. 711
25.269.3.5	GetPrivateCreator	. 711
25.269.3.6	IsGroupLength	. 711
25.269.3.7	IsGroupXX	. 711
25.269.3.8	IsIllegal	. 711
25.269.3.9	IsPrivate	. 711
25.269.3.10	IsPrivateCreator	. 712
25.269.3.11	IsPublic	. 712
25.269.3.12	operator!=	. 712
25.269.3.13	operator<	. 712
25.269.3.14	operator<=	. 712
25.269.3.15	operator=	. 712
25.269.3.16	operator==	. 712
25.269.3.17	operator[]	. 712
25.269.3.18	operator[]	. 712
25.269.3.19	PrintAsPipeSeparatedString	. 713
25.269.3.20	Read	. 713
25.269.3.21	ReadFromCommaSeparatedString	. 713
25.269.3.22	ReadFromPipeSeparatedString	. 713
25.269.3.23	SetElement	. 713
25.269.3.24	SetElementTag	. 713
25.269.3.25	SetElementTag	. 713
25.269.3.26	SetGroup	. 713
25.269.3.27	SetPrivateCreator	. 714
25.269.3.28	Write	. 714
25.269.4	Friends And Related Function Documentation	. 714
25.269.4.1	operator<<	. 714
25.269.4.2	operator>>	. 714
25.269.5	Member Data Documentation	. 714
25.269.5.1	bytes	. 714
25.269.5.2	tag	. 714
25.269.5.3	tags	. 714
25.270	GDCM::TagPath Class Reference	. 714
25.270.1	Detailed Description	. 715
25.270.2	Constructor & Destructor Documentation	. 715
25.270.2.1	TagPath	. 715

25.270.2.2~TagPath	715
25.270.3Member Function Documentation	715
25.270.3.1ConstructFromString	715
25.270.3.2ConstructFromTagList	715
25.270.3.3IsValid	715
25.270.3.4Print	715
25.270.3.5Push	715
25.270.3.6Push	715
25.271gdcm::Testing Class Reference	716
25.271.1Detailed Description	717
25.271.2Member Typedef Documentation	717
25.271.2.1MD5DataImagesType	717
25.271.2.2MediaStorageDataFilesType	717
25.271.3Constructor & Destructor Documentation	717
25.271.3.1Testing	717
25.271.3.2~Testing	717
25.271.4Member Function Documentation	717
25.271.4.1ComputeFileMD5	717
25.271.4.2ComputeMD5	717
25.271.4.3GetDataExtraRoot	717
25.271.4.4GetDataRoot	718
25.271.4.5GetFileName	718
25.271.4.6GetFileNames	718
25.271.4.7GetLossyFlagFromFile	718
25.271.4.8GetMD5DataImage	718
25.271.4.9GetMD5DataImages	718
25.271.4.10GetMD5FromBrokenFile	718
25.271.4.11GetMD5FromFile	718
25.271.4.12GetMediaStorageDataFile	718
25.271.4.13GetMediaStorageDataFiles	718
25.271.4.14GetMediaStorageFromFile	718
25.271.4.15GetNumberOfFileNames	718
25.271.4.16GetNumberOfMD5DataImages	718
25.271.4.17GetNumberOfMediaStorageDataFiles	719
25.271.4.18GetPixelSpacingDataRoot	719
25.271.4.19GetSelectedTagsOffsetFromFile	719
25.271.4.20GetSourceDirectory	719

25.271.4.20	GetStreamOffsetFromFile	. 719
25.271.4.20	GetTempDirectory	. 719
25.271.4.20	GetTempDirectoryW	. 719
25.271.4.20	GetTempFilename	. 719
25.271.4.20	GetTempFilenameW	. 719
25.271.4.20	Print	. 719
25.270	gdcmm::Trace Class Reference	. 719
25.272.1	Detailed Description	. 720
25.272.2	Constructor & Destructor Documentation	. 721
25.272.2.1	Trace	. 721
25.272.2.2	~Trace	. 721
25.272.3	Member Function Documentation	. 721
25.272.3.1	DebugOff	. 721
25.272.3.2	DebugOn	. 721
25.272.3.3	ErrorOff	. 721
25.272.3.4	ErrorOn	. 721
25.272.3.5	GetDebugFlag	. 721
25.272.3.6	GetDebugStream	. 721
25.272.3.7	GetErrorFlag	. 721
25.272.3.8	GetErrorStream	. 721
25.272.3.9	GetStream	. 721
25.272.3.10	GetWarningFlag	. 721
25.272.3.10	GetWarningStream	. 721
25.272.3.10	SetDebug	. 721
25.272.3.10	SetDebugStream	. 721
25.272.3.10	SetError	. 722
25.272.3.10	SetErrorStream	. 722
25.272.3.10	SetStream	. 722
25.272.3.10	SetStreamToFile	. 722
25.272.3.10	SetWarning	. 722
25.272.3.10	SetWarningStream	. 722
25.272.3.20	WarningOff	. 722
25.272.3.20	WarningOn	. 722
25.270	gdcmm::TransferSyntax Class Reference	. 723
25.273.1	Detailed Description	. 724
25.273.2	Member Enumeration Documentation	. 724
25.273.2.1	NegotiatedType	. 724

25.273.2.2TSType	724
25.273.3Constructor & Destructor Documentation	725
25.273.3.1TransferSyntax	725
25.273.4Member Function Documentation	725
25.273.4.1CanStoreLossy	725
25.273.4.2GetNegociatedType	725
25.273.4.3GetString	725
25.273.4.4GetSwapCode	725
25.273.4.5GetTSString	726
25.273.4.6GetTSType	726
25.273.4.7IsEncapsulated	726
25.273.4.8IsEncoded	726
25.273.4.9IsExplicit	726
25.273.4.10IsImplicit	726
25.273.4.11IsLossless	726
25.273.4.12IsLossy	726
25.273.4.13IsValid	726
25.273.4.14operator TSType	726
25.273.5Friends And Related Function Documentation	726
25.273.5.1operator<<	726
25.274dcm::network::TransferSyntaxSub Class Reference	726
25.274.1Detailed Description	727
25.274.2Constructor & Destructor Documentation	727
25.274.2.1TransferSyntaxSub	727
25.274.3Member Function Documentation	727
25.274.3.1GetName	727
25.274.3.2operator==	727
25.274.3.3Print	727
25.274.3.4Read	727
25.274.3.5SetName	727
25.274.3.6SetNameFromUID	727
25.274.3.7Size	727
25.274.3.8Write	727
25.275dcm::network::Transition Struct Reference	727
25.275.1Constructor & Destructor Documentation	728
25.275.1.1Transition	728
25.275.1.2~Transition	728

25.275.1.3Transition	728
25.275.2Member Function Documentation	729
25.275.2.1MakeNew	729
25.275.3Member Data Documentation	729
25.275.3.1mAction	729
25.275.3.2mEnd	729
25.276dcm::Type Class Reference	729
25.276.1Detailed Description	730
25.276.2Member Enumeration Documentation	730
25.276.2.1TypeType	730
25.276.3Constructor & Destructor Documentation	730
25.276.3.1Type	730
25.276.4Member Function Documentation	730
25.276.4.1GetTypeString	730
25.276.4.2GetTypeType	730
25.276.4.3operator TypeType	731
25.276.5Friends And Related Function Documentation	731
25.276.5.1operator<<	731
25.277dcm::UI Struct Reference	731
25.277.1Friends And Related Function Documentation	731
25.277.1.1operator<<	731
25.277.2Member Data Documentation	731
25.277.2.1Internal	731
25.278dcm::UIDGenerator Class Reference	731
25.278.1Detailed Description	732
25.278.2Constructor & Destructor Documentation	732
25.278.2.1UIDGenerator	732
25.278.3Member Function Documentation	732
25.278.3.1Generate	732
25.278.3.2GenerateUUID	732
25.278.3.3GetGDCMUID	732
25.278.3.4GetRoot	733
25.278.3.5IsValid	733
25.278.3.6SetRoot	733
25.279dcm::UIDs Class Reference	733
25.279.1Detailed Description	738
25.279.2Member Typedef Documentation	738

25.279.2.1TransferSyntaxStringsType	738
25.279.3Member Enumeration Documentation	738
25.279.3.1TSName	738
25.279.3.2TSType	745
25.279.4Member Function Documentation	751
25.279.4.1GetName	751
25.279.4.2GetNumberOfTransferSyntaxStrings	752
25.279.4.3GetString	752
25.279.4.4GetTransferSyntaxString	752
25.279.4.5GetTransferSyntaxStrings	752
25.279.4.6GetUIDName	752
25.279.4.7GetUIDString	752
25.279.4.8operator TSType	752
25.279.4.9SetFromUID	752
25.280dcm::network::ULAction Class Reference	752
25.280.1Detailed Description	754
25.280.2Constructor & Destructor Documentation	754
25.280.2.1ULAction	754
25.280.2.2~ULAction	754
25.280.3Member Function Documentation	754
25.280.3.1PerformAction	754
25.281dcm::network::ULActionAA1 Class Reference	755
25.281.1Member Function Documentation	755
25.281.1.1PerformAction	755
25.282dcm::network::ULActionAA2 Class Reference	756
25.282.1Member Function Documentation	756
25.282.1.1PerformAction	757
25.283dcm::network::ULActionAA3 Class Reference	757
25.283.1Member Function Documentation	758
25.283.1.1PerformAction	758
25.284dcm::network::ULActionAA4 Class Reference	758
25.284.1Member Function Documentation	759
25.284.1.1PerformAction	759
25.285dcm::network::ULActionAA5 Class Reference	759
25.285.1Member Function Documentation	760
25.285.1.1PerformAction	760
25.286dcm::network::ULActionAA6 Class Reference	760

25.286.1Member Function Documentation	761
25.286.1.1PerformAction	761
25.287dcm::network::ULActionAA7 Class Reference	762
25.287.1Member Function Documentation	762
25.287.1.1PerformAction	762
25.288dcm::network::ULActionAA8 Class Reference	763
25.288.1Member Function Documentation	763
25.288.1.1PerformAction	764
25.289dcm::network::ULActionAE1 Class Reference	764
25.289.1Member Function Documentation	765
25.289.1.1PerformAction	765
25.290dcm::network::ULActionAE2 Class Reference	765
25.290.1Member Function Documentation	766
25.290.1.1PerformAction	766
25.291dcm::network::ULActionAE3 Class Reference	766
25.291.1Member Function Documentation	767
25.291.1.1PerformAction	767
25.292dcm::network::ULActionAE4 Class Reference	767
25.292.1Member Function Documentation	768
25.292.1.1PerformAction	768
25.293dcm::network::ULActionAE5 Class Reference	769
25.293.1Member Function Documentation	769
25.293.1.1PerformAction	769
25.294dcm::network::ULActionAE6 Class Reference	770
25.294.1Member Function Documentation	770
25.294.1.1PerformAction	771
25.295dcm::network::ULActionAE7 Class Reference	771
25.295.1Member Function Documentation	772
25.295.1.1PerformAction	772
25.296dcm::network::ULActionAE8 Class Reference	772
25.296.1Member Function Documentation	773
25.296.1.1PerformAction	773
25.297dcm::network::ULActionAR1 Class Reference	773
25.297.1Member Function Documentation	774
25.297.1.1PerformAction	774
25.298dcm::network::ULActionAR10 Class Reference	774
25.298.1Member Function Documentation	775

25.298.1.1PerformAction	775
25.299dcm::network::ULActionAR2 Class Reference	776
25.299.1Member Function Documentation	776
25.299.1.1PerformAction	776
25.300dcm::network::ULActionAR3 Class Reference	777
25.300.1Member Function Documentation	777
25.300.1.1PerformAction	778
25.301dcm::network::ULActionAR4 Class Reference	778
25.301.1Member Function Documentation	779
25.301.1.1PerformAction	779
25.302dcm::network::ULActionAR5 Class Reference	779
25.302.1Member Function Documentation	780
25.302.1.1PerformAction	780
25.303dcm::network::ULActionAR6 Class Reference	780
25.303.1Member Function Documentation	781
25.303.1.1PerformAction	781
25.304dcm::network::ULActionAR7 Class Reference	781
25.304.1Member Function Documentation	782
25.304.1.1PerformAction	782
25.305dcm::network::ULActionAR8 Class Reference	783
25.305.1Member Function Documentation	783
25.305.1.1PerformAction	783
25.306dcm::network::ULActionAR9 Class Reference	784
25.306.1Member Function Documentation	784
25.306.1.1PerformAction	785
25.307dcm::network::ULActionDT1 Class Reference	785
25.307.1Member Function Documentation	786
25.307.1.1PerformAction	786
25.308dcm::network::ULActionDT2 Class Reference	786
25.308.1Member Function Documentation	787
25.308.1.1PerformAction	787
25.309dcm::network::ULBasicCallback Class Reference	787
25.309.1Detailed Description	788
25.309.2Constructor & Destructor Documentation	788
25.309.2.1ULBasicCallback	788
25.309.2.2~ULBasicCallback	788
25.309.3Member Function Documentation	788

25.309.3.1GetDataSets	788
25.309.3.2GetResponses	788
25.309.3.3HandleDataSet	788
25.309.3.4HandleResponse	789
25.310dcm::network::ULConnection Class Reference	789
25.310.1Detailed Description	790
25.310.2Constructor & Destructor Documentation	790
25.310.2.1ULConnection	790
25.310.2.2~ULConnection	790
25.310.3Member Function Documentation	790
25.310.3.1AddAcceptedPresentationContext	790
25.310.3.2FindContext	790
25.310.3.3GetAcceptedPresentationContexts	790
25.310.3.4GetAcceptedPresentationContexts	790
25.310.3.5GetConnectionInfo	790
25.310.3.6GetMaxPDUSize	790
25.310.3.7GetPresentationContextACByID	790
25.310.3.8GetPresentationContextIDFromPresentationContext	790
25.310.3.9GetPresentationContextRQByID	790
25.310.3.10GetPresentationContexts	790
25.310.3.11GetProtocol	790
25.310.3.12GetState	790
25.310.3.13GetTimer	791
25.310.3.14InitializeConnection	791
25.310.3.15InitializeIncomingConnection	791
25.310.3.16SetMaxPDUSize	791
25.310.3.17SetPresentationContexts	791
25.310.3.18SetPresentationContexts	791
25.310.3.19SetState	791
25.310.3.20StopProtocol	791
25.311dcm::network::ULConnectionCallback Class Reference	791
25.311.1Detailed Description	792
25.311.2Constructor & Destructor Documentation	792
25.311.2.1ULConnectionCallback	792
25.311.2.2~ULConnectionCallback	792
25.311.3Member Function Documentation	792
25.311.3.1DataSetHandled	792

25.311.3.2	DataSetHandles	792
25.311.3.3	HandleDataSet	792
25.311.3.4	HandleResponse	792
25.311.3.5	ResetHandledDataSet	792
25.312	gdcm::network::ULConnectionInfo Class Reference	793
25.312.1	Detailed Description	793
25.312.2	Constructor & Destructor Documentation	793
25.312.2.1	ULConnectionInfo	793
25.312.3	Member Function Documentation	793
25.312.3.1	GetCalledAETitle	793
25.312.3.2	GetCalledComputerName	793
25.312.3.3	GetCalledIPAddress	793
25.312.3.4	GetCalledIPPort	793
25.312.3.5	GetCallingAETitle	793
25.312.3.6	GetMaxPDULength	793
25.312.3.7	Initialize	793
25.312.3.8	SetMaxPDULength	794
25.313	gdcm::network::ULConnectionManager Class Reference	794
25.313.1	Detailed Description	796
25.313.2	Constructor & Destructor Documentation	796
25.313.2.1	ULConnectionManager	796
25.313.2.2	~ULConnectionManager	796
25.313.3	Member Function Documentation	796
25.313.3.1	BreakConnection	796
25.313.3.2	BreakConnectionNow	796
25.313.3.3	EstablishConnection	796
25.313.3.4	EstablishConnectionMove	796
25.313.3.5	SendEcho	796
25.313.3.6	SendFind	796
25.313.3.7	SendFind	796
25.313.3.8	SendMove	796
25.313.3.9	SendMove	796
25.313.3.10	SendStore	796
25.313.3.11	SendStore	797
25.314	gdcm::network::ULEvent Class Reference	797
25.314.1	Detailed Description	797
25.314.2	Constructor & Destructor Documentation	797

25.314.2.1	ULEvent	797
25.314.2.2	ULEvent	797
25.314.2.3	~ULEvent	797
25.314.3	Member Function Documentation	797
25.314.3.1	GetEvent	797
25.314.3.2	GetPDUs	797
25.314.3.3	SetEvent	797
25.314.3.4	SetPDU	798
25.315	dcm::network::ULTransitionTable Class Reference	798
25.315.1	Detailed Description	798
25.315.2	Constructor & Destructor Documentation	798
25.315.2.1	ULTransitionTable	798
25.315.3	Member Function Documentation	798
25.315.3.1	HandleEvent	798
25.315.3.2	PrintTable	798
25.316	dcm::network::ULWritingCallback Class Reference	798
25.316.1	Constructor & Destructor Documentation	799
25.316.1.1	ULWritingCallback	800
25.316.1.2	~ULWritingCallback	800
25.316.2	Member Function Documentation	800
25.316.2.1	HandleDataSet	800
25.316.2.2	HandleResponse	800
25.316.2.3	SetDirectory	800
25.317	dcm::UNExplicitDataElement Class Reference	800
25.317.1	Detailed Description	801
25.317.2	Member Function Documentation	801
25.317.2.1	GetLength	801
25.317.2.2	Read	802
25.317.2.3	ReadPreValue	802
25.317.2.4	ReadValue	802
25.317.2.5	ReadWithLength	802
25.318	dcm::UNExplicitImplicitDataElement Class Reference	802
25.318.1	Detailed Description	803
25.318.2	Member Function Documentation	803
25.318.2.1	GetLength	803
25.318.2.2	Read	804
25.318.2.3	ReadPreValue	804

25.318.2.4ReadValue	804
25.319dcm::Unpacker12Bits Class Reference	804
25.319.1Detailed Description	804
25.319.2Member Function Documentation	804
25.319.2.1Pack	804
25.319.2.2Unpack	804
25.320dcm::Usage Class Reference	805
25.320.1Detailed Description	805
25.320.2Member Enumeration Documentation	806
25.320.2.1UsageType	806
25.320.3Constructor & Destructor Documentation	806
25.320.3.1Usage	806
25.320.4Member Function Documentation	806
25.320.4.1GetUsageString	806
25.320.4.2GetUsageType	806
25.320.4.3operator UsageType	806
25.320.5Friends And Related Function Documentation	806
25.320.5.1operator<<	806
25.321dcm::UserEvent Class Reference	806
25.322dcm::network::UserInformation Class Reference	808
25.322.1Detailed Description	808
25.322.2Constructor & Destructor Documentation	808
25.322.2.1UserInformation	808
25.322.2.2~UserInformation	808
25.322.3Member Function Documentation	808
25.322.3.1AddRoleSelectionSub	808
25.322.3.2AddSOPClassExtendedNegociationSub	808
25.322.3.3GetMaximumLengthSub	808
25.322.3.4GetMaximumLengthSub	808
25.322.3.5operator=	808
25.322.3.6Print	808
25.322.3.7Read	808
25.322.3.8Size	809
25.322.3.9Write	809
25.323dcm::Validate Class Reference	809
25.323.1Detailed Description	810
25.323.2Constructor & Destructor Documentation	810

25.323.2.1Validate	810
25.323.2.2~Validate	810
25.323.3Member Function Documentation	810
25.323.3.1GetValidatedFile	810
25.323.3.2SetFile	810
25.323.3.3Validation	810
25.323.4Member Data Documentation	810
25.323.4.1F	810
25.323.4.2V	810
25.324dcm::Value Class Reference	810
25.324.1Detailed Description	811
25.324.2Constructor & Destructor Documentation	811
25.324.2.1Value	811
25.324.2.2~Value	811
25.324.3Member Function Documentation	811
25.324.3.1Clear	811
25.324.3.2GetLength	812
25.324.3.3operator==	812
25.324.3.4SetLength	812
25.325dcm::ValueIO< TDE, TSwap, TType > Class Template Reference	812
25.325.1Detailed Description	812
25.325.2Member Function Documentation	812
25.325.2.1Read	812
25.325.2.2Write	812
25.326dcm::Version Class Reference	813
25.326.1Detailed Description	813
25.326.2Constructor & Destructor Documentation	813
25.326.2.1Version	813
25.326.2.2~Version	813
25.326.3Member Function Documentation	813
25.326.3.1GetBuildVersion	813
25.326.3.2GetMajorVersion	813
25.326.3.3GetMinorVersion	813
25.326.3.4GetVersion	813
25.326.3.5Print	813
25.326.4Friends And Related Function Documentation	814
25.326.4.1operator<<	814

25.327	gdc::VL Class Reference	814
25.327.1	Detailed Description	815
25.327.2	Member Typedef Documentation	815
25.327.2.1	Type	815
25.327.3	Constructor & Destructor Documentation	815
25.327.3.1	VL	815
25.327.4	Member Function Documentation	815
25.327.4.1	GetLength	815
25.327.4.2	GetVL16Max	815
25.327.4.3	GetVL32Max	815
25.327.4.4	IsOdd	815
25.327.4.5	IsUndefined	815
25.327.4.6	operator uint32_t	815
25.327.4.7	operator++	815
25.327.4.8	operator++	815
25.327.4.9	operator+=	815
25.327.4.10	Read	816
25.327.4.11	Read16	816
25.327.4.12	SetToUndefined	816
25.327.4.13	Write	816
25.327.4.14	Write16	816
25.327.5	Friends And Related Function Documentation	816
25.327.5.1	operator<<	816
25.328	gdc::VM Class Reference	816
25.328.1	Detailed Description	818
25.328.2	Member Enumeration Documentation	818
25.328.2.1	VMType	818
25.328.3	Constructor & Destructor Documentation	819
25.328.3.1	VM	819
25.328.4	Member Function Documentation	819
25.328.4.1	Compatible	819
25.328.4.2	GetIndex	819
25.328.4.3	GetLength	819
25.328.4.4	GetNumberOfElementsFromArray	819
25.328.4.5	GetVMString	819
25.328.4.6	GetVMType	820
25.328.4.7	GetVMTypeFromLength	820

25.328.4.8IsValid	820
25.328.4.9operator VMType	820
25.328.5Friends And Related Function Documentation	820
25.328.5.1operator<<	820
25.329gdcmm::VMToLength< T > Struct Template Reference	820
25.330gdcmm::VR Class Reference	820
25.330.1Detailed Description	822
25.330.2Member Enumeration Documentation	822
25.330.2.1VRType	822
25.330.3Constructor & Destructor Documentation	823
25.330.3.1VR	823
25.330.4Member Function Documentation	823
25.330.4.1CanDisplay	823
25.330.4.2Compatible	823
25.330.4.3GetLength	824
25.330.4.4GetLength	824
25.330.4.5GetSize	824
25.330.4.6GetSizeof	824
25.330.4.7GetVRString	824
25.330.4.8GetVRStringFromFile	824
25.330.4.9GetVRType	824
25.330.4.10GetVRTypeFromFile	824
25.330.4.11IsASCII	824
25.330.4.12IsASCII2	824
25.330.4.13IsBinary	824
25.330.4.14IsBinary2	824
25.330.4.15IsDual	824
25.330.4.16IsSwap	824
25.330.4.17IsValid	824
25.330.4.18IsValid	824
25.330.4.19IsVRFile	824
25.330.4.20operator VRType	824
25.330.4.21Read	824
25.330.4.22Write	824
25.330.5Friends And Related Function Documentation	825
25.330.5.1operator<<	825
25.331gdcmm::VR16ExplicitDataElement Class Reference	825

25.331.1	Detailed Description	826
25.331.2	Member Function Documentation	826
25.331.2.1	GetLength	826
25.331.2.2	Read	827
25.331.2.3	ReadPreValue	827
25.331.2.4	ReadValue	827
25.331.2.5	ReadWithLength	827
25.332	dcm::VRToEncoding< T > Struct Template Reference	827
25.333	dcm::VRToType< T > Struct Template Reference	827
25.333.1	Detailed Description	827
25.334	dcm::VRVLSize< T > Class Template Reference	828
25.335	dcm::VRVLSize< 0 > Class Template Reference	828
25.335.1	Member Function Documentation	828
25.335.1.1	Read	828
25.335.1.2	Write	828
25.336	dcm::VRVLSize< 1 > Class Template Reference	828
25.336.1	Member Function Documentation	828
25.336.1.1	Read	828
25.336.1.2	Write	828
25.337	vtkGDCMImageReader Class Reference	829
25.337.1	Detailed Description	831
25.337.2	Constructor & Destructor Documentation	831
25.337.2.1	vtkGDCMImageReader	831
25.337.2.2	~vtkGDCMImageReader	832
25.337.3	Member Function Documentation	832
25.337.3.1	CanReadFile	832
25.337.3.2	ExecuteData	832
25.337.3.3	ExecuteInformation	832
25.337.3.4	FillMedicalImageInformation	832
25.337.3.5	GetDescriptiveName	832
25.337.3.6	GetFileExtensions	832
25.337.3.7	GetIconImage	832
25.337.3.8	GetOverlay	832
25.337.3.9	LoadSingleFile	832
25.337.3.10	New	832
25.337.3.11	PrintSelf	832
25.337.3.12	RequestDataCompat	832

25.337.3.18	RequestInformationCompat	832
25.337.3.19	SetCurve	832
25.337.3.19	SetFileNames	833
25.337.3.19	SetFilePattern	833
25.337.3.19	SetFilePrefix	833
25.337.3.19	SetMedicalImageProperties	833
25.337.3.19	tkBooleanMacro	833
25.337.3.20	tkBooleanMacro	833
25.337.3.20	tkBooleanMacro	833
25.337.3.20	tkBooleanMacro	833
25.337.3.20	tkBooleanMacro	833
25.337.3.21	tkGetMacro	833
25.337.3.21	tkGetMacro	833
25.337.3.21	tkGetMacro	833
25.337.3.27	tkGetMacro	833
25.337.3.28	tkGetMacro	833
25.337.3.28	tkGetMacro	833
25.337.3.30	tkGetMacro	833
25.337.3.30	tkGetMacro	833
25.337.3.31	tkGetMacro	833
25.337.3.31	tkGetMacro	833
25.337.3.31	tkGetMacro	833
25.337.3.31	tkGetMacro	833
25.337.3.35	tkGetObjectMacro	833
25.337.3.36	tkGetObjectMacro	833
25.337.3.37	tkGetObjectMacro	833
25.337.3.38	tkGetObjectMacro	834
25.337.3.38	tkGetStringMacro	834
25.337.3.40	tkGetStringMacro	834
25.337.3.41	tkGetVector3Macro	834
25.337.3.42	tkGetVector6Macro	834
25.337.3.43	tkSetMacro	834
25.337.3.44	tkSetMacro	834
25.337.3.45	tkSetMacro	834
25.337.3.46	tkSetMacro	834
25.337.3.47	tkSetVector6Macro	834
25.337.3.48	tkTypeRevisionMacro	834
25.337.4	Member Data Documentation	834

25.337.4.1	ApplyInverseVideo	834
25.337.4.2	ApplyLookupTable	834
25.337.4.3	ApplyPlanarConfiguration	834
25.337.4.4	ApplyShiftScale	834
25.337.4.5	ApplyYBRToRGB	834
25.337.4.6	Curve	834
25.337.4.7	DirectionCosines	834
25.337.4.8	FileNames	834
25.337.4.9	ForceRescale	834
25.337.4.10	IconDataScalarType	834
25.337.4.11	IconImageDataExtent	834
25.337.4.12	IconNumberOfScalarComponents	834
25.337.4.13	IconImageFormat	834
25.337.4.14	IconImageOrientationPatient	834
25.337.4.15	IconImagePositionPatient	835
25.337.4.16	LoadIconImage	835
25.337.4.17	LoadOverlays	835
25.337.4.18	LossyFlag	835
25.337.4.19	MedicalImageProperties	835
25.337.4.20	NumberOfIconImages	835
25.337.4.21	NumberOfOverlays	835
25.337.4.22	PlanarConfiguration	835
25.337.4.23	Scale	835
25.337.4.24	Shift	835
25.338	vtkGDCMImageWriter Class Reference	835
25.338.1	Detailed Description	837
25.338.2	Member Enumeration Documentation	837
25.338.2.1	CompressionTypes	837
25.338.3	Constructor & Destructor Documentation	837
25.338.3.1	vtkGDCMImageWriter	837
25.338.3.2	~vtkGDCMImageWriter	837
25.338.4	Member Function Documentation	837
25.338.4.1	GetDescriptiveName	838
25.338.4.2	GetFileExtensions	838
25.338.4.3	GetFileName	838
25.338.4.4	New	838
25.338.4.5	PrintSelf	838

25.338.4.6SetDirectionCosines	838
25.338.4.7SetDirectionCosinesFromImageOrientationPatient	838
25.338.4.8SetFileNames	838
25.338.4.9SetMedicalImageProperties	838
25.338.4.10kBooleanMacro	838
25.338.4.11kBooleanMacro	838
25.338.4.12kGetMacro	838
25.338.4.13kGetMacro	838
25.338.4.14kGetMacro	838
25.338.4.15kGetMacro	839
25.338.4.16kGetMacro	839
25.338.4.17kGetMacro	839
25.338.4.18kGetMacro	839
25.338.4.19kGetObjectMacro	839
25.338.4.20kGetObjectMacro	839
25.338.4.21kGetObjectMacro	839
25.338.4.22kGetStringMacro	839
25.338.4.23kGetStringMacro	839
25.338.4.24kSetMacro	839
25.338.4.25kSetMacro	839
25.338.4.26kSetMacro	839
25.338.4.27kSetMacro	839
25.338.4.28kSetMacro	839
25.338.4.29kSetMacro	839
25.338.4.30kSetMacro	839
25.338.4.31kSetStringMacro	839
25.338.4.32kSetStringMacro	839
25.338.4.33kTypeRevisionMacro	839
25.338.4.34Write	839
25.338.4.35WriteGDCMData	839
25.338.4.36WriteSlice	839
25.339tkGDCMMedicalImageProperties Class Reference	840
25.339.1Constructor & Destructor Documentation	841
25.339.1.1vtkGDCMMedicalImageProperties	841
25.339.1.2~vtkGDCMMedicalImageProperties	841
25.339.2Member Function Documentation	841
25.339.2.1Clear	841

25.339.2.2	GetFile	841
25.339.2.3	New	841
25.339.2.4	PrintSelf	841
25.339.2.5	PushBackFile	841
25.339.2.6	vtkTypeRevisionMacro	841
25.339.3	Friends And Related Function Documentation	841
25.339.3.1	vtkGDCMImageReader	841
25.339.3.2	vtkGDCMImageWriter	841
25.340	vtkGDCMPolyDataReader Class Reference	841
25.340.1	Detailed Description	843
25.340.2	Constructor & Destructor Documentation	843
25.340.2.1	vtkGDCMPolyDataReader	843
25.340.2.2	~vtkGDCMPolyDataReader	843
25.340.3	Member Function Documentation	843
25.340.3.1	FillMedicalImageInformation	843
25.340.3.2	New	843
25.340.3.3	PrintSelf	843
25.340.3.4	RequestData	843
25.340.3.5	RequestData_HemodynamicWaveformStorage	843
25.340.3.6	RequestData_RTStructureSetStorage	844
25.340.3.7	RequestInformation	844
25.340.3.8	RequestInformation_HemodynamicWaveformStorage	844
25.340.3.9	RequestInformation_RTStructureSetStorage	844
25.340.3.10	GetObjectMacro	844
25.340.3.11	vtkGetObjectMacro	844
25.340.3.12	GetStringMacro	844
25.340.3.13	SetStringMacro	844
25.340.3.14	vtkTypeRevisionMacro	844
25.340.4	Member Data Documentation	844
25.340.4.1	FileName	844
25.340.4.2	MedicalImageProperties	844
25.340.4.3	RTStructSetProperties	844
25.341	vtkGDCMPolyDataWriter Class Reference	844
25.341.1	Detailed Description	846
25.341.2	Constructor & Destructor Documentation	846
25.341.2.1	vtkGDCMPolyDataWriter	846
25.341.2.2	~vtkGDCMPolyDataWriter	846

25.341.3	Member Function Documentation	846
25.341.3.1	InitializeRTStructSet	846
25.341.3.2	New	846
25.341.3.3	PrintSelf	846
25.341.3.4	SetMedicalImageProperties	846
25.341.3.5	SetNumberOfInputPorts	847
25.341.3.6	SetRTStructSetProperties	847
25.341.3.7	vtkTypeRevisionMacro	847
25.341.3.8	WriteData	847
25.341.3.9	WriteRTSTRUCTData	847
25.341.3.10	WriteRTSTRUCTInfo	847
25.341.4	Member Data Documentation	847
25.341.4.1	MedicalImageProperties	847
25.341.4.2	RTStructSetProperties	847
25.342	vtkGDCMTesting Class Reference	847
25.342.1	Detailed Description	848
25.342.2	Member Typedef Documentation	849
25.342.2.1	MD5MetalImagesType	849
25.342.3	Constructor & Destructor Documentation	849
25.342.3.1	vtkGDCMTesting	849
25.342.3.2	~vtkGDCMTesting	849
25.342.4	Member Function Documentation	849
25.342.4.1	GetGDCMDataRoot	849
25.342.4.2	GetMD5MetalImage	849
25.342.4.3	GetMHDMD5FromFile	849
25.342.4.4	GetNumberOfMD5MetalImages	849
25.342.4.5	GetRAWMD5FromFile	849
25.342.4.6	GetVTKDataRoot	849
25.342.4.7	New	849
25.342.4.8	PrintSelf	850
25.342.4.9	vtkTypeRevisionMacro	850
25.343	vtkGDCMThreadedImageReader Class Reference	850
25.343.1	Constructor & Destructor Documentation	851
25.343.1.1	vtkGDCMThreadedImageReader	852
25.343.1.2	~vtkGDCMThreadedImageReader	852
25.343.2	Member Function Documentation	852
25.343.2.1	ExecuteData	852

25.343.2.2ExecuteInformation	852
25.343.2.3New	852
25.343.2.4PrintSelf	852
25.343.2.5ReadFiles	852
25.343.2.6RequestDataCompat	852
25.343.2.7vtkBooleanMacro	852
25.343.2.8vtkGetMacro	852
25.343.2.9vtkSetMacro	852
25.343.2.10vtkSetMacro	852
25.343.2.11vtkSetMacro	852
25.343.2.12vtkTypeRevisionMacro	852
25.344.vtkGDCMThreadedImageReader2 Class Reference	852
25.344.1.Constructor & Destructor Documentation	854
25.344.1.1vtkGDCMThreadedImageReader2	854
25.344.1.2~vtkGDCMThreadedImageReader2	854
25.344.2.Member Function Documentation	854
25.344.2.1GetFileName	854
25.344.2.2New	854
25.344.2.3PrintSelf	854
25.344.2.4RequestInformation	854
25.344.2.5SetFileName	854
25.344.2.6SetFileNames	855
25.344.2.7SplitExtent	855
25.344.2.8ThreadedRequestData	855
25.344.2.9vtkBooleanMacro	855
25.344.2.10vtkBooleanMacro	855
25.344.2.11vtkBooleanMacro	855
25.344.2.12vtkGetMacro	855
25.344.2.13vtkGetMacro	855
25.344.2.14vtkGetMacro	855
25.344.2.15vtkGetMacro	855
25.344.2.16vtkGetMacro	855
25.344.2.17vtkGetMacro	855
25.344.2.18vtkGetMacro	855
25.344.2.19vtkGetMacro	855
25.344.2.20vtkGetObjectMacro	855
25.344.2.21vtkGetVector3Macro	855

25.344.2.21kGetVector3Macro	855
25.344.2.21kGetVector6Macro	855
25.344.2.24kSetMacro	855
25.344.2.25kSetMacro	855
25.344.2.26kSetMacro	855
25.344.2.27kSetMacro	855
25.344.2.28kSetMacro	855
25.344.2.29kSetMacro	855
25.344.2.30kSetMacro	855
25.344.2.31kSetVector3Macro	856
25.344.2.32kSetVector3Macro	856
25.344.2.33kSetVector6Macro	856
25.344.2.34kTypeRevisionMacro	856
25.345.1tkImageColorViewer Class Reference	856
25.345.1Detailed Description	859
25.345.2Member Enumeration Documentation	859
25.345.2.1anonymous enum	859
25.345.3Constructor & Destructor Documentation	859
25.345.3.1tkImageColorViewer	859
25.345.3.2~tkImageColorViewer	859
25.345.4Member Function Documentation	859
25.345.4.1AddInput	859
25.345.4.2AddInputConnection	859
25.345.4.3GetColorLevel	859
25.345.4.4GetColorWindow	859
25.345.4.5GetInput	859
25.345.4.6GetOffScreenRendering	859
25.345.4.7GetOverlayVisibility	859
25.345.4.8GetPosition	860
25.345.4.9GetSize	860
25.345.4.10GetSliceMax	860
25.345.4.10GetSliceMin	860
25.345.4.10GetSliceRange	860
25.345.4.10GetSliceRange	860
25.345.4.10GetSliceRange	860
25.345.4.10GetSliceRange	860
25.345.4.10GetWindowName	860
25.345.4.10stallPipeline	860

25.345.4.1New	860
25.345.4.1PrintSelf	860
25.345.4.1Render	860
25.345.4.2SetColorLevel	860
25.345.4.2SetColorWindow	860
25.345.4.2SetDisplayId	860
25.345.4.2SetInput	860
25.345.4.2SetInputConnection	860
25.345.4.2SetOffScreenRendering	860
25.345.4.2SetOverlayVisibility	860
25.345.4.2SetParentId	861
25.345.4.2SetPosition	861
25.345.4.2SetPosition	861
25.345.4.3SetRenderer	861
25.345.4.3SetRenderWindow	861
25.345.4.3SetSize	861
25.345.4.3SetSize	861
25.345.4.3SetSlice	861
25.345.4.3SetSliceOrientation	861
25.345.4.3SetSliceOrientationToXY	861
25.345.4.3SetSliceOrientationToXZ	861
25.345.4.3SetSliceOrientationToYZ	861
25.345.4.3SetupInteractor	861
25.345.4.4SetWindowId	862
25.345.4.4InstallPipeline	862
25.345.4.4UpdateDisplayExtent	862
25.345.4.4UpdateOrientation	862
25.345.4.4TK_LEGACY	862
25.345.4.4TK_LEGACY	862
25.345.4.4TK_LEGACY	862
25.345.4.4TK_LEGACY	862
25.345.4.4BooleanMacro	862
25.345.4.4GetMacro	862
25.345.4.5GetMacro	862
25.345.4.5tkGetObjectMacro	862
25.345.4.5tkGetObjectMacro	862
25.345.4.5tkGetObjectMacro	862

25.345.4.54	tkGetObjectMacro	862
25.345.4.55	tkGetObjectMacro	862
25.345.4.56	tkTypeRevisionMacro	862
25.345.5	Member Data Documentation	862
25.345.5.1	FirstRender	862
25.345.5.2	ImageActor	862
25.345.5.3	Interactor	862
25.345.5.4	InteractorStyle	862
25.345.5.5	OverlayImageActor	862
25.345.5.6	Renderer	862
25.345.5.7	RenderWindow	862
25.345.5.8	Slice	862
25.345.5.9	SliceOrientation	863
25.345.5.10	WindowLevel	863
25.346	tkImageMapToColors16 Class Reference	863
25.346.1	Constructor & Destructor Documentation	864
25.346.1.1	tkImageMapToColors16	864
25.346.1.2	~tkImageMapToColors16	864
25.346.2	Member Function Documentation	864
25.346.2.1	GetMTime	864
25.346.2.2	New	864
25.346.2.3	PrintSelf	865
25.346.2.4	RequestData	865
25.346.2.5	RequestInformation	865
25.346.2.6	SetLookupTable	865
25.346.2.7	SetOutputFormatToLuminance	865
25.346.2.8	SetOutputFormatToLuminanceAlpha	865
25.346.2.9	SetOutputFormatToRGB	865
25.346.2.10	SetOutputFormatToRGBA	865
25.346.2.11	ThreadedRequestData	865
25.346.2.12	tkBooleanMacro	865
25.346.2.13	tkGetMacro	865
25.346.2.14	tkGetMacro	865
25.346.2.15	tkGetMacro	865
25.346.2.16	tkGetObjectMacro	865
25.346.2.17	tkSetMacro	865
25.346.2.18	tkSetMacro	865

25.346.2.1	vtkSetMacro	865
25.346.2.2	vtkTypeRevisionMacro	865
25.346.3	Member Data Documentation	865
25.346.3.1	ActiveComponent	865
25.346.3.2	DataWasPassed	865
25.346.3.3	LookupTable	865
25.346.3.4	OutputFormat	865
25.346.3.5	PassAlphaToOutput	866
25.347	vtkImageMapToWindowLevelColors2 Class Reference	866
25.347.1	Constructor & Destructor Documentation	867
25.347.1.1	vtkImageMapToWindowLevelColors2	867
25.347.1.2	~vtkImageMapToWindowLevelColors2	867
25.347.2	Member Function Documentation	867
25.347.2.1	New	867
25.347.2.2	PrintSelf	867
25.347.2.3	RequestData	867
25.347.2.4	RequestInformation	867
25.347.2.5	ThreadedRequestData	867
25.347.2.6	vtkGetMacro	867
25.347.2.7	vtkGetMacro	867
25.347.2.8	vtkSetMacro	868
25.347.2.9	vtkSetMacro	868
25.347.2.10	vtkTypeRevisionMacro	868
25.347.3	Member Data Documentation	868
25.347.3.1	Level	868
25.347.3.2	Window	868
25.348	vtkImagePlanarComponentsToComponents Class Reference	868
25.348.1	Constructor & Destructor Documentation	869
25.348.1.1	vtkImagePlanarComponentsToComponents	869
25.348.1.2	~vtkImagePlanarComponentsToComponents	869
25.348.2	Member Function Documentation	869
25.348.2.1	New	869
25.348.2.2	PrintSelf	869
25.348.2.3	RequestData	870
25.348.2.4	vtkTypeRevisionMacro	870
25.349	vtkImageRGBToYBR Class Reference	870
25.349.1	Constructor & Destructor Documentation	871

25.349.1.1	vtkImageRGBToYBR	871
25.349.1.2	~vtkImageRGBToYBR	871
25.349.2	Member Function Documentation	871
25.349.2.1	New	871
25.349.2.2	PrintSelf	871
25.349.2.3	ThreadedExecute	871
25.349.2.4	vtkTypeRevisionMacro	871
25.350	vtkImageYBRToRGB Class Reference	871
25.350.1	Constructor & Destructor Documentation	873
25.350.1.1	vtkImageYBRToRGB	873
25.350.1.2	~vtkImageYBRToRGB	873
25.350.2	Member Function Documentation	873
25.350.2.1	New	873
25.350.2.2	PrintSelf	873
25.350.2.3	ThreadedExecute	873
25.350.2.4	vtkTypeRevisionMacro	873
25.351	vtkLookupTable16 Class Reference	873
25.351.1	Constructor & Destructor Documentation	874
25.351.1.1	vtkLookupTable16	874
25.351.1.2	~vtkLookupTable16	874
25.351.2	Member Function Documentation	874
25.351.2.1	Build	875
25.351.2.2	GetPointer	875
25.351.2.3	MapScalarsThroughTable2	875
25.351.2.4	New	875
25.351.2.5	PrintSelf	875
25.351.2.6	SetNumberOfTableValues	875
25.351.2.7	vtkTypeRevisionMacro	875
25.351.2.8	WritePointer	875
25.351.3	Member Data Documentation	875
25.351.3.1	Table16	875
25.352	vtkRTStructSetProperties Class Reference	875
25.352.1	Detailed Description	877
25.352.2	Constructor & Destructor Documentation	877
25.352.2.1	vtkRTStructSetProperties	877
25.352.2.2	~vtkRTStructSetProperties	877
25.352.3	Member Function Documentation	877

25.352.3.1AddContourReferencedFrameOfReference	878
25.352.3.2AddReferencedFrameOfReference	878
25.352.3.3AddStructureSetROI	878
25.352.3.4AddStructureSetROIObservation	878
25.352.3.5Clear	878
25.352.3.6DeepCopy	878
25.352.3.7GetContourReferencedFrameOfReferenceClassUID	878
25.352.3.8GetContourReferencedFrameOfReferenceInstanceUID	878
25.352.3.9GetNumberOfContourReferencedFrameOfReferences	878
25.352.3.10GetNumberOfContourReferencedFrameOfReferences	878
25.352.3.10GetNumberOfReferencedFrameOfReferences	878
25.352.3.10GetNumberOfStructureSetROIs	878
25.352.3.10GetReferencedFrameOfReferenceClassUID	878
25.352.3.10GetReferencedFrameOfReferenceInstanceUID	878
25.352.3.10GetStructureSetObservationNumber	878
25.352.3.10GetStructureSetROIDescription	878
25.352.3.10GetStructureSetROIGenerationAlgorithm	878
25.352.3.10GetStructureSetROIName	878
25.352.3.10GetStructureSetROINumber	878
25.352.3.20GetStructureSetROIObservationLabel	878
25.352.3.20GetStructureSetROIRefFrameRefUID	878
25.352.3.20GetStructureSetRTROIInterpretedType	878
25.352.3.21New	879
25.352.3.21PrintSelf	879
25.352.3.26kGetStringMacro	879
25.352.3.26kGetStringMacro	879
25.352.3.27kGetStringMacro	879
25.352.3.28kGetStringMacro	879
25.352.3.28kGetStringMacro	879
25.352.3.30kGetStringMacro	879
25.352.3.31kGetStringMacro	879
25.352.3.32kGetStringMacro	879
25.352.3.32kGetStringMacro	879
25.352.3.34kSetStringMacro	879
25.352.3.35kSetStringMacro	879
25.352.3.36kSetStringMacro	879
25.352.3.37kSetStringMacro	879

25.352.3.38kSetStringMacro	879
25.352.3.39kSetStringMacro	879
25.352.3.40kSetStringMacro	879
25.352.3.41kSetStringMacro	879
25.352.3.42kSetStringMacro	879
25.352.3.43kTypeRevisionMacro	879
25.352.4Member Data Documentation	879
25.352.4.1Internals	879
25.352.4.2ReferenceFrameOfReferenceUID	879
25.352.4.3ReferenceSeriesInstanceUID	880
25.352.4.4SeriesInstanceUID	880
25.352.4.5SOPInstanceUID	880
25.352.4.6StructureSetDate	880
25.352.4.7StructureSetLabel	880
25.352.4.8StructureSetName	880
25.352.4.9StructureSetTime	880
25.352.4.10StudyInstanceUID	880
25.353dcm::Waveform Class Reference	880
25.353.1Detailed Description	880
25.353.2Constructor & Destructor Documentation	880
25.353.2.1Waveform	880
25.354dcm::Writer Class Reference	880
25.354.1Detailed Description	883
25.354.2Constructor & Destructor Documentation	884
25.354.2.1Writer	884
25.354.2.2~Writer	884
25.354.3Member Function Documentation	884
25.354.3.1CheckFileMetaInformationOff	884
25.354.3.2CheckFileMetaInformationOn	884
25.354.3.3GetFile	884
25.354.3.4GetStreamPtr	884
25.354.3.5SetCheckFileMetaInformation	884
25.354.3.6SetFile	884
25.354.3.7SetFileName	885
25.354.3.8SetStream	885
25.354.3.9SetWriteDataSetOnly	885
25.354.3.10Write	885

25.354.4Friends And Related Function Documentation	885
25.354.4.1StreamImageWriter	885
25.354.5Member Data Documentation	885
25.354.5.1Ofstream	885
25.354.5.2Stream	885
25.355gdcmm::XMLDictReader Class Reference	886
25.355.1Detailed Description	887
25.355.2Constructor & Destructor Documentation	887
25.355.2.1XMLDictReader	887
25.355.2.2~XMLDictReader	887
25.355.3Member Function Documentation	887
25.355.3.1CharacterDataHandler	887
25.355.3.2EndElement	887
25.355.3.3GetDict	887
25.355.3.4HandleDescription	887
25.355.3.5HandleEntry	887
25.355.3.6StartElement	887
25.356gdcmm::XMLPrivateDictReader Class Reference	887
25.356.1Detailed Description	888
25.356.2Constructor & Destructor Documentation	889
25.356.2.1XMLPrivateDictReader	889
25.356.2.2~XMLPrivateDictReader	889
25.356.3Member Function Documentation	889
25.356.3.1CharacterDataHandler	889
25.356.3.2EndElement	889
25.356.3.3GetPrivateDict	889
25.356.3.4HandleDescription	889
25.356.3.5HandleEntry	889
25.356.3.6StartElement	889
26 File Documentation	891
26.1 gdcmm2pnm.man File Reference	891
26.2 gdcmm2vtk.man File Reference	891
26.3 gdcmmAAbortPDU.h File Reference	891
26.4 gdcmmAAssociateACPDU.h File Reference	892
26.5 gdcmmAAssociateRJPDU.h File Reference	893
26.6 gdcmmAAssociateRQPDU.h File Reference	894

26.7 gdcAbstractSyntax.h File Reference	894
26.8 gdcmanon.man File Reference	896
26.9 gdcAnonymizeEvent.h File Reference	896
26.10gdcAnonymizer.h File Reference	897
26.11gdcApplicationContext.h File Reference	898
26.12gdcApplicationEntity.h File Reference	899
26.13gdcARReleaseRPPDU.h File Reference	899
26.14gdcARReleaseRQPDU.h File Reference	900
26.15gdcARTIMTimer.h File Reference	902
26.16gdcASN1.h File Reference	903
26.17gdcAsynchronousOperationsWindowSub.h File Reference	904
26.18gdcAttribute.h File Reference	905
26.19gdcAudioCodec.h File Reference	906
26.20gdcBase64.h File Reference	907
26.21gdcBaseCompositeMessage.h File Reference	907
26.22gdcBasePDU.h File Reference	909
26.23gdcBaseRootQuery.h File Reference	910
26.24gdcBasicOffsetTable.h File Reference	911
26.25gdcBitmap.h File Reference	912
26.26gdcBitmapToBitmapFilter.h File Reference	913
26.27gdcBoxRegion.h File Reference	914
26.28gdcByteBuffer.h File Reference	915
26.29gdcByteSwap.h File Reference	917
26.30gdcByteSwapFilter.h File Reference	917
26.31gdcByteValue.h File Reference	918
26.32gdcCEchoMessages.h File Reference	919
26.33gdcCFindMessages.h File Reference	920
26.34gdcCMoveMessages.h File Reference	921
26.35gdcCodec.h File Reference	922
26.36gdcCoder.h File Reference	923
26.37gdcCodeString.h File Reference	925
26.38gdcCommand.h File Reference	925
26.39gdcCommandDataSet.h File Reference	927
26.40gdcCompositeMessageFactory.h File Reference	928
26.41gdcCompositeNetworkFunctions.h File Reference	928
26.42gdcConstCharWrapper.h File Reference	929
26.43gdcconv.man File Reference	930

26.44gdcmlCP246ExplicitDataElement.h File Reference	930
26.45gdcmlCryptographicMessageSyntax.h File Reference	930
26.46gdcmlCSAElement.h File Reference	931
26.47gdcmlCSAHeader.h File Reference	933
26.48gdcmlCSAHeaderDict.h File Reference	934
26.49gdcmlCSAHeaderDictEntry.h File Reference	935
26.50gdcmlCStoreMessages.h File Reference	936
26.51gdcmlCurve.h File Reference	937
26.52gdcmlDataElement.h File Reference	939
26.53gdcmlDataEvent.h File Reference	940
26.54gdcmlDataSet.h File Reference	941
26.55gdcmlDataSetEvent.h File Reference	942
26.56gdcmlDataSetHelper.h File Reference	942
26.57gdcmlDecoder.h File Reference	943
26.58gdcmlDefinedTerms.h File Reference	945
26.59gdcmlDeflateStream.h File Reference	945
26.60gdcmlDefs.h File Reference	946
26.61gdcmlDeltaEncodingCodec.h File Reference	947
26.62gdcmlDICOMDIR.h File Reference	948
26.63gdcmlDICOMDIRGenerator.h File Reference	949
26.64gdcmlDict.h File Reference	950
26.65gdcmlDictConverter.h File Reference	952
26.66gdcmlDictEntry.h File Reference	952
26.67gdcmlDictPrinter.h File Reference	954
26.68gdcmlDicts.h File Reference	954
26.69gdcmldiff.man File Reference	956
26.70gdcmlDIMSE.h File Reference	956
26.71gdcmlDirectionCosines.h File Reference	957
26.72gdcmlDirectory.h File Reference	957
26.73gdcmlDirectoryHelper.h File Reference	958
26.74gdcmlDummyValueGenerator.h File Reference	959
26.75gdcmldump.man File Reference	960
26.76gdcmlDumper.h File Reference	960
26.77gdcmlElement.h File Reference	961
26.78gdcmlEncapsulatedDocument.h File Reference	963
26.79gdcmlEnumeratedValues.h File Reference	964
26.80gdcmlEvent.h File Reference	964

26.80.1 Macro Definition Documentation	966
26.80.1.1 gdcmlEventMacro	966
26.81gdcmlException.h File Reference	966
26.82gdcmlExplicitDataElement.h File Reference	967
26.83gdcmlExplicitImplicitDataElement.h File Reference	968
26.84gdcmlFiducials.h File Reference	969
26.85gdcmlFile.h File Reference	970
26.86gdcmlFileAnonymizer.h File Reference	971
26.87gdcmlFileDerivation.h File Reference	972
26.88gdcmlFileExplicitFilter.h File Reference	972
26.89gdcmlFileMetaInformation.h File Reference	973
26.90gdcmlFilename.h File Reference	974
26.91gdcmlFilenameGenerator.h File Reference	975
26.92gdcmlFileSet.h File Reference	976
26.93gdcmlFindPatientRootQuery.h File Reference	978
26.94gdcmlFindStudyRootQuery.h File Reference	979
26.95gdcmlFragment.h File Reference	979
26.96gdcmlgendir.man File Reference	981
26.97gdcmlGlobal.h File Reference	981
26.98gdcmlGroupDict.h File Reference	982
26.99gdcmlIconImage.h File Reference	983
26.100gdcmlIconImageFilter.h File Reference	984
26.101gdcmlIconImageGenerator.h File Reference	984
26.102gdcmlImage.h File Reference	985
26.103gdcmlImageApplyLookupTable.h File Reference	987
26.104gdcmlImageChangePhotometricInterpretation.h File Reference	987
26.105gdcmlImageChangePlanarConfiguration.h File Reference	988
26.106gdcmlImageChangeTransferSyntax.h File Reference	989
26.107gdcmlImageCodec.h File Reference	990
26.108gdcmlImageConverter.h File Reference	991
26.109gdcmlImageFragmentSplitter.h File Reference	992
26.110gdcmlImageHelper.h File Reference	993
26.111gdcmlImageReader.h File Reference	994
26.112gdcmlImageRegionReader.h File Reference	996
26.113gdcmlImageToImageFilter.h File Reference	996
26.114gdcmlImageWriter.h File Reference	997
26.115gdcmlimg.man File Reference	998

26.110dcmImplementationClassUIDSub.h File Reference	998
26.117dcmImplementationUIDSub.h File Reference	1000
26.119dcmImplementationVersionNameSub.h File Reference	1000
26.119dcmImplicitDataElement.h File Reference	1002
26.120dcmInfo.man File Reference	1002
26.124dcmIOD.h File Reference	1003
26.129dcmIODEntry.h File Reference	1005
26.129dcmIODs.h File Reference	1007
26.124dcmIPPSorter.h File Reference	1008
26.125dcmItem.h File Reference	1009
26.126dcmJPEG12Codec.h File Reference	1010
26.127dcmJPEG16Codec.h File Reference	1011
26.129dcmJPEG2000Codec.h File Reference	1012
26.129dcmJPEG8Codec.h File Reference	1012
26.130dcmJPEGCodec.h File Reference	1013
26.134dcmJPEGLSCodec.h File Reference	1015
26.139dcmKAKADUCodec.h File Reference	1015
26.139dcmLegacyMacro.h File Reference	1016
26.133.1Macro Definition Documentation	1017
26.133.1.1GDCM_LEGACY	1017
26.133.1.2GDCM_LEGACY_BODY	1017
26.133.1.3GDCM_LEGACY_REPLACED_BODY	1017
26.134dcmLO.h File Reference	1017
26.135dcmLookupTable.h File Reference	1018
26.136dcmMacro.h File Reference	1019
26.137dcmMacroEntry.h File Reference	1022
26.137.1Macro Definition Documentation	1023
26.137.1.1GDCMMACROENTRY_H	1023
26.139dcmMacros.h File Reference	1023
26.139dcmMaximumLengthSub.h File Reference	1025
26.140dcmMD5.h File Reference	1026
26.144dcmMediaStorage.h File Reference	1027
26.149dcmMeshPrimitive.h File Reference	1029
26.149dcmModule.h File Reference	1030
26.144dcmModuleEntry.h File Reference	1032
26.145dcmModules.h File Reference	1034
26.146dcmMovePatientRootQuery.h File Reference	1035

26.147	dcmMoveStudyRootQuery.h File Reference	1036
26.148	dcmNestedModuleEntries.h File Reference	1037
26.149	dcmNetworkEvents.h File Reference	1039
26.150	dcmNetworkStateID.h File Reference	1040
26.151	dcmObject.h File Reference	1041
26.152	dcmOrientation.h File Reference	1042
26.153	dcmOverlay.h File Reference	1043
26.154	dcmParseException.h File Reference	1044
26.155	dcmParser.h File Reference	1045
26.156	dcmPatient.h File Reference	1046
26.157	dcmPDataTFPDU.h File Reference	1046
26.158	dcmPDBElement.h File Reference	1047
26.159	dcmPDBHeader.h File Reference	1049
26.160	dcmpdf.man File Reference	1049
26.161	dcmPDFCodec.h File Reference	1050
26.162	dcmPDUFactory.h File Reference	1050
26.163	dcmPersonName.h File Reference	1051
26.164	dcmPGXCodec.h File Reference	1052
26.165	dcmPhotometricInterpretation.h File Reference	1053
26.166	dcmPixelFormat.h File Reference	1054
26.167	dcmPixmap.h File Reference	1056
26.168	dcmPixmapReader.h File Reference	1057
26.169	dcmPixmapToPixmapFilter.h File Reference	1058
26.170	dcmPixmapWriter.h File Reference	1059
26.171	dcmPNMCodec.h File Reference	1060
26.172	dcmPreamble.h File Reference	1061
26.173	dcmPresentationContext.h File Reference	1062
26.174	dcmPresentationContextAC.h File Reference	1063
26.175	dcmPresentationContextGenerator.h File Reference	1064
26.176	dcmPresentationContextRQ.h File Reference	1065
26.177	dcmPresentationDataValue.h File Reference	1066
26.178	dcmPrinter.h File Reference	1067
26.179	dcmPrivateTag.h File Reference	1068
26.180	dcmProgressEvent.h File Reference	1069
26.181	dcmPVRGCodec.h File Reference	1070
26.182	dcmPythonFilter.h File Reference	1071
26.183	dcmQueryBase.h File Reference	1072

26.184	dcmQueryFactory.h File Reference	1074
26.185	dcmQueryImage.h File Reference	1075
26.186	dcmQueryPatient.h File Reference	1076
26.187	dcmQuerySeries.h File Reference	1077
26.188	dcmQueryStudy.h File Reference	1078
26.189	dcmraw.man File Reference	1079
26.190	dcmRAWCodec.h File Reference	1079
26.191	dcmReader.h File Reference	1080
26.192	dcmRegion.h File Reference	1081
26.193	dcmRescaler.h File Reference	1082
26.194	dcmRLECodec.h File Reference	1083
26.195	dcmRoleSelectionSub.h File Reference	1084
26.196	dcmScanner.h File Reference	1084
26.197	dcmscanner.man File Reference	1085
26.198	dcmscu.man File Reference	1086
26.199	dcmSegment.h File Reference	1086
26.200	dcmSegmentedPaletteColorLookupTable.h File Reference	1087
26.201	dcmSegmentHelper.h File Reference	1088
26.202	dcmSegmentReader.h File Reference	1089
26.203	dcmSegmentWriter.h File Reference	1090
26.204	dcmSequenceOfFragments.h File Reference	1092
26.205	dcmSequenceOfItems.h File Reference	1092
26.206	dcmSerieHelper.h File Reference	1093
26.207	dcmSeries.h File Reference	1095
26.208	dcmServiceClassApplicationInformation.h File Reference	1096
26.209	dcmServiceClassUser.h File Reference	1098
26.210	dcmSHA1.h File Reference	1098
26.211	dcmSimpleSubjectWatcher.h File Reference	1099
26.212	dcmSmartPointer.h File Reference	1100
26.213	dcmSOPClassExtendedNegociationSub.h File Reference	1101
26.214	dcmSOPClassUIDToIOD.h File Reference	1102
26.215	dcmSorter.h File Reference	1103
26.216	dcmSpacing.h File Reference	1105
26.217	dcmSpectroscopy.h File Reference	1105
26.218	dcmSplitMosaicFilter.h File Reference	1106
26.219	dcmStaticAssert.h File Reference	1107
26.219.1	Macro Definition Documentation	1108

26.219.1.1GDCM_DO_JOIN	1108
26.219.1.2GDCM_DO_JOIN2	1108
26.219.1.3GDCM_JOIN	1108
26.219.1.4GDCM_STATIC_ASSERT	1108
26.220dcmStreamImageReader.h File Reference	1109
26.221dcmStreamImageWriter.h File Reference	1109
26.222dcmString.h File Reference	1110
26.223dcmStringFilter.h File Reference	1111
26.224dcmStudy.h File Reference	1112
26.225dcmSubject.h File Reference	1114
26.226dcmSurface.h File Reference	1115
26.227dcmSurfaceHelper.h File Reference	1116
26.228dcmSurfaceReader.h File Reference	1117
26.229dcmSurfaceWriter.h File Reference	1117
26.230dcmSwapCode.h File Reference	1118
26.231dcmSwapper.h File Reference	1119
26.232dcmSystem.h File Reference	1120
26.233dcmTable.h File Reference	1121
26.234dcmTableEntry.h File Reference	1122
26.235dcmTableReader.h File Reference	1124
26.236dcmTag.h File Reference	1125
26.237dcmTagPath.h File Reference	1126
26.238dcmTagToVR.h File Reference	1127
26.239dcmtar.man File Reference	1127
26.240dcmTerminal.h File Reference	1127
26.241dcmTestDriver.h File Reference	1128
26.242dcmTesting.h File Reference	1129
26.243dcmTrace.h File Reference	1130
26.243.1Macro Definition Documentation	1131
26.243.1.1GDCM_FUNCTION	1131
26.243.1.2dcmAssertAlwaysMacro	1131
26.243.1.3dcmAssertMacro	1131
26.243.1.4dcmDebugMacro	1132
26.243.1.5dcmErrorMacro	1132
26.243.1.6dcmWarningMacro	1132
26.244dcmTransferSyntax.h File Reference	1133
26.245dcmTransferSyntaxSub.h File Reference	1134

26.246dcmType.h File Reference	1135
26.247dcmTypes.h File Reference	1137
26.248dcmUIDGenerator.h File Reference	1137
26.249dcmUIDs.h File Reference	1138
26.250dcmULAction.h File Reference	1140
26.251dcmULActionAA.h File Reference	1141
26.252dcmULActionAE.h File Reference	1141
26.253dcmULActionAR.h File Reference	1142
26.254dcmULActionDT.h File Reference	1143
26.255dcmULBasicCallback.h File Reference	1144
26.256dcmULConnection.h File Reference	1145
26.257dcmULConnectionCallback.h File Reference	1146
26.258dcmULConnectionInfo.h File Reference	1147
26.259dcmULConnectionManager.h File Reference	1149
26.260dcmULEvent.h File Reference	1150
26.261dcmULTransitionTable.h File Reference	1151
26.262dcmULWritingCallback.h File Reference	1152
26.263dcmUNExplicitDataElement.h File Reference	1153
26.264dcmUNExplicitImplicitDataElement.h File Reference	1153
26.265dcmUnpacker12Bits.h File Reference	1154
26.266dcmUsage.h File Reference	1155
26.267dcmUserInformation.h File Reference	1157
26.268dcmValidate.h File Reference	1158
26.269dcmValue.h File Reference	1159
26.270dcmValueIO.h File Reference	1159
26.271dcmVersion.h File Reference	1160
26.272dcmviewer.man File Reference	1161
26.273dcmVL.h File Reference	1161
26.274dcmVM.h File Reference	1162
26.274.1Macro Definition Documentation	1164
26.274.1.1TYPETOLENGTH	1164
26.275dcmVR.h File Reference	1164
26.275.1Macro Definition Documentation	1166
26.275.1.1TYPETOENCODING	1166
26.275.1.2VRTypeTemplateCase	1166
26.276dcmVR16ExplicitDataElement.h File Reference	1166
26.277dcmWaveform.h File Reference	1167

26.270	dcmWin32.h File Reference	1167
26.278.1	Macro Definition Documentation	1168
26.278.1.1	IGDCM_EXPORT	1168
26.279	dcmWriter.h File Reference	1168
26.280	dcmXMLDictReader.h File Reference	1169
26.281	dcmXMLPrivateDictReader.h File Reference	1169
26.282	README.txt File Reference	1170
26.283	TestsList.txt File Reference	1170
26.284.1	tkGDCMImageReader.h File Reference	1170
26.284.1	Macro Definition Documentation	1172
26.284.1.1	VTK_CMYK	1172
26.284.1.2	VTK_INVERSE_LUMINANCE	1172
26.284.1.3	VTK_LOOKUP_TABLE	1172
26.284.1.4	VTK_YBR	1172
26.285	tkGDCMImageWriter.h File Reference	1172
26.286	tkGDCMMedicalImageProperties.h File Reference	1172
26.287	tkGDCMPolyDataReader.h File Reference	1173
26.288	tkGDCMPolyDataWriter.h File Reference	1174
26.289	tkGDCMTesting.h File Reference	1175
26.290	tkGDCMThreadedImageReader.h File Reference	1175
26.291	tkGDCMThreadedImageReader2.h File Reference	1176
26.292	tkImageColorViewer.h File Reference	1176
26.293	tkImageMapToColors16.h File Reference	1177
26.294	tkImageMapToWindowLevelColors2.h File Reference	1177
26.295	tkImagePlanarComponentsToComponents.h File Reference	1178
26.296	tkImageRGBToYBR.h File Reference	1178
26.297	tkImageYBRToRGB.h File Reference	1179
26.298	tkLookupTable16.h File Reference	1179
26.299	tkRTStructSetProperties.h File Reference	1180
27	Example Documentation	1181
27.1	AWTMedical3.java	1181
27.2	BasicAnonymizer.cs	1185
27.3	BasicImageAnonymizer.cs	1186
27.4	CastConvertPhilips.py	1188
27.5	ChangeSequenceUltrasound.cxx	1190
27.6	CheckBigEndianBug.cxx	1191

27.7 ClinicalTrialAnnotate.cxx	1193
27.8 ClinicalTrialIdentificationWorkflow.cs	1194
27.9 CompressImage.cxx	1197
27.10CompressLossyJPEG.cs	1198
27.11Convert16BitsTo8Bits.cxx	1199
27.12ConvertMPL.py	1200
27.13ConvertMultiFrameToSingleFrame.cxx	1201
27.14ConvertNumpy.py	1202
27.15ConvertPIL.py	1203
27.16ConvertRGBToLuminance.cxx	1204
27.17ConvertSingleBitTo8Bits.cxx	1205
27.18ConvertToQImage.cxx	1206
27.19CreateARGBImage.cxx	1208
27.20CreateCMYKImage.cxx	1209
27.21CreateJPIPDataSet.cxx	1210
27.22CreateRAWStorage.py	1211
27.23csa2img.cxx	1213
27.24CStoreQtProgress.cxx	1215
27.25DecompressImage.cs	1217
27.26DecompressImage.java	1218
27.27DecompressImage.py	1219
27.28DecompressImageMultiframe.cs	1220
27.29DecompressJPEGFile.cs	1222
27.30DecompressPixmap.java	1223
27.31DiffFile.cxx	1224
27.32DiscriminateVolume.cxx	1225
27.33DumbAnonymizer.py	1229
27.34DumpADAC.cxx	1230
27.35DumpGEMSMovieGroup.cxx	1235
27.36DumpImageHeaderInfo.cxx	1241
27.37DumpToSQLITE3.cxx	1243
27.38DuplicatePCDE.cxx	1245
27.39ELSCINT1WaveToText.cxx	1247
27.40EncapsulateFileInRawData.cxx	1249
27.41ExtractEncapsulatedFile.cs	1250
27.42ExtractEncryptedContent.cxx	1251
27.43ExtractIconFromFile.cxx	1252

27.44ExtractImageRegion.cs	1253
27.45ExtractImageRegionWithLUT.cs	1255
27.46Extracting_All_Resolution.cxx	1256
27.47ExtractOneFrame.cs	1262
27.48Fake_Image_Using_Stream_Image_Writer.cxx	1263
27.49FileAnonymize.cs	1266
27.50FileAnonymize.java	1267
27.51FindAllPatientName.py	1268
27.52FixBrokenJ2K.cxx	1268
27.53FixCommaBug.py	1270
27.54FixJAIBugJPEGLS.cxx	1271
27.55gdcmortoplanes.cxx	1274
27.56gdcmrlice.cxx	1280
27.57gdcmrionplan.cxx	1282
27.58gdcmrtpplan.cxx	1286
27.59gdcmscene.cxx	1289
27.60gdcmttexture.cxx	1291
27.61gdcmvolume.cxx	1293
27.62GenAllIVR.cxx	1294
27.63GenerateDICOMDIR.cs	1296
27.64GenerateRTSTRUCT.cxx	1297
27.65GenerateStandardSOPClasses.cxx	1300
27.66GenFakeIdentifyFile.cxx	1301
27.67GenFakeImage.cxx	1303
27.68GenLongSeqs.cxx	1305
27.69GenSeqs.cxx	1306
27.70GetArray.cs	1307
27.71GetJPEGSamplePrecision.cxx	1309
27.72GetPortionCSAHeader.py	1310
27.73GetSequenceUltrasound.cxx	1311
27.74GetSubSequenceData.cxx	1313
27.75headsq2dcm.py	1316
27.76HelloActiviz.cs	1316
27.77HelloActiviz2.cs	1318
27.78HelloActiviz3.cs	1319
27.79HelloActiviz4.cs	1320
27.80HelloActiviz5.cs	1320

27.81HelloSimple.java	1322
27.82HelloVizWorld.cxx	1322
27.83HelloVTKWorld.cs	1323
27.84HelloVTKWorld.java	1324
27.85HelloVTKWorld2.cs	1325
27.86HelloWorld.cxx	1326
27.87HelloWorld.py	1327
27.88iU22tomultisc.cxx	1328
27.89LargeVRDSExplicit.cxx	1329
27.90MagnifyFile.cxx	1332
27.91ManipulateFile.cs	1332
27.92ManipulateFile.py	1333
27.93ManipulateSequence.py	1335
27.94MergeFile.py	1336
27.95MergeTwoFiles.cxx	1337
27.96MetalImageMD5Activiz.cs	1338
27.97MIPViewer.java	1339
27.98MPRViewer.java	1342
27.99MPRViewer2.java	1344
27.10MrProtocol.cxx	1348
27.10NewSequence.cs	1355
27.10NewSequence.py	1356
27.10ffscreenimage.cxx	1357
27.10PatchFile.cxx	1358
27.10PhilipsPrivateRescaleInterceptSlope.py	1359
27.10PlaySound.py	1360
27.10pmsct_rgb1.cxx	1362
27.10PrivateDict.py	1365
27.10PublicDict.cxx	1365
27.10ReadAndDumpDICOMDIR.cxx	1366
27.11ReadAndDumpDICOMDIR.py	1369
27.11ReadAndPrintAttributes.cxx	1372
27.11ReadExplicitLengthSQIVR.cxx	1373
27.11ReadFiles.java	1374
27.11ReadGEMSSDO.cxx	1375
27.11ReadMultiTimesException.cxx	1378
27.11ReadSeriesIntoVTK.java	1378

27.118	ReadUTF8QtDir.cxx	1380
27.119	RefCounting.cs	1381
27.120	ReformatFile.cs	1382
27.121	RemovePrivateTags.py	1383
27.122	RescaleImage.cs	1384
27.123	Reslicesphere.cxx	1385
27.124	ReWriteSCAsMR.py	1393
27.125	Re2img.cxx	1394
27.126	structapp.cxx	1396
27.127	ScanDirectory.cs	1398
27.128	ScanDirectory.java	1399
27.129	ScanDirectory.py	1402
27.130	SendFileSCU.cs	1403
27.131	SimplePrint.cs	1404
27.132	SimplePrintPatientName.cs	1405
27.133	SimpleScanner.cxx	1406
27.134	SortImage.cxx	1407
27.135	SortImage.py	1409
27.136	SortImage2.cs	1409
27.137	StandardizeFiles.cs	1410
27.138	StreamImageReaderTest.cxx	1411
27.139	TestByteSwap.cxx	1415
27.140	TestReader.cxx	1417
27.141	TestReader.py	1418
27.142	hreadgdcm.cxx	1419
27.143	TraverseModules.cxx	1422
27.144	uid_unique.cxx	1423
27.145	VolumeSorter.cxx	1424
27.146	WriteBuffer.py	1426

Chapter 1

GDCM Documentation

This is the developers documentation.

A PDF version of this doxygen documentation can be found here:

<http://gdcm.sourceforge.net/2.2/gdcm-2.2.4.pdf>

A tarball version of this HTML doxygen documentation can be found here:

<http://gdcm.sourceforge.net/2.2/gdcm-2.2.4-doc.tar.gz>

Author

Mathieu Malaterre

Chapter 2

off-screen rendering of DICOM images

2.1 SYNOPSIS

```
gdcm2pnm [options] file-in bitmap-out
```

2.2 DESCRIPTION

The **gdcm2pnm** command line program takes as input a DICOM file and produces a rendered bitmap file.

2.3 PARAMETERS

file-in DICOM input filename

bitmap-out Bitmap output filename

2.4 options

2.4.1 options

2.4.2 general options

```
-h    --help  
      print this help text and exit  
  
-v    --version  
      print version information and exit  
  
-V    --verbose  
      verbose mode (warning+error).  
  
-W    --warning  
      warning mode, print warning information
```

```
-E  --error  
    error mode, print error information  
  
-D  --debug  
    debug mode, print debug information
```

2.5 Simple usage

gdcm2pnm will take as input DICOM and render it into a bitmap file using the window/level attributes value.

```
$ gdcm2pnm input.dcm output.png
```

It is much different from the **gdcmraw** or **gdcmimg** command line tool as it will render a DICOM image. This means that the output will be rendered in 8bits ready for display.

2.6 SEE ALSO

gdcm2vtk(1), **gdcmimg(1)**

2.7 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 3

Convert a file supported by VTK into DICOM.

3.1 SYNOPSIS

```
gdcm2vtk [options] file-in file-out
```

3.2 DESCRIPTION

The **gdcm2vtk** takes as input any file supported by VTK (including DICOM file) and will generate as output a DICOM file.

3.3 PARAMETERS

file-in input filename (DICOM or VTK supported)

file-out DICOM output filename

3.4 options

3.4.1 options

--force-rescale	force rescale.
--force-spacing	force spacing.
--palette-color	when supported generate a PALETTE COLOR file.
--argb	when supported generate a ARGB file.
--compress	when supported generate a compressed file.
--use-vtkdicom	Use vtkDICOMImageReader (instead of GDCM).
--modality	set Modality.
--lower-left	set lower left.
--shift	set shift.
--scale	set scale.
--compress	set compression (MetaIO).
-T --study-uid	Study UID.
-S --series-uid	Series UID.
--root-uid	Root UID.

3.4.2 compression options

```
-J --jpeg          Compress image in jpeg.
-K --j2k          Compress image in j2k.
-L --jpegls       Compress image in jpeg-ls.
-R --rle          Compress image in rle (lossless only).
```

3.4.3 general options

```
-h  --help          print this help text and exit
-v  --version       print version information and exit
-V  --verbose       verbose mode (warning+error).
-W  --warning       warning mode, print warning information
-E  --error         error mode, print error information
-D  --debug         debug mode, print debug information
```

3.4.4 environment variable

```
GDCM_ROOT_UID Root UID
```

3.5 DESCRIPTION

Convert a file supported by VTK into DICOM.

Typical usage is:

```
$ gdcmm2vtk inputfile output.dcm
```

It uses the internal factory mechanism of VTK to recognize a file (CanRead function). See VTK supported file here:

What image file formats can VTK read and write? http://www.vtk.org/Wiki/VTK_FAQ#What_image_file_formats_can_VTK

If your input file has 4 components, the 4th comp (alpha) will be removed from the output file as DICOM does not support alpha component anymore (see `--argb` option).

Special care was taken for the following file format:

1. DICOM: Direction Cosines and `vtkMedicalImageInformation` are passed to the output
2. BMP: The file can be saved with a Lookup Table (see `--palette-color`)
3. GE Signa: `vtkMedicalImageProperties` is passed to the output
4. MINC: Direction Cosines is passed to the output
5. TIFF: `vtkTIFFReader` is currently in bad shape in VTK (different behavior in VTK 5.2 and CVS). Only use it,

3.5.1 CONVERT MetaImage (mhd, mha)

```
$ gdcmm2vtk inputfile output.mha
```


This command will convert the input DICOM file: inputfile into a MetaImage .mha file. Same goes for .mhd file.

3.5.2 CONVERT MHA/MHD

```
$ gdc2vtk inputfile output.mha
```

or

```
$ gdc2vtk inputfile output.mhd
```

This command will convert the input DICOM file: inputfile into a MetaImageData .mha/.mhd file.

3.5.3 CONVERT VTI

```
$ gdc2vtk inputfile output.vti
```

This command will convert the input DICOM file: inputfile into a XML VTK ImageData .vti file.

3.5.4 CONVERT VTK

```
$ gdc2vtk inputfile output.vtk
```

This command will convert the input DICOM file: inputfile into an old VTK Structured PointSets .vtk file.

3.6 CONVERT DICOM

```
$ gdc2vtk input.dcm output.dcm
```

[vtkGDCMImageReader](#) will be used to read in a DICOM file, not the default `vtkDICOMImageReader`. See option `--use-vtkdicom` to use `vtkDICOMImageReader`.

3.7 RoundTrip DICOM to MHD to DICOM

```
$ gdc2vtk input_ybr.dcm output.mhd
$ gdc2vtk --modality US --imageformat 7 output.mhd output.dcm
```

The above section shows how to convert a DICOM using the Photometric Interpretation of YBR_FULL (or even YBR_FULL_422 is lossy) into another file format: MetaImage (mhd). Since this file format does not handle color space, we have to explicitly set it using the `--imageformat` command line option. The `--modality` command line option is required in this case since the default Secondary Capture Image Storage Class family does not allow for YBR Photometric Interpretation.

3.8 gdc2vtk notes

IMPORTANT NOTE: The internal VTK structured will be filled from the input DICOM, and then pass to the output DICOM writer. Some information might be lost during the conversion DICOM to VTK to DICOM. This option is mostly used to test the `vtkGDCMImageReader/vtkGDCMImageWriter` combination.

IMPORTANT NOTE: When converting from a lossy format such as JPEG, the information of lossiness is important. The output DICOM will contains the required Lossy Image Compression attribute that indicates that image was lossy-compressed somewhere along the pipeline. See also `gdcmimg` (better handling of JPEG in general).

IMPORTANT NOTE: When using `-use-vtkdicom` the output DICOM file will always be written as MR Image Storage as this information is not available from the reader itself. This allow setting the Image Orientation (Patient) properly.

3.9 SEE ALSO

`gdcmdump(1)`, `gdcmviewer(1)`, `gdcmimg(1)`

3.10 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 4

Tool to anonymize a DICOM file.

4.1 SYNOPSIS

```
gdcmanon [options] file-in file-out  
gdcmanon [options] dir-in  dir-out
```

4.2 DESCRIPTION

The **gdcmanon** tool is an implementation of PS 3.15 / E.1 / Basic Application Level Confidentiality Profile (Implementation of E.1.1 De-identify & E.1.2 Re-identify)

This tool is split into two very different operating mode:

- An implementation of PS 3.15, see -e and -d flags
- A dumb mode, see -dumb

Dumb mode and PS 3.15 do not work well together, you should really only use one type of anonymization. In case of doubt, avoid using -dumb.

In order to use the PS 3.15 implementation (-d & -e flag), you'll need a certificate to do de-identification operations, and the associated private key to do the re-identification operation. If you are only doing a one-shot anonymization and do not need to properly re-identify the DICOM file, you can safely discard the private key and only keep the certificate. See OpenSSL section below for an example on how to generate the private key/certificate pair.

gdcmanon will exit early if OpenSSL was not configured/build properly into the library (see GDCM_USE_SYSTEM_OPENSSL in cmake).

4.3 PARAMETERS

```
file-in  DICOM input filename
```

```
file-out DICOM output filename
```

or

```
file-in  DICOM input directory
```

```
file-out DICOM output directory
```

4.4 options

You need to specify at least one operating mode, from the following list (and only one):

4.4.1 Required parameters

```
-e --de-identify      De-identify DICOM (default)
-d --re-identify      Re-identify DICOM
  --dumb              Dumb mode anonymizer
```

Warning when operating in dumb mode, you need to also specify an operation to do, such as 'remove' or 'empty' a tag, see below the dumb mode options.

4.4.2 options

```
-i --input            DICOM filename / directory
-o --output           DICOM filename / directory
-r --recursive        recursively process (sub-)directories.
  --continue          Do not stop when file found is not DICOM.
  --root-uid           Root UID.
  --resources-path     Resources path.
-k --key              Path to RSA Private Key.
-c --certificate       Path to Certificate.
```

4.4.3 encryption options

```
--des                DES.
--des3               Triple DES.
--aes128             AES 128.
--aes192             AES 192.
--aes256             AES 256.
```

4.4.4 dumb mode options

```
--empty %d,%d        DICOM tag(s) to empty
--remove %d,%d        DICOM tag(s) to remove
--replace %d,%d,%s    DICOM tag(s) to replace
```

4.4.5 general options

```
-h --help            print this help text and exit
-v --version         print version information and exit
-V --verbose         verbose mode (warning+error).
-W --warning         warning mode, print warning information
-E --error           error mode, print error information
-D --debug           debug mode, print debug information
```

4.4.6 environment variable

```
GDCM_ROOT_UID Root UID
GDCM_RESOURCES_PATH path pointing to resources files (Part3.xml, ...)
```

4.5 Typical usage

4.5.1 De-identification (anonymization, encrypt)

The only thing required for this operation is a certificate file (in PEM format).

```
$ gdcmanon --certificate certificate.pem -e original.dcm original_anonymized.dcm
```

4.5.2 Re-identification (de-anonymization, decrypt)

The only thing required for this operation is a private key (in PEM format). It is required that the private key used for the re-identification process, was the actual private key used to generate the certificate file (certificate.pem) used during the de-identification step.

```
$ gdcmanon --key privatekey.pem -d original_anonymized.dcm original_copy.dcm
```

You can then check that original.dcm and original_copy.dcm are identical.

4.5.3 Multiple files caveat

It is very important to understand the following section, when anonymizing more than one single file. When anonymizing multiple DICOM files, you are required to use the directory input. You cannot call multiple time the gdcmanon command line tool. Indeed the tool stores in memory during the process only a hash table of conversion so that each time a particular value is found it get always replaced by the same de-identified value (think: consistent Series Instance UID).

4.5.4 Dumb mode

This functionality is not described in the DICOM standard. Users are advised that improper use of that mode is not recommended, meaning that important tag can be emptied/removed/replaced resulting in illegal/invalid DICOM file. Only use when you know what you are doing. If you delete a Type 1 attribute, chance is that your DICOM file will be not accepted in most DICOM third party viewer. Unfortunately this is often this mode that is implemented in popular DICOM Viewer, always prefer what the DICOM standard describes, and avoid the dumb mode.

The following example shows how to use dumb mode and achieve 5 operations at the same time:

- Empty the tag (0010,0010) Patient's Name,
- Empty the tag (0010,0020) Patient ID,
- Remove the tag (0010,0040) Patient's Sex
- Remove the tag (0010,1010) Patient's Age
- Replace the tag (0010,1030) Patient's Weight with the value '10'

You are required to check which DICOM attribute is Type 1 and Type 1C, before trying to **'Empty'** or **'Remove'** a particular DICOM attribute. For the same reason, you are required to check what are valid value in a replace operation.

```
$ gdcmanon --dumb --empty 10,10 --empty 10,20 --remove 10,40 --remove 10,1010 --replace 10,1030,10 012345.002.050
```

Multiple operation of `--dumb` mode can take place, just reuse the output of the previous operation. Always use `gdcmdump` on the input and output file to check what was actually achieved. You can use a diff program to check only what changed (see `diff(1)` for example).

4.5.4.1 Irreversible Anonymization

In some very rare cases, one would want to anonymize using the PS 3.15 mode so as to take benefit of the automatic conversion of all content that could contain Patient related information.

In the end all Patient related information has been removed and has been secretly stored in the 0400,0500 DICOM attribute. However to make sure that no-one ever try to break that security using brute-force algorithm, one want want to remove completely this DICOM attribute. This will make the DICOM:

- Completely free of any Patient related information (as per PS 3.15 specification)
- Remove any mean of people to brute force attack the file to find out the identity of the Patient

In this case one could simply do, as a first step execute the reversible anonymizer:

```
$ gdcmanon -c certificate.pem input.dcm anonymized_reversible.dcm
```

and now completely remove the DICOM attribute containing the secretly encrypted Patient related information:

```
$ gdcmanon --dumb --remove 400,500 --remove 12,62 --remove 12,63 anonymized_reversible.dcm anonymized_irreversible.dcm
```

Remarks

As mentionned in DICOM Sup 142, this anonymization is preferred over de-identification since:

It is not required that the Encrypted Attributes Data Set be created; indeed, there may be circumstances where the Dataset is expected to be archived long enough that any contemporary encryption technology may be inadequate to provide long term protection against unauthorized recovery of identification

4.6 OpenSSL

On most system you can have access to OpenSSL to generate the Private Key/Certificate pair.

4.6.1 Generating a Private Key

Command line to generate a rsa key (512bit)

```
$ openssl genrsa -out CA_key.pem
```

Command line to generate a rsa key (2048bit)

```
$ openssl genrsa -out CA_key.pem 2048
```

Command line to generate a rsa key (2048bit) + passphrase

```
$ openssl genrsa -des3 -out CA_key.pem 2048
```

4.6.2 Generating a Certificate

From your previously generated Private Key, you can now generate a certificate in PEM (DER format is currently not supported).

```
$ openssl req -new -key CA_key.pem -x509 -days 365 -out CA_cert.cer
```

4.7 DICOM Standard:

Page to the DICOM Standard:

<http://dicom.nema.org/>

The DICOM Standard at the time of releasing gdcmanon is:

<ftp://medical.nema.org/medical/dicom/2008/>

Direct link to PS 3.15-2008:

ftp://medical.nema.org/medical/dicom/2008/08_15pu.pdf

4.8 Warnings

Certain attributes may still contain Protected Health Information (PHI) after an anonymization step. This is typically the case for Patient's Address (0010,1040). The reason is that this particular attribute is not supposed to be in the composite IODs in the first place. DICOM Supp 142 includes it (however gdcmanon does not implement it).

4.9 SEE ALSO

gdcconv(1), gdcmdump(1), gdcminfo(1), openssl(1), dumpasn1(1)

4.10 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 5

Tool to convert DICOM to DICOM.

5.1 SYNOPSIS

```
gdcmconv [options] file-in file-out
```

5.2 DESCRIPTION

The **gdcmconv** command line program takes as input a DICOM file (file-in) and process it to generate an output DICOM file (file-out). The command line option dictate the type of operation(s) gdcmconv will use to generate the output file.

5.3 PARAMETERS

```
file-in    DICOM input filename
```

```
file-out   DICOM output filename
```

5.4 options

5.4.1 PARAMETERS

```
-i --input      DICOM filename
-o --output     DICOM filename
```

5.4.2 options

```
-X --explicit    Change Transfer Syntax to explicit.
-M --implicit    Change Transfer Syntax to implicit.
-U --use-dict     Use dict for VR (only public by default).
  --with-private-dict Use private dict for VR (advanced user only).
-C --check-meta  Check File Meta Information (advanced user only).
  --root-uid      Root UID.
  --remove-gl     Remove group length (deprecated in DICOM 2008).
  --remove-private-tags Remove private tags.
  --remove-retired Remove retired tags.
```

5.4.3 image options

```
-l --apply-lut           Apply LUT (non-standard, advanced user only).
-P --photometric-interpretation %s Change Photometric Interpretation (when possible).
-w --raw                Decompress image.
-d --deflated            Compress using deflated (gzip).
-J --jpeg               Compress image in jpeg.
-K --j2k                Compress image in j2k.
-L --jpegls             Compress image in jpeg-ls.
-R --rle                Compress image in rle (lossless only).
-F --force              Force decompression/merging before recompression/splitting.
  --generate-icon        Generate icon.
  --icon-minmax %d,%d    Min/Max value for icon.
  --icon-auto-minmax     Automatically compute best Min/Max values for icon.
  --compress-icon        Decide whether icon follows main TransferSyntax or remains uncompressed.
  --planar-configuration [01] Change planar configuration.
-Y --lossy              Use the lossy (if possible) compressor.
-S --split %d           Write 2D image with multiple fragments (using max size)
```

5.4.4 JPEG options

```
-q --quality %*f        set quality.
```

5.4.5 JPEG-LS options

```
-e --lossy-error %*i    set error.
```

5.4.6 J2K options

```
-r --rate %*f           set rate.
-q --quality %*f        set quality.
-t --tile %d,%d         set tile size.
-n --number-resolution %d set number of resolution.
  --irreversible         set irreversible.
```

5.4.7 general options

```
-h --help               print this help text and exit
-v --version            print version information and exit
-V --verbose            verbose mode (warning+error).
-W --warning            warning mode, print warning information
-E --error              error mode, print error information
-D --debug              debug mode, print debug information
```

5.4.8 special options

```
-I --ignore-errors      convert even if file is corrupted (advanced users only, see disclaimers).
```

5.4.9 environment variable

```
GDCM_ROOT_UID Root UID
```

5.5 Simple usage

gdcmmconv is a great tool to convert broken DICOM implementation into properly parsable DICOM file. Usage is simply:

```
$ gdcmmconv input.dcm output.dcm
```

or if you prefer being explicit:

```
$ gdcmmconv -i input.dcm -o output.dcm
```

Even though **gdcmmconv** can overwrite directly on the same file (`input.dcm = output.dcm`), it is recommended that user should first convert into a different file to make sure the bug is properly handled by GDCM.

Typical cases where you would want to use **gdcmmconv** in its simple form:

- convert non-cp246 conforming file into conforming cp246,
- convert implicit little endian transfer syntax file meta header into proper explicit little endian transfer syntax,
- convert the GE-13 bytes bug,
- convert dual syntax file: implicit/explicit,
- convert Philips dual Little Endian/Big Endian file,
- convert GDCM 1.2.0 broken UN-2-bytes fields,
- &...
- All other broken files listed in the supported section.

When no option other is used, only the dataset is inspected. So encapsulated Pixel Data, for instance, is not inspected for well known bugs.

When doing this kind of work, this is usually a good idea to perform some kind of quality control, see **gdcmmconv** Quality Control section (down below).

5.6 Typical usage

5.6.1 File Meta Header

Running

```
$ gdcmmconv input.dcm output.dcm
```

Is not enough to recompute file meta header, when input file is buggy. You may want to use: `--check-meta`

```
$ gdcmmconv --check-meta input.dcm output.dcm
```

See typical cases such as: `GE_DLX-8-MONO2-PrivateSyntax.dcm` or `PICKER-16-MONO2-No_DicomV3_Preamble.dcm` from `gdcmmData`.

5.6.2 Conversion to Explicit Transfer Syntax

To convert a file that was written using Implicit Transfer Syntax into Explicit Transfer Syntax simply use:

```
$ gdcconv --explicit uncompressed.dcm compressed.dcm
```

5.6.3 Compressing to lossless JPEG

To compress an uncompressed DICOM file to a JPEG Lossless encapsulated format:

```
$ gdcconv --jpeg uncompressed.dcm compressed.dcm
```

5.6.4 Compressing to lossy JPEG

To compress an uncompressed DICOM file to a JPEG Lossy encapsulated format:

```
$ gdcconv --lossy --jpeg -q 90 uncompressed.dcm compressed.dcm
```

Note:

`-q` is just one of the many way to specify lossy quality, you need to inspect the other cmd line flag to specify

5.6.5 Compressing to lossless JPEG-LS

To compress an uncompressed DICOM file to a JPEG-LS Lossless encapsulated format:

```
$ gdcconv --jpeglS uncompressed.dcm compressed.dcm
```

5.6.6 Compressing to lossy JPEG-LS

To compress an uncompressed DICOM file to a JPEG-LS Lossy encapsulated format:

```
$ gdcconv --lossy --jpeglS -e 2 uncompressed.dcm lossy_compressed.dcm
```

Note:

`-e` (or `-lossy-error`) means that the maximum tolerate error is 2 for each pixel value

5.6.7 Compressing to lossless J2K

To compress an uncompressed DICOM file to a JPEG-2000 Lossless encapsulated format:

```
$ gdcconv --j2k uncompressed.dcm compressed.dcm
```

5.6.8 Compressing to lossy J2K

To compress an uncompressed DICOM file to a JPEG-2000 Lossy encapsulated format:

```
$ gdcconv --lossy -q 55,50,45 --j2k uncompressed.dcm lossy_compressed.dcm
```

Note:

`-q` is just one of the many way to specify lossy quality, you need to inspect the other cmd line flag to specify

5.6.9 Compressing to lossless RLE

To compress an uncompressed DICOM file to a RLE Lossless encapsulated format:

```
$ gdcconv --rle uncompressed.dcm compressed.dcm
```

There is no such thing as lossy RLE compression.

5.6.10 Split encapsulated DICOM:

To split an encapsulated stream into smaller chunk (1024 bytes each):

```
$ gdcconv --split 1024 rle.dcm rle_1024.dcm
```

If an odd number of bytes is passed it will be rounded down to the next even number (eg. 1025 -> 1024) since DICOM only allow even number for Value Length.

5.6.11 Forcing (re)compression

Sometime it is necessary to use the `-force` option. By default when user specify `-j2k` and input file is already in JPEG 2000 encapsulated DICOM format then no operation takes places. By using `-force` you make sure that (re)compression operation takes places.

Real life example of why you would use `-force`:

- When Pixel Data is missing data / is padded with junk
- When you would like to make sure GDCM can handle decompression & recompression cycle

5.6.12 Decompressing a Compressed DICOM

```
$ gdcconv --raw compressed.dcm uncompressed.dcm
```

5.6.13 Compressing an uncompressed Icon

By default when compressing a DICOM Image file, `gdcconv` will not compress the icon. A user option needs to be turned on to explicitly force the compression of the Icon Image Sequence Pixel Data

For example, by default we will not compress the Icon Image Sequence Pixel Data attribute:

```
$ gdcconv --jpeg gdcData/simpleImageWithIcon.dcm uncompressed_icon.dcm
```

In the following example we will explicitly compress the Icon Image Sequence Pixel Data attribute. In that case the same Transfer Syntax is being used for both the main Pixel Data and the Pixel Data from the Icon Image Sequence:

```
$ gdcconv --jpeg --compress-icon gdcData/simpleImageWithIcon.dcm compressed_icon.dcm
```

5.6.14 Generating an Icon

For some application it might be necessary to produce a small preview of the main image to be able to quickly load that short preview instead of the main image. In that case:

```
$ gdcconv --raw --generate-icon gdcData/test.acr test_icon.dcm
```

In some cases the main Pixel Data element is expressed as pixel defined on 16bits. Since Icon can only store at most pixel of size 8bits, a rescale operation needs to take place. In order to properly select a better interval for doing the rescale operation user can specify the min max used for the rescale operation:

```
$ gdcconv --raw --generate-icon --icon-minmax 0,192 gdcData/012345.002.050.dcm icon_minmax.dcm
```

5.6.15 Changing the planar Configuration

Often RLE files are compressed using a different Planar Configuration (RRR ... GGG... BBB...) instead of the usual triplet (RGB ... RGB ... RGB). So upon decompression the Planar Configuration is 1. This is perfectly legal in DICOM, however this is unconventional, and thus it may be a good idea to also change the planar configuration and set it to the default :

```
$ gdcconv --raw --planar-configuration 0 compressed.dcm uncompressed1.dcm
```

To reinvert the planar configuration of file 'uncompressed1.dcm', simply do:

```
$ gdcconv --raw --planar-configuration 1 uncompressed1.dcm uncompressed2.dcm
```

5.7 Lossless Conversion

When talking about lossless conversion, there is an ambiguity that need to be understood. To achieve higher compression ratio, the RGB color space is usually not used, in favor of a YBR one. Changing from one color space to the other is (bit level) not lossless.

For more detail, see what are the true lossless transformations as described:

http://gdc.sourceforge.net/wiki/index.php/Color_Space_Transformations

5.8 Quality Control

One important part when using gdcconv it to have a way to quality control the output.

You can use 3rd party tool to check the output of gdcconv is correct.

5.8.1 DCMTK / dicom3tools

Using another DICOM implementation such as the one from DCMTK or dicom3tools can be a good process to check the output of gdcconv.

- For DCMTK use: dcmdump
- For dicom3tools use: dcdump

For reference, gdcconv --raw will act as dcmdjpeg +cn +px, since it never tries to convert color space.

5.8.2 VIM: vimdiff

You can setup your favorite editor to compare the output, for instance in vim:

```
autocmd BufReadPre *.dcm set ro
autocmd BufReadPost *.dcm silent %!gdcm dump -M +uc "%"
```

then simply do:

```
$ vimdiff input.dcm output.dcm
```

5.8.3 vbindiff

On UNIX you can visually compare binary file using the vbindiff command:

```
$ vbindiff input.dcm output.dcm
```

5.9 SEE ALSO

gdcmdump(1), **gdcmlraw(1)**, **gdcminfo(1)**, **gdcmdiff(1)**

5.10 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 6

dumps differences of two DICOM files

6.1 SYNOPSIS

```
gdcmdiff [options] file1 file2
```

6.2 DESCRIPTION

The **gdcmdiff** command line program takes as input two DICOM file: file1 and file2.

6.3 PARAMETERS

file1 DICOM input filename

file2 DICOM output filename

6.4 options

6.4.1 options

```
-m      --meta          Compare metainformation. Default is off.  
-t <n>  --truncate <n> String values trimmed to n characters.
```

6.4.2 general options

```
-h      --help          print this help text and exit  
  
-v      --version       print version information and exit  
  
-V      --verbose       verbose mode (warning+error).  
  
-W      --warning       warning mode, print warning information
```

```
-E  --error  
    error mode, print error information  
  
-D  --debug  
    debug mode, print debug information
```

6.5 Simple usage

gdcmdiff is a great tool to diff DICOM files. Usage is simply:

```
$ gdcmdiff input1.dcm input2.dcm
```

6.6 SEE ALSO

gdcmdump(1), **gdcminfo(1)**

6.7 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 7

dumps a DICOM file, it will display the structure and values contained in the specified DICOM file.

7.1 SYNOPSIS

```
gdcm dump [options] dcm_file
gdcm dump [options] dcm_directory
```

7.2 DESCRIPTION

The **gdcm dump** command line program dumps a DICOM file to the console. For those familiar with **dcm dump** (DCMTK) output, **gdcm dump** has some minor differences. Namely:

- For Implicit Transfer Syntax **gdcm dump** will print ?? instead of the dictionary VR

gdcm dump has a limited private dictionary that is used to lookup private element whenever possible.

7.3 PARAMETERS

```
dcm_file          DICOM input filename
dcm_directory     DICOM input directory
```

7.4 options

7.4.1 options

-x --xml-dict	generate the XML dict (only private elements for now).
-r --recursive	recursive (input is a directory)
-d --dump	dump value (limited use).
-p --print	print value instead of simply dumping (default).
-c --color	print in color.
-C --csa	print SIEMENS CSA Header (0029,[12]0,SIEMENS CSA HEADER).
-P --pdb	print GEMS Protocol Data Block (0025,1b,GEMS_SERS_01).
--elscint	print ELSCINT Protocol Information (01f7,26,ELSCINT1).
--vepro	print VEPRO Protocol Information (0055,20,VEPRO VIF 3.0 DATA).

```

                or VEPRO Protocol Information (0055,20,VEPRO VIM 5.0 DATA).
--sds           print Philips MR Series Data Storage (1.3.46.670589.11.0.0.12.2) Information (2005,32,Philips)
-A --asn1       print encapsulated ASN1 structure >(0400,0520).
--map-uid-names map UID to names.

```

7.4.2 general options

```

-h --help
    print this help text and exit

-v --version
    print version information and exit

-V --verbose
    verbose mode (warning+error).

-W --warning
    warning mode, print warning information

-E --error
    error mode, print error information

-D --debug
    debug mode, print debug information

```

7.4.3 special options

```

-I --ignore-errors  dumps even if file is corrupted (advanced users only, see disclaimers).

```

7.5 Typical usage

7.5.1 Printing Implicit Transfer Syntax

The VR are not found in the file, thus are presented with a "(??)", and right next to it (if found) the correct VR.

Eg.:

```
$ gdcmdump GE_DLX-8-MONO2-PrivateSyntax.dcm
```

```

# Dicom-File-Format
\&...
(0008,0000) ?? (UL) 434                                # 4,1 Generic Group Length
(0008,0005) ?? (CS) [ISO_IR 100]                        # 10,1-n Specific Character Set
(0008,0008) ?? (CS) [ORIGINAL\\PRIMARY\\SINGLE PLANE ]   # 30,2-n Image Type
(0008,0016) ?? (UI) [1.2.840.10008.5.1.4.1.1.12.1]      # 28,1 SOP Class UID
(0008,0018) ?? (UI) [1.2.840.113619.2.16.1.0.906539207.1.24207] # 42,1 SOP Instance UID
(0008,0020) ?? (DA) [19980923]                          # 8,1 Study Date
(0008,0021) ?? (DA) [19980923]                          # 8,1 Series Date
(0008,0022) ?? (DA) [19980923]                          # 8,1 Acquisition Date
(0008,0023) ?? (DA) [19980923]                          # 8,1 Content Date
(0008,0030) ?? (TM) [101229.000]                        # 10,1 Study Time
(0008,0031) ?? (TM) [101229.000]                        # 10,1 Series Time
(0008,0032) ?? (TM) [102653.000]                        # 10,1 Acquisition Time
(0008,0033) ?? (TM) [102653.000]                        # 10,1 Content Time
\&...

```

7.5.2 Print Private Attributes

GDCM has a limited private dictionary. Whenever possible, it will try to lookup the private data element.

```
$ gdcmdump 012345.002.050.dcm
```

```
\&...
(0009,0010) LO [GEMS_IDEN_01] # 12,1 Private Creator
(0009,1001) LO [GE_GENESIS_FF ] # 14,1 Full fidelity
(0009,1002) SH [MRCV] # 4,1 Suite id
(0009,1004) SH [SIGNA ] # 6,1 Product id
(0009,1027) SL 985968524 # 4,1 Image actual date
(0009,1030) SH [19356UMR2 ] # 10,1 Service id
(0009,1031) SH [999 ] # 4,1 Mobile location number
(0009,10e3) UI [1.2.840.113619.1.1.4.1762386977] # 32,1 Equipment UID
(0009,10e6) SH [08] # 2,1 Genesis Version - now
(0009,10e7) UL 2757786872 # 4,1 Exam Record checksum
(0009,10e9) SL 985968523 # 4,1 Actual series data time stamp
\&...
(0019,0000) UL 1208 # 4,1 Generic Group Length
(0019,0010) LO [GEMS_ACQU_01] # 12,1 Private Creator
(0019,100f) DS [424.399994] # 10,1 Horiz. Frame of ref.
(0019,1011) SS 0 # 2,1 Series contrast
\&...
(0019,10e0) DS [0.000000] # 8,1 User data 24 {# DTI Diffusion Dir., relea
(0019,10e2) DS [0.000000] # 8,1 Velocity Encode Scale
(0019,10f2) SS 0 # 2,1 Fast phases
(0019,10f9) DS [98] # 2,1 Transmit gain
\&...
(0021,0000) UL 372 # 4,1 Generic Group Length
(0021,0010) LO [GEMS_RELA_01] # 12,1 Private Creator
(0021,1003) SS 0 # 2,1 Series from which Prescribed
\&...
```

7.5.3 SIEMENS CSA Header

Using this option it is possible to dump as a readable text what is contained in the private attribute as found in typical SIEMENS MR DICOM file.

Eg.:

```
$ gdcmdump --csa MR_SIEMENS_forceLoad29-1010_29-1020.dcm
```

```
(0029,0010)siemens csa header
Image shadow data (0029,xx10)
```

```
0 - 'EchoLinePosition' VM 1, VR IS, SyngoDT 6, NoOfItems 6, Data '64      '
1 - 'EchoColumnPosition' VM 1, VR IS, SyngoDT 6, NoOfItems 6, Data '64      '
2 - 'EchoPartitionPosition' VM 1, VR IS, SyngoDT 6, NoOfItems 6, Data '32      '
3 - 'UsedChannelMask' VM 1, VR UL, SyngoDT 9, NoOfItems 6, Data '255      '
4 - 'Actual3DImaPartNumber' VM 1, VR IS, SyngoDT 6, NoOfItems 0, Data
5 - 'ICE_Dims' VM 1, VR LO, SyngoDT 19, NoOfItems 6, Data 'X_1_1_1_1_1_31_1_1_1_1_19'
6 - 'B_value' VM 1, VR IS, SyngoDT 6, NoOfItems 6, Data '0      '
7 - 'Filter1' VM 1, VR IS, SyngoDT 6, NoOfItems 0, Data
8 - 'Filter2' VM 1, VR IS, SyngoDT 6, NoOfItems 0, Data
\&...
```

7.5.4 GEMS Protocol Data Block

Using this option it is possible to dump as a readable text what is contained in the private attribute as found in typical GEMS MR DICOM file.

Protocol Data Block : 0025,xx1b,GEMS_SERS_01

```
$ gdcmdump --pdb GE_MR_0025xx1bProtocolDataBlock.dcm
```

```
ENTRY "Head First"
POSITION "Supine"
ANREF "NA"
COIL "HEAD"
PLANE "OBLIQUE"
SEDESCFLAG "1"
SEDESC "AX FSE T2"
IMODE "2D"
PSEQ "FSE-XL"
IOPT "FC, EDR, TRF, Fast"
PLUG "22"
FILTCHOICE "None"
BWRT "-1"
TRICKSIMG "1"
TAG_SPACE "7"
TAG_TYPE "None"
\&...
```

7.5.5 ELSCINT Protocol Information

Using this option it is possible to dump as a readable text what is contained in the private attribute as found in typical ELSCINT CT DICOM file.

ELSCINT Protocol Information: (01f7,26,ELSCINT1)

```
$ gdcmdump --elscint ELSCINT1_ProtocolInformation.dcm
```

```
ELSCINT1 Dumping info from tag (01f7,26,elscint1)
```

```
ELSCINT1/Item name: []
  ApprovedStep [yes]
  RefSurview [1\0]
  STD-first-img-pos [11.5]
  current-step [yes]
  ntimed-steps [0]
  orig-n-slices [390]
  protocol-file [Head_Multi_1032_usr.proc]
  protocol-name [FACE-TRAUMA/Head/Hx]
  protocol-path [/usr/diamond.root/spr/]
  protocol-step [1]
  protocol-version [2.51]
```

```
ELSCINT1/Item name: [doseright]
```

```
  ACS [n/a]
  ACS-bed-position [0]
  ACS-calc-mas [0]
  ACS-ig-parameter [0]
  ACS-learn-allowed [no]
  ACS-water-radius [-1.000000]
  ACS-water-radius-scan [-1]
\&...
```

7.5.6 VEPRO Protocol Information

Using this option it is possible to dump as a readable text what is contained in the private attribute as found in typical VEPRO CT DICOM file.

ELSCINT Protocol Information: (0055,20,VEPRO VIM 5.0 DATA)

```
$ gdcmdump --vepro VEPRO_ProtocolInformation.dcm

VIMDATA2: (0055,20,VEPRO VIM 5.0 DATA)
  ID: VIM
  Version: 5.0
  UserName:
  UserAdress1: Name of Institution
  UserAdress2: Street of Institution
  UserAdress3: City of Institution
  UserAdress4:
  UserAdress5:
  RecDate: 20101001
  RecTime: 211321
  RecPlace:
  RecSource: DICOM Distributor
  DF1: P-09/10-41808
  DF2: Sultana Razia
  DF3: 19411001
  DF4: F
  DF5:
  DF6:
  DF7:
  DF8: CT Scan Brain without Contrast
  DF9: 10/10-0034873
  DF10: 10/10-00348
  DF11:
  DF12:
  DF13:
  DF14: Head 0.5
  DF15: 4
  DF16:
  DF17:
  DF18:
  DF19:
  DF20:
  StudyUID: 1.2.392.200036.9116.2.6.1.48.1214228007.1285934880.206831
  SeriesUID: 1.2.392.200036.9116.2.6.1.48.1214228007.1285935201.938653
  Modality: CT
```

7.5.7 Philips Private MR Series Data Storage (1.3.46.670589.11.0.0.12.2)

Using this option it is possible to dump as a readable text what is contained in the private attribute as found in typical Philips Private MR Series Data Storage file.

PMS Series Data Storage (2005,32,Philips MR Imaging DD 002)

```
$ gdcmdump --sds PMS_SeriesDataStorage.dcm

\&...
PMS/Item name: [PDF_CONTROL_GEN_PARS/IEEE_PDF/Y ]
\&...
PMS/Item name: [PDF_CONTROL_PREP_PARS /IEEE_PDF/Y ]
\&...
PMS/Item name: [PDF_CONTROL_RECON_PARS/IEEE_PDF/Y ]
\&...
PMS/Item name: [PDF_CONTROL_SCAN_PARS /IEEE_PDF/Y ]
\&...
PMS/Item name: [PDF_EXAM_PARS /IEEE_PDF/Y ]
\&...
PMS/Item name: [PDF_HARDWARE_PARS /IEEE_PDF/Y ]
\&...
PMS/Item name: [PDF_PREP_PARS /IEEE_PDF/Y ]
\&...
PMS/Item name: [PDF_SPT_PARS/IEEE_PDF/Y ]
```

```

SP_scan_resol [256\256] # 2
SP_pda_profiles [0\0] # 2
SP_filter [324074] # 1
SP_analyse_with_iqt [0] # 1
SP_main_system_type [3] # 1
SP_gradient_system [6] # 1
SP_coil_type [2\2\0\0\0\0\0\0\0\0\0\0\0\0\0\0] # 16
SP_coil_id [2\34\0\0\0\0\0\0\0\0\0\0\0\0\0\0] # 16
SP_coil_part [0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0] # 16
SP_act_q [0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0] # 16
SP_act_coil_freq [0\0\0\0\0\0\0\0\0\0\0\0\0\0\0\0] # 16
SP_coil_m_pos [255\255\255\0\0\0\0\0\0\0\0\0\0\0\0\255] # 16
SP_coil_t_pos [255\128\255\0\0\0\0\0\0\0\0\0\0\0\0\255] # 16
SP_surface_coil_con [0\1\0\0\0\0\0\0\0\0\0\0\0\0\0\0] # 16
SP_proton_freq [127801349] # 1
SP_tm_result [2\2\2\2\2\2\2\2\2\2\2\2\2\2\2\2] # 16
SP_f0_result [0] # 1
SP_as_result [0] # 1
SP_po_result [0] # 1
SP_rg_result [0] # 1
SP_dc_result [0] # 1
SP_ph_result [0] # 1
\&...

```

7.5.8 Encapsulated ASN1 Structure

This option is mainly used for dumping the ASN1 structure of the encrypted Attribute (0040,0520)

```
$ gdcmdump encrypted.dcm
```

```

\&...
(0400,0500) SQ # u/1,1 Encrypted Attributes Sequence
  (fffe,e000) na (Item with undefined length)
    (0400,0510) UI [1.2.840.10008.1.2] # 18,1 Encrypted Content Transfer Syntax UID
    (0400,0520) OB 30\82\03\ba\06\09\2a\86\48\55\04\08\13 # 958,1 Encrypted Content
  (fffe,e00d)
(fffe,e0dd)
\&...

```

```
$ gdcmdump --asn1 encrypted.dcm
```

```

0:d=0 hl=4 l= 954 cons: SEQUENCE
4:d=1 hl=2 l= 9 prim: OBJECT :pkcs7-envelopedData
15:d=1 hl=4 l= 939 cons: cont [ 0 ]
19:d=2 hl=4 l= 935 cons: SEQUENCE
23:d=3 hl=2 l= 1 prim: INTEGER :00
26:d=3 hl=4 l= 366 cons: SET
30:d=4 hl=4 l= 362 cons: SEQUENCE
34:d=5 hl=2 l= 1 prim: INTEGER :00
37:d=5 hl=2 l= 82 cons: SEQUENCE
39:d=6 hl=2 l= 69 cons: SEQUENCE
41:d=7 hl=2 l= 11 cons: SET
43:d=8 hl=2 l= 9 cons: SEQUENCE
45:d=9 hl=2 l= 3 prim: OBJECT :countryName
50:d=9 hl=2 l= 2 prim: PRINTABLESTRING :AU
54:d=7 hl=2 l= 19 cons: SET
56:d=8 hl=2 l= 17 cons: SEQUENCE
58:d=9 hl=2 l= 3 prim: OBJECT :stateOrProvinceName
63:d=9 hl=2 l= 10 prim: PRINTABLESTRING :Some-State
75:d=7 hl=2 l= 33 cons: SET
77:d=8 hl=2 l= 31 cons: SEQUENCE
79:d=9 hl=2 l= 3 prim: OBJECT :organizationName
84:d=9 hl=2 l= 24 prim: PRINTABLESTRING :Internet Widgits Pty Ltd
110:d=6 hl=2 l= 9 prim: INTEGER :AC966D88787A51B4

```



```

121:d=5 hl=2 l= 13 cons: SEQUENCE
123:d=6 hl=2 l= 9 prim: OBJECT :rsaEncryption
134:d=6 hl=2 l= 0 prim: NULL
136:d=5 hl=4 l= 256 prim: OCTET STRING [HEX DUMP]:822368070285AD756C962ECB973514B291F946...
396:d=3 hl=4 l= 558 cons: SEQUENCE
400:d=4 hl=2 l= 9 prim: OBJECT :pkcs7-data
411:d=4 hl=2 l= 29 cons: SEQUENCE
413:d=5 hl=2 l= 9 prim: OBJECT :aes-256-cbc
424:d=5 hl=2 l= 16 prim: OCTET STRING [HEX DUMP]:3B49AFE71749F2BFF1519EBAEA95A393
442:d=4 hl=4 l= 512 prim: cont [ 0 ]

```

7.6 SEE ALSO

gdcmdump(1), **gdcmrw(1)**, **gdcmanon(1)**

7.7 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 8

Tool to generate a DICOMDIR file from a File-Set.

8.1 SYNOPSIS

```
gdcmgendir [options] file-in file-out
```

8.2 DESCRIPTION

8.3 PARAMETERS

```
file-in    DICOM input filename
```

```
file-out   DICOM output filename
```

8.4 options

8.4.1 Parameters

8.4.2 options

```
-i --input          DICOM filename or directory
-o --output         DICOM filename or directory
-r --recursive      recursive.
  --descriptor      descriptor.
  --root-uid        Root UID.
```

8.4.3 general options

```
-h  --help
    print this help text and exit

-v  --version
    print version information and exit
```

```
-V  --verbose
    verbose mode (warning+error).

-W  --warning
    warning mode, print warning information

-E  --error
    error mode, print error information

-D  --debug
    debug mode, print debug information
```

8.4.4 environment variable

```
GDCM_ROOT_UID Root UID
```

8.5 Typical usage

8.6 NOTE

One may have to run some preliminary steps in order to get `gdcmgendir` to generate the DICOMDIR file. Namely two steps:

- Batch renaming of the DICOM filename into something compatible with ISO 9660 filename convention
- Convert all DICOM file into the Explicit VR Little Endian Uncompressed (1.2.840.10008.1.2.1)

Step 1. can be solved in a numerous way. Eg. on UNIX environment this could either be solved using the `mkisofs` command line tool. Filenames should not contains any extension since the VR CS does not allow for the '.' character. Only upper case, digit 0-9, the space ' ' and the underscore '_' character are valid in VR CS, with a maximum of 8 bytes. Another simple tool that can be handy is 'rename' in conjunction with 'basename'.

Step 2. can simply be achieved using the `gdcconv` command line tool:

```
$ for i in `ls IMG*`; do gdcconv --raw --force $i /tmp/out/$i; done
```

8.7 SEE ALSO

`gdcconv(1)`, `gdcmanon(1)`, `rename(1)`, `mkisofs(1)`

8.8 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 9

Manipulate DICOM image file.

gdcmimg is a low level tool to allow de-/encapsulation from/to DICOM image. This tool does not understand Transfer Syntax conversion. It will encapsulate the raw data as-is. This has some impact in some cases, see special warnings below.

9.1 SYNOPSIS

```
gdcmimg [options] file-in file-out
```

9.2 DESCRIPTION

The **gdcmimg** command line tool can be used in two fashions:

- 1. Converting a recognized file format into its encapsulated DICOM counterpart,
- 2. Anonymizing a rectangular portion of a DICOM file.

9.3 PARAMETERS

```
file-in    input filename
```

```
file-out   output filename
```

9.4 options

9.4.1 PARAMETERS

```
-i --input      Input filename
-o --output     Output filename
```

9.4.2 options

```
--endian %s      Endianness (LSB/MSB) .
```

```

-d --depth %d      Depth (Either 8/16/32 or BitsAllocated eg. 12 when known).
--sign %s          Pixel sign (0/1).
--spp %d           Sample Per Pixel (1/3).
-s --size %d,%d    Size.
-C --sop-class-uid SOP Class UID (name or value).
-T --study-uid     Study UID.
-S --series-uid    Series UID.
--root-uid         Root UID.

```

9.4.3 fill options

```

-R --region %d,%d  Region.
-F --fill %d       Fill with pixel value specified.

```

9.4.4 general options

```

-h --help          print this help text and exit

-v --version       print version information and exit

-V --verbose       verbose mode (warning+error).

-W --warning       warning mode, print warning information

-E --error         error mode, print error information

-D --debug         debug mode, print debug information

```

9.4.5 environment variable

```
GDCM_ROOT_UID Root UID
```

9.5 Supported File Format (appropriate file extension) gdcming

will base it's conversion process based on the file extension. Follows the list of recognized file extension. When no extension is found, DICOM file is assumed.

input format

```

* RAW      (raw, rawl, gray, rgb)
* RLE      (rle)
* PNM      (pgm, pnm, ppm)
* JPEG-LS  (jls)
* JPEG 2000 (jp2, j2k, j2c, jpx, jpc)
* JPEG     (jpg, jpeg, ljpg, ljpeg)
* DICOM    ()

```

output format:

```

* PGM      (pgm, pnm, ppm)
* DICOM    ()

```

For RAW file format, you should take special care of the `--endian` option. For the (old) JPEG file format, both the lossy and lossless format are supported, user should pay attention to the `--sign` option. For file format such as RLE or RAW, user is expected to fill in information required to find the dimension and type of input data as there is no other way to find this information. For all other file format, the properties are derived from the file format itself. PNM file are supposed to be big endian (important for depth > 8)

9.6 Typical usage

9.6.1 Remove a rectangular part of the image

To fill the region $[0,100] \times [0,100]$ of a DICOM image simply do:

```
$ gdcimg --fill 0 --region 0,100,0,100 -i input.dcm -o output_black.dcm
```

Warning: if the Pixel Data is compressed, the image is first decompressed so that pixel can be set to 0, but it is not recompressed.

9.6.2 Convert RAW to DICOM

Recognized extension is `.raw`, `.rawl`, `.gray` or `.rgb` (case insensitive)

```
$ gdcimg --size 512,512 --depth 16 -i input.raw -o output.dcm
```

the image will be a Secondary Capture.

When the input is 3 component, one need to specify explicitly the Samples Per Pixel:

```
$ gdcimg --size 512,512 --spp 3 input_rgb.raw output_rgb.dcm
```

When the filename contains `.rgb` as file extension output is automatically recognized as RGB no need to specify `--spp`

```
$ gdcimg --size 512,512 input.rgb output_rgb.dcm
```

You can use the `dd` cmd line to skip any header you would like to discard, for instance, if you would like to skip the first 108 bytes, simply do:

```
$ dd skip=108 bs=1 if=input.raw of=output.raw
```

`.raw` and `.rawl` extension are equivalent. You need to explicitly specify the endianness manually:

```
$ gdcimg --endian MSB --size 512,512 --depth 16 -i input.raw -o output.dcm
```

or

```
$ gdcimg --endian LSB --size 512,512 --depth 16 -i input.raw -o output.dcm
```

9.6.3 Convert PGM/PNM/PPM to DICOM

Recognized extensions are `.pgm`, `.pnm`, `.ppm` (case insensitive)

```
$ gdcimg -i input.pgm -o output.dcm
```

the image will be a Secondary Capture

9.6.4 Convert RLE to DICOM

Recognized extension is .rle (case insensitive)

```
$ gdcimg --size 512,512 --depth 16 -i input.rle -o output.dcm
```

the image will be a Secondary Capture

9.6.5 Convert JPEG to DICOM

Recognized extensions are .jpg, .jpeg, .ljpg, .ljpeg (case insensitive)

```
$ gdcimg -i input.ljpeg -o output.dcm
```

the image will be a Secondary Capture

9.6.6 Convert J2K to DICOM

Recognized extensions are .j2k, .jp2, .jpc, .jpx, .j2c (case insensitive)

```
$ gdcimg -i input.j2k -o output.dcm
```

the image will be a Secondary Capture.

All Pixel informations (Bits Stored/Allocated...) will be derived from the image itself, and not from the command line options.

9.6.7 Specifying a SOP Class UID

Instead of the default Secondary Capture Image Storage, one may want to specify, say VL Photographic Image Storage.

```
$ gdcimg --sop-class-uid 1.2.840.10008.5.1.4.1.1.77.1.4 input.jpg output.dcm
```

9.7 Multiple Files

gdcimg handle nicely a set of files (for instance jpeg):

```
$ gdcimg 1.jpg 2.jpg 3.jpg 4.jpg output.dcm
```

9.8 Start Offset

In some case, one may want to create a 2D slice from an arbitrary volume (e.g 3D). In which case --offset becomes handy:

```
$ gdcimg --offset 4954104330 --size 1673,1673 Input3D_1673_1673_1775.raw slice_1770.dcm
```


9.9 Warning

There are a couple of issues with gdcming implementation:

For RAW file, one should pay attention that when using `-endian MSB` the Pixel Data will be encapsulated as is (not touched by gdcming). Therefore the only possible transfer syntax available is Implicit VR Big Endian DLX (G.E Private). GDCM does handle this private Transfer Syntax. So if you need to convert this Transfer Syntax to another one (and allow Pixel Data manipulation), you can use:

```
$ gdcmconv --raw --force input_big_endian_dlx.raw -o output_implicit_vr_little_endian.dcm
```

For JFIF file and JP2 file (with header) the header is copied into the Pixel Data element which is illegal for JP2. Use gdcmconv to properly re-encode a JP2/JFIF file into J2K/JPG.

```
$ gdcming input.jp2 output_jp2.dcm
$ gdcmconv --j2k --force output_jp2.dcm output_j2k.dcm
```

For RLE file, no check is done for crossing the row boundary. It is recommended to use gdcmconv `-rle` to re-encode into a proper RLE file in case of doubt.

Of course if the compression is not ok with your setup, you can always de-encapsulated the DICOM file (typically JPEG) to a non-encapsulated form, using gdcmconv:

```
$ gdcmconv --raw input_jpeg.dcm output_raw.dcm
```

9.10 SEE ALSO

gdcmdump(1), gdcmdump(1), gdcmraw(1), convert(1), dd(1)

9.11 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 10

Display meta info about the input DICOM file.

10.1 SYNOPSIS

```
gdcminfo [options] file-in
```

10.2 DESCRIPTION

The **gdcminfo** command line program takes as input a DICOM file, or a directory and process it to extract meta-information about the DICOM file processed.

10.3 PARAMETERS

```
file-in    DICOM input filename
```

10.4 options

10.4.1 options

<code>-r --recursive</code>	recursive.
<code>-d --check-deflated</code>	check if file is proper deflated syntax.
<code>--resources-path</code>	Resources path.
<code>--md5sum</code>	Compute md5sum of Pixel Data attribute value.
<code>--check-compression</code>	check the encapsulated stream compression (lossless/lossy).

10.4.2 general options

<code>-h --help</code>	print this help text and exit
<code>-v --version</code>	print version information and exit
<code>-V --verbose</code>	verbose mode (warning+error).

```
-W  --warning
    warning mode, print warning information

-E  --error
    error mode, print error information

-D  --debug
    debug mode, print debug information
```

10.4.3 environment variable

GDCM_RESOURCES_PATH path pointing to resources files (Part3.xml, ...)

10.5 Simple usage

10.5.1 gdcmdata

Using data from gdcmdata:

```
$ gdcminfo gdcmdata/012345.002.050.dcm
```

```
MediaStorage is 1.2.840.10008.5.1.4.1.1.4 [MR Image Storage]
NumberOfDimensions: 2
Dimensions: (256,256)
Origin: (-85,21.6,108.7)
Spacing: (0.664062,0.664062,1.5)
DirectionCosines: (1,0,0,0,0,-1)
Rescale Intercept/Slope: (0,1)
SamplesPerPixel      :1
BitsAllocated        :16
BitsStored           :16
HighBit              :15
PixelRepresentation:1
Orientation Label: CORONAL
```

10.5.2 Davie Clunie datasets:

Using data from David Clunie datasets:

```
$ gdcminfo BRTUM001.dcm
```

```
MediaStorage is 1.2.840.10008.5.1.4.1.1.4.1 [Enhanced MR Image Storage]
NumberOfDimensions: 3
Dimensions: (256,256,15)
Origin: (40,-105,105)
Spacing: (0.820312,0.820312,6)
DirectionCosines: (0,1,0,0,0,-1)
Rescale Intercept/Slope: (0,1)
SamplesPerPixel      :1
BitsAllocated        :16
BitsStored           :16
HighBit              :15
PixelRepresentation:1
Orientation Label: SAGITTAL
```

10.5.3 Checking the md5sum of the Pixel Data

After compressing a DICOM file (see `gdcmconv`) using a lossless compression algorithm, it is fairly easy to compare the two files for differences at DICOM attribute level. However one operation is slightly easier to do: how to make sure the compression was actually lossless ? In this case one could use the `--md5sum` operation.

Take an uncompressed DICOM image file:

```
$ gdcminfo --md5sum SIEMENS_ImageLocationUN.dcm
```

The tool return: 0621954acd5815e0b4f7b65fcc6506b1

Now compress this file:

```
$ gdcmmconv --jpegls SIEMENS_ImageLocationUN.dcm lossless_compressed.dcm
```

and then check again the md5sum:

```
$ gdcminfo --md5sum lossless_compressed.dcm
```

The tool return: 0621954acd5815e0b4f7b65fcc6506b1

10.5.4 Checking if Pixel Data is lossless

In some environment one wish to check whether or not the DICOM file is lossless or not. It is fairly easy to do that in most cases. Only in two occasion this is not clear from the sole DICOM Attribute. When the Transfer Syntax is JPEG 2000 Image Compression (1.2.840.10008.1.2.4.91) and when the Transfer Syntax is JPEG-LS Lossy (Near-Lossless) Image Compression (1.2.840.10008.1.2.4.81).

In this case, the only solution is to open the Pixel Data element, read the specific JPEG header and check whether or not the JPEG transformation was lossless or not:

```
$ gdcminfo --check-compression gdcmmData/MAROTECH_CT_JP2Lossy.dcm
```

The tool returns: "Encapsulated Stream was found to be: lossy"

10.6 SEE ALSO

`gdcmdump(1)`, `gdcmraw(1)`, `gdcmconv(1)`

10.7 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 11

Tool to convert PDF to PDF/DICOM.

11.1 SYNOPSIS

```
gdcmpdf [options] file-in file-out
```

11.2 DESCRIPTION

The **gdcmpdf** tool convert a PDF file (any PDF version) into an encapsulated PDF/DICOM file. By default it will try to read the PDF meta information stored in the PDF and convert this information to some specific DICOM fields (see below). However it may fails (eg. wrong password on encrypted PDF file) in which case empty value are used.

11.3 PARAMETERS

file-in PDF input filename

file-out DICOM output filename

11.4 options

11.4.1 general options

```
-h    --help  
      print this help text and exit  
  
-v    --version  
      print version information and exit  
  
-V    --verbose  
      verbose mode (warning+error).  
  
-W    --warning  
      warning mode, print warning information  
  
-E    --error  
      error mode, print error information  
  
-D    --debug
```

```
debug mode, print debug information
```

11.5 Usage Example

```
$ wget http://gdcm.sourceforge.net/gdcm.pdf
$ gdcmpdf gdcm.pdf gdcm.dcm
```

To re-extract the encapsulated pdf file:

```
$ gdcmrw -i gdcm.dcm -t 42,11 -o gdcm.dcm.pdf
$ diff gdcm.pdf gdcm.dcm.pdf
```

11.6 PDF Info Mapping

Here is how the PDF info is mapped to DICOM information (typical pdfinfo output):

```
Title:      GDCM Reference Manual
Subject:    Grassroots DICOM API reference
Keywords:   GDCM,DICOM,JPEG,Lossless JPEG,JPEG-LS,J2K,JPEG 2000,RLE
Author:     Mathieu Malaterre and co.
Creator:    LaTeX with hyperref package
Producer:   pdfTeX-1.21a
CreationDate: Tue Apr 28 15:34:26 2009
Tagged:     no
Pages:      1188
Encrypted:  no
Page size:  612 x 792 pts (letter)
File size:  13756841 bytes
Optimized:  yes
PDF version: 1.4
```

Converted to DICOM this leads to:

```
# Dicom-Data-Set
# Used TransferSyntax: Little Endian Explicit
(0008,0005) CS [ISO_IR 100] # 10, 1 SpecificCharacterSet
(0008,0012) DA [20090428] # 8, 1 InstanceCreationDate
(0008,0013) TM [182550.302631] # 14, 1 InstanceCreationTime
(0008,0016) UI =EncapsulatedPDFStorage # 30, 1 SOPClassUID
(0008,0018) UI [1.2.826.0.1.3680043.2.1143.776842935192792959289022034349197114] # 64, 1 SOPInstanceUID
(0008,0020) DA [20090428] # 8, 1 StudyDate
(0008,0023) DA [20090428] # 8, 1 ContentDate
(0008,002a) DT [20090428153437.000000] # 22, 1 AcquisitionDateTime
(0008,0030) TM [182550.302160] # 14, 1 StudyTime
(0008,0033) TM [153426.000000] # 14, 1 ContentTime
(0008,0050) SH (no value available) # 0, 0 AccessionNumber
(0008,0060) CS [OT] # 2, 1 Modality
(0008,0064) CS [WSD] # 4, 1 ConversionType
(0008,0070) LO [LaTeX with hyperref package] # 28, 1 Manufacturer
(0008,0090) PN (no value available) # 0, 0 ReferringPhysiciansName
(0010,0010) PN [Mathieu Malaterre and co.] # 26, 1 PatientsName
(0010,0020) LO (no value available) # 0, 0 PatientID
(0010,0030) DA (no value available) # 0, 0 PatientsBirthDate
(0010,0040) CS (no value available) # 0, 0 PatientsSex
(0018,1020) LO [pdfTeX-1.21a] # 14, 1 SoftwareVersions
(0020,000d) UI [1.2.826.0.1.3680043.2.1143.1868121832223417351654232480755123133] # 64, 1 StudyInstanceUID
(0020,000e) UI [1.2.826.0.1.3680043.2.1143.1330099150825746617507846107663964311] # 64, 1 SeriesInstanceUID
(0020,0010) SH (no value available) # 0, 0 StudyID
(0020,0011) IS [1] # 2, 1 SeriesNumber
```



```

(0020,0013) IS [1] # 2, 1 InstanceNumber
(0028,0301) CS [YES] # 4, 1 BurnedInAnnotation
(0040,a043) SQ (Sequence with explicit length #=0) # 0, 1 ConceptNameCodeSequence
(ffff,e0dd) na (SequenceDelimitationItem for re-encod.) # 0, 0 SequenceDelimitationItem
(0042,0010) ST [GDCM Reference Manual] # 22, 1 DocumentTitle
(0042,0011) OB 25\\50\\44\\46\\2d\\31\\2e\\34\\0a\\25\\e7\\f3\\cf\\d3\\0a\\33\\32\\30\\37\\37\\20\\30... # 137568
(0042,0012) LO [application/pdf] # 16, 1 MIMETimeTypeOfEncapsulatedDocument

```

```

$ stat gdc.m.pdf
  File: `gdc.m.pdf'
  Size: 13756841      Blocks: 26912      IO Block: 4096   regular file
Device: fe01h/65025d Inode: 2675750      Links: 1
Access: (0644/-rw-r--r--)  Uid: ( 1002/mmalaterre)   Gid: ( 1002/mmalaterre)
Access: 2009-04-28 16:05:00.000000000 +0200
Modify: 2009-04-28 15:34:37.000000000 +0200
Change: 2009-04-28 16:05:00.000000000 +0200

```

Explanation for the different Date/Time mappings:

- Study Date/Time, Instance Creation Date/Time are both equal to the current time gdc.mpdf tool was run,
- Acquisition Date Time is set to the Modify Time of the actual pdf file,
- Content Date/Time are set from the actual PDF header info: CreationDate.

11.7 SEE ALSO

gdc.mconv(1), **gdc.mraw(1)**, **pdfinfo(1)**

11.8 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 12

Extract Data Element Value Field.

12.1 SYNOPSIS

```
gdcmmraw [options] file-in file-out
```

12.2 DESCRIPTION

The **gdcmmraw** tool is mostly used for development purpose. It is used to extract a specific binary field from a DICOM DataSet.

12.3 PARAMETERS

```
file-in    DICOM input filename
```

```
file-out    output filename
```

12.4 options

12.4.1 PARAMETERS

```
-i --input      Input filename
-o --output      Output filename
-t --tag         Specify tag to extract value from.
```

12.4.2 options

```
-S --split-frags Split fragments into multiple files.
-p --pattern      Specify trailing file pattern (see split-frags).
-P --pixel-data   Pixel Data trailing 0.
```

12.4.3 general options

```
-h    --help
```



```
-rw-r--r-- 1 mathieu mathieu 81512 2008-08-08 22:10 jpeg03.ljpeg  
-rw-r--r-- 1 mathieu mathieu 81694 2008-08-08 22:10 jpeg02.ljpeg  
-rw-r--r-- 1 mathieu mathieu 81564 2008-08-08 22:10 jpeg01.ljpeg  
-rw-r--r-- 1 mathieu mathieu 79970 2008-08-08 22:10 jpeg00.ljpeg
```

12.6 Footnote about JPEG files

It is a common misunderstanding to interchange 'JPEG 8bits lossy' with simply JPEG file. The JPEG specification is much broader than simply the common lossy 8bits file (as found on internet).

You can have

- JPEG Lossy 8bits
- JPEG Lossy 12bits
- JPEG Lossless 2-16bits

Those are what is defined in ITU-T T.81, ISO/IEC IS 10918-1.

12.7 SEE ALSO

gdcmdump(1), **gdcmrw(1)**

12.8 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 13

Scan a directory containing DICOM files.

13.1 SYNOPSIS

```
gdcmscanner [options] directory
```

13.2 DESCRIPTION

The **gdcmscanner** is a command line tool to quickly extract value from a set of DICOM attribute in a DICOM File-Set.

13.2.1 PARAMETERS

```
-d --dir          DICOM directory
-t --tag %d,%d    DICOM tag(s) to look for
```

13.2.2 options

```
-p --print        Print output.
-r --recursive    Recusively descend directory.
```

13.2.3 general options

```
-h  --help
    print this help text and exit

-v  --version
    print version information and exit

-V  --verbose
    verbose mode (warning+error).

-W  --warning
    warning mode, print warning information

-E  --error
    error mode, print error information

-D  --debug
    debug mode, print debug information
```

13.3 Typical usage

13.4 Simple usage

In order to display all the value for Patient Name (0010,0010) in the directory name **gdcmlData**, simply do:

```
$ gdcmscanner -t 10,10 -d gdcmlData -p
```

13.5 Complex usage

Because gdcmscanner does not support progress, you have to wait until all files are traversed to see any results. This is quite cumbersome, on UNIX this can be worked around with the following trick:

```
$ find gdcmlData -type d -exec gdcmscanner -t 10,10 -d {} -p ';'`
```

So all directory are locally traversed (no child directory are recursively traversed), which means results comes out much faster.

13.6 SEE ALSO

gdcmdump(1), **gdcmlraw(1)**

13.7 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 14

Tool to execute a DICOM Query/Retrieve operation

14.1 SYNOPSIS

```
gdcmscu [OPTION]...[OPERATION]...HOSTNAME...[PORT]...
```

Execute a DICOM Q/R operation to HOSTNAME, using port PORT (104 when not specified)

14.2 DESCRIPTION

The **gdcmscu** command line program is the tool to execute DICOM Query/Retrieve operation. It supports:

- C-ECHO (SCU)
- C-FIND (SCU)
- C-STORE (SCU)
- C-MOVE (SCU/SCP) C-MOVE operation are executed using two different ports (one for the SCU and one for the SCP).

14.3 PARAMETERS

14.4 options

14.4.1 options

```
-H --hostname    %s  Hostname.
-p --port        %d  Port number.
  --aetitle      %s  Set calling AE Title.
  --call         %s  Set called AE Title.
```

14.4.2 mode options

```
--echo          C-ECHO (default when none).
--store          C-STORE.
```

```
--find      C-FIND.
--move      C-MOVE.
```

14.4.3 C-STORE options

```
-i --input      %s  DICOM filename
-r --recursive  recursively process (sub-)directories
--store-query %s  Store constructed query in file
```

14.4.4 C-FIND/C-MOVE options

```
--patientroot  C-FIND Patient Root Model.
--studyroot    C-FIND Study Root Model.

--patient      C-FIND Query on Patient Info (cannot be used with --studyroot).
--study        C-FIND Query on Study Info.
--series       C-FIND Query on Series Info.
--image        C-FIND Query on Image Info.
--key %d,%d[%s] 0123,4567=VALUE for specifying search criteria (wildcard allowed)
                  With --key, leave blank (ie, --key 10,20="" or --key 10,20) to retrieve values
```

14.4.5 C-MOVE options

```
-o --output      %s  DICOM filename / directory
--port-scp %d      Port for incoming associations
--key %d,%d[%s]    0123,4567=VALUE for specifying search criteria (wildcard not allowed)
                  Note that C-MOVE supports the same queries as C-FIND, but no wildcards are allowed
```

14.4.6 general options

```
-h --help
    print this help text and exit

-v --version
    print version information and exit

-V --verbose
    verbose mode (warning+error).

-W --warning
    warning mode, print warning information

-E --error
    error mode, print error information

-D --debug
    debug mode, print debug information

-L --log-file
    specify a filename where to write logs

--queryhelp
    print query help
```

14.4.7 environment variable

```
GDCM_ROOT_UID Root UID
```

14.5 C-ECHO usage

gdcm SCU is a great tool to test if a DICOM server is up. For example to send a C-ECHO to server `dicom.example.com` using port 104, use:

```
$ gdcm SCU dicom.example.com
```

or if you prefer being explicit:

```
$ gdcm SCU --echo dicom.example.com 104
```

Using basic security your DICOM server might require that you set the appropriate called AE-TITLE

```
$ gdcm SCU --echo dicom.example.com 11112 --call SERVSCP
```

If you want to specify your own AE-TITLE (default is GDCMSCU), simply use:

```
$ gdcm SCU --echo dicom.example.com 11112 --call SERVSCP --aetitle MYSCU
```

For example you could test on the DICOM server provided by DICOMObject team:

```
$ gdcm SCU www.dicomserver.co.uk 11112
```

14.6 C-STORE usage

C-STORE is the operation that allow sending a DICOM file to a remote DICOM server. For instance to send a file called `myfile.dcm`

```
$ gdcm SCU --store dicom.example.com 104 myfile.dcm
```

or if you prefer being explicit:

```
$ gdcm SCU --store dicom.example.com 104 -i myfile.dcm
```

You can even send multiple files using the same association:

```
$ gdcm SCU --store dicom.example.com 104 myfile1.dcm myfile2.dcm myfile3.dcm ...
```

14.7 C-FIND usage

gdcm SCU also allow querying a DICOM server. This is the C-FIND operation, for example to find all DICOM Instance where PatientsName match a particular pattern, usage is simply:

```
$ gdcm SCU --find --patient dicom.example.com 11112 --patientroot --key 10,10,"A*"
```

We also support a DCMTK compatible convention:

```
$ gdcm SCU --find --patient dicom.example.com 11112 --patientroot --key 10,10="A*"
```

When an attribute is set without a value it will be part of the output result:

```
$ gdcm SCU --find --patient dicom.example.com 11112 --call MI2B2 --patientroot -k 10,10="A*" -k 10,20
```

14.8 C-MOVE usage

C-MOVE is the operation to retrieve a DICOM instance from a remote DICOM server. Most of the time, it is a subsequent operation after a C-FIND query. To retrieve a DICOM instance where PatientID is ABCD1234, simply execute:

```
$ gdcmscu --move --patient --aetitle ACME1 --call ACME_STORE dicom.example.com 5678 --patientroot -k 10,20="ABCD1234"
```

WARNING For this operation to work you need information from the DICOM server you are communicating with. Only the DICOM server you are sending a C-MOVE query will be responsible for sending back incoming associations (the actual C-STORE SCP). Therefore you need to make sure that your mapping of (AE-TITLE,PortNumber) is properly set on the DICOM server side as well as the port for incoming association (`--port-scp`).

gdcmscu does not currently support external C-STORE association (C-STORE request sent to an external SCP application).

14.9 patientroot notes

The flag `--patientroot` is just simply a wrapper around the syntax `--key 8,52=PATIENT`. For instance one would write using DCMTK syntax:

```
$ findscu --patient dicom.example.com 11112 --key 8,52=PATIENT --key 10,10="F*"
```

This would become using GDCM syntax:

```
$ gdcmscu --find --patient dicom.example.com 11112 --patientroot --key 10,10="F*"
```

14.10 Debugging

This is sometime difficult to investigate why a connection to a remote DICOM server cannot be done. Some recommendations follow:

Always try to do a simple C-ECHO at first. If you cannot get the C-ECHO to work none of the other operations will work. Before trying to a C-MOVE operation, make sure you can execute the C-FIND equivalent query first.

When doing a C-MOVE operation you really need to communicate with the PACS admin as the C-MOVE operation is different from the other lower level operation such as HTTP/GET. When doing a C-MOVE, the server will communicate back using another channel (could be different port) using its internal database to map an AE-TITLE back to the destination IP. Indeed the C-MOVE operation by design does not always use your incoming IP address to send back the resulting dataset. Instead it uses a mapping of AE-TITLE to IP address to send back any results. So pay particular attention to the spelling of your AE-TITLE and your incoming port (which may be different from the port to connect to the server).

14.11 Port Warning

Watch out that port ranging [1-1024] are reserved for admin and not easily accessible unless granted special privileges. Therefore the default 104 DICOM port might not be accessible to all your users.

14.12 C-STORE Warnings

When constructing a C-STORE operation, `gdcm SCU` will always use the Media Storage as found in the file to be sent. For encapsulated DICOM file (eg. RLE Lossless) the receiving SCP server might not support this compression and will legitimately refuse the C-STORE operation. In this case users have to manually convert to a non-compressed form this particular file:

```
$ gdcmconv --raw compressed.dcm non_compressed.dcm
```

14.13 C-MOVE Warnings

At the moment `gdcm SCU` only supports non-compressed transfer syntax. It will always request DataSet using Implicit VR Little Endian Transfer Syntax during a C-MOVE operation.

14.14 C-FIND IMAGE level (Composite Object Instance)

One should pay attention that `gdcm SCU -find` and `find SCU` are not completely equivalent. Using `gdcm SCU -find`, all Unique Keys will be added automatically. One can therefore execute something like this:

```
$ gdcm SCU --find --patientroot --image --key 8,18=1.2.3.4.5.6 dicom.example.com 11112
```

instead of the more explicit form

```
$ gdcm SCU --find --patientroot --image --key 8,18=1.2.3.4.5.6 dicom.example.com 11112 --key 10,20 --key 20,d --key
```

This would also be equivalent to:

```
$ find SCU --patient --key 8,52=IMAGE --key 8,18=1.2.3.4.5.6 dicom.example.com 11112 --key 10,20 --key 20,d --key
```

14.15 Storing the Query

It is also possible to store the query:

```
gdcm SCU --find --patient --patientroot dicom.example.com 11112 --key 10,20="*" --key 10,10 --store-query query.dcm
```

One can then check the DataSet values send for the query:

```
$ gdcmdump query.dcm
# Dicom-File-Format

# Dicom-Meta-Information-Header
# Used TransferSyntax:

# Dicom-Data-Set
# Used TransferSyntax: 1.2.840.10008.1.2
(0008,0005) ?? (CS) [ISO_IR 192] # 10,1-n Specific Character Set
(0008,0052) ?? (CS) [PATIENT ] # 8,1 Query/Retrieve Level
(0010,0010) ?? (PN) (no value) # 0,1 Patient's Name
(0010,0020) ?? (LO) [* ] # 2,1 Patient ID
```

The Specific Character Set was set to "ISO_IR 192" as the locale encoding of the system was found automatically by `gdcm SCU` to be UTF-8.

This means that the following command line will properly setup the Query with the appropriate Charset to be executed correctly:

```
$ gdcm SCU --find --patient --patientroot dicom.example.com 11112 --key 10,10="*Jérôme"
```

the query is always executed on the server side (SCP), some implementations does not support string matching with different Character Set.

14.16 DICOM Public Servers

An up to date list of DICOM Public Servers can be found at:

<http://www.dclunie.com/medical-image-faq/html/part8.html#DICOMPublicServers>

14.17 SEE ALSO

`gdcmconv(1)`

14.18 COPYRIGHT

Copyright Insight Software Consortium

Chapter 15

Concatenate/Extract DICOM files.

15.1 SYNOPSIS

```
gdcmtar [options] file-in file-out
```

15.2 DESCRIPTION

The **gdcmtar** is a command line tool used to tar/untar multi-frames images (including SIEMENS MOSAIC file)

15.3 PARAMETERS

file-in DICOM input filename

file-out DICOM output filename

15.4 options

15.4.1 options

```
--enhance      enhance (default)
-U --unenhance  unenhance
-M --mosaic     Split SIEMENS Mosaic image into multiple frames.
-p --pattern    Specify trailing file pattern.
--root-uid      Root UID.
```

15.4.2 general options

```
-h --help      print this help text and exit
-v --version    print version information and exit
-V --verbose    verbose mode (warning+error).
```

```
-W  --warning
    warning mode, print warning information

-E  --error
    error mode, print error information

-D  --debug
    debug mode, print debug information
```

15.4.3 environment variable

GDCM_ROOT_UID Root UID

15.5 Typical usage

15.5.1 SIEMENS Mosaic

```
$ gdcminfo MR-sonata-3D-as-Tile.dcm
```

```
MediaStorage is 1.2.840.10008.5.1.4.1.1.4 [MR Image Storage]
TransferSyntax is 1.2.840.10008.1.2.1 [Explicit VR Little Endian]
NumberOfDimensions: 2
Dimensions: (384,384,1)
\&...
```

```
$ gdcmtar --mosaic -i MR-sonata-3D-as-Tile.dcm -o mosaic --pattern %03d.dcm
```

Will output:

```
-rw-r--r-- 1 mathieu mathieu 72882 2009-08-10 11:14 mosaic000.dcm
-rw-r--r-- 1 mathieu mathieu 72886 2009-08-10 11:14 mosaic001.dcm
-rw-r--r-- 1 mathieu mathieu 72886 2009-08-10 11:14 mosaic002.dcm
-rw-r--r-- 1 mathieu mathieu 72886 2009-08-10 11:14 mosaic003.dcm
-rw-r--r-- 1 mathieu mathieu 72886 2009-08-10 11:14 mosaic004.dcm
-rw-r--r-- 1 mathieu mathieu 72886 2009-08-10 11:14 mosaic005.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic006.dcm
-rw-r--r-- 1 mathieu mathieu 72882 2009-08-10 11:14 mosaic007.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic008.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic009.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic010.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic011.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic012.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic013.dcm
-rw-r--r-- 1 mathieu mathieu 72882 2009-08-10 11:14 mosaic014.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic015.dcm
-rw-r--r-- 1 mathieu mathieu 72882 2009-08-10 11:14 mosaic016.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic017.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic018.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic019.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic020.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic021.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic022.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic023.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic024.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic025.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic026.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic027.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic028.dcm
-rw-r--r-- 1 mathieu mathieu 72884 2009-08-10 11:14 mosaic029.dcm
-rw-r--r-- 1 mathieu mathieu 72882 2009-08-10 11:14 mosaic030.dcm
```



```
$ gdcminfo mosaic000.dcm
```

```
MediaStorage is 1.2.840.10008.5.1.4.1.1.4 [MR Image Storage]  
TransferSyntax is 1.2.840.10008.1.2.1 [Explicit VR Little Endian]  
NumberOfDimensions: 2  
Dimensions: (64,64,1)  
\&...
```

15.6 SEE ALSO

gdcmdump(1), **gdcmrw(1)**, **gdcminfo(1)**

15.7 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 16

Simple DICOM viewer.

16.1 SYNOPSIS

```
gdcviewer [options] file-in
```

16.2 DESCRIPTION

The **gdcviewer** is a simple tool that show how to use [vtkGDCMImageReader](#). The class that use gdc to make a layer to VTK. **gdcviewer** is basically only just a wrapper around VTK/GDCM.

This tool is meant for testing integration of GDCM in VTK. You should see it as a demo tool. It does compile with VTK ranging from 4.2 to 5.8, but only with VTK 5.2 (or above) can only play with the widgets (as described below).

16.3 PARAMETERS

```
file-in    DICOM input filename
```

16.4 options

16.4.1 options

<code>--force-rescale</code>	force rescale (advanced users)
<code>--force-spacing</code>	force spacing (advanced users)
<code>-r --recursive</code>	Recursively descend directory

16.4.2 general options

<code>-h</code>	<code>--help</code>	print this help text and exit
<code>-v</code>	<code>--version</code>	print version information and exit
<code>-V</code>	<code>--verbose</code>	verbose mode (warning+error).

```
-W  --warning
    warning mode, print warning information

-E  --error
    error mode, print error information

-D  --debug
    debug mode, print debug information
```

16.5 Typical usage

16.6 Simple usage

For now `gdcmviewer` should be started from a command line prompt. The next argument should be the name of the DICOM file you wish to read. For instance:

```
$ gdcmviewer -V 012345.002.050.dcm
```

`gdcmviewer` will try to read your file, and then print the `vtk` information associated with this file. Basically what kind of image you are looking at.

- `ScalarType` is the DICOM Real World Value type
- `Dimensions` is the dimension of the image
- `Spacing` is the spacing of the image
- `NumberOfScalarComponents` should be 1 for grayscale & `PALETTE COLOR` and 3 for `RGB`, `YBR` data.

16.7 Wiki Link

The wiki page, with color pictures can be found at: <http://gdcm.sourceforge.net/wiki/index.php/-Gdcmviewer>

16.8 SEE ALSO

`gdcmdump(1)`, `gdcm2vtk(1)`

16.9 COPYRIGHT

Copyright (c) 2006-2011 Mathieu Malaterre

Chapter 17

Todo List

Class [gdcm::CSAHeader](#)

MrEvaProtocol in 29,1020 contains ^M that would be nice to get rid of on UNIX system...

Class [gdcm::Overlay](#)

Is there actually any way to recognize an overlay ? On images with multiple overlay I do not see any way to differentiate them (other than the group tag).

Class [gdcm::SequenceOfFragments](#)

I do not enforce that Sequence of Fragments ends with a SQ end del

Class [gdcm::TransferSyntax](#)

: The implementation is completely retarded -> see [gdcm::UIDs](#) for a replacement We need: IsSupported We need preprocess of raw/xml file We need GetFullName()

Member [gdcm::UIDGenerator::IsValid](#) (const char *uid)

: Move that in DataStructureAndEncoding (see FileMetaInformation::CheckFileMetaInformation)

Chapter 18

Deprecated List

Member `gdcm::CompositeNetworkFunctions::ConstructQuery` (`ERootType` inRootType, `EQueryLevel` inQueryLevel, `const KeyValuePairArrayType &keys`, `bool` inMove=false)

Member `gdcm::DataElement::GetSequenceOfItems` () `const`

Replaced by `DataElement::GetValueAsSQ()` as of GDCM 2.2.

Member `gdcm::FileSet::AddFile` (`File` `const &`)

. Does nothing

Member `gdcm::TransferSyntax::GetSwapCode` () `const`

Return the `SwapCode` associated with the Transfer Syntax. Be careful with the special GE private syntax the `DataSet` is written in little endian but the Pixel Data is in Big Endian.

Chapter 19

Bug List

Class `gdcm::DICOMDIRGenerator`

: There is a current limitation of not handling Referenced SOP Class UID / Referenced SOP Instance UID simply because the `gdcm::Scanner` does not allow us See PS 3.11 / Table D.3-2 STD-GEN Additional DICOMDIR Keys

Class `gdcm::IPPSorter`

There are currently a couple of bugs in this implementation:

Chapter 20

Namespace Index

20.1 Namespace List

Here is a list of all namespaces with brief descriptions:

gdc	103
gdc::network	124
gdc::SegmentHelper	130
gdc::terminal	
Class for Terminal Allow one to print in color in a shell	130

Chapter 21

Hierarchical Index

21.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

gdcn::network::AbstractSyntax	144
gdcn::network::ApplicationContext	154
gdcn::ApplicationEntity	155
gdcn::network::ARTIMTimer	160
gdcn::ASN1	161
gdcn::network::AsynchronousOperationsWindowSub	162
gdcn::Attribute< Group, Element, TVR, TVM >	162
gdcn::Attribute< Group, Element, TVR, VM::VM1 >	170
gdcn::Attribute< Group, Element, TVR, VM::VM1_n >	177
gdcn::Attribute< Group, Element, TVR, VM::VM1_3 >	174
gdcn::Attribute< Group, Element, TVR, VM::VM1_8 >	176
gdcn::Attribute< Group, Element, TVR, VM::VM2_n >	183
gdcn::Attribute< Group, Element, TVR, VM::VM2_2n >	181
gdcn::Attribute< Group, Element, TVR, VM::VM3_n >	186
gdcn::Attribute< Group, Element, TVR, VM::VM3_3n >	184
gdcn::Base64	189
gdcn::network::BaseCompositeMessage	191
gdcn::network::CEchoRQ	223
gdcn::network::CEchoRSP	224
gdcn::network::CFindCancelRQ	226
gdcn::network::CFindRQ	227
gdcn::network::CFindRSP	229
gdcn::network::CMoveCancelRq	230
gdcn::network::CMoveRQ	231
gdcn::network::CMoveRSP	233
gdcn::network::CStoreRQ	264
gdcn::network::CStoreRSP	266
gdcn::network::BasePDU	192
gdcn::network::AAabortPDU	133
gdcn::network::AAssociateACPDU	135
gdcn::network::AAssociateRJPDU	138
gdcn::network::AAssociateRQPDU	139
gdcn::network::AReleaseRPPDU	156

gdcmm::network::AReleaseRQPDU	158
gdcmm::network::PDataTFPDU	525
std::basic_string< Char >	
std::string	
gdcmm::String< TDelimiter, TMaxLength, TPadChar >	674
gdcmm::SegmentHelper::BasicCodedEntry	198
gdcmm::BitmapToBitmapFilter	211
gdcmm::PixmapToPixmapFilter	552
gdcmm::ImageToImageFilter	428
gdcmm::ImageApplyLookupTable	397
gdcmm::ImageChangePhotometricInterpretation	399
gdcmm::ImageChangePlanarConfiguration	403
gdcmm::ImageChangeTransferSyntax	406
gdcmm::ImageFragmentSplitter	416
gdcmm::ByteBuffer	216
gdcmm::ByteSwap< T >	217
gdcmm::ByteSwapFilter	218
gdcmm::network::CFind	226
gdcmm::Coder	235
gdcmm::Codec	234
gdcmm::AudioCodec	187
gdcmm::ImageCodec	410
gdcmm::DeltaEncodingCodec	296
gdcmm::JPEG2000Codec	455
gdcmm::JPEGCodec	460
gdcmm::JPEG12Codec	451
gdcmm::JPEG16Codec	453
gdcmm::JPEG8Codec	458
gdcmm::JPEGLSCCodec	464
gdcmm::KAKADUCCodec	467
gdcmm::PGXCodec	536
gdcmm::PNMCodec	557
gdcmm::PVRGCodec	579
gdcmm::RAWCodec	593
gdcmm::RLECodec	605
gdcmm::PDFCodec	532
gdcmm::CodeString	237
gdcmm::network::CompositeMessageFactory	243
gdcmm::CompositeNetworkFunctions	244
gdcmm::ConstCharWrapper	247
gdcmm::CryptographicMessageSyntax	250
gdcmm::CSAElement	251
gdcmm::CSAHeader	256
gdcmm::CSAHeaderDict	260
gdcmm::CSAHeaderDictEntry	262
gdcmm::DataElement	270
gdcmm::CP246ExplicitDataElement	248
gdcmm::ExplicitDataElement	350
gdcmm::ExplicitImplicitDataElement	351
gdcmm::Fragment	381
gdcmm::BasicOffsetTable	201
gdcmm::ImplicitDataElement	435
gdcmm::Item	446

gdcmm::UNExplicitDataElement	800
gdcmm::UNExplicitImplicitDataElement	802
gdcmm::VR16ExplicitDataElement	825
gdcmm::DataSet	282
gdcmm::CommandDataSet	241
gdcmm::FileMetaInformation	364
gdcmm::DataSetHelper	291
gdcmm::Decoder	292
gdcmm::Codec	234
gdcmm::DefinedTerms	293
gdcmm::Defs	294
gdcmm::DICOMDIR	298
gdcmm::DICOMDIRGenerator	298
gdcmm::Dict	301
gdcmm::DictConverter	303
gdcmm::DictEntry	305
gdcmm::Dicts	310
gdcmm::network::DIMSE	312
gdcmm::DirectionCosines	314
gdcmm::Directory	316
gdcmm::DirectoryHelper	318
gdcmm::DummyValueGenerator	320
gdcmm::Element< TVR, TVM >	323
gdcmm::Element< TVR, VM::VM1_n >	327
gdcmm::Element< TVR, VM::VM1_2 >	326
gdcmm::Element< TVR, VM::VM2_n >	331
gdcmm::Element< TVR, VM::VM2_2n >	329
gdcmm::Element< TVR, VM::VM3_n >	334
gdcmm::Element< TVR, VM::VM3_3n >	332
gdcmm::Element< VR::AS, VM::VM5 >	335
gdcmm::Element< VR::OB, VM::VM1_n >	323
gdcmm::Element< VR::OB, VM::VM1 >	336
gdcmm::Element< VR::OW, VM::VM1_n >	323
gdcmm::Element< VR::OW, VM::VM1 >	337
gdcmm::ElementDisableCombinations< TVR, TVM >	339
gdcmm::ElementDisableCombinations< VR::OB, VM::VM1_n >	340
gdcmm::ElementDisableCombinations< VR::OW, VM::VM1_n >	340
gdcmm::EncapsulatedDocument	340
gdcmm::EncodingImplementation< T >	341
gdcmm::EncodingImplementation< VR::VRASCII >	341
gdcmm::EncodingImplementation< VR::VRBINARY >	342
gdcmm::EnumeratedValues	344
gdcmm::Event	345
gdcmm::AnyEvent	152
gdcmm::AbortEvent	143
gdcmm::AnonymizeEvent	145
gdcmm::DataEvent	280
gdcmm::DataSetEvent	289
gdcmm::EndEvent	343
gdcmm::ExitEvent	348
gdcmm::InitializeEvent	436
gdcmm::IterationEvent	449

gdcmm::ModifiedEvent	495
gdcmm::ProgressEvent	576
gdcmm::StartEvent	664
gdcmm::UserEvent	806
gdcmm::NoEvent	509
std::exception	
gdcmm::CSAHeaderDictException	263
gdcmm::DataElementException	279
gdcmm::Exception	347
gdcmm::ParseException	521
gdcmm::Fiducials	353
gdcmm::FileDerivation	360
gdcmm::FileExplicitFilter	362
gdcmm::Filename	370
gdcmm::FilenameGenerator	372
gdcmm::FileSet	374
gdcmm::Global	384
gdcmm::GroupDict	386
gdcmm::IconImageFilter	388
gdcmm::IconImageGenerator	390
gdcmm::ignore_char	392
gdcmm::ImageConverter	415
gdcmm::ImageHelper	418
gdcmm::network::ImplementationClassUIDSub	433
gdcmm::network::ImplementationUIDSub	433
gdcmm::network::ImplementationVersionNameSub	434
gdcmm::IOD	438
gdcmm::IODEntry	439
gdcmm::IODs	441
gdcmm::Scanner::ltstr	476
gdcmm::Macro	476
gdcmm::Macros	478
gdcmm::network::MaximumLengthSub	479
gdcmm::MD5	480
gdcmm::MediaStorage	481
gdcmm::Module	497
gdcmm::ModuleEntry	499
gdcmm::NestedModuleEntries	507
gdcmm::Modules	501
gdcmm::Object	510
gdcmm::BaseRootQuery	194
gdcmm::FindPatientRootQuery	377
gdcmm::FindStudyRootQuery	379
gdcmm::MovePatientRootQuery	503
gdcmm::MoveStudyRootQuery	505
gdcmm::Bitmap	203
gdcmm::Pixmap	545
gdcmm::Image	393
gdcmm::Curve	267
gdcmm::File	354
gdcmm::FileWithName	375
gdcmm::LookupTable	471
gdcmm::SegmentedPaletteColorLookupTable	621

gdcmmesh::MeshPrimitive	492
gdcmmesh::Overlay	515
gdcmmesh::Segment	616
gdcmmesh::Subject	680
gdcmmesh::Anonymizer	148
gdcmmesh::Command	239
gdcmmesh::MemberCommand< T >	488
gdcmmesh::SimpleMemberCommand< T >	647
gdcmmesh::FileAnonymizer	357
gdcmmesh::network::ULConnectionManager	794
gdcmmesh::Scanner	610
gdcmmesh::ServiceClassUser	642
gdcmmesh::Surface	683
gdcmmesh::Value	810
gdcmmesh::ByteValue	218
gdcmmesh::SequenceOfFragments	627
gdcmmesh::SequenceOfItems	632
gdcmmesh::Orientation	513
gdcmmesh::Parser	523
gdcmmesh::Patient	525
gdcmmesh::PDBelement	528
gdcmmesh::PDBHeader	530
gdcmmesh::network::PDUFactory	533
gdcmmesh::PersonName	535
gdcmmesh::PhotometricInterpretation	538
gdcmmesh::PixelFormat	540
gdcmmesh::Preamble	560
gdcmmesh::PresentationContext	561
gdcmmesh::network::PresentationContextAC	563
gdcmmesh::PresentationContextGenerator	564
gdcmmesh::network::PresentationContextRQ	566
gdcmmesh::network::PresentationDataValue	568
gdcmmesh::Printer	570
gdcmmesh::DictPrinter	308
gdcmmesh::Dumper	321
gdcmmesh::PrivateDict	573
gdcmmesh::PythonFilter	581
gdcmmesh::QueryBase	582
gdcmmesh::QueryImage	585
gdcmmesh::QueryPatient	587
gdcmmesh::QuerySeries	589
gdcmmesh::QueryStudy	591
gdcmmesh::QueryFactory	584
gdcmmesh::Reader	595
gdcmmesh::PixmapReader	548
gdcmmesh::ImageReader	421
gdcmmesh::ImageRegionReader	425
gdcmmesh::SegmentReader	622
gdcmmesh::SurfaceReader	692
gdcmmesh::Region	600
gdcmmesh::BoxRegion	213
gdcmmesh::Rescaler	602

gdcm::network::RoleSelectionSub	608
gdcm::SerieHelper::Rule	609
gdcm::SerieHelper	638
gdcm::Series	640
gdcm::network::ServiceClassApplicationInformation	641
gdcm::SHA1	646
gdcm::SimpleSubjectWatcher	651
gdcm::SmartPointer< ObjectType >	652
gdcm::SmartPointer< gdcm::Bitmap >	652
gdcm::SmartPointer< gdcm::File >	652
gdcm::SmartPointer< gdcm::gdcm::Subject >	652
gdcm::SmartPointer< gdcm::Image >	652
gdcm::SmartPointer< gdcm::MemberCommand >	652
gdcm::SmartPointer< gdcm::MeshPrimitive >	652
gdcm::SmartPointer< gdcm::Pixmap >	652
gdcm::SmartPointer< gdcm::SimpleMemberCommand >	652
gdcm::SmartPointer< LookupTable >	652
gdcm::SmartPointer< Segment >	652
gdcm::SmartPointer< Surface >	652
gdcm::SmartPointer< Value >	652
gdcm::network::SOPClassExtendedNegociationSub	655
gdcm::SOPClassUIDToIOD	656
gdcm::Sorter	657
gdcm::IPPSorter	442
gdcm::Spacing	661
gdcm::Spectroscopy	663
gdcm::SplitMosaicFilter	663
gdcm::static_assert_test< x >	666
gdcm::STATIC_ASSERTION_FAILURE< x >	666
gdcm::STATIC_ASSERTION_FAILURE< true >	666
gdcm::StreamImageReader	666
gdcm::StreamImageWriter	669
String<'\', 64 >	
gdcm::LO	469
gdcm::StringFilter	678
gdcm::Study	680
gdcm::SurfaceHelper	689
gdcm::SwapCode	696
gdcm::SwapperDoOp	698
gdcm::SwapperNoOp	699
gdcm::System	699
gdcm::Table	703
gdcm::TableEntry	704
gdcm::TableReader	705
gdcm::XMLDictReader	886
gdcm::XMLPrivateDictReader	887
gdcm::network::TableRow	707
gdcm::Tag	708
gdcm::PrivateTag	575
gdcm::TagPath	714
gdcm::Testing	716
gdcm::Trace	719
gdcm::TransferSyntax	723

gdcm::network::TransferSyntaxSub	726
gdcm::network::Transition	727
gdcm::Type	729
gdcm::UI	731
gdcm::UIDGenerator	731
gdcm::UIDs	733
gdcm::network::ULAction	752
gdcm::network::ULActionAA1	755
gdcm::network::ULActionAA2	756
gdcm::network::ULActionAA3	757
gdcm::network::ULActionAA4	758
gdcm::network::ULActionAA5	759
gdcm::network::ULActionAA6	760
gdcm::network::ULActionAA7	762
gdcm::network::ULActionAA8	763
gdcm::network::ULActionAE1	764
gdcm::network::ULActionAE2	765
gdcm::network::ULActionAE3	766
gdcm::network::ULActionAE4	767
gdcm::network::ULActionAE5	769
gdcm::network::ULActionAE6	770
gdcm::network::ULActionAE7	771
gdcm::network::ULActionAE8	772
gdcm::network::ULActionAR1	773
gdcm::network::ULActionAR10	774
gdcm::network::ULActionAR2	776
gdcm::network::ULActionAR3	777
gdcm::network::ULActionAR4	778
gdcm::network::ULActionAR5	779
gdcm::network::ULActionAR6	780
gdcm::network::ULActionAR7	781
gdcm::network::ULActionAR8	783
gdcm::network::ULActionAR9	784
gdcm::network::ULActionDT1	785
gdcm::network::ULActionDT2	786
gdcm::network::ULConnection	789
gdcm::network::ULConnectionCallback	791
gdcm::network::ULBasicCallback	787
gdcm::network::ULWritingCallback	798
gdcm::network::ULConnectionInfo	793
gdcm::network::ULEvent	797
gdcm::network::ULTransitionTable	798
gdcm::Unpacker12Bits	804
gdcm::Usage	805
gdcm::network::UserInformation	808
gdcm::Validate	809
gdcm::ValueIO< TDE, TSwap, TType >	812
gdcm::Version	813
gdcm::VL	814
gdcm::VM	816
gdcm::VMToLength< T >	820
gdcm::VR	820
gdcm::VRToEncoding< T >	827
gdcm::VRToType< T >	827

gdcmm::VRToType< TVR >	827
gdcmm::VRVLSIZE< T >	828
gdcmm::VRVLSIZE< 0 >	828
gdcmm::VRVLSIZE< 1 >	828
vtkImageAlgorithm	
vtkImagePlanarComponentsToComponents	868
vtkImageMapToColors	
vtkImageMapToWindowLevelColors2	866
vtkImageWriter	
vtkGDCMImageWriter	835
vtkLookupTable	
vtkLookupTable16	873
vtkMedicalImageProperties	
vtkGDCMMedicalImageProperties	840
vtkMedicalImageReader2	
vtkGDCMImageReader	829
vtkGDCMThreadedImageReader	850
vtkObject	
vtkGDCMTesting	847
vtkImageColorViewer	856
vtkRTStructSetProperties	875
vtkPolyDataAlgorithm	
vtkGDCMPolyDataReader	841
vtkPolyDataWriter	
vtkGDCMPolyDataWriter	844
vtkThreadedImageAlgorithm	
vtkGDCMThreadedImageReader2	852
vtkImageMapToColors16	863
vtkImageRGBToYBR	870
vtkImageYBRToRGB	871
gdcmm::Waveform	880
gdcmm::Writer	880
gdcmm::PixmapWriter	554
gdcmm::ImageWriter	430
gdcmm::SegmentWriter	625
gdcmm::SurfaceWriter	695

Chapter 22

Class Index

22.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

gdcn::network::AAabortPDU	
AAabortPDU Table 9-26 A-ABORT PDU FIELDS	133
gdcn::network::AAssociateACPDU	
AAssociateACPDU Table 9-17 ASSOCIATE-AC PDU fields	135
gdcn::network::AAssociateRJPDU	
AAssociateRJPDU Table 9-21 ASSOCIATE-RJ PDU FIELDS	138
gdcn::network::AAssociateRQPDU	
AAssociateRQPDU Table 9-11 ASSOCIATE-RQ PDU fields	139
gdcn::AbortEvent	143
gdcn::network::AbstractSyntax	
AbstractSyntax Table 9-14 ABSTRACT SYNTAX SUB-ITEM FIELDS	144
gdcn::AnonymizeEvent	
AnonymizeEvent Special type of event triggered during the Anonymization process	145
gdcn::Anonymizer	
Anonymizer This class is a multi purpose anonymizer. It can work in 2 mode:	148
gdcn::AnyEvent	152
gdcn::network::ApplicationContext	
ApplicationContext Table 9-12 APPLICATION CONTEXT ITEM FIELDS Looks like Application Con- text can only be 64 bytes at max (see Figure 9-1 / PS 3.8 - 2009)	154
gdcn::ApplicationEntity	
ApplicationEntity	155
gdcn::network::AReleaseRPPDU	
AReleaseRPPDU Table 9-25 A-RELEASE-RP PDU fields	156
gdcn::network::AReleaseRQPDU	
AReleaseRQPDU Table 9-24 A-RELEASE-RQ PDU FIELDS	158
gdcn::network::ARTIMTimer	
ARTIMTimer This file contains the code for the ARTIM timer	160
gdcn::ASN1	
Class for ASN1	161
gdcn::network::AsynchronousOperationsWindowSub	
AsynchronousOperationsWindowSub PS 3.7 Table D.3-7 ASYNCHRONOUS OPERATIONS WIND- OW SUB-ITEM FIELDS (A-ASSOCIATE-RQ)	162

gdcm::Attribute< Group, Element, TVR, TVM >	
Attribute class This class use template metaprograming tricks to let the user know when the template instantiation does not match the public dictionary	162
gdcm::Attribute< Group, Element, TVR, VM::VM1 >	170
gdcm::Attribute< Group, Element, TVR, VM::VM1_3 >	174
gdcm::Attribute< Group, Element, TVR, VM::VM1_8 >	176
gdcm::Attribute< Group, Element, TVR, VM::VM1_n >	177
gdcm::Attribute< Group, Element, TVR, VM::VM2_2n >	181
gdcm::Attribute< Group, Element, TVR, VM::VM2_n >	183
gdcm::Attribute< Group, Element, TVR, VM::VM3_3n >	184
gdcm::Attribute< Group, Element, TVR, VM::VM3_n >	186
gdcm::AudioCodec	
AudioCodec	187
gdcm::Base64	
Class for Base64	189
gdcm::network::BaseCompositeMessage	
BaseCompositeMessage The Composite events described in section 3.7-2009 of the DICOM standard all use their own messages. These messages are constructed using Presentation Data Values, from section 3.8-2009 of the standard, and then fill in appropriate values in their datasets	191
gdcm::network::BasePDU	
BasePDU base class for PDUs	192
gdcm::BaseRootQuery	
BaseRootQuery contains: a baseclass which will produce a dataset for c-find and c-move with patient/study root	194
gdcm::SegmentHelper::BasicCodedEntry	
This structure defines a basic coded entry with all of its attributes	198
gdcm::BasicOffsetTable	
Class to represent a BasicOffsetTable	201
gdcm::Bitmap	
Bitmap class A bitmap based image. Used as parent for both IconImage and the main Pixel Data Image It does not contains any World Space information (IPP, IOP)	203
gdcm::BitmapToBitmapFilter	
BitmapToBitmapFilter class Super class for all filter taking an image and producing an output image	211
gdcm::BoxRegion	
Class for manipulation box region This is a very simple implementation of the Region class. It only support 3D box type region. It assumes the 3D Box does not have a tilt Origin is as (0,0,0)	213
gdcm::ByteBuffer	
ByteBuffer	216
gdcm::ByteSwap< T >	
ByteSwap	217
gdcm::ByteSwapFilter	
ByteSwapFilter In place byte-swapping of a dataset FIXME: FL status ??	218
gdcm::ByteValue	
Class to represent binary value (array of bytes)	218
gdcm::network::CEchoRQ	
CEchoRQ this file defines the messages for the cecho action	223
gdcm::network::CEchoRSP	
CEchoRSP this file defines the messages for the cecho action	224
gdcm::network::CFind	226
gdcm::network::CFindCancelRQ	
CFindCancelRQ this file defines the messages for the cfind action	226
gdcm::network::CFindRQ	
CFindRQ this file defines the messages for the cfind action	227

gdcm::network::CFindRSP	
CFindRSP this file defines the messages for the cfind action	229
gdcm::network::CMoveCancelRq	230
gdcm::network::CMoveRQ	
CMoveRQ this file defines the messages for the cmove action	231
gdcm::network::CMoveRSP	
CMoveRSP this file defines the messages for the cmove action	233
gdcm::Codec	
Codec class	234
gdcm::Coder	
Coder	235
gdcm::CodeString	
CodeString This is an implementation of DICOM VR: CS The ctor will properly Trim so that operator== is correct	237
gdcm::Command	
Command superclass for callback/observer methods	239
gdcm::CommandDataSet	
Class to represent a Command DataSet	241
gdcm::network::CompositeMessageFactory	
CompositeMessageFactory This class constructs PDataPDUs, but that have been specifically constructed for the composite DICOM services (C-Echo, C-Find, C-Get, C-Move, and C-Store). It will also handle parsing the incoming data to determine which of the CompositePDUs the incoming data is, and so therefore allowing the scu to determine what to do with incoming data (if acting as a storescp server, for instance)	243
gdcm::CompositeNetworkFunctions	
Composite Network Functions These functions provide a generic API to the DICOM functions implemented in GDCM. Advanced users can use this code as a template for building their own versions of these functions (for instance, to provide progress bars or some other way of handling returned query information), but for most users, these functions should be sufficient to interface with a PACS to a local machine. Note that these functions are not contained within a static class or some other class-style interface, because multiple connections can be instantiated in the same program. The DICOM standard is much more function oriented rather than class oriented in this instance, so the design of this API reflects that functional approach. These functions implements the following SCU operations:	244
gdcm::ConstCharWrapper	
Do not use me	247
gdcm::CP246ExplicitDataElement	
Class to read/write a DataElement as CP246Explicit Data Element	248
gdcm::CryptographicMessageSyntax	
Class for CryptographicMessageSyntax encryption. This is just a simple wrapper around openssl PKCS7_encrypt functionalities	250
gdcm::CSAElement	
Class to represent a CSA Element	251
gdcm::CSAHeader	
Class for CSAHeader	256
gdcm::CSAHeaderDict	
Class to represent a map of CSAHeaderDictEntry	260
gdcm::CSAHeaderDictEntry	
Class to represent an Entry in the Dict Does not really exist within the DICOM definition, just a way to minimize storage and have a mapping from gdcm::Tag to the needed information	262
gdcm::CSAHeaderDictException	263
gdcm::network::CStoreRQ	
CStoreRQ this file defines the messages for the cecho action	264

gdcm::network::CStoreRSP	
CStoreRSP this file defines the messages for the cecho action	266
gdcm::Curve	
Curve class to handle element 50xx,3000 Curve Data WARNING: This is deprecated and lastly defined in PS 3.3 - 2004	267
gdcm::DataElement	
Class to represent a Data Element either Implicit or Explicit	270
gdcm::DataElementException	279
gdcm::DataEvent	
DataEvent	280
gdcm::DataSet	
Class to represent a Data Set (which contains Data Elements) A Data Set represents an instance of a real world Information Object	282
gdcm::DataSetEvent	
DataSetEvent Special type of event triggered during the DataSet store/move process	289
gdcm::DataSetHelper	
DataSetHelper (internal class, not intended for user level)	291
gdcm::Decoder	
Decoder	292
gdcm::DefinedTerms	
Defined Terms are used when the specified explicit Values may be extended by implementors to include additional new Values. These new Values shall be specified in the Conformance Statement (see PS 3.2) and shall not have the same meaning as currently defined Values in this standard. A Data Element with Defined Terms that does not contain a Value equivalent to one of the Values currently specified in this standard shall not be considered to have an invalid value. Note: Interpretation Type ID (4008,0210) is an example of a Data Element having Defined Terms. It is defined to have a Value that may be one of the set of standard Values; REPORT or AMENDMENT (see PS 3.3). Because this Data Element has Defined Terms other Interpretation Type IDs may be defined by the implementor	293
gdcm::Defs	
FIXME I do not like the name ' Defs '	294
gdcm::DeltaEncodingCodec	
DeltaEncodingCodec compression used by some private vendor	296
gdcm::DICOMDIR	
DICOMDIR class	298
gdcm::DICOMDIRGenerator	
DICOMDIRGenerator class This is a STD-GEN-CD DICOMDIR generator. ref: PS 3.11-2008 Annex D (Normative) - General Purpose CD-R and DVD Interchange Profiles	298
gdcm::Dict	
Class to represent a map of DictEntry	301
gdcm::DictConverter	
Class to convert a .dic file into something else:	303
gdcm::DictEntry	
Class to represent an Entry in the Dict Does not really exist within the DICOM definition, just a way to minimize storage and have a mapping from gdcm::Tag to the needed information	305
gdcm::DictPrinter	
DictPrinter class	308
gdcm::Dicts	
Class to manipulate the sum of knowledge (all the dict user load)	310
gdcm::network::DIMSE	
DIMSE PS 3.7 - 2009 Annex E Command Dictionary (Normative) E.1 REGISTRY OF DICOM COMMAND ELEMENTS Table E.1-1 COMMAND FIELDS (PART 1)	312
gdcm::DirectionCosines	
Class to handle DirectionCosines	314

gdcm::Directory	
Class for manipulation directories	316
gdcm::DirectoryHelper	
DirectoryHelper this class is designed to help mitigate some of the commonly performed operations on directories. namely: 1) the ability to determine the number of series in a directory by what type of series is present 2) the ability to find all ct series in a directory 3) the ability to find all mr series in a directory 4) to load a set of DataSets from a series that's already been sorted by the IPP sorter 5) For rtstruct stuff, you need to know the sopinstanceuid of each z plane, so there's a retrieval function for that 6) then a few other functions for rtstruct writeouts	318
gdcm::DummyValueGenerator	
Class for generating dummy value	320
gdcm::Dumper	
Codec class	321
gdcm::Element< TVR, TVM >	
Element class	323
gdcm::Element< TVR, VM::VM1_2 >	326
gdcm::Element< TVR, VM::VM1_n >	327
gdcm::Element< TVR, VM::VM2_2n >	329
gdcm::Element< TVR, VM::VM2_n >	331
gdcm::Element< TVR, VM::VM3_3n >	332
gdcm::Element< TVR, VM::VM3_n >	334
gdcm::Element< VR::AS, VM::VM5 >	335
gdcm::Element< VR::OB, VM::VM1 >	336
gdcm::Element< VR::OW, VM::VM1 >	337
gdcm::ElementDisableCombinations< TVR, TVM >	
A class which is used to produce compile errors for an invalid combination of template parameters	339
gdcm::ElementDisableCombinations< VR::OB, VM::VM1_n >	340
gdcm::ElementDisableCombinations< VR::OW, VM::VM1_n >	340
gdcm::EncapsulatedDocument	
EncapsulatedDocument	340
gdcm::EncodingImplementation< T >	
EncodingImplementation	341
gdcm::EncodingImplementation< VR::VRASCII >	341
gdcm::EncodingImplementation< VR::VRBINARY >	342
gdcm::EndEvent	343
gdcm::EnumeratedValues	
Element . A Data Element with Enumerated Values that does not have a Value equivalent to one of the Values specified in this standard has an invalid value within the scope of a specific Information Object/SOP Class definition. Note:	344
gdcm::Event	
Superclass for callback/observer methods	345
gdcm::Exception	
Exception	347
gdcm::ExitEvent	348
gdcm::ExplicitDataElement	
Class to read/write a DataElement as Explicit Data Element	350
gdcm::ExplicitImplicitDataElement	
Class to read/write a DataElement as ExplicitImplicit Data Element	351
gdcm::Fiducials	
Fiducials	353
gdcm::File	
DICOM File See PS 3.10 File : A File is an ordered string of zero or more bytes, where the first byte is at the beginning of the file and the last byte at the end of the File . Files are identified by a unique File ID and may be written, read and/or deleted	354

gdcm::FileAnonymizer	
FileAnonymizer	357
gdcm::FileDerivation	
FileDerivation class See PS 3.16 - 2008 For the list of Code Value that can be used for in Derivation	
Code Sequence	360
gdcm::FileExplicitFilter	
FileExplicitFilter class After changing a file from Implicit to Explicit representation (see ImageChange-TransferSyntax) one operation is to make sure the VR of each DICOM attribute are accurate and do match the one from PS 3.6. Indeed when a file is written in Implicit representation, the VR is not stored directly in the file	362
gdcm::FileMetaInformation	
Class to represent a File Meta Information	364
gdcm::Filename	
Class to manipulate file name's	370
gdcm::FilenameGenerator	
FilenameGenerator	372
gdcm::FileSet	
File-set: A File-set is a collection of DICOM Files (and possibly non-DICOM Files) that share a common naming space within which File IDs are unique	374
gdcm::FileWithName	
FileWithName	375
gdcm::FindPatientRootQuery	
PatientRootQuery contains: the class which will produce a dataset for c-find with patient root	377
gdcm::FindStudyRootQuery	
FindStudyRootQuery contains: the class which will produce a dataset for C-FIND with study root	379
gdcm::Fragment	
Class to represent a Fragment	381
gdcm::Global	
Global	384
gdcm::GroupDict	
Class to represent the mapping from group number to its abbreviation and name	386
gdcm::IconImageFilter	
IconImageFilter This filter will extract icons from a gdcm::File This filter will loop over all known sequence (public and private) that may contains an IconImage and retrieve them. The filter will fails with a value of false if no icon can be found Since it handle both public and private icon type, one should not assume the icon is in uncompress form, some private vendor store private icon in JPEG8/JPEG12	388
gdcm::IconImageGenerator	
IconImageGenerator This filter will generate a valid Icon from the Pixel Data element (an instance of gdcm::Pixmap). To generate a valid Icon, one is only allowed the following Photometric Interpretation:	390
gdcm::ignore_char	392
gdcm::Image	
Image This is the container for an Image in the general sense. From this container you should be able to request information like:	393
gdcm::ImageApplyLookupTable	
ImageApplyLookupTable class It applies the LUT the PixelData (only PALETTE_COLOR images) Output will be a PhotometricInterpretation =RGB image	397
gdcm::ImageChangePhotometricInterpretation	
ImageChangePhotometricInterpretation class Class to change the Photometric Interpretation of an input DICOM	399
gdcm::ImageChangePlanarConfiguration	
ImageChangePlanarConfiguration class Class to change the Planar configuration of an input DICOM By default it will change into the more usual representation: PlanarConfiguration = 0	403
gdcm::ImageChangeTransferSyntax	
ImageChangeTransferSyntax class Class to change the transfer syntax of an input DICOM	406

gdcm::ImageCodec	
ImageCodec	410
gdcm::ImageConverter	
Image Converter	415
gdcm::ImageFragmentSplitter	
ImageFragmentSplitter class For single frame image, DICOM standard allow splitting the frame into multiple fragments	416
gdcm::ImageHelper	
ImageHelper (internal class, not intended for user level)	418
gdcm::ImageReader	
ImageReader	421
gdcm::ImageRegionReader	
ImageRegionReader	425
gdcm::ImageToImageFilter	
ImageToImageFilter class Super class for all filter taking an image and producing an output image	428
gdcm::ImageWriter	
ImageWriter	430
gdcm::network::ImplementationClassUIDSub	
ImplementationClassUIDSub PS 3.7 Table D.3-1 IMPLEMENTATION CLASS UID SUB-ITEM FIELDS (A-ASSOCIATE-RQ)	433
gdcm::network::ImplementationUIDSub	
ImplementationUIDSub Table D.3-2 IMPLEMENTATION UID SUB-ITEM FIELDS (A-ASSOCIATE--AC)	433
gdcm::network::ImplementationVersionNameSub	
ImplementationVersionNameSub Table D.3-3 IMPLEMENTATION VERSION NAME SUB-ITEM FIELDS (A-ASSOCIATE-RQ)	434
gdcm::ImplicitDataElement	
Class to represent an <i>Implicit VR</i> Data Element	435
gdcm::InitializeEvent	436
gdcm::IOD	
Class for representing a IOD	438
gdcm::IODEntry	
Class for representing a IODEntry	439
gdcm::IODs	
Class for representing a IODs	441
gdcm::IPPSorter	
IPPSorter Implement a simple Image Position (Patient) sorter, along the Image Orientation (Patient) direction. This algorithm does NOT support duplicate and will FAIL in case of duplicate IPP	442
gdcm::Item	
Class to represent an Item A component of the value of a Data Element that is of Value Representation Sequence of Items. An Item contains a Data Set . See PS 3.5 7.5.1 Item Encoding Rules Each Item of a Data Element of VR SQ shall be encoded as a DICOM Standard Data Element with a specific Data Element Tag of Value (FFFE,E000). The Item Tag is followed by a 4 byte Item Length field encoded in one of the following two ways Explicit/ Implicit	446
gdcm::IterationEvent	449
gdcm::JPEG12Codec	
Class to do JPEG 12bits (lossy & lossless)	451
gdcm::JPEG16Codec	
Class to do JPEG 16bits (lossless)	453
gdcm::JPEG2000Codec	
Class to do JPEG 2000	455
gdcm::JPEG8Codec	
Class to do JPEG 8bits (lossy & lossless)	458

gdcm::JPEGCodec	
JPEG codec Class to do JPEG (8bits, 12bits, 16bits lossy & lossless). It redispach in between the different codec implementation: gdcm::JPEG8Codec , gdcm::JPEG12Codec & gdcm::JPEG16Codec	
It also support inconsistency in between DICOM header and JPEG compressed stream ImageCodec implementation for the JPEG case	460
gdcm::JPEGLSCodec	
JPEG-LS	464
gdcm::KAKADUCodec	
KAKADUCodec	467
gdcm::LO	
LO	469
gdcm::LookupTable	
LookupTable class	471
gdcm::Scanner::Itstr	476
gdcm::Macro	
Class for representing a Macro	476
gdcm::Macros	
Class for representing a Modules	478
gdcm::network::MaximumLengthSub	
MaximumLengthSub Annex D Table D.1-1 MAXIMUM LENGTH SUB-ITEM FIELDS (A-ASSOCIAT-E-RQ)	479
gdcm::MD5	
Class for MD5	480
gdcm::MediaStorage	
MediaStorage	481
gdcm::MemberCommand< T >	
Command subclass that calls a pointer to a member function	488
gdcm::MeshPrimitive	
This class defines surface mesh primitives. It is designed from surface mesh primitives macro	492
gdcm::ModifiedEvent	495
gdcm::Module	
Class for representing a Module	497
gdcm::ModuleEntry	
Class for representing a ModuleEntry	499
gdcm::Modules	
Class for representing a Modules	501
gdcm::MovePatientRootQuery	
MovePatientRootQuery contains: the class which will produce a dataset for c-move with patient root	503
gdcm::MoveStudyRootQuery	
MoveStudyRootQuery contains: the class which will produce a dataset for C-MOVE with study root	505
gdcm::NestedModuleEntries	
Class for representing a NestedModuleEntries	507
gdcm::NoEvent	509
gdcm::Object	
Object	510
gdcm::Orientation	
Class to handle Orientation	513
gdcm::Overlay	
Overlay class	515
gdcm::ParseException	
ParseException Standard exception handling object	521
gdcm::Parser	
Parser ala XML_Parser from expat (SAX)	523

gdcm::Patient	
See PS 3.3 - 2007 DICOM MODEL OF THE REAL-WORLD, p 54	525
gdcm::network::PDataTFPDU	
PDataTFPDU Table 9-22 P-DATA-TF PDU FIELDS	525
gdcm::PDBElement	
Class to represent a PDB Element	528
gdcm::PDBHeader	
Class for PDBHeader	530
gdcm::PDFCodec	
PDFCodec class	532
gdcm::network::PDUFactory	
PDUFactory basically, given an initial byte, construct the appropriate PDU. This way, the event loop doesn't have to know about all the different PDU types	533
gdcm::PersonName	
PersonName class	535
gdcm::PGXCodec	
Class to do PGX See PGX as used in JPEG 2000 implementation and reference images	536
gdcm::PhotometricInterpretation	
Class to represent an PhotometricInterpretation	538
gdcm::PixelFormat	
PixelFormat	540
gdcm::Pixmap	
Pixmap class A bitmap based image. Used as parent for both IconImage and the main Pixel Data Image It does not contains any World Space information (IPP, IOP)	545
gdcm::PixmapReader	
PixmapReader	548
gdcm::PixmapToPixmapFilter	
PixmapToPixmapFilter class Super class for all filter taking an image and producing an output image	552
gdcm::PixmapWriter	
PixmapWriter This class will takes two inputs:	554
gdcm::PNMCodec	
Class to do PNM PNM is the Portable anymap file format. The main web page can be found at: http://netpbm.sourceforge.net/	557
gdcm::Preamble	
DICOM Preamble (Part 10)	560
gdcm::PresentationContext	
PresentationContext	561
gdcm::network::PresentationContextAC	
PresentationContextAC Table 9-18 PRESENTATION CONTEXT ITEM FIELDS	563
gdcm::PresentationContextGenerator	
PresentationContextGenerator This class is responsible for generating the proper PresentationContext that will be used in subsequent operation during a DICOM Query/Retrieve association. The step of the association is very sensible as special care need to be taken to explicitly define what instance are going to be send and how they are encoded	564
gdcm::network::PresentationContextRQ	
PresentationContextRQ Table 9-13 PRESENTATION CONTEXT ITEM FIELDS	566
gdcm::network::PresentationDataValue	
PresentationDataValue Table 9-23 PRESENTATION-DATA-VALUE ITEM FIELDS	568
gdcm::Printer	
Printer class	570
gdcm::PrivateDict	
Private Dict	573
gdcm::PrivateTag	
Class to represent a Private DICOM Data Element (Attribute) Tag (Group, Element , Owner)	575

gdcm::ProgressEvent	
ProgressEvent	Special type of event triggered during 576
gdcm::PVRGCodec	
PVRGCodec 579
gdcm::PythonFilter	
PythonFilter	PythonFilter is the class that make gdcm2.x looks more like gdcm1 and transform the binary blob contained in a DataElement into a string, typically this is a nice feature to have for wrapped language 581
gdcm::QueryBase	
QueryBase	contains: the base class for constructing a query dataset for a C-FIND and a C-MOVE . 582
gdcm::QueryFactory	
QueryFactory.h 584
gdcm::QueryImage	
QueryImage	contains: class to construct an image-based query for C-FIND and C-MOVE 585
gdcm::QueryPatient	
QueryPatient	contains: class to construct a patient-based query for c-find and c-move 587
gdcm::QuerySeries	
QuerySeries	contains: class to construct a series-based query for c-find and c-move 589
gdcm::QueryStudy	
QueryStudy.h	contains: class to construct a study-based query for C-FIND and C-MOVE 591
gdcm::RAWCodec	
RAWCodec	class 593
gdcm::Reader	
Reader	ala DOM (Document Object Model) 595
gdcm::Region	
Class for manipulation region 600
gdcm::Rescaler	
Rescale class	This class is meant to apply the linear transform of Stored Pixel Value to Real World Value. This is mostly found in CT or PET dataset, where the value are stored using one type, but need to be converted to another scale using a linear transform. There are basically two cases: In CT: the linear transform is generally integer based. E.g. the Stored Pixel Type is unsigned short 12bits, but to get Hounsfield unit, one need to apply the linear transform:
	$RWV = 1.*SV - 1024$
So the best scalar to store the Real World Value will be 16 bits signed type 602
gdcm::RLECodec	
Class to do RLE 605
gdcm::network::RoleSelectionSub	
RoleSelectionSub	PS 3.7 Table D.3-9 SCP/SCU ROLE SELECTION SUB-ITEM FIELDS (A-ASSOCIATE-RQ) 608
gdcm::SerieHelper::Rule 609
gdcm::Scanner	
Scanner	This filter is meant for quickly browsing a FileSet (a set of files on disk). Special consideration are taken so as to read the minimum amount of information in each file in order to retrieve the user specified set of DICOM Attribute 610
gdcm::Segment	
This class defines a segment. It mainly contains attributes of group 0x0062. In addition, it can be associated with surface 616
gdcm::SegmentedPaletteColorLookupTable	
SegmentedPaletteColorLookupTable	class 621
gdcm::SegmentReader	
This class defines a segment reader. It reads attributes of group 0x0062 622
gdcm::SegmentWriter	
This class defines a segment writer. It writes attributes of group 0x0062 625

gdcm::SequenceOfFragments	
Class to represent a Sequence Of Fragments	627
gdcm::SequenceOfItems	
Class to represent a Sequence Of Items (value representation : SQ)	632
gdcm::SerieHelper	
SerieHelper DO NOT USE this class, it is only a temporary solution for ITK migration from GDCM 1.x to GDCM 2.x It will disapear soon, you've been warned	638
gdcm::Series	
Series	640
gdcm::network::ServiceClassApplicationInformation	641
gdcm::ServiceClassUser	
ServiceClassUser	642
gdcm::SHA1	
Class for SHA1	646
gdcm::SimpleMemberCommand< T >	
Command subclass that calls a pointer to a member function	647
gdcm::SimpleSubjectWatcher	
SimpleSubjectWatcher This is a typical Subject Watcher class. It will observe all events	651
gdcm::SmartPointer< ObjectType >	
Class for Smart Pointer	652
gdcm::network::SOPClassExtendedNegociationSub	
SOPClassExtendedNegociationSub PS 3.7 Table D.3-11 SOP CLASS EXTENDED NEGOTIATION SUB-ITEM FIELDS (A-ASSOCIATE-RQ and A-ASSOCIATE-AC)	655
gdcm::SOPClassUIDToIOD	
Class convert a class SOP Class UID into IOD	656
gdcm::Sorter	
Sorter General class to do sorting using a custom function You simply need to provide a function of type: Sorter::SortFunction	657
gdcm::Spacing	
Class for Spacing	661
gdcm::Spectroscopy	
Spectroscopy class	663
gdcm::SplitMosaicFilter	
SplitMosaicFilter class Class to reshuffle bytes for a SIEMENS Mosaic image Siemens CSA Image Header CSA:= Common Siemens Architecture, sometimes also known as Common syngo Architecture	663
gdcm::StartEvent	664
gdcm::static_assert_test< x >	666
gdcm::STATIC_ASSERTION_FAILURE< x >	666
gdcm::STATIC_ASSERTION_FAILURE< true >	666
gdcm::StreamImageReader	
StreamImageReader	666
gdcm::StreamImageWriter	
StreamImageReader	669
gdcm::String< TDelimiter, TMaxLength, TPadChar >	
String	674
gdcm::StringFilter	
StringFilter StringFilter is the class that make gdcm2.x looks more like gdcm1 and transform the binary blob contained in a DataElement into a string, typically this is a nice feature to have for wrapped language	678
gdcm::Study	
Study	680
gdcm::Subject	
Subject	680

gdcm::Surface	
This class defines a SURFACE IE. This members are taken from required surface mesh module attributes	683
gdcm::SurfaceHelper	
SurfaceHelper Helper class for Surface object	689
gdcm::SurfaceReader	
This class defines a SURFACE IE reader. It reads surface mesh module attributes	692
gdcm::SurfaceWriter	
This class defines a SURFACE IE writer. It writes surface mesh module attributes	695
gdcm::SwapCode	
SwapCode representation	696
gdcm::SwapperDoOp	698
gdcm::SwapperNoOp	699
gdcm::System	
Class to do system operation	699
gdcm::Table	
Table	703
gdcm::TableEntry	
TableEntry	704
gdcm::TableReader	
Class for representing a TableReader	705
gdcm::network::TableRow	707
gdcm::Tag	
Class to represent a DICOM Data Element (Attribute) Tag (Group, Element). Basically an uint32_t which can also be expressed as two uint16_t (group and element)	708
gdcm::TagPath	
Class to handle a path of tag	714
gdcm::Testing	
Class for testing	716
gdcm::Trace	
Trace	719
gdcm::TransferSyntax	
Class to manipulate Transfer Syntax	723
gdcm::network::TransferSyntaxSub	
TransferSyntaxSub Table 9-15 TRANSFER SYNTAX SUB-ITEM FIELDS	726
gdcm::network::Transition	727
gdcm::Type	
Type	729
gdcm::UI	731
gdcm::UIDGenerator	
Class for generating unique UID	731
gdcm::UIDs	
All known uids	733
gdcm::network::ULAction	
ULAction A ULConnection in a given ULState can perform certain ULActions. This base class provides the interface for running those ULActions on a given ULConnection	752
gdcm::network::ULActionAA1	755
gdcm::network::ULActionAA2	756
gdcm::network::ULActionAA3	757
gdcm::network::ULActionAA4	758
gdcm::network::ULActionAA5	759
gdcm::network::ULActionAA6	760
gdcm::network::ULActionAA7	762
gdcm::network::ULActionAA8	763

gdcmm::network::ULActionAE1	764
gdcmm::network::ULActionAE2	765
gdcmm::network::ULActionAE3	766
gdcmm::network::ULActionAE4	767
gdcmm::network::ULActionAE5	769
gdcmm::network::ULActionAE6	770
gdcmm::network::ULActionAE7	771
gdcmm::network::ULActionAE8	772
gdcmm::network::ULActionAR1	773
gdcmm::network::ULActionAR10	774
gdcmm::network::ULActionAR2	776
gdcmm::network::ULActionAR3	777
gdcmm::network::ULActionAR4	778
gdcmm::network::ULActionAR5	779
gdcmm::network::ULActionAR6	780
gdcmm::network::ULActionAR7	781
gdcmm::network::ULActionAR8	783
gdcmm::network::ULActionAR9	784
gdcmm::network::ULActionDT1	785
gdcmm::network::ULActionDT2	786
gdcmm::network::ULBasicCallback	
ULBasicCallback This is the most basic of callbacks for how the ULConnectionManager handles incoming datasets. DataSets are just concatenated to the mDataSets vector, and the result can be pulled out of the vector by later code. Alternatives to this method include progress updates, saving to disk, etc. This class is NOT THREAD SAFE. Access the dataset vector after the entire set of datasets has been returned by the ULConnectionManager	787
gdcmm::network::ULConnection	
ULConnection This is the class that contains the socket to another machine, and passes data through itself, as well as maintaining a sense of state	789
gdcmm::network::ULConnectionCallback	791
gdcmm::network::ULConnectionInfo	
ULConnectionInfo this class contains all the information about a particular connection as established by the user. That is, it's: User Information Calling AE Title Called AE Title IP address/computer name IP Port A connection must be established with this information, that's subsequently placed into various primitives for actual communication	793
gdcmm::network::ULConnectionManager	
ULConnectionManager The ULConnectionManager performs actions on the ULConnection given inputs from the user and from the state of what's going on around the connection (ie, timeouts of the ARTIM timer, responses from the peer across the connection, etc)	794
gdcmm::network::ULEvent	
ULEvent base class for network events	797
gdcmm::network::ULTransitionTable	
ULTransitionTable The transition table of all the ULEvents, new ULActions, and ULStates	798
gdcmm::network::ULWritingCallback	798
gdcmm::UNExplicitDataElement	
Class to read/write a DataElement as UNExplicit Data Element	800
gdcmm::UNExplicitImplicitDataElement	
Class to read/write a DataElement as ExplicitImplicit Data Element This class gather two known bugs:	802
gdcmm::Unpacker12Bits	
Pack/Unpack 12 bits pixel into 16bits	804
gdcmm::Usage	
Usage	805
gdcmm::UserEvent	806

gdcm::network::UserInformation	
UserInformation Table 9-16 USER INFORMATION ITEM FIELDS	808
gdcm::Validate	
Validate class	809
gdcm::Value	
Class to represent the value of a Data Element	810
gdcm::ValueIO< TDE, TSwap, TType >	
Class to dispatch template calls	812
gdcm::Version	
Major/minor and build version	813
gdcm::VL	
Value Length	814
gdcm::VM	
Value Multiplicity Looking at the DICOMV3 dict only there is very few cases: 1 2 3 4 5 6 8 16 24 1-2 1-3 1-8 1-32 1-99 1-n 2-2n 2-n 3-3n 3-n	816
gdcm::VMToLength< T >	820
gdcm::VR	
VR class This is adapted from DICOM standard The biggest difference is the INVALID VR and the composite one that differ from standard (more like an addition) This allow us to represent all the possible case express in the DICOMV3 dict	820
gdcm::VR16ExplicitDataElement	
Class to read/write a DataElement as Explicit Data Element	825
gdcm::VRToEncoding< T >	827
gdcm::VRToType< T >	827
gdcm::VRVLSize< T >	828
gdcm::VRVLSize< 0 >	828
gdcm::VRVLSize< 1 >	828
vtkGDCMImageReader	829
vtkGDCMImageWriter	835
vtkGDCMMedicalImageProperties	840
vtkGDCMPolyDataReader	841
vtkGDCMPolyDataWriter	844
vtkGDCMTesting	847
vtkGDCMThreadedImageReader	850
vtkGDCMThreadedImageReader2	852
vtkImageColorViewer	856
vtkImageMapToColors16	863
vtkImageMapToWindowLevelColors2	866
vtkImagePlanarComponentsToComponents	868
vtkImageRGBToYBR	870
vtkImageYBRToRGB	871
vtkLookupTable16	873
vtkRTStructSetProperties	875
gdcm::Waveform	
Waveform class	880
gdcm::Writer	
Writer ala DOM (Document Object Model) This class is a non-validating writer, it will only performs well- formedness check only	880
gdcm::XMLDictReader	
Class for representing a XMLDictReader	886
gdcm::XMLPrivateDictReader	
Class for representing a XMLPrivateDictReader	887

Chapter 23

File Index

23.1 File List

Here is a list of all files with brief descriptions:

gdc2pnm.man	891
gdc2vtk.man	891
gdcmAAabortPDU.h	891
gdcmAAAssociateACPDU.h	892
gdcmAAAssociateRJPDU.h	893
gdcmAAAssociateRQPDU.h	894
gdcmAbstractSyntax.h	894
gdcmanon.man	896
gdcmAnonymizeEvent.h	896
gdcmAnonymizer.h	897
gdcmApplicationContext.h	898
gdcmApplicationEntity.h	899
gdcmAReleaseRPPDU.h	899
gdcmAReleaseRQPDU.h	900
gdcmARTIMTimer.h	902
gdcmASN1.h	903
gdcmAsynchronousOperationsWindowSub.h	904
gdcmAttribute.h	905
gdcmAudioCodec.h	906
gdcmBase64.h	907
gdcmBaseCompositeMessage.h	907
gdcmBasePDU.h	909
gdcmBaseRootQuery.h	910
gdcmBasicOffsetTable.h	911
gdcmBitmap.h	912
gdcmBitmapToBitmapFilter.h	913
gdcmBoxRegion.h	914
gdcmByteBuffer.h	915
gdcmByteSwap.h	917
gdcmByteSwapFilter.h	917
gdcmByteValue.h	918
gdcmCEchoMessages.h	919
gdcmCFindMessages.h	920
gdcmCMoveMessages.h	921

gdcmCodec.h	922
gdcmCoder.h	923
gdcmCodeString.h	925
gdcmCommand.h	925
gdcmCommandDataSet.h	927
gdcmCompositeMessageFactory.h	928
gdcmCompositeNetworkFunctions.h	928
gdcmConstCharWrapper.h	929
gdcmconv.man	930
gdcmCP246ExplicitDataElement.h	930
gdcmCryptographicMessageSyntax.h	930
gdcmCSAElement.h	931
gdcmCSAHeader.h	933
gdcmCSAHeaderDict.h	934
gdcmCSAHeaderDictEntry.h	935
gdcmCStoreMessages.h	936
gdcmCurve.h	937
gdcmDataElement.h	939
gdcmDataEvent.h	940
gdcmDataSet.h	941
gdcmDataSetEvent.h	942
gdcmDataSetHelper.h	942
gdcmDecoder.h	943
gdcmDefinedTerms.h	945
gdcmDeflateStream.h	945
gdcmDefs.h	946
gdcmDeltaEncodingCodec.h	947
gdcmDICOMDIR.h	948
gdcmDICOMDIRGenerator.h	949
gdcmDict.h	950
gdcmDictConverter.h	952
gdcmDictEntry.h	952
gdcmDictPrinter.h	954
gdcmDicts.h	954
gdcmdiff.man	956
gdcmDIMSE.h	956
gdcmDirectionCosines.h	957
gdcmDirectory.h	957
gdcmDirectoryHelper.h	958
gdcmDummyValueGenerator.h	959
gdcmdump.man	960
gdcmDumper.h	960
gdcmElement.h	961
gdcmEncapsulatedDocument.h	963
gdcmEnumeratedValues.h	964
gdcmEvent.h	964
gdcmException.h	966
gdcmExplicitDataElement.h	967
gdcmExplicitImplicitDataElement.h	968
gdcmFiducials.h	969
gdcmFile.h	970
gdcmFileAnonymizer.h	971
gdcmFileDerivation.h	972
gdcmFileExplicitFilter.h	972

gdcmFileMetaInformation.h	973
gdcmFilename.h	974
gdcmFilenameGenerator.h	975
gdcmFileSet.h	976
gdcmFindPatientRootQuery.h	978
gdcmFindStudyRootQuery.h	979
gdcmFragment.h	979
gdcmgendir.man	981
gdcmGlobal.h	981
gdcmGroupDict.h	982
gdcmIconImage.h	983
gdcmIconImageFilter.h	984
gdcmIconImageGenerator.h	984
gdcmImage.h	985
gdcmImageApplyLookupTable.h	987
gdcmImageChangePhotometricInterpretation.h	987
gdcmImageChangePlanarConfiguration.h	988
gdcmImageChangeTransferSyntax.h	989
gdcmImageCodec.h	990
gdcmImageConverter.h	991
gdcmImageFragmentSplitter.h	992
gdcmImageHelper.h	993
gdcmImageReader.h	994
gdcmImageRegionReader.h	996
gdcmImageToImageFilter.h	996
gdcmImageWriter.h	997
gdcmimg.man	998
gdcmImplementationClassUIDSub.h	998
gdcmImplementationUIDSub.h	1000
gdcmImplementationVersionNameSub.h	1000
gdcmImplicitDataElement.h	1002
gdcminfo.man	1002
gdcmIOD.h	1003
gdcmIODEntry.h	1005
gdcmIODs.h	1007
gdcmIPPSorter.h	1008
gdcmItem.h	1009
gdcmJPEG12Codec.h	1010
gdcmJPEG16Codec.h	1011
gdcmJPEG2000Codec.h	1012
gdcmJPEG8Codec.h	1012
gdcmJPEGCodec.h	1013
gdcmJPEGLSCCodec.h	1015
gdcmKAKADUCodec.h	1015
gdcmLegacyMacro.h	1016
gdcmLO.h	1017
gdcmLookupTable.h	1018
gdcmMacro.h	1019
gdcmMacroEntry.h	1022
gdcmMacros.h	1023
gdcmMaximumLengthSub.h	1025
gdcmMD5.h	1026
gdcmMediaStorage.h	1027
gdcmMeshPrimitive.h	1029

gdcmModule.h	1030
gdcmModuleEntry.h	1032
gdcmModules.h	1034
gdcmMovePatientRootQuery.h	1035
gdcmMoveStudyRootQuery.h	1036
gdcmNestedModuleEntries.h	1037
gdcmNetworkEvents.h	1039
gdcmNetworkStateID.h	1040
gdcmObject.h	1041
gdcmOrientation.h	1042
gdcmOverlay.h	1043
gdcmParseException.h	1044
gdcmParser.h	1045
gdcmPatient.h	1046
gdcmPDataTFPDU.h	1046
gdcmPDBElement.h	1047
gdcmPDBHeader.h	1049
gdcmpdf.man	1049
gdcmPDFCodec.h	1050
gdcmPDUFactory.h	1050
gdcmPersonName.h	1051
gdcmPGXCodec.h	1052
gdcmPhotometricInterpretation.h	1053
gdcmPixelFormat.h	1054
gdcmPixmap.h	1056
gdcmPixmapReader.h	1057
gdcmPixmapToPixmapFilter.h	1058
gdcmPixmapWriter.h	1059
gdcmPNMCodec.h	1060
gdcmPreamble.h	1061
gdcmPresentationContext.h	1062
gdcmPresentationContextAC.h	1063
gdcmPresentationContextGenerator.h	1064
gdcmPresentationContextRQ.h	1065
gdcmPresentationDataValue.h	1066
gdcmPrinter.h	1067
gdcmPrivateTag.h	1068
gdcmProgressEvent.h	1069
gdcmPVRGCodec.h	1070
gdcmPythonFilter.h	1071
gdcmQueryBase.h	1072
gdcmQueryFactory.h	1074
gdcmQueryImage.h	1075
gdcmQueryPatient.h	1076
gdcmQuerySeries.h	1077
gdcmQueryStudy.h	1078
gdcmraw.man	1079
gdcmRAWCodec.h	1079
gdcmReader.h	1080
gdcmRegion.h	1081
gdcmRescaler.h	1082
gdcmRLECodec.h	1083
gdcmRoleSelectionSub.h	1084
gdcmScanner.h	1084

gdcmscanner.man	1085
gdcmscu.man	1086
gdcmSegment.h	1086
gdcmSegmentedPaletteColorLookupTable.h	1087
gdcmSegmentHelper.h	1088
gdcmSegmentReader.h	1089
gdcmSegmentWriter.h	1090
gdcmSequenceOfFragments.h	1092
gdcmSequenceOfItems.h	1092
gdcmSerieHelper.h	1093
gdcmSeries.h	1095
gdcmServiceClassApplicationInformation.h	1096
gdcmServiceClassUser.h	1098
gdcmSHA1.h	1098
gdcmSimpleSubjectWatcher.h	1099
gdcmSmartPointer.h	1100
gdcmSOPClassExtendedNegociationSub.h	1101
gdcmSOPClassUIDToIOD.h	1102
gdcmSorter.h	1103
gdcmSpacing.h	1105
gdcmSpectroscopy.h	1105
gdcmSplitMosaicFilter.h	1106
gdcmStaticAssert.h	1107
gdcmStreamImageReader.h	1109
gdcmStreamImageWriter.h	1109
gdcmString.h	1110
gdcmStringFilter.h	1111
gdcmStudy.h	1112
gdcmSubject.h	1114
gdcmSurface.h	1115
gdcmSurfaceHelper.h	1116
gdcmSurfaceReader.h	1117
gdcmSurfaceWriter.h	1117
gdcmSwapCode.h	1118
gdcmSwapper.h	1119
gdcmSystem.h	1120
gdcmTable.h	1121
gdcmTableEntry.h	1122
gdcmTableReader.h	1124
gdcmTag.h	1125
gdcmTagPath.h	1126
gdcmTagToVR.h	1127
gdcm.tar.man	1127
gdcmTerminal.h	1127
gdcmTestDriver.h	1128
gdcmTesting.h	1129
gdcmTrace.h	1130
gdcmTransferSyntax.h	1133
gdcmTransferSyntaxSub.h	1134
gdcmType.h	1135
gdcmTypes.h	1137
gdcmUIDGenerator.h	1137
gdcmUIDs.h	1138
gdcmULAction.h	1140

gdcmULActionAA.h	1141
gdcmULActionAE.h	1141
gdcmULActionAR.h	1142
gdcmULActionDT.h	1143
gdcmULBasicCallback.h	1144
gdcmULConnection.h	1145
gdcmULConnectionCallback.h	1146
gdcmULConnectionInfo.h	1147
gdcmULConnectionManager.h	1149
gdcmULEvent.h	1150
gdcmULTransitionTable.h	1151
gdcmULWritingCallback.h	1152
gdcmUNExplicitDataElement.h	1153
gdcmUNExplicitImplicitDataElement.h	1153
gdcmUnpacker12Bits.h	1154
gdcmUsage.h	1155
gdcmUserInformation.h	1157
gdcmValidate.h	1158
gdcmValue.h	1159
gdcmValueIO.h	1159
gdcmVersion.h	1160
gdcmviewer.man	1161
gdcmVL.h	1161
gdcmVM.h	1162
gdcmVR.h	1164
gdcmVR16ExplicitDataElement.h	1166
gdcmWaveform.h	1167
gdcmWin32.h	1167
gdcmWriter.h	1168
gdcmXMLDictReader.h	1169
gdcmXMLPrivateDictReader.h	1169
vtkGDCMImageReader.h	1170
vtkGDCMImageWriter.h	1172
vtkGDCMMedicalImageProperties.h	1172
vtkGDCMPolyDataReader.h	1173
vtkGDCMPolyDataWriter.h	1174
vtkGDCMTesting.h	1175
vtkGDCMThreadedImageReader.h	1175
vtkGDCMThreadedImageReader2.h	1176
vtkImageColorViewer.h	1176
vtkImageMapToColors16.h	1177
vtkImageMapToWindowLevelColors2.h	1177
vtkImagePlanarComponentsToComponents.h	1178
vtkImageRGBToYBR.h	1178
vtkImageYBRToRGB.h	1179
vtkLookupTable16.h	1179
vtkRTStructSetProperties.h	1180

Chapter 24

Namespace Documentation

24.1 gdcmm Namespace Reference

Namespaces

- [network](#)
- [SegmentHelper](#)
- [terminal](#)

Class for Terminal Allow one to print in color in a shell.

Classes

- class [AbortEvent](#)
- class [AnonymizeEvent](#)
[AnonymizeEvent](#) Special type of event triggered during the Anonymization process.
- class [Anonymizer](#)
[Anonymizer](#) This class is a multi purpose anonymizer. It can work in 2 mode:
- class [AnyEvent](#)
- class [ApplicationEntity](#)
[ApplicationEntity](#).
- class [ASN1](#)
Class for [ASN1](#).
- class [Attribute](#)
[Attribute](#) class This class use template metaprograming tricks to let the user know when the template instanciation does not match the public dictionary.
- class [Attribute< Group, Element, TVR, VM::VM1 >](#)
- class [Attribute< Group, Element, TVR, VM::VM1_3 >](#)
- class [Attribute< Group, Element, TVR, VM::VM1_8 >](#)
- class [Attribute< Group, Element, TVR, VM::VM1_n >](#)
- class [Attribute< Group, Element, TVR, VM::VM2_2n >](#)
- class [Attribute< Group, Element, TVR, VM::VM2_n >](#)
- class [Attribute< Group, Element, TVR, VM::VM3_3n >](#)
- class [Attribute< Group, Element, TVR, VM::VM3_n >](#)
- class [AudioCodec](#)

- [AudioCodec](#).
- class [Base64](#)
 - Class for [Base64](#).*
- class [BaseRootQuery](#)
 - [BaseRootQuery](#) contains: a baseclass which will produce a dataset for c-find and c-move with patient/study root.*
- class [BasicOffsetTable](#)
 - Class to represent a [BasicOffsetTable](#).*
- class [Bitmap](#)
 - [Bitmap](#) class A bitmap based image. Used as parent for both [IconImage](#) and the main Pixel Data [Image](#) It does not contains any World Space information (IPP, IOP)*
- class [BitmapToBitmapFilter](#)
 - [BitmapToBitmapFilter](#) class Super class for all filter taking an image and producing an output image.*
- class [BoxRegion](#)
 - Class for manipulation box region This is a very simple implementation of the [Region](#) class. It only support 3D box type region. It assumes the 3D Box does not have a tilt Origin is as (0,0,0)*
- class [ByteBuffer](#)
 - [ByteBuffer](#).*
- class [ByteSwap](#)
 - [ByteSwap](#).*
- class [ByteSwapFilter](#)
 - [ByteSwapFilter](#) In place byte-swapping of a dataset FIXME: FL status ??*
- class [ByteValue](#)
 - Class to represent binary value (array of bytes)*
- class [Codec](#)
 - [Codec](#) class.*
- class [Coder](#)
 - [Coder](#).*
- class [CodeString](#)
 - [CodeString](#) This is an implementation of DICOM [VR](#): CS The ctor will properly Trim so that operator== is correct.*
- class [Command](#)
 - [Command](#) superclass for callback/observer methods.*
- class [CommandDataSet](#)
 - Class to represent a [Command DataSet](#).*
- class [CompositeNetworkFunctions](#)
 - Composite Network Functions These functions provide a generic API to the DICOM functions implemented in GDCM. Advanced users can use this code as a template for building their own versions of these functions (for instance, to provide progress bars or some other way of handling returned query information), but for most users, these functions should be sufficient to interface with a PACS to a local machine. Note that these functions are not contained within a static class or some other class-style interface, because multiple connections can be instantiated in the same program. The DICOM standard is much more function oriented rather than class oriented in this instance, so the design of this API reflects that functional approach. These functions implements the following SCU operations:*
- class [ConstCharWrapper](#)
 - Do not use me.*
- class [CP246ExplicitDataElement](#)
 - Class to read/write a [DataElement](#) as CP246Explicit Data [Element](#).*
- class [CryptographicMessageSyntax](#)
 - Class for [CryptographicMessageSyntax](#) encryption. This is just a simple wrapper around openssl PKCS7_encrypt functionalities.*
- class [CSAElement](#)

- Class to represent a CSA [Element](#).
- class [CSAHeader](#)
 - Class for [CSAHeader](#).
- class [CSAHeaderDict](#)
 - Class to represent a map of [CSAHeaderDictEntry](#).
- class [CSAHeaderDictEntry](#)
 - Class to represent an Entry in the [Dict](#) Does not really exist within the DICOM definition, just a way to minimize storage and have a mapping from [gdcm::Tag](#) to the needed information.
- class [CSAHeaderDictException](#)
- class [Curve](#)
 - [Curve](#) class to handle element 50xx,3000 [Curve](#) Data WARNING: This is deprecated and lastly defined in PS 3.3 - 2004.
- class [DataElement](#)
 - Class to represent a Data [Element](#) either Implicit or Explicit.
- class [DataElementException](#)
- class [DataEvent](#)
 - [DataEvent](#).
- class [DataSet](#)
 - Class to represent a Data Set (which contains Data Elements) A Data Set represents an instance of a real world Information [Object](#).
- class [DataSetEvent](#)
 - [DataSetEvent](#) Special type of event triggered during the [DataSet](#) store/move process.
- class [DataSetHelper](#)
 - [DataSetHelper](#) (internal class, not intended for user level)
- class [Decoder](#)
 - [Decoder](#).
- class [DefinedTerms](#)
 - Defined Terms are used when the specified explicit Values may be extended by implementors to include additional new Values. These new Values shall be specified in the Conformance Statement (see PS 3.2) and shall not have the same meaning as currently defined Values in this standard. A Data [Element](#) with Defined Terms that does not contain a [Value](#) equivalent to one of the Values currently specified in this standard shall not be considered to have an invalid value. Note: Interpretation [Type](#) ID (4008,0210) is an example of a Data [Element](#) having Defined Terms. It is defined to have a [Value](#) that may be one of the set of standard Values; REPORT or AMENDMENT (see PS 3.3). Because this Data [Element](#) has Defined Terms other Interpretation [Type](#) IDs may be defined by the implementor.
- class [Defs](#)
 - FIXME I do not like the name '[Defs](#)'.
- class [DeltaEncodingCodec](#)
 - [DeltaEncodingCodec](#) compression used by some private vendor.
- class [DICOMDIR](#)
 - [DICOMDIR](#) class.
- class [DICOMDIRGenerator](#)
 - [DICOMDIRGenerator](#) class This is a STD-GEN-CD [DICOMDIR](#) generator. ref: PS 3.11-2008 Annex D (Normative) - General Purpose CD-R and DVD Interchange Profiles.
- class [Dict](#)
 - Class to represent a map of [DictEntry](#).
- class [DictConverter](#)
 - Class to convert a .dic file into something else:
- class [DictEntry](#)
 - Class to represent an Entry in the [Dict](#) Does not really exist within the DICOM definition, just a way to minimize storage and have a mapping from [gdcm::Tag](#) to the needed information.

- class [DictPrinter](#)
DictPrinter class.
- class [Dicts](#)
Class to manipulate the sum of knowledge (all the dict user load)
- class [DirectionCosines](#)
class to handle DirectionCosines
- class [Directory](#)
Class for manipulation directories.
- class [DirectoryHelper](#)
DirectoryHelper this class is designed to help mitigate some of the commonly performed operations on directories. namely: 1) the ability to determine the number of series in a directory by what type of series is present 2) the ability to find all ct series in a directory 3) the ability to find all mr series in a directory 4) to load a set of DataSets from a series that's already been sorted by the IPP sorter 5) For rtstruct stuff, you need to know the sopinstanceuid of each z plane, so there's a retrieval function for that 6) then a few other functions for rtstruct writeouts.
- class [DummyValueGenerator](#)
Class for generating dummy value.
- class [Dumper](#)
Codec class.
- class [Element](#)
Element class.
- class [Element< TVR, VM::VM1_2 >](#)
- class [Element< TVR, VM::VM1_n >](#)
- class [Element< TVR, VM::VM2_2n >](#)
- class [Element< TVR, VM::VM2_n >](#)
- class [Element< TVR, VM::VM3_3n >](#)
- class [Element< TVR, VM::VM3_n >](#)
- class [Element< VR::AS, VM::VM5 >](#)
- class [Element< VR::OB, VM::VM1 >](#)
- class [Element< VR::OW, VM::VM1 >](#)
- class [ElementDisableCombinations](#)
A class which is used to produce compile errors for an invalid combination of template parameters.
- class [ElementDisableCombinations< VR::OB, VM::VM1_n >](#)
- class [ElementDisableCombinations< VR::OW, VM::VM1_n >](#)
- class [EncapsulatedDocument](#)
EncapsulatedDocument.
- class [EncodingImplementation](#)
EncodingImplementation.
- class [EncodingImplementation< VR::VRASCII >](#)
- class [EncodingImplementation< VR::VRBINARY >](#)
- class [EndEvent](#)
- class [EnumeratedValues](#)
Element. A Data Element with Enumerated Values that does not have a Value equivalent to one of the Values specified in this standard has an invalid value within the scope of a specific Information Object/SOP Class definition. Note:
- class [Event](#)
superclass for callback/observer methods
- class [Exception](#)
Exception.
- class [ExitEvent](#)
- class [ExplicitDataElement](#)

- Class to read/write a [DataElement](#) as Explicit Data [Element](#).
- class [ExplicitImplicitDataElement](#)
 - Class to read/write a [DataElement](#) as ExplicitImplicit Data [Element](#).
- class [Fiducials](#)
 - [Fiducials](#).
- class [File](#)
 - a DICOM [File](#) See PS 3.10 [File](#): A [File](#) is an ordered string of zero or more bytes, where the first byte is at the beginning of the file and the last byte at the end of the [File](#). Files are identified by a unique [File](#) ID and may be written, read and/or deleted.
- class [FileAnonymizer](#)
 - [FileAnonymizer](#).
- class [FileDerivation](#)
 - [FileDerivation](#) class See PS 3.16 - 2008 For the list of Code [Value](#) that can be used for in Derivation Code Sequence.
- class [FileExplicitFilter](#)
 - [FileExplicitFilter](#) class After changing a file from Implicit to Explicit representation (see [ImageChangeTransferSyntax](#)) one operation is to make sure the [VR](#) of each DICOM attribute are accurate and do match the one from PS 3.6. Indeed when a file is written in Implicit representation, the [VR](#) is not stored directly in the file.
- class [FileMetaInformation](#)
 - Class to represent a [File](#) Meta Information.
- class [Filename](#)
 - Class to manipulate file name's.
- class [FilenameGenerator](#)
 - [FilenameGenerator](#).
- class [FileSet](#)
 - File-set: A File-set is a collection of DICOM Files (and possibly non-DICOM Files) that share a common naming space within which [File](#) IDs are unique.
- class [FileWithName](#)
 - [FileWithName](#).
- class [FindPatientRootQuery](#)
 - [PatientRootQuery](#) contains: the class which will produce a dataset for c-find with patient root.
- class [FindStudyRootQuery](#)
 - [FindStudyRootQuery](#) contains: the class which will produce a dataset for C-FIND with study root.
- class [Fragment](#)
 - Class to represent a [Fragment](#).
- class [Global](#)
 - [Global](#).
- class [GroupDict](#)
 - Class to represent the mapping from group number to its abbreviation and name.
- class [IconImageFilter](#)
 - [IconImageFilter](#) This filter will extract icons from a [gdcm::File](#) This filter will loop over all known sequence (public and private) that may contains an [IconImage](#) and retrieve them. The filter will fails with a value of false if no icon can be found Since it handle both public and private icon type, one should not assume the icon is in uncompress form, some private vendor store private icon in JPEG8/JPEG12.
- class [IconImageGenerator](#)
 - [IconImageGenerator](#) This filter will generate a valid Icon from the Pixel Data element (an instance of [gdcm::Pixmap](#)). To generate a valid Icon, one is only allowed the following Photometric Interpretation:
- struct [ignore_char](#)
- class [Image](#)

Image This is the container for an *Image* in the general sense. From this container you should be able to request information like:

- class *ImageApplyLookupTable*
ImageApplyLookupTable class It applies the LUT the *PixelData* (only *PALETTE_COLOR* images) Output will be a *PhotometricInterpretation=RGB* image.
- class *ImageChangePhotometricInterpretation*
ImageChangePhotometricInterpretation class Class to change the *Photometric Interpretation* of an input *DICOM*.
- class *ImageChangePlanarConfiguration*
ImageChangePlanarConfiguration class Class to change the *Planar configuration* of an input *DICOM* By default it will change into the more usual representation: *PlanarConfiguration = 0*.
- class *ImageChangeTransferSyntax*
ImageChangeTransferSyntax class Class to change the transfer syntax of an input *DICOM*.
- class *ImageCodec*
ImageCodec.
- class *ImageConverter*
Image Converter.
- class *ImageFragmentSplitter*
ImageFragmentSplitter class For single frame image, *DICOM* standard allow splitting the frame into multiple fragments.
- class *ImageHelper*
ImageHelper (internal class, not intended for user level)
- class *ImageReader*
ImageReader.
- class *ImageRegionReader*
ImageRegionReader.
- class *ImageToImageFilter*
ImageToImageFilter class Super class for all filter taking an image and producing an output image.
- class *ImageWriter*
ImageWriter.
- class *ImplicitDataElement*
Class to represent an *Implicit VR Data Element*.
- class *InitializeEvent*
- class *IOD*
Class for representing a *IOD*.
- class *IODEntry*
Class for representing a *IODEntry*.
- class *IODs*
Class for representing a *IODs*.
- class *IPPSorter*
IPPSorter Implement a simple *Image Position (Patient)* sorter, along the *Image Orientation (Patient)* direction. This algorithm does NOT support duplicate and will FAIL in case of duplicate IPP.
- class *Item*
Class to represent an *Item* A component of the value of a *Data Element* that is of *Value Representation Sequence* of *Items*. An *Item* contains a *Data Set*. See PS 3.5 7.5.1 *Item Encoding Rules* Each *Item* of a *Data Element* of *VR SQ* shall be encoded as a *DICOM Standard Data Element* with a specific *Data Element Tag* of *Value (FFFE,E000)*. The *Item Tag* is followed by a 4 byte *Item Length* field encoded in one of the following two ways *Explicit/ Implicit*.
- class *IterationEvent*
- class *JPEG12Codec*
Class to do *JPEG 12bits (lossy & lossless)*
- class *JPEG16Codec*

- Class to do JPEG 16bits (lossless)*
- class [JPEG2000Codec](#)
 - Class to do JPEG 2000.*
- class [JPEG8Codec](#)
 - Class to do JPEG 8bits (lossy & lossless)*
- class [JPEGCodec](#)
 - JPEG codec Class to do JPEG (8bits, 12bits, 16bits lossy & lossless). It redispach in between the different codec implementation: [gdcm::JPEG8Codec](#), [gdcm::JPEG12Codec](#) & [gdcm::JPEG16Codec](#) It also support inconsistency in between DICOM header and JPEG compressed stream [ImageCodec](#) implementation for the JPEG case.*
- class [JPEGLSCCodec](#)
 - JPEG-LS.*
- class [KAKADUCodec](#)
 - KAKADUCodec.*
- class [LO](#)
 - LO.*
- class [LookupTable](#)
 - LookupTable class.*
- class [Macro](#)
 - Class for representing a [Macro](#).*
- class [Macros](#)
 - Class for representing a [Modules](#).*
- class [MD5](#)
 - Class for [MD5](#).*
- class [MediaStorage](#)
 - MediaStorage.*
- class [MemberCommand](#)
 - Command subclass that calls a pointer to a member function.*
- class [MeshPrimitive](#)
 - This class defines surface mesh primitives. It is designed from surface mesh primitives macro.*
- class [ModifiedEvent](#)
- class [Module](#)
 - Class for representing a [Module](#).*
- class [ModuleEntry](#)
 - Class for representing a [ModuleEntry](#).*
- class [Modules](#)
 - Class for representing a [Modules](#).*
- class [MovePatientRootQuery](#)
 - [MovePatientRootQuery](#) contains: the class which will produce a dataset for c-move with patient root.*
- class [MoveStudyRootQuery](#)
 - [MoveStudyRootQuery](#) contains: the class which will produce a dataset for C-MOVE with study root.*
- class [NestedModuleEntries](#)
 - Class for representing a [NestedModuleEntries](#).*
- class [NoEvent](#)
- class [Object](#)
 - Object.*
- class [Orientation](#)
 - class to handle [Orientation](#)*
- class [Overlay](#)

- Overlay* class.
- class [ParseException](#)
 - ParseException* Standard exception handling object.
- class [Parser](#)
 - Parser* ala XML_Parser from expat (SAX)
- class [Patient](#)
 - See PS 3.3 - 2007 DICOM MODEL OF THE REAL-WORLD, p 54.
- class [PDBElement](#)
 - Class to represent a PDB *Element*.
- class [PDBHeader](#)
 - Class for *PDBHeader*.
- class [PDFCodec](#)
 - PDFCodec* class.
- class [PersonName](#)
 - PersonName* class.
- class [PGXCodec](#)
 - Class to do PGX See PGX as used in JPEG 2000 implementation and reference images.
- class [PhotometricInterpretation](#)
 - Class to represent an *PhotometricInterpretation*.
- class [PixelFormat](#)
 - PixelFormat*.
- class [Pixmap](#)
 - Pixmap* class A bitmap based image. Used as parent for both *IconImage* and the main Pixel Data *Image* It does not contains any World Space information (IPP, IOP)
- class [PixmapReader](#)
 - PixmapReader*.
- class [PixmapToPixmapFilter](#)
 - PixmapToPixmapFilter* class Super class for all filter taking an image and producing an output image.
- class [PixmapWriter](#)
 - PixmapWriter* This class will takes two inputs:
- class [PNMCodec](#)
 - Class to do PNM PNM is the Portable anymap file format. The main web page can be found at: <http://netpbm.sourceforge.net/>.
- class [Preamble](#)
 - DICOM *Preamble* (Part 10)
- class [PresentationContext](#)
 - PresentationContext*.
- class [PresentationContextGenerator](#)
 - PresentationContextGenerator* This class is responsible for generating the proper *PresentationContext* that will be used in subsequent operation during a DICOM Query/Retrieve association. The step of the association is very sensible as special care need to be taken to explicitly define what instance are going to be send and how they are encoded.
- class [Printer](#)
 - Printer* class.
- class [PrivateDict](#)
 - Private *Dict*.
- class [PrivateTag](#)
 - Class to represent a Private DICOM Data *Element* (*Attribute*) *Tag* (Group, *Element*, Owner)
- class [ProgressEvent](#)

- ProgressEvent* Special type of event triggered during.
 - class [PVRGCodec](#)
 - PVRGCodec.*
 - class [PythonFilter](#)
 - PythonFilter* *PythonFilter* is the class that make gdcm2.x looks more like gdcm1 and transform the binary blob contained in a [DataElement](#) into a string, typically this is a nice feature to have for wrapped language.
 - class [QueryBase](#)
 - QueryBase* contains: the base class for constructing a query dataset for a C-FIND and a C-MOVE.
 - class [QueryFactory](#)
 - QueryFactory.h.*
 - class [QueryImage](#)
 - QueryImage* contains: class to construct an image-based query for C-FIND and C-MOVE.
 - class [QueryPatient](#)
 - QueryPatient* contains: class to construct a patient-based query for c-find and c-move.
 - class [QuerySeries](#)
 - QuerySeries* contains: class to construct a series-based query for c-find and c-move.
 - class [QueryStudy](#)
 - QueryStudy.h* contains: class to construct a study-based query for C-FIND and C-MOVE.
 - class [RAWCodec](#)
 - RAWCodec* class.
 - class [Reader](#)
 - Reader* ala DOM (Document [Object](#) Model)
 - class [Region](#)
 - Class for manipulation region.*
 - class [Rescaler](#)
 - Rescale class* This class is meant to apply the linear transform of Stored Pixel [Value](#) to Real World [Value](#). This is mostly found in CT or PET dataset, where the value are stored using one type, but need to be converted to another scale using a linear transform. There are basically two cases: In CT: the linear transform is generally integer based. E.g. the Stored Pixel [Type](#) is unsigned short 12bits, but to get Hounsfield unit, one need to apply the linear transform:
- $$RWV = 1. * SV - 1024$$
- So the best scalar to store the Real World [Value](#) will be 16 bits signed type.*
 - class [RLECodec](#)
 - Class to do RLE.*
 - class [Scanner](#)
 - Scanner* This filter is meant for quickly browsing a [FileSet](#) (a set of files on disk). Special consideration are taken so as to read the minimum amount of information in each file in order to retrieve the user specified set of DICOM [Attribute](#).
 - class [Segment](#)
 - This class defines a segment. It mainly contains attributes of group 0x0062. In addition, it can be associated with surface.*
 - class [SegmentedPaletteColorLookupTable](#)
 - SegmentedPaletteColorLookupTable* class.
 - class [SegmentReader](#)
 - This class defines a segment reader. It reads attributes of group 0x0062.*
 - class [SegmentWriter](#)
 - This class defines a segment writer. It writes attributes of group 0x0062.*
 - class [SequenceOfFragments](#)
 - Class to represent a Sequence Of Fragments.*
 - class [SequenceOfItems](#)

Class to represent a Sequence Of Items (value representation : SQ)

- class [SerieHelper](#)
[SerieHelper](#) DO NOT USE this class, it is only a temporary solution for ITK migration from GDCM 1.x to GDCM 2.x It will disappear soon, you've been warned.
- class [Series](#)
[Series](#).
- class [ServiceClassUser](#)
[ServiceClassUser](#).
- class [SHA1](#)
Class for [SHA1](#).
- class [SimpleMemberCommand](#)
[Command](#) subclass that calls a pointer to a member function.
- class [SimpleSubjectWatcher](#)
[SimpleSubjectWatcher](#) This is a typical [Subject](#) Watcher class. It will observe all events.
- class [SmartPointer](#)
Class for Smart Pointer.
- class [SOPClassUIDToIOD](#)
Class convert a class SOP Class UID into [IOD](#).
- class [Sorter](#)
[Sorter](#) General class to do sorting using a custom function You simply need to provide a function of type: [Sorter::Sort-Function](#).
- class [Spacing](#)
Class for [Spacing](#).
- class [Spectroscopy](#)
[Spectroscopy](#) class.
- class [SplitMosaicFilter](#)
[SplitMosaicFilter](#) class Class to reshuffle bytes for a SIEMENS Mosaic image Siemens CSA [Image](#) Header CSA:= Common Siemens Architecture, sometimes also known as Common syngo Architecture.
- class [StartEvent](#)
- struct [static_assert_test](#)
- struct [STATIC_ASSERTION_FAILURE](#)
- struct [STATIC_ASSERTION_FAILURE< true >](#)
- class [StreamImageReader](#)
[StreamImageReader](#).
- class [StreamImageWriter](#)
[StreamImageReader](#).
- class [String](#)
[String](#).
- class [StringFilter](#)
[StringFilter](#) [StringFilter](#) is the class that make gdc2.x looks more like gdc1 and transform the binary blob contained in a [DataElement](#) into a string, typically this is a nice feature to have for wrapped language.
- class [Study](#)
[Study](#).
- class [Subject](#)
[Subject](#).
- class [Surface](#)
This class defines a SURFACE IE. This members are taken from required surface mesh module attributes.
- class [SurfaceHelper](#)

- SurfaceHelper* Helper class for *Surface* object.
- class [SurfaceReader](#)
 - This class defines a SURFACE IE reader. It reads surface mesh module attributes.*
- class [SurfaceWriter](#)
 - This class defines a SURFACE IE writer. It writes surface mesh module attributes.*
- class [SwapCode](#)
 - SwapCode* representation.
- class [SwapperDoOp](#)
- class [SwapperNoOp](#)
- class [System](#)
 - Class to do system operation.*
- class [Table](#)
 - Table.*
- class [TableEntry](#)
 - TableEntry.*
- class [TableReader](#)
 - Class for representing a [TableReader](#).*
- class [Tag](#)
 - Class to represent a DICOM Data [Element](#) ([Attribute](#)) [Tag](#) (Group, [Element](#)). Basically an uint32_t which can also be expressed as two uint16_t (group and element)*
- class [TagPath](#)
 - class to handle a path of tag.*
- class [Testing](#)
 - class for testing*
- class [Trace](#)
 - Trace.*
- class [TransferSyntax](#)
 - Class to manipulate Transfer Syntax.*
- class [Type](#)
 - Type.*
- struct [UI](#)
- class [UIDGenerator](#)
 - Class for generating unique UID.*
- class [UIDs](#)
 - all known uids*
- class [UNExplicitDataElement](#)
 - Class to read/write a [DataElement](#) as UNExplicit Data [Element](#).*
- class [UNExplicitImplicitDataElement](#)
 - Class to read/write a [DataElement](#) as ExplicitImplicit Data [Element](#) This class gather two known bugs:*
- class [Unpacker12Bits](#)
 - Pack/Unpack 12 bits pixel into 16bits.*
- class [Usage](#)
 - Usage.*
- class [UserEvent](#)
- class [Validate](#)
 - [Validate](#) class.*
- class [Value](#)

- Class to represent the value of a Data [Element](#).*
- class [ValueIO](#)
 - Class to dispatch template calls.*
- class [Version](#)
 - major/minor and build version*
- class [VL](#)
 - [Value](#) Length.*
- class [VM](#)
 - [Value](#) Multiplicity Looking at the DICOMV3 dict only there is very few cases: 1 2 3 4 5 6 8 16 24 1-2 1-3 1-8 1-32 1-99 1-n 2-2n 2-n 3-3n 3-n.*
- struct [VMToLength](#)
- class [VR](#)
 - [VR](#) class This is adapted from DICOM standard The biggest difference is the INVALID [VR](#) and the composite one that differ from standard (more like an addition) This allow us to represent all the possible case express in the DICOMV3 dict.*
- class [VR16ExplicitDataElement](#)
 - Class to read/write a [DataElement](#) as Explicit Data [Element](#).*
- struct [VRToEncoding](#)
- struct [VRToType](#)
- class [VRVLSize](#)
- class [VRVLSize< 0 >](#)
- class [VRVLSize< 1 >](#)
- class [Waveform](#)
 - [Waveform](#) class.*
- class [Writer](#)
 - [Writer](#) ala DOM (Document [Object](#) Model) This class is a non-validating writer, it will only performs well- formedness check only.*
- class [XMLDictReader](#)
 - Class for representing a [XMLDictReader](#).*
- class [XMLPrivateDictReader](#)
 - Class for representing a [XMLPrivateDictReader](#).*

Typedefs

- typedef [String](#)<"\", 16 > [AECComp](#)
- typedef [String](#)<"\", 64 > [ASComp](#)
- typedef bool(* [BOOL_FUNCTION_PFILE_PFILE_POINTER](#))(File *, [File](#) *)
- typedef [String](#)<"\", 16 > [CSCComp](#)
- typedef [String](#)<"\", 64 > [DACComp](#)
- typedef [String](#)<"\", 64 > [DTComp](#)
- typedef std::vector< [SmartPointer](#)< [FileWithName](#) > > [FileList](#)
- typedef [Bitmap](#) [IconImage](#)
- typedef [String](#)<"\", 64 > [LOComp](#)
- typedef [String](#)<"\", 64 > [LTComp](#)
- typedef [ModuleEntry](#) [MacroEntry](#)
- typedef [NestedModuleEntries](#) [NestedMacroEntries](#)
- typedef [String](#)<"\", 64 > [PNComp](#)
- typedef [String](#)<"\", 64 > [SHComp](#)
- typedef [String](#)<"\", 64 > [STComp](#)
- typedef [String](#)<"\", 16 > [TMComp](#)
- typedef [String](#)<"\", 64, 0 > [UIComp](#)
- typedef [String](#)<"\", 64 > [UTComp](#)

Enumerations

- enum [CompOperators](#) {
[GDCM_EQUAL](#) = 0,
[GDCM_DIFFERENT](#),
[GDCM_GREATER](#),
[GDCM_GREATEROREQUAL](#),
[GDCM_LESS](#),
[GDCM_LESSCOREQUAL](#) }
- enum [ECharSet](#) {
[eLatin1](#) = 0,
[eLatin2](#),
[eLatin3](#),
[eLatin4](#),
[eCyrillic](#),
[eArabic](#),
[eGreek](#),
[eHebrew](#),
[eLatin5](#),
[eJapanese](#),
[eThai](#),
[eJapaneseKanjiMultibyte](#),
[eJapaneseSupplementaryKanjiMultibyte](#),
[eKoreanHangulHanjaMultibyte](#),
[eUTF8](#),
[eGB18030](#) }
- enum [EQueryLevel](#) {
[ePatient](#) = 0,
[eStudy](#) = 1,
[eSeries](#) = 2,
[eImage](#) = 3 }
- enum [EQueryType](#) {
[eFind](#) = 0,
[eMove](#) }
- enum [ERootType](#) {
[ePatientRootType](#),
[eStudyRootType](#) }
- enum [LodModeType](#) {
[LD_ALL](#) = 0x00000000,
[LD_NOSEQ](#) = 0x00000001,
[LD_NOSHADOW](#) = 0x00000002,
[LD_NOSHADOWSEQ](#) = 0x00000004 }

Functions

- [ignore_char](#) const [backslash](#) ("\\")
- [VR::VRType GetVRFromTag](#) ([Tag](#) const &tag)
- bool [operator!=](#) (const [CodeString](#) &ref, const [CodeString](#) &cs)
- bool [operator!=](#) (const [DataElement](#) &lhs, const [DataElement](#) &rhs)
- std::ostream & [operator<<](#) (std::ostream &os, const [Version](#) &v)
- std::ostream & [operator<<](#) (std::ostream &_os, const [NestedModuleEntries](#) &_val)
- std::ostream & [operator<<](#) (std::ostream &os, const [SwapCode](#) &sc)
- std::ostream & [operator<<](#) (std::ostream &os, const [FileSet](#) &f)

- `std::ostream & operator<< (std::ostream &os, const Region &r)`
- `std::ostream & operator<< (std::ostream &os, Event &e)`

Generic inserter operator for [Event](#) and its subclasses.

- `std::ostream & operator<< (std::ostream &os, const PDElement &val)`
- `std::ostream & operator<< (std::ostream &os, const CommandDataSet &val)`
- `std::ostream & operator<< (std::ostream &os, const PrivateTag &val)`
- `std::ostream & operator<< (std::ostream &os, const Orientation &o)`
- `std::ostream & operator<< (std::ostream &_os, const IODs &_val)`
- `std::ostream & operator<< (std::ostream &_os, const Macros &_val)`
- `std::ostream & operator<< (std::ostream &_os, const Modules &_val)`
- `std::ostream & operator<< (std::ostream &_os, const Type &val)`
- `std::ostream & operator<< (std::ostream &_os, const ModuleEntry &_val)`
- `std::ostream & operator<< (std::ostream &_os, const GroupDict &_val)`
- `std::ostream & operator<< (std::ostream &_os, const IOD &_val)`
- `std::ostream & operator<< (std::ostream &os, const File &val)`
- `std::ostream & operator<< (std::ostream &_os, const Usage &val)`
- `std::ostream & operator<< (std::ostream &os, const Sorter &s)`
- `std::ostream & operator<< (std::ostream &os, const CSAHeaderDictEntry &val)`
- `std::ostream & operator<< (std::ostream &os, const Preamble &val)`
- `std::ostream & operator<< (std::ostream &os, const Dicts &d)`
- `std::ostream & operator<< (std::ostream &_os, const IODEntry &_val)`
- `std::ostream & operator<< (std::ostream &_os, const Macro &_val)`
- `std::ostream & operator<< (std::ostream &os, const CSAHeaderDict &val)`
- `std::ostream & operator<< (std::ostream &os, const PDBHeader &d)`
- `std::ostream & operator<< (std::ostream &os, const CodeString &str)`
- `std::ostream & operator<< (std::ostream &_os, const Module &_val)`
- `std::ostream & operator<< (std::ostream &os, const PhotometricInterpretation &val)`
- `std::ostream & operator<< (std::ostream &os, const Directory &d)`
- `std::ostream & operator<< (std::ostream &os, const Global &g)`
- `std::ostream & operator<< (std::ostream &os, const Object &obj)`
- `std::ostream & operator<< (std::ostream &os, const BasicOffsetTable &val)`
- `std::ostream & operator<< (std::ostream &os, const DictEntry &val)`
- `std::ostream & operator<< (std::ostream &os, const CSAElement &val)`
- `std::ostream & operator<< (std::ostream &os, const CSAHeader &d)`
- `std::ostream & operator<< (std::ostream &os, const VL &val)`
- `std::ostream & operator<< (std::ostream &_os, const TransferSyntax &ts)`
- `std::ostream & operator<< (std::ostream &os, const FileMetaInformation &val)`
- `std::ostream & operator<< (std::ostream &_os, const VM &_val)`
- `std::ostream & operator<< (std::ostream &os, const Scanner &s)`
- `std::ostream & operator<< (std::ostream &os, const Dict &val)`
- `std::ostream & operator<< (std::ostream &_os, const MediaStorage &ms)`
- `std::ostream & operator<< (std::ostream &_os, const VR &val)`
- `std::ostream & operator<< (std::ostream &os, const PixelFormat &pf)`
- `std::ostream & operator<< (std::ostream &os, const Fragment &val)`
- `std::ostream & operator<< (std::ostream &_os, const UI &_val)`
- `std::ostream & operator<< (std::ostream &os, const DataElement &val)`
- `std::ostream & operator<< (std::ostream &_os, const Tag &_val)`
- `std::ostream & operator<< (std::ostream &os, const DataSet &val)`
- `std::ostream & operator<< (std::ostream &os, const Item &val)`
- `std::ostream & operator<< (std::ostream &os, const PrivateDict &val)`

- `std::ostream & operator<<` (`std::ostream &_os`, `const UIDs &uid`)
- `bool operator==` (`const CodeString &ref`, `const CodeString &cs`)
- `template<char TDelimiter, unsigned int TMaxLength, char TPadChar>`
`std::istream & operator>>` (`std::istream &is`, `String< TDelimiter, TMaxLength, TPadChar > &ms`)
- `std::istream & operator>>` (`std::istream &in`, `ignore_char const &ic`)
- `std::istream & operator>>` (`std::istream &_is`, `Tag &_val`)
- `template<typename Float >`
`std::string to_string` (`Float data`)
- `TYPETOENCODING` (`SQ`, `VRBINARY`, `unsigned char`) `TYPETOENCODING(UN`

Variables

- static `Global GlobalInstance`
- `VRBINARY`

24.1.1 Detailed Description

This header defines the classes for the AA Actions, Association Abort Related Actions ([Table 9-9 of ps 3.8-2009](#)).

Since each class is essentially a placeholder for a function pointer, I'm breaking with having each class have its own file for the sake of brevity of the number of files.

This header defines the classes for the AE Actions, Association Establishment Related Actions ([Table 9-6 of ps 3.8-2009](#)).

Since each class is essentially a placeholder for a function pointer, I'm breaking with having each class have its own file for the sake of brevity of the number of files.

This header defines the classes for the AR Actions, Association Release Related Actions ([Table 9-8 of ps 3.8-2009](#)).

Since each class is essentially a placeholder for a function pointer, I'm breaking with having each class have its own file for the sake of brevity of the number of files.

This header defines the classes for the DT Actions, Data Transfer Related Actions ([Table 9-8 of ps 3.8-2009](#)).

Since each class is essentially a placeholder for a function pointer, I'm breaking with having each class have its own file for the sake of brevity of the number of files.

24.1.2 Typedef Documentation

24.1.2.1 `typedef String<'\\',16> gdcm::AECComp`

24.1.2.2 `typedef String<'\\',64> gdcm::ASComp`

24.1.2.3 `typedef bool(* gdcm::BOOL_FUNCTION_PFILE_PFILE_POINTER)(File *, File *)`

24.1.2.4 `typedef String<'\\',16> gdcm::CSCComp`

24.1.2.5 `typedef String<'\\',64> gdcm::DACComp`

24.1.2.6 `typedef String<'\\',64> gdcm::DTComp`

24.1.2.7 `typedef std::vector< SmartPointer<FileWithName> > gdcm::FileList`

24.1.2.8 `typedef Bitmap gdcm::IconImage`

24.1.2.9 `typedef String<'\',64> gdcm::LOComp`

24.1.2.10 `typedef String<'\',64> gdcm::LTComp`

24.1.2.11 `typedef ModuleEntry gdcm::MacroEntry`

24.1.2.12 `typedef NestedModuleEntries gdcm::NestedMacroEntries`

24.1.2.13 `typedef String<'\',64> gdcm::PNComp`

24.1.2.14 `typedef String<'\',64> gdcm::SHComp`

24.1.2.15 `typedef String<'\',64> gdcm::STComp`

24.1.2.16 `typedef String<'\',16> gdcm::TMComp`

24.1.2.17 `typedef String<'\',64,0> gdcm::UIComp`

24.1.2.18 `typedef String<'\',64> gdcm::UTComp`

24.1.3 Enumeration Type Documentation

24.1.3.1 `enum gdcm::CompOperators`

Enumerator

GDCM_EQUAL

GDCM_DIFFERENT

GDCM_GREATER

GDCM_GREATEROREQUAL

GDCM_LESS

GDCM_LESOREQUAL

24.1.3.2 `enum gdcm::ECharSet`

The character sets enumerated in PS 3.3 2009 Annex C, section C.12.1.1.2 The resulting character set is stored in 0008,0005 The conversion to the data element is performed by the [QueryFactory](#) itself

Enumerator

eLatin1

eLatin2

eLatin3

eLatin4

eCyrillic

eArabic

eGreek

eHebrew
eLatin5
eJapanese
eThai
eJapaneseKanjiMultibyte
eJapaneseSupplementaryKanjiMultibyte
eKoreanHangulHanjaMultibyte
eUTF8
eGB18030

24.1.3.3 enum gdcm::EQueryLevel

Enumerator

ePatient
eStudy
eSeries
eImage

24.1.3.4 enum gdcm::EQueryType

Enumerator

eFind
eMove

24.1.3.5 enum gdcm::ERootType

Enumerator

ePatientRootType
eStudyRootType

24.1.3.6 enum gdcm::LodModeType

Enumerator

LD_ALL
LD_NOSEQ
LD_NOSHADOW
LD_NOSHADOWSEQ

24.1.4 Function Documentation

24.1.4.1 ignore_char const gdcm::backslash ('\ ')

Referenced by gdcm::EncodingImplementation< VR::VRASCII >::ReadComputeLength().

24.1.4.2 `VR::VRType gdcmm::GetVRFromTag (Tag const & tag)`

24.1.4.3 `bool gdcmm::operator!= (const CodeString & ref, const CodeString & cs)` `[inline]`

24.1.4.4 `bool gdcmm::operator!= (const DataElement & lhs, const DataElement & rhs)` `[inline]`

24.1.4.5 `std::ostream& gdcmm::operator<< (std::ostream & os, const Version & v)` `[inline]`

References `gdcmm::Version::Print()`.

24.1.4.6 `std::ostream& gdcmm::operator<< (std::ostream & _os, const NestedModuleEntries & _val)` `[inline]`

References `gdcmm::ModuleEntry::DataElementType`, `gdcmm::ModuleEntry::DescriptionField`, and `gdcmm::ModuleEntry::Name`.

24.1.4.7 `std::ostream& gdcmm::operator<< (std::ostream & os, const SwapCode & sc)` `[inline]`

References `gdcmm::SwapCode::GetSwapCodeString()`.

24.1.4.8 `std::ostream& gdcmm::operator<< (std::ostream & os, const FileSet & f)` `[inline]`

24.1.4.9 `std::ostream& gdcmm::operator<< (std::ostream & os, const Region & r)` `[inline]`

References `gdcmm::Region::Print()`.

24.1.4.10 `std::ostream& gdcmm::operator<< (std::ostream & os, Event & e)` `[inline]`

Generic inserter operator for [Event](#) and its subclasses.

References `gdcmm::Event::Print()`.

24.1.4.11 `std::ostream& gdcmm::operator<< (std::ostream & os, const PDBElement & val)` `[inline]`

References `gdcmm::PDBElement::NameField`, and `gdcmm::PDBElement::ValueField`.

24.1.4.12 `std::ostream& gdcmm::operator<< (std::ostream & os, const CommandDataSet & val)` `[inline]`

References `gdcmm::DataSet::Print()`.

24.1.4.13 `std::ostream& gdcmm::operator<< (std::ostream & os, const PrivateTag & val)` `[inline]`

24.1.4.14 `std::ostream& gdcmm::operator<< (std::ostream & os, const Orientation & o)` `[inline]`

References `gdcmm::Orientation::Print()`.

24.1.4.15 `std::ostream& gdcm::operator<< (std::ostream & _os, const IODs & _val) [inline]`

24.1.4.16 `std::ostream& gdcm::operator<< (std::ostream & _os, const Macros & _val) [inline]`

24.1.4.17 `std::ostream& gdcm::operator<< (std::ostream & _os, const Modules & _val) [inline]`

24.1.4.18 `std::ostream& gdcm::operator<< (std::ostream & _os, const Type & val) [inline]`

References `gdcm::Type::GetTypeString()`.

24.1.4.19 `std::ostream& gdcm::operator<< (std::ostream & _os, const ModuleEntry & _val) [inline]`

References `gdcm::ModuleEntry::DataElementType`, `gdcm::ModuleEntry::DescriptionField`, and `gdcm::ModuleEntry::Name`.

24.1.4.20 `std::ostream& gdcm::operator<< (std::ostream & _os, const GroupDict & _val) [inline]`

References `gdcm::GroupDict::GetAbbreviation()`, `gdcm::GroupDict::GetName()`, and `gdcm::GroupDict::Size()`.

24.1.4.21 `std::ostream& gdcm::operator<< (std::ostream & _os, const IOD & _val) [inline]`

24.1.4.22 `std::ostream& gdcm::operator<< (std::ostream & os, const File & val) [inline]`

References `gdcm::File::GetHeader()`.

24.1.4.23 `std::ostream& gdcm::operator<< (std::ostream & _os, const Usage & val) [inline]`

References `gdcm::Usage::GetUsageString()`.

24.1.4.24 `std::ostream& gdcm::operator<< (std::ostream & os, const Sorter & s) [inline]`

References `gdcm::Sorter::Print()`.

24.1.4.25 `std::ostream& gdcm::operator<< (std::ostream & os, const CSAHeaderDictEntry & val) [inline]`

24.1.4.26 `std::ostream& gdcm::operator<< (std::ostream & os, const Preamble & val) [inline]`

24.1.4.27 `std::ostream& gdcm::operator<< (std::ostream & os, const Dicts & d) [inline]`

24.1.4.28 `std::ostream& gdcm::operator<< (std::ostream & _os, const IODEntry & _val) [inline]`

24.1.4.29 `std::ostream& gdcm::operator<< (std::ostream & _os, const Macro & _val) [inline]`

24.1.4.30 `std::ostream& gdcm::operator<< (std::ostream & os, const CSAHeaderDict & val) [inline]`

24.1.4.31 `std::ostream& gdcm::operator<< (std::ostream & os, const PDBHeader & d) [inline]`

References `gdcm::PDBHeader::Print()`.

24.1.4.32 `std::ostream& gdcmm::operator<< (std::ostream & os, const CodeString & str)` `[inline]`

24.1.4.33 `std::ostream& gdcmm::operator<< (std::ostream & _os, const Module & _val)` `[inline]`

24.1.4.34 `std::ostream& gdcmm::operator<< (std::ostream & os, const PhotometricInterpretation & val)` `[inline]`

References `gdcmm::PhotometricInterpretation::GetPIString()`.

24.1.4.35 `std::ostream& gdcmm::operator<< (std::ostream & os, const Directory & d)` `[inline]`

References `gdcmm::Directory::Print()`.

24.1.4.36 `std::ostream& gdcmm::operator<< (std::ostream & os, const Global & g)` `[inline]`

24.1.4.37 `std::ostream& gdcmm::operator<< (std::ostream & os, const Object & obj)` `[inline]`

References `gdcmm::Object::Print()`.

24.1.4.38 `std::ostream& gdcmm::operator<< (std::ostream & os, const BasicOffsetTable & val)` `[inline]`

References `gdcmm::DataElement::GetByteValue()`, `gdcmm::DataElement::ValueField`, and `gdcmm::DataElement::ValueLengthField`.

24.1.4.39 `std::ostream& gdcmm::operator<< (std::ostream & os, const DictEntry & val)` `[inline]`

24.1.4.40 `std::ostream& gdcmm::operator<< (std::ostream & os, const CSAElement & val)` `[inline]`

References `gdcmm::CSAElement::DataField`, `gdcmm::ByteValue::GetLength()`, `gdcmm::ByteValue::GetPointer()`, `gdcmm::CSAElement::KeyField`, `gdcmm::CSAElement::NameField`, `gdcmm::CSAElement::NoOfItemsField`, `gdcmm::CSAElement::SyngoDTField`, `gdcmm::CSAElement::ValueMultiplicityField`, `gdcmm::VM::VM1`, and `gdcmm::CSAElement::VRField`.

24.1.4.41 `std::ostream& gdcmm::operator<< (std::ostream & os, const CSAHeader & d)` `[inline]`

References `gdcmm::CSAHeader::Print()`.

24.1.4.42 `std::ostream& gdcmm::operator<< (std::ostream & os, const VL & val)` `[inline]`

24.1.4.43 `std::ostream& gdcmm::operator<< (std::ostream & _os, const TransferSyntax & ts)` `[inline]`

References `gdcmm::TransferSyntax::GetTSSString()`.

24.1.4.44 `std::ostream& gdcmm::operator<< (std::ostream & os, const FileMetaInformation & val)` `[inline]`

References `gdcmm::FileMetaInformation::GetPreamble()`, and `gdcmm::DataSet::Print()`.

24.1.4.45 `std::ostream& gdcmm::operator<< (std::ostream & _os, const VM & _val)` `[inline]`

References `gdcmm::VM::GetVMString()`.

24.1.4.46 `std::ostream& gdcm::operator<< (std::ostream & os, const Scanner & s)` `[inline]`

References `gdcm::Scanner::Print()`.

24.1.4.47 `std::ostream& gdcm::operator<< (std::ostream & os, const Dict & val)` `[inline]`

24.1.4.48 `std::ostream& gdcm::operator<< (std::ostream & _os, const MediaStorage & ms)` `[inline]`

References `gdcm::MediaStorage::GetMSString()`.

24.1.4.49 `std::ostream& gdcm::operator<< (std::ostream & _os, const VR & val)` `[inline]`

References `gdcm::VR::GetVRString()`.

24.1.4.50 `std::ostream& gdcm::operator<< (std::ostream & os, const PixelFormat & pf)` `[inline]`

References `gdcm::PixelFormat::Print()`.

24.1.4.51 `std::ostream& gdcm::operator<< (std::ostream & os, const Fragment & val)` `[inline]`

References `gdcm::DataElement::TagField`, `gdcm::DataElement::ValueField`, and `gdcm::DataElement::ValueLengthField`.

24.1.4.52 `std::ostream& gdcm::operator<< (std::ostream & _os, const UI & _val)` `[inline]`

References `gdcm::UI::Internal`.

24.1.4.53 `std::ostream& gdcm::operator<< (std::ostream & os, const DataElement & val)` `[inline]`

References `gdcm::Object::Print()`, `gdcm::DataElement::TagField`, `gdcm::DataElement::ValueField`, `gdcm::DataElement::ValueLengthField`, and `gdcm::DataElement::VRField`.

24.1.4.54 `std::ostream& gdcm::operator<< (std::ostream & _os, const Tag & _val)` `[inline]`

24.1.4.55 `std::ostream& gdcm::operator<< (std::ostream & os, const DataSet & val)` `[inline]`

References `gdcm::DataSet::Print()`.

24.1.4.56 `std::ostream& gdcm::operator<< (std::ostream & os, const Item & val)` `[inline]`

References `gdcm::DataSet::Print()`, `gdcm::DataElement::TagField`, and `gdcm::DataElement::ValueLengthField`.

24.1.4.57 `std::ostream& gdcm::operator<< (std::ostream & os, const PrivateDict & val)` `[inline]`

24.1.4.58 `std::ostream& gdcm::operator<< (std::ostream & _os, const UIDs & uid)` `[inline]`

References `gdcm::UIDs::GetName()`, and `gdcm::UIDs::GetString()`.

24.1.4.59 `bool gdcm::operator== (const CodeString & ref, const CodeString & cs)` `[inline]`

24.1.4.60 `template<char TDelimiter, unsigned int TMaxLength, char TPadChar> std::istream& gdcm::operator>> (std::istream & is, String< TDelimiter, TMaxLength, TPadChar > & ms)` `[inline]`

24.1.4.61 `std::istream& gdcm::operator>> (std::istream & in, ignore_char const & ic)` `[inline]`

References `gdcm::ignore_char::m_char`.

24.1.4.62 `std::istream& gdcm::operator>> (std::istream & _is, Tag & _val)` `[inline]`

References `gdcm::Tag::SetElement()`, and `gdcm::Tag::SetGroup()`.

24.1.4.63 `template<typename Float > std::string gdcm::to_string (Float data)`

Referenced by `gdcm::EncodingImplementation< VR::VRASCII >::Write()`.

24.1.4.64 `gdcm::TYPETOENCODING (SQ , VRBINARY , unsigned char)`

24.1.5 Variable Documentation

24.1.5.1 `Global gdcm::GlobalInstance` `[static]`

24.1.5.2 `gdcm::VRBINARY`

24.2 gdcm::network Namespace Reference

Classes

- class [AAbortPDU](#)
[AAbortPDU Table](#) 9-26 A-ABORT PDU FIELDS.
- class [AAssociateACPDU](#)
[AAssociateACPDU Table](#) 9-17 ASSOCIATE-AC PDU fields.
- class [AAssociateRJPDU](#)
[AAssociateRJPDU Table](#) 9-21 ASSOCIATE-RJ PDU FIELDS.
- class [AAssociateRQPDU](#)
[AAssociateRQPDU Table](#) 9-11 ASSOCIATE-RQ PDU fields.
- class [AbstractSyntax](#)
[AbstractSyntax Table](#) 9-14 ABSTRACT SYNTAX SUB-ITEM FIELDS.
- class [ApplicationContext](#)
[ApplicationContext Table](#) 9-12 APPLICATION CONTEXT ITEM FIELDS Looks like Application Context can only be 64 bytes at max (see Figure 9-1 / PS 3.8 - 2009)
- class [AReleaseRPPDU](#)
[AReleaseRPPDU Table](#) 9-25 A-RELEASE-RP PDU fields.
- class [AReleaseRQPDU](#)
[AReleaseRQPDU Table](#) 9-24 A-RELEASE-RQ PDU FIELDS.
- class [ARTIMTimer](#)
[ARTIMTimer](#) This file contains the code for the ARTIM timer.

- class [AsynchronousOperationsWindowSub](#)
AsynchronousOperationsWindowSub PS 3.7 [Table D.3-7 ASYNCHRONOUS OPERATIONS WINDOW SUB-ITEM FIELDS \(A-ASSOCIATE-RQ\)](#)
- class [BaseCompositeMessage](#)
BaseCompositeMessage The Composite events described in section 3.7-2009 of the DICOM standard all use their own messages. These messages are constructed using Presentation Data Values, from section 3.8-2009 of the standard, and then fill in appropriate values in their datasets.
- class [BasePDU](#)
BasePDU base class for PDUs.
- class [CEchoRQ](#)
CEchoRQ this file defines the messages for the echo action.
- class [CEchoRSP](#)
CEchoRSP this file defines the messages for the echo action.
- class [CFind](#)
- class [CFindCancelRQ](#)
CFindCancelRQ this file defines the messages for the cfind action.
- class [CFindRQ](#)
CFindRQ this file defines the messages for the cfind action.
- class [CFindRSP](#)
CFindRSP this file defines the messages for the cfind action.
- class [CMoveCancelRq](#)
- class [CMoveRQ](#)
CMoveRQ this file defines the messages for the cmove action.
- class [CMoveRSP](#)
CMoveRSP this file defines the messages for the cmove action.
- class [CompositeMessageFactory](#)
CompositeMessageFactory This class constructs PDataPDUs, but that have been specifically constructed for the composite DICOM services (C-Echo, C-Find, C-Get, C-Move, and C-Store). It will also handle parsing the incoming data to determine which of the CompositePDUs the incoming data is, and so therefore allowing the scu to determine what to do with incoming data (if acting as a storescp server, for instance).
- class [CStoreRQ](#)
CStoreRQ this file defines the messages for the echo action.
- class [CStoreRSP](#)
CStoreRSP this file defines the messages for the echo action.
- class [DIMSE](#)
DIMSE PS 3.7 - 2009 Annex E [Command Dictionary \(Normative\) E.1 REGISTRY OF DICOM COMMAND ELEMENTS Table E.1-1 COMMAND FIELDS \(PART 1\)](#)
- class [ImplementationClassUIDSub](#)
ImplementationClassUIDSub PS 3.7 [Table D.3-1 IMPLEMENTATION CLASS UID SUB-ITEM FIELDS \(A-ASSOCIATE-RQ\)](#)
- class [ImplementationUIDSub](#)
ImplementationUIDSub [Table D.3-2 IMPLEMENTATION UID SUB-ITEM FIELDS \(A-ASSOCIATE-AC\)](#)
- class [ImplementationVersionNameSub](#)
ImplementationVersionNameSub [Table D.3-3 IMPLEMENTATION VERSION NAME SUB-ITEM FIELDS \(A-ASSOCIATE-RQ\)](#)
- class [MaximumLengthSub](#)
MaximumLengthSub Annex D [Table D.1-1 MAXIMUM LENGTH SUB-ITEM FIELDS \(A-ASSOCIATE-RQ\)](#)
- class [PDataTFPDU](#)
PDataTFPDU [Table 9-22 P-DATA-TF PDU FIELDS.](#)

- class [PDUFactory](#)
PDUFactory basically, given an initial byte, construct the appropriate PDU. This way, the event loop doesn't have to know about all the different PDU types.
- class [PresentationContextAC](#)
PresentationContextAC [Table 9-18](#) PRESENTATION CONTEXT ITEM FIELDS.
- class [PresentationContextRQ](#)
PresentationContextRQ [Table 9-13](#) PRESENTATION CONTEXT ITEM FIELDS.
- class [PresentationDataValue](#)
PresentationDataValue [Table 9-23](#) PRESENTATION-DATA-VALUE ITEM FIELDS.
- class [RoleSelectionSub](#)
RoleSelectionSub [PS 3.7 Table D.3-9](#) SCP/SCU ROLE SELECTION SUB-ITEM FIELDS (A-ASSOCIATE-RQ)
- class [ServiceClassApplicationInformation](#)
- class [SOPClassExtendedNegociationSub](#)
SOPClassExtendedNegociationSub [PS 3.7 Table D.3-11](#) SOP CLASS EXTENDED NEGOTIATION SUB-ITEM FIELDS (A-ASSOCIATE-RQ and A-ASSOCIATE-AC)
- class [TableRow](#)
- class [TransferSyntaxSub](#)
TransferSyntaxSub [Table 9-15](#) TRANSFER SYNTAX SUB-ITEM FIELDS.
- struct [Transition](#)
- class [ULAction](#)
ULAction A [ULConnection](#) in a given [ULState](#) can perform certain [ULActions](#). This base class provides the interface for running those [ULActions](#) on a given [ULConnection](#).
- class [ULActionAA1](#)
- class [ULActionAA2](#)
- class [ULActionAA3](#)
- class [ULActionAA4](#)
- class [ULActionAA5](#)
- class [ULActionAA6](#)
- class [ULActionAA7](#)
- class [ULActionAA8](#)
- class [ULActionAE1](#)
- class [ULActionAE2](#)
- class [ULActionAE3](#)
- class [ULActionAE4](#)
- class [ULActionAE5](#)
- class [ULActionAE6](#)
- class [ULActionAE7](#)
- class [ULActionAE8](#)
- class [ULActionAR1](#)
- class [ULActionAR10](#)
- class [ULActionAR2](#)
- class [ULActionAR3](#)
- class [ULActionAR4](#)
- class [ULActionAR5](#)
- class [ULActionAR6](#)
- class [ULActionAR7](#)
- class [ULActionAR8](#)
- class [ULActionAR9](#)
- class [ULActionDT1](#)
- class [ULActionDT2](#)

- class [ULBasicCallback](#)

[ULBasicCallback](#) This is the most basic of callbacks for how the [ULConnectionManager](#) handles incoming datasets. Data-Sets are just concatenated to the `mDataSets` vector, and the result can be pulled out of the vector by later code. Alternatives to this method include progress updates, saving to disk, etc. This class is NOT THREAD SAFE. Access the dataset vector after the entire set of datasets has been returned by the [ULConnectionManager](#).

- class [ULConnection](#)

[ULConnection](#) This is the class that contains the socket to another machine, and passes data through itself, as well as maintaining a sense of state.

- class [ULConnectionCallback](#)

- class [ULConnectionInfo](#)

[ULConnectionInfo](#) this class contains all the information about a particular connection as established by the user. That is, it's: User Information Calling AE Title Called AE Title IP address/computer name IP Port A connection must be established with this information, that's subsequently placed into various primitives for actual communication.

- class [ULConnectionManager](#)

[ULConnectionManager](#) The [ULConnectionManager](#) performs actions on the [ULConnection](#) given inputs from the user and from the state of what's going on around the connection (ie, timeouts of the ARTIM timer, responses from the peer across the connection, etc).

- class [ULEvent](#)

[ULEvent](#) base class for network events.

- class [ULTransitionTable](#)

[ULTransitionTable](#) The transition table of all the [ULEvents](#), new [ULActions](#), and [ULStates](#).

- class [ULWritingCallback](#)

- class [UserInformation](#)

[UserInformation](#) Table 9-16 USER INFORMATION ITEM FIELDS.

Enumerations

- enum [EEventID](#) {
[eAASSOCIATERequestLocalUser](#) = 0,
[eTransportConnConfirmLocal](#),
[eASSOCIATE_ACPDUreceived](#),
[eASSOCIATE_RJPDUreceived](#),
[eTransportConnIndicLocal](#),
[eAASSOCIATE_RQPDUreceived](#),
[eAASSOCIATEResponseAccept](#),
[eAASSOCIATEResponseReject](#),
[ePDATArequest](#),
[ePDATATFPDU](#),
[eARELEASERequest](#),
[eARELEASE_RQPDUReceivedOpen](#),
[eARELEASE_RPPDUReceived](#),
[eARELEASEResponse](#),
[eAABORTRequest](#),
[eAABORTPDUReceivedOpen](#),
[eTransportConnectionClosed](#),
[eARTIMTimerExpired](#),
[eUnrecognizedPDUReceived](#),
[eEventDoesNotExist](#) }

- enum [EStateID](#) {
[eStaDoesNotExist](#) = 0,
[eSta1Idle](#) = 1,
[eSta2Open](#) = 2,
[eSta3WaitLocalAssoc](#) = 4,
[eSta4LocalAssocDone](#) = 8,
[eSta5WaitRemoteAssoc](#) = 16,
[eSta6TransferReady](#) = 32,
[eSta7WaitRelease](#) = 64,
[eSta8WaitLocalRelease](#) = 128,
[eSta9ReleaseCollisionRqLocal](#) = 256,
[eSta10ReleaseCollisionAc](#) = 512,
[eSta11ReleaseCollisionRq](#) = 1024,
[eSta12ReleaseCollisionAcLocal](#) = 2048,
[eSta13AwaitingClose](#) = 4096 }

Functions

- int [GetStateIndex](#) ([EStateID](#) inState)

Variables

- const int [cMaxEventID](#) = [eEventDoesNotExist](#)
- const int [cMaxStateID](#) = 13

24.2.1 Enumeration Type Documentation

24.2.1.1 enum `gdcmm::network::EEventID`

Enumerator

eAASSOCIATERequestLocalUser
eTransportConnConfirmLocal
eASSOCIATE_ACPDUreceived
eASSOCIATE_RJPDUreceived
eTransportConnIndicLocal
eAASSOCIATE_RQPDUreceived
eAASSOCIATEResponseAccept
eAASSOCIATEResponseReject
ePDATArequest
ePDATATFPDU
eARELEASERequest
eARELEASE_RQPDUReceivedOpen
eARELEASE_RPPDUReceived
eARELEASEResponse
eAABORTRequest
eAABORTPDUReceivedOpen

eTransportConnectionClosed
eARTIMTimerExpired
eUnrecognizedPDUReceived
eEventDoesNotExist

24.2.1.2 enum gdcmm::network::EStateID

Each network connection will be in a particular state at any given time. Those states have IDs as described in the standard ps3.8-2009, roughly 1-13. This enumeration lists those states. The actual ULState class will contain more information about transitions to other states.

name and date: 16 sept 2010 mmr

Enumerator

eStaDoesNotExist
eSta1Idle
eSta2Open
eSta3WaitLocalAssoc
eSta4LocalAssocDone
eSta5WaitRemoteAssoc
eSta6TransferReady
eSta7WaitRelease
eSta8WaitLocalRelease
eSta9ReleaseCollisionRqLocal
eSta10ReleaseCollisionAc
eSta11ReleaseCollisionRq
eSta12ReleaseCollisionAcLocal
eSta13AwaitingClose

24.2.2 Function Documentation

24.2.2.1 int gdcmm::network::GetStateIndex (EStateID inState) [inline]

References eSta10ReleaseCollisionAc, eSta11ReleaseCollisionRq, eSta12ReleaseCollisionAcLocal, eSta13AwaitingClose, eSta1Idle, eSta2Open, eSta3WaitLocalAssoc, eSta4LocalAssocDone, eSta5WaitRemoteAssoc, eSta6TransferReady, eSta7WaitRelease, eSta8WaitLocalRelease, eSta9ReleaseCollisionRqLocal, and eStaDoesNotExist.

24.2.3 Variable Documentation

24.2.3.1 const int gdcmm::network::cMaxEventID = eEventDoesNotExist

24.2.3.2 const int gdcmm::network::cMaxStateID = 13

Referenced by gdcmm::network::TableRow::TableRow(), and gdcmm::network::TableRow::~~TableRow().

24.3 gdcmm::SegmentHelper Namespace Reference

Classes

- struct [BasicCodedEntry](#)

This structure defines a basic coded entry with all of its attributes.

24.4 gdcmm::terminal Namespace Reference

Class for Terminal Allow one to print in color in a shell.

Enumerations

- enum [Attribute](#) {
 [reset](#) = 0,
 [bright](#) = 1,
 [dim](#) = 2,
 [underline](#) = 3,
 [blink](#) = 5,
 [reverse](#) = 7,
 [hidden](#) = 8 }
- enum [Color](#) {
 [black](#) = 0,
 [red](#),
 [green](#),
 [yellow](#),
 [blue](#),
 [magenta](#),
 [cyan](#),
 [white](#) }
- enum [Mode](#) {
 [CONSOLE](#) = 0,
 [VT100](#) }

Functions

- [GDCM_EXPORT](#) std::string [setattribute](#) ([Attribute](#) att)
- [GDCM_EXPORT](#) std::string [setbgcolor](#) ([Color](#) c)
- [GDCM_EXPORT](#) std::string [setfgcolor](#) ([Color](#) c)
- [GDCM_EXPORT](#) void [setmode](#) ([Mode](#) m)

24.4.1 Detailed Description

Class for Terminal Allow one to print in color in a shell.

- support VT100 compatible shell
- win32 console

24.4.2 Enumeration Type Documentation

24.4.2.1 enum gdcmm::terminal::Attribute

Enumerator

reset
bright
dim
underline
blink
reverse
hidden

24.4.2.2 enum gdcmm::terminal::Color

Enumerator

black
red
green
yellow
blue
magenta
cyan
white

24.4.2.3 enum gdcmm::terminal::Mode

Enumerator

CONSOLE
VT100

24.4.3 Function Documentation

24.4.3.1 GDCM_EXPORT std::string gdcmm::terminal::setattribute (Attribute *att*)

24.4.3.2 GDCM_EXPORT std::string gdcmm::terminal::setbgcolor (Color *c*)

24.4.3.3 GDCM_EXPORT std::string gdcmm::terminal::setfgcolor (Color *c*)

24.4.3.4 GDCM_EXPORT void gdcmm::terminal::setmode (Mode *m*)

Chapter 25


Class Documentation

25.1 gdcmm::network::AAabortPDU Class Reference


[AAabortPDU](#) [Table 9-26](#) A-ABORT PDU FIELDS.

```
#include <gdcmmAAabortPDU.h>
```

Inheritance diagram for gdcmm::network::AAabortPDU:



Collaboration diagram for `gdcm::network::AAabortPDU`:



Public Member Functions

- [AAabortPDU](#) ()
- bool [IsLastFragment](#) () const
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- void [SetReason](#) (const uint8_t r)
- void [SetSource](#) (const uint8_t s)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.1.1 Detailed Description

[AAabortPDU Table](#) 9-26 A-ABORT PDU FIELDS.

25.1.2 Constructor & Destructor Documentation

25.1.2.1 `gdcm::network::AAabortPDU::AAabortPDU ()`

25.1.3 Member Function Documentation

25.1.3.1 `bool gdcm::network::AAabortPDU::IsLastFragment () const` `[inline],[virtual]`

Implements [gdcm::network::BasePDU](#).

25.1.3.2 `void gdcm::network::AAabortPDU::Print (std::ostream & os) const` `[virtual]`

Implements [gdcm::network::BasePDU](#).

25.1.3.3 `std::istream& gdcm::network::AAabortPDU::Read (std::istream & is)` `[virtual]`

Implements [gdcm::network::BasePDU](#).

25.1.3.4 void gdcm::network::AAbortPDU::SetReason (const uint8_t r)

25.1.3.5 void gdcm::network::AAbortPDU::SetSource (const uint8_t s)

25.1.3.6 size_t gdcm::network::AAbortPDU::Size () const [virtual]

Implements [gdcm::network::BasePDU](#).

25.1.3.7 const std::ostream& gdcm::network::AAbortPDU::Write (std::ostream & os) const [virtual]

Implements [gdcm::network::BasePDU](#).

The documentation for this class was generated from the following file:


- [gdcmAAbortPDU.h](#)

25.2 gdcm::network::AAssociateACPDU Class Reference


[AAssociateACPDU](#) Table 9-17 ASSOCIATE-AC PDU fields.

```
#include <gdcmAAssociateACPDU.h>
```

Inheritance diagram for gdcm::network::AAssociateACPDU:



Collaboration diagram for `gdcmm::network::AAssociateACPDU`:



Public Types

- `typedef std::vector`
`< PresentationContextAC >`
`::size_type SizeType`

Public Member Functions

- [AAssociateACPDU](#) ()
- `void AddPresentationContextAC (PresentationContextAC const &pcac)`
- `SizeType GetNumberOfPresentationContextAC () const`
- `const PresentationContextAC & GetPresentationContextAC (SizeType i)`
- `const UserInfo & GetUserInfo () const`
- `void InitFromRQ (AAssociateRQPDU const &rqpdu)`
- `bool IsLastFragment () const`
- `void Print (std::ostream &os) const`
- `std::istream & Read (std::istream &is)`
- `SizeType Size () const`
- `const std::ostream & Write (std::ostream &os) const`

Protected Member Functions

- `void SetCalledAETitle (const char calledaetitle[16])`
- `void SetCallingAETitle (const char callingaetitle[16])`

Friends

- class [AAssociateRQPDU](#)

25.2.1 Detailed Description

[AAssociateACPDU Table 9-17](#) ASSOCIATE-AC PDU fields.

25.2.2 Member Typedef Documentation

25.2.2.1 `typedef std::vector<PresentationContextAC>::size_type gdcm::network::AAssociateACPDU::SizeType`

25.2.3 Constructor & Destructor Documentation

25.2.3.1 `gdcm::network::AAssociateACPDU::AAssociateACPDU ()`

25.2.4 Member Function Documentation

25.2.4.1 `void gdcm::network::AAssociateACPDU::AddPresentationContextAC (PresentationContextAC const & pcac)`

25.2.4.2 `SizeType gdcm::network::AAssociateACPDU::GetNumberOfPresentationContextAC () const [inline]`

25.2.4.3 `const PresentationContextAC& gdcm::network::AAssociateACPDU::GetPresentationContextAC (SizeType i) [inline]`

25.2.4.4 `const UserInformation& gdcm::network::AAssociateACPDU::GetUserInformation () const [inline]`

25.2.4.5 `void gdcm::network::AAssociateACPDU::InitFromRQ (AAssociateRQPDU const & rqpdu)`

25.2.4.6 `bool gdcm::network::AAssociateACPDU::IsLastFragment () const [inline],[virtual]`

Implements [gdcm::network::BasePDU](#).

25.2.4.7 `void gdcm::network::AAssociateACPDU::Print (std::ostream & os) const [virtual]`

Implements [gdcm::network::BasePDU](#).

25.2.4.8 `std::istream& gdcm::network::AAssociateACPDU::Read (std::istream & is) [virtual]`

Implements [gdcm::network::BasePDU](#).

25.2.4.9 `void gdcm::network::AAssociateACPDU::SetCalledAETitle (const char calledaetitle[16]) [protected]`

25.2.4.10 `void gdcm::network::AAssociateACPDU::SetCallingAETitle (const char callingaetitle[16]) [protected]`

25.2.4.11 `SizeType gdcm::network::AAssociateACPDU::Size () const [virtual]`

Implements [gdcm::network::BasePDU](#).

25.2.4.12 `const std::ostream& gdcm::network::AAssociateACPDU::Write (std::ostream & os) const [virtual]`

Implements [gdcm::network::BasePDU](#).

25.2.5 Friends And Related Function Documentation

25.2.5.1 friend class **AAssociateRQPDU** [friend]

The documentation for this class was generated from the following file:


- [gdcmAAssociateACPDU.h](#)

25.3 gdcmm::network::AAssociateRJPDU Class Reference


[AAssociateRJPDU](#) Table 9-21 ASSOCIATE-RJ PDU FIELDS.

```
#include <gdcmAAssociateRJPDU.h>
```

Inheritance diagram for gdcmm::network::AAssociateRJPDU:



Collaboration diagram for gdcmm::network::AAssociateRJPDU:



Public Member Functions

- [AAssociateRJPDU](#) ()

- bool [IsLastFragment](#) () const
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.3.1 Detailed Description

[AAssociateRJPDUTable](#) 9-21 ASSOCIATE-RJ PDU FIELDS.

25.3.2 Constructor & Destructor Documentation

25.3.2.1 `gdcm::network::AAssociateRJPDUTable::AAssociateRJPDUTable ()`

25.3.3 Member Function Documentation

25.3.3.1 `bool gdcm::network::AAssociateRJPDUTable::IsLastFragment () const` `[inline], [virtual]`

Implements [gdcm::network::BasePDU](#).

25.3.3.2 `void gdcm::network::AAssociateRJPDUTable::Print (std::ostream & os) const` `[virtual]`

Implements [gdcm::network::BasePDU](#).

25.3.3.3 `std::istream& gdcm::network::AAssociateRJPDUTable::Read (std::istream & is)` `[virtual]`

Implements [gdcm::network::BasePDU](#).

25.3.3.4 `size_t gdcm::network::AAssociateRJPDUTable::Size () const` `[virtual]`

Implements [gdcm::network::BasePDU](#).

25.3.3.5 `const std::ostream& gdcm::network::AAssociateRJPDUTable::Write (std::ostream & os) const` `[virtual]`

Implements [gdcm::network::BasePDU](#).

The documentation for this class was generated from the following file:


- [gdcmAAssociateRJPDUTable.h](#)

25.4 gdcm::network::AAssociateRQPDU Class Reference


[AAssociateRQPDU Table](#) 9-11 ASSOCIATE-RQ PDU fields.

```
#include <gdcmAAssociateRQPDU.h>
```

Inheritance diagram for `gdc::network::AAssociateRQPDU`:



Collaboration diagram for `gdc::network::AAssociateRQPDU`:



Public Types

- `typedef std::vector< PresentationContextRQ > PresentationContextArrayType`
- `typedef std::vector< PresentationContextRQ >::size_type SizeType`

Public Member Functions

- [AAssociateRQPDU](#) ()
- [AAssociateRQPDU](#) (const [AAssociateRQPDU](#) &pdu)
- void [AddPresentationContext](#) ([PresentationContextRQ](#) const &pc)
- std::string [GetCalledAETitle](#) () const
- std::string [GetCallingAETitle](#) () const

- [SizeType](#) [GetNumberOfPresentationContext](#) () const
- [PresentationContextRQ](#) const & [GetPresentationContext](#) ([SizeType](#) i) const
- const [PresentationContextRQ](#) * [GetPresentationContextByAbstractSyntax](#) ([AbstractSyntax](#) const &as) const
- const [PresentationContextRQ](#) * [GetPresentationContextByID](#) (uint8_t i) const
- [PresentationContextArrayType](#)
const & [GetPresentationContexts](#) ()
- const [UserInfoInformation](#) & [GetUserInfoInformation](#) () const
- bool [IsLastFragment](#) () const
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- void [SetCalledAETitle](#) (const char calledaetitle[16])
Set the Called AE Title.
- void [SetCallingAETitle](#) (const char callingaetitle[16])
Set the Calling AE Title.
- void [SetUserInfoInformation](#) ([UserInfoInformation](#) const &ui)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

Static Public Member Functions

- static bool [IsAETitleValid](#) (const char title[16])
Check whether or not the title is a valid AE title.

Protected Member Functions

- std::string [GetReserved43_74](#) () const

Friends

- class [AAssociateACPDU](#)

25.4.1 Detailed Description

[AAssociateRQPDU Table](#) 9-11 ASSOCIATE-RQ PDU fields.

25.4.2 Member Typedef Documentation

25.4.2.1 typedef std::vector<[PresentationContextRQ](#)> gdcm::network::AAssociateRQPDU::PresentationContext-ArrayType

25.4.2.2 typedef std::vector<[PresentationContextRQ](#)>::size_type gdcm::network::AAssociateRQPDU::SizeType

25.4.3 Constructor & Destructor Documentation

25.4.3.1 gdcm::network::AAssociateRQPDU::AAssociateRQPDU ()

25.4.3.2 gdcm::network::AAssociateRQPDU::AAssociateRQPDU (const AAssociateRQPDU & pdu) [\[inline\]](#)

25.4.4 Member Function Documentation

25.4.4.1 `void gdcn::network::AAAssociateRQPDU::AddPresentationContext (PresentationContextRQ const & pc)`

25.4.4.2 `std::string gdcn::network::AAAssociateRQPDU::GetCalledAETitle () const [inline]`

25.4.4.3 `std::string gdcn::network::AAAssociateRQPDU::GetCallingAETitle () const [inline]`

25.4.4.4 `SizeType gdcn::network::AAAssociateRQPDU::GetNumberOfPresentationContext () const [inline]`

25.4.4.5 `PresentationContextRQ const& gdcn::network::AAAssociateRQPDU::GetPresentationContext (SizeType i) const [inline]`

25.4.4.6 `const PresentationContextRQ* gdcn::network::AAAssociateRQPDU::GetPresentationContextByAbstractSyntax (AbstractSyntax const & as) const`

25.4.4.7 `const PresentationContextRQ* gdcn::network::AAAssociateRQPDU::GetPresentationContextByID (uint8_t i) const`

25.4.4.8 `PresentationContextArrayType const& gdcn::network::AAAssociateRQPDU::GetPresentationContexts () [inline]`

25.4.4.9 `std::string gdcn::network::AAAssociateRQPDU::GetReserved43_74 () const [protected]`

25.4.4.10 `const UserInformation& gdcn::network::AAAssociateRQPDU::GetUserInformation () const [inline]`

25.4.4.11 `static bool gdcn::network::AAAssociateRQPDU::IsAETitleValid (const char title[16]) [static]`

Check whether or not the title is a valid AE title.

25.4.4.12 `bool gdcn::network::AAAssociateRQPDU::IsLastFragment () const [inline],[virtual]`

Implements [gdcn::network::BasePDU](#).

25.4.4.13 `void gdcn::network::AAAssociateRQPDU::Print (std::ostream & os) const [virtual]`

This function will initialize an [AAAssociateACPDU](#) from the fields in the [AAAssociateRQPDU](#) structure

Implements [gdcn::network::BasePDU](#).

25.4.4.14 `std::istream& gdcn::network::AAAssociateRQPDU::Read (std::istream & is) [virtual]`

Implements [gdcn::network::BasePDU](#).

25.4.4.15 `void gdcn::network::AAAssociateRQPDU::SetCalledAETitle (const char calledaetitle[16])`

Set the Called AE Title.

25.4.4.16 `void gdcn::network::AAAssociateRQPDU::SetCallingAETitle (const char callingaetitle[16])`

Set the Calling AE Title.

25.4.4.17 `void gdcm::network::AAssociateRQPDU::SetUserInformation (UserInformation const & ui)`

25.4.4.18 `size_t gdcm::network::AAssociateRQPDU::Size () const` `[virtual]`

Implements [gdcm::network::BasePDU](#).

25.4.4.19 `const std::ostream& gdcm::network::AAssociateRQPDU::Write (std::ostream & os) const` `[virtual]`

Implements [gdcm::network::BasePDU](#).

25.4.5 Friends And Related Function Documentation

25.4.5.1 `friend class AAssociateACPDU` `[friend]`


The documentation for this class was generated from the following file:

- [gdcmAAssociateRQPDU.h](#)


25.5 gdcm::AbortEvent Class Reference

```
#include <gdcmEvent.h>
```

Inheritance diagram for `gdcm::AbortEvent`:



Collaboration diagram for `gdcm::AbortEvent`:



Additional Inherited Members

The documentation for this class was generated from the following file:

- [gdcmEvent.h](#)

25.6 gdcm::network::AbstractSyntax Class Reference

[AbstractSyntax](#) Table 9-14 ABSTRACT SYNTAX SUB-ITEM FIELDS.

```
#include <gdcmAbstractSyntax.h>
```

Public Member Functions

- [AbstractSyntax](#) ()
- [DataElement GetAsDataElement](#) () const
- const char * [GetName](#) () const
- bool [operator==](#) (const [AbstractSyntax](#) &as) const
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- void [SetName](#) (const char *name)
- void [SetNameFromUID](#) (UIDs::TSName tsname)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.6.1 Detailed Description

[AbstractSyntax](#) Table 9-14 ABSTRACT SYNTAX SUB-ITEM FIELDS.

25.6.2 Constructor & Destructor Documentation

25.6.2.1 `gdcm::network::AbstractSyntax::AbstractSyntax ()`

25.6.3 Member Function Documentation

25.6.3.1 `DataElement gdcm::network::AbstractSyntax::GetAsDataElement () const`

25.6.3.2 `const char* gdcm::network::AbstractSyntax::GetName () const` `[inline]`

25.6.3.3 `bool gdcm::network::AbstractSyntax::operator== (const AbstractSyntax & as) const` `[inline]`

25.6.3.4 `void gdcm::network::AbstractSyntax::Print (std::ostream & os) const`

25.6.3.5 `std::istream& gdcm::network::AbstractSyntax::Read (std::istream & is)`

25.6.3.6 `void gdcm::network::AbstractSyntax::SetName (const char * name)` `[inline]`

25.6.3.7 `void gdcm::network::AbstractSyntax::SetNameFromUID (UIDs::TSName tsname)`

25.6.3.8 `size_t gdcm::network::AbstractSyntax::Size () const`

25.6.3.9 `const std::ostream& gdcm::network::AbstractSyntax::Write (std::ostream & os) const`

The documentation for this class was generated from the following file:


- [gdcmAbstractSyntax.h](#)

25.7 gdcm::AnonymizeEvent Class Reference


[AnonymizeEvent](#) Special type of event triggered during the Anonymization process.

```
#include <gdcmAnonymizeEvent.h>
```

Inheritance diagram for `gdcm::AnonymizeEvent`:



Collaboration diagram for `gdcm::AnonymizeEvent`:



Public Types

- typedef [AnonymizeEvent](#) `Self`
- typedef [AnyEvent](#) `Superclass`

Public Member Functions

- [AnonymizeEvent](#) (`Tag` const &tag=0)

- [AnonymizeEvent](#) (const [Self](#) &s)
- virtual [~AnonymizeEvent](#) ()
- virtual bool [CheckEvent](#) (const [::gdcm::Event](#) *e) const
- virtual const char * [GetEventName](#) () const
- [Tag](#) const & [GetTag](#) () const
- virtual [::gdcm::Event](#) * [MakeObject](#) () const
- void [SetTag](#) (const [Tag](#) &t)

25.7.1 Detailed Description

[AnonymizeEvent](#) Special type of event triggered during the Anonymization process.

See Also

[Anonymizer](#)

25.7.2 Member Typedef Documentation

25.7.2.1 typedef [AnonymizeEvent](#) [gdcm::AnonymizeEvent::Self](#)

25.7.2.2 typedef [AnyEvent](#) [gdcm::AnonymizeEvent::Superclass](#)

25.7.3 Constructor & Destructor Documentation

25.7.3.1 [gdcm::AnonymizeEvent::AnonymizeEvent](#) ([Tag](#) const & *tag* = 0) [\[inline\]](#)

25.7.3.2 virtual [gdcm::AnonymizeEvent::~~AnonymizeEvent](#) () [\[inline\]](#),[\[virtual\]](#)

25.7.3.3 [gdcm::AnonymizeEvent::AnonymizeEvent](#) ([const Self](#) & *s*) [\[inline\]](#)

25.7.4 Member Function Documentation

25.7.4.1 virtual bool [gdcm::AnonymizeEvent::CheckEvent](#) ([const ::gdcm::Event](#) * *e*) const [\[inline\]](#),[\[virtual\]](#)

25.7.4.2 virtual const char* [gdcm::AnonymizeEvent::GetEventName](#) () const [\[inline\]](#),[\[virtual\]](#)

Return the StringName associated with the event.

Implements [gdcm::Event](#).

25.7.4.3 [Tag](#) const& [gdcm::AnonymizeEvent::GetTag](#) () const [\[inline\]](#)

25.7.4.4 virtual [::gdcm::Event](#)* [gdcm::AnonymizeEvent::MakeObject](#) () const [\[inline\]](#),[\[virtual\]](#)

Create an [Event](#) of this type This method work as a Factory for creating events of each particular type.

Implements [gdcm::Event](#).

25.7.4.5 void [gdcm::AnonymizeEvent::SetTag](#) ([const Tag](#) & *t*) [\[inline\]](#)

The documentation for this class was generated from the following file:


- [gdcmAnonymizeEvent.h](#)

25.8 gdcm::Anonymizer Class Reference


[Anonymizer](#) This class is a multi purpose anonymizer. It can work in 2 mode:

```
#include <gdcmAnonymizer.h>
```

Inheritance diagram for gdcm::Anonymizer:



Collaboration diagram for gdcm::Anonymizer:



Public Member Functions

- [Anonymizer](#) ()
- [~Anonymizer](#) ()
- bool [BasicApplicationLevelConfidentialityProfile](#) (bool deidentify=true)
- bool [Empty](#) (Tag const &t)
- const [CryptographicMessageSyntax](#) * [GetCryptographicMessageSyntax](#) () const
- [File](#) & [GetFile](#) ()
- bool [Remove](#) (Tag const &t)
- bool [RemoveGroupLength](#) ()
 - Main function that loop over all elements and remove group length.*
- bool [RemovePrivateTags](#) ()
 - Main function that loop over all elements and remove private tags.*
- bool [RemoveRetired](#) ()
 - Main function that loop over all elements and remove retired element.*
- bool [Replace](#) (Tag const &t, const char *value)
- bool [Replace](#) (Tag const &t, const char *value, [VL](#) const &vl)
- void [SetCryptographicMessageSyntax](#) ([CryptographicMessageSyntax](#) *cms)
 - Set/Get CMS key that will be used to encrypt the dataset within BasicApplicationLevelConfidentialityProfile.*
- void [SetFile](#) (const [File](#) &f)
 - Set/Get File.*

Static Public Member Functions

- static std::vector< [Tag](#) > [GetBasicApplicationLevelConfidentialityProfileAttributes](#) ()
 - Return the list of Tag that will be considered when anonymizing a DICOM file.*
- static [SmartPointer](#)< [Anonymizer](#) > [New](#) ()
 - for wrapped language: instantiate a reference counted object*

Protected Member Functions

- bool [BALCPPProtect](#) ([DataSet](#) &ds, [Tag](#) const &tag, const [IOD](#) &iod)
- bool [CanEmptyTag](#) ([Tag](#) const &tag, const [IOD](#) &iod) const
- void [RecurseDataSet](#) ([DataSet](#) &ds)

25.8.1 Detailed Description

[Anonymizer](#) This class is a multi purpose anonymizer. It can work in 2 mode:

- Full (irreversible) anonymizer (aka dumb mode)
- reversible de-identifier/re-identifier (aka smart mode). This implements the Basic Application Level Confidentiality Profile, DICOM PS 3.15-2009

1. dumb mode This is a dumb anonymizer implementation. All it allows user is simple operation such as:

[Tag](#) based functions:

- complete removal of DICOM attribute ([Remove](#))

- make a tag empty, ie make it's length 0 (Empty)
- replace with another string-based value (Replace)

[DataSet](#) based functions:

- Remove all group length attribute from a DICOM dataset (Group Length element are deprecated, DICOM 2008)
- Remove all private attributes
- Remove all retired attributes

All function calls actually execute the user specified request. Previous implementation were calling a general Anonymize function but traversing a `std::set` is $O(n)$ operation, while a simple user specified request is $O(\log(n))$ operation. So 'm' user interaction is $O(m*\log(n))$ which is $< O(n)$ complexity.

1. smart mode this mode implements the Basic Application Level Confidentiality Profile (DICOM PS 3.15-2008) In this case, it is extremely important to use the same [gdcm::Anonymizer](#) class when anonymizing a [FileSet](#). Once the [gdcm::Anonymizer](#) is destroyed its memory of known (already processed) [UIDs](#) will be lost. which will make the anonymizer behaves incorrectly for attributes such as [Series](#) UID [Study](#) UID where user want some consistency. When attribute is [Type](#) 1 / [Type](#) 1C, a dummy generator will take in the existing value and produce a dummy value (a sha1 representation). sha1 algorithm is considered to be cryptographically strong (compared to md5sum) so that we meet the following two conditions:

- Produce the same dummy value for the same input value
- do not provide an easy way to retrieve the original value from the sha1 generated value

This class implement the Subject/Observer pattern trigger the following event:

- [AnonymizeEvent](#)
- [IterationEvent](#)
- [StartEvent](#)
- [EndEvent](#)

See Also

[CryptographicMessageSyntax](#)

Examples:

[ClinicalTrialAnnotate.cxx](#), [CreateJPIPDataSet.cxx](#), and [EncapsulateFileInRawData.cxx](#).

25.8.2 Constructor & Destructor Documentation

25.8.2.1 `gdcm::Anonymizer::Anonymizer ()` `[inline]`

25.8.2.2 `gdcm::Anonymizer::~~Anonymizer ()`

25.8.3 Member Function Documentation

25.8.3.1 `bool gdcm::Anonymizer::BALCPPProtect (DataSet & ds, Tag const & tag, const IOD & iod)` `[protected]`

25.8.3.2 `bool gdcm::Anonymizer::BasicApplicationLevelConfidentialityProfile (bool deidentify = true)`

PS 3.15 / E.1.1 De-Identifier An Application may claim conformance to the Basic Application Level Confidentiality Profile as a deidentifier if it protects all Attributes that might be used by unauthorized entities to identify the patient. NOT THREAD SAFE

25.8.3.3 `bool gdcm::Anonymizer::CanEmptyTag (Tag const & tag, const IOD & iod) const` [protected]

25.8.3.4 `bool gdcm::Anonymizer::Empty (Tag const & t)`

Make [Tag](#) *t* empty (if not found tag will be created) Warning: does not handle SQ element

Examples:

[CreateJPIPDataSet.cxx](#).

25.8.3.5 `static std::vector<Tag> gdcm::Anonymizer::GetBasicApplicationLevelConfidentialityProfileAttributes ()` [static]

Return the list of [Tag](#) that will be considered when anonymizing a DICOM file.

Examples:

[GenFakeIdentifyFile.cxx](#), and [TraverseModules.cxx](#).

25.8.3.6 `const CryptographicMessageSyntax* gdcm::Anonymizer::GetCryptographicMessageSyntax () const`

25.8.3.7 `File& gdcm::Anonymizer::GetFile ()` [inline]

25.8.3.8 `static SmartPointer<Anonymizer> gdcm::Anonymizer::New ()` [inline],[static]

for wrapped language: instantiate a reference counted object

25.8.3.9 `void gdcm::Anonymizer::RecurseDataSet (DataSet & ds)` [protected]

25.8.3.10 `bool gdcm::Anonymizer::Remove (Tag const & t)`

remove a tag (even a SQ can be removed) Return code is false when tag *t* cannot be found

25.8.3.11 `bool gdcm::Anonymizer::RemoveGroupLength ()`

Main function that loop over all elements and remove group length.

Examples:

[ClinicalTrialAnnotate.cxx](#).

25.8.3.12 `bool gdcm::Anonymizer::RemovePrivateTags ()`

Main function that loop over all elements and remove private tags.

Examples:

[ClinicalTrialAnnotate.cxx](#).

25.8.3.13 `bool gdcm::Anonymizer::RemoveRetired ()`

Main function that loop over all elements and remove retired element.

25.8.3.14 `bool gdcm::Anonymizer::Replace (Tag const & t, const char * value)`

Replace tag with another value, if tag is not found it will be created: WARNING: this function can only execute if tag is a VRASCI

Examples:

[ClinicalTrialAnnotate.cxx](#), [CreateJPIPDataSet.cxx](#), and [EncapsulateFileInRawData.cxx](#).

25.8.3.15 `bool gdcm::Anonymizer::Replace (Tag const & t, const char * value, VL const & vl)`

when the value contains \0, it is a good idea to specify the length. This function is required when dealing with VRBINARY tag

25.8.3.16 `void gdcm::Anonymizer::SetCryptographicMessageSyntax (CryptographicMessageSyntax * cms)`

Set/Get CMS key that will be used to encrypt the dataset within BasicApplicationLevelConfidentialityProfile.

25.8.3.17 `void gdcm::Anonymizer::SetFile (const File & f) [inline]`

Set/Get [File](#).

Examples:

[ClinicalTrialAnnotate.cxx](#), [CreateJPIPDataSet.cxx](#), and [EncapsulateFileInRawData.cxx](#).


The documentation for this class was generated from the following file:

- [gdcmAnonymizer.h](#)


25.9 `gdcm::AnyEvent` Class Reference

```
#include <gdcmEvent.h>
```

Inheritance diagram for gdcM::AnyEvent:



Collaboration diagram for gdcM::AnyEvent:



Additional Inherited Members

The documentation for this class was generated from the following file:

- [gdcmEvent.h](#)

25.10 gdcm::network::ApplicationContext Class Reference

[ApplicationContext Table 9-12 APPLICATION CONTEXT ITEM FIELDS](#) Looks like Application Context can only be 64 bytes at max (see Figure 9-1 / PS 3.8 - 2009)

```
#include <gdcmApplicationContext.h>
```

Public Member Functions

- [ApplicationContext](#) ()
- const char * [GetName](#) () const
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- void [SetName](#) (const char *name)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.10.1 Detailed Description

[ApplicationContext Table 9-12 APPLICATION CONTEXT ITEM FIELDS](#) Looks like Application Context can only be 64 bytes at max (see Figure 9-1 / PS 3.8 - 2009)

25.10.2 Constructor & Destructor Documentation

25.10.2.1 `gdcm::network::ApplicationContext::ApplicationContext ()`

25.10.3 Member Function Documentation

25.10.3.1 `const char* gdcm::network::ApplicationContext::GetName () const` `[inline]`

25.10.3.2 `void gdcm::network::ApplicationContext::Print (std::ostream & os) const`

25.10.3.3 `std::istream& gdcm::network::ApplicationContext::Read (std::istream & is)`

25.10.3.4 `void gdcm::network::ApplicationContext::SetName (const char * name)` `[inline]`

25.10.3.5 `size_t gdcm::network::ApplicationContext::Size () const`

25.10.3.6 `const std::ostream& gdcm::network::ApplicationContext::Write (std::ostream & os) const`

The documentation for this class was generated from the following file:


- [gdcmApplicationContext.h](#)

25.11 gdcm::ApplicationEntity Class Reference

[ApplicationEntity](#).

```
#include <gdcmApplicationEntity.h>
```

Collaboration diagram for gdcm::ApplicationEntity:



Public Member Functions

- bool [IsValid](#) () const
- void [Print](#) (std::ostream &os) const
- void [SetBlob](#) (const std::vector< char > &v)
- void [Squeeze](#) ()

Public Attributes

- std::string [Internal](#)

Static Public Attributes

- static const unsigned int [MaxLength](#) = 16
- static const unsigned int [MaxNumberOfComponents](#) = 1
- static const char [Padding](#) = ' '
- static const char [Separator](#) = ' '

25.11.1 Detailed Description

[ApplicationEntity](#).

- AE Application Entity
- A string of characters that identifies an Application Entity with leading and trailing spaces (20H) being non-significant. A value consisting solely of spaces shall not be used.
- Default Character Repertoire excluding character code 5CH (the BACKSLASH \ in ISO-IR 6), and control characters LF, FF, CR and ESC.
- 16 bytes maximum

25.11.2 Member Function Documentation

25.11.2.1 `bool gdcM::ApplicationEntity::IsValid () const` `[inline]`

25.11.2.2 `void gdcM::ApplicationEntity::Print (std::ostream & os) const` `[inline]`

25.11.2.3 `void gdcM::ApplicationEntity::SetBlob (const std::vector< char > & v)` `[inline]`

25.11.2.4 `void gdcM::ApplicationEntity::Squeeze ()` `[inline]`

25.11.3 Member Data Documentation

25.11.3.1 `std::string gdcM::ApplicationEntity::Internal`

25.11.3.2 `const unsigned int gdcM::ApplicationEntity::MaxLength = 16` `[static]`

25.11.3.3 `const unsigned int gdcM::ApplicationEntity::MaxNumberOfComponents = 1` `[static]`

25.11.3.4 `const char gdcM::ApplicationEntity::Padding = ''` `[static]`

25.11.3.5 `const char gdcM::ApplicationEntity::Separator = ''` `[static]`

The documentation for this class was generated from the following file:


- [gdcMApplicationEntity.h](#)

25.12 gdcM::network::AReleaseRPPDU Class Reference


[AReleaseRPPDU Table](#) 9-25 A-RELEASE-RP PDU fields.

```
#include <gdcMAReleaseRPPDU.h>
```

Inheritance diagram for gdcmm::network::AReleaseRPPDU:



Collaboration diagram for gdcmm::network::AReleaseRPPDU:



Public Member Functions

- [AReleaseRPPDU](#) ()
- bool [IsLastFragment](#) () const
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.12.1 Detailed Description

[AReleaseRPPDU](#) Table 9-25 A-RELEASE-RP PDU fields.

25.12.2 Constructor & Destructor Documentation

25.12.2.1 `gdcn::network::AReleaseRPPDU::AReleaseRPPDU ()`

25.12.3 Member Function Documentation

25.12.3.1 `bool gdcn::network::AReleaseRPPDU::IsLastFragment () const` `[inline],[virtual]`

Implements [gdcn::network::BasePDU](#).

25.12.3.2 `void gdcn::network::AReleaseRPPDU::Print (std::ostream & os) const` `[virtual]`

Implements [gdcn::network::BasePDU](#).

25.12.3.3 `std::istream& gdcn::network::AReleaseRPPDU::Read (std::istream & is)` `[virtual]`

Implements [gdcn::network::BasePDU](#).

25.12.3.4 `size_t gdcn::network::AReleaseRPPDU::Size () const` `[virtual]`

Implements [gdcn::network::BasePDU](#).

25.12.3.5 `const std::ostream& gdcn::network::AReleaseRPPDU::Write (std::ostream & os) const` `[virtual]`

Implements [gdcn::network::BasePDU](#).

The documentation for this class was generated from the following file:


- [gdcnAReleaseRPPDU.h](#)

25.13 gdcn::network::AReleaseRQPDU Class Reference


[AReleaseRQPDU](#) Table 9-24 A-RELEASE-RQ PDU FIELDS.

```
#include <gdcnAReleaseRQPDU.h>
```

Inheritance diagram for `gdcn::network::AReleaseRQPDU`:



Collaboration diagram for gdcmm::network::AReleaseRQPDU:



Public Member Functions

- [AReleaseRQPDU](#) ()
- bool [IsLastFragment](#) () const
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.13.1 Detailed Description

[AReleaseRQPDU](#) Table 9-24 A-RELEASE-RQ PDU FIELDS.

25.13.2 Constructor & Destructor Documentation

25.13.2.1 `gdcmm::network::AReleaseRQPDU::AReleaseRQPDU ()`

25.13.3 Member Function Documentation

25.13.3.1 `bool gdcmm::network::AReleaseRQPDU::IsLastFragment () const` `[inline], [virtual]`

Implements [gdcmm::network::BasePDU](#).

25.13.3.2 `void gdcmm::network::AReleaseRQPDU::Print (std::ostream & os) const` `[virtual]`

Implements [gdcmm::network::BasePDU](#).

25.13.3.3 `std::istream& gdcmm::network::AReleaseRQPDU::Read (std::istream & is)` `[virtual]`

Implements [gdcmm::network::BasePDU](#).

25.13.3.4 `size_t gdcmm::network::AReleaseRQPDU::Size () const` [virtual]

Implements [gdcmm::network::BasePDU](#).

25.13.3.5 `const std::ostream& gdcmm::network::AReleaseRQPDU::Write (std::ostream & os) const` [virtual]

Implements [gdcmm::network::BasePDU](#).

The documentation for this class was generated from the following file:

- [gdcmAReleaseRQPDU.h](#)

25.14 gdcmm::network::ARTIMTimer Class Reference

[ARTIMTimer](#) This file contains the code for the ARTIM timer.

```
#include <gdcmmARTIMTimer.h>
```

Public Member Functions

- [ARTIMTimer](#) ()
- double [GetElapsedTime](#) () const
- bool [GetHasExpired](#) () const
- double [GetTimeout](#) () const
- void [SetTimeout](#) (double inTimeout)
- void [Start](#) ()
- void [Stop](#) ()

25.14.1 Detailed Description

[ARTIMTimer](#) This file contains the code for the ARTIM timer.

Basically, the ARTIM timer will just get the wall time when it's started, and then can be queried for the current time, and then can be stopped (ie, the start time reset).

Because we're trying to do this without threading, we should be able to 'start' the ARTIM timer by this mechanism, and then when waiting for a particular response, tight loop that with sleep calls and determinations of when the ARTIM timer has reached its peak. As such, this isn't a strict 'timer' in the traditional sense of the word, but more of a time keeper.

There can be only one ARTIM timer per connection.

25.14.2 Constructor & Destructor Documentation

25.14.2.1 `gdcmm::network::ARTIMTimer::ARTIMTimer ()`

25.14.3 Member Function Documentation

25.14.3.1 `double gdcmm::network::ARTIMTimer::GetElapsedTime () const`

25.14.3.2 `bool gdcmm::network::ARTIMTimer::GetHasExpired () const`

25.14.3.3 double gdcm::network::ARTIMTimer::GetTimeout () const

25.14.3.4 void gdcm::network::ARTIMTimer::SetTimeout (double *inTimeout*)

25.14.3.5 void gdcm::network::ARTIMTimer::Start ()

25.14.3.6 void gdcm::network::ARTIMTimer::Stop ()

The documentation for this class was generated from the following file:

- [gdcmARTIMTimer.h](#)

25.15 gdcm::ASN1 Class Reference

Class for [ASN1](#).

```
#include <gdcmASN1.h>
```

Public Member Functions

- [ASN1](#) ()
- [~ASN1](#) ()

Static Public Member Functions

- static bool [ParseDump](#) (const char *array, size_t length)
- static bool [ParseDumpFile](#) (const char *filename)

Protected Member Functions

- int [TestPBKDF2](#) ()

25.15.1 Detailed Description

Class for [ASN1](#).

25.15.2 Constructor & Destructor Documentation

25.15.2.1 gdcm::ASN1::ASN1 ()

25.15.2.2 gdcm::ASN1::~~ASN1 ()

25.15.3 Member Function Documentation

25.15.3.1 static bool gdcm::ASN1::ParseDump (const char * *array*, size_t *length*) [static]

25.15.3.2 static bool gdcm::ASN1::ParseDumpFile (const char * *filename*) [static]

25.15.3.3 `int gdcm::ASN1::TestPBKDF2 ()` [protected]

The documentation for this class was generated from the following file:

- [gdcmASN1.h](#)

25.16 `gdcm::network::AsynchronousOperationsWindowSub` Class Reference

[AsynchronousOperationsWindowSub](#) PS 3.7 [Table D.3-7](#) ASYNCHRONOUS OPERATIONS WINDOW SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

```
#include <gdcmAsynchronousOperationsWindowSub.h>
```

Public Member Functions

- [AsynchronousOperationsWindowSub](#) ()
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.16.1 Detailed Description

[AsynchronousOperationsWindowSub](#) PS 3.7 [Table D.3-7](#) ASYNCHRONOUS OPERATIONS WINDOW SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

25.16.2 Constructor & Destructor Documentation

25.16.2.1 `gdcm::network::AsynchronousOperationsWindowSub::AsynchronousOperationsWindowSub ()`

25.16.3 Member Function Documentation

25.16.3.1 `void gdcm::network::AsynchronousOperationsWindowSub::Print (std::ostream & os) const`

25.16.3.2 `std::istream& gdcm::network::AsynchronousOperationsWindowSub::Read (std::istream & is)`

25.16.3.3 `size_t gdcm::network::AsynchronousOperationsWindowSub::Size () const`

25.16.3.4 `const std::ostream& gdcm::network::AsynchronousOperationsWindowSub::Write (std::ostream & os) const`

The documentation for this class was generated from the following file:


- [gdcmAsynchronousOperationsWindowSub.h](#)

25.17 `gdcm::Attribute< Group, Element, TVR, TVM >` Class Template Reference

[Attribute](#) class This class use template metaprograming tricks to let the user know when the template instantiation does not match the public dictionary.

```
#include <gdcmmAttribute.h>
```

Collaboration diagram for gdcmm::Attribute< Group, Element, TVR, TVM >:



Public Types

- enum { `VMType` = `VMToLength<TVM>::Length` }
- typedef `VRTToType< TVR >::Type` `ArrayType`

Public Member Functions

- `GDCM_STATIC_ASSERT` (((`VR::VRTType`) `TVR` & (`VR::VRTType`) (`TagToType< Group, Element >::VRTType`)))
- `GDCM_STATIC_ASSERT` (((`VM::VMType`) `TVM` & (`VM::VMType`) (`TagToType< Group, Element >::VMType`)))
- `GDCM_STATIC_ASSERT` (((((`VR::VRTType`) `TVR` & `VR::VR_VM1`) && ((`VM::VMType`) `TVM` == `VM::VM1`)) || !((`VR::VRTType`) `TVR` & `VR::VR_VM1`)))
- `DataElement` `GetAsDataElement` () const
- unsigned int `GetNumberOfValues` () const
- `ArrayType` & `GetValue` (unsigned int `idx`=0)
- `ArrayType` const & `GetValue` (unsigned int `idx`=0) const
- const `ArrayType` * `GetValues` () const
- bool `operator!=` (const `Attribute` &`att`) const
- bool `operator<` (const `Attribute` &`att`) const
- bool `operator==` (const `Attribute` &`att`) const
- `ArrayType` & `operator[]` (unsigned int `idx`)
- `ArrayType` const & `operator[]` (unsigned int `idx`) const
- void `Print` (std::ostream &`os`) const
- void `Set` (`DataSet` const &`ds`)
- void `SetFromDataElement` (`DataElement` const &`de`)
- void `SetFromDataSet` (`DataSet` const &`ds`)

- void [SetValue](#) ([ArrayType](#) v, unsigned int idx=0)
- void [SetValues](#) (const [ArrayType](#) *array, unsigned int numel=[VMType](#))

Static Public Member Functions

- static [VM GetDictVM](#) ()
- static [VR GetDictVR](#) ()
- static [Tag GetTag](#) ()
- static [VM GetVM](#) ()
- static [VR GetVR](#) ()

Public Attributes

- [ArrayType Internal](#) [[VMToLength](#)< TVM >::Length]

Protected Member Functions

- void [SetByteValue](#) (const [ByteValue](#) *bv)
- void [SetByteValueNoSwap](#) (const [ByteValue](#) *bv)

25.17.1 Detailed Description

```
template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType>class gdcmm::Attribute< Group, Element, TVR, TVM >
```

[Attribute](#) class This class use template metaprograming tricks to let the user know when the template instantiation does not match the public dictionary.

Typical example that compile is: `Attribute<0x0008,0x9007> a = {"ORIGINAL","PRIMARY","T1","NONE"};`

Examples that will NOT compile are:

```
Attribute<0x0018,0x1182, VR::IS, VM::VM1> fd1 = {}; // not enough parameters
Attribute<0x0018,0x1182, VR::IS, VM::VM2> fd2 = {0,1,2}; // too many initializers
Attribute<0x0018,0x1182, VR::IS, VM::VM3> fd3 = {0,1,2}; // VM3 is not valid
Attribute<0x0018,0x1182, VR::UL, VM::VM2> fd3 = {0,1}; // UL is not valid VR
```

Examples:

[CreateJIPIDataSet.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [gdcmmrtionplan.cxx](#), [gdcmmrtplan.cxx](#), [GenFakeldentifyFile.cxx](#), [GetSequenceUltrasound.cxx](#), [HelloWorld.cxx](#), [LargeVRDSExplicit.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [ReadAndPrintAttributes.cxx](#), [rle2img.cxx](#), [SortImage.cxx](#), [StreamImage-ReaderTest.cxx](#), and [VolumeSorter.cxx](#).

25.17.2 Member Typedef Documentation

25.17.2.1 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> typedef VRToType<TVR>::Type gdcmm::Attribute< Group, Element, TVR, TVM >::ArrayType`

25.17.3 Member Enumeration Documentation

25.17.3.1 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> anonymous enum`

Enumerator

VMType

25.17.4 Member Function Documentation

25.17.4.1 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> gdcm::Attribute< Group, Element, TVR, TVM >::GDCM_STATIC_ASSERT (((VR::VRType) TVR &(VR::VRType)(TagToType< Group, Element >::VRType)))`

25.17.4.2 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> gdcm::Attribute< Group, Element, TVR, TVM >::GDCM_STATIC_ASSERT (((VM::VMType) TVM &(VM::VMType)(TagToType< Group, Element >::VMType)))`

25.17.4.3 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> gdcm::Attribute< Group, Element, TVR, TVM >::GDCM_STATIC_ASSERT ((((VR::VRType) TVR &VR::VR_VM1)&&((VM::VMType) TVM==VM::VM1))||!((VR::VRType) TVR &VR::VR_VM1)))`

25.17.4.4 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> DataElement gdcm::Attribute< Group, Element, TVR, TVM >::GetAsDataElement () const [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetTag()`, `gdcm::DataElement::GetVR()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetVR()`, `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`, `gdcm::DataElement::SetByteValue()`, `gdcm::DataElement::SetVR()`, `gdcm::VR::SQ`, `gdcm::VR::UI`, and `gdcm::VR::VRASCII`.

25.17.4.5 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> static VM gdcm::Attribute< Group, Element, TVR, TVM >::GetDictVM () [inline], [static]`

25.17.4.6 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> static VR gdcm::Attribute< Group, Element, TVR, TVM >::GetDictVR () [inline], [static]`

25.17.4.7 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> unsigned int gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues () const [inline]`

Referenced by `gdcm::Attribute< Group, Element, TVR, TVM >::GetAsDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetAsDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetAsDataElement()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetValue()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetValue()`, `gdcm::Attribute< Group, Element, TVR, TVM >::operator!=()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::operator!=()`, `gdcm::Attribute< Group, Element, TVR, TVM >::operator<()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::operator<()`, `gdcm::Attribute< Group, Element, TVR, TVM >::operator==()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::operator==()`, `gdcm::Attribute< Group, Element, TVR, TVM >::Print()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::Print()`, `gdcm::Attribute< Group, Element, TVR, TVM >::SetByteValue()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetByteValue()`, `gdcm::Attribute< Group, Element, TVR, TVM >::SetByteValueNoSwap()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetByteValueNoSwap()`,

gdcmm::Attribute< Group, Element, TVR, TVM >::SetValue(), gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetValue(), gdcmm::Attribute< Group, Element, TVR, TVM >::SetValues(), and gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetValues().

25.17.4.8 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> static Tag gdcmm::Attribute< Group, Element, TVR, TVM >::GetTag () [inline], [static]`

Referenced by gdcmm::Attribute< Group, Element, TVR, TVM >::GetAsDataElement(), gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::GetAsDataElement(), gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::GetAsDataElement(), gdcmm::Attribute< Group, Element, TVR, TVM >::Print(), gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::Print(), gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::Print(), gdcmm::Attribute< Group, Element, TVR, TVM >::Set(), gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::Set(), gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::Set(), gdcmm::Attribute< Group, Element, TVR, TVM >::SetFromDataElement(), gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataElement(), gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataElement(), gdcmm::Attribute< Group, Element, TVR, TVM >::SetFromDataSet(), gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataSet(), and gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataSet().

25.17.4.9 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> ArrayType& gdcmm::Attribute< Group, Element, TVR, TVM >::GetValue (unsigned int idx = 0) [inline]`

References gdcmm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues(), and gdcmm::Attribute< Group, Element, TVR, TVM >::Internal.

Referenced by gdcmm::Attribute< Group, Element, TVR, TVM >::operator[](), and gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::operator[]().

25.17.4.10 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> ArrayType const& gdcmm::Attribute< Group, Element, TVR, TVM >::GetValue (unsigned int idx = 0) const [inline]`

References gdcmm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues(), and gdcmm::Attribute< Group, Element, TVR, TVM >::Internal.

25.17.4.11 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> const ArrayType* gdcmm::Attribute< Group, Element, TVR, TVM >::GetValues () const [inline]`

References gdcmm::Attribute< Group, Element, TVR, TVM >::Internal.

Referenced by gdcmm::Attribute< Group, Element, TVR, TVM >::operator!(), gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::operator!(), gdcmm::Attribute< Group, Element, TVR, TVM >::operator<(), gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::operator<(), gdcmm::Attribute< Group, Element, TVR, TVM >::operator==(), and gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::operator==().


```
25.17.4.12 template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM =
TagToType<Group, Element>::VMType> static VM gdcm::Attribute< Group, Element, TVR, TVM >::GetVM ( )
[inline], [static]
```

Referenced by gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetDictVM(), and gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::Print().

```
25.17.4.13 template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM =
TagToType<Group, Element>::VMType> static VR gdcm::Attribute< Group, Element, TVR, TVM >::GetVR ( )
[inline], [static]
```

Referenced by gdcm::Attribute< Group, Element, TVR, TVM >::GetAsDataElement(), gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetAsDataElement(), gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetAsDataElement(), gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::Print(), gdcm::Attribute< Group, Element, TVR, TVM >::SetFromDataElement(), gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataElement(), and gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataElement().

```
25.17.4.14 template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM =
TagToType<Group, Element>::VMType> bool gdcm::Attribute< Group, Element, TVR, TVM >::operator!= ( const
Attribute< Group, Element, TVR, TVM > & att ) const [inline]
```

References gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues(), gdcm::Attribute< Group, Element, TVR, TVM >::GetValues(), and gdcm::Attribute< Group, Element, TVR, TVM >::Internal.

```
25.17.4.15 template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM =
TagToType<Group, Element>::VMType> bool gdcm::Attribute< Group, Element, TVR, TVM >::operator< ( const
Attribute< Group, Element, TVR, TVM > & att ) const [inline]
```

References gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues(), gdcm::Attribute< Group, Element, TVR, TVM >::GetValues(), and gdcm::Attribute< Group, Element, TVR, TVM >::Internal.

```
25.17.4.16 template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM =
TagToType<Group, Element>::VMType> bool gdcm::Attribute< Group, Element, TVR, TVM >::operator==( const
Attribute< Group, Element, TVR, TVM > & att ) const [inline]
```

References gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues(), gdcm::Attribute< Group, Element, TVR, TVM >::GetValues(), and gdcm::Attribute< Group, Element, TVR, TVM >::Internal.

```
25.17.4.17 template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM =
TagToType<Group, Element>::VMType> ArrayType& gdcm::Attribute< Group, Element, TVR, TVM >::operator[]
( unsigned int idx ) [inline]
```

References gdcm::Attribute< Group, Element, TVR, TVM >::GetValue().

```
25.17.4.18 template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM =
TagToType<Group, Element>::VMType> ArrayType const& gdcm::Attribute< Group, Element, TVR, TVM
>::operator[] ( unsigned int idx ) const [inline]
```

References gdcm::Attribute< Group, Element, TVR, TVM >::GetValue().

25.17.4.19 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> void gdcM::Attribute< Group, Element, TVR, TVM >::Print (std::ostream & os) const [inline]`

References `gdcM::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcM::Attribute< Group, Element, TVR, TVM >::GetTag()`, and `gdcM::Attribute< Group, Element, TVR, TVM >::Internal`.

25.17.4.20 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> void gdcM::Attribute< Group, Element, TVR, TVM >::Set (DataSet const & ds) [inline]`

References `gdcM::DataSet::GetDataElement()`, `gdcM::Attribute< Group, Element, TVR, TVM >::GetTag()`, and `gdcM::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`.

25.17.4.21 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> void gdcM::Attribute< Group, Element, TVR, TVM >::SetByteValue (const ByteValue * bv) [inline], [protected]`

References `gdcM::ByteValue::GetLength()`, `gdcM::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcM::ByteValue::GetPointer()`, and `gdcM::Attribute< Group, Element, TVR, TVM >::Internal`.

Referenced by `gdcM::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`, `gdcM::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataElement()`, and `gdcM::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataElement()`.

25.17.4.22 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> void gdcM::Attribute< Group, Element, TVR, TVM >::SetByteValueNoSwap (const ByteValue * bv) [inline], [protected]`

References `gdcM::ByteValue::GetLength()`, `gdcM::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcM::ByteValue::GetPointer()`, and `gdcM::Attribute< Group, Element, TVR, TVM >::Internal`.

Referenced by `gdcM::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`, and `gdcM::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataElement()`.

25.17.4.23 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> void gdcM::Attribute< Group, Element, TVR, TVM >::SetFromDataElement (DataElement const & de) [inline]`

References `gdcM::DataElement::GetByteValue()`, `gdcM::Tag::GetGroup()`, `gdcM::DataElement::GetTag()`, `gdcM::Attribute< Group, Element, TVR, TVM >::GetTag()`, `gdcM::DataElement::GetVR()`, `gdcM::Attribute< Group, Element, TVR, TVM >::GetVR()`, `gdcM::VR::INVALID`, `gdcM::DataElement::IsEmpty()`, `gdcM::Attribute< Group, Element, TVR, TVM >::SetByteValue()`, `gdcM::Attribute< Group, Element, TVR, TVM >::SetByteValueNoSwap()`, and `gdcM::VR::UN`.

Referenced by `gdcM::Attribute< Group, Element, TVR, TVM >::Set()`, `gdcM::Attribute< Group, Element, TVR, VM::VM1 >::Set()`, `gdcM::Attribute< Group, Element, TVR, VM::VM1_n >::Set()`, `gdcM::Attribute< Group, Element, TVR, TVM >::SetFromDataSet()`, `gdcM::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataSet()`, and `gdcM::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataSet()`.

25.17.4.24 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> void gdcmm::Attribute< Group, Element, TVR, TVM >::SetFromDataSet (DataSet const & ds) [inline]`

References `gdcmm::DataSet::FindDataElement()`, `gdcmm::DataSet::GetDataElement()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::GetTag()`, `gdcmm::DataElement::IsEmpty()`, and `gdcmm::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`.

25.17.4.25 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> void gdcmm::Attribute< Group, Element, TVR, TVM >::SetValue (ArrayType v, unsigned int idx = 0) [inline]`

References `gdcmm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, and `gdcmm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.17.4.26 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> void gdcmm::Attribute< Group, Element, TVR, TVM >::SetValues (const ArrayType * array, unsigned int numel = VMType) [inline]`

Examples:

[LargeVRDSExplicit.cxx](#).

References `gdcmm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, and `gdcmm::Attribute< Group, Element, TVR, TVM >::Internal`.

Referenced by `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetByteValue()`, and `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetNumberOfValues()`.

25.17.5 Member Data Documentation

25.17.5.1 `template<uint16_t Group, uint16_t Element, int TVR = TagToType<Group, Element>::VRType, int TVM = TagToType<Group, Element>::VMType> ArrayType gdcmm::Attribute< Group, Element, TVR, TVM >::Internal[VMToLength< TVM >::Length]`

Referenced by `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::Attribute()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::GetAsDataElement()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::GetAsDataElement()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::GetAsDataElement()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::GetValue()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::GetValue()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::GetValue()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::GetValues()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::GetValues()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::GetValues()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::operator!=()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::operator!=()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::operator<()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::operator<()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::operator==()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::operator==()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::Print()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::Print()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::Print()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::SetByteValue()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::SetByteValue()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::SetByteValueNoSwap()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::SetByteValueNoSwap()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::SetValue()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::SetValue()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetValue()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::SetValues()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetValues()`, and `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::~~Attribute()`.


The documentation for this class was generated from the following file:

- [gdcmAttribute.h](#)

25.18 gdcm::Attribute< Group, Element, TVR, VM::VM1 > Class Template Reference

```
#include <gdcmAttribute.h>
```

Collaboration diagram for gdcm::Attribute< Group, Element, TVR, VM::VM1 >:



Public Types

- enum { `VMType` = `VMToLength<VM::VM1>::Length` }
- typedef `VRTToType< TVR >::Type` `ArrayType`

Public Member Functions

- `GDCM_STATIC_ASSERT (VMToLength< VM::VM1 >::Length==1)`
- `GDCM_STATIC_ASSERT (((VR::VRTType) TVR &(VR::VRTType)(TagToType< Group, Element >::VRTType)))`
- `GDCM_STATIC_ASSERT (((VM::VMType) VM::VM1 &(VM::VMType)(TagToType< Group, Element >::VMType)))`
- `GDCM_STATIC_ASSERT (((((VR::VRTType) TVR &VR::VR_VM1)&&((VM::VMType) VM::VM1==VM::VM1))||!((VR::VRTType) TVR &VR::VR_VM1))))`
- `DataElement GetAsDataElement () const`
- `unsigned int GetNumberOfValues () const`
- `ArrayType & GetValue ()`
- `ArrayType const & GetValue () const`

- const [ArrayType](#) * [GetValues](#) () const
- bool [operator!=](#) (const [Attribute](#) &att) const
- bool [operator<](#) (const [Attribute](#) &att) const
- bool [operator==](#) (const [Attribute](#) &att) const
- void [Print](#) (std::ostream &os) const
- void [Set](#) ([DataSet](#) const &ds)
- void [SetFromDataElement](#) ([DataElement](#) const &de)
- void [SetFromDataSet](#) ([DataSet](#) const &ds)
- void [SetValue](#) ([ArrayType](#) v)

Static Public Member Functions

- static [VM](#) [GetDictVM](#) ()
- static [VR](#) [GetDictVR](#) ()
- static [Tag](#) [GetTag](#) ()
- static [VM](#) [GetVM](#) ()
- static [VR](#) [GetVR](#) ()

Public Attributes

- [ArrayType](#) [Internal](#)

Protected Member Functions

- void [SetByteValue](#) (const [ByteValue](#) *bv)
- void [SetByteValueNoSwap](#) (const [ByteValue](#) *bv)

25.18.1 Member Typedef Documentation

25.18.1.1 `template<uint16_t Group, uint16_t Element, int TVR> typedef VRToType<TVR>::Type gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::ArrayType`

25.18.2 Member Enumeration Documentation

25.18.2.1 `template<uint16_t Group, uint16_t Element, int TVR> anonymous enum`

Enumerator

VMType

25.18.3 Member Function Documentation

25.18.3.1 `template<uint16_t Group, uint16_t Element, int TVR> gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::GDCM_STATIC_ASSERT (VMToLength< VM::VM1 >::Length == 1)`

25.18.3.2 `template<uint16_t Group, uint16_t Element, int TVR> gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::GDCM_STATIC_ASSERT (((VR::VRType) TVR &(VR::VRType)(TagToType< Group, Element >::VRType)))`

25.18.3.3 `template<uint16_t Group, uint16_t Element, int TVR> gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GDCM_STATIC_ASSERT (((VM::VMType) VM::VM1 &(VM::VMType)(TagToType< Group, Element >::VMType)))`

25.18.3.4 `template<uint16_t Group, uint16_t Element, int TVR> gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GDCM_STATIC_ASSERT ((((VR::VRType) TVR &VR::VR_VM1)&&((VM::VMType) VM::VM1==VM::VM1))||!((VR::VRType) TVR &VR::VR_VM1)))`

25.18.3.5 `template<uint16_t Group, uint16_t Element, int TVR> DataElement gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetAsDataElement () const [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetTag()`, `gdcm::DataElement::GetVR()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetVR()`, `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`, `gdcm::DataElement::SetByteValue()`, `gdcm::DataElement::SetVR()`, `gdcm::VR::SQ`, `gdcm::VR::UI`, and `gdcm::VR::VRASCII`.

25.18.3.6 `template<uint16_t Group, uint16_t Element, int TVR> static VM gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetDictVM () [inline],[static]`

25.18.3.7 `template<uint16_t Group, uint16_t Element, int TVR> static VR gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetDictVR () [inline],[static]`

25.18.3.8 `template<uint16_t Group, uint16_t Element, int TVR> unsigned int gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetNumberOfValues () const [inline]`

25.18.3.9 `template<uint16_t Group, uint16_t Element, int TVR> static Tag gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetTag () [inline],[static]`

25.18.3.10 `template<uint16_t Group, uint16_t Element, int TVR> ArrayType& gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetValue () [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.18.3.11 `template<uint16_t Group, uint16_t Element, int TVR> ArrayType const& gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetValue () const [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.18.3.12 `template<uint16_t Group, uint16_t Element, int TVR> const ArrayType* gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetValues () const [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.18.3.13 `template<uint16_t Group, uint16_t Element, int TVR> static VM gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetVM () [inline],[static]`

References `gdcm::VM::VM1`.

25.18.3.14 `template<uint16_t Group, uint16_t Element, int TVR> static VR gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetVR () [inline], [static]`

25.18.3.15 `template<uint16_t Group, uint16_t Element, int TVR> bool gdcm::Attribute< Group, Element, TVR, VM::VM1 >::operator!= (const Attribute< Group, Element, TVR, VM::VM1 > & att) const [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetValues()`, and `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.18.3.16 `template<uint16_t Group, uint16_t Element, int TVR> bool gdcm::Attribute< Group, Element, TVR, VM::VM1 >::operator< (const Attribute< Group, Element, TVR, VM::VM1 > & att) const [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetValues()`, and `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.18.3.17 `template<uint16_t Group, uint16_t Element, int TVR> bool gdcm::Attribute< Group, Element, TVR, VM::VM1 >::operator== (const Attribute< Group, Element, TVR, VM::VM1 > & att) const [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetValues()`, and `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.18.3.18 `template<uint16_t Group, uint16_t Element, int TVR> void gdcm::Attribute< Group, Element, TVR, VM::VM1 >::Print (std::ostream & os) const [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::GetTag()`, and `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.18.3.19 `template<uint16_t Group, uint16_t Element, int TVR> void gdcm::Attribute< Group, Element, TVR, VM::VM1 >::Set (DataSet const & ds) [inline]`

References `gdcm::DataSet::GetDataElement()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetTag()`, and `gdcm::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`.

25.18.3.20 `template<uint16_t Group, uint16_t Element, int TVR> void gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetByteValue (const ByteValue * bv) [inline], [protected]`

References `gdcm::ByteValue::GetLength()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcm::ByteValue::GetPointer()`, and `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.18.3.21 `template<uint16_t Group, uint16_t Element, int TVR> void gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetByteValueNoSwap (const ByteValue * bv) [inline], [protected]`

References `gdcm::ByteValue::GetLength()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcm::ByteValue::GetPointer()`, and `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.18.3.22 `template<uint16_t Group, uint16_t Element, int TVR> void gdcM::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataElement (DataElement const & de) [inline]`

References `gdcM::DataElement::GetByteValue()`, `gdcM::Tag::GetGroup()`, `gdcM::DataElement::GetTag()`, `gdcM::Attribute< Group, Element, TVR, TVM >::GetTag()`, `gdcM::DataElement::GetVR()`, `gdcM::Attribute< Group, Element, TVR, TVM >::GetVR()`, `gdcM::VR::INVALID`, `gdcM::DataElement::IsEmpty()`, `gdcM::Attribute< Group, Element, TVR, TVM >::SetByteValue()`, `gdcM::Attribute< Group, Element, TVR, TVM >::SetByteValueNoSwap()`, and `gdcM::VR::UN`.

25.18.3.23 `template<uint16_t Group, uint16_t Element, int TVR> void gdcM::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataSet (DataSet const & ds) [inline]`

References `gdcM::DataSet::FindDataElement()`, `gdcM::DataSet::GetDataElement()`, `gdcM::Attribute< Group, Element, TVR, TVM >::GetTag()`, `gdcM::DataElement::IsEmpty()`, and `gdcM::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`.

25.18.3.24 `template<uint16_t Group, uint16_t Element, int TVR> void gdcM::Attribute< Group, Element, TVR, VM::VM1 >::SetValue (ArrayType v) [inline]`

References `gdcM::Attribute< Group, Element, TVR, TVM >::Internal`.

25.18.4 Member Data Documentation

25.18.4.1 `template<uint16_t Group, uint16_t Element, int TVR> ArrayType gdcM::Attribute< Group, Element, TVR, VM::VM1 >::Internal`


The documentation for this class was generated from the following file:

- [gdcMAttribute.h](#)


25.19 gdcM::Attribute< Group, Element, TVR, VM::VM1_3 > Class Template Reference

```
#include <gdcMAttribute.h>
```


Inheritance diagram for gdcm::Attribute< Group, Element, TVR, VM::VM1_3 >:



Collaboration diagram for gdcm::Attribute< Group, Element, TVR, VM::VM1_3 >:



Public Member Functions

- [VM GetVM](#) () const

Additional Inherited Members

25.19.1 Member Function Documentation

25.19.1.1 `template<uint16_t Group, uint16_t Element, int TVR> VM gdcm::Attribute< Group, Element, TVR, VM::VM1_3 >::GetVM () const [inline]`

References `gdcm::VM::VM1_3`.


The documentation for this class was generated from the following file:

- [gdcMAttribute.h](#)


25.20 gdcM::Attribute< Group, Element, TVR, VM::VM1_8 > Class Template Reference

```
#include <gdcMAttribute.h>
```

Inheritance diagram for gdcM::Attribute< Group, Element, TVR, VM::VM1_8 >:



Collaboration diagram for gdcM::Attribute< Group, Element, TVR, VM::VM1_8 >:



Public Member Functions

- [VM GetVM](#) () const

Additional Inherited Members

25.20.1 Member Function Documentation

25.20.1.1 `template<uint16_t Group, uint16_t Element, int TVR> VM gdcm::Attribute< Group, Element, TVR, VM::VM1_8 >::GetVM() const [inline]`

References `gdcm::VM::VM1_8`.


The documentation for this class was generated from the following file:

- [gdcmAttribute.h](#)

25.21 gdcm::Attribute< Group, Element, TVR, VM::VM1_n > Class Template Reference

```
#include <gdcmAttribute.h>
```

Inheritance diagram for `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >`:



Public Types

- typedef `VRToType< TVR >::Type ArrayType`

Public Member Functions

- `Attribute()`
- `~Attribute()`
- `GDCM_STATIC_ASSERT(((VR::VRType) TVR & (VR::VRType)(TagToType< Group, Element >::VRType)))`
- `GDCM_STATIC_ASSERT((VM::VM1_n & (VM::VMType)(TagToType< Group, Element >::VMType)))`
- `GDCM_STATIC_ASSERT((((VR::VRType) TVR & VR::VR_VM1) && ((VM::VMType) TagToType< Group, Element >::VMType == VM::VM1)) || ((VR::VRType) TVR & VR::VR_VM1))`
- `DataElement GetAsDataElement() const`
- `unsigned int GetNumberOfValues() const`
- `ArrayType & GetValue(unsigned int idx=0)`
- `ArrayType const & GetValue(unsigned int idx=0) const`
- `const ArrayType * GetValues() const`
- `ArrayType & operator[] (unsigned int idx)`
- `ArrayType const & operator[] (unsigned int idx) const`

- void [Print](#) (std::ostream &os) const
- void [Set](#) ([DataSet](#) const &ds)
- void [SetFromDataElement](#) ([DataElement](#) const &de)
- void [SetFromDataSet](#) ([DataSet](#) const &ds)
- void [SetNumberOfValues](#) (unsigned int numel)
- void [SetValue](#) (unsigned int idx, [ArrayType](#) v)
- void [SetValue](#) ([ArrayType](#) v)
- void [SetValues](#) (const [ArrayType](#) *array, unsigned int numel, bool own=false)

Static Public Member Functions

- static [VM GetDictVM](#) ()
- static [VR GetDictVR](#) ()
- static [Tag GetTag](#) ()
- static [VM GetVM](#) ()
- static [VR GetVR](#) ()

Protected Member Functions

- void [SetByteValue](#) (const [ByteValue](#) *bv)

25.21.1 Member Typedef Documentation

25.21.1.1 `template<uint16_t Group, uint16_t Element, int TVR> typedef VRToType<TVR>::Type gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::ArrayType`

25.21.2 Constructor & Destructor Documentation

25.21.2.1 `template<uint16_t Group, uint16_t Element, int TVR> gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::Attribute () [inline],[explicit]`

References `gdcmm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.21.2.2 `template<uint16_t Group, uint16_t Element, int TVR> gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::~~Attribute () [inline]`

References `gdcmm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.21.3 Member Function Documentation

25.21.3.1 `template<uint16_t Group, uint16_t Element, int TVR> gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::GDCM_STATIC_ASSERT (((VR::VRType) TVR &(VR::VRType)(TagToType< Group, Element >::VRType)))`

25.21.3.2 `template<uint16_t Group, uint16_t Element, int TVR> gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::GDCM_STATIC_ASSERT ((VM::VM1_n &(VM::VMType)(TagToType< Group, Element >::VMType)))`

25.21.3.3 `template<uint16_t Group, uint16_t Element, int TVR> gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GDCM_STATIC_ASSERT ((((VR::VRType) TVR &VR::VR_VM1)&&((VM::VMType) TagToType< Group, Element >::VMType==VM::VM1))||!((VR::VRType) TVR &VR::VR_VM1)))`

25.21.3.4 `template<uint16_t Group, uint16_t Element, int TVR> DataElement gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetAsDataElement () const [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetTag()`, `gdcm::DataElement::GetVR()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetVR()`, `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`, `gdcm::DataElement::SetByteValue()`, `gdcm::DataElement::SetVR()`, `gdcm::VR::SQ`, `gdcm::VR::UI`, and `gdcm::VR::VRASCII`.

25.21.3.5 `template<uint16_t Group, uint16_t Element, int TVR> static VM gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetDictVM () [inline], [static]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::GetVM()`.

25.21.3.6 `template<uint16_t Group, uint16_t Element, int TVR> static VR gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetDictVR () [inline], [static]`

25.21.3.7 `template<uint16_t Group, uint16_t Element, int TVR> unsigned int gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetNumberOfValues () const [inline]`

25.21.3.8 `template<uint16_t Group, uint16_t Element, int TVR> static Tag gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetTag () [inline], [static]`

25.21.3.9 `template<uint16_t Group, uint16_t Element, int TVR> ArrayType& gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetValue (unsigned int idx = 0) [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, and `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.21.3.10 `template<uint16_t Group, uint16_t Element, int TVR> ArrayType const& gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetValue (unsigned int idx = 0) const [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, and `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.21.3.11 `template<uint16_t Group, uint16_t Element, int TVR> const ArrayType* gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetValues () const [inline]`

References `gdcm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.21.3.12 `template<uint16_t Group, uint16_t Element, int TVR> static VM gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetVM () [inline], [static]`

References `gdcm::VM::VM1_n`.

25.21.3.13 `template<uint16_t Group, uint16_t Element, int TVR> static VR gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::GetVR () [inline], [static]`

25.21.3.14 `template<uint16_t Group, uint16_t Element, int TVR> ArrayType& gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::operator[] (unsigned int idx) [inline]`

References `gdcmm::Attribute< Group, Element, TVR, TVM >::GetValue()`.

25.21.3.15 `template<uint16_t Group, uint16_t Element, int TVR> ArrayType const& gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::operator[] (unsigned int idx) const [inline]`

References `gdcmm::Attribute< Group, Element, TVR, TVM >::GetValue()`.

25.21.3.16 `template<uint16_t Group, uint16_t Element, int TVR> void gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::Print (std::ostream & os) const [inline]`

References `gdcmm::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::GetTag()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::GetVM()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::GetVR()`, and `gdcmm::Attribute< Group, Element, TVR, TVM >::Internal`.

25.21.3.17 `template<uint16_t Group, uint16_t Element, int TVR> void gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::Set (DataSet const & ds) [inline]`

References `gdcmm::DataSet::GetDataElement()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::GetTag()`, and `gdcmm::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`.

25.21.3.18 `template<uint16_t Group, uint16_t Element, int TVR> void gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetByteValue (const ByteValue * bv) [inline], [protected]`

References `gdcmm::ByteValue::GetLength()`, `gdcmm::ByteValue::GetPointer()`, and `gdcmm::Attribute< Group, Element, TVR, TVM >::SetValues()`.

25.21.3.19 `template<uint16_t Group, uint16_t Element, int TVR> void gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataElement (DataElement const & de) [inline]`

References `gdcmm::DataElement::GetByteValue()`, `gdcmm::Tag::GetGroup()`, `gdcmm::DataElement::GetTag()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::GetTag()`, `gdcmm::DataElement::GetVR()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::GetVR()`, `gdcmm::DataElement::IsEmpty()`, and `gdcmm::Attribute< Group, Element, TVR, TVM >::SetByteValue()`.

25.21.3.20 `template<uint16_t Group, uint16_t Element, int TVR> void gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataSet (DataSet const & ds) [inline]`

References `gdcmm::DataSet::FindDataElement()`, `gdcmm::DataSet::GetDataElement()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::GetTag()`, `gdcmm::DataElement::IsEmpty()`, and `gdcmm::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`.

25.21.3.21 `template<uint16_t Group, uint16_t Element, int TVR> void gdcM::Attribute< Group, Element, TVR, VM::VM1_n >::SetNumberOfValues (unsigned int numel) [inline]`

References `gdcM::Attribute< Group, Element, TVR, TVM >::SetValues()`.

25.21.3.22 `template<uint16_t Group, uint16_t Element, int TVR> void gdcM::Attribute< Group, Element, TVR, VM::VM1_n >::SetValue (unsigned int idx, ArrayType v) [inline]`

References `gdcM::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, and `gdcM::Attribute< Group, Element, TVR, TVM >::Internal`.

25.21.3.23 `template<uint16_t Group, uint16_t Element, int TVR> void gdcM::Attribute< Group, Element, TVR, VM::VM1_n >::SetValue (ArrayType v) [inline]`

References `SetValue()`.

Referenced by `SetValue()`.

25.21.3.24 `template<uint16_t Group, uint16_t Element, int TVR> void gdcM::Attribute< Group, Element, TVR, VM::VM1_n >::SetValues (const ArrayType * array, unsigned int numel, bool own = false) [inline]`

References `gdcM::Attribute< Group, Element, TVR, TVM >::GetNumberOfValues()`, and `gdcM::Attribute< Group, Element, TVR, TVM >::Internal`.


The documentation for this class was generated from the following file:

- [gdcMAttribute.h](#)


25.22 `gdcM::Attribute< Group, Element, TVR, VM::VM2_2n >` Class Template Reference

```
#include <gdcMAttribute.h>
```

Inheritance diagram for `gdcM::Attribute< Group, Element, TVR, VM::VM2_2n >`:



Collaboration diagram for `gdcM::Attribute< Group, Element, TVR, VM::VM2_2n >`:



Static Public Member Functions

- static [VM](#) [GetVM](#) ()

Additional Inherited Members

25.22.1 Member Function Documentation

25.22.1.1 `template<uint16_t Group, uint16_t Element, int TVR> static VM gdcM::Attribute< Group, Element, TVR, VM::VM2_2n >::GetVM() [inline], [static]`

References gdcM::VM::VM2_2n.


The documentation for this class was generated from the following file:

- [gdcMAttribute.h](#)


25.23 gdcM::Attribute< Group, Element, TVR, VM::VM2_n > Class Template Reference

```
#include <gdcMAttribute.h>
```

Inheritance diagram for gdcM::Attribute< Group, Element, TVR, VM::VM2_n >:



Collaboration diagram for `gdcm::Attribute< Group, Element, TVR, VM::VM2_n >`:



Public Member Functions

- [VM GetVM](#) () const

Additional Inherited Members

25.23.1 Member Function Documentation

25.23.1.1 `template<uint16_t Group, uint16_t Element, int TVR> VM gdcm::Attribute< Group, Element, TVR, VM::VM2_n >::GetVM () const` [inline]

References `gdcm::VM::VM2_n`.


The documentation for this class was generated from the following file:

- [gdcmAttribute.h](#)


25.24 `gdcm::Attribute< Group, Element, TVR, VM::VM3_3n >` Class Template Reference

```
#include <gdcmAttribute.h>
```

Inheritance diagram for gdcm::Attribute< Group, Element, TVR, VM::VM3_3n >:



Collaboration diagram for gdcm::Attribute< Group, Element, TVR, VM::VM3_3n >:



Static Public Member Functions

- static [VM GetVM](#) ()

Additional Inherited Members

25.24.1 Member Function Documentation

25.24.1.1 `template<uint16_t Group, uint16_t Element, int TVR> static VM gdcM::Attribute< Group, Element, TVR, VM::VM3_3n >::GetVM() [inline], [static]`

References `gdcM::VM::VM3_3n`.


The documentation for this class was generated from the following file:

- [gdcMAttribute.h](#)


25.25 gdcM::Attribute< Group, Element, TVR, VM::VM3_n > Class Template Reference

```
#include <gdcMAttribute.h>
```

Inheritance diagram for `gdcM::Attribute< Group, Element, TVR, VM::VM3_n >`:



Collaboration diagram for gdcm::Attribute< Group, Element, TVR, VM::VM3_n >:



Static Public Member Functions

- static [VM GetVM](#) ()

Additional Inherited Members

25.25.1 Member Function Documentation

25.25.1.1 `template<uint16_t Group, uint16_t Element, int TVR> static VM gdcm::Attribute< Group, Element, TVR, VM::VM3_n >::GetVM () [inline],[static]`

References `gdcm::VM::VM3_n`.

The documentation for this class was generated from the following file:


- [gdcmAttribute.h](#)

25.26 gdcm::AudioCodec Class Reference


[AudioCodec](#).

```
#include <gdcmAudioCodec.h>
```

Inheritance diagram for `gdcm::AudioCodec`:



Collaboration diagram for `gdcm::AudioCodec`:



Public Member Functions

- [AudioCodec](#) ()
- [~AudioCodec](#) ()
- `bool CanCode (TransferSyntax const &) const`
Return whether this coder support this transfer syntax (can code it)
- `bool CanDecode (TransferSyntax const &) const`
Return whether this decoder support this transfer syntax (can decode it)

- bool [Decode](#) ([DataElement](#) const &is, [DataElement](#) &os)
Decode.

Additional Inherited Members

25.26.1 Detailed Description

[AudioCodec](#).

25.26.2 Constructor & Destructor Documentation

25.26.2.1 `gdcm::AudioCodec::AudioCodec ()`

25.26.2.2 `gdcm::AudioCodec::~~AudioCodec ()`

25.26.3 Member Function Documentation

25.26.3.1 `bool gdcm::AudioCodec::CanCode (TransferSyntax const &) const` `[inline],[virtual]`

Return whether this coder support this transfer syntax (can code it)

Implements [gdcm::Coder](#).

25.26.3.2 `bool gdcm::AudioCodec::CanDecode (TransferSyntax const &) const` `[inline],[virtual]`

Return whether this decoder support this transfer syntax (can decode it)

Implements [gdcm::Decoder](#).

25.26.3.3 `bool gdcm::AudioCodec::Decode (DataElement const & , DataElement &)` `[virtual]`

Decode.

Reimplemented from [gdcm::Decoder](#).

The documentation for this class was generated from the following file:

- [gdcmAudioCodec.h](#)

25.27 gdcm::Base64 Class Reference

Class for [Base64](#).

```
#include <gdcmBase64.h>
```

Public Member Functions

- [Base64](#) ()
- [~Base64](#) ()

Static Public Member Functions

- static int [Decode](#) (char *dst, int dlen, const char *src, int slen)
Decode a base64-formatted buffer.
- static int [Encode](#) (char *dst, int dlen, const char *src, int slen)
Encode a buffer into base64 format.
- static int [GetDecodeLength](#) (const char *src, int slen)
- static int [GetEncodeLength](#) (const char *src, int slen)

25.27.1 Detailed Description

Class for [Base64](#).

25.27.2 Constructor & Destructor Documentation

25.27.2.1 `gdcm::Base64::Base64 ()`

25.27.2.2 `gdcm::Base64::~~Base64 ()`

25.27.3 Member Function Documentation

25.27.3.1 `static int gdcm::Base64::Decode (char * dst, int dlen, const char * src, int slen)` `[static]`

Decode a base64-formatted buffer.

Parameters

<i>dst</i>	destination buffer
<i>dlen</i>	size of the buffer
<i>src</i>	source buffer
<i>slen</i>	amount of data to be decoded

Returns

0 if successful

25.27.3.2 `static int gdcm::Base64::Encode (char * dst, int dlen, const char * src, int slen)` `[static]`

Encode a buffer into base64 format.

Parameters

<i>dst</i>	destination buffer
<i>dlen</i>	size of the buffer
<i>src</i>	source buffer
<i>slen</i>	amount of data to be encoded

Returns

0 if successful

25.27.3.3 `static int gdcm::Base64::GetDecodeLength (const char * src, int slen) [static]`

Call this function with *dlen = 0 to obtain the required buffer size in *dlen

25.27.3.4 `static int gdcm::Base64::GetEncodeLength (const char * src, int slen) [static]`

Call this function with dlen = 0 to obtain the required buffer size in dlen

The documentation for this class was generated from the following file:


- [gdcmBase64.h](#)

25.28 gdcm::network::BaseCompositeMessage Class Reference

[BaseCompositeMessage](#) The Composite events described in section 3.7-2009 of the DICOM standard all use their own messages. These messages are constructed using Presentation Data Values, from section 3.8-2009 of the standard, and then fill in appropriate values in their datasets.

```
#include <gdcmBaseCompositeMessage.h>
```

Inheritance diagram for `gdcm::network::BaseCompositeMessage`:



Public Member Functions

- virtual std::vector
< [PresentationDataValue](#) > [ConstructPDV](#) (const [ULConnection](#) &inConnection, const [BaseRootQuery](#) *inRootQuery)=0

25.28.1 Detailed Description

[BaseCompositeMessage](#) The Composite events described in section 3.7-2009 of the DICOM standard all use their own messages. These messages are constructed using Presentation Data Values, from section 3.8-2009 of the standard, and then fill in appropriate values in their datasets.

So, for the five composites:

- C-ECHO
- C-FIND
- C-MOVE
- C-GET
- C-STORE there are a series of messages. However, all of these messages are obtained as part of a PDataPDU, and all have to be placed there. Therefore, since they all have shared functionality and construction tropes, that will be put into a base class. Further, the base class will be then returned by the factory class, [gdcmCompositePDUFactory](#).

This is an abstract class. It cannot be instantiated on its own.

25.28.2 Member Function Documentation

25.28.2.1 virtual std::vector<[PresentationDataValue](#)> [gdcm::network::BaseCompositeMessage::ConstructPDV](#) (const [ULConnection](#) & *inConnection*, const [BaseRootQuery](#) * *inRootQuery*) [pure virtual]

Implemented in [gdcm::network::CMoveRQ](#), [gdcm::network::CFindRQ](#), and [gdcm::network::CEchoRQ](#).

The documentation for this class was generated from the following file:


- [gdcmBaseCompositeMessage.h](#)

25.29 gdcm::network::BasePDU Class Reference

[BasePDU](#) base class for PDUs.

```
#include <gdcmBasePDU.h>
```

Inheritance diagram for gdcmm::network::BasePDU:



Public Member Functions

- virtual [~BasePDU](#) ()
- virtual bool [IsLastFragment](#) () const =0
- virtual void [Print](#) (std::ostream &os) const =0
- virtual std::istream & [Read](#) (std::istream &is)=0
- virtual size_t [Size](#) () const =0
- virtual const std::ostream & [Write](#) (std::ostream &os) const =0

25.29.1 Detailed Description

[BasePDU](#) base class for PDUs.

all PDUs start with the first ten bytes as specified: 01 PDU type 02 reserved 3-6 PDU Length (unsigned) 7-10 variable on some, 7-10 are split (7-8 as protocol version in Associate-RQ, for instance, while associate-rj splits those four bytes differently).

Also common to all the PDUs is their ability to read and write to a stream.

So, let's just get them all bunched together into one (abstract) class, shall we?

Why? 1) so that the [ULEvent](#) can have the PDU stored in it, since the event takes PDUs and not other class structures (other class structures get converted into PDUs) 2) to make reading PDUs in the event loop cleaner

25.29.2 Constructor & Destructor Documentation

25.29.2.1 `virtual gdcm::network::BasePDU::~BasePDU () [inline],[virtual]`

25.29.3 Member Function Documentation

25.29.3.1 `virtual bool gdcm::network::BasePDU::IsLastFragment () const [pure virtual]`

Implemented in [gdcm::network::AAssociateRQPDU](#), [gdcm::network::AAssociateACPDU](#), [gdcm::network::PDataTFPDU](#), [gdcm::network::AAabortPDU](#), [gdcm::network::AAssociateRJPDU](#), [gdcm::network::AReleaseRPPDU](#), and [gdcm::network::AReleaseRQPDU](#).

25.29.3.2 `virtual void gdcm::network::BasePDU::Print (std::ostream & os) const [pure virtual]`

Implemented in [gdcm::network::AAssociateRQPDU](#), [gdcm::network::AAssociateACPDU](#), [gdcm::network::PDataTFPDU](#), [gdcm::network::AAabortPDU](#), [gdcm::network::AReleaseRPPDU](#), [gdcm::network::AReleaseRQPDU](#), and [gdcm::network::AAssociateRJPDU](#).

25.29.3.3 `virtual std::istream& gdcm::network::BasePDU::Read (std::istream & is) [pure virtual]`

Implemented in [gdcm::network::AAssociateACPDU](#), [gdcm::network::AAssociateRQPDU](#), [gdcm::network::PDataTFPDU](#), [gdcm::network::AAssociateRJPDU](#), [gdcm::network::AReleaseRPPDU](#), [gdcm::network::AReleaseRQPDU](#), and [gdcm::network::AAabortPDU](#).

25.29.3.4 `virtual size_t gdcm::network::BasePDU::Size () const [pure virtual]`

Implemented in [gdcm::network::AAssociateACPDU](#), [gdcm::network::AAssociateRQPDU](#), [gdcm::network::PDataTFPDU](#), [gdcm::network::AAabortPDU](#), [gdcm::network::AAssociateRJPDU](#), [gdcm::network::AReleaseRPPDU](#), and [gdcm::network::AReleaseRQPDU](#).

25.29.3.5 `virtual const std::ostream& gdcm::network::BasePDU::Write (std::ostream & os) const [pure virtual]`

Implemented in [gdcm::network::AAssociateACPDU](#), [gdcm::network::AAssociateRQPDU](#), [gdcm::network::PDataTFPDU](#), [gdcm::network::AAssociateRJPDU](#), [gdcm::network::AReleaseRPPDU](#), [gdcm::network::AReleaseRQPDU](#), and [gdcm::network::AAabortPDU](#).

The documentation for this class was generated from the following file:


- [gdcmBasePDU.h](#)

25.30 gdcm::BaseRootQuery Class Reference


[BaseRootQuery](#) contains: a baseclass which will produce a dataset for c-find and c-move with patient/study root.

```
#include <gdcmBaseRootQuery.h>
```

Inheritance diagram for gdcmm::BaseRootQuery:



Collaboration diagram for gdcmm::BaseRootQuery:



Public Member Functions

- virtual `~BaseRootQuery ()`
- void `AddQueryDataSet (const DataSet &ds)`
- virtual `UIDs::TSName GetAbstractSyntaxUID () const =0`
- `DataSet` const & `GetQueryDataSet () const`
Set/Get the internal representation of the query as a DataSet.
- `DataSet` & `GetQueryDataSet ()`
- `EQueryLevel` `GetQueryLevelFromQueryRoot (ERootType roottype)`
- virtual `std::vector< Tag > GetTagListByLevel (const EQueryLevel &inQueryLevel)=0`
- virtual void `InitializeDataSet (const EQueryLevel &inQueryLevel)=0`
- void `Print (std::ostream &os) const`
- void `SetSearchParameter (const Tag &inTag, const std::string &inValue)`
- void `SetSearchParameter (const std::string &inKeyword, const std::string &inValue)`
- virtual bool `ValidateQuery (bool inStrict=true) const =0`

- const std::ostream & [WriteHelpFile](#) (std::ostream &os)
- bool [WriteQuery](#) (const std::string &inFileName)

Static Public Member Functions

- static [QueryBase](#) * [Construct](#) ([ERootType](#) inRootType, [EQueryLevel](#) qllevel)
- static int [GetQueryLevelFromString](#) (const char *str)
- static const char * [GetQueryLevelString](#) ([EQueryLevel](#) ql)

Protected Member Functions

- [BaseRootQuery](#) ()
- void [SetSearchParameter](#) (const [Tag](#) &inTag, const [DictEntry](#) &inDictEntry, const std::string &inValue)

Protected Attributes

- [DataSet](#) mDataSet
- std::string mHelpDescription
- [QueryImage](#) mImage
- [QueryPatient](#) mPatient
- [ERootType](#) mRootType
- [QuerySeries](#) mSeries
- [QueryStudy](#) mStudy

Friends

- class [QueryFactory](#)

25.30.1 Detailed Description

[BaseRootQuery](#) contains: a baseclass which will produce a dataset for c-find and c-move with patient/study root.

This class contains the functionality used in patient c-find and c-move queries. PatientRootQuery and StudyRootQuery derive from this class.

Namely: 1) list all tags associated with a particular query type 2) produce a query dataset via tag association

Eventually, it can be used to validate a particular dataset type.

The dataset held by this object (or, really, one of its derivatives) should be passed to a c-find or c-move query.

25.30.2 Constructor & Destructor Documentation

25.30.2.1 `gdcm::BaseRootQuery::BaseRootQuery ()` [protected]

25.30.2.2 `virtual gdcm::BaseRootQuery::~~BaseRootQuery ()` [virtual]

25.30.3 Member Function Documentation

25.30.3.1 void gdcm::BaseRootQuery::AddQueryDataSet (const DataSet & ds)

25.30.3.2 static QueryBase* gdcm::BaseRootQuery::Construct (ERootType inRootType, EQueryLevel qllevel)
[static]

25.30.3.3 virtual UIDs::TSName gdcm::BaseRootQuery::GetAbstractSyntaxUID () const [pure virtual]

Implemented in [gdcm::FindStudyRootQuery](#), [gdcm::MovePatientRootQuery](#), [gdcm::MoveStudyRootQuery](#), and [gdcm::FindPatientRootQuery](#).

25.30.3.4 DataSet const& gdcm::BaseRootQuery::GetQueryDataSet () const

Set/Get the internal representation of the query as a [DataSet](#).

25.30.3.5 DataSet& gdcm::BaseRootQuery::GetQueryDataSet ()

25.30.3.6 EQueryLevel gdcm::BaseRootQuery::GetQueryLevelFromQueryRoot (ERootType roottype)

25.30.3.7 static int gdcm::BaseRootQuery::GetQueryLevelFromString (const char * str) [static]

25.30.3.8 static const char* gdcm::BaseRootQuery::GetQueryLevelString (EQueryLevel ql) [static]

25.30.3.9 virtual std::vector<Tag> gdcm::BaseRootQuery::GetTagListByLevel (const EQueryLevel & inQueryLevel) [pure virtual]

this function will return all tags at a given query level, so that they maybe selected for searching. The boolean forFind is true if the query is a find query, or false for a move query.

Implemented in [gdcm::FindPatientRootQuery](#), [gdcm::FindStudyRootQuery](#), [gdcm::MovePatientRootQuery](#), and [gdcm::MoveStudyRootQuery](#).

25.30.3.10 virtual void gdcm::BaseRootQuery::InitializeDataSet (const EQueryLevel & inQueryLevel) [pure virtual]

this function sets tag 8,52 to the appropriate value based on query level also fills in the right unique tags, as per the standard's requirements should allow for connection with dcmTk

Implemented in [gdcm::FindPatientRootQuery](#), [gdcm::FindStudyRootQuery](#), [gdcm::MovePatientRootQuery](#), and [gdcm::MoveStudyRootQuery](#).

25.30.3.11 void gdcm::BaseRootQuery::Print (std::ostream & os) const [virtual]

Reimplemented from [gdcm::Object](#).

25.30.3.12 void gdcm::BaseRootQuery::SetSearchParameter (const Tag & inTag, const DictEntry & inDictEntry, const std::string & inValue) [protected]

25.30.3.13 void gdcm::BaseRootQuery::SetSearchParameter (const Tag & inTag, const std::string & inValue)

25.30.3.14 void gdcm::BaseRootQuery::SetSearchParameter (const std::string & inKeyword, const std::string & inValue)

25.30.3.15 `virtual bool gdcm::BaseRootQuery::ValidateQuery (bool inStrict = true) const` [pure virtual]

have to be able to ensure that 0x8,0x52 is set (which will be true if InitializeDataSet is called...) that the level is appropriate (ie, not setting PATIENT for a study query that the tags in the query match the right level (either required, unique, optional) by default, this function checks to see if the query is for finding, which is more permissive than for moving. For moving, only the unique tags are allowed. 10 Jan 2011: adding in the 'strict' mode. according to the standard (at least, how I've read it), only tags for a particular level should be allowed in a particular query (ie, just series level tags in a series level query). However, it seems that dcm4chee doesn't share that interpretation. So, if 'inStrict' is false, then tags from the current level and all higher levels are now considered valid. So, if you're doing a non-strict series-level query, tags from the patient and study level can be passed along as well.

Implemented in [gdcm::FindStudyRootQuery](#), [gdcm::MovePatientRootQuery](#), [gdcm::MoveStudyRootQuery](#), and [gdcm::FindPatientRootQuery](#).

25.30.3.16 `const std::ostream& gdcm::BaseRootQuery::WriteHelpFile (std::ostream & os)`

25.30.3.17 `bool gdcm::BaseRootQuery::WriteQuery (const std::string & inFileName)`

25.30.4 Friends And Related Function Documentation

25.30.4.1 `friend class QueryFactory` [friend]

25.30.5 Member Data Documentation

25.30.5.1 `DataSet gdcm::BaseRootQuery::mDataSet` [protected]

25.30.5.2 `std::string gdcm::BaseRootQuery::mHelpDescription` [protected]

25.30.5.3 `QueryImage gdcm::BaseRootQuery::mImage` [protected]

25.30.5.4 `QueryPatient gdcm::BaseRootQuery::mPatient` [protected]

25.30.5.5 `ERootType gdcm::BaseRootQuery::mRootType` [protected]

25.30.5.6 `QuerySeries gdcm::BaseRootQuery::mSeries` [protected]

25.30.5.7 `QueryStudy gdcm::BaseRootQuery::mStudy` [protected]

The documentation for this class was generated from the following file:


- [gdcmBaseRootQuery.h](#)

25.31 gdcm::SegmentHelper::BasicCodedEntry Struct Reference

This structure defines a basic coded entry with all of its attributes.

```
#include <gdcmSegmentHelper.h>
```


Collaboration diagram for gdcm::SegmentHelper::BasicCodedEntry:



Public Member Functions

- [BasicCodedEntry](#) ()
Constructor.
- [BasicCodedEntry](#) (const char *a_CV, const char *a_CSD, const char *a_CM)
constructor which defines type 1 attributes.
- [BasicCodedEntry](#) (const char *a_CV, const char *a_CSD, const char *a_CSV, const char *a_CM)
constructor which defines attributes.
- bool [IsEmpty](#) (const bool checkOptionalAttributes=false) const
Check if each attributes of the basic coded entry is defined.

Public Attributes

- std::string [CM](#)
Coding Scheme [Version](#) attribute.
- std::string [CSD](#)
Code [Value](#) attribute.
- std::string [CSV](#)
Coding Scheme Designator attribute.
- std::string [CV](#)

25.31.1 Detailed Description

This structure defines a basic coded entry with all of its attributes.

See Also

PS 3.3 section 8.8.

25.31.2 Constructor & Destructor Documentation

25.31.2.1 `gdcm::SegmentHelper::BasicCodedEntry::BasicCodedEntry () [inline]`

Constructor.

25.31.2.2 `gdcm::SegmentHelper::BasicCodedEntry::BasicCodedEntry (const char * a_CV, const char * a_CSD, const char * a_CM) [inline]`

constructor which defines type 1 attributes.

25.31.2.3 `gdcm::SegmentHelper::BasicCodedEntry::BasicCodedEntry (const char * a_CV, const char * a_CSD, const char * a_CSV, const char * a_CM) [inline]`

constructor which defines attributes.

25.31.3 Member Function Documentation

25.31.3.1 `bool gdcm::SegmentHelper::BasicCodedEntry::IsEmpty (const bool checkOptionalAttributes = false) const`

Check if each attributes of the basic coded entry is defined.

Parameters

<i>checkOptional-Attributes</i>	Check also type 1C attributes.
---------------------------------	--------------------------------

25.31.4 Member Data Documentation

25.31.4.1 `std::string gdcm::SegmentHelper::BasicCodedEntry::CM`

Coding Scheme [Version](#) attribute.

25.31.4.2 `std::string gdcm::SegmentHelper::BasicCodedEntry::CSD`

Code [Value](#) attribute.

25.31.4.3 `std::string gdcm::SegmentHelper::BasicCodedEntry::CSV`

Coding Scheme Designator attribute.

25.31.4.4 `std::string gdcm::SegmentHelper::BasicCodedEntry::CV`

The documentation for this struct was generated from the following file:


- [gdcmSegmentHelper.h](#)

25.32 gdcm::BasicOffsetTable Class Reference


Class to represent a [BasicOffsetTable](#).

```
#include <gdcmBasicOffsetTable.h>
```

Inheritance diagram for `gdcm::BasicOffsetTable`:



Collaboration diagram for `gdcm::BasicOffsetTable`:



Public Member Functions

- [BasicOffsetTable](#) ()
- `template<typename TSwap >`
`std::istream & Read (std::istream &is)`

Friends

- `std::ostream & operator<< (std::ostream &os, const BasicOffsetTable &val)`

Additional Inherited Members

25.32.1 Detailed Description

Class to represent a [BasicOffsetTable](#).

25.32.2 Constructor & Destructor Documentation

25.32.2.1 `gdcm::BasicOffsetTable::BasicOffsetTable ()` [`inline`]

25.32.3 Member Function Documentation

25.32.3.1 `template<typename TSwap> std::istream& gdcm::BasicOffsetTable::Read (std::istream & is)` `[inline]`

25.32.4 Friends And Related Function Documentation

25.32.4.1 `std::ostream& operator<< (std::ostream & os, const BasicOffsetTable & val)` `[friend]`

The documentation for this class was generated from the following file:


- [gdcmBasicOffsetTable.h](#)

25.33 gdcm::Bitmap Class Reference


Bitmap class A bitmap based image. Used as parent for both IconImage and the main Pixel Data **Image** It does not contains any World Space information (IPP, IOP)

```
#include <gdcmBitmap.h>
```

Inheritance diagram for gdcm::Bitmap:



Collaboration diagram for `gdcm::Bitmap`:



Public Member Functions

- `Bitmap ()`
- `~Bitmap ()`
- virtual bool `AreOverlaysInPixelData ()` const
- void `Clear ()`
- bool `GetBuffer (char *buffer)` const
Acces the raw data.
- unsigned long `GetBufferLength ()` const
- unsigned int `GetColumns ()` const
- const `DataElement & GetDataElement ()` const
- `DataElement & GetDataElement ()`
- unsigned int `GetDimension (unsigned int idx)` const
- const unsigned int * `GetDimensions ()` const
Return the dimension of the pixel data, first dimension (x), then 2nd (y), then 3rd (z)...
- const `LookupTable & GetLUT ()` const
- `LookupTable & GetLUT ()`
- bool `GetNeedByteSwap ()` const
- unsigned int `GetNumberOfDimensions ()` const
Return the number of dimension of the pixel data bytes; for example 2 for a 2D matrices of values.
- const `PhotometricInterpretation & GetPhotometricInterpretation ()` const
return the photometric interpretation
- const `PixelFormat & GetPixelFormat ()` const
Get/Set PixelFormat.
- `PixelFormat & GetPixelFormat ()`
- unsigned int `GetPlanarConfiguration ()` const
return the planar configuration
- unsigned int `GetRows ()` const
- const `TransferSyntax & GetTransferSyntax ()` const
- bool `IsEmpty ()` const
- bool `IsLossy ()` const
Return whether or not the image was compressed using a lossy compressor or not.
- bool `IsTransferSyntaxCompatible (TransferSyntax const &ts)` const
- void `Print (std::ostream &)` const
- void `SetColumns (unsigned int col)`

- void [SetDataElement](#) ([DataElement](#) const &de)
- void [SetDimension](#) (unsigned int idx, unsigned int dim)
- void [SetDimensions](#) (const unsigned int dims[3])
- void [SetLossyFlag](#) (bool f)
Specifically set that the image was compressed using a lossy compression mechanism.
- void [SetLUT](#) ([LookupTable](#) const &lut)
Set/Get LUT.
- void [SetNeedByteSwap](#) (bool b)
- void [SetNumberOfDimensions](#) (unsigned int dim)
- void [SetPhotometricInterpretation](#) ([PhotometricInterpretation](#) const &pi)
- void [SetPixelFormat](#) ([PixelFormat](#) const &pf)
- void [SetPlanarConfiguration](#) (unsigned int pc)
- void [SetRows](#) (unsigned int rows)
- void [SetTransferSyntax](#) ([TransferSyntax](#) const &ts)
Transfer syntax.

Protected Types

- typedef [SmartPointer](#)< [LookupTable](#) > [LUTPtr](#)

Protected Member Functions

- bool [ComputeLossyFlag](#) ()
- bool [GetBuffer2](#) (std::ostream &os) const
- bool [TryJPEG2000Codec](#) (char *buffer, bool &lossyflag) const
- bool [TryJPEG2000Codec2](#) (std::ostream &os) const
- bool [TryJPEGCodec](#) (char *buffer, bool &lossyflag) const
- bool [TryJPEGCodec2](#) (std::ostream &os) const
- bool [TryJPEGLSCodec](#) (char *buffer, bool &lossyflag) const
- bool [TryKAKADUCoec](#) (char *buffer, bool &lossyflag) const
- bool [TryPVRGCodec](#) (char *buffer, bool &lossyflag) const
- bool [TryRAWCodec](#) (char *buffer, bool &lossyflag) const
- bool [TryRLECodec](#) (char *buffer, bool &lossyflag) const

Protected Attributes

- std::vector< unsigned int > [Dimensions](#)
- bool [LossyFlag](#)
- [LUTPtr](#) [LUT](#)
- bool [NeedByteSwap](#)
- unsigned int [NumberOfDimensions](#)
- [PixelFormat](#) [PF](#)
- [PhotometricInterpretation](#) [PI](#)
- [DataElement](#) [PixelData](#)
- unsigned int [PlanarConfiguration](#)
- [TransferSyntax](#) [TS](#)

Friends

- class [ImageChangeTransferSyntax](#)
- class [PixmapReader](#)

25.33.1 Detailed Description

[Bitmap](#) class A bitmap based image. Used as parent for both [IconImage](#) and the main Pixel Data [Image](#) It does not contains any World Space information (IPP, IOP)

Examples:

[ExtractIconFromFile.cxx](#).

25.33.2 Member Typedef Documentation

25.33.2.1 `typedef SmartPointer<LookupTable> gdcm::Bitmap::LUTPtr` `[protected]`

25.33.3 Constructor & Destructor Documentation

25.33.3.1 `gdcm::Bitmap::Bitmap ()`

25.33.3.2 `gdcm::Bitmap::~~Bitmap ()`

25.33.4 Member Function Documentation

25.33.4.1 `virtual bool gdcm::Bitmap::AreOverlaysInPixelData () const` `[inline],[virtual]`

Reimplemented in [gdcm::Pixmap](#).

25.33.4.2 `void gdcm::Bitmap::Clear ()`

25.33.4.3 `bool gdcm::Bitmap::ComputeLossyFlag ()` `[protected]`

25.33.4.4 `bool gdcm::Bitmap::GetBuffer (char * buffer) const`

Acces the raw data.

Examples:

[ConvertToQImage.cxx](#), [ReadMultiTimesException.cxx](#), and [threadgdcm.cxx](#).

25.33.4.5 `bool gdcm::Bitmap::GetBuffer2 (std::ostream & os) const` `[protected]`

25.33.4.6 `unsigned long gdcm::Bitmap::GetBufferLength () const`

Return the length of the image after decompression WARNING for palette color: It will NOT take into account the Palette Color thus you need to multiply this length by 3 if computing the size of equivalent RGB image

Examples:

[ConvertToQImage.cxx](#), [GenFakelImage.cxx](#), [PatchFile.cxx](#), [ReadMultiTimesException.cxx](#), and [threadgdcm.cxx](#).

25.33.4.7 `unsigned int gdcm::Bitmap::GetColumns () const [inline]`

25.33.4.8 `const DataElement& gdcm::Bitmap::GetDataElement () const [inline]`

Examples:

[ExtractIconFromFile.cxx](#).

25.33.4.9 `DataElement& gdcm::Bitmap::GetDataElement () [inline]`

25.33.4.10 `unsigned int gdcm::Bitmap::GetDimension (unsigned int idx) const`

25.33.4.11 `const unsigned int* gdcm::Bitmap::GetDimensions () const`

Return the dimension of the pixel data, first dimension (x), then 2nd (y), then 3rd (z)...

Examples:

[ConvertToQImage.cxx](#), [ExtractIconFromFile.cxx](#), [FixJAIBugJPEGLS.cxx](#), [HelloVizWorld.cxx](#), and [threadgdcm.cxx](#).

25.33.4.12 `const LookupTable& gdcm::Bitmap::GetLUT () const [inline]`

Examples:

[ExtractIconFromFile.cxx](#).

25.33.4.13 `LookupTable& gdcm::Bitmap::GetLUT () [inline]`

25.33.4.14 `bool gdcm::Bitmap::GetNeedByteSwap () const [inline]`

25.33.4.15 `unsigned int gdcm::Bitmap::GetNumberOfDimensions () const`

Return the number of dimension of the pixel data bytes; for example 2 for a 2D matrices of values.

Examples:

[HelloVizWorld.cxx](#), and [threadgdcm.cxx](#).

25.33.4.16 `const PhotometricInterpretation& gdcm::Bitmap::GetPhotometricInterpretation () const`

return the photometric interpretation

Examples:

[ConvertToQImage.cxx](#), [ExtractIconFromFile.cxx](#), and [HelloVizWorld.cxx](#).

25.33.4.17 `const PixelFormat& gdcm::Bitmap::GetPixelFormat () const` `[inline]`

Get/Set [PixelFormat](#).

Examples:

[ConvertToQImage.cxx](#), [ExtractIconFromFile.cxx](#), [FixJAI BugJPEGLS.cxx](#), [GenFakeImage.cxx](#), [GetJPEGSamplePrecision.cxx](#), and [threadgdcm.cxx](#).

25.33.4.18 `PixelFormat& gdcm::Bitmap::GetPixelFormat ()` `[inline]`

25.33.4.19 `unsigned int gdcm::Bitmap::GetPlanarConfiguration () const`

return the planar configuration

25.33.4.20 `unsigned int gdcm::Bitmap::GetRows () const` `[inline]`

25.33.4.21 `const TransferSyntax& gdcm::Bitmap::GetTransferSyntax () const` `[inline]`

Examples:

[ExtractIconFromFile.cxx](#).

25.33.4.22 `bool gdcm::Bitmap::IsEmpty () const` `[inline]`

25.33.4.23 `bool gdcm::Bitmap::IsLossy () const`

Return whether or not the image was compressed using a lossy compressor or not.

25.33.4.24 `bool gdcm::Bitmap::IsTransferSyntaxCompatible (TransferSyntax const & ts) const`

25.33.4.25 `void gdcm::Bitmap::Print (std::ostream &) const` `[virtual]`

Reimplemented from [gdcm::Object](#).

Reimplemented in [gdcm::Image](#), and [gdcm::Pixmap](#).

Examples:

[ExtractIconFromFile.cxx](#).

25.33.4.26 `void gdcm::Bitmap::SetColumns (unsigned int col)` `[inline]`

25.33.4.27 `void gdcm::Bitmap::SetDataElement (DataElement const & de)` `[inline]`

Examples:

[CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [csa2img.cxx](#), [GenFakeImage.cxx](#), and [iU22tomultisc.cxx](#).

25.33.4.28 void gdcm::Bitmap::SetDimension (unsigned int *idx*, unsigned int *dim*)

Examples:

[csa2img.cxx](#), [GenFakelImage.cxx](#), and [iU22tomultisc.cxx](#).

25.33.4.29 void gdcm::Bitmap::SetDimensions (const unsigned int *dims*[3])

Examples:

[CreateARGBImage.cxx](#), and [CreateCMYKImage.cxx](#).

25.33.4.30 void gdcm::Bitmap::SetLossyFlag (bool *f*) [inline]

Specifically set that the image was compressed using a lossy compression mechanism.

25.33.4.31 void gdcm::Bitmap::SetLUT (LookupTable const & *lut*) [inline]

Set/Get LUT.

25.33.4.32 void gdcm::Bitmap::SetNeedByteSwap (bool *b*) [inline]

25.33.4.33 void gdcm::Bitmap::SetNumberOfDimensions (unsigned int *dim*)

Examples:

[CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [csa2img.cxx](#), [GenFakelImage.cxx](#), [GetSubSequenceData.cxx](#), and [iU22tomultisc.cxx](#).

25.33.4.34 void gdcm::Bitmap::SetPhotometricInterpretation (PhotometricInterpretation const & *pi*)

Examples:

[CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [csa2img.cxx](#), [GenFakelImage.cxx](#), and [iU22tomultisc.cxx](#).

25.33.4.35 void gdcm::Bitmap::SetPixelFormat (PixelFormat const & *pf*) [inline]

Examples:

[CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [csa2img.cxx](#), and [iU22tomultisc.cxx](#).

References gdcm::PixelFormat::Validate().

25.33.4.36 void gdcm::Bitmap::SetPlanarConfiguration (unsigned int *pc*)

Warning

you need to call SetPixelFormat first (before SetPlanarConfiguration) for consistency checking

25.33.4.37 void `gdcm::Bitmap::SetRows (unsigned int rows)` `[inline]`

25.33.4.38 void `gdcm::Bitmap::SetTransferSyntax (TransferSyntax const & ts)` `[inline]`

Transfer syntax.

Examples:

[CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), and [MergeTwoFiles.cxx](#).

25.33.4.39 bool `gdcm::Bitmap::TryJPEG2000Codec (char * buffer, bool & lossyflag) const` `[protected]`

25.33.4.40 bool `gdcm::Bitmap::TryJPEG2000Codec2 (std::ostream & os) const` `[protected]`

25.33.4.41 bool `gdcm::Bitmap::TryJPEGCodec (char * buffer, bool & lossyflag) const` `[protected]`

25.33.4.42 bool `gdcm::Bitmap::TryJPEGCodec2 (std::ostream & os) const` `[protected]`

25.33.4.43 bool `gdcm::Bitmap::TryJPEGLSCodec (char * buffer, bool & lossyflag) const` `[protected]`

25.33.4.44 bool `gdcm::Bitmap::TryKAKADUCodec (char * buffer, bool & lossyflag) const` `[protected]`

25.33.4.45 bool `gdcm::Bitmap::TryPVRGCodec (char * buffer, bool & lossyflag) const` `[protected]`

25.33.4.46 bool `gdcm::Bitmap::TryRAWCodec (char * buffer, bool & lossyflag) const` `[protected]`

25.33.4.47 bool `gdcm::Bitmap::TryRLECodec (char * buffer, bool & lossyflag) const` `[protected]`

25.33.5 Friends And Related Function Documentation

25.33.5.1 friend class `ImageChangeTransferSyntax` `[friend]`

25.33.5.2 friend class `PixmapReader` `[friend]`

25.33.6 Member Data Documentation

25.33.6.1 `std::vector<unsigned int> gdcm::Bitmap::Dimensions` `[protected]`

25.33.6.2 bool `gdcm::Bitmap::LossyFlag` `[protected]`

25.33.6.3 `LUTPtr gdcm::Bitmap::LUT` `[protected]`

25.33.6.4 bool `gdcm::Bitmap::NeedByteSwap` `[protected]`

25.33.6.5 unsigned int `gdcm::Bitmap::NumberOfDimensions` `[protected]`

25.33.6.6 `PixelFormat gdcm::Bitmap::PF` `[protected]`

25.33.6.7 `PhotometricInterpretation gdcm::Bitmap::PI` `[protected]`

25.33.6.8 `DataElement gdcm::Bitmap::PixelData` `[protected]`

25.33.6.9 unsigned int gdcm::Bitmap::PlanarConfiguration [protected]

25.33.6.10 TransferSyntax gdcm::Bitmap::TS [protected]

The documentation for this class was generated from the following file:


- [gdcmBitmap.h](#)

25.34 gdcm::BitmapToBitmapFilter Class Reference


[BitmapToBitmapFilter](#) class Super class for all filter taking an image and producing an output image.

```
#include <gdcmBitmapToBitmapFilter.h>
```

Inheritance diagram for gdcm::BitmapToBitmapFilter:



Collaboration diagram for gdcm::BitmapToBitmapFilter:



Public Member Functions

- [BitmapToBitmapFilter](#) ()
- [~BitmapToBitmapFilter](#) ()
- const [Bitmap](#) & [GetOutput](#) () const
Get Output image.
- const [Bitmap](#) & [GetOutputAsBitmap](#) () const
- void [SetInput](#) (const [Bitmap](#) &image)
Set input image.

Protected Attributes

- [SmartPointer](#)< [Bitmap](#) > [Input](#)
- [SmartPointer](#)< [Bitmap](#) > [Output](#)

25.34.1 Detailed Description

[BitmapToBitmapFilter](#) class Super class for all filter taking an image and producing an output image.

25.34.2 Constructor & Destructor Documentation

25.34.2.1 `gdcm::BitmapToBitmapFilter::BitmapToBitmapFilter ()`

25.34.2.2 `gdcm::BitmapToBitmapFilter::~~BitmapToBitmapFilter ()` `[inline]`

25.34.3 Member Function Documentation

25.34.3.1 `const Bitmap& gdcm::BitmapToBitmapFilter::GetOutput () const` `[inline]`

Get Output image.

25.34.3.2 `const Bitmap& gdcm::BitmapToBitmapFilter::GetOutputAsBitmap () const`

25.34.3.3 `void gdcm::BitmapToBitmapFilter::SetInput (const Bitmap & image)`

Set input image.

Examples:

[CompressImage.cxx](#).

25.34.4 Member Data Documentation

25.34.4.1 `SmartPointer<Bitmap> gdcm::BitmapToBitmapFilter::Input` `[protected]`

25.34.4.2 `SmartPointer<Bitmap> gdcm::BitmapToBitmapFilter::Output` `[protected]`

The documentation for this class was generated from the following file:


- [gdcmBitmapToBitmapFilter.h](#)

25.35 gdcm::BoxRegion Class Reference


Class for manipulation box region This is a very simple implementation of the [Region](#) class. It only support 3D box type region. It assumes the 3D Box does not have a tilt Origin is as (0,0,0)

```
#include <gdcmBoxRegion.h>
```

Inheritance diagram for gdcm::BoxRegion:



Collaboration diagram for gdcm::BoxRegion:



Public Member Functions

- [BoxRegion](#) ()
- [BoxRegion](#) (const [BoxRegion](#) &)
copy/cstor and al.
- [~BoxRegion](#) ()
- [size_t Area](#) () const
compute the area
- [Region * Clone](#) () const
- [BoxRegion ComputeBoundingBox](#) ()
Return the Axis-Aligned minimum bounding box for all regions.

- bool [Empty](#) () const
return whether this domain is empty:
- unsigned int [GetXMax](#) () const
- unsigned int [GetXMin](#) () const
Get domain.
- unsigned int [GetYMax](#) () const
- unsigned int [GetYMin](#) () const
- unsigned int [GetZMax](#) () const
- unsigned int [GetZMin](#) () const
- bool [IsValid](#) () const
return whether this is valid domain
- void [operator=](#) (const [BoxRegion](#) &)
- void [Print](#) (std::ostream &os=std::cout) const
Print.
- void [SetDomain](#) (unsigned int xmin, unsigned int xmax, unsigned int ymin, unsigned int ymax, unsigned int zmin, unsigned int zmax)
Set domain.

Static Public Member Functions

- static [BoxRegion BoundingBox](#) ([BoxRegion](#) const &b1, [BoxRegion](#) const &b2)
Helper class to compute the bounding box of two [BoxRegion](#).

25.35.1 Detailed Description

Class for manipulation box region This is a very simple implementation of the [Region](#) class. It only support 3D box type region. It assumes the 3D Box does not have a tilt Origin is as (0,0,0)

25.35.2 Constructor & Destructor Documentation

25.35.2.1 `gdcm::BoxRegion::BoxRegion ()`

25.35.2.2 `gdcm::BoxRegion::~~BoxRegion ()`

25.35.2.3 `gdcm::BoxRegion::BoxRegion (const BoxRegion &)`

copy/cstor and al.

25.35.3 Member Function Documentation

25.35.3.1 `size_t gdcm::BoxRegion::Area () const` `[virtual]`

compute the area

Implements [gdcm::Region](#).

25.35.3.2 **static BoxRegion** gdcm::BoxRegion::BoundingBox (**BoxRegion** const & *b1*, **BoxRegion** const & *b2*)
[static]

Helper class to compute the bounding box of two [BoxRegion](#).

25.35.3.3 **Region*** gdcm::BoxRegion::Clone () const [virtual]

Implements [gdcm::Region](#).

25.35.3.4 **BoxRegion** gdcm::BoxRegion::ComputeBoundingBox () [virtual]

Return the Axis-Aligned minimum bounding box for all regions.

Implements [gdcm::Region](#).

25.35.3.5 **bool** gdcm::BoxRegion::Empty () const [virtual]

return whether this domain is empty:

Implements [gdcm::Region](#).

25.35.3.6 **unsigned int** gdcm::BoxRegion::GetXMax () const

25.35.3.7 **unsigned int** gdcm::BoxRegion::GetXMin () const

Get domain.

25.35.3.8 **unsigned int** gdcm::BoxRegion::GetYMax () const

25.35.3.9 **unsigned int** gdcm::BoxRegion::GetYMin () const

25.35.3.10 **unsigned int** gdcm::BoxRegion::GetZMax () const

25.35.3.11 **unsigned int** gdcm::BoxRegion::GetZMin () const

25.35.3.12 **bool** gdcm::BoxRegion::IsValid () const [virtual]

return whether this is valid domain

Implements [gdcm::Region](#).

25.35.3.13 **void** gdcm::BoxRegion::operator= (**const BoxRegion** &)

25.35.3.14 **void** gdcm::BoxRegion::Print (**std::ostream** & *os* = **std::cout**) const [virtual]

Print.

Reimplemented from [gdcm::Region](#).

25.35.3.15 void gdcM::BoxRegion::SetDomain (unsigned int *xmin*, unsigned int *xmax*, unsigned int *ymin*, unsigned int *ymax*, unsigned int *zmin*, unsigned int *zmax*)

Set domain.

The documentation for this class was generated from the following file:

- [gdcMBoxRegion.h](#)

25.36 gdcM::ByteBuffer Class Reference

[ByteBuffer](#).

```
#include <gdcMByteBuffer.h>
```

Public Member Functions

- [ByteBuffer](#) ()
- char * [Get](#) (int len)
- const char * [GetStart](#) () const
- void [ShiftEnd](#) (int len)
- void [UpdatePosition](#) ()

25.36.1 Detailed Description

[ByteBuffer](#).

Detailed description here

Note

looks like a std::streambuf or std::filebuf class with the get and peek pointer

25.36.2 Constructor & Destructor Documentation

25.36.2.1 gdcM::ByteBuffer::ByteBuffer () [inline]

25.36.3 Member Function Documentation

25.36.3.1 char* gdcM::ByteBuffer::Get (int *len*) [inline]

25.36.3.2 const char* gdcM::ByteBuffer::GetStart () const [inline]

25.36.3.3 void gdcM::ByteBuffer::ShiftEnd (int *len*) [inline]

25.36.3.4 void gdcM::ByteBuffer::UpdatePosition () [inline]

The documentation for this class was generated from the following file:

- [gdcMByteBuffer.h](#)

25.37 gdcmm::ByteSwap< T > Class Template Reference

[ByteSwap.](#)

```
#include <gdcmmByteSwap.h>
```

Static Public Member Functions

- static void [Swap](#) (T &p)
- static void [SwapFromSwapCodeIntoSystem](#) (T &p, [SwapCode](#) const &sc)
- static void [SwapRange](#) (T *p, unsigned int num)
- static void [SwapRangeFromSwapCodeIntoSystem](#) (T *p, [SwapCode](#) const &sc, std::streamoff num)
- static bool [SystemIsBigEndian](#) ()
- static bool [SystemIsLittleEndian](#) ()

25.37.1 Detailed Description

```
template<class T>class gdcmm::ByteSwap< T >
```

[ByteSwap.](#)

Perform machine dependent byte swapping (Little Endian, Big Endian, Bad Little Endian, Bad Big Endian). TODO: bswap_32 / bswap_64 ...

Examples:

[TestByteSwap.cxx.](#)

25.37.2 Member Function Documentation

25.37.2.1 `template<class T> static void gdcmm::ByteSwap< T >::Swap (T & p) [static]`

25.37.2.2 `template<class T> static void gdcmm::ByteSwap< T >::SwapFromSwapCodeIntoSystem (T & p, SwapCode const & sc) [static]`

Examples:

[TestByteSwap.cxx.](#)

25.37.2.3 `template<class T> static void gdcmm::ByteSwap< T >::SwapRange (T * p, unsigned int num) [static]`

25.37.2.4 `template<class T> static void gdcmm::ByteSwap< T >::SwapRangeFromSwapCodeIntoSystem (T * p, SwapCode const & sc, std::streamoff num) [static]`

Examples:

[TestByteSwap.cxx.](#)

25.37.2.5 `template<class T> static bool gdcmm::ByteSwap< T >::SystemIsBigEndian () [static]`

Query the machine Endian-ness.

25.37.2.6 `template<class T> static bool gdcM::ByteSwap<T>::SystemIsLittleEndian () [static]`

The documentation for this class was generated from the following file:

- [gdcMByteSwap.h](#)

25.38 gdcM::ByteSwapFilter Class Reference

[ByteSwapFilter](#) In place byte-swapping of a dataset FIXME: FL status ??

```
#include <gdcMByteSwapFilter.h>
```

Public Member Functions

- [ByteSwapFilter](#) ([DataSet](#) &ds)
- [~ByteSwapFilter](#) ()
- bool [ByteSwap](#) ()
- void [SetByteSwapTag](#) (bool b)

25.38.1 Detailed Description

[ByteSwapFilter](#) In place byte-swapping of a dataset FIXME: FL status ??

25.38.2 Constructor & Destructor Documentation

25.38.2.1 `gdcM::ByteSwapFilter::ByteSwapFilter (DataSet & ds) [inline]`

25.38.2.2 `gdcM::ByteSwapFilter::~~ByteSwapFilter ()`

25.38.3 Member Function Documentation

25.38.3.1 `bool gdcM::ByteSwapFilter::ByteSwap ()`

25.38.3.2 `void gdcM::ByteSwapFilter::SetByteSwapTag (bool b) [inline]`

The documentation for this class was generated from the following file:


- [gdcMByteSwapFilter.h](#)

25.39 gdcM::ByteValue Class Reference


Class to represent binary value (array of bytes)

```
#include <gdcMByteValue.h>
```

Inheritance diagram for gdcm::ByteValue:



Collaboration diagram for gdcm::ByteValue:



Public Member Functions

- [ByteValue](#) (const char *array=0, [VL](#) const &vl=0)
- [ByteValue](#) (std::vector< char > &v)
- [~ByteValue](#) ()
- void [Clear](#) ()
- void [Fill](#) (char c)
- bool [GetBuffer](#) (char *buffer, unsigned long length) const

- [VL GetLength](#) () const
- const char * [GetPointer](#) () const
- bool [IsEmpty](#) () const
- bool [IsPrintable](#) (VL length) const

Checks whether a 'ByteValue' is printable or not (in order to avoid corrupting the terminal of invocation when printing) I dont think this function is working since it does not handle UNICODE or character set...

- [operator const std::vector< char > &](#) () const
- [ByteValue & operator=](#) (const [ByteValue](#) &val)
- bool [operator==](#) (const [ByteValue](#) &val) const
- bool [operator==](#) (const [Value](#) &val) const
- void [PrintASCII](#) (std::ostream &os, [VL](#) maxlength) const
- void [PrintGroupLength](#) (std::ostream &os)
- void [PrintHex](#) (std::ostream &os, [VL](#) maxlength) const
- template<typename TSwap , typename TType >
std::istream & [Read](#) (std::istream &is)
- template<typename TSwap >
std::istream & [Read](#) (std::istream &is)
- void [SetLength](#) (VL vl)
- template<typename TSwap , typename TType >
std::ostream const & [Write](#) (std::ostream &os) const
- template<typename TSwap >
std::ostream const & [Write](#) (std::ostream &os) const
- bool [WriteBuffer](#) (std::ostream &os) const

Protected Member Functions

- void [Print](#) (std::ostream &os) const

25.39.1 Detailed Description

Class to represent binary value (array of bytes)

Note

Examples:

[DumpADAC.cxx](#), [DumplmageHeaderInfo.cxx](#), [DuplicatePCDE.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncrypted-Content.cxx](#), [ExtractIconFromFile.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GetSubSequenceData.cxx](#), [Mr-Protocol.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [ReadExplicitLengthSQIVR.cxx](#), and [rle2img.cxx](#).

25.39.2 Constructor & Destructor Documentation

25.39.2.1 `gdcmm::ByteValue::ByteValue (const char * array = 0, VL const & vl = 0) [inline]`

References `gdcmmDebugMacro`.

25.39.2.2 `gdcm::ByteValue::ByteValue (std::vector< char > & v) [inline]`

Warning

casting to uint32_t

25.39.2.3 `gdcm::ByteValue::~~ByteValue () [inline]`

25.39.3 Member Function Documentation

25.39.3.1 `void gdcm::ByteValue::Clear () [inline],[virtual]`

Implements [gdcm::Value](#).

25.39.3.2 `void gdcm::ByteValue::Fill (char c) [inline]`

Examples:

[DuplicatePCDE.cxx](#).

25.39.3.3 `bool gdcm::ByteValue::GetBuffer (char * buffer, unsigned long length) const`

Examples:

[FixJAIBugJPEGLS.cxx](#).

25.39.3.4 `VL gdcm::ByteValue::GetLength () const [inline],[virtual]`

Implements [gdcm::Value](#).

Examples:

[DumpADAC.cxx](#), [DumpImageHeaderInfo.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [ExtractIconFromFile.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GetSubSequenceData.cxx](#), [MrProtocol.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [ReadExplicitLengthSQIVR.cxx](#), [ReadGEMSSDO.cxx](#), and [rle2img.cxx](#).

Referenced by `gdcm::operator<<()`, `gdcm::SequenceOfFragments::ReadValue()`, `gdcm::Element< VR::OB, VM::VM1_n >::Set()`, `gdcm::Element< TVR, VM::VM1_n >::Set()`, `gdcm::Attribute< Group, Element, TVR, TVM >::SetByteValue()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetByteValue()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::SetByteValue()`, `gdcm::Attribute< Group, Element, TVR, TVM >::SetByteValueNoSwap()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetByteValueNoSwap()`, `gdcm::Element< VR::OB, VM::VM1_n >::SetNoSwap()`, `gdcm::Element< TVR, VM::VM1_n >::SetNoSwap()`, and `gdcm::Fragment::Write()`.

25.39.3.5 `const char* gdcm::ByteValue::GetPointer () const [inline]`

Examples:

[DumpADAC.cxx](#), [DumpImageHeaderInfo.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [ExtractIconFromFile.cxx](#), [FixBrokenJ2K.cxx](#), [GetSubSequenceData.cxx](#), [MrProtocol.cxx](#), [pmsct_rgb1.cxx](#), [ReadExplicitLengthSQIVR.cxx](#), [ReadGEMSSDO.cxx](#), and [rle2img.cxx](#).

Referenced by `gdcmm::operator<<()`, `gdcmm::SequenceOfFragments::ReadValue()`, `gdcmm::Element< VR::OB, VM::VM1_n >::Set()`, `gdcmm::Element< TVR, VM::VM1_n >::Set()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::SetByteValue()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::SetByteValue()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetByteValue()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::SetByteValueNoSwap()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::SetByteValueNoSwap()`, `gdcmm::Element< VR::OB, VM::VM1_n >::SetNoSwap()`, and `gdcmm::Element< TVR, VM::VM1_n >::SetNoSwap()`.

25.39.3.6 `bool gdcmm::ByteValue::IsEmpty () const [inline]`

25.39.3.7 `bool gdcmm::ByteValue::IsPrintable (VL length) const [inline]`

Checks whether a 'ByteValue' is printable or not (in order to avoid corrupting the terminal of invocation when printing) I dont think this function is working since it does not handle UNICODE or character set...

25.39.3.8 `gdcmm::ByteValue::operator const std::vector< char > & () const [inline]`

25.39.3.9 `ByteValue& gdcmm::ByteValue::operator= (const ByteValue & val) [inline]`

25.39.3.10 `bool gdcmm::ByteValue::operator== (const ByteValue & val) const [inline]`

25.39.3.11 `bool gdcmm::ByteValue::operator== (const Value & val) const [inline], [virtual]`

Implements [gdcmm::Value](#).

25.39.3.12 `void gdcmm::ByteValue::Print (std::ostream & os) const [inline], [protected], [virtual]`

Reimplemented from [gdcmm::Object](#).

25.39.3.13 `void gdcmm::ByteValue::PrintASCII (std::ostream & os, VL maxlength) const`

25.39.3.14 `void gdcmm::ByteValue::PrintGroupLength (std::ostream & os) [inline]`

25.39.3.15 `void gdcmm::ByteValue::PrintHex (std::ostream & os, VL maxlength) const`

25.39.3.16 `template<typename TSwap, typename TType > std::istream& gdcmm::ByteValue::Read (std::istream & is) [inline]`

25.39.3.17 `template<typename TSwap > std::istream& gdcmm::ByteValue::Read (std::istream & is) [inline]`

25.39.3.18 `void gdcmm::ByteValue::SetLength (VL vl) [inline], [virtual]`

Implements [gdcmm::Value](#).

References `gdcmm::DebugMacro`, `gdcmm::VL::IsOdd()`, and `gdcmm::VL::IsUndefined()`.

25.39.3.19 `template<typename TSwap, typename TType > std::ostream const& gdcmm::ByteValue::Write (std::ostream & os) const [inline]`

Referenced by `gdcmm::Fragment::Write()`.

25.39.3.20 `template<typename TSwap > std::ostream const& gdcm::ByteValue::Write (std::ostream & os) const` `[inline]`

25.39.3.21 `bool gdcm::ByteValue::WriteBuffer (std::ostream & os) const` `[inline]`

The documentation for this class was generated from the following file:


- [gdcmByteValue.h](#)

25.40 gdcm::network::CEchoRQ Class Reference


[CEchoRQ](#) this file defines the messages for the cecho action.

```
#include <gdcmCEchoMessages.h>
```

Inheritance diagram for gdcm::network::CEchoRQ:



Collaboration diagram for gdcm::network::CEchoRQ:



Public Member Functions

- `std::vector< PresentationDataValue > ConstructPDV` (const [ULConnection](#) &inConnection, const [BaseRootQuery](#) *inRootQuery)

Public Attributes

- [UIComp](#) [AffectedSOPClassUID](#)
- `uint16_t` [MessageID](#)

25.40.1 Detailed Description

[CEchoRQ](#) this file defines the messages for the cecho action.

25.40.2 Member Function Documentation

25.40.2.1 `std::vector<PresentationDataValue> gdcmm::network::CEchoRQ::ConstructPDV (const ULConnection &inConnection, const BaseRootQuery * inRootQuery)` [virtual]

Implements [gdcmm::network::BaseCompositeMessage](#).

25.40.3 Member Data Documentation

25.40.3.1 `UIComp` [gdcmm::network::CEchoRQ::AffectedSOPClassUID](#)

25.40.3.2 `uint16_t` [gdcmm::network::CEchoRQ::MessageID](#)

The documentation for this class was generated from the following files:


- [gdcmmCEchoMessages.h](#)
- [gdcmmDIMSE.h](#)

25.41 gdcmm::network::CEchoRSP Class Reference


[CEchoRSP](#) this file defines the messages for the cecho action.

```
#include <gdcmmCEchoMessages.h>
```

Inheritance diagram for gdcm::network::CEchoRSP:



Collaboration diagram for gdcm::network::CEchoRSP:



Public Member Functions

- `std::vector`
`< PresentationDataValue > ConstructPDVByDataSet (const DataSet *inDataSet)`

25.41.1 Detailed Description

`CEchoRSP` this file defines the messages for the cecho action.

25.41.2 Member Function Documentation

25.41.2.1 `std::vector<PresentationDataValue> gdcm::network::CEchoRSP::ConstructPDVByDataSet (const DataSet * inDataSet)`

The documentation for this class was generated from the following file:

- [gdcmCEchoMessages.h](#)

25.42 gdcm::network::CFind Class Reference

```
#include <gdcmDIMSE.h>
```

25.42.1 Detailed Description

PS 3.4 - 2009 [Table B.2-1](#) C-STORE STATUS

The documentation for this class was generated from the following file:


- [gdcmDIMSE.h](#)

25.43 gdcm::network::CFindCancelRQ Class Reference


[CFindCancelRQ](#) this file defines the messages for the cfind action.

```
#include <gdcmCFindMessages.h>
```

Inheritance diagram for gdcm::network::CFindCancelRQ:



Collaboration diagram for gdcm::network::CFindCancelRQ:



Public Member Functions

- `std::vector`
`< PresentationDataValue > ConstructPDVByDataSet (const DataSet *inDataSet)`

25.43.1 Detailed Description

`CFindCancelRQ` this file defines the messages for the cfind action.

25.43.2 Member Function Documentation

25.43.2.1 `std::vector<PresentationDataValue> gdcm::network::CFindCancelRQ::ConstructPDVByDataSet (const DataSet *inDataSet)`

The documentation for this class was generated from the following file:


- `gdcmCFindMessages.h`

25.44 gdcm::network::CFindRQ Class Reference


`CFindRQ` this file defines the messages for the cfind action.

```
#include <gdcmCFindMessages.h>
```

Inheritance diagram for `gdcm::network::CFindRQ`:



Collaboration diagram for `gdcm::network::CFindRQ`:



Public Member Functions

- `std::vector`
`< PresentationDataValue > ConstructPDV` (const `ULConnection` &inConnection, const `BaseRootQuery` *inRootQuery)

25.44.1 Detailed Description

`CFindRQ` this file defines the messages for the cfind action.

25.44.2 Member Function Documentation

25.44.2.1 `std::vector<PresentationDataValue> gdcm::network::CFindRQ::ConstructPDV (const ULConnection & inConnection, const BaseRootQuery * inRootQuery) [virtual]`

Implements [gdcm::network::BaseCompositeMessage](#).

The documentation for this class was generated from the following file:


- [gdcmCFindMessages.h](#)

25.45 gdcm::network::CFindRSP Class Reference


[CFindRSP](#) this file defines the messages for the cfind action.

```
#include <gdcmCFindMessages.h>
```

Inheritance diagram for `gdcm::network::CFindRSP`:



Collaboration diagram for `gdcm::network::CFindRSP`:



Public Member Functions

- `std::vector`
 < [PresentationDataValue](#) > [ConstructPDVByDataSet](#) (const [DataSet](#) *inDataSet)

25.45.1 Detailed Description

[CFindRSP](#) this file defines the messages for the cfind action.

25.45.2 Member Function Documentation

25.45.2.1 `std::vector<PresentationDataValue> gdcm::network::CFindRSP::ConstructPDVByDataSet (const DataSet *
 inDataSet)`


The documentation for this class was generated from the following file:

- [gdcmCFindMessages.h](#)


25.46 gdcm::network::CMoveCancelRq Class Reference

```
#include <gdcmCMoveMessages.h>
```

Inheritance diagram for `gdcm::network::CMoveCancelRq`:



Collaboration diagram for gdcm::network::CMoveCancelRq:



Public Member Functions

- `std::vector`
`< PresentationDataValue > ConstructPDVByDataSet (const DataSet *inDataSet)`

25.46.1 Member Function Documentation

25.46.1.1 `std::vector<PresentationDataValue> gdcm::network::CMoveCancelRq::ConstructPDVByDataSet (const DataSet *inDataSet)`

The documentation for this class was generated from the following file:


- [gdcmCMoveMessages.h](#)

25.47 gdcm::network::CMoveRQ Class Reference


[CMoveRQ](#) this file defines the messages for the cmove action.

```
#include <gdcmCMoveMessages.h>
```

Inheritance diagram for `gdcm::network::CMoveRQ`:



Collaboration diagram for `gdcm::network::CMoveRQ`:



Public Member Functions

- `std::vector`
 `< PresentationDataValue > ConstructPDV` (const `ULConnection` &inConnection, const `BaseRootQuery` *inRootQuery)

25.47.1 Detailed Description

`CMoveRQ` this file defines the messages for the cmove action.

25.47.2 Member Function Documentation

25.47.2.1 `std::vector<PresentationDataValue> gdcm::network::CMoveRQ::ConstructPDV (const ULConnection & inConnection, const BaseRootQuery * inRootQuery) [virtual]`

Implements [gdcm::network::BaseCompositeMessage](#).

The documentation for this class was generated from the following file:


- [gdcmCMoveMessages.h](#)

25.48 gdcm::network::CMoveRSP Class Reference


[CMoveRSP](#) this file defines the messages for the cmove action.

```
#include <gdcmCMoveMessages.h>
```


Inheritance diagram for `gdcm::network::CMoveRSP`:



Collaboration diagram for `gdcm::network::CMoveRSP`:



Collaboration diagram for gdcmm::Codec:



Additional Inherited Members

25.49.1 Detailed Description

[Codec](#) class.

The documentation for this class was generated from the following file:


- [gdcmmCodec.h](#)

25.50 gdcmm::Coder Class Reference

[Coder](#).

```
#include <gdcmmCoder.h>
```

Inheritance diagram for gdcmm::Coder:



Public Member Functions

- virtual [~Coder](#) ()
- virtual bool [CanCode](#) ([TransferSyntax](#) const &) const =0
Return whether this coder support this transfer syntax (can code it)
- virtual bool [Code](#) ([DataElement](#) const &in_, [DataElement](#) &out_)
Code.

Protected Member Functions

- virtual bool [InternalCode](#) (const char *bv, unsigned long len, std::ostream &os)

25.50.1 Detailed Description

[Coder](#).

25.50.2 Constructor & Destructor Documentation

25.50.2.1 virtual [gdcmm::Coder::~Coder](#) () [inline],[virtual]

25.50.3 Member Function Documentation

25.50.3.1 virtual bool [gdcmm::Coder::CanCode](#) ([TransferSyntax](#) const &) const [pure virtual]

Return whether this coder support this transfer syntax (can code it)

Implemented in [gdcmm::JPEGCodec](#), [gdcmm::RLECodec](#), [gdcmm::PVRGCodec](#), [gdcmm::JPEG2000Codec](#), [gdcmm::JPEGLSCodec](#), [gdcmm::ImageCodec](#), [gdcmm::PNMCodec](#), [gdcmm::PGXCodec](#), [gdcmm::KAKADUCodec](#), [gdcmm::RAWCodec](#), [gdcmm::AudioCodec](#), and [gdcmm::PDFCodec](#).

25.50.3.2 virtual bool [gdcmm::Coder::Code](#) ([DataElement](#) const & in_, [DataElement](#) & out_) [inline],[virtual]

Code.

Reimplemented in [gdcmm::JPEGCodec](#), [gdcmm::RLECodec](#), [gdcmm::JPEGLSCodec](#), [gdcmm::PVRGCodec](#), [gdcmm::JPEG2000Codec](#), [gdcmm::KAKADUCodec](#), and [gdcmm::RAWCodec](#).

25.50.3.3 virtual bool [gdcmm::Coder::InternalCode](#) (const char * bv, unsigned long len, std::ostream & os) [inline],[protected],[virtual]

Reimplemented in [gdcmm::JPEG12Codec](#), [gdcmm::JPEG16Codec](#), and [gdcmm::JPEG8Codec](#).

The documentation for this class was generated from the following file:

- [gdcmmCoder.h](#)

25.51 gdcm::CodeString Class Reference

[CodeString](#) This is an implementation of DICOM [VR: CS](#) The ctor will properly Trim so that operator== is correct.

```
#include <gdcmCodeString.h>
```

Public Types

- typedef [InternalClass::const_iterator](#) const_iterator
- typedef [InternalClass::const_reference](#) const_reference
- typedef [InternalClass::const_reverse_iterator](#) const_reverse_iterator
- typedef [InternalClass::difference_type](#) difference_type
- typedef [InternalClass::iterator](#) iterator
- typedef [InternalClass::pointer](#) pointer
- typedef [InternalClass::reference](#) reference
- typedef [InternalClass::reverse_iterator](#) reverse_iterator
- typedef [InternalClass::size_type](#) size_type
- typedef [InternalClass::value_type](#) value_type

Public Member Functions

- [CodeString](#) ()
CodeString constructors.
- [CodeString](#) (const [value_type](#) *s)
- [CodeString](#) (const [value_type](#) *s, [size_type](#) n)
- [CodeString](#) (const [InternalClass](#) &s, [size_type](#) pos=0, [size_type](#) n=[InternalClass::npos](#))
- std::string [GetAsString](#) () const
Return the full code string as std::string.
- bool [IsValid](#) () const
Check if CodeString obj is correct..
- [size_type](#) [Size](#) () const
Return the size of the string.

Protected Member Functions

- std::string [TrimInternal](#) () const

Friends

- bool [operator!=](#) (const [CodeString](#) &ref, const [CodeString](#) &cs)
- std::ostream & [operator<<](#) (std::ostream &os, const [CodeString](#) &str)
- bool [operator==](#) (const [CodeString](#) &ref, const [CodeString](#) &cs)

25.51.1 Detailed Description

[CodeString](#) This is an implementation of DICOM VR: CS The ctor will properly Trim so that operator== is correct.

Note

the ctor of [CodeString](#) will Trim the string on the fly so as to remove the extra leading and ending spaces. However it will not perform validation on the fly ([CodeString](#) obj can contains invalid char such as lower cases). This design was chosen to be a little tolerant to broken DICOM implementation, and thus allow user to compare lower case CS from there input file without the need to first rewrite them to get rid of invalid character (validation is a different operation from searching, querying).

Warning

when writing out DICOM file it is highly recommended to perform the [IsValid\(\)](#) call, at least to check that the length of the string match the definition in the standard.

25.51.2 Member Typedef Documentation

25.51.2.1 `typedef InternalClass::const_iterator gdcm::CodeString::const_iterator`

25.51.2.2 `typedef InternalClass::const_reference gdcm::CodeString::const_reference`

25.51.2.3 `typedef InternalClass::const_reverse_iterator gdcm::CodeString::const_reverse_iterator`

25.51.2.4 `typedef InternalClass::difference_type gdcm::CodeString::difference_type`

25.51.2.5 `typedef InternalClass::iterator gdcm::CodeString::iterator`

25.51.2.6 `typedef InternalClass::pointer gdcm::CodeString::pointer`

25.51.2.7 `typedef InternalClass::reference gdcm::CodeString::reference`

25.51.2.8 `typedef InternalClass::reverse_iterator gdcm::CodeString::reverse_iterator`

25.51.2.9 `typedef InternalClass::size_type gdcm::CodeString::size_type`

25.51.2.10 `typedef InternalClass::value_type gdcm::CodeString::value_type`

25.51.3 Constructor & Destructor Documentation

25.51.3.1 `gdcm::CodeString::CodeString () [inline]`

[CodeString](#) constructors.

25.51.3.2 `gdcm::CodeString::CodeString (const value_type * s) [inline]`

25.51.3.3 `gdcm::CodeString::CodeString (const value_type * s, size_type n) [inline]`

25.51.3.4 `gdcm::CodeString::CodeString (const InternalClass & s, size_type pos = 0, size_type n = InternalClass::npos) [inline]`

25.51.4 Member Function Documentation

25.51.4.1 `std::string gdcm::CodeString::GetAsString () const` `[inline]`

Return the full code string as std::string.

25.51.4.2 `bool gdcm::CodeString::IsValid () const`

Check if [CodeString](#) obj is correct..

25.51.4.3 `size_type gdcm::CodeString::Size () const` `[inline]`

Return the size of the string.

25.51.4.4 `std::string gdcm::CodeString::TrimInternal () const` `[inline],[protected]`

25.51.5 Friends And Related Function Documentation

25.51.5.1 `bool operator!= (const CodeString & ref, const CodeString & cs)` `[friend]`

25.51.5.2 `std::ostream& operator<< (std::ostream & os, const CodeString & str)` `[friend]`

25.51.5.3 `bool operator== (const CodeString & ref, const CodeString & cs)` `[friend]`

The documentation for this class was generated from the following file:


- [gdcmCodeString.h](#)

25.52 gdcm::Command Class Reference


[Command](#) superclass for callback/observer methods.

```
#include <gdcmCommand.h>
```

Inheritance diagram for `gdcM::Command`:



Collaboration diagram for `gdcM::Command`:



Public Member Functions

- virtual void `Execute` (`Subject` *caller, const `Event` &event)=0
Abstract method that defines the action to be taken by the command.
- virtual void `Execute` (const `Subject` *caller, const `Event` &event)=0

Protected Member Functions

- `Command` ()

- [~Command\(\)](#)

25.52.1 Detailed Description

[Command](#) superclass for callback/observer methods.

See Also

[Subject](#)

25.52.2 Constructor & Destructor Documentation

25.52.2.1 `gdcm::Command::Command()` [protected]

25.52.2.2 `gdcm::Command::~~Command()` [protected]

25.52.3 Member Function Documentation

25.52.3.1 `virtual void gdcm::Command::Execute(Subject * caller, const Event & event)` [pure virtual]

Abstract method that defines the action to be taken by the command.

Implemented in [gdcm::SimpleMemberCommand< T >](#), and [gdcm::MemberCommand< T >](#).

25.52.3.2 `virtual void gdcm::Command::Execute(const Subject * caller, const Event & event)` [pure virtual]

Abstract method that defines the action to be taken by the command. This variant is expected to be used when requests comes from a const [Object](#)

Implemented in [gdcm::SimpleMemberCommand< T >](#), and [gdcm::MemberCommand< T >](#).

The documentation for this class was generated from the following file:


- [gdcmCommand.h](#)

25.53 gdcm::CommandDataSet Class Reference


Class to represent a [Command DataSet](#).

```
#include <gdcmCommandDataSet.h>
```

Inheritance diagram for `gdcm::CommandDataSet`:



Collaboration diagram for `gdcm::CommandDataSet`:



Public Member Functions

- [CommandDataSet](#) ()
- [~CommandDataSet](#) ()
- void [Insert](#) (const [DataElement](#) &de)
- std::istream & [Read](#) (std::istream &is)
Read.
- void [Replace](#) (const [DataElement](#) &de)
- std::ostream & [Write](#) (std::ostream &os) const
Write.

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [CommandDataSet](#) &_val)

Additional Inherited Members

25.53.1 Detailed Description

Class to represent a [Command DataSet](#).

See Also

[DataSet](#)

25.53.2 Constructor & Destructor Documentation

25.53.2.1 `gdcm::CommandDataSet::CommandDataSet ()` `[inline]`

25.53.2.2 `gdcm::CommandDataSet::~~CommandDataSet ()` `[inline]`

25.53.3 Member Function Documentation

25.53.3.1 `void gdcm::CommandDataSet::Insert (const DataElement & de)` `[inline]`

References `gdcmErrorMacro`, `gdcm::Tag::GetGroup()`, and `gdcm::DataElement::GetTag()`.

25.53.3.2 `std::istream& gdcm::CommandDataSet::Read (std::istream & is)`

Read.

25.53.3.3 `void gdcm::CommandDataSet::Replace (const DataElement & de)` `[inline]`

References `gdcm::DataElement::GetTag()`.

25.53.3.4 `std::ostream& gdcm::CommandDataSet::Write (std::ostream & os) const`

Write.

25.53.4 Friends And Related Function Documentation

25.53.4.1 `std::ostream& operator<< (std::ostream & _os, const CommandDataSet & _val)` `[friend]`

The documentation for this class was generated from the following file:

- [gdcmCommandDataSet.h](#)

25.54 gdcm::network::CompositeMessageFactory Class Reference

[CompositeMessageFactory](#) This class constructs PDataPDUs, but that have been specifically constructed for the composite DICOM services (C-Echo, C-Find, C-Get, C-Move, and C-Store). It will also handle parsing the incoming data to determine which of the CompositePDUs the incoming data is, and so therefore allowing the scu to determine what to do with incoming data (if acting as a storescp server, for instance).

```
#include <gdcmCompositeMessageFactory.h>
```

Static Public Member Functions

- static std::vector
< [PresentationDataValue](#) > [ConstructCEchoRQ](#) (const [ULConnection](#) &inConnection)
- static std::vector
< [PresentationDataValue](#) > [ConstructCFindRQ](#) (const [ULConnection](#) &inConnection, const [BaseRootQuery](#) *inRootQuery)
- static std::vector
< [PresentationDataValue](#) > [ConstructCMoveRQ](#) (const [ULConnection](#) &inConnection, const [BaseRootQuery](#) *inRootQuery)
- static std::vector
< [PresentationDataValue](#) > [ConstructCStoreRQ](#) (const [ULConnection](#) &inConnection, const [File](#) &file)
- static std::vector
< [PresentationDataValue](#) > [ConstructCStoreRSP](#) (const [DataSet](#) *inDataSet, const [BasePDU](#) *inPC)

25.54.1 Detailed Description

[CompositeMessageFactory](#) This class constructs PDataPDUs, but that have been specifically constructed for the composite DICOM services (C-Echo, C-Find, C-Get, C-Move, and C-Store). It will also handle parsing the incoming data to determine which of the CompositePDUs the incoming data is, and so therefore allowing the scu to determine what to do with incoming data (if acting as a storescp server, for instance).

25.54.2 Member Function Documentation

- 25.54.2.1 static std::vector<[PresentationDataValue](#)> [gdcm::network::CompositeMessageFactory::ConstructCEchoRQ](#) (const [ULConnection](#) & *inConnection*) [static]
- 25.54.2.2 static std::vector<[PresentationDataValue](#)> [gdcm::network::CompositeMessageFactory::ConstructCFindRQ](#) (const [ULConnection](#) & *inConnection*, const [BaseRootQuery](#) * *inRootQuery*) [static]
- 25.54.2.3 static std::vector<[PresentationDataValue](#)> [gdcm::network::CompositeMessageFactory::ConstructCMoveRQ](#) (const [ULConnection](#) & *inConnection*, const [BaseRootQuery](#) * *inRootQuery*) [static]
- 25.54.2.4 static std::vector<[PresentationDataValue](#)> [gdcm::network::CompositeMessageFactory::ConstructCStoreRQ](#) (const [ULConnection](#) & *inConnection*, const [File](#) & *file*) [static]
- 25.54.2.5 static std::vector<[PresentationDataValue](#)> [gdcm::network::CompositeMessageFactory::ConstructCStoreRSP](#) (const [DataSet](#) * *inDataSet*, const [BasePDU](#) * *inPC*) [static]

The documentation for this class was generated from the following file:

- [gdcmCompositeMessageFactory.h](#)

25.55 gdcm::CompositeNetworkFunctions Class Reference

Composite Network Functions These functions provide a generic API to the DICOM functions implemented in GDCM. Advanced users can use this code as a template for building their own versions of these functions (for instance, to

provide progress bars or some other way of handling returned query information), but for most users, these functions should be sufficient to interface with a PACS to a local machine. Note that these functions are not contained within a static class or some other class-style interface, because multiple connections can be instantiated in the same program. The DICOM standard is much more function oriented rather than class oriented in this instance, so the design of this API reflects that functional approach. These functions implements the following SCU operations:

```
#include <gdcmCompositeNetworkFunctions.h>
```

Public Types

- typedef std::vector
 < [KeyValuePairType](#) > [KeyValuePairArrayType](#)
- typedef std::pair< [Tag](#),
 std::string > [KeyValuePairType](#)

Static Public Member Functions

- static bool [CEcho](#) (const char *remote, uint16_t portno, const char *aetitle=NULL, const char *call=NULL)
- static bool [CFind](#) (const char *remote, uint16_t portno, const [BaseRootQuery](#) *query, std::vector< [DataSet](#) > &retDataSets, const char *aetitle=NULL, const char *call=NULL)
- static bool [CMove](#) (const char *remote, uint16_t portno, const [BaseRootQuery](#) *query, uint16_t portscp, const char *aetitle=NULL, const char *call=NULL, const char *outputdir=NULL)
- static [BaseRootQuery](#) * [ConstructQuery](#) ([ERootType](#) inRootType, [EQueryLevel](#) inQueryLevel, const [DataSet](#) &queryds, bool inMove=false)
- static [BaseRootQuery](#) * [ConstructQuery](#) ([ERootType](#) inRootType, [EQueryLevel](#) inQueryLevel, const [KeyValuePairArrayType](#) &keys, bool inMove=false)
- static bool [CStore](#) (const char *remote, uint16_t portno, const [Directory::FileNamesType](#) &filenames, const char *aetitle=NULL, const char *call=NULL)

25.55.1 Detailed Description

Composite Network Functions These functions provide a generic API to the DICOM functions implemented in GDCM. Advanced users can use this code as a template for building their own versions of these functions (for instance, to provide progress bars or some other way of handling returned query information), but for most users, these functions should be sufficient to interface with a PACS to a local machine. Note that these functions are not contained within a static class or some other class-style interface, because multiple connections can be instantiated in the same program. The DICOM standard is much more function oriented rather than class oriented in this instance, so the design of this API reflects that functional approach. These functions implements the following SCU operations:

- C-ECHO SCU
- C-FIND SCU
- C-STORE SCU
- C-MOVE SCU (+internal C-STORE SCP)

25.55.2 Member Typedef Documentation

25.55.2.1 typedef std::vector< [KeyValuePairType](#) > gdcm::CompositeNetworkFunctions::KeyValuePairArrayType

25.55.2.2 `typedef std::pair<Tag, std::string> gdcmm::CompositeNetworkFunctions::KeyValuePairType`

25.55.3 Member Function Documentation

25.55.3.1 `static bool gdcmm::CompositeNetworkFunctions::CEcho (const char * remote, uint16_t portno, const char * aetitle = NULL, const char * call = NULL) [static]`

The most basic network function. Use this function to ensure that the remote server is responding on the given IP and port number as expected.

Parameters

<i>aetitle</i>	when not set will default to 'GDCMSCU'
<i>call</i>	when not set will default to 'ANY-SCP' This is an error to set remote to NULL or portno to 0

Returns

true if it worked.

25.55.3.2 `static bool gdcmm::CompositeNetworkFunctions::CFind (const char * remote, uint16_t portno, const BaseRootQuery * query, std::vector< DataSet > & retDataSets, const char * aetitle = NULL, const char * call = NULL) [static]`

This function will use the provided query to determine what files a remote server contains that match the query strings. The return is a vector of datasets that contain tags as reported by the server. If the dataset is empty, then it is possible that an error condition was encountered; in which case, the user should monitor the error and warning streams.

Parameters

<i>aetitle</i>	when not set will default to 'GDCMSCU'
<i>call</i>	when not set will default to 'ANY-SCP' This is an error to set remote to NULL or portno to 0

Returns

true if it worked.

25.55.3.3 `static bool gdcmm::CompositeNetworkFunctions::CMove (const char * remote, uint16_t portno, const BaseRootQuery * query, uint16_t portscp, const char * aetitle = NULL, const char * call = NULL, const char * outputdir = NULL) [static]`

This function will use the provided query to get files from a remote server. NOTE that this functionality is essentially equivalent to C-GET in the DICOM standard; however, C-GET has been deprecated, so this function allows for the user to ask a remote server for files matching a query and return them to the local machine. Files will be written to the given output directory. If the operation succeeds, the function returns true. This function is a prime candidate for being overwritten by expert users; if the datasets should remain in memory, for instance, that behavior can be changed by creating a user-level version of this function.

Parameters

<i>aetitle</i>	when not set will default to 'GDCMSCU'
----------------	--

<i>call</i>	when not set will default to 'ANY-SCP' This is an error to set remote to NULL or portno to 0 when
<i>outputdir</i>	is not set default to current dir ('.')

Returns

true if it worked.

25.55.3.4 static BaseRootQuery* gdcm::CompositeNetworkFunctions::ConstructQuery (ERootType *inRootType*, EQueryLevel *inQueryLevel*, const DataSet & *queryds*, bool *inMove* = false) [static]

This function will take a list of strings and tags and fill in a query that can be used for either CFind or CMove (depending on the input boolean

Parameters

<i>inMove</i>).	Note that the caller is responsible for deleting the constructed query. This function is used to build both a move and a find query (true for inMove if it's move, false if it's find)
------------------	--

25.55.3.5 static BaseRootQuery* gdcm::CompositeNetworkFunctions::ConstructQuery (ERootType *inRootType*, EQueryLevel *inQueryLevel*, const KeyValuePairArrayType & *keys*, bool *inMove* = false) [static]

Deprecated

25.55.3.6 static bool gdcm::CompositeNetworkFunctions::CStore (const char * *remote*, uint16_t *portno*, const Directory::FileNamesType & *filenames*, const char * *aetitle* = NULL, const char * *call* = NULL) [static]

This function will place the provided files into the remote server. The function returns true if it worked for all files.

Warning

the server side can refuse an association on a given file

Parameters

<i>aetitle</i>	when not set will default to 'GDCMSCU'
<i>call</i>	when not set will default to 'ANY-SCP' This is an error to set remote to NULL or portno to 0

Returns

true if it worked for all files

The documentation for this class was generated from the following file:

- [gdcmCompositeNetworkFunctions.h](#)

25.56 gdcm::ConstCharWrapper Class Reference

Do not use me.

```
#include <gdcmConstCharWrapper.h>
```

Public Member Functions

- [ConstCharWrapper](#) (const char *i=0)
- [operator const char * \(\)](#) const

25.56.1 Detailed Description

Do not use me.

25.56.2 Constructor & Destructor Documentation

25.56.2.1 `gdcm::ConstCharWrapper::ConstCharWrapper (const char * i = 0) [inline]`

25.56.3 Member Function Documentation

25.56.3.1 `gdcm::ConstCharWrapper::operator const char * () const [inline]`

The documentation for this class was generated from the following file:


- [gdcmConstCharWrapper.h](#)

25.57 gdcm::CP246ExplicitDataElement Class Reference


Class to read/write a [DataElement](#) as CP246Explicit Data [Element](#).

```
#include <gdcmCP246ExplicitDataElement.h>
```

Inheritance diagram for `gdcm::CP246ExplicitDataElement`:



Collaboration diagram for gdcm::CP246ExplicitDataElement:



Public Member Functions

- [VL GetLength](#) () const
- template<typename TSwap >
std::istream & [Read](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadPreValue](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadValue](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadWithLength](#) (std::istream &is, [VL](#) &length)

Additional Inherited Members

25.57.1 Detailed Description

Class to read/write a [DataElement](#) as CP246Explicit Data [Element](#).

Note

Some system are producing SQ, declare them as UN, but encode the SQ as 'Explicit' instead of Implicit

25.57.2 Member Function Documentation

25.57.2.1 VL gdcm::CP246ExplicitDataElement::GetLength () const

25.57.2.2 `template<typename TSwap> std::istream& gdcmm::CP246ExplicitDataElement::Read (std::istream & is)`

25.57.2.3 `template<typename TSwap> std::istream& gdcmm::CP246ExplicitDataElement::ReadPreValue (std::istream & is)`

25.57.2.4 `template<typename TSwap> std::istream& gdcmm::CP246ExplicitDataElement::ReadValue (std::istream & is)`

25.57.2.5 `template<typename TSwap> std::istream& gdcmm::CP246ExplicitDataElement::ReadWithLength (std::istream & is, VL & length)`

The documentation for this class was generated from the following file:

- [gdcmmCP246ExplicitDataElement.h](#)

25.58 gdcmm::CryptographicMessageSyntax Class Reference

Class for [CryptographicMessageSyntax](#) encryption. This is just a simple wrapper around openssl PKCS7_encrypt functionalities.

```
#include <gdcmmCryptographicMessageSyntax.h>
```

Public Types

- enum [CipherTypes](#) {
[DES_CIPHER](#),
[DES3_CIPHER](#),
[AES128_CIPHER](#),
[AES192_CIPHER](#),
[AES256_CIPHER](#) }

Public Member Functions

- [CryptographicMessageSyntax](#) ()
- [~CryptographicMessageSyntax](#) ()
- bool [Decrypt](#) (char *output, size_t &outlen, const char *array, size_t len) const
decrypt content from a PKCS#7 envelopedData structure
- bool [Encrypt](#) (char *output, size_t &outlen, const char *array, size_t len) const
create a PKCS#7 envelopedData structure
- [CipherTypes](#) [GetCipherType](#) () const
- bool [ParseCertificateFile](#) (const char *filename)
- bool [ParseKeyFile](#) (const char *filename)
- void [SetCipherType](#) ([CipherTypes](#) type)

25.58.1 Detailed Description

Class for [CryptographicMessageSyntax](#) encryption. This is just a simple wrapper around openssl PKCS7_encrypt functionalities.

See online documentation http://www.openssl.org/docs/crypto/PKCS7_encrypt.html

25.58.2 Member Enumeration Documentation

25.58.2.1 enum gdcmm::CryptographicMessageSyntax::CipherTypes

Enumerator

DES_CIPHER

DES3_CIPHER

AES128_CIPHER

AES192_CIPHER

AES256_CIPHER

25.58.3 Constructor & Destructor Documentation

25.58.3.1 gdcmm::CryptographicMessageSyntax::CryptographicMessageSyntax ()

25.58.3.2 gdcmm::CryptographicMessageSyntax::~~CryptographicMessageSyntax ()

25.58.4 Member Function Documentation

25.58.4.1 bool gdcmm::CryptographicMessageSyntax::Decrypt (char * *output*, size_t & *outlen*, const char * *array*, size_t *len*) const

decrypt content from a PKCS#7 envelopedData structure

25.58.4.2 bool gdcmm::CryptographicMessageSyntax::Encrypt (char * *output*, size_t & *outlen*, const char * *array*, size_t *len*) const

create a PKCS#7 envelopedData structure

25.58.4.3 CipherTypes gdcmm::CryptographicMessageSyntax::GetCipherType () const

25.58.4.4 bool gdcmm::CryptographicMessageSyntax::ParseCertificateFile (const char * *filename*)

25.58.4.5 bool gdcmm::CryptographicMessageSyntax::ParseKeyFile (const char * *filename*)

25.58.4.6 void gdcmm::CryptographicMessageSyntax::SetCipherType (CipherTypes *type*)

Set Cipher [Type](#). Default is: AES256_CIPHER

The documentation for this class was generated from the following file:


- [gdcmmCryptographicMessageSyntax.h](#)

25.59 gdcmm::CSAElement Class Reference

Class to represent a CSA [Element](#).

```
#include <gdcmmCSAElement.h>
```

Collaboration diagram for `gdcm::CSAElement`:



Public Member Functions

- `CSAElement` (unsigned int kf=0)
- `CSAElement` (const `CSAElement` &_val)
- const `ByteValue` * `GetByteValue` () const
- unsigned int `GetKey` () const
Set/Get Key.
- const char * `GetName` () const
Set/Get Name.
- unsigned int `GetNoOfItems` () const
Set/Get NoOfItems.
- unsigned int `GetSyngoDT` () const
Set/Get SyngoDT.
- `Value` const & `GetValue` () const
Set/Get Value (bytes array, SQ of items, SQ of fragments):
- `Value` & `GetValue` ()
- const `VM` & `GetVM` () const
Set/Get VM.
- `VR` const & `GetVR` () const
Set/Get VR.
- bool `IsEmpty` () const
Check if CSA Element is empty.
- bool `operator<` (const `CSAElement` &de) const
- `CSAElement` & `operator=` (const `CSAElement` &de)
- bool `operator==` (const `CSAElement` &de) const
- void `SetByteValue` (const char *array, `VL` length)
Set.
- void `SetKey` (unsigned int key)
- void `SetName` (const char *name)
- void `SetNoOfItems` (unsigned int items)

- void [SetSyngoDT](#) (unsigned int syngodt)
- void [SetValue](#) ([Value](#) const &vl)
- void [SetVM](#) (const [VM](#) &vm)
- void [SetVR](#) ([VR](#) const &vr)

Protected Types

- typedef [SmartPointer](#)< [Value](#) > [DataPtr](#)

Protected Attributes

- [DataPtr](#) [DataField](#)
- unsigned int [KeyField](#)
- std::string [NameField](#)
- unsigned int [NoOfItemsField](#)
- unsigned int [SyngoDTField](#)
- [VM](#) [ValueMultiplicityField](#)
- [VR](#) [VRField](#)

Friends

- std::ostream & [operator<<](#) (std::ostream &os, const [CSAElement](#) &val)

25.59.1 Detailed Description

Class to represent a CSA [Element](#).

See Also

[CSAHeader](#)

Examples:

[csa2img.cxx](#), and [MrProtocol.cxx](#).

25.59.2 Member Typedef Documentation

25.59.2.1 typedef [SmartPointer](#)<[Value](#)> [gdcm::CSAElement::DataPtr](#) [protected]

25.59.3 Constructor & Destructor Documentation

25.59.3.1 [gdcm::CSAElement::CSAElement](#) (unsigned int *kf* = 0) [inline]

25.59.3.2 [gdcm::CSAElement::CSAElement](#) (const [CSAElement](#) &*_val*) [inline]

25.59.4 Member Function Documentation

25.59.4.1 const [ByteValue](#)* [gdcm::CSAElement::GetByteValue](#) () const [inline]

Return the [Value](#) of [CSAElement](#) as a [ByteValue](#) (if possible)

Warning

: You need to check for NULL return value

Examples:

[MrProtocol.cxx](#).

25.59.4.2 `unsigned int gdcm::CSAElement::GetKey () const` `[inline]`

Set/Get Key.

Referenced by operator<().

25.59.4.3 `const char* gdcm::CSAElement::GetName () const` `[inline]`

Set/Get Name.

25.59.4.4 `unsigned int gdcm::CSAElement::GetNoOfItems () const` `[inline]`

Set/Get NoOfItems.

25.59.4.5 `unsigned int gdcm::CSAElement::GetSyngoDT () const` `[inline]`

Set/Get SyngoDT.

25.59.4.6 `Value const& gdcm::CSAElement::GetValue () const` `[inline]`

Set/Get [Value](#) (bytes array, SQ of items, SQ of fragments):

Examples:

[csa2img.cxx](#).

25.59.4.7 `Value& gdcm::CSAElement::GetValue ()` `[inline]`

25.59.4.8 `const VM& gdcm::CSAElement::GetVM () const` `[inline]`

Set/Get [VM](#).

25.59.4.9 `VR const& gdcm::CSAElement::GetVR () const` `[inline]`

Set/Get [VR](#).

25.59.4.10 `bool gdcm::CSAElement::IsEmpty () const` `[inline]`

Check if CSA [Element](#) is empty.

Examples:

[csa2img.cxx](#).

25.59.4.11 `bool gdcm::CSAElement::operator< (const CSAElement & de) const` `[inline]`

References `GetKey()`.

25.59.4.12 `CSAElement& gdcm::CSAElement::operator= (const CSAElement & de)` `[inline]`

References `DataField`, `KeyField`, `NameField`, `NoOfItemsField`, `SyngoDTField`, `ValueMultiplicityField`, and `VRField`.

25.59.4.13 `bool gdcm::CSAElement::operator== (const CSAElement & de) const` `[inline]`

References `KeyField`, `NameField`, `SyngoDTField`, `ValueMultiplicityField`, and `VRField`.

25.59.4.14 `void gdcm::CSAElement::SetByteValue (const char * array, VL length)` `[inline]`

`Set`.

25.59.4.15 `void gdcm::CSAElement::SetKey (unsigned int key)` `[inline]`

25.59.4.16 `void gdcm::CSAElement::SetName (const char * name)` `[inline]`

25.59.4.17 `void gdcm::CSAElement::SetNoOfItems (unsigned int items)` `[inline]`

25.59.4.18 `void gdcm::CSAElement::SetSyngoDT (unsigned int syngodt)` `[inline]`

25.59.4.19 `void gdcm::CSAElement::SetValue (Value const & vl)` `[inline]`

25.59.4.20 `void gdcm::CSAElement::SetVM (const VM & vm)` `[inline]`

25.59.4.21 `void gdcm::CSAElement::SetVR (VR const & vr)` `[inline]`

25.59.5 Friends And Related Function Documentation

25.59.5.1 `std::ostream& operator<< (std::ostream & os, const CSAElement & val)` `[friend]`

25.59.6 Member Data Documentation

25.59.6.1 `DataPtr gdcm::CSAElement::DataField` `[protected]`

Referenced by `gdcm::operator<<()`, and `operator=()`.

25.59.6.2 `unsigned int gdcm::CSAElement::KeyField` `[protected]`

Referenced by `gdcm::operator<<()`, `operator=()`, and `operator==()`.

25.59.6.3 `std::string gdcm::CSAElement::NameField` [protected]

Referenced by `gdcm::operator<<()`, `operator=()`, and `operator==()`.

25.59.6.4 `unsigned int gdcm::CSAElement::NoOfItemsField` [protected]

Referenced by `gdcm::operator<<()`, and `operator=()`.

25.59.6.5 `unsigned int gdcm::CSAElement::SyngoDTField` [protected]

Referenced by `gdcm::operator<<()`, `operator=()`, and `operator==()`.

25.59.6.6 `VM gdcm::CSAElement::ValueMultiplicityField` [protected]

Referenced by `gdcm::operator<<()`, `operator=()`, and `operator==()`.

25.59.6.7 `VR gdcm::CSAElement::VRField` [protected]

Referenced by `gdcm::operator<<()`, `operator=()`, and `operator==()`.

The documentation for this class was generated from the following file:

- [gdcmCSAElement.h](#)

25.60 gdcm::CSAHeader Class Reference

Class for [CSAHeader](#).

```
#include <gdcmCSAHeader.h>
```

Public Types

- enum [CSAHeaderType](#) {
`UNKNOWN` = 0,
`SV10`,
`NOMAGIC`,
`DATASET_FORMAT`,
`INTERFILE`,
`ZEROED_OUT` }

Divers format of [CSAHeader](#) as found 'in the wild'.

Public Member Functions

- [CSAHeader](#) ()
- [~CSAHeader](#) ()
- bool [FindCSAElementByName](#) (const char *name)
- const [CSAElement](#) & [GetCSAElementByName](#) (const char *name)
- const [DataSet](#) & [GetDataSet](#) () const

Return the [DataSet](#) output (use only if Format == DATASET_FORMAT)

- [CSAHeaderType](#) [GetFormat](#) () const
- const char * [GetInterfile](#) () const

Return the string output (use only if Format == Interfile)

- bool [LoadFromDataElement](#) ([DataElement](#) const &de)

Decode the [CSAHeader](#) from element 'de'.

- void [Print](#) (std::ostream &os) const

Print the [CSAHeader](#) (use only if Format == SV10 or NOMAGIC)

- template<typename TSwap >
std::istream & [Read](#) (std::istream &is)
- template<typename TSwap >
const std::ostream & [Write](#) (std::ostream &os) const

Static Public Member Functions

- static const [PrivateTag](#) & [GetCSADataInfo](#) ()
- static const [PrivateTag](#) & [GetCSAImageHeaderInfoTag](#) ()
- static const [PrivateTag](#) & [GetCSASeriesHeaderInfoTag](#) ()

Protected Member Functions

- const [CSAElement](#) & [GetCSAEEnd](#) () const

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [CSAHeader](#) &d)

25.60.1 Detailed Description

Class for [CSAHeader](#).

SIEMENS store private information in tag (0x0029,0x10,"SIEMENS CSA HEADER") this class is meant for user wishing to access values stored within this private attribute. There are basically two main 'format' for this attribute : SV10/NOMAGIC and DATASET_FORMAT SV10 and NOMAGIC are from a user prospective identical, see CSAHeader.xml for possible name / value stored in this format. DATASET_FORMAT is in fact simply just another DICOM dataset (implicit) with -currently unknown- value. This can be only be printed for now.

Warning

Everything you do with this code is at your own risk, since decoding process was not written from specification documents.
the API of this class might change.

Todo MrEvaProtocol in 29,1020 contains ^M that would be nice to get rid of on UNIX system...

See Also

[PDBHeader](#)

External references: 5.1.3.2.4.1 MEDCOM History Information and 5.1.4.3 CSA Non-Image [Module](#) in http://tamsinfo.toshiba.com/docrequest/pdf/E.Soft_v2.0.pdf

Examples:

[csa2img.cxx](#), and [MrProtocol.cxx](#).

25.60.2 Member Enumeration Documentation

25.60.2.1 enum gdcm::CSAHeader::CSAHeaderType

Divers format of [CSAHeader](#) as found 'in the wild'.

Enumerator

UNKNOWN

SV10

NOMAGIC

DATASET_FORMAT

INTERFILE

ZEROED_OUT

25.60.3 Constructor & Destructor Documentation

25.60.3.1 gdcm::CSAHeader::CSAHeader () `[inline]`

25.60.3.2 gdcm::CSAHeader::~~CSAHeader () `[inline]`

25.60.4 Member Function Documentation

25.60.4.1 bool gdcm::CSAHeader::FindCSAElementByName (const char * *name*)

Return true if the CSA element matching 'name' is found or not

Warning

Case Sensitive

Examples:

[csa2img.cxx](#), and [MrProtocol.cxx](#).

25.60.4.2 static const PrivateTag& gdcm::CSAHeader::GetCSADatInfo () `[static]`

Return the private tag used by SIEMENS to store the CSA Data Info This is: [PrivateTag](#)(0x0029,0x0010,"SIEMENS CSA NON-IMAGE");

25.60.4.3 `const CSAElement& gdcm::CSAHeader::GetCSAEEnd () const` `[protected]`

25.60.4.4 `const CSAElement& gdcm::CSAHeader::GetCSAElementByName (const char * name)`

Return the [CSAElement](#) corresponding to name 'name'

Warning

Case Sensitive

Examples:

[csa2img.cxx](#), and [MrProtocol.cxx](#).

25.60.4.5 `static const PrivateTag& gdcm::CSAHeader::GetCSAImageHeaderInfoTag ()` `[static]`

Return the private tag used by SIEMENS to store the CSA [Image](#) Header This is: [PrivateTag](#)(0x0029,0x0010,"SIEMENS CSA HEADER");

Examples:

[csa2img.cxx](#), and [PublicDict.cxx](#).

25.60.4.6 `static const PrivateTag& gdcm::CSAHeader::GetCSASeriesHeaderInfoTag ()` `[static]`

Return the private tag used by SIEMENS to store the CSA [Series](#) Header This is: [PrivateTag](#)(0x0029,0x0020,"SIEMENS CSA HEADER");

Examples:

[MrProtocol.cxx](#).

25.60.4.7 `const DataSet& gdcm::CSAHeader::GetDataSet () const` `[inline]`

Return the [DataSet](#) output (use only if Format == DATASET_FORMAT)

25.60.4.8 `CSAHeaderType gdcm::CSAHeader::GetFormat () const`

return the format of the [CSAHeader](#) SV10 and NOMAGIC are equivalent.

25.60.4.9 `const char* gdcm::CSAHeader::GetInterfile () const` `[inline]`

Return the string output (use only if Format == Interfile)

25.60.4.10 `bool gdcm::CSAHeader::LoadFromDataElement (DataElement const & de)`

Decode the [CSAHeader](#) from element 'de'.

Examples:

[csa2img.cxx](#), and [MrProtocol.cxx](#).

25.60.4.11 `void gdcmm::CSAHeader::Print (std::ostream & os) const`

Print the [CSAHeader](#) (use only if Format == SV10 or NOMAGIC)

Examples:

[csa2img.cxx](#).

Referenced by `gdcmm::operator<<()`.

25.60.4.12 `template<typename TSwap > std::istream& gdcmm::CSAHeader::Read (std::istream & is)`

25.60.4.13 `template<typename TSwap > const std::ostream& gdcmm::CSAHeader::Write (std::ostream & os) const`

25.60.5 Friends And Related Function Documentation

25.60.5.1 `std::ostream& operator<< (std::ostream & _os, const CSAHeader & d)` `[friend]`

The documentation for this class was generated from the following file:

- [gdcmmCSAHeader.h](#)

25.61 gdcmm::CSAHeaderDict Class Reference

Class to represent a map of [CSAHeaderDictEntry](#).

```
#include <gdcmmCSAHeaderDict.h>
```

Public Types

- typedef
MapCSAHeaderDictEntry::const_iterator [ConstIterator](#)
- typedef
MapCSAHeaderDictEntry::iterator [Iterator](#)
- typedef std::set
< [CSAHeaderDictEntry](#) > [MapCSAHeaderDictEntry](#)

Public Member Functions

- [CSAHeaderDict](#) ()
- void [AddCSAHeaderDictEntry](#) (const [CSAHeaderDictEntry](#) &de)
- [ConstIterator](#) [Begin](#) () const
- [ConstIterator](#) [End](#) () const
- const [CSAHeaderDictEntry](#) & [GetCSAHeaderDictEntry](#) (const char *name) const
- bool [IsEmpty](#) () const

Protected Member Functions

- void [LoadDefault](#) ()

Friends

- class [Dicts](#)
- std::ostream & [operator<<](#) (std::ostream &_os, const [CSAHeaderDict](#) &_val)

25.61.1 Detailed Description

Class to represent a map of [CSAHeaderDictEntry](#).

Examples:

[MrProtocol.cxx](#).

25.61.2 Member Typedef Documentation

25.61.2.1 typedef MapCSAHeaderDictEntry::const_iterator gdcm::CSAHeaderDict::ConstIterator

25.61.2.2 typedef MapCSAHeaderDictEntry::iterator gdcm::CSAHeaderDict::Iterator

25.61.2.3 typedef std::set<CSAHeaderDictEntry> gdcm::CSAHeaderDict::MapCSAHeaderDictEntry

25.61.3 Constructor & Destructor Documentation

25.61.3.1 gdcm::CSAHeaderDict::CSAHeaderDict () [\[inline\]](#)

25.61.4 Member Function Documentation

25.61.4.1 void gdcm::CSAHeaderDict::AddCSAHeaderDictEntry (const CSAHeaderDictEntry & de) [\[inline\]](#)

25.61.4.2 ConstIterator gdcm::CSAHeaderDict::Begin () const [\[inline\]](#)

25.61.4.3 ConstIterator gdcm::CSAHeaderDict::End () const [\[inline\]](#)

25.61.4.4 const CSAHeaderDictEntry& gdcm::CSAHeaderDict::GetCSAHeaderDictEntry (const char * name) const [\[inline\]](#)

Examples:

[MrProtocol.cxx](#).

25.61.4.5 bool gdcm::CSAHeaderDict::IsEmpty () const [\[inline\]](#)

25.61.4.6 void gdcm::CSAHeaderDict::LoadDefault () [\[protected\]](#)

25.61.5 Friends And Related Function Documentation

25.61.5.1 friend class Dicts [\[friend\]](#)

25.61.5.2 std::ostream& operator<< (std::ostream &_os, const CSAHeaderDict &_val) [\[friend\]](#)

The documentation for this class was generated from the following file:

- [gdcmCSAHeaderDict.h](#)

25.62 gdcm::CSAHeaderDictEntry Class Reference

Class to represent an Entry in the [Dict](#) Does not really exist within the DICOM definition, just a way to minimize storage and have a mapping from [gdcm::Tag](#) to the needed information.

```
#include <gdcmCSAHeaderDictEntry.h>
```

Public Member Functions

- [CSAHeaderDictEntry](#) (const char *name="", [VR](#) const &vr=[VR::INVALID](#), [VM](#) const &vm=[VM::VM0](#), const char *desc="")
- const char * [GetDescription](#) () const
Set/Get Description.
- const char * [GetName](#) () const
Set/Get Name.
- const [VM](#) & [GetVM](#) () const
Set/Get VM.
- const [VR](#) & [GetVR](#) () const
Set/Get VR.
- bool [operator<](#) (const [CSAHeaderDictEntry](#) &entry) const
- void [SetDescription](#) (const char *desc)
- void [SetName](#) (const char *name)
- void [SetVM](#) ([VM](#) const &vm)
- void [SetVR](#) (const [VR](#) &vr)

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [CSAHeaderDictEntry](#) &_val)

25.62.1 Detailed Description

Class to represent an Entry in the [Dict](#) Does not really exist within the DICOM definition, just a way to minimize storage and have a mapping from [gdcm::Tag](#) to the needed information.

Note

bla TODO FIXME: Need a PublicCSAHeaderDictEntry...indeed [CSAHeaderDictEntry](#) has a notion of retired which does not exist in PrivateCSAHeaderDictEntry...

See Also

[gdcm::Dict](#)

Examples:

[MrProtocol.cxx](#).

25.62.2 Constructor & Destructor Documentation

25.62.2.1 `gdcm::CSAHeaderDictEntry::CSAHeaderDictEntry (const char * name = " ", VR const & vr = VR::INVALID, VM const & vm = VM::VM0, const char * desc = " ") [inline]`

25.62.3 Member Function Documentation

25.62.3.1 `const char* gdcm::CSAHeaderDictEntry::GetDescription () const [inline]`

Set/Get Description.

25.62.3.2 `const char* gdcm::CSAHeaderDictEntry::GetName () const [inline]`

Set/Get Name.

Referenced by operator<().

25.62.3.3 `const VM& gdcm::CSAHeaderDictEntry::GetVM () const [inline]`

Set/Get [VM](#).

25.62.3.4 `const VR& gdcm::CSAHeaderDictEntry::GetVR () const [inline]`

Set/Get [VR](#).

25.62.3.5 `bool gdcm::CSAHeaderDictEntry::operator< (const CSAHeaderDictEntry & entry) const [inline]`

References GetName().

25.62.3.6 `void gdcm::CSAHeaderDictEntry::SetDescription (const char * desc) [inline]`

25.62.3.7 `void gdcm::CSAHeaderDictEntry::SetName (const char * name) [inline]`

25.62.3.8 `void gdcm::CSAHeaderDictEntry::SetVM (VM const & vm) [inline]`

25.62.3.9 `void gdcm::CSAHeaderDictEntry::SetVR (const VR & vr) [inline]`

25.62.4 Friends And Related Function Documentation

25.62.4.1 `std::ostream& operator<< (std::ostream & _os, const CSAHeaderDictEntry & _val) [friend]`


The documentation for this class was generated from the following file:

- [gdcmCSAHeaderDictEntry.h](#)


25.63 gdcm::CSAHeaderDictException Class Reference

```
#include <gdcmCSAHeaderDict.h>
```

Inheritance diagram for `gdcm::CSAHeaderDictException`:



Collaboration diagram for `gdcm::CSAHeaderDictException`:



The documentation for this class was generated from the following file:


- [gdcmCSAHeaderDict.h](#)

25.64 `gdcm::network::CStoreRQ` Class Reference


`CStoreRQ` this file defines the messages for the cecho action.

```
#include <gdcmCStoreMessages.h>
```

Inheritance diagram for gdcmm::network::CStoreRQ:



Collaboration diagram for gdcmm::network::CStoreRQ:



Public Member Functions

- `std::vector`
`< PresentationDataValue > ConstructPDV (const ULConnection &inConnection, const File &file)`

25.64.1 Detailed Description

`CStoreRQ` this file defines the messages for the cecho action.

25.64.2 Member Function Documentation

- 25.64.2.1 `std::vector<PresentationDataValue> gdcmm::network::CStoreRQ::ConstructPDV (const ULConnection & inConnection, const File & file)`

The documentation for this class was generated from the following file:


- [gdcmCStoreMessages.h](#)

25.65 gdcm::network::CStoreRSP Class Reference


[CStoreRSP](#) this file defines the messages for the cecho action.

```
#include <gdcmCStoreMessages.h>
```

Inheritance diagram for `gdcm::network::CStoreRSP`:



Collaboration diagram for `gdcm::network::CStoreRSP`:



Public Member Functions

- `std::vector`
 < [PresentationDataValue](#) > [ConstructPDV](#) (const [DataSet](#) *inDataSet, const [BasePDU](#) *inPC)

25.65.1 Detailed Description

[CStoreRSP](#) this file defines the messages for the cecho action.

25.65.2 Member Function Documentation

25.65.2.1 `std::vector<PresentationDataValue> gdcm::network::CStoreRSP::ConstructPDV (const DataSet * inDataSet, const BasePDU * inPC)`

The documentation for this class was generated from the following file:


- [gdcmCStoreMessages.h](#)

25.66 gdcm::Curve Class Reference


[Curve](#) class to handle element 50xx,3000 [Curve](#) Data WARNING: This is deprecated and lastly defined in PS 3.3 - 2004.

```
#include <gdcmCurve.h>
```

Inheritance diagram for `gdcm::Curve`:



Collaboration diagram for `gdcm::Curve`:



Public Member Functions

- [Curve](#) ()
- [Curve](#) ([Curve](#) const &ov)
- [~Curve](#) ()
- void [Decode](#) (std::istream &is, std::ostream &os)
- void [GetAsPoints](#) (float *array) const
- std::vector< unsigned short >
const & [GetCurveDataDescriptor](#) () const
- unsigned short [GetDataValueRepresentation](#) () const
- unsigned short [GetDimensions](#) () const
- unsigned short [GetGroup](#) () const
- unsigned short [GetNumberOfPoints](#) () const
- const char * [GetTypeOfData](#) () const
- const char * [GetTypeOfDataDescription](#) () const
- bool [IsEmpty](#) () const
- void [Print](#) (std::ostream &) const
- void [SetCoordinateStartValue](#) (unsigned short v)
- void [SetCoordinateStepValue](#) (unsigned short v)
- void [SetCurve](#) (const char *array, unsigned int length)
- void [SetCurveDataDescriptor](#) (const uint16_t *values, size_t num)
- void [SetCurveDescription](#) (const char *curvedescription)
- void [SetDataValueRepresentation](#) (unsigned short datavaluerepresentation)
- void [SetDimensions](#) (unsigned short dimensions)
- void [SetGroup](#) (unsigned short group)
- void [SetNumberOfPoints](#) (unsigned short numberofpoints)
- void [SetTypeOfData](#) (const char *typeofdata)
- void [Update](#) (const [DataElement](#) &de)

Static Public Member Functions

- static unsigned int [GetNumberOfCurves](#) ([DataSet](#) const &ds)

Additional Inherited Members

25.66.1 Detailed Description

[Curve](#) class to handle element 50xx,3000 [Curve](#) Data WARNING: This is deprecated and lastly defined in PS 3.3 - 2004.

Examples:

- GE_DLX-8-MONO2-Multiframe-Jpeg_Lossless.dcm
- GE_DLX-8-MONO2-Multiframe.dcm
- gdcmSampleData/Philips_Medical_Images/integriss_HV_5000/xa_integriss.dcm
- TOSHIBA-CurveData[1-3].dcm

25.66.2 Constructor & Destructor Documentation

25.66.2.1 `gdcm::Curve::Curve ()`

25.66.2.2 `gdcm::Curve::~~Curve ()`

25.66.2.3 `gdcm::Curve::Curve (Curve const & ov)`

25.66.3 Member Function Documentation

25.66.3.1 `void gdcm::Curve::Decode (std::istream & is, std::ostream & os)`

25.66.3.2 `void gdcm::Curve::GetAsPoints (float * array) const`

25.66.3.3 `std::vector<unsigned short> const& gdcm::Curve::GetCurveDataDescriptor () const`

25.66.3.4 `unsigned short gdcm::Curve::GetDataValueRepresentation () const`

25.66.3.5 `unsigned short gdcm::Curve::GetDimensions () const`

25.66.3.6 `unsigned short gdcm::Curve::GetGroup () const`

25.66.3.7 `static unsigned int gdcm::Curve::GetNumberOfCurves (DataSet const & ds) [static]`

25.66.3.8 `unsigned short gdcm::Curve::GetNumberOfPoints () const`

25.66.3.9 `const char* gdcm::Curve::GetTypeOfData () const`

25.66.3.10 `const char* gdcm::Curve::GetTypeOfDataDescription () const`

25.66.3.11 `bool gdcm::Curve::IsEmpty () const`

25.66.3.12 `void gdcm::Curve::Print (std::ostream &) const [virtual]`

Reimplemented from [gdcm::Object](#).

25.66.3.13 void gdcM::Curve::SetCoordinateStartValue (unsigned short *v*)

25.66.3.14 void gdcM::Curve::SetCoordinateStepValue (unsigned short *v*)

25.66.3.15 void gdcM::Curve::SetCurve (const char * *array*, unsigned int *length*)

25.66.3.16 void gdcM::Curve::SetCurveDataDescriptor (const uint16_t * *values*, size_t *num*)

25.66.3.17 void gdcM::Curve::SetCurveDescription (const char * *curvedescription*)

25.66.3.18 void gdcM::Curve::SetDataValueRepresentation (unsigned short *datavaluerepresentation*)

25.66.3.19 void gdcM::Curve::SetDimensions (unsigned short *dimensions*)

25.66.3.20 void gdcM::Curve::SetGroup (unsigned short *group*)

25.66.3.21 void gdcM::Curve::SetNumberOfPoints (unsigned short *numberofpoints*)

25.66.3.22 void gdcM::Curve::SetTypeOfData (const char * *typeofdata*)

25.66.3.23 void gdcM::Curve::Update (const DataElement & *de*)

The documentation for this class was generated from the following file:


- [gdcMCurve.h](#)

25.67 gdcM::DataElement Class Reference


Class to represent a Data [Element](#) either Implicit or Explicit.

```
#include <gdcMDataElement.h>
```


Inheritance diagram for gdcM::DataElement:



Collaboration diagram for gdcM::DataElement:



Public Member Functions

- **DataElement** (const **Tag** &t=**Tag**(0), const **VL** &vl=0, const **VR** &vr=**VR::INVALID**)
- **DataElement** (const **DataElement** &_val)
- void **Clear** ()

*Clear Data **Element** (make **Value** empty and invalidate **Tag** & **VR**)*

- void [Empty](#) ()
 - Make Data [Element](#) empty (no [Value](#))*
- const [ByteValue](#) * [GetByteValue](#) () const
- template<typename TDE >
 - [VL](#) [GetLength](#) () const
- const [SequenceOfFragments](#) * [GetSequenceOfFragments](#) () const
- const [SequenceOfItems](#) * [GetSequenceOfItems](#) () const
- [SequenceOfItems](#) * [GetSequenceOfItems](#) ()
- const [Tag](#) & [GetTag](#) () const
 - Get [Tag](#).*
- [Tag](#) & [GetTag](#) ()
- [Value](#) const & [GetValue](#) () const
 - Set/Get [Value](#) (bytes array, SQ of items, SQ of fragments):*
- [Value](#) & [GetValue](#) ()
- [SmartPointer](#)< [SequenceOfItems](#) > [GetValueAsSQ](#) () const
- const [VL](#) & [GetVL](#) () const
 - Get [VL](#).*
- [VL](#) & [GetVL](#) ()
- [VR](#) const & [GetVR](#) () const
- bool [IsEmpty](#) () const
 - Check if Data [Element](#) is empty.*
- bool [IsUndefinedLength](#) () const
 - return if [Value](#) Length if of undefined length*
- bool [operator](#)< (const [DataElement](#) &de) const
- [DataElement](#) & [operator](#)= (const [DataElement](#) &de)
- bool [operator](#)== (const [DataElement](#) &de) const
- template<typename TDE , typename TSwap >
 - std::istream & [Read](#) (std::istream &is)
- template<typename TDE , typename TSwap >
 - std::istream & [ReadOrSkip](#) (std::istream &is, std::set< [Tag](#) > const &skiptags)
- template<typename TDE , typename TSwap >
 - std::istream & [ReadPreValue](#) (std::istream &is, std::set< [Tag](#) > const &skiptags)
- template<typename TDE , typename TSwap >
 - std::istream & [ReadValue](#) (std::istream &is, std::set< [Tag](#) > const &skiptags)
- template<typename TDE , typename TSwap >
 - std::istream & [ReadWithLength](#) (std::istream &is, [VL](#) &length)
- void [SetByteValue](#) (const char *array, [VL](#) length)
- void [SetTag](#) (const [Tag](#) &t)
- void [SetValue](#) ([Value](#) const &vl)
- void [SetVL](#) (const [VL](#) &vl)
- void [SetVLToUndefined](#) ()
- void [SetVR](#) ([VR](#) const &vr)
- template<typename TDE , typename TSwap >
 - const std::ostream & [Write](#) (std::ostream &os) const

Protected Types

- typedef [SmartPointer](#)< [Value](#) > [ValuePtr](#)

Protected Attributes

- [Tag](#) [TagField](#)
- [ValuePtr](#) [ValueField](#)
- [VL](#) [ValueLengthField](#)
- [VR](#) [VRField](#)

Friends

- `std::ostream & operator<< (std::ostream &_os, const DataElement &_val)`

25.67.1 Detailed Description

Class to represent a Data [Element](#) either Implicit or Explicit.

DATA ELEMENT: A unit of information as defined by a single entry in the data dictionary. An encoded Information [Object](#) Definition (IOD) [Attribute](#) that is composed of, at a minimum, three fields: a Data [Element](#) [Tag](#), a [Value](#) Length, and a [Value](#) Field. For some specific Transfer Syntaxes, a Data [Element](#) also contains a [VR](#) Field where the [Value](#) Representation of that Data [Element](#) is specified explicitly.

Design:

- A [DataElement](#) in GDCM always store [VL](#) ([Value](#) Length) on a 32 bits integer even when [VL](#) is 16 bits
- A [DataElement](#) always store the [VR](#) even for Implicit TS, in which case [VR](#) is defaulted to [VR::INVALID](#)
- For [Item](#) start/end (See 0xfffe tags), [Value](#) is NULL

See Also

[ExplicitDataElement](#) [ImplicitDataElement](#)

Examples:

[ChangeSequenceUltrasound.cxx](#), [CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [csa2img.cxx](#), [DiffFile.cxx](#), [DumpADAC.cxx](#), [DumpGEMSMovieGroup.cxx](#), [DumpImageHeaderInfo.cxx](#), [DuplicatePCDE.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [ExtractIconFromFile.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GenAllIVR.cxx](#), [GenFakelIdentifyFile.cxx](#), [GenFakelImage.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetJPEG-SamplePrecision.cxx](#), [GetSequenceUltrasound.cxx](#), [GetSubSequenceData.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDS-Explicit.cxx](#), [pmsct_rgb1.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [ReadExplicitLengthSQIVR.cxx](#), [ReadGEMSSDO.cxx](#), [rle2img.cxx](#), and [StreamImageReaderTest.cxx](#).

25.67.2 Member Typedef Documentation

25.67.2.1 `typedef SmartPointer<Value> gdcm::DataElement::ValuePtr [protected]`

25.67.3 Constructor & Destructor Documentation

25.67.3.1 `gdcm::DataElement::DataElement (const Tag & t = Tag (0), const VL & vl = 0, const VR & vr = VR::INVALID)`
[inline]

25.67.3.2 `gdcm::DataElement::DataElement (const DataElement & _val) [inline]`

25.67.4 Member Function Documentation

25.67.4.1 `void gdcm::DataElement::Clear () [inline]`

Clear Data [Element](#) (make [Value](#) empty and invalidate [Tag](#) & [VR](#))

References `gdcm::VR::INVALID`.

Referenced by `gdcm::Item::Clear()`.

25.67.4.2 `void gdcm::DataElement::Empty () [inline]`

Make Data [Element](#) empty (no [Value](#))

25.67.4.3 `const ByteValue* gdcm::DataElement::GetByteValue () const [inline]`

Return the [Value](#) of [DataElement](#) as a [ByteValue](#) (if possible)

Warning

: You need to check for NULL return value

Examples:

[DumpADAC.cxx](#), [DumpImageHeaderInfo.cxx](#), [DuplicatePCDE.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [ExtractIconFromFile.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GetSubSequenceData.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [ReadExplicitLengthSQIVR.cxx](#), [ReadGEMSSDO.cxx](#), and [rle2img.cxx](#).

Referenced by `gdcm::operator<<()`, `gdcm::Element< VR::OB, VM::VM1_n >::SetFromDataElement()`, `gdcm::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataElement()`, `gdcm::Element< TVR, VM::VM1_n >::SetFromDataElement()`, and `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataElement()`.

25.67.4.4 `template<typename TDE> VL gdcm::DataElement::GetLength () const [inline]`

25.67.4.5 `const SequenceOfFragments* gdcm::DataElement::GetSequenceOfFragments () const`

Return the [Value](#) of [DataElement](#) as a Sequence Of Fragments (if possible)

Warning

: You need to check for NULL return value

Examples:

[FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), and [GetJPEGSamplePrecision.cxx](#).

25.67.4.6 `const SequenceOfItems* gdcm::DataElement::GetSequenceOfItems () const`

Return the [Value](#) of [DataElement](#) as a Sequence Of Items (if possible)

Warning

: You need to check for NULL return value
 : In some case a [Value](#) could not have been recognized as a [SequenceOfItems](#) in those case the return of the function will be NULL, while the [Value](#) would be a valid [SequenceOfItems](#), in those case prefer GetValueAsSQ. In which case the code internally trigger an assert to warn developer. When in doubt do not use this function and prefer [GetValueAsSQ\(\)](#)

Deprecated Replaced by [DataElement::GetValueAsSQ\(\)](#) as of GDCM 2.2.

25.67.4.7 **SequenceOfItems*** [gdcm::DataElement::GetSequenceOfItems \(\)](#)

25.67.4.8 **const Tag&** [gdcm::DataElement::GetTag \(\) const](#) `[inline]`

Get [Tag](#).

Examples:

[DumpGEMSMovieGroup.cxx](#), [DuplicatePCDE.cxx](#), [pmsct_rgb1.cxx](#), and [rle2img.cxx](#).

Referenced by [gdcm::CommandDataSet::Insert\(\)](#), [gdcm::FileMetaInformation::Insert\(\)](#), [gdcm::DataSet::Insert\(\)](#), [operator<\(\)](#), [gdcm::SequenceOfItems::Read\(\)](#), [gdcm::SequenceOfFragments::ReadValue\(\)](#), [gdcm::CommandDataSet::Replace\(\)](#), [gdcm::FileMetaInformation::Replace\(\)](#), [gdcm::Attribute< Group, Element, TVR, TVM >::SetFromDataElement\(\)](#), [gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataElement\(\)](#), and [gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataElement\(\)](#).

25.67.4.9 **Tag&** [gdcm::DataElement::GetTag \(\)](#) `[inline]`

25.67.4.10 **Value const&** [gdcm::DataElement::GetValue \(\) const](#) `[inline]`

Set/Get [Value](#) (bytes array, SQ of items, SQ of fragments):

Examples:

[ReadAndDumpDICOMDIR.cxx](#).

Referenced by [gdcm::DataSet::InsertDataElement\(\)](#), [gdcm::Element< VR::OB, VM::VM1_n >::SetFromDataElement\(\)](#), and [gdcm::Element< TVR, VM::VM1_n >::SetFromDataElement\(\)](#).

25.67.4.11 **Value&** [gdcm::DataElement::GetValue \(\)](#) `[inline]`

25.67.4.12 **SmartPointer<SequenceOfItems>** [gdcm::DataElement::GetValueAsSQ \(\) const](#)

Interpret the [Value](#) stored in the [DataElement](#). This is more robust (but also more expensive) to call this function rather than the simplest form: [GetSequenceOfItems\(\)](#) It also return NULL when the [Value](#) is NOT of type [SequenceOfItems](#)

Warning

in case [GetSequenceOfItems\(\)](#) succeed the function return this value, otherwise it creates a new [SequenceOfItems](#), you should handle that in your case, for instance: `SmartPointer<SequenceOfItems> sqi = de.GetValueAsSQ();`

Examples:

[ChangeSequenceUltrasound.cxx](#), [DumpGEMSMovieGroup.cxx](#), [ExtractEncryptedContent.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GetSequenceUltrasound.cxx](#), [LargeVRDSExplicit.cxx](#), and [ReadAndDumpDICOMDIR.cxx](#).

25.67.4.13 `const VL& gdcm::DataElement::GetVL () const` `[inline]`

Get [VL](#).

Referenced by `gdcm::DataSet::InsertDataElement()`, `gdcm::SequenceOfItems::Read()`, and `gdcm::SequenceOfFragments::ReadValue()`.

25.67.4.14 `VL& gdcm::DataElement::GetVL ()` `[inline]`

25.67.4.15 `VR const& gdcm::DataElement::GetVR () const` `[inline]`

Get [VR](#) do not set [VR::SQ](#) on bytevalue data element

Examples:

[DuplicatePCDE.cxx](#), and [GenFakeIdentifyFile.cxx](#).

Referenced by `gdcm::Element< VR::OB, VM::VM1_n >::GetAsDataElement()`, `gdcm::Attribute< Group, Element, TVR, TVM >::GetAsDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetAsDataElement()`, `gdcm::Element< TVR, VM::VM1_n >::GetAsDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetAsDataElement()`, `gdcm::Element< VR::OB, VM::VM1_n >::SetFromDataElement()`, `gdcm::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataElement()`, `gdcm::Element< TVR, VM::VM1_n >::SetFromDataElement()`, and `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataElement()`.

25.67.4.16 `bool gdcm::DataElement::IsEmpty () const` `[inline]`

Check if Data [Element](#) is empty.

Examples:

[DumpADAC.cxx](#), [DumpGEMSMovieGroup.cxx](#), [DumpImageHeaderInfo.cxx](#), [ELSCINT1WaveToText.cxx](#), [FixJAI-BugJPEGLS.cxx](#), [pmsct_rgb1.cxx](#), and [rle2img.cxx](#).

Referenced by `gdcm::DataSet::InsertDataElement()`, `gdcm::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataElement()`, `gdcm::Attribute< Group, Element, TVR, TVM >::SetFromDataSet()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataSet()`, and `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataSet()`.

25.67.4.17 `bool gdcm::DataElement::IsUndefinedLength () const` `[inline]`

return if [Value](#) Length if of undefined length

25.67.4.18 `bool gdcm::DataElement::operator< (const DataElement & de) const` `[inline]`

References `GetTag()`.

25.67.4.19 **DataElement& gdcm::DataElement::operator= (const DataElement & de)** `[inline]`

References TagField, ValueField, ValueLengthField, and VRField.

25.67.4.20 **bool gdcm::DataElement::operator== (const DataElement & de) const** `[inline]`

References TagField, ValueField, ValueLengthField, and VRField.

25.67.4.21 **template<typename TDE , typename TSwap > std::istream& gdcm::DataElement::Read (std::istream & is)**
`[inline]`

25.67.4.22 **template<typename TDE , typename TSwap > std::istream& gdcm::DataElement::ReadOrSkip (std::istream & is, std::set< Tag > const & skiptags)** `[inline]`

25.67.4.23 **template<typename TDE , typename TSwap > std::istream& gdcm::DataElement::ReadPreValue (std::istream & is, std::set< Tag > const & skiptags)** `[inline]`

25.67.4.24 **template<typename TDE , typename TSwap > std::istream& gdcm::DataElement::ReadValue (std::istream & is, std::set< Tag > const & skiptags)** `[inline]`

25.67.4.25 **template<typename TDE , typename TSwap > std::istream& gdcm::DataElement::ReadWithLength (std::istream & is, VL & length)** `[inline]`

25.67.4.26 **void gdcm::DataElement::SetByteValue (const char * array, VL length)** `[inline]`

Set the byte value

Warning

user need to read DICOM standard for an understanding of:

- even padding
- \0 vs space padding By default even padding is achieved using \0 regardless of the of [VR](#)

Examples:

[ChangeSequenceUltrasound.cxx](#), [CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenFakeImage.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetSubSequenceData.cxx](#), [iU22tomultisc.cxx](#), and [StreamImageReaderTest.cxx](#).

Referenced by `gdcm::Element< VR::OB, VM::VM1_n >::GetAsDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetAsDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetAsDataElement()`, `gdcm::Element< TVR, VM::VM1_n >::GetAsDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetAsDataElement()`, and `gdcm::SequenceOfFragments::ReadPreValue()`.

25.67.4.27 **void gdcm::DataElement::SetTag (const Tag & t)** `[inline]`

Set [Tag](#) Use with cautious (need to match Part 6)

Examples:

[Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [GenFakeIdentifyFile.cxx](#), and [GetSubSequenceData.cxx](#).

25.67.4.28 void `gdcm::DataElement::SetValue (Value const & v/)` [`inline`]

Warning

you need to set the `ValueLengthField` explicitly

Examples:

[DuplicatePCDE.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [FixBrokenJ2K.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenLongSeqs.cxx](#), and [GenSeqs.cxx](#).

References `gdcm::Value::GetLength()`.

25.67.4.29 void `gdcm::DataElement::SetVL (const VL & v/)` [`inline`]

Set [VL](#) Use with cautious (need to match Part 6), advanced user only

See Also

[SetByteValue](#)

25.67.4.30 void `gdcm::DataElement::SetVLToUndefined ()`

Examples:

[Fake_Image_Using_Stream_Image_Writer.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenLongSeqs.cxx](#), and [GenSeqs.cxx](#).

25.67.4.31 void `gdcm::DataElement::SetVR (VR const & vr)` [`inline`]

Set [VR](#) Use with cautious (need to match Part 6), advanced user only

Precondition

`vr` is a [VR::VRALL](#) (not a dual one such as `OB_OW`)

Examples:

[Fake_Image_Using_Stream_Image_Writer.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetSubSequenceData.cxx](#), [iU22tomultisc.cxx](#), and [StreamImageReader-Test.cxx](#).

References `gdcm::VR::IsVRFile()`.

Referenced by `gdcm::Element< VR::OB, VM::VM1_n >::GetAsDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetAsDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::GetAsDataElement()`, `gdcm::Element< TVR, VM::VM1_n >::GetAsDataElement()`, and `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::GetAsDataElement()`.

25.67.4.32 `template<typename TDE , typename TSwap > const std::ostream& gdcm::DataElement::Write (std::ostream & os)
const [inline]`

25.67.5 Friends And Related Function Documentation

25.67.5.1 `std::ostream& operator<< (std::ostream & _os, const DataElement & _val) [friend]`

25.67.6 Member Data Documentation

25.67.6.1 `Tag gdcm::DataElement::TagField [protected]`

Referenced by `gdcm::operator<<()`, `operator=()`, and `operator==()`.

25.67.6.2 `ValuePtr gdcm::DataElement::ValueField [protected]`

Referenced by `gdcm::operator<<()`, `operator=()`, and `operator==()`.

25.67.6.3 `VL gdcm::DataElement::ValueLengthField [protected]`

Referenced by `gdcm::operator<<()`, `operator=()`, and `operator==()`.

25.67.6.4 `VR gdcm::DataElement::VRField [protected]`

Referenced by `gdcm::operator<<()`, `operator=()`, and `operator==()`.


The documentation for this class was generated from the following file:

- [gdcmDataElement.h](#)


25.68 gdcm::DataElementException Class Reference

```
#include <gdcmDataSet.h>
```

Inheritance diagram for `gdcm::DataElementException`:



Collaboration diagram for `gdcm::DataElementException`:



The documentation for this class was generated from the following file:


- [gdcmDataSet.h](#)

25.69 `gdcm::DataEvent` Class Reference


[DataEvent](#).

```
#include <gdcmDataEvent.h>
```

Inheritance diagram for `gdcm::DataEvent`:



Collaboration diagram for gdcm::DataEvent:



Public Types

- typedef [DataEvent](#) `Self`
- typedef [AnyEvent](#) `Superclass`

Public Member Functions

- [DataEvent](#) (`const char *bytes=0, size_t len=0`)
- [DataEvent](#) (`const Self &s`)
- virtual `~DataEvent ()`
- virtual `bool CheckEvent (const ::gdcm::Event *e) const`
- `const char * GetData () const`
- `size_t GetDataLength () const`
- virtual `const char * GetEventName () const`
- virtual `::gdcm::Event * MakeObject () const`
- void [SetData](#) (`const char *bytes, size_t len`)

25.69.1 Detailed Description

[DataEvent](#).

25.69.2 Member Typedef Documentation

25.69.2.1 typedef `DataEvent` `gdcm::DataEvent::Self`

25.69.2.2 typedef `AnyEvent` `gdcm::DataEvent::Superclass`

25.69.3 Constructor & Destructor Documentation

25.69.3.1 `gdcm::DataEvent::DataEvent (const char * bytes = 0, size_t len = 0)` `[inline]`

25.69.3.2 `virtual gdcm::DataEvent::~DataEvent ()` `[inline],[virtual]`

25.69.3.3 `gdcm::DataEvent::DataEvent (const Self & s)` `[inline]`

25.69.4 Member Function Documentation

25.69.4.1 `virtual bool gdcm::DataEvent::CheckEvent (const ::gdcm::Event * e)const` `[inline],[virtual]`

25.69.4.2 `const char* gdcm::DataEvent::GetData ()const` `[inline]`

25.69.4.3 `size_t gdcm::DataEvent::GetDataLength ()const` `[inline]`

25.69.4.4 `virtual const char* gdcm::DataEvent::GetEventName ()const` `[inline],[virtual]`

Return the StringName associated with the event.

Implements [gdcm::Event](#).

25.69.4.5 `virtual ::gdcm::Event* gdcm::DataEvent::MakeObject ()const` `[inline],[virtual]`

Create an [Event](#) of this type This method work as a Factory for creating events of each particular type.

Implements [gdcm::Event](#).

25.69.4.6 `void gdcm::DataEvent::SetData (const char * bytes, size_t len)` `[inline]`

The documentation for this class was generated from the following file:


- [gdcmDataEvent.h](#)

25.70 gdcm::DataSet Class Reference

Class to represent a Data Set (which contains Data Elements) A Data Set represents an instance of a real world Information [Object](#).

```
#include <gdcmDataSet.h>
```

Inheritance diagram for gdcm::DataSet:



Public Types

- typedef
DataElementSet::const_iterator [ConstIterator](#)
- typedef std::set< [DataElement](#) > [DataElementSet](#)
- typedef DataElementSet::iterator [Iterator](#)
- typedef DataElementSet::size_type [SizeType](#)

Public Member Functions

- [ConstIterator Begin](#) () const
- [Iterator Begin](#) ()
- void [Clear](#) ()
- template<typename TDE >
unsigned int [ComputeGroupLength](#) ([Tag](#) const &tag) const
- [ConstIterator End](#) () const
- [Iterator End](#) ()
- bool [FindDataElement](#) (const [PrivateTag](#) &t) const
Look up if private tag 't' is present in the dataset:
- bool [FindDataElement](#) (const [Tag](#) &t) const
- const [DataElement](#) & [FindNextDataElement](#) (const [Tag](#) &t) const
- const [DataElement](#) & [GetDataElement](#) (const [Tag](#) &t) const
- const [DataElement](#) & [GetDataElement](#) (const [PrivateTag](#) &t) const
Return the dataelement.
- const [DataElementSet](#) & [GetDES](#) () const
- [DataElementSet](#) & [GetDES](#) ()
- template<typename TDE >
[VL GetLength](#) () const
- [MediaStorage GetMediaStorage](#) () const
- std::string [GetPrivateCreator](#) (const [Tag](#) &t) const
Return the private creator of the private tag 't':
- void [Insert](#) (const [DataElement](#) &de)
- bool [IsEmpty](#) () const
Returns if the dataset is empty.

- const [DataElement](#) & [operator\(\)](#) (uint16_t group, uint16_t element) const
- [DataSet](#) & [operator=](#) ([DataSet](#) const &val)
- const [DataElement](#) & [operator\[\]](#) (const [Tag](#) &t) const
- void [Print](#) (std::ostream &os, std::string const &indent="") const
- template<typename TDE , typename TSwap >
std::istream & [Read](#) (std::istream &is)
- template<typename TDE , typename TSwap >
std::istream & [ReadNested](#) (std::istream &is)
- template<typename TDE , typename TSwap >
std::istream & [ReadSelectedTags](#) (std::istream &is, const std::set< [Tag](#) > &tags)
- template<typename TDE , typename TSwap >
std::istream & [ReadSelectedTagsWithLength](#) (std::istream &is, const std::set< [Tag](#) > &tags, [VL](#) &length)
- template<typename TDE , typename TSwap >
std::istream & [ReadUpToTag](#) (std::istream &is, const [Tag](#) &t, std::set< [Tag](#) > const &skiptags)
- template<typename TDE , typename TSwap >
std::istream & [ReadUpToTagWithLength](#) (std::istream &is, const [Tag](#) &t, [VL](#) &length)
- template<typename TDE , typename TSwap >
std::istream & [ReadWithLength](#) (std::istream &is, [VL](#) &length)
- [SizeType Remove](#) (const [Tag](#) &tag)
Completely remove a dataelement from the dataset.
- void [Replace](#) (const [DataElement](#) &de)
Replace a dataelement with another one.
- void [ReplaceEmpty](#) (const [DataElement](#) &de)
Only replace a DICOM attribute when it is missing or empty.
- [SizeType Size](#) () const
- template<typename TDE , typename TSwap >
std::ostream const & [Write](#) (std::ostream &os) const

Protected Member Functions

- [Tag ComputeDataElement](#) (const [PrivateTag](#) &t) const
- const [DataElement](#) & [GetDEEnd](#) () const
- void [InsertDataElement](#) (const [DataElement](#) &de)

Friends

- class [CSAHeader](#)
- std::ostream & [operator<<](#) (std::ostream &_os, const [DataSet](#) &val)

25.70.1 Detailed Description

Class to represent a Data Set (which contains Data Elements) A Data Set represents an instance of a real world Information [Object](#).

Note

DATA SET: Exchanged information consisting of a structured set of [Attribute](#) values directly or indirectly related to Information Objects. The value of each [Attribute](#) in a Data Set is expressed as a Data [Element](#). A collection of Data Elements ordered by increasing Data [Element Tag](#) number that is an encoding of the values of Attributes of a real world object.

Implementation note. If one do: [DataSet](#) ds; ds.SetLength(0); ds.Read(is); setting length to 0 actually means try to read is as if it was a root [DataSet](#). Other value are undefined (nested dataset with undefined length) or defined length (different from 0) means nested dataset with defined length.

Warning

a [DataSet](#) does not have a Transfer Syntax type, only a [File](#) does.

Examples:

[ChangeSequenceUltrasound.cxx](#), [CreateJPIPDataSet.cxx](#), [csa2img.cxx](#), [DiffFile.cxx](#), [DumpADAC.cxx](#), [DumpGEMSMovieGroup.cxx](#), [DumpImageHeaderInfo.cxx](#), [DuplicatePCDE.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetJPEGSamplePrecision.cxx](#), [GetSequenceUltrasound.cxx](#), [GetSubSequenceData.cxx](#), [HelloWorld.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDSExplicit.cxx](#), [MergeTwoFiles.cxx](#), [MrProtocol.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [ReadAndPrintAttributes.cxx](#), [ReadExplicitLengthSQIVR.cxx](#), [ReadGEMSSDO.cxx](#), [rle2img.cxx](#), [SortImage.cxx](#), [StreamImageReaderTest.cxx](#), and [VolumeSorter.cxx](#).

25.70.2 Member Typedef Documentation

25.70.2.1 `typedef DataSet::const_iterator gdcm::DataSet::ConstIterator`

25.70.2.2 `typedef std::set<DataElement> gdcm::DataSet::DataElementSet`

25.70.2.3 `typedef DataSet::iterator gdcm::DataSet::Iterator`

25.70.2.4 `typedef DataSet::size_type gdcm::DataSet::SizeType`

25.70.3 Member Function Documentation

25.70.3.1 `ConstIterator DataSet::Begin () const [inline]`

Examples:

[DiffFile.cxx](#), [DumpGEMSMovieGroup.cxx](#), and [DuplicatePCDE.cxx](#).

25.70.3.2 `Iterator DataSet::Begin () [inline]`

25.70.3.3 `void DataSet::Clear () [inline]`

Referenced by `gdcm::Item::Read()`.

25.70.3.4 `Tag DataSet::ComputeDataElement (const PrivateTag & t) const [protected]`

25.70.3.5 `template<typename TDE > unsigned int gdcm::DataSet::ComputeGroupLength (Tag const & tag) const` `[inline]`

References `gdcm::Tag::GetElement()`, and `gdcm::Tag::GetGroup()`.

25.70.3.6 `ConstIterator gdcm::DataSet::End () const` `[inline]`

Examples:

[DiffFile.cxx](#), [DumpGEMSMovieGroup.cxx](#), and [DuplicatePCDE.cxx](#).

25.70.3.7 `Iterator gdcm::DataSet::End ()` `[inline]`

25.70.3.8 `bool gdcm::DataSet::FindDataElement (const PrivateTag & t) const`

Look up if private tag 't' is present in the dataset:

Examples:

[ChangeSequenceUltrasound.cxx](#), [csa2img.cxx](#), [DumpADAC.cxx](#), [DumpGEMSMovieGroup.cxx](#), [DumpImage-HeaderInfo.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GetSequenceUltrasound.cxx](#), [GetSubSequenceData.cxx](#), [LargeVRDSExplicit.cxx](#), [MrProtocol.cxx](#), [pmsct_rgb1.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [ReadAndPrintAttributes.cxx](#), [ReadGEMSSDO.cxx](#), and [rle2img.cxx](#).

Referenced by `gdcm::Attribute< Group, Element, TVR, TVM >::SetFromDataSet()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataSet()`, and `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataSet()`.

25.70.3.9 `bool gdcm::DataSet::FindDataElement (const Tag & t) const` `[inline]`

25.70.3.10 `const DataElement& gdcm::DataSet::FindNextDataElement (const Tag & t) const` `[inline]`

Examples:

[DuplicatePCDE.cxx](#).

25.70.3.11 `const DataElement& gdcm::DataSet::GetDataElement (const Tag & t) const` `[inline]`

Return the [DataElement](#) with Tag 't'

Warning

: This only search at the 'root level' of the [DataSet](#)

Examples:

[ChangeSequenceUltrasound.cxx](#), [csa2img.cxx](#), [DumpADAC.cxx](#), [DumpGEMSMovieGroup.cxx](#), [DumpImage-HeaderInfo.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GetJPEGSamplePrecision.cxx](#), [GetSequenceUltrasound.cxx](#), [GetSubSequenceData.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDSExplicit.cxx](#), [MrProtocol.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [ReadExplicitLengthSQIVR.cxx](#), [ReadGEMSSDO.cxx](#), and [rle2img.cxx](#).

Referenced by `gdcmm::Attribute< Group, Element, TVR, TVM >::Set()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::Set()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::Set()`, `gdcmm::Attribute< Group, Element, TVR, TVM >::SetFromDataSet()`, `gdcmm::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataSet()`, and `gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataSet()`.

25.70.3.12 `const DataElement& gdcmm::DataSet::GetDataElement (const PrivateTag & t) const`

Return the dataelement.

25.70.3.13 `const DataElement& gdcmm::DataSet::GetDEEnd () const` `[protected]`

25.70.3.14 `const DataElementSet& gdcmm::DataSet::GetDES () const` `[inline]`

Examples:

[ReadAndDumpDICOMDIR.cxx](#).

25.70.3.15 `DataElementSet& gdcmm::DataSet::GetDES ()` `[inline]`

25.70.3.16 `template<typename TDE > VL gdcmm::DataSet::GetLength () const` `[inline]`

25.70.3.17 `MediaStorage gdcmm::DataSet::GetMediaStorage () const`

25.70.3.18 `std::string gdcmm::DataSet::GetPrivateCreator (const Tag & t) const`

Return the private creator of the private tag 't':

Examples:

[DuplicatePCDE.cxx](#).

25.70.3.19 `void gdcmm::DataSet::Insert (const DataElement & de)` `[inline]`

Insert a [DataElement](#) in the [DataSet](#).

Warning

: [Tag](#) need to be $\geq 0x8$ to be considered valid data element

Examples:

[CreateJIPIDDataSet.cxx](#), [DuplicatePCDE.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [GenAllIVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), and [StreamImageReader-Test.cxx](#).

References `gdcmmErrorMacro`, `gdcmm::Tag::GetGroup()`, and `gdcmm::DataElement::GetTag()`.

25.70.3.20 `void gdcmm::DataSet::InsertDataElement (const DataElement & de)` `[inline]`, `[protected]`

References `gdcmmWarningMacro`, `gdcmm::Value::GetLength()`, `gdcmm::DataElement::GetValue()`, `gdcmm::DataElement::GetVL()`, and `gdcmm::DataElement::IsEmpty()`.

25.70.3.21 `bool gdcmm::DataSet::IsEmpty () const [inline]`

Returns if the dataset is empty.

Referenced by `gdcmm::Item::Read()`.

25.70.3.22 `const DataElement& gdcmm::DataSet::operator() (uint16_t group, uint16_t element) const [inline]`

25.70.3.23 `DataSet& gdcmm::DataSet::operator= (DataSet const & val) [inline]`

25.70.3.24 `const DataElement& gdcmm::DataSet::operator[] (const Tag & t) const [inline]`

25.70.3.25 `void gdcmm::DataSet::Print (std::ostream & os, std::string const & indent = " ") const [inline]`

Referenced by `gdcmm::operator<<()`.

25.70.3.26 `template<typename TDE , typename TSwap > std::istream& gdcmm::DataSet::Read (std::istream & is)`

25.70.3.27 `template<typename TDE , typename TSwap > std::istream& gdcmm::DataSet::ReadNested (std::istream & is)`

25.70.3.28 `template<typename TDE , typename TSwap > std::istream& gdcmm::DataSet::ReadSelectedTags (std::istream & is, const std::set< Tag > & tags)`

25.70.3.29 `template<typename TDE , typename TSwap > std::istream& gdcmm::DataSet::ReadSelectedTagsWithLength (std::istream & is, const std::set< Tag > & tags, VL & length)`

25.70.3.30 `template<typename TDE , typename TSwap > std::istream& gdcmm::DataSet::ReadUpToTag (std::istream & is, const Tag & t, std::set< Tag > const & skiptags)`

25.70.3.31 `template<typename TDE , typename TSwap > std::istream& gdcmm::DataSet::ReadUpToTagWithLength (std::istream & is, const Tag & t, VL & length)`

25.70.3.32 `template<typename TDE , typename TSwap > std::istream& gdcmm::DataSet::ReadWithLength (std::istream & is, VL & length)`

25.70.3.33 `SizeType gdcmm::DataSet::Remove (const Tag & tag) [inline]`

Completely remove a dataelement from the dataset.

Examples:

[GenFakeIdentifyFile.cxx](#), [LargeVRDSExplicit.cxx](#), [MergeTwoFiles.cxx](#), [pmsct_rgb1.cxx](#), and [rle2img.cxx](#).

25.70.3.34 `void gdcmm::DataSet::Replace (const DataElement & de) [inline]`

Replace a dataelement with another one.

Examples:

[ChangeSequenceUltrasound.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GenFakeIdentifyFile.cxx](#), [Hello-World.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDSExplicit.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), and [rle2img.cxx](#).

25.70.3.35 `void gdcm::DataSet::ReplaceEmpty (const DataElement & de)` `[inline]`

Only replace a DICOM attribute when it is missing or empty.

25.70.3.36 `SizeType gdcm::DataSet::Size () const` `[inline]`

Examples:

[DumpGEMSMovieGroup.cxx](#).

Referenced by `gdcm::SequenceOfItems::Read()`.

25.70.3.37 `template<typename TDE , typename TSwap > std::ostream const& gdcm::DataSet::Write (std::ostream & os) const`

25.70.4 Friends And Related Function Documentation

25.70.4.1 `friend class CSAHeader` `[friend]`

25.70.4.2 `std::ostream& operator<< (std::ostream & _os, const DataSet & val)` `[friend]`

The documentation for this class was generated from the following file:


- [gdcmDataSet.h](#)

25.71 gdcm::DataSetEvent Class Reference


[DataSetEvent](#) Special type of event triggered during the [DataSet](#) store/move process.

```
#include <gdcmDataSetEvent.h>
```

Inheritance diagram for `gdcm::DataSetEvent`:



Collaboration diagram for `gdcm::DataSetEvent`:



Public Types

- typedef [DataSetEvent](#) `Self`
- typedef [AnyEvent](#) `Superclass`

Public Member Functions

- [DataSetEvent](#) ([DataSet](#) const *ds=NULL)
- [DataSetEvent](#) (const [Self](#) &s)
- virtual [~DataSetEvent](#) ()
- virtual bool [CheckEvent](#) (const ::[gdcm::Event](#) *e) const
- [DataSet](#) const & [GetDataSet](#) () const
- virtual const char * [GetEventName](#) () const
- virtual ::[gdcm::Event](#) * [MakeObject](#) () const

25.71.1 Detailed Description

[DataSetEvent](#) Special type of event triggered during the [DataSet](#) store/move process.

See Also

25.71.2 Member Typedef Documentation

25.71.2.1 typedef `DataSetEvent` `gdcm::DataSetEvent::Self`

25.71.2.2 typedef `AnyEvent` `gdcm::DataSetEvent::Superclass`

25.71.3 Constructor & Destructor Documentation

25.71.3.1 `gdcm::DataSetEvent::DataSetEvent (DataSet const * ds = NULL)` `[inline]`

25.71.3.2 `virtual gdcm::DataSetEvent::~~DataSetEvent ()` `[inline], [virtual]`

25.71.3.3 `gdcm::DataSetEvent::DataSetEvent (const Self & s)` `[inline]`

25.71.4 Member Function Documentation

25.71.4.1 `virtual bool gdcm::DataSetEvent::CheckEvent (const ::gdcm::Event * e) const` `[inline], [virtual]`

25.71.4.2 `DataSet const& gdcm::DataSetEvent::GetDataSet () const` `[inline]`

25.71.4.3 `virtual const char* gdcm::DataSetEvent::GetEventName () const` `[inline], [virtual]`

Return the StringName associated with the event.

Implements [gdcm::Event](#).

25.71.4.4 `virtual ::gdcm::Event* gdcm::DataSetEvent::MakeObject () const` `[inline], [virtual]`

Create an [Event](#) of this type This method work as a Factory for creating events of each particular type.

Implements [gdcm::Event](#).

The documentation for this class was generated from the following file:

- [gdcmDataSetEvent.h](#)

25.72 gdcm::DataSetHelper Class Reference

[DataSetHelper](#) (internal class, not intended for user level)

```
#include <gdcmDataSetHelper.h>
```

Static Public Member Functions

- static [VR ComputeVR](#) ([File](#) const &file, [DataSet](#) const &ds, const [Tag](#) &tag)

25.72.1 Detailed Description

[DataSetHelper](#) (internal class, not intended for user level)

25.72.2 Member Function Documentation

25.72.2.1 `static VR gdcm::DataSetHelper::ComputeVR (File const & file, DataSet const & ds, const Tag & tag)` `[static]`

ds -> current dataset, which is not the same as the root dataset return [VR::INVALID](#) in case of error

The documentation for this class was generated from the following file:


- [gdcmDataSetHelper.h](#)

25.73 gdcm::Decoder Class Reference

[Decoder.](#)

```
#include <gdcmDecoder.h>
```

Inheritance diagram for gdcm::Decoder:



Public Member Functions

- virtual [~Decoder](#) ()
- virtual bool [CanDecode](#) ([TransferSyntax](#) const &) const =0
Return whether this decoder support this transfer syntax (can decode it)
- virtual bool [Decode](#) ([DataElement](#) const &, [DataElement](#) &)
Decode.

Protected Member Functions

- virtual bool [DecodeByStreams](#) (std::istream &, std::ostream &)

25.73.1 Detailed Description

[Decoder.](#)

25.73.2 Constructor & Destructor Documentation

25.73.2.1 virtual gdcm::Decoder::~~Decoder () [inline], [virtual]

25.73.3 Member Function Documentation

25.73.3.1 `virtual bool gdcm::Decoder::CanDecode (TransferSyntax const &) const` `[pure virtual]`

Return whether this decoder support this transfer syntax (can decode it)

Implemented in [gdcm::JPEGCodec](#), [gdcm::RLECodec](#), [gdcm::PVRGCodec](#), [gdcm::JPEG2000Codec](#), [gdcm::ImageCodec](#), [gdcm::JPEGLSCodec](#), [gdcm::PNMCodec](#), [gdcm::RAWCodec](#), [gdcm::AudioCodec](#), [gdcm::PDFCodec](#), [gdcm::PGXCodec](#), and [gdcm::KAKADUCodec](#).

25.73.3.2 `virtual bool gdcm::Decoder::Decode (DataElement const & , DataElement &)` `[inline],[virtual]`

Decode.

Reimplemented in [gdcm::JPEGCodec](#), [gdcm::RLECodec](#), [gdcm::JPEGLSCodec](#), [gdcm::PVRGCodec](#), [gdcm::JPEG2000Codec](#), [gdcm::ImageCodec](#), [gdcm::DeltaEncodingCodec](#), [gdcm::KAKADUCodec](#), [gdcm::RAWCodec](#), [gdcm::AudioCodec](#), and [gdcm::PDFCodec](#).

25.73.3.3 `virtual bool gdcm::Decoder::DecodeByStreams (std::istream & , std::ostream &)` `[inline],[protected],[virtual]`

Reimplemented in [gdcm::JPEGCodec](#), [gdcm::JPEG2000Codec](#), [gdcm::RLECodec](#), [gdcm::ImageCodec](#), [gdcm::RAWCodec](#), [gdcm::JPEG12Codec](#), [gdcm::JPEG16Codec](#), and [gdcm::JPEG8Codec](#).

The documentation for this class was generated from the following file:

- [gdcmDecoder.h](#)

25.74 gdcm::DefinedTerms Class Reference

Defined Terms are used when the specified explicit Values may be extended by implementors to include additional new Values. These new Values shall be specified in the Conformance Statement (see PS 3.2) and shall not have the same meaning as currently defined Values in this standard. A Data [Element](#) with Defined Terms that does not contain a [Value](#) equivalent to one of the Values currently specified in this standard shall not be considered to have an invalid value. Note: Interpretation [Type](#) ID (4008,0210) is an example of a Data [Element](#) having Defined Terms. It is defined to have a [Value](#) that may be one of the set of standard Values; REPORT or AMENDMENT (see PS 3.3). Because this Data [Element](#) has Defined Terms other Interpretation [Type](#) IDs may be defined by the implementor.

```
#include <gdcmDefinedTerms.h>
```

Public Member Functions

- [DefinedTerms](#) ()

25.74.1 Detailed Description

Defined Terms are used when the specified explicit Values may be extended by implementors to include additional new Values. These new Values shall be specified in the Conformance Statement (see PS 3.2) and shall not have the same meaning as currently defined Values in this standard. A Data [Element](#) with Defined Terms that does not contain a [Value](#) equivalent to one of the Values currently specified in this standard shall not be considered to have an invalid value. Note: Interpretation [Type](#) ID (4008,0210) is an example of a Data [Element](#) having Defined Terms. It is defined to have a [Value](#)

that may be one of the set of standard Values; REPORT or AMENDMENT (see PS 3.3). Because this Data [Element](#) has Defined Terms other Interpretation [Type](#) IDs may be defined by the implementor.

25.74.2 Constructor & Destructor Documentation

25.74.2.1 `gdcm::DefinedTerms::DefinedTerms () [inline]`

The documentation for this class was generated from the following file:

- [gdcmDefinedTerms.h](#)

25.75 `gdcm::Defs` Class Reference

FIXME I do not like the name '[Defs](#)'.

```
#include <gdcmDefs.h>
```

Public Member Functions

- [Defs](#) ()
- [~Defs](#) ()
- const [IOD](#) & [GetIODFromFile](#) (const [File](#) &file) const
- const [IODs](#) & [GetIODs](#) () const
- [IODs](#) & [GetIODs](#) ()
- const [Macros](#) & [GetMacros](#) () const
- [Macros](#) & [GetMacros](#) ()
- const [Modules](#) & [GetModules](#) () const
- [Modules](#) & [GetModules](#) ()
- [Type](#) [GetTypeFromTag](#) (const [File](#) &file, const [Tag](#) &tag) const
- bool [IsEmpty](#) () const
- bool [Verify](#) (const [File](#) &file) const
- bool [Verify](#) (const [DataSet](#) &ds) const

Static Public Member Functions

- static const char * [GetIODNameFromMediaStorage](#) ([MediaStorage](#) const &ms)

Protected Member Functions

- void [LoadDefaults](#) ()
- void [LoadFromFile](#) (const char *filename)

Friends

- class [Global](#)

25.75.1 Detailed Description

FIXME I do not like the name '[Defs](#)'.

Note

bla

Examples:

[GenerateStandardSOPClasses.cxx](#), and [TraverseModules.cxx](#).

25.75.2 Constructor & Destructor Documentation

25.75.2.1 `gdcm::Defs::Defs ()`

25.75.2.2 `gdcm::Defs::~~Defs ()`

25.75.3 Member Function Documentation

25.75.3.1 `const IOD& gdcm::Defs::GetIODFromFile (const File & file) const`

25.75.3.2 `static const char* gdcm::Defs::GetIODNameFromMediaStorage (MediaStorage const & ms) [static]`

Examples:

[GenerateStandardSOPClasses.cxx](#).

25.75.3.3 `const IODs& gdcm::Defs::GetIODs () const [inline]`

25.75.3.4 `IODs& gdcm::Defs::GetIODs () [inline]`

25.75.3.5 `const Macros& gdcm::Defs::GetMacros () const [inline]`

Users should not directly use [Macro](#). [Macro](#) are simply a way for DICOM WG to re-use Tables. [Macros](#) are conveniently wrapped within [Modules](#). See [gdcm::Module](#) API directly

25.75.3.6 `Macros& gdcm::Defs::GetMacros () [inline]`

25.75.3.7 `const Modules& gdcm::Defs::GetModules () const [inline]`

25.75.3.8 `Modules& gdcm::Defs::GetModules () [inline]`

25.75.3.9 `Type gdcm::Defs::GetTypeFromTag (const File & file, const Tag & tag) const`

25.75.3.10 `bool gdcm::Defs::IsEmpty () const [inline]`

25.75.3.11 `void gdcm::Defs::LoadDefaults () [protected]`

25.75.3.12 `void gdcm::Defs::LoadFromFile (const char * filename) [protected]`

25.75.3.13 `bool gdcM::Defs::Verify (const File & file) const`

25.75.3.14 `bool gdcM::Defs::Verify (const DataSet & ds) const`

25.75.4 Friends And Related Function Documentation

25.75.4.1 `friend class Global` [*friend*]

The documentation for this class was generated from the following file:


- [gdcMDefs.h](#)

25.76 gdcM::DeltaEncodingCodec Class Reference


[DeltaEncodingCodec](#) compression used by some private vendor.

```
#include <gdcMDeltaEncodingCodec.h>
```

Inheritance diagram for gdcM::DeltaEncodingCodec:



Collaboration diagram for gdcm::DeltaEncodingCodec:



Public Member Functions

- [DeltaEncodingCodec](#) ()
- [~DeltaEncodingCodec](#) ()
- bool [CanDecode](#) ([TransferSyntax](#) const &ts)
- bool [Decode](#) ([DataElement](#) const &is, [DataElement](#) &os)

Decode.

Protected Member Functions

- bool [Decode](#) (std::istream &is, std::ostream &os)

Additional Inherited Members

25.76.1 Detailed Description

[DeltaEncodingCodec](#) compression used by some private vendor.

25.76.2 Constructor & Destructor Documentation

25.76.2.1 [gdcm::DeltaEncodingCodec::DeltaEncodingCodec](#) ()

25.76.2.2 [gdcm::DeltaEncodingCodec::~~DeltaEncodingCodec](#) ()

25.76.3 Member Function Documentation

25.76.3.1 bool [gdcm::DeltaEncodingCodec::CanDecode](#) ([TransferSyntax](#) const &ts)

25.76.3.2 bool [gdcm::DeltaEncodingCodec::Decode](#) ([DataElement](#) const &, [DataElement](#) &) [virtual]

Decode.

Reimplemented from [gdcm::Decoder](#).

25.76.3.3 `bool gdcm::DeltaEncodingCodec::Decode (std::istream & is, std::ostream & os)` [protected]

The documentation for this class was generated from the following file:

- [gdcmDeltaEncodingCodec.h](#)

25.77 gdcm::DICOMDIR Class Reference

[DICOMDIR](#) class.

```
#include <gdcmDICOMDIR.h>
```

Public Member Functions

- [DICOMDIR](#) ()
- [DICOMDIR](#) (const [FileSet](#) &fs)

25.77.1 Detailed Description

[DICOMDIR](#) class.

Structured for handling [DICOMDIR](#)

25.77.2 Constructor & Destructor Documentation

25.77.2.1 `gdcm::DICOMDIR::DICOMDIR ()` [inline]

25.77.2.2 `gdcm::DICOMDIR::DICOMDIR (const FileSet & fs)` [inline]

The documentation for this class was generated from the following file:

- [gdcmDICOMDIR.h](#)

25.78 gdcm::DICOMDIRGenerator Class Reference

[DICOMDIRGenerator](#) class This is a STD-GEN-CD [DICOMDIR](#) generator. ref: PS 3.11-2008 Annex D (Normative) - General Purpose CD-R and DVD Interchange Profiles.

```
#include <gdcmDICOMDIRGenerator.h>
```

Public Types

- typedef [Directory::FileNamesType](#) [FileNamesType](#)
- typedef [Directory::FilenameType](#) [FilenameType](#)

Public Member Functions

- [DICOMDIRGenerator](#) ()
- [~DICOMDIRGenerator](#) ()
- bool [Generate](#) ()
Main function to generate the [DICOMDIR](#).
- [File](#) & [GetFile](#) ()
- void [SetDescriptor](#) (const char *d)
- void [SetFile](#) (const [File](#) &f)
Set/Get file. The [DICOMDIR](#) file will be valid once a call to Generate has been done.
- void [SetFilenames](#) ([FilenamesType](#) const &fns)
Set the list of filenames from which the [DICOMDIR](#) should be generated from.
- void [SetRootDirectory](#) ([FilenameType](#) const &root)
Set the root directory from which the filenames should be considered.

Protected Member Functions

- bool [AddImageDirectoryRecord](#) ()
- bool [AddPatientDirectoryRecord](#) ()
- bool [AddSeriesDirectoryRecord](#) ()
- bool [AddStudyDirectoryRecord](#) ()
- [Scanner](#) & [GetScanner](#) ()

25.78.1 Detailed Description

[DICOMDIRGenerator](#) class This is a STD-GEN-CD [DICOMDIR](#) generator. ref: PS 3.11-2008 Annex D (Normative) - General Purpose CD-R and DVD Interchange Profiles.

Note

PS 3.11 - 2008 / D.3.2 Physical Medium And Medium Format The STD-GEN-CD and STD-GEN-SEC-CD application profiles require the 120 mm CD-R physical medium with the ISO/IEC 9660 Media Format, as defined in PS3.12. See also PS 3.12 - 2008 / Annex F 120mm CD-R Medium (Normative) and PS 3.10 - 2008 / 8 DICOM [File](#) Service / 8.1 FILE-SET

Warning

: PS 3.11 - 2008 / D.3.1 SOP Classes and Transfer Syntaxes Composite [Image](#) & Stand-alone Storage are required to be stored as Explicit [VR](#) Little Endian Uncompressed (1.2.840.10008.1.2.1). When a DICOM file is found using another Transfer Syntax the generator will simply stops.

- Input files should be Explicit [VR](#) Little Endian
- filenames should be valid [VR::CS](#) value (16 bytes, upper case ...)

Bug : There is a current limitation of not handling Referenced SOP Class UID / Referenced SOP Instance UID simply because the [gdcm::Scanner](#) does not allow us See PS 3.11 / [Table](#) D.3-2 STD-GEN Additional [DICOMDIR](#) Keys

25.78.2 Member Typedef Documentation

25.78.2.1 `typedef Directory::FilenameType gdcm::DICOMDIRGenerator::FilenameType`

25.78.2.2 `typedef Directory::FilenameType gdcm::DICOMDIRGenerator::FilenameType`

25.78.3 Constructor & Destructor Documentation

25.78.3.1 `gdcm::DICOMDIRGenerator::DICOMDIRGenerator ()`

25.78.3.2 `gdcm::DICOMDIRGenerator::~~DICOMDIRGenerator ()`

25.78.4 Member Function Documentation

25.78.4.1 `bool gdcm::DICOMDIRGenerator::AddImageDirectoryRecord ()` [protected]

25.78.4.2 `bool gdcm::DICOMDIRGenerator::AddPatientDirectoryRecord ()` [protected]

25.78.4.3 `bool gdcm::DICOMDIRGenerator::AddSeriesDirectoryRecord ()` [protected]

25.78.4.4 `bool gdcm::DICOMDIRGenerator::AddStudyDirectoryRecord ()` [protected]

25.78.4.5 `bool gdcm::DICOMDIRGenerator::Generate ()`

Main function to generate the [DICOMDIR](#).

25.78.4.6 `File& gdcm::DICOMDIRGenerator::GetFile ()`

25.78.4.7 `Scanner& gdcm::DICOMDIRGenerator::GetScanner ()` [protected]

25.78.4.8 `void gdcm::DICOMDIRGenerator::SetDescriptor (const char * d)`

Set the [File](#) Set ID.

Warning

 this need to be a valid [VR::CS](#) value

25.78.4.9 `void gdcm::DICOMDIRGenerator::SetFile (const File & f)`

Set/Get file. The [DICOMDIR](#) file will be valid once a call to Generate has been done.

25.78.4.10 `void gdcm::DICOMDIRGenerator::SetFilenames (FilenameType const & fns)`

Set the list of filenames from which the [DICOMDIR](#) should be generated from.

25.78.4.11 `void gdcm::DICOMDIRGenerator::SetRootDirectory (FilenameType const & root)`

Set the root directory from which the filenames should be considered.

The documentation for this class was generated from the following file:

- [gdcmDICOMDIRGenerator.h](#)

25.79 gdcm::Dict Class Reference

Class to represent a map of [DictEntry](#).

```
#include <gdcmDict.h>
```

Public Types

- typedef MapDictEntry::const_iterator [ConstIterator](#)
- typedef MapDictEntry::iterator [Iterator](#)
- typedef std::map< [Tag](#), [DictEntry](#) > [MapDictEntry](#)

Public Member Functions

- [Dict](#) ()
- void [AddDictEntry](#) (const [Tag](#) &tag, const [DictEntry](#) &de)
- [ConstIterator](#) [Begin](#) () const
- [ConstIterator](#) [End](#) () const
- const [DictEntry](#) & [GetDictEntry](#) (const [Tag](#) &tag) const
- const [DictEntry](#) & [GetDictEntryByKeyword](#) (const char *keyword, [Tag](#) &tag) const
- const [DictEntry](#) & [GetDictEntryByName](#) (const char *name, [Tag](#) &tag) const
- const char * [GetKeywordFromTag](#) ([Tag](#) const &tag) const
Function to return the Keyword from a [Tag](#).
- bool [IsEmpty](#) () const

Protected Member Functions

- void [LoadDefault](#) ()

Friends

- class [Dicts](#)
- std::ostream & [operator<<](#) (std::ostream &_os, const [Dict](#) &_val)

25.79.1 Detailed Description

Class to represent a map of [DictEntry](#).

Note

bla TODO FIXME: For [Element](#) == 0x0 need to return Name = Group Length ValueRepresentation = UL Value-Multiplicity = 1

Examples:

[GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [PublicDict.cxx](#), and [ReadAndPrintAttributes.cxx](#).

25.79.2 Member Typedef Documentation

25.79.2.1 `typedef MapDictEntry::const_iterator gdcmm::Dict::ConstIterator`

25.79.2.2 `typedef MapDictEntry::iterator gdcmm::Dict::Iterator`

25.79.2.3 `typedef std::map<Tag, DictEntry> gdcmm::Dict::MapDictEntry`

25.79.3 Constructor & Destructor Documentation

25.79.3.1 `gdcmm::Dict::Dict () [inline]`

25.79.4 Member Function Documentation

25.79.4.1 `void gdcmm::Dict::AddDictEntry (const Tag & tag, const DictEntry & de) [inline]`

25.79.4.2 `ConstIterator gdcmm::Dict::Begin () const [inline]`

Examples:

[GenAllVR.cxx](#), and [GenFakeIdentifyFile.cxx](#).

25.79.4.3 `ConstIterator gdcmm::Dict::End () const [inline]`

Examples:

[GenAllVR.cxx](#), and [GenFakeIdentifyFile.cxx](#).

25.79.4.4 `const DictEntry& gdcmm::Dict::GetDictEntry (const Tag & tag) const [inline]`

Examples:

[GenFakeIdentifyFile.cxx](#), and [PublicDict.cxx](#).

25.79.4.5 `const DictEntry& gdcmm::Dict::GetDictEntryByKeyword (const char * keyword, Tag & tag) const [inline]`

Lookup [DictEntry](#) by keyword. Even if DICOM standard defines keyword as being unique. The lookup table is built on [Tag](#). Therefore looking up a [DictEntry](#) by Keyword is more inefficient than looking up by [Tag](#).

25.79.4.6 `const DictEntry& gdcmm::Dict::GetDictEntryByName (const char * name, Tag & tag) const [inline]`

Inefficient way of looking up tag by name. Technically DICOM does not guarantee uniqueness (and [Curve](#) / [Overlay](#) are there to prove it). But most of the time name is in fact unique and can be uniquely link to a tag

Examples:

[ReadAndPrintAttributes.cxx](#).

25.79.4.7 `const char* gdcm::Dict::GetKeywordFromTag (Tag const & tag) const` `[inline]`

Function to return the Keyword from a [Tag](#).

25.79.4.8 `bool gdcm::Dict::IsEmpty () const` `[inline]`

Referenced by `gdcm::Dicts::IsEmpty()`.

25.79.4.9 `void gdcm::Dict::LoadDefault ()` `[protected]`

25.79.5 Friends And Related Function Documentation

25.79.5.1 `friend class Dicts` `[friend]`

25.79.5.2 `std::ostream& operator<< (std::ostream & _os, const Dict & _val)` `[friend]`

The documentation for this class was generated from the following file:

- [gdcmDict.h](#)

25.80 gdcm::DictConverter Class Reference

Class to convert a .dic file into something else:

```
#include <gdcmDictConverter.h>
```

Public Types

- enum [OutputTypes](#) {
 [DICT_DEFAULT](#) = 0,
 [DICT_DEBUG](#),
 [DICT_XML](#) }

Public Member Functions

- [DictConverter](#) ()
- [~DictConverter](#) ()
- void [Convert](#) ()
- const std::string & [GetDictName](#) () const
- const std::string & [GetInputFilename](#) () const
- const std::string & [GetOutputFilename](#) () const
- int [GetOutputType](#) () const
- void [SetDictName](#) (const char *name)
- void [SetInputFileName](#) (const char *filename)
- void [SetOutputFileName](#) (const char *filename)
- void [SetOutputType](#) (int type)

Static Public Member Functions

- static bool [Readuint16](#) (const char *raw, uint16_t &ov)
- static bool [ReadVM](#) (const char *raw, [VM::VMType](#) &type)
- static bool [ReadVR](#) (const char *raw, [VR::VRType](#) &type)

Protected Member Functions

- void [AddGroupLength](#) ()
- bool [ConvertToCXX](#) (const char *raw, std::string &cxx)
- bool [ConvertToXML](#) (const char *raw, std::string &cxx)
- void [WriteFooter](#) ()
- void [WriteHeader](#) ()

25.80.1 Detailed Description

Class to convert a .dic file into something else:

- CXX code : embeded dict into shared lib (DICT_DEFAULT)
- Debug mode (DICT_DEBUG)
- XML dict (DICT_XML)

Note

25.80.2 Member Enumeration Documentation

25.80.2.1 enum gdcm::DictConverter::OutputTypes

Enumerator

DICT_DEFAULT
DICT_DEBUG
DICT_XML

25.80.3 Constructor & Destructor Documentation

25.80.3.1 `gdcm::DictConverter::DictConverter ()`

25.80.3.2 `gdcm::DictConverter::~~DictConverter ()`

25.80.4 Member Function Documentation

25.80.4.1 `void gdcm::DictConverter::AddGroupLength ()` [protected]

25.80.4.2 `void gdcm::DictConverter::Convert ()`

25.80.4.3 `bool gdcm::DictConverter::ConvertToCXX (const char * raw, std::string & cxx)` [protected]

- 25.80.4.4 `bool gdcmm::DictConverter::ConvertToXML (const char * raw, std::string & cxx)` [protected]
- 25.80.4.5 `const std::string& gdcmm::DictConverter::GetDictName ()` const
- 25.80.4.6 `const std::string& gdcmm::DictConverter::GetInputFilename ()` const
- 25.80.4.7 `const std::string& gdcmm::DictConverter::GetOutputFilename ()` const
- 25.80.4.8 `int gdcmm::DictConverter::GetOutputType ()` const [inline]
- 25.80.4.9 `static bool gdcmm::DictConverter::Readuint16 (const char * raw, uint16_t & ov)` [static]
- 25.80.4.10 `static bool gdcmm::DictConverter::ReadVM (const char * raw, VM::VMType & type)` [static]
- 25.80.4.11 `static bool gdcmm::DictConverter::ReadVR (const char * raw, VR::VRType & type)` [static]
- 25.80.4.12 `void gdcmm::DictConverter::SetDictName (const char * name)`
- 25.80.4.13 `void gdcmm::DictConverter::SetInputFileName (const char * filename)`
- 25.80.4.14 `void gdcmm::DictConverter::SetOutputFileName (const char * filename)`
- 25.80.4.15 `void gdcmm::DictConverter::SetOutputType (int type)` [inline]
- 25.80.4.16 `void gdcmm::DictConverter::WriteFooter ()` [protected]
- 25.80.4.17 `void gdcmm::DictConverter::WriteHeader ()` [protected]

The documentation for this class was generated from the following file:

- [gdcmmDictConverter.h](#)

25.81 gdcmm::DictEntry Class Reference

Class to represent an Entry in the [Dict](#) Does not really exist within the DICOM definition, just a way to minimize storage and have a mapping from [gdcmm::Tag](#) to the needed information.

```
#include <gdcmmDictEntry.h>
```

Public Member Functions

- [DictEntry](#) (const char *name="", const char *keyword="", [VR](#) const &vr=[VR::INVALID](#), [VM](#) const &vm=[VM::VM0](#), bool ret=false)
- const char * [GetKeyword](#) () const
same as GetName but without spaces...
- const char * [GetName](#) () const
Set/Get Name.
- bool [GetRetired](#) () const
Set/Get Retired flag.
- const [VM](#) & [GetVM](#) () const

- *Set/Get VM.*
- const [VR](#) & [GetVR](#) () const
- *Set/Get VR.*
- bool [IsUnique](#) () const
- void [SetElementXX](#) (bool v)
- *Set whether element is shared in multiple elements (Source [Image](#) IDs typically)*
- void [SetGroupXX](#) (bool v)
- *Set whether element is shared in multiple groups (Curve/Overlay typically)*
- void [SetKeyword](#) (const char *keyword)
- void [SetName](#) (const char *name)
- void [SetRetired](#) (bool retired)
- void [SetVM](#) (VM const &vm)
- void [SetVR](#) (const [VR](#) &vr)

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [DictEntry](#) &_val)

25.81.1 Detailed Description

Class to represent an Entry in the [Dict](#) Does not really exist within the DICOM definition, just a way to minimize storage and have a mapping from [gdcm::Tag](#) to the needed information.

Note

bla TODO FIXME: Need a PublicDictEntry...indeed [DictEntry](#) has a notion of retired which does not exist in Private-DictEntry...

See Also

[gdcm::Dict](#)

Examples:

[GenAllVR.cxx](#), [GenFakelIdentifyFile.cxx](#), [PublicDict.cxx](#), and [TraverseModules.cxx](#).

25.81.2 Constructor & Destructor Documentation

- 25.81.2.1 `gdcm::DictEntry::DictEntry (const char * name = " ", const char * keyword = " ", VR const & vr = VR::INVALID, VM const & vm = VM::VMO, bool ret = false) [inline]`

25.81.3 Member Function Documentation

- 25.81.3.1 `const char* gdcm::DictEntry::GetKeyword () const [inline]`

same as GetName but without spaces...

- 25.81.3.2 `const char* gdcm::DictEntry::GetName () const [inline]`

Set/Get Name.

Referenced by `gdcm::PrivateDict::PrintXML()`.

25.81.3.3 `bool gdcM::DictEntry::GetRetired () const [inline]`

Set/Get Retired flag.

Examples:

[GenAllVR.cxx](#).

25.81.3.4 `const VM& gdcM::DictEntry::GetVM () const [inline]`

Set/Get [VM](#).

Referenced by `gdcM::PrivateDict::AddDictEntry()`, and `gdcM::PrivateDict::PrintXML()`.

25.81.3.5 `const VR& gdcM::DictEntry::GetVR () const [inline]`

Set/Get [VR](#).

Examples:

[GenAllVR.cxx](#), and [GenFakeIdentifyFile.cxx](#).

Referenced by `gdcM::PrivateDict::AddDictEntry()`, and `gdcM::PrivateDict::PrintXML()`.

25.81.3.6 `bool gdcM::DictEntry::IsUnique () const [inline]`

Return whether the name of the [DataElement](#) can be considered to be unique. As of 2008 all elements name were unique (except the explicitly 'XX' ones)

25.81.3.7 `void gdcM::DictEntry::SetElementXX (bool v) [inline]`

Set whether element is shared in multiple elements (Source [Image](#) IDs typically)

25.81.3.8 `void gdcM::DictEntry::SetGroupXX (bool v) [inline]`

Set whether element is shared in multiple groups (Curve/Overlay typically)

25.81.3.9 `void gdcM::DictEntry::SetKeyword (const char * keyword) [inline]`

25.81.3.10 `void gdcM::DictEntry::SetName (const char * name) [inline]`

25.81.3.11 `void gdcM::DictEntry::SetRetired (bool retired) [inline]`

25.81.3.12 `void gdcM::DictEntry::SetVM (VM const & vm) [inline]`

25.81.3.13 `void gdcM::DictEntry::SetVR (const VR & vr) [inline]`

Referenced by `gdcM::PrivateDict::AddDictEntry()`.

25.81.4 Friends And Related Function Documentation

25.81.4.1 `std::ostream& operator<< (std::ostream & _os, const DictEntry & _val)` [*friend*]

The documentation for this class was generated from the following file:


- [gdcMDictEntry.h](#)

25.82 gdcM::DictPrinter Class Reference


[DictPrinter](#) class.

```
#include <gdcMDictPrinter.h>
```

Inheritance diagram for gdcM::DictPrinter:



Collaboration diagram for gdcm::DictPrinter:



Public Member Functions

- [DictPrinter](#) ()
- [~DictPrinter](#) ()
- void [Print](#) (std::ostream &os)

Protected Member Functions

- void [PrintDataElement2](#) (std::ostream &os, const [DataSet](#) &ds, const [DataElement](#) &ide)
- void [PrintDataSet2](#) (std::ostream &os, const [DataSet](#) &ds)

Additional Inherited Members

25.82.1 Detailed Description

[DictPrinter](#) class.

25.82.2 Constructor & Destructor Documentation

25.82.2.1 `gdcm::DictPrinter::DictPrinter ()`

25.82.2.2 `gdcm::DictPrinter::~~DictPrinter ()`

25.82.3 Member Function Documentation

25.82.3.1 `void gdcm::DictPrinter::Print (std::ostream & os)`

25.82.3.2 `void gdcm::DictPrinter::PrintDataElement2 (std::ostream & os, const DataSet & ds, const DataElement & ide)`
[protected]

25.82.3.3 `void gdcm::DictPrinter::PrintDataSet2 (std::ostream & os, const DataSet & ds)` [protected]

The documentation for this class was generated from the following file:

- [gdcmDictPrinter.h](#)

25.83 gdcm::Dicts Class Reference

Class to manipulate the sum of knowledge (all the dict user load)

```
#include <gdcmDicts.h>
```

Public Member Functions

- [Dicts](#) ()
- [~Dicts](#) ()
- const [CSAHeaderDict](#) & [GetCSAHeaderDict](#) () const
- const [DictEntry](#) & [GetDictEntry](#) (const [Tag](#) &tag, const char *owner=NULL) const
- const [DictEntry](#) & [GetDictEntry](#) (const [PrivateTag](#) &tag) const
- const [PrivateDict](#) & [GetPrivateDict](#) () const
- [PrivateDict](#) & [GetPrivateDict](#) ()
- const [Dict](#) & [GetPublicDict](#) () const
- bool [IsEmpty](#) () const

Protected Types

- enum [ConstructorType](#) {
 [PHILIPS](#),
 [GEMS](#),
 [SIEMENS](#) }

Protected Member Functions

- void [LoadDefaults](#) ()

Static Protected Member Functions

- static const char * [GetConstructorString](#) ([ConstructorType](#) type)

Friends

- class [Global](#)
- `std::ostream & operator<< (std::ostream &_os, const Dicts &d)`

25.83.1 Detailed Description

Class to manipulate the sum of knowledge (all the dict user load)

Note

bla

Examples:

[GenAllVR.cxx](#), [GenFakelIdentifyFile.cxx](#), [PublicDict.cxx](#), [ReadAndPrintAttributes.cxx](#), and [TraverseModules.cxx](#).

25.83.2 Member Enumeration Documentation

25.83.2.1 `enum gdcm::Dicts::ConstructorType` `[protected]`

Enumerator

PHILIPS

GEMS

SIEMENS

25.83.3 Constructor & Destructor Documentation

25.83.3.1 `gdcm::Dicts::Dicts ()`

25.83.3.2 `gdcm::Dicts::~~Dicts ()`

25.83.4 Member Function Documentation

25.83.4.1 `static const char* gdcm::Dicts::GetConstructorString (ConstructorType type)` `[static], [protected]`

25.83.4.2 `const CSAHeaderDict& gdcm::Dicts::GetCSAHeaderDict () const`

Examples:

[MrProtocol.cxx](#).

25.83.4.3 `const DictEntry& gdcm::Dicts::GetDictEntry (const Tag & tag, const char * owner = NULL) const`

works for both public and private dicts: owner is null for public dict

Warning

owner need to be set to appropriate owner for call to work. see

Examples:

[PublicDict.cxx](#).

25.83.4.4 `const DictEntry& gdcM::Dicts::GetDictEntry (const PrivateTag & tag) const`

25.83.4.5 `const PrivateDict& gdcM::Dicts::GetPrivateDict () const`

25.83.4.6 `PrivateDict& gdcM::Dicts::GetPrivateDict ()`

25.83.4.7 `const Dict& gdcM::Dicts::GetPublicDict () const`

Examples:

[GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [PublicDict.cxx](#), and [ReadAndPrintAttributes.cxx](#).

25.83.4.8 `bool gdcM::Dicts::IsEmpty () const [inline]`

References `gdcM::Dict::IsEmpty()`.

25.83.4.9 `void gdcM::Dicts::LoadDefaults () [protected]`

25.83.5 Friends And Related Function Documentation

25.83.5.1 `friend class Global [friend]`

25.83.5.2 `std::ostream& operator<< (std::ostream & _os, const Dicts & d) [friend]`

The documentation for this class was generated from the following file:

- [gdcMDicts.h](#)

25.84 gdcM::network::DIMSE Class Reference

[DIMSE PS 3.7 - 2009 Annex E Command Dictionary \(Normative\) E.1 REGISTRY OF DICOM COMMAND ELEMENTS Table E.1-1 COMMAND FIELDS \(PART 1\)](#)

```
#include <gdcMDIMSE.h>
```

Public Types

- enum [CommandTypes](#) {
 - [C_STORE_RQ](#) = 0x0001,
 - [C_STORE_RSP](#) = 0x8001,
 - [C_GET_RQ](#) = 0x0010,
 - [C_GET_RSP](#) = 0x8010,
 - [C_FIND_RQ](#) = 0x0020,
 - [C_FIND_RSP](#) = 0x8020,
 - [C_MOVE_RQ](#) = 0x0021,
 - [C_MOVE_RSP](#) = 0x8021,
 - [C_ECHO_RQ](#) = 0x0030,
 - [C_ECHO_RSP](#) = 0x8030,
 - [N_EVENT_REPORT_RQ](#) = 0x0100,
 - [N_EVENT_REPORT_RSP](#) = 0x8100,
 - [N_GET_RQ](#) = 0x0110,
 - [N_GET_RSP](#) = 0x8110,
 - [N_SET_RQ](#) = 0x0120,
 - [N_SET_RSP](#) = 0x8120,
 - [N_ACTION_RQ](#) = 0x0130,
 - [N_ACTION_RSP](#) = 0x8130,
 - [N_CREATE_RQ](#) = 0x0140,
 - [N_CREATE_RSP](#) = 0x8140,
 - [N_DELETE_RQ](#) = 0x0150,
 - [N_DELETE_RSP](#) = 0x8150,
 - [C_CANCEL_RQ](#) = 0x0FFF }

25.84.1 Detailed Description

[DIMSE PS 3.7 - 2009 Annex E](#) [Command](#) Dictionary (Normative) E.1 REGISTRY OF DICOM COMMAND ELEMENTS
[Table E.1-1](#) COMMAND FIELDS (PART 1)

25.84.2 Member Enumeration Documentation

25.84.2.1 enum gdcmm::network::DIMSE::CommandTypes

Enumerator

C_STORE_RQ

C_STORE_RSP

C_GET_RQ

C_GET_RSP

C_FIND_RQ

C_FIND_RSP

C_MOVE_RQ

C_MOVE_RSP

C_ECHO_RQ

C_ECHO_RSP

N_EVENT_REPORT_RQ

N_EVENT_REPORT_RSP

N_GET_RQ
N_GET_RSP
N_SET_RQ
N_SET_RSP
N_ACTION_RQ
N_ACTION_RSP
N_CREATE_RQ
N_CREATE_RSP
N_DELETE_RQ
N_DELETE_RSP
C_CANCEL_RQ

The documentation for this class was generated from the following file:

- [gdcmdIMSE.h](#)

25.85 gdcmd::DirectionCosines Class Reference

class to handle [DirectionCosines](#)

```
#include <gdcmdDirectionCosines.h>
```

Public Member Functions

- [DirectionCosines](#) ()
- [DirectionCosines](#) (const double dircos[6])
- [~DirectionCosines](#) ()
- double [ComputeDistAlongNormal](#) (const double ipp[3]) const
Compute the distance along the normal.
- void [Cross](#) (double z[3]) const
Compute Cross product.
- double [CrossDot](#) ([DirectionCosines](#) const &dc) const
Compute the Dot product of the two cross vector of both [DirectionCosines](#) object.
- double [Dot](#) () const
Compute Dot.
- bool [IsValid](#) () const
Return whether or not this is a valid direction cosines.
- void [Normalize](#) ()
Normalize in-place.
- [operator const double *](#) () const
*Make the class behave like a const double *.*
- void [Print](#) (std::ostream &) const
Print.
- bool [SetFromString](#) (const char *str)

25.85.1 Detailed Description

class to handle [DirectionCosines](#)

Examples:

[DiscriminateVolume.cxx](#).

25.85.2 Constructor & Destructor Documentation

25.85.2.1 `gdcm::DirectionCosines::DirectionCosines ()`

25.85.2.2 `gdcm::DirectionCosines::DirectionCosines (const double dircos[6])`

25.85.2.3 `gdcm::DirectionCosines::~~DirectionCosines ()`

25.85.3 Member Function Documentation

25.85.3.1 `double gdcm::DirectionCosines::ComputeDistAlongNormal (const double ipp[3]) const`

Compute the distance along the normal.

25.85.3.2 `void gdcm::DirectionCosines::Cross (double z[3]) const`

Compute Cross product.

25.85.3.3 `double gdcm::DirectionCosines::CrossDot (DirectionCosines const & dc) const`

Compute the Dot product of the two cross vector of both [DirectionCosines](#) object.

Examples:

[DiscriminateVolume.cxx](#).

25.85.3.4 `double gdcm::DirectionCosines::Dot () const`

Compute Dot.

25.85.3.5 `bool gdcm::DirectionCosines::IsValid () const`

Return whether or not this is a valid direction cosines.

25.85.3.6 `void gdcm::DirectionCosines::Normalize ()`

Normalize in-place.

25.85.3.7 `gdcm::DirectionCosines::operator const double * () const` `[inline]`

Make the class behave like a const double *.

25.85.3.8 void `gdcm::DirectionCosines::Print (std::ostream &)` const

Print.

25.85.3.9 bool `gdcm::DirectionCosines::SetFromString (const char * str)`

Initialize from string str. It requires 6 floating point separated by a backslash character.

Examples:

[DiscriminateVolume.cxx](#).

The documentation for this class was generated from the following file:

- [gdcmDirectionCosines.h](#)

25.86 gdcm::Directory Class Reference

Class for manipulation directories.

```
#include <gdcmDirectory.h>
```

Public Types

- typedef std::vector< [FilenameType](#) > [FilenamesType](#)
- typedef std::string [FilenameType](#)

Public Member Functions

- [Directory](#) ()
- [~Directory](#) ()
- [FilenamesType](#) const & [GetDirectories](#) () const
Return the Directories traversed.
- [FilenamesType](#) const & [GetFileNames](#) () const
Set/Get the file names within the directory.
- [FilenameType](#) const & [GetToplevel](#) () const
Get the name of the toplevel directory.
- unsigned int [Load](#) ([FilenameType](#) const &name, bool recursive=false)
- void [Print](#) (std::ostream &os=std::cout) const
Print.

Protected Member Functions

- unsigned int [Explore](#) ([FilenameType](#) const &name, bool recursive)
Return number of file found when 'recursive'ly exploring directory name

Friends

- `std::ostream & operator<< (std::ostream &_os, const Directory &d)`

25.86.1 Detailed Description

Class for manipulation directories.

Note

This implementation provide a cross platform implementation for manipulating diretores: basically traversing directories and harvesting files
will not take into account unix type hidden file recursive option will not look into UNIX type hidden directory (those starting with a '.')
Since python or C# provide there own equivalent implementation, in which case [gdcm::Directory](#) does not make much sense.

Examples:

[DiscriminateVolume.cxx](#), [DumpToSQLITE3.cxx](#), [gdcmorthoplanes.cxx](#), [GenerateRTSTRUCT.cxx](#), [ReadUTF8Qt-Dir.cxx](#), [reslicesphere.cxx](#), [SortImage.cxx](#), [threadgdcm.cxx](#), and [VolumeSorter.cxx](#).

25.86.2 Member Typedef Documentation

25.86.2.1 `typedef std::vector<FilenameType> gdcm::Directory::FilenameType`

Examples:

[DiscriminateVolume.cxx](#).

25.86.2.2 `typedef std::string gdcm::Directory::FilenameType`

25.86.3 Constructor & Destructor Documentation

25.86.3.1 `gdcm::Directory::Directory () \[inline\]`

25.86.3.2 `gdcm::Directory::~~Directory () \[inline\]`

25.86.4 Member Function Documentation

25.86.4.1 `unsigned int gdcm::Directory::Explore (FilenameType const & name, bool recursive) \[protected\]`

Return number of file found when 'recursive'ly exploring directory *name*

25.86.4.2 `FilenameType const& gdcm::Directory::GetDirectories () const \[inline\]`

Return the Directories traversed.

25.86.4.3 `FilenameType` const& `gdcmm::Directory::GetFilenames ()` const [inline]

Set/Get the file names within the directory.

Examples:

[DiscriminateVolume.cxx](#), [DumpToSQLITE3.cxx](#), [gdcmmorthoplanes.cxx](#), [GenerateRTSTRUCT.cxx](#), [ReadUTF8Qt-Dir.cxx](#), [reslicesphere.cxx](#), [SortImage.cxx](#), [threadgdcmm.cxx](#), and [VolumeSorter.cxx](#).

25.86.4.4 `FilenameType` const& `gdcmm::Directory::GetToplevel ()` const [inline]

Get the name of the toplevel directory.

25.86.4.5 `unsigned int` `gdcmm::Directory::Load (FilenameType const & name, bool recursive = false)` [inline]

construct a list of filenames and subdirectory beneath directory: name

Warning

: hidden file and hidden directory are not loaded.

Examples:

[DiscriminateVolume.cxx](#), [DumpToSQLITE3.cxx](#), [gdcmmorthoplanes.cxx](#), [GenerateRTSTRUCT.cxx](#), [ReadUTF8Qt-Dir.cxx](#), [reslicesphere.cxx](#), [SortImage.cxx](#), [threadgdcmm.cxx](#), and [VolumeSorter.cxx](#).

25.86.4.6 `void` `gdcmm::Directory::Print (std::ostream & os = std::cout)` const

Print.

Examples:

[SortImage.cxx](#).

Referenced by `gdcmm::operator<<()`.

25.86.5 Friends And Related Function Documentation

25.86.5.1 `std::ostream&` `operator<< (std::ostream & _os, const Directory & d)` [friend]

The documentation for this class was generated from the following file:

- [gdcmmDirectory.h](#)

25.87 `gdcmm::DirectoryHelper` Class Reference

[DirectoryHelper](#) this class is designed to help mitigate some of the commonly performed operations on directories. namely: 1) the ability to determine the number of series in a directory by what type of series is present 2) the ability to

find all ct series in a directory 3) the ability to find all mr series in a directory 4) to load a set of DataSets from a series that's already been sorted by the IPP sorter 5) For rtstruct stuff, you need to know the sopinstanceuid of each z plane, so there's a retrieval function for that 6) then a few other functions for rtstruct writeouts.

```
#include <gdcmDirectoryHelper.h>
```

Static Public Member Functions

- static [Directory::FilenameType GetCTImageSeriesUIDs](#) (const std::string &inDirectory)
- static [Directory::FilenameType GetFilenamesFromSeriesUIDs](#) (const std::string &inDirectory, const std::string &inSeriesUID)
- static std::string [GetFrameOfReference](#) (const std::vector< [DataSet](#) > &inDS)
- static [Directory::FilenameType GetMRImageSeriesUIDs](#) (const std::string &inDirectory)
- static [Directory::FilenameType GetRTStructSeriesUIDs](#) (const std::string &inDirectory)
- static [Directory::FilenameType GetSeriesUIDsBySOPClassUID](#) (const std::string &inDirectory, const std::string &inSOPClassUID)
- static std::string [GetSOPClassUID](#) (const std::vector< [DataSet](#) > &inDS)
- static std::string [GetStringValueFromTag](#) (const [gdcm::Tag](#) &t, const [gdcm::DataSet](#) &ds)
- static std::vector< [DataSet](#) > [LoadImageFromFiles](#) (const std::string &inDirectory, const std::string &inSeriesUID)
- static std::string [RetrieveSOPInstanceUIDFromIndex](#) (int inIndex, const std::vector< [DataSet](#) > &inDS)
- static std::string [RetrieveSOPInstanceUIDFromZPosition](#) (double inZPos, const std::vector< [DataSet](#) > &inDS)

25.87.1 Detailed Description

[DirectoryHelper](#) this class is designed to help mitigate some of the commonly performed operations on directories. namely: 1) the ability to determine the number of series in a directory by what type of series is present 2) the ability to find all ct series in a directory 3) the ability to find all mr series in a directory 4) to load a set of DataSets from a series that's already been sorted by the IPP sorter 5) For rtstruct stuff, you need to know the sopinstanceuid of each z plane, so there's a retrieval function for that 6) then a few other functions for rtstruct writeouts.

25.87.2 Member Function Documentation

25.87.2.1 static [Directory::FilenameType](#) [gdcm::DirectoryHelper::GetCTImageSeriesUIDs](#) (const std::string & *inDirectory*)
[static]

25.87.2.2 static [Directory::FilenameType](#) [gdcm::DirectoryHelper::GetFilenamesFromSeriesUIDs](#) (const std::string & *inDirectory*, const std::string & *inSeriesUID*) [static]

Examples:

[GenerateRTSTRUCT.cxx](#).

25.87.2.3 static std::string [gdcm::DirectoryHelper::GetFrameOfReference](#) (const std::vector< [DataSet](#) > & *inDS*) [static]

25.87.2.4 static [Directory::FilenameType](#) [gdcm::DirectoryHelper::GetMRImageSeriesUIDs](#) (const std::string & *inDirectory*)
[static]

25.87.2.5 **static** `Directory::FilenameType` `gdcm::DirectoryHelper::GetRTStructSeriesUIDs` (`const std::string & inDirectory`)
[static]

Examples:

[GenerateRTSTRUCT.cxx](#).

25.87.2.6 **static** `Directory::FilenameType` `gdcm::DirectoryHelper::GetSeriesUIDsBySOPClassUID` (`const std::string & inDirectory, const std::string & inSOPClassUID`) [static]

25.87.2.7 **static** `std::string` `gdcm::DirectoryHelper::GetSOPClassUID` (`const std::vector< DataSet > & inDS`) [static]

25.87.2.8 **static** `std::string` `gdcm::DirectoryHelper::GetStringValueFromTag` (`const gdcm::Tag & t, const gdcm::DataSet & ds`)
[static]

25.87.2.9 **static** `std::vector<DataSet>` `gdcm::DirectoryHelper::LoadImageFromFiles` (`const std::string & inDirectory, const std::string & inSeriesUID`) [static]

25.87.2.10 **static** `std::string` `gdcm::DirectoryHelper::RetrieveSOPInstanceUIDFromIndex` (`int inIndex, const std::vector< DataSet > & inDS`) [static]

25.87.2.11 **static** `std::string` `gdcm::DirectoryHelper::RetrieveSOPInstanceUIDFromZPosition` (`double inZPos, const std::vector< DataSet > & inDS`) [static]

The documentation for this class was generated from the following file:

- [gdcmDirectoryHelper.h](#)

25.88 gdcm::DummyValueGenerator Class Reference

Class for generating dummy value.

```
#include <gdcmDummyValueGenerator.h>
```

Static Public Member Functions

- `static const char *` [Generate](#) (`const char *input`)

25.88.1 Detailed Description

Class for generating dummy value.

See Also

[Anonymizer](#)

25.88.2 Member Function Documentation

25.88.2.1 `static const char* gdcmm::DummyValueGenerator::Generate (const char * input)` `[static]`

Generate a dummy value from an input value. This is guarantee to always return the same output value when input is identical. Return an array of bytes that can be used for anonymization purpose, return NULL on error NOT THREAD SAFE

The documentation for this class was generated from the following file:


- [gdcmmDummyValueGenerator.h](#)

25.89 gdcmm::Dumper Class Reference


[Codec](#) class.

```
#include <gdcmmDumper.h>
```

Inheritance diagram for gdcmm::Dumper:



Collaboration diagram for `gdc::Dumper`:



Public Member Functions

- [Dumper](#) ()
- [~Dumper](#) ()

Additional Inherited Members

25.89.1 Detailed Description

[Codec](#) class.

Note

Use it to simply dump value read from the file. No interpretation is done. But it is real fast ! Almost no overhead

25.89.2 Constructor & Destructor Documentation

25.89.2.1 `gdc::Dumper::Dumper ()` `[inline]`

25.89.2.2 `gdc::Dumper::~~Dumper ()` `[inline]`

The documentation for this class was generated from the following file:


- [gdcDumper.h](#)

25.90 gdcmm::Element< TVR, TVM > Class Template Reference


[Element](#) class.

```
#include <gdcmmElement.h>
```

Inheritance diagram for gdcmm::Element< TVR, TVM >:



Collaboration diagram for gdcmm::Element< TVR, TVM >:



Public Types

- typedef [VRToType](#)< TVR >::Type Type

Public Member Functions

- [DataElement](#) [GetAsDataElement](#) () const
- unsigned long [GetLength](#) () const
- const [VRToType](#)< TVR >::Type & [GetValue](#) (unsigned int idx=0) const
- [VRToType](#)< TVR >::Type & [GetValue](#) (unsigned int idx=0)
- const [VRToType](#)< TVR >::Type * [GetValues](#) () const
- [VRToType](#)< TVR >::Type [operator\[\]](#) (unsigned int idx) const
- void [Print](#) (std::ostream &_os) const
- void [Read](#) (std::istream &_is)
- void [Set](#) ([Value](#) const &v)
- void [SetFromDataElement](#) ([DataElement](#) const &de)
- void [SetValue](#) (typename [VRToType](#)< TVR >::Type v, unsigned int idx=0)
- void [Write](#) (std::ostream &_os) const

Static Public Member Functions

- static [VM](#) [GetVM](#) ()
- static [VR](#) [GetVR](#) ()

Public Attributes

- [VRToType](#)< TVR >::Type [Internal](#) [[VMToLength](#)< TVM >::Length]

Protected Member Functions

- void [SetNoSwap](#) ([Value](#) const &v)

25.90.1 Detailed Description

template<int TVR, int TVM>class gdcmm::Element< TVR, TVM >

[Element](#) class.

Note

TODO

Examples:

[csa2img.cxx](#), [DumpADAC.cxx](#), [DumpGEMSMovieGroup.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [GetSubSequenceData.cxx](#), and [iU22tomultisc.cxx](#).

25.90.2 Member Typedef Documentation

25.90.2.1 `template<int TVR, int TVM> typedef VRToType<TVR>::Type gdcmm::Element< TVR, TVM >::Type`

25.90.3 Member Function Documentation

25.90.3.1 `template<int TVR, int TVM> DataElement gdcmm::Element< TVR, TVM >::GetAsDataElement () const`
[inline]

25.90.3.2 `template<int TVR, int TVM> unsigned long gdcmm::Element< TVR, TVM >::GetLength () const` [inline]

25.90.3.3 `template<int TVR, int TVM> const VRToType<TVR>::Type& gdcmm::Element< TVR, TVM >::GetValue (unsigned int idx = 0) const` [inline]

25.90.3.4 `template<int TVR, int TVM> VRToType<TVR>::Type& gdcmm::Element< TVR, TVM >::GetValue (unsigned int idx = 0)` [inline]

25.90.3.5 `template<int TVR, int TVM> const VRToType<TVR>::Type* gdcmm::Element< TVR, TVM >::GetValues () const`
[inline]

25.90.3.6 `template<int TVR, int TVM> static VM gdcmm::Element< TVR, TVM >::GetVM ()` [inline],[static]

25.90.3.7 `template<int TVR, int TVM> static VR gdcmm::Element< TVR, TVM >::GetVR ()` [inline],[static]

25.90.3.8 `template<int TVR, int TVM> VRToType<TVR>::Type gdcmm::Element< TVR, TVM >::operator[] (unsigned int idx) const` [inline]

25.90.3.9 `template<int TVR, int TVM> void gdcmm::Element< TVR, TVM >::Print (std::ostream &_os) const` [inline]

25.90.3.10 `template<int TVR, int TVM> void gdcmm::Element< TVR, TVM >::Read (std::istream &_is)` [inline]

25.90.3.11 `template<int TVR, int TVM> void gdcmm::Element< TVR, TVM >::Set (Value const & v)` [inline]

25.90.3.12 `template<int TVR, int TVM> void gdcmm::Element< TVR, TVM >::SetFromDataElement (DataElement< TVR, TVM > const & de)` [inline]

25.90.3.13 `template<int TVR, int TVM> void gdcmm::Element< TVR, TVM >::SetNoSwap (Value const & v)` [inline],[protected]

25.90.3.14 `template<int TVR, int TVM> void gdcmm::Element< TVR, TVM >::SetValue (typename VRToType< TVR >::Type v, unsigned int idx = 0)` [inline]

25.90.3.15 `template<int TVR, int TVM> void gdcmm::Element< TVR, TVM >::Write (std::ostream &_os) const` [inline]

25.90.4 Member Data Documentation

25.90.4.1 `template<int TVR, int TVM> VRToType<TVR>::Type gdcmm::Element< TVR, TVM >::Internal[VMToLength< TVM >::Length]`


The documentation for this class was generated from the following file:

- [gdcmmElement.h](#)


25.91 `gdcm::Element< TVR, VM::VM1_2 >` Class Template Reference

```
#include <gdcmElement.h>
```

Inheritance diagram for `gdcm::Element< TVR, VM::VM1_2 >`:



Collaboration diagram for `gdcm::Element< TVR, VM::VM1_2 >`:



Public Types

- typedef `Element< TVR, VM::VM1_n >` `Parent`

Public Member Functions

- void `SetLength` (int len)

Additional Inherited Members

25.91.1 Member Typedef Documentation

25.91.1.1 `template<int TVR> typedef Element<TVR, VM::VM1_n> gdcmm::Element< TVR, VM::VM1_2 >::Parent`

25.91.2 Member Function Documentation

25.91.2.1 `template<int TVR> void gdcmm::Element< TVR, VM::VM1_2 >::SetLength (int len) [inline]`


The documentation for this class was generated from the following file:

- [gdcmmElement.h](#)

25.92 gdcmm::Element< TVR, VM::VM1_n > Class Template Reference

```
#include <gdcmmElement.h>
```

Inheritance diagram for gdcmm::Element< TVR, VM::VM1_n >:



Public Types

- typedef `VRToType< TVR >::Type` `Type`

Public Member Functions

- `Element ()`
- `Element (const Element &_val)`
- `~Element ()`
- `DataElement GetAsDataElement () const`
- `unsigned long GetLength () const`
- `const VRToType< TVR >::Type & GetValue (unsigned int idx=0) const`
- `VRToType< TVR >::Type & GetValue (unsigned int idx=0)`
- `Element & operator= (const Element &_val)`
- `VRToType< TVR >::Type operator[] (unsigned int idx) const`
- `void Print (std::ostream &_os) const`

- void [Read](#) (std::istream &_is)
- void [Set](#) ([Value](#) const &v)
- void [SetArray](#) (const [Type](#) *array, unsigned long len, bool save=false)
- void [SetFromDataElement](#) ([DataElement](#) const &de)
- void [SetLength](#) (unsigned long len)
- void [SetValue](#) (typename [VRToType](#)< TVR >::Type v, unsigned int idx=0)
- void [Write](#) (std::ostream &_os) const
- void [WriteASCII](#) (std::ostream &os) const

Static Public Member Functions

- static [VM GetVM](#) ()
- static [VR GetVR](#) ()

Protected Member Functions

- void [SetNoSwap](#) ([Value](#) const &v)

25.92.1 Member Typedef Documentation

25.92.1.1 `template<int TVR> typedef VRToType<TVR>::Type gdcm::Element< TVR, VM::VM1_n >::Type`

25.92.2 Constructor & Destructor Documentation

25.92.2.1 `template<int TVR> gdcm::Element< TVR, VM::VM1_n >::Element () [inline],[explicit]`

25.92.2.2 `template<int TVR> gdcm::Element< TVR, VM::VM1_n >::~~Element () [inline]`

25.92.2.3 `template<int TVR> gdcm::Element< TVR, VM::VM1_n >::Element (const Element< TVR, VM::VM1_n > &_val) [inline]`

25.92.3 Member Function Documentation

25.92.3.1 `template<int TVR> DataElement gdcm::Element< TVR, VM::VM1_n >::GetAsDataElement () const [inline]`

References `gdcm::DataElement::GetVR()`, `gdcm::DataElement::SetByteValue()`, `gdcm::DataElement::SetVR()`, `gdcm::VR::SQ`, `gdcm::VR::UI`, and `gdcm::VR::VRASCII`.

25.92.3.2 `template<int TVR> unsigned long gdcm::Element< TVR, VM::VM1_n >::GetLength () const [inline]`

25.92.3.3 `template<int TVR> const VRToType<TVR>::Type& gdcm::Element< TVR, VM::VM1_n >::GetValue (unsigned int idx = 0) const [inline]`

25.92.3.4 `template<int TVR> VRToType<TVR>::Type& gdcm::Element< TVR, VM::VM1_n >::GetValue (unsigned int idx = 0) [inline]`

25.92.3.5 `template<int TVR> static VM gdcm::Element< TVR, VM::VM1_n >::GetVM () [inline],[static]`

References `gdcm::VM::VM1_n`.

25.92.3.6 `template<int TVR> static VR gdcmm::Element< TVR, VM::VM1_n >::GetVR () [inline], [static]`

25.92.3.7 `template<int TVR> Element& gdcmm::Element< TVR, VM::VM1_n >::operator= (const Element< TVR, VM::VM1_n > &_val) [inline]`

25.92.3.8 `template<int TVR> VRToType<TVR>::Type gdcmm::Element< TVR, VM::VM1_n >::operator[] (unsigned int idx) const [inline]`

25.92.3.9 `template<int TVR> void gdcmm::Element< TVR, VM::VM1_n >::Print (std::ostream &_os) const [inline]`

25.92.3.10 `template<int TVR> void gdcmm::Element< TVR, VM::VM1_n >::Read (std::istream &_is) [inline]`

25.92.3.11 `template<int TVR> void gdcmm::Element< TVR, VM::VM1_n >::Set (Value const & v) [inline]`

References `gdcmm::ByteValue::GetLength()`, `gdcmm::ByteValue::GetPointer()`, and `gdcmm::VR::VRBINARY`.

25.92.3.12 `template<int TVR> void gdcmm::Element< TVR, VM::VM1_n >::SetArray (const Type * array, unsigned long len, bool save = false) [inline]`

25.92.3.13 `template<int TVR> void gdcmm::Element< TVR, VM::VM1_n >::SetFromDataElement (DataElement< TVR, VM::VM1_n > const & de) [inline]`

References `gdcmm::DataElement::GetByteValue()`, `gdcmm::DataElement::GetValue()`, `gdcmm::DataElement::GetVR()`, `gdcmm::VR::INVALID`, and `gdcmm::VR::UN`.

25.92.3.14 `template<int TVR> void gdcmm::Element< TVR, VM::VM1_n >::SetLength (unsigned long len) [inline]`

25.92.3.15 `template<int TVR> void gdcmm::Element< TVR, VM::VM1_n >::SetNoSwap (Value const & v) [inline], [protected]`

References `gdcmm::ByteValue::GetLength()`, `gdcmm::ByteValue::GetPointer()`, and `gdcmm::VR::VRBINARY`.

25.92.3.16 `template<int TVR> void gdcmm::Element< TVR, VM::VM1_n >::SetValue (typename VRToType< TVR >::Type v, unsigned int idx = 0) [inline]`

25.92.3.17 `template<int TVR> void gdcmm::Element< TVR, VM::VM1_n >::Write (std::ostream &_os) const [inline]`

25.92.3.18 `template<int TVR> void gdcmm::Element< TVR, VM::VM1_n >::WriteASCII (std::ostream & os) const [inline]`


The documentation for this class was generated from the following file:

- [gdcmmElement.h](#)


25.93 gdcmm::Element< TVR, VM::VM2_2n > Class Template Reference

```
#include <gdcmmElement.h>
```

Inheritance diagram for `gdcm::Element< TVR, VM::VM2_2n >`:



Collaboration diagram for `gdcm::Element< TVR, VM::VM2_2n >`:



Public Types

- typedef `Element< TVR, VM::VM2_n >` `Parent`

Public Member Functions

- void [SetLength](#) (int len)

Additional Inherited Members

25.93.1 Member Typedef Documentation

25.93.1.1 `template<int TVR> typedef Element<TVR, VM::VM2_n> gdcm::Element< TVR, VM::VM2_2n >::Parent`

25.93.2 Member Function Documentation

25.93.2.1 `template<int TVR> void gdcm::Element< TVR, VM::VM2_2n >::SetLength (int len) [inline]`


The documentation for this class was generated from the following file:

- [gdcmElement.h](#)


25.94 `gdcm::Element< TVR, VM::VM2_n >` Class Template Reference

```
#include <gdcmElement.h>
```

Inheritance diagram for `gdcm::Element< TVR, VM::VM2_n >`:



Collaboration diagram for `gdcm::Element< TVR, VM::VM2_n >`:



Public Types

- typedef `Element< TVR, VM::VM1_n >` `Parent`

Public Member Functions

- void `SetLength` (int *len*)

Additional Inherited Members

25.94.1 Member Typedef Documentation

25.94.1.1 `template<int TVR> typedef Element<TVR, VM::VM1_n> gdcm::Element< TVR, VM::VM2_n >::Parent`

25.94.2 Member Function Documentation

25.94.2.1 `template<int TVR> void gdcm::Element< TVR, VM::VM2_n >::SetLength (int len)` `[inline]`


The documentation for this class was generated from the following file:

- `gdcmElement.h`


25.95 `gdcm::Element< TVR, VM::VM3_3n >` Class Template Reference

```
#include <gdcmElement.h>
```

Inheritance diagram for gdcm::Element< TVR, VM::VM3_3n >:



Collaboration diagram for gdcm::Element< TVR, VM::VM3_3n >:



Public Types

- typedef `Element< TVR, VM::VM3_n >` `Parent`

Public Member Functions

- void [SetLength](#) (int len)

Additional Inherited Members

25.95.1 Member Typedef Documentation

25.95.1.1 `template<int TVR> typedef Element<TVR, VM::VM3_n> gdcm::Element< TVR, VM::VM3_3n >::Parent`

25.95.2 Member Function Documentation

25.95.2.1 `template<int TVR> void gdcm::Element< TVR, VM::VM3_3n >::SetLength (int len)` `[inline]`


The documentation for this class was generated from the following file:

- [gdcmElement.h](#)


25.96 gdcm::Element< TVR, VM::VM3_n > Class Template Reference

```
#include <gdcmElement.h>
```

Inheritance diagram for `gdcm::Element< TVR, VM::VM3_n >`:



Collaboration diagram for gdcmm::Element< TVR, VM::VM3_n >:



Public Types

- typedef [Element](#)< TVR, [VM::VM1_n](#) > [Parent](#)

Public Member Functions

- void [SetLength](#) (int len)

Additional Inherited Members

25.96.1 Member Typedef Documentation

25.96.1.1 `template<int TVR> typedef Element<TVR, VM::VM1_n> gdcmm::Element< TVR, VM::VM3_n >::Parent`

25.96.2 Member Function Documentation

25.96.2.1 `template<int TVR> void gdcmm::Element< TVR, VM::VM3_n >::SetLength (int len) [inline]`

The documentation for this class was generated from the following file:

- [gdcmmElement.h](#)

25.97 gdcmm::Element< VR::AS, VM::VM5 > Class Template Reference

```
#include <gdcmmElement.h>
```

Public Member Functions

- unsigned long [GetLength](#) () const
- void [Print](#) (std::ostream &_os) const

Public Attributes

- char [Internal](#) [[VMToLength](#)< [VM::VM5](#)>::Length *sizeof([VRToType](#)< [VR::AS](#)>::Type)]

25.97.1 Member Function Documentation

25.97.1.1 unsigned long [gdcm::Element](#)< [VR::AS](#), [VM::VM5](#)>::GetLength () const [\[inline\]](#)

25.97.1.2 void [gdcm::Element](#)< [VR::AS](#), [VM::VM5](#)>::Print ([std::ostream](#) &_os) const [\[inline\]](#)

25.97.2 Member Data Documentation

25.97.2.1 char [gdcm::Element](#)< [VR::AS](#), [VM::VM5](#)>::Internal[[VMToLength](#)< [VM::VM5](#)>::Length *sizeof([VRToType](#)< [VR::AS](#)>::Type)]


The documentation for this class was generated from the following file:

- [gdcmElement.h](#)


25.98 [gdcm::Element](#)< [VR::OB](#), [VM::VM1](#) > Class Template Reference

```
#include <gdcmElement.h>
```

Inheritance diagram for [gdcm::Element](#)< [VR::OB](#), [VM::VM1](#) >:



Collaboration diagram for gdcm::Element< VR::OB, VM::VM1 >:



Additional Inherited Members


The documentation for this class was generated from the following file:

- [gdcmElement.h](#)


25.99 gdcm::Element< VR::OW, VM::VM1 > Class Template Reference

```
#include <gdcmElement.h>
```

Inheritance diagram for gdcM::Element< VR::OW, VM::VM1 >:



Collaboration diagram for gdcm::Element< VR::OW, VM::VM1 >:



Additional Inherited Members

The documentation for this class was generated from the following file:

- [gdcmElement.h](#)

25.100 gdcm::ElementDisableCombinations< TVR, TVM > Class Template Reference

A class which is used to produce compile errors for an invalid combination of template parameters.

```
#include <gdcmElement.h>
```

25.100.1 Detailed Description

```
template<int TVR, int TVM>class gdcm::ElementDisableCombinations< TVR, TVM >
```

A class which is used to produce compile errors for an invalid combination of template parameters.

Invalid combinations have specialized declarations with no definition.

The documentation for this class was generated from the following file:

- [gdcmElement.h](#)

25.101 `gdcm::ElementDisableCombinations< VR::OB, VM::VM1_n >` Class Template Reference

```
#include <gdcmElement.h>
```

The documentation for this class was generated from the following file:

- [gdcmElement.h](#)

25.102 `gdcm::ElementDisableCombinations< VR::OW, VM::VM1_n >` Class Template Reference

```
#include <gdcmElement.h>
```

The documentation for this class was generated from the following file:

- [gdcmElement.h](#)

25.103 `gdcm::EncapsulatedDocument` Class Reference

[EncapsulatedDocument.](#)

```
#include <gdcmEncapsulatedDocument.h>
```

Public Member Functions

- [EncapsulatedDocument\(\)](#)

25.103.1 Detailed Description

[EncapsulatedDocument.](#)

25.103.2 Constructor & Destructor Documentation

25.103.2.1 `gdcm::EncapsulatedDocument::EncapsulatedDocument()` `[inline]`

The documentation for this class was generated from the following file:

- [gdcmEncapsulatedDocument.h](#)

25.104 gdcm::EncodingImplementation< T > Class Template Reference

[EncodingImplementation](#).

```
#include <gdcmElement.h>
```

25.104.1 Detailed Description

```
template<int T>class gdcm::EncodingImplementation< T >
```

[EncodingImplementation](#).

Note

TODO

The documentation for this class was generated from the following file:

- [gdcmElement.h](#)

25.105 gdcm::EncodingImplementation< VR::VRASCII > Class Template Reference

```
#include <gdcmElement.h>
```

Public Member Functions

- template<>
void [Write](#) (const float *data, unsigned long length, std::ostream &_os)
- template<>
void [Write](#) (const double *data, unsigned long length, std::ostream &_os)

Static Public Member Functions

- template<typename T >
static void [Read](#) (T *data, unsigned long length, std::istream &_is)
- template<typename T >
static void [ReadComputeLength](#) (T *data, unsigned int &length, std::istream &_is)
- template<typename T >
static void [ReadNoSwap](#) (T *data, unsigned long length, std::istream &_is)
- template<typename T >
static void [Write](#) (const T *data, unsigned long length, std::ostream &_os)

25.105.1 Member Function Documentation

25.105.1.1 template<typename T > static void gdcm::EncodingImplementation< VR::VRASCII >::Read (T * *data*, unsigned long *length*, std::istream & *is*) `[inline]`, `[static]`

25.105.1.2 `template<typename T> static void gdcm::EncodingImplementation< VR::VRASCII >::ReadComputeLength (T * data, unsigned int & length, std::istream & _is) [inline], [static]`

References `gdcm::backslash()`.

25.105.1.3 `template<typename T> static void gdcm::EncodingImplementation< VR::VRASCII >::ReadNoSwap (T * data, unsigned long length, std::istream & _is) [inline], [static]`

25.105.1.4 `template<typename T> static void gdcm::EncodingImplementation< VR::VRASCII >::Write (const T * data, unsigned long length, std::ostream & _os) [inline], [static]`

25.105.1.5 `template<> void gdcm::EncodingImplementation< VR::VRASCII >::Write (const float * data, unsigned long length, std::ostream & _os) [inline]`

References `gdcm::to_string()`.

25.105.1.6 `template<> void gdcm::EncodingImplementation< VR::VRASCII >::Write (const double * data, unsigned long length, std::ostream & _os) [inline]`

References `gdcm::to_string()`.

The documentation for this class was generated from the following file:

- [gdcmElement.h](#)

25.106 `gdcm::EncodingImplementation< VR::VRBINARY >` Class Template Reference

```
#include <gdcmElement.h>
```

Static Public Member Functions

- `template<typename T> static void Read (T *data, unsigned long length, std::istream &_is)`
- `template<typename T> static void ReadComputeLength (T *data, unsigned int &length, std::istream &_is)`
- `template<typename T> static void ReadNoSwap (T *data, unsigned long length, std::istream &_is)`
- `template<typename T> static void Write (const T *data, unsigned long length, std::ostream &_os)`

25.106.1 Member Function Documentation

25.106.1.1 `template<typename T> static void gdcm::EncodingImplementation< VR::VRBINARY >::Read (T * data, unsigned long length, std::istream & _is) [inline], [static]`

References `gdcm::SwapperNoOp::SwapArray()`.

25.106.1.2 `template<typename T> static void gdcm::EncodingImplementation< VR::VRBINARY >::ReadComputeLength (T * data, unsigned int & length, std::istream & _is) [inline], [static]`

25.106.1.3 `template<typename T> static void gdcm::EncodingImplementation< VR::VRBINARY >::ReadNoSwap (T * data, unsigned long length, std::istream & _is) [inline], [static]`

25.106.1.4 `template<typename T> static void gdcm::EncodingImplementation< VR::VRBINARY >::Write (const T * data, unsigned long length, std::ostream & _os) [inline], [static]`

References `gdcm::SwapperNoOp::Swap()`.


The documentation for this class was generated from the following file:

- [gdcmElement.h](#)


25.107 gdcm::EndEvent Class Reference

```
#include <gdcmEvent.h>
```

Inheritance diagram for `gdcm::EndEvent`:



Collaboration diagram for `gdcm::EndEvent`:



Additional Inherited Members

The documentation for this class was generated from the following file:

- [gdcmEvent.h](#)

25.108 gdcm::EnumeratedValues Class Reference

Element. A Data [Element](#) with Enumerated Values that does not have a [Value](#) equivalent to one of the Values specified in this standard has an invalid value within the scope of a specific Information Object/SOP Class definition. Note:

```
#include <gdcmEnumeratedValues.h>
```

Public Member Functions

- [EnumeratedValues](#) ()

25.108.1 Detailed Description

Element. A Data [Element](#) with Enumerated Values that does not have a [Value](#) equivalent to one of the Values specified in this standard has an invalid value within the scope of a specific Information Object/SOP Class definition. Note:

1. [Patient](#) Sex (0010, 0040) is an example of a Data [Element](#) having Enumerated Values. It is defined to have a [Value](#) that is either "M", "F", or "O" (see PS 3.3). No other [Value](#) shall be given to this Data [Element](#).
2. Future modifications of this standard may add to the set of allowed values for Data Elements with Enumerated Values. Such additions by themselves may or may not require a change in SOP Class [UIDs](#), depending on the semantics of the Data [Element](#).

25.108.2 Constructor & Destructor Documentation

25.108.2.1 gdcm::EnumeratedValues::EnumeratedValues () [inline]

The documentation for this class was generated from the following file:


- [gdcmEnumeratedValues.h](#)

25.109 gdcm::Event Class Reference

superclass for callback/observer methods

```
#include <gdcmEvent.h>
```

Inheritance diagram for gdcm::Event:



Public Member Functions

- [Event](#) ()
- [Event](#) (const [Event](#) &)
- virtual [~Event](#) ()
- virtual bool [CheckEvent](#) (const [Event](#) *) const =0
- virtual const char * [GetEventName](#) (void) const =0
- virtual [Event](#) * [MakeObject](#) () const =0
- virtual void [Print](#) (std::ostream &os) const

25.109.1 Detailed Description

superclass for callback/observer methods

See Also

[Command Subject](#)

25.109.2 Constructor & Destructor Documentation

25.109.2.1 `gdcm::Event::Event ()`

25.109.2.2 `gdcm::Event::Event (const Event &)`

25.109.2.3 `virtual gdcm::Event::~~Event () [virtual]`

25.109.3 Member Function Documentation

25.109.3.1 `virtual bool gdcm::Event::CheckEvent (const Event *) const [pure virtual]`

Check if given event matches or derives from this event.

25.109.3.2 `virtual const char* gdcm::Event::GetEventName (void) const [pure virtual]`

Return the StringName associated with the event.

Implemented in [gdcm::ProgressEvent](#), [gdcm::DataSetEvent](#), [gdcm::AnonymizeEvent](#), and [gdcm::DataEvent](#).

25.109.3.3 `virtual Event* gdcm::Event::MakeObject () const [pure virtual]`

Create an [Event](#) of this type This method work as a Factory for creating events of each particular type.

Implemented in [gdcm::ProgressEvent](#), [gdcm::DataSetEvent](#), [gdcm::AnonymizeEvent](#), and [gdcm::DataEvent](#).

25.109.3.4 `virtual void gdcm::Event::Print (std::ostream & os) const [virtual]`

Print [Event](#) information. This method can be overridden by specific [Event](#) subtypes. The default is to print out the type of the event.

Referenced by `gdcm::operator<<()`.

The documentation for this class was generated from the following file:


- [gdcmEvent.h](#)

25.110 gdcm::Exception Class Reference


[Exception.](#)

```
#include <gdcmException.h>
```

Inheritance diagram for gdcm::Exception:



Collaboration diagram for gdcm::Exception:



Public Member Functions

- [Exception](#) (const char *desc="None", const char *file=__FILE__, unsigned int lineNumber=__LINE__, const char *func="")
- virtual [~Exception](#) () throw ()

- `const char * GetDescription () const`
Return the Description.
- `const char * what () const throw ()`
what implementation

25.110.1 Detailed Description

[Exception](#).

Standard exception handling object.

Note

Its copy-constructor and assignment operator are generated by the compiler.

25.110.2 Constructor & Destructor Documentation

25.110.2.1 `gdcm::Exception::Exception (const char * desc = "None", const char * file = __FILE__, unsigned int lineNumber = __LINE__, const char * func = " ") [inline],[explicit]`

Explicit constructor, initializing the description and the text returned by [what\(\)](#).

Note

The last parameter is ignored for the time being. It may be used to specify the function where the exception was thrown.

25.110.2.2 `virtual gdcm::Exception::~~Exception () throw) [inline],[virtual]`

25.110.3 Member Function Documentation

25.110.3.1 `const char* gdcm::Exception::GetDescription () const [inline]`

Return the Description.

Referenced by `gdcm::SequenceOfItems::Read()`.

25.110.3.2 `const char* gdcm::Exception::what () const throw) [inline]`

what implementation

Referenced by `gdcm::SequenceOfFragments::ReadValue()`.


The documentation for this class was generated from the following file:

- [gdcmException.h](#)


25.111 gdcm::ExitEvent Class Reference

```
#include <gdcmEvent.h>
```

Inheritance diagram for gdcm::ExitEvent:



Collaboration diagram for gdcm::ExitEvent:



Additional Inherited Members

The documentation for this class was generated from the following file:


- [gdcmEvent.h](#)

25.112 gdcm::ExplicitDataElement Class Reference


Class to read/write a [DataElement](#) as Explicit Data [Element](#).

```
#include <gdcmExplicitDataElement.h>
```

Inheritance diagram for gdcm::ExplicitDataElement:



Collaboration diagram for gdcm::ExplicitDataElement:



Public Member Functions

- [VL GetLength](#) () const
- template<typename TSwap >
std::istream & [Read](#) (std::istream &is)

- `template<typename TSwap >`
`std::istream & ReadPreValue (std::istream &is)`
- `template<typename TSwap >`
`std::istream & ReadValue (std::istream &is)`
- `template<typename TSwap >`
`std::istream & ReadWithLength (std::istream &is, VL &length)`
- `template<typename TSwap >`
`const std::ostream & Write (std::ostream &os) const`

Additional Inherited Members

25.112.1 Detailed Description

Class to read/write a [DataElement](#) as Explicit Data [Element](#).

Note

bla

25.112.2 Member Function Documentation

25.112.2.1 `VL gdcm::ExplicitDataElement::GetLength () const`

25.112.2.2 `template<typename TSwap > std::istream& gdcm::ExplicitDataElement::Read (std::istream & is)`

25.112.2.3 `template<typename TSwap > std::istream& gdcm::ExplicitDataElement::ReadPreValue (std::istream & is)`

25.112.2.4 `template<typename TSwap > std::istream& gdcm::ExplicitDataElement::ReadValue (std::istream & is)`

25.112.2.5 `template<typename TSwap > std::istream& gdcm::ExplicitDataElement::ReadWithLength (std::istream & is, VL & length)`

25.112.2.6 `template<typename TSwap > const std::ostream& gdcm::ExplicitDataElement::Write (std::ostream & os) const`

The documentation for this class was generated from the following file:


- [gdcmExplicitDataElement.h](#)

25.113 gdcm::ExplicitImplicitDataElement Class Reference


Class to read/write a [DataElement](#) as ExplicitImplicit Data [Element](#).

```
#include <gdcmExplicitImplicitDataElement.h>
```

Inheritance diagram for `gdcM::ExplicitImplicitDataElement`:



Collaboration diagram for `gdcM::ExplicitImplicitDataElement`:



Public Member Functions

- [VL GetLength](#) () const
- template<typename TSwap >
std::istream & [Read](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadPreValue](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadValue](#) (std::istream &is)

- `template<typename TSwap >`
`std::istream & ReadWithLength (std::istream &is, VL &length)`

Additional Inherited Members

25.113.1 Detailed Description

Class to read/write a [DataElement](#) as ExplicitImplicit Data [Element](#).

Note

This only happen for some Philips images Should I derive from [ExplicitDataElement](#) instead ? This is the class that is the closest the GDCM1.x parser. At each element we try first to read it as explicit, if this fails, then we try again as an implicit element.

25.113.2 Member Function Documentation

25.113.2.1 `VL gdcm::ExplicitImplicitDataElement::GetLength () const`

25.113.2.2 `template<typename TSwap > std::istream& gdcm::ExplicitImplicitDataElement::Read (std::istream & is)`

25.113.2.3 `template<typename TSwap > std::istream& gdcm::ExplicitImplicitDataElement::ReadPreValue (std::istream & is)`

25.113.2.4 `template<typename TSwap > std::istream& gdcm::ExplicitImplicitDataElement::ReadValue (std::istream & is)`

25.113.2.5 `template<typename TSwap > std::istream& gdcm::ExplicitImplicitDataElement::ReadWithLength (std::istream & is, VL & length) [inline]`

The documentation for this class was generated from the following file:

- [gdcmExplicitImplicitDataElement.h](#)

25.114 gdcm::Fiducials Class Reference

[Fiducials](#).

```
#include <gdcmFiducials.h>
```

Public Member Functions

- [Fiducials](#) ()

25.114.1 Detailed Description

[Fiducials](#).

25.114.2 Constructor & Destructor Documentation

25.114.2.1 `gdcm::Fiducials::Fiducials ()` `[inline]`

The documentation for this class was generated from the following file:


- [gdcmFiducials.h](#)

25.115 `gdcm::File` Class Reference


a DICOM [File](#) See PS 3.10 [File](#): A [File](#) is an ordered string of zero or more bytes, where the first byte is at the beginning of the file and the last byte at the end of the [File](#). Files are identified by a unique [File](#) ID and may be written, read and/or deleted.

```
#include <gdcmFile.h>
```

Inheritance diagram for `gdcm::File`:



Collaboration diagram for gdcm::File:



Public Member Functions

- [File](#) ()
- [~File](#) ()
- const [DataSet](#) & [GetDataSet](#) () const
Get Data Set.
- [DataSet](#) & [GetDataSet](#) ()
Get Data Set.
- const [FileMetaInformation](#) & [GetHeader](#) () const
Get File Meta Information.
- [FileMetaInformation](#) & [GetHeader](#) ()
Get File Meta Information.
- std::istream & [Read](#) (std::istream &is)
Read.
- void [SetDataSet](#) (const [DataSet](#) &ds)
Set Data Set.
- void [SetHeader](#) (const [FileMetaInformation](#) &fmi)
Set File Meta Information.
- std::ostream const & [Write](#) (std::ostream &os) const
Write.

Friends

- std::ostream & [operator<<](#) (std::ostream &os, const [File](#) &val)

Additional Inherited Members

25.115.1 Detailed Description

a DICOM [File](#) See PS 3.10 [File](#): A [File](#) is an ordered string of zero or more bytes, where the first byte is at the beginning of the file and the last byte at the end of the [File](#). Files are identified by a unique [File](#) ID and may be written, read and/or deleted.

See Also

[Reader Writer](#)

Examples:

[ChangeSequenceUltrasound.cxx](#), [CreateJPIPDataSet.cxx](#), [DiffFile.cxx](#), [DumpGEMSMovieGroup.cxx](#), [DuplicatePCDE.cxx](#), [EncapsulateFileInRawData.cxx](#), [ExtractEncryptedContent.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [FixBrokenJ2K.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenFakeImage.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetJPEGSamplePrecision.cxx](#), [GetSequenceUltrasound.cxx](#), [GetSubSequenceData.cxx](#), [HelloWorld.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDSExplicit.cxx](#), [PatchFile.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [ReadAndPrintAttributes.cxx](#), [ReadGEMSSDO.cxx](#), and [StreamImageReaderTest.cxx](#).

25.115.2 Constructor & Destructor Documentation

25.115.2.1 `gdcm::File::File () [inline]`

25.115.2.2 `gdcm::File::~~File () [inline]`

25.115.3 Member Function Documentation

25.115.3.1 `const DataSet& gdcm::File::GetDataSet () const [inline]`

Get Data Set.

Examples:

[ChangeSequenceUltrasound.cxx](#), [CreateJPIPDataSet.cxx](#), [csa2img.cxx](#), [DiffFile.cxx](#), [DumpADAC.cxx](#), [DumpImageHeaderInfo.cxx](#), [DuplicatePCDE.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetJPEGSamplePrecision.cxx](#), [GetSequenceUltrasound.cxx](#), [HelloWorld.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDSExplicit.cxx](#), [MergeTwoFiles.cxx](#), [MrProtocol.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [ReadAndPrintAttributes.cxx](#), [ReadExplicitLengthSQIVR.cxx](#), [ReadGEMSSDO.cxx](#), [rle2img.cxx](#), and [StreamImageReaderTest.cxx](#).

25.115.3.2 `DataSet& gdcm::File::GetDataSet () [inline]`

Get Data Set.

25.115.3.3 `const FileMetaInformation& gdcm::File::GetHeader () const [inline]`

Get [File](#) Meta Information.

Examples:

[CreateJPIPDataSet.cxx](#), [EncapsulateFileInRawData.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GetJPEGSamplePrecision.cxx](#), [LargeVRDSExplicit.cxx](#), [MergeTwoFiles.cxx](#), [pmsct_rgb1.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [rle2img.cxx](#), and [StreamImageReaderTest.cxx](#).

Referenced by `gdcm::operator<<()`.

25.115.3.4 **FileMetaInformation&** gdcm::File::GetHeader () [inline]

Get [File](#) Meta Information.

25.115.3.5 **std::istream&** gdcm::File::Read (**std::istream & is**)

Read.

25.115.3.6 **void** gdcm::File::SetDataSet (**const DataSet & ds**) [inline]

Set Data Set.

25.115.3.7 **void** gdcm::File::SetHeader (**const FileMetaInformation & fmi**) [inline]

Set [File](#) Meta Information.

25.115.3.8 **std::ostream const&** gdcm::File::Write (**std::ostream & os**) **const**

Write.

25.115.4 Friends And Related Function Documentation

25.115.4.1 **std::ostream&** operator<< (**std::ostream & os**, **const File & val**) [friend]

The documentation for this class was generated from the following file:


- [gdcmFile.h](#)

25.116 gdcm::FileAnonymizer Class Reference


[FileAnonymizer](#).

```
#include <gdcmFileAnonymizer.h>
```

Inheritance diagram for `gdcm::FileAnonymizer`:



Collaboration diagram for `gdcm::FileAnonymizer`:



Public Member Functions

- [FileAnonymizer](#) ()
- [~FileAnonymizer](#) ()
- void [Empty](#) ([Tag](#) const &t)
- void [Remove](#) ([Tag](#) const &t)
remove a tag (even a SQ can be removed)
- void [Replace](#) ([Tag](#) const &t, const char *value)

- void [Replace](#) ([Tag](#) const &t, const char *value, [VL](#) const &vl)
- void [SetInputFileName](#) (const char *filename_native)
Set input filename.
- void [SetOutputFileName](#) (const char *filename_native)
Set output filename.
- bool [Write](#) ()
Write the output file.

Additional Inherited Members

25.116.1 Detailed Description

[FileAnonymizer](#).

This [Anonymizer](#) is a file-based [Anonymizer](#). It requires a valid DICOM file and will use the [Value](#) Length to skip over any information.

It will not load the data into memory and should consume much less memory than [gdcm::Anonymizer](#)

caveats: This class will NOT work with unordered attributes in a DICOM [File](#).

This class does neither recompute nor update the Group Length element.

This class currently does not update the [File](#) Meta Information header

25.116.2 Constructor & Destructor Documentation

25.116.2.1 [gdcm::FileAnonymizer::FileAnonymizer](#) ()

25.116.2.2 [gdcm::FileAnonymizer::~~FileAnonymizer](#) ()

25.116.3 Member Function Documentation

25.116.3.1 void [gdcm::FileAnonymizer::Empty](#) ([Tag](#) const & t)

Make [Tag](#) t empty Warning: does not handle SQ element

25.116.3.2 void [gdcm::FileAnonymizer::Remove](#) ([Tag](#) const & t)

remove a tag (even a SQ can be removed)

25.116.3.3 void [gdcm::FileAnonymizer::Replace](#) ([Tag](#) const & t, const char * value)

Replace tag with another value, if tag is not found it will be created: WARNING: this function can only execute if tag is a VRASCII WARNING: Do not ever try to write a value in a SQ Data [Element](#) !

25.116.3.4 void [gdcm::FileAnonymizer::Replace](#) ([Tag](#) const & t, const char * value, [VL](#) const & vl)

when the value contains \0, it is a good idea to specify the length. This function is required when dealing with VRBINARY tag

25.116.3.5 void `gdcm::FileAnonymizer::SetInputFileName` (const char * *filename_native*)

Set input filename.

25.116.3.6 void `gdcm::FileAnonymizer::SetOutputFileName` (const char * *filename_native*)

Set output filename.

25.116.3.7 bool `gdcm::FileAnonymizer::Write` ()

Write the output file.

The documentation for this class was generated from the following file:

- [gdcmFileAnonymizer.h](#)

25.117 `gdcm::FileDerivation` Class Reference

`FileDerivation` class See PS 3.16 - 2008 For the list of Code [Value](#) that can be used for in Derivation Code Sequence.

```
#include <gdcmFileDerivation.h>
```

Public Member Functions

- [FileDerivation](#) ()
- [~FileDerivation](#) ()
- bool [AddReference](#) (const char *referencedsopclassuid, const char *referencedsopinstanceuid)
- bool [Derive](#) ()
Change.
- [File](#) & [GetFile](#) ()
- const [File](#) & [GetFile](#) () const
- void [SetDerivationCodeSequenceCodeValue](#) (unsigned int codevalue)
Specify the Derivation Code Sequence Code [Value](#). Eg 113040.
- void [SetDerivationDescription](#) (const char *dd)
Specify the Derivation Description. Eg "lossy conversion".
- void [SetFile](#) (const [File](#) &f)
Set/Get [File](#).
- void [SetPurposeOfReferenceCodeSequenceCodeValue](#) (unsigned int codevalue)
Specify the Purpose Of Reference Code [Value](#). Eg. 121320.

Protected Member Functions

- bool [AddDerivationDescription](#) ()
- bool [AddPurposeOfReferenceCodeSequence](#) ([DataSet](#) &ds)
- bool [AddSourceImageSequence](#) ()

25.117.1 Detailed Description

[FileDerivation](#) class See PS 3.16 - 2008 For the list of Code [Value](#) that can be used for in Derivation Code Sequence.

URL: http://medical.nema.org/medical/dicom/2008/08_16pu.pdf

DICOM Part 16 has two Context Groups CID 7202 and CID 7203 which contain a set of codes defining reason for a source image reference (ie. reason code for referenced image sequence) and a coded description of the derivation applied to the new image data from the original. Both these context groups are extensible.

[File](#) Derivation is compulsory when creating a lossy derived image.

Examples:

[GenFakelImage.cxx](#).

25.117.2 Constructor & Destructor Documentation

25.117.2.1 `gdcm::FileDerivation::FileDerivation ()`

25.117.2.2 `gdcm::FileDerivation::~~FileDerivation ()`

25.117.3 Member Function Documentation

25.117.3.1 `bool gdcm::FileDerivation::AddDerivationDescription ()` [protected]

25.117.3.2 `bool gdcm::FileDerivation::AddPurposeOfReferenceCodeSequence (DataSet & ds)` [protected]

25.117.3.3 `bool gdcm::FileDerivation::AddReference (const char * referencedsopclassuid, const char * referencedsopinstanceuid)`

Create the proper reference. Need to pass the original SOP Class UID and the original SOP Instance UID, so that those value can be used as Reference.

Warning

`referencedsopclassuid` and `referencedsopinstanceuid` needs to be `\0` padded. This is not compatible with how `ByteValue->GetPointer` works.

Examples:

[GenFakelImage.cxx](#).

25.117.3.4 `bool gdcm::FileDerivation::AddSourceImageSequence ()` [protected]

25.117.3.5 `bool gdcm::FileDerivation::Derive ()`

Change.

Examples:

[GenFakelImage.cxx](#).

25.117.3.6 **File& gdcmm::FileDerivation::GetFile ()** [inline]

Examples:

[GenFakelImage.cxx](#).

25.117.3.7 **const File& gdcmm::FileDerivation::GetFile () const** [inline]

25.117.3.8 **void gdcmm::FileDerivation::SetDerivationCodeSequenceCodeValue (unsigned int *codevalue*)**

Specify the Derivation Code Sequence Code [Value](#). Eg 113040.

Examples:

[GenFakelImage.cxx](#).

25.117.3.9 **void gdcmm::FileDerivation::SetDerivationDescription (const char * *dd*)**

Specify the Derivation Description. Eg "lossy conversion".

25.117.3.10 **void gdcmm::FileDerivation::SetFile (const File & *f*)** [inline]

Set/Get [File](#).

Examples:

[GenFakelImage.cxx](#).

25.117.3.11 **void gdcmm::FileDerivation::SetPurposeOfReferenceCodeSequenceCodeValue (unsigned int *codevalue*)**

Specify the Purpose Of Reference Code [Value](#). Eg. 121320.

Examples:

[GenFakelImage.cxx](#).

The documentation for this class was generated from the following file:

- [gdcmmFileDerivation.h](#)

25.118 gdcmm::FileExplicitFilter Class Reference

[FileExplicitFilter](#) class After changing a file from Implicit to Explicit representation (see [ImageChangeTransferSyntax](#)) one operation is to make sure the [VR](#) of each DICOM attribute are accurate and do match the one from PS 3.6. Indeed when a file is written in Implicit representation, the [VR](#) is not stored directly in the file.

```
#include <gdcmmFileExplicitFilter.h>
```

Public Member Functions

- [FileExplicitFilter](#) ()
- [~FileExplicitFilter](#) ()
- bool [Change](#) ()
Set FMI Transfer Syntax.
- [File](#) & [GetFile](#) ()
- void [SetChangePrivateTags](#) (bool b)
Decide whether or not to [VR](#)ify private tags.
- void [SetFile](#) (const [File](#) &f)
Set/Get [File](#).
- void [SetRecomputeItemLength](#) (bool b)
By default set Sequence & [Item](#) length to Undefined to avoid recomputing length:
- void [SetRecomputeSequenceLength](#) (bool b)
- void [SetUseVRUN](#) (bool b)
When [VR](#)=16bits in explicit but Implicit has a 32bits length, use [VR](#)=UN.

Protected Member Functions

- bool [ChangeFMI](#) ()
- bool [ProcessDataSet](#) ([DataSet](#) &ds, [Dicts](#) const &dicts)

25.118.1 Detailed Description

[FileExplicitFilter](#) class After changing a file from Implicit to Explicit representation (see [ImageChangeTransferSyntax](#)) one operation is to make sure the [VR](#) of each DICOM attribute are accurate and do match the one from PS 3.6. Indeed when a file is written in Implicit representation, the [VR](#) is not stored directly in the file.

Warning

changing an implicit dataset to an explicit dataset is NOT a trivial task of simply changing the [VR](#) to the dict one:

- One has to make sure SQ is properly set
- One has to recompute the explicit length SQ
- One has to make sure that [VR](#) is valid for the encoding
- One has to make sure that [VR](#) 16bits can store the original value length

Examples:

[GenAllVR.cxx](#), and [LargeVRDSExplicit.cxx](#).

25.118.2 Constructor & Destructor Documentation

25.118.2.1 `gdcm::FileExplicitFilter::FileExplicitFilter ()` `[inline]`

25.118.2.2 `gdcm::FileExplicitFilter::~~FileExplicitFilter ()` `[inline]`

25.118.3 Member Function Documentation

25.118.3.1 `bool gdcmm::FileExplicitFilter::Change ()`

Set FMI Transfer Syntax.

Change

Examples:

[GenAllVR.cxx](#), and [LargeVRDSEExplicit.cxx](#).

25.118.3.2 `bool gdcmm::FileExplicitFilter::ChangeFMI ()` `[protected]`

25.118.3.3 `File& gdcmm::FileExplicitFilter::GetFile ()` `[inline]`

25.118.3.4 `bool gdcmm::FileExplicitFilter::ProcessDataSet (DataSet & ds, Dicts const & dicts)` `[protected]`

25.118.3.5 `void gdcmm::FileExplicitFilter::SetChangePrivateTags (bool b)` `[inline]`

Decide whether or not to [VR](#)ify private tags.

25.118.3.6 `void gdcmm::FileExplicitFilter::SetFile (const File & f)` `[inline]`

Set/Get [File](#).

Examples:

[GenAllVR.cxx](#), and [LargeVRDSEExplicit.cxx](#).

25.118.3.7 `void gdcmm::FileExplicitFilter::SetRecomputeItemLength (bool b)`

By default set Sequence & [Item](#) length to Undefined to avoid recomputing length:

25.118.3.8 `void gdcmm::FileExplicitFilter::SetRecomputeSequenceLength (bool b)`

25.118.3.9 `void gdcmm::FileExplicitFilter::SetUseVRUN (bool b)` `[inline]`

When [VR](#)=16bits in explicit but Implicit has a 32bits length, use [VR](#)=UN.

The documentation for this class was generated from the following file:


- [gdcmmFileExplicitFilter.h](#)

25.119 gdcmm::FileMetaInformation Class Reference


Class to represent a [File](#) Meta Information.

```
#include <gdcmmFileMetaInformation.h>
```

Inheritance diagram for gdcm::FileMetaInformation:



Collaboration diagram for gdcm::FileMetaInformation:



Public Member Functions

- [FileMetaInformation](#) ()
- [FileMetaInformation](#) ([FileMetaInformation](#) const &fmi)
- [~FileMetaInformation](#) ()
- void [FillFromDataSet](#) ([DataSet](#) const &ds)
 - Construct a [FileMetaInformation](#) from an already existing [DataSet](#):*
- const [TransferSyntax](#) & [GetDataSetTransferSyntax](#) () const
- VL [GetFullLength](#) () const
- [MediaStorage](#) [GetMediaStorage](#) () const
- [TransferSyntax::NegociatedType](#) [GetMetaInformationTS](#) () const
- const [Preamble](#) & [GetPreamble](#) () const
 - Get [Preamble](#).*
- [Preamble](#) & [GetPreamble](#) ()
- void [Insert](#) (const [DataElement](#) &de)
- bool [IsValid](#) () const

- `std::istream & Read (std::istream &is)`
Read.
- `std::istream & ReadCompat (std::istream &is)`
- `void Replace (const DataElement &de)`
- `void SetDataSetTransferSyntax (const TransferSyntax &ts)`
- `void SetPreamble (const Preamble &p)`
- `std::ostream & Write (std::ostream &os) const`
Write.

Static Public Member Functions

- `static void AppendImplementationClassUID (const char *imp)`
- `static const char * GetImplementationClassUID ()`
- `static const char * GetImplementationVersionName ()`
- `static const char * GetSourceApplicationEntityTitle ()`
- `static void SetImplementationClassUID (const char *imp)`
Override the GDCM default values:
- `static void SetImplementationVersionName (const char *version)`
- `static void SetSourceApplicationEntityTitle (const char *title)`

Protected Member Functions

- `void ComputeDataSetMediaStorageSOPClass ()`
- `void ComputeDataSetTransferSyntax ()`
- `void Default ()`
- `template<typename TSwap >`
`std::istream & ReadCompatInternal (std::istream &is)`

Static Protected Member Functions

- `static const char * GetFileMetaInformationVersion ()`
- `static const char * GetGDCMImplementationClassUID ()`
- `static const char * GetGDCMImplementationVersionName ()`
- `static const char * GetGDCMSourceApplicationEntityTitle ()`

Protected Attributes

- `MediaStorage::MSType DataSetMS`
- `TransferSyntax DataSetTS`
- `TransferSyntax::NegociatedType MetaInformationTS`

Friends

- `std::ostream & operator<< (std::ostream &_os, const FileMetaInformation &_val)`

Additional Inherited Members

25.119.1 Detailed Description

Class to represent a [File](#) Meta Information.

[FileMetaInformation](#) is a Explicit Structured Set. Whenever the file contains an [ImplicitDataElement DataSet](#), a conversion will take place.

Definition: The [File](#) Meta Information includes identifying information on the encapsulated Data Set. This header consists of a 128 byte [File Preamble](#), followed by a 4 byte DICOM prefix, followed by the [File](#) Meta Elements shown in [Table 7.1-1](#). This header shall be present in every DICOM file.

See Also

[Writer Reader](#)

Examples:

[GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [LargeVRDSEExplicit.cxx](#), and [ReadAndDumpDICOMDIR.cxx](#).

25.119.2 Constructor & Destructor Documentation

25.119.2.1 `gdcm::FileMetaInformation::FileMetaInformation () [inline]`

25.119.2.2 `gdcm::FileMetaInformation::~~FileMetaInformation () [inline]`

25.119.2.3 `gdcm::FileMetaInformation::FileMetaInformation (FileMetaInformation const & fmi) [inline]`

References [DataSetMS](#), [DataSetTS](#), and [MetaInformationTS](#).

25.119.3 Member Function Documentation

25.119.3.1 `static void gdcm::FileMetaInformation::AppendImplementationClassUID (const char * imp) [static]`

25.119.3.2 `void gdcm::FileMetaInformation::ComputeDataSetMediaStorageSOPClass () [protected]`

25.119.3.3 `void gdcm::FileMetaInformation::ComputeDataSetTransferSyntax () [protected]`

25.119.3.4 `void gdcm::FileMetaInformation::Default () [protected]`

25.119.3.5 `void gdcm::FileMetaInformation::FillFromDataSet (DataSet const & ds)`

Construct a [FileMetaInformation](#) from an already existing [DataSet](#):

25.119.3.6 `const TransferSyntax& gdcm::FileMetaInformation::GetDataSetTransferSyntax () const [inline]`

Examples:

[GetJPEGSamplePrecision.cxx](#), and [MergeTwoFiles.cxx](#).

25.119.3.7 `static const char* gdcm::FileMetaInformation::GetFileMetaInformationVersion () [static],[protected]`

25.119.3.8 `VL gdcm::FileMetaInformation::GetFullLength () const [inline]`

References `gdcm::VL::GetLength()`.

25.119.3.9 `static const char* gdcm::FileMetaInformation::GetGDCMImplementationClassUID () [static],[protected]`

25.119.3.10 `static const char* gdcm::FileMetaInformation::GetGDCMImplementationVersionName () [static],[protected]`

25.119.3.11 `static const char* gdcm::FileMetaInformation::GetGDCMSourceApplicationEntityTitle () [static],[protected]`

25.119.3.12 `static const char* gdcm::FileMetaInformation::GetImplementationClassUID () [static]`

25.119.3.13 `static const char* gdcm::FileMetaInformation::GetImplementationVersionName () [static]`

25.119.3.14 `MediaStorage gdcm::FileMetaInformation::GetMediaStorage () const`

25.119.3.15 `TransferSyntax::NegociatedType gdcm::FileMetaInformation::GetMetaInformationTS () const [inline]`

25.119.3.16 `const Preamble& gdcm::FileMetaInformation::GetPreamble () const [inline]`

Get [Preamble](#).

Referenced by `gdcm::operator<<()`.

25.119.3.17 `Preamble& gdcm::FileMetaInformation::GetPreamble () [inline]`

25.119.3.18 `static const char* gdcm::FileMetaInformation::GetSourceApplicationEntityTitle () [static]`

25.119.3.19 `void gdcm::FileMetaInformation::Insert (const DataElement & de) [inline]`

References `gdcmErrorMacro`, `gdcm::Tag::GetGroup()`, and `gdcm::DataElement::GetTag()`.

25.119.3.20 `bool gdcm::FileMetaInformation::IsValid () const [inline]`

25.119.3.21 `std::istream& gdcm::FileMetaInformation::Read (std::istream & is)`

Read.

25.119.3.22 `std::istream& gdcm::FileMetaInformation::ReadCompat (std::istream & is)`

25.119.3.23 `template<typename TSwap > std::istream& gdcm::FileMetaInformation::ReadCompatInternal (std::istream & is) [protected]`

25.119.3.24 `void gdcm::FileMetaInformation::Replace (const DataElement & de) [inline]`

Examples:

[LargeVRDSExplicit.cxx](#).

References `gdcm::DataElement::GetTag()`.

25.119.3.25 `void gdcm::FileMetaInformation::SetDataSetTransferSyntax (const TransferSyntax & ts)`

Examples:

[CreateJPIPDataSet.cxx](#), [EncapsulateFileInRawData.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GenAIIVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [LargeVRDSExplicit.cxx](#), [pmsct_rgb1.cxx](#), [rle2img.cxx](#), and [StreamImageReaderTest.cxx](#).

25.119.3.26 `static void gdcm::FileMetaInformation::SetImplementationClassUID (const char * imp) [static]`

Override the GDCM default values:

25.119.3.27 `static void gdcm::FileMetaInformation::SetImplementationVersionName (const char * version) [static]`

25.119.3.28 `void gdcm::FileMetaInformation::SetPreamble (const Preamble & p) [inline]`

25.119.3.29 `static void gdcm::FileMetaInformation::SetSourceApplicationEntityTitle (const char * title) [static]`

Examples:

[FixJAIBugJPEGLS.cxx](#).

25.119.3.30 `std::ostream& gdcm::FileMetaInformation::Write (std::ostream & os) const`

Write.

25.119.4 Friends And Related Function Documentation

25.119.4.1 `std::ostream& operator<< (std::ostream & _os, const FileMetaInformation & _val) [friend]`

25.119.5 Member Data Documentation

25.119.5.1 `MediaStorage::MSType gdcm::FileMetaInformation::DataSetMS [protected]`

Referenced by `FileMetaInformation()`.

25.119.5.2 `TransferSyntax gdcm::FileMetaInformation::DataSetTS [protected]`

Referenced by `FileMetaInformation()`.

25.119.5.3 TransferSyntax::NegociatedType gdcm::FileMetaInformation::MetaInformationTS [protected]

Referenced by FileMetaInformation().

The documentation for this class was generated from the following file:

- [gdcmFileMetaInformation.h](#)

25.120 gdcm::Filename Class Reference

Class to manipulate file name's.

```
#include <gdcmFilename.h>
```

Public Member Functions

- [Filename](#) (const char *filename="")
- bool [EndWith](#) (const char ending[]) const
Does the filename ends with a particular string ?
- const char * [GetExtension](#) ()
return only the extension part of a filename
- const char * [GetFileName](#) () const
Return the full filename.
- const char * [GetName](#) ()
return only the name part of a filename
- const char * [GetPath](#) ()
Return only the path component of a filename.
- bool [IsEmpty](#) () const
return whether the filename is empty
- bool [IsIdentical](#) ([Filename](#) const &fn) const
- operator const char * () const
- const char * [ToUnixSlashes](#) ()
Convert backslash (windows style) to UNIX style slash.
- const char * [ToWindowsSlashes](#) ()
Convert foward slash (UNIX style) to windows style slash.

Static Public Member Functions

- static const char * [Join](#) (const char *path, const char *filename)

25.120.1 Detailed Description

Class to manipulate file name's.

Note

OS independant representation of a filename (to query path, name and extension from a filename)

25.120.2 Constructor & Destructor Documentation

25.120.2.1 `gdcmm::Filename::Filename (const char * filename = " ") [inline]`

25.120.3 Member Function Documentation

25.120.3.1 `bool gdcmm::Filename::EndWith (const char ending[]) const`

Does the filename ends with a particular string ?

25.120.3.2 `const char* gdcmm::Filename::GetExtension ()`

return only the extension part of a filename

25.120.3.3 `const char* gdcmm::Filename::GetFileName () const [inline]`

Return the full filename.

25.120.3.4 `const char* gdcmm::Filename::GetName ()`

return only the name part of a filename

25.120.3.5 `const char* gdcmm::Filename::GetPath ()`

Return only the path component of a filename.

25.120.3.6 `bool gdcmm::Filename::IsEmpty () const [inline]`

return whether the filename is empty

25.120.3.7 `bool gdcmm::Filename::IsIdentical (Filename const & fn) const`

25.120.3.8 `static const char* gdcmm::Filename::Join (const char * path, const char * filename) [static]`

Join two paths NOT THREAD SAFE

25.120.3.9 `gdcmm::Filename::operator const char * () const [inline]`

Simple operator to allow `Filename myfilename("...")`; `const char * s = myfilename`;

25.120.3.10 `const char* gdcmm::Filename::ToUnixSlashes ()`

Convert backslash (windows style) to UNIX style slash.

25.120.3.11 `const char* gdcm::Filename::ToWindowsSlashes ()`

Convert forward slash (UNIX style) to windows style slash.

The documentation for this class was generated from the following file:

- [gdcmFilename.h](#)

25.121 `gdcm::FilenameGenerator` Class Reference

[FilenameGenerator](#).

```
#include <gdcmFilenameGenerator.h>
```

Public Types

- typedef std::vector< [FilenameType](#) > [FileNamesType](#)
- typedef std::string [FilenameType](#)
- typedef [FileNamesType](#)::size_type [SizeType](#)

Public Member Functions

- [FilenameGenerator](#) ()
- [~FilenameGenerator](#) ()
- bool [Generate](#) ()
Generate (return success)
- const char * [GetFilename](#) ([SizeType](#) n) const
Get a particular filename (call after Generate)
- [FileNamesType](#) const & [GetFileNames](#) () const
Return all filenames.
- [SizeType](#) [GetNumberOfFileNames](#) () const
- const char * [GetPattern](#) () const
- const char * [GetPrefix](#) () const
- void [SetNumberOfFileNames](#) ([SizeType](#) nfiles)
Set/Get the number of filenames to generate.
- void [SetPattern](#) (const char *pattern)
Set/Get pattern.
- void [SetPrefix](#) (const char *prefix)
Set/Get prefix.

25.121.1 Detailed Description

[FilenameGenerator](#).

class to generate filenames based on a pattern (C-style)

Output will be:

for i = 0, number of filenames: outfilename[i] = prefix + (pattern % i)

where pattern % i means C-style sprintf of Pattern using value 'i'

Examples:

[ConvertMultiFrameToSingleFrame.cxx](#).

25.121.2 Member Typedef Documentation

25.121.2.1 `typedef std::vector<FilenameType> gdcm::FilenameGenerator::FileNamesType`

25.121.2.2 `typedef std::string gdcm::FilenameGenerator::FilenameType`

25.121.2.3 `typedef FileNamesType::size_type gdcm::FilenameGenerator::SizeType`

25.121.3 Constructor & Destructor Documentation

25.121.3.1 `gdcm::FilenameGenerator::FilenameGenerator ()` `[inline]`

25.121.3.2 `gdcm::FilenameGenerator::~~FilenameGenerator ()` `[inline]`

25.121.4 Member Function Documentation

25.121.4.1 `bool gdcm::FilenameGenerator::Generate ()`

Generate (return success)

Examples:

[ConvertMultiFrameToSingleFrame.cxx](#).

25.121.4.2 `const char* gdcm::FilenameGenerator::GetFilename (SizeType n) const`

Get a particular filename (call after Generate)

Examples:

[ConvertMultiFrameToSingleFrame.cxx](#).

25.121.4.3 `FileNamesType const& gdcm::FilenameGenerator::GetFileNames () const` `[inline]`

Return all filenames.

25.121.4.4 `SizeType gdcm::FilenameGenerator::GetNumberOfFileNames () const`

Examples:

[ConvertMultiFrameToSingleFrame.cxx](#).

25.121.4.5 `const char* gdcm::FilenameGenerator::GetPattern () const` `[inline]`

25.121.4.6 `const char* gdcm::FilenameGenerator::GetPrefix () const` `[inline]`

25.121.4.7 `void gdcm::FilenameGenerator::SetNumberOfFileNames (SizeType nfiles)`

Set/Get the number of filenames to generate.

Examples:

[ConvertMultiFrameToSingleFrame.cxx](#).

25.121.4.8 `void gdcm::FilenameGenerator::SetPattern (const char * pattern)` `[inline]`

Set/Get pattern.

Examples:

[ConvertMultiFrameToSingleFrame.cxx](#).

25.121.4.9 `void gdcm::FilenameGenerator::SetPrefix (const char * prefix)` `[inline]`

Set/Get prefix.

The documentation for this class was generated from the following file:

- [gdcmFilenameGenerator.h](#)

25.122 gdcm::FileSet Class Reference

File-set: A File-set is a collection of DICOM Files (and possibly non-DICOM Files) that share a common naming space within which [File](#) IDs are unique.

```
#include <gdcmFileSet.h>
```

Public Types

- typedef std::vector< [FileType](#) > [FilesType](#)
- typedef std::string [FileType](#)

Public Member Functions

- [FileSet](#) ()
- void [AddFile](#) ([File](#) const &)
- bool [AddFile](#) (const char *filename)
- [FilesType](#) const & [GetFiles](#) () const
- void [SetFiles](#) ([FilesType](#) const &files)

Friends

- `std::ostream & operator<< (std::ostream &_os, const FileSet &d)`

25.122.1 Detailed Description

File-set: A File-set is a collection of DICOM Files (and possibly non-DICOM Files) that share a common naming space within which File IDs are unique.

25.122.2 Member Typedef Documentation

25.122.2.1 `typedef std::vector<FileType> gdcm::FileSet::FileType`

25.122.2.2 `typedef std::string gdcm::FileSet::FileType`

25.122.3 Constructor & Destructor Documentation

25.122.3.1 `gdcm::FileSet::FileSet () [inline]`

25.122.4 Member Function Documentation

25.122.4.1 `void gdcm::FileSet::AddFile (File const &) [inline]`

Deprecated . Does nothing

25.122.4.2 `bool gdcm::FileSet::AddFile (const char * filename)`

Add a file 'filename' to the list of files. Return true on success, false in case filename could not be found on system.

25.122.4.3 `FileType const& gdcm::FileSet::GetFiles () const [inline]`

25.122.4.4 `void gdcm::FileSet::SetFiles (FileType const & files)`

25.122.5 Friends And Related Function Documentation

25.122.5.1 `std::ostream& operator<< (std::ostream &_os, const FileSet &d) [friend]`

The documentation for this class was generated from the following file:


- [gdcmFileSet.h](#)

25.123 gdcm::FileWithName Class Reference


[FileWithName.](#)

```
#include <gdcmSerieHelper.h>
```

Inheritance diagram for `gdcM::FileWithName`:



Collaboration diagram for `gdcM::FileWithName`:



Public Member Functions

- [FileWithName](#) ([File](#) &*f*)

Public Attributes

- `std::string` [filename](#)

Additional Inherited Members

25.123.1 Detailed Description

[FileWithName.](#)

Backward only class do not use in newer code

25.123.2 Constructor & Destructor Documentation

25.123.2.1 `gdcm::FileWithName::FileWithName (File & f)` `[inline]`

25.123.3 Member Data Documentation

25.123.3.1 `std::string` `gdcm::FileWithName::filename`

The documentation for this class was generated from the following file:


- [gdcmSerieHelper.h](#)

25.124 gdcm::FindPatientRootQuery Class Reference


PatientRootQuery contains: the class which will produce a dataset for c-find with patient root.

```
#include <gdcmFindPatientRootQuery.h>
```

Inheritance diagram for `gdcm::FindPatientRootQuery`:



Collaboration diagram for `gdcm::FindPatientRootQuery`:



Public Member Functions

- [FindPatientRootQuery](#) ()
- [UIDs::TSName GetAbstractSyntaxUID](#) () const
- [std::vector< Tag > GetTagListByLevel](#) (const [EQueryLevel](#) &inQueryLevel)
- void [InitializeDataSet](#) (const [EQueryLevel](#) &inQueryLevel)
- bool [ValidateQuery](#) (bool inStrict=true) const

Friends

- class [QueryFactory](#)

Additional Inherited Members

25.124.1 Detailed Description

PatientRootQuery contains: the class which will produce a dataset for c-find with patient root.

25.124.2 Constructor & Destructor Documentation

25.124.2.1 `gdcm::FindPatientRootQuery::FindPatientRootQuery ()`

25.124.3 Member Function Documentation

25.124.3.1 `UIDs::TSName gdcm::FindPatientRootQuery::GetAbstractSyntaxUID () const` `[virtual]`

Implements [gdcm::BaseRootQuery](#).

25.124.3.2 `std::vector<Tag> gdcm::FindPatientRootQuery::GetTagListByLevel (const EQueryLevel & inQueryLevel)` `[virtual]`

this function will return all tags at a given query level, so that they maybe selected for searching. The boolean forFind is true if the query is a find query, or false for a move query.

Implements [gdcm::BaseRootQuery](#).

25.124.3.3 `void gdcm::FindPatientRootQuery::InitializeDataSet (const EQueryLevel & inQueryLevel) [virtual]`

this function sets tag 8,52 to the appropriate value based on query level also fills in the right unique tags, as per the standard's requirements should allow for connection with dcmTk

Implements [gdcm::BaseRootQuery](#).

25.124.3.4 `bool gdcm::FindPatientRootQuery::ValidateQuery (bool inStrict = true) const [virtual]`

have to be able to ensure that 0x8,0x52 is set (which will be true if InitializeDataSet is called...) that the level is appropriate (ie, not setting PATIENT for a study query that the tags in the query match the right level (either required, unique, optional) by default, this function checks to see if the query is for finding, which is more permissive than for moving. For moving, only the unique tags are allowed. 10 Jan 2011: adding in the 'strict' mode. according to the standard (at least, how I've read it), only tags for a particular level should be allowed in a particular query (ie, just series level tags in a series level query). However, it seems that dcm4chee doesn't share that interpretation. So, if 'inStrict' is false, then tags from the current level and all higher levels are now considered valid. So, if you're doing a non-strict series-level query, tags from the patient and study level can be passed along as well.

Implements [gdcm::BaseRootQuery](#).

25.124.4 Friends And Related Function Documentation

25.124.4.1 `friend class QueryFactory [friend]`

The documentation for this class was generated from the following file:


- [gdcmFindPatientRootQuery.h](#)

25.125 gdcm::FindStudyRootQuery Class Reference


[FindStudyRootQuery](#) contains: the class which will produce a dataset for C-FIND with study root.

```
#include <gdcmFindStudyRootQuery.h>
```

Inheritance diagram for `gdcM::FindStudyRootQuery`:



Collaboration diagram for `gdcM::FindStudyRootQuery`:



Public Member Functions

- [FindStudyRootQuery](#) ()
- [UIDs::TSName GetAbstractSyntaxUID](#) () const
- `std::vector< Tag > GetTagListByLevel` (const [EQueryLevel](#) &inQueryLevel)
- void [InitializeDataSet](#) (const [EQueryLevel](#) &inQueryLevel)
- bool [ValidateQuery](#) (bool inStrict=true) const

Friends

- class [QueryFactory](#)

Additional Inherited Members

25.125.1 Detailed Description

[FindStudyRootQuery](#) contains: the class which will produce a dataset for C-FIND with study root.

25.125.2 Constructor & Destructor Documentation

25.125.2.1 `gdcm::FindStudyRootQuery::FindStudyRootQuery ()`

25.125.3 Member Function Documentation

25.125.3.1 `UIDs::TSName gdcm::FindStudyRootQuery::GetAbstractSyntaxUID () const [virtual]`

Implements [gdcm::BaseRootQuery](#).

25.125.3.2 `std::vector<Tag> gdcm::FindStudyRootQuery::GetTagListByLevel (const EQueryLevel & inQueryLevel) [virtual]`

this function will return all tags at a given query level, so that they maybe selected for searching. The boolean forFind is true if the query is a find query, or false for a move query.

Implements [gdcm::BaseRootQuery](#).

25.125.3.3 `void gdcm::FindStudyRootQuery::InitializeDataSet (const EQueryLevel & inQueryLevel) [virtual]`

this function sets tag 8,52 to the appropriate value based on query level also fills in the right unique tags, as per the standard's requirements should allow for connection with dcmtk

Implements [gdcm::BaseRootQuery](#).

25.125.3.4 `bool gdcm::FindStudyRootQuery::ValidateQuery (bool inStrict=true) const [virtual]`

have to be able to ensure that (0008,0052) is set that the level is appropriate (ie, not setting PATIENT for a study query that the tags in the query match the right level (either required, unique, optional)

Implements [gdcm::BaseRootQuery](#).

25.125.4 Friends And Related Function Documentation

25.125.4.1 `friend class QueryFactory [friend]`

The documentation for this class was generated from the following file:


- [gdcmFindStudyRootQuery.h](#)

25.126 gdcm::Fragment Class Reference


Class to represent a [Fragment](#).

```
#include <gdcmFragment.h>
```

Inheritance diagram for `gdcm::Fragment`:



Collaboration diagram for `gdcm::Fragment`:



Public Member Functions

- [Fragment](#) ()
- [VL GetLength](#) () const

- `template<typename TSwap >`
`std::istream & Read (std::istream &is)`
- `template<typename TSwap >`
`std::istream & ReadBacktrack (std::istream &is)`
- `template<typename TSwap >`
`std::istream & ReadPreValue (std::istream &is)`
- `template<typename TSwap >`
`std::istream & ReadValue (std::istream &is)`
- `template<typename TSwap >`
`std::ostream & Write (std::ostream &os) const`

Friends

- `std::ostream & operator<< (std::ostream &os, const Fragment &val)`

Additional Inherited Members

25.126.1 Detailed Description

Class to represent a [Fragment](#).

Examples:

[FixBrokenJ2K.cxx](#), and [FixJAIBugJPEGLS.cxx](#).

25.126.2 Constructor & Destructor Documentation

25.126.2.1 `gdcm::Fragment::Fragment ()` `[inline]`

25.126.3 Member Function Documentation

25.126.3.1 `VL gdcm::Fragment::GetLength () const` `[inline]`

References `gdcm::VL::GetLength()`.

25.126.3.2 `template<typename TSwap > std::istream& gdcm::Fragment::Read (std::istream & is)` `[inline]`

Referenced by `gdcm::SequenceOfFragments::ReadValue()`.

25.126.3.3 `template<typename TSwap > std::istream& gdcm::Fragment::ReadBacktrack (std::istream & is)` `[inline]`

References `gdcmErrorMacro`, `gdcmWarningMacro`, and `gdcm::ParseException::SetLastElement()`.

Referenced by `gdcm::SequenceOfFragments::ReadValue()`.

25.126.3.4 `template<typename TSwap > std::istream& gdcm::Fragment::ReadPreValue (std::istream & is)` `[inline]`

25.126.3.5 `template<typename TSwap > std::istream& gdcm::Fragment::ReadValue (std::istream & is)` `[inline]`

References `gdcmWarningMacro`, and `gdcm::ParseException::SetLastElement()`.

25.126.3.6 `template<typename TSwap > std::ostream& gdcm::Fragment::Write (std::ostream & os) const` `[inline]`

References `gdcm::ByteValue::GetLength()`, `gdcm::VL::Write()`, and `gdcm::ByteValue::Write()`.

25.126.4 Friends And Related Function Documentation

25.126.4.1 `std::ostream& operator<< (std::ostream & os, const Fragment & val)` `[friend]`

The documentation for this class was generated from the following file:

- [gdcmFragment.h](#)

25.127 gdcm::Global Class Reference

[Global](#).

```
#include <gdcmGlobal.h>
```

Public Member Functions

- [Global](#) ()
- [~Global](#) ()
- bool [Append](#) (const char *path)
- [Defs](#) const & [GetDefs](#) () const
- [Dicts](#) const & [GetDicts](#) () const
- [Dicts](#) & [GetDicts](#) ()
- bool [LoadResourcesFiles](#) ()
- bool [Prepend](#) (const char *path)

Static Public Member Functions

- static [Global](#) & [GetInstance](#) ()
return the singleton instance

Protected Member Functions

- const char * [Locate](#) (const char *resfile) const
Locate a ressource file.

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [Global](#) &g)

25.127.1 Detailed Description

[Global](#).

Note

[Global](#) should be included in any translation unit that will use [Dict](#) or that implements the singleton pattern. It makes sure that the [Dict](#) singleton is created before and destroyed after all other singletons in GDCM.

Examples:

[GenAllVR.cxx](#), [GenerateStandardSOPClasses.cxx](#), [GenFakeIdentifyFile.cxx](#), [PublicDict.cxx](#), [ReadAndPrintAttributes.cxx](#), and [TraverseModules.cxx](#).

25.127.2 Constructor & Destructor Documentation

25.127.2.1 `gdcmm::Global::Global ()`

25.127.2.2 `gdcmm::Global::~~Global ()`

25.127.3 Member Function Documentation

25.127.3.1 `bool gdcmm::Global::Append (const char * path)`

Append path at the end of the path list

Warning

not thread safe !

25.127.3.2 `Defs const& gdcmm::Global::GetDefs () const`

retrieve the default/internal (Part 3) You need to explicitly call LoadResourcesFiles before

Examples:

[GenerateStandardSOPClasses.cxx](#).

25.127.3.3 `Dicts const& gdcmm::Global::GetDicts () const`

retrieve the default/internal dicts (Part 6) This dict is filled up at load time

Examples:

[GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [MrProtocol.cxx](#), [PublicDict.cxx](#), and [ReadAndPrintAttributes.cxx](#).

25.127.3.4 `Dicts& gdcmm::Global::GetDicts ()`

25.127.3.5 `static Global& gdcmm::Global::GetInstance () [static]`

return the singleton instance

Examples:

[GenAllVR.cxx](#), [GenerateStandardSOPClasses.cxx](#), [GenFakeIdentifyFile.cxx](#), [MrProtocol.cxx](#), [PublicDict.cxx](#), [ReadAndPrintAttributes.cxx](#), and [TraverseModules.cxx](#).

25.127.3.6 bool gdcm::Global::LoadResourcesFiles ()

Load all internal XML files, ressource path need to have been set before calling this member function (see Append/-Prepend members func)

Warning

not thread safe !

Examples:

[GenerateStandardSOPClasses.cxx](#).

25.127.3.7 const char* gdcm::Global::Locate (const char * *resfile*) const [protected]

Locate a ressource file.

25.127.3.8 bool gdcm::Global::Prepend (const char * *path*)

Prepend path at the begining of the path list

Warning

not thread safe !

25.127.4 Friends And Related Function Documentation**25.127.4.1 std::ostream& operator<< (std::ostream & *_os*, const Global & *g*)** [friend]

The documentation for this class was generated from the following file:

- [gdcmGlobal.h](#)

25.128 gdcm::GroupDict Class Reference

Class to represent the mapping from group number to its abbreviation and name.

```
#include <gdcmGroupDict.h>
```

Public Types

- typedef std::vector< std::string > [GroupStringVector](#)

Public Member Functions

- [GroupDict](#) ()
- [~GroupDict](#) ()
- std::string const & [GetAbbreviation](#) (uint16_t num) const
- std::string const & [GetName](#) (uint16_t num) const
- size_t [Size](#) () const

Protected Member Functions

- void [Add](#) (std::string const &abbreviation, std::string const &name)
- void [Insert](#) (uint16_t num, std::string const &abbreviation, std::string const &name)

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [GroupDict](#) &_val)

25.128.1 Detailed Description

Class to represent the mapping from group number to its abbreviation and name.

Note

Should I rewrite this class to use a std::map instead of std::vector for problem of memory consumption ?

25.128.2 Member Typedef Documentation

25.128.2.1 typedef std::vector<std::string> [gdcm::GroupDict::GroupStringVector](#)

25.128.3 Constructor & Destructor Documentation

25.128.3.1 [gdcm::GroupDict::GroupDict](#) () `[inline]`

25.128.3.2 [gdcm::GroupDict::~~GroupDict](#) () `[inline]`

25.128.4 Member Function Documentation

25.128.4.1 void [gdcm::GroupDict::Add](#) (std::string const & *abbreviation*, std::string const & *name*) `[protected]`

25.128.4.2 std::string const& [gdcm::GroupDict::GetAbbreviation](#) (uint16_t *num*) const

Referenced by [gdcm::operator<<\(\)](#).

25.128.4.3 std::string const& [gdcm::GroupDict::GetName](#) (uint16_t *num*) const

Referenced by [gdcm::operator<<\(\)](#).

25.128.4.4 void `gdcm::GroupDict::Insert` (uint16_t *num*, std::string const & *abbreviation*, std::string const & *name*)
[protected]

25.128.4.5 size_t `gdcm::GroupDict::Size` () const [inline]

Referenced by `gdcm::operator<<()`.

25.128.5 Friends And Related Function Documentation

25.128.5.1 std::ostream& `operator<<` (std::ostream & *_os*, const `GroupDict` & *_val*) [friend]

The documentation for this class was generated from the following file:

- [gdcmGroupDict.h](#)

25.129 gdcm::IconImageFilter Class Reference

IconImageFilter This filter will extract icons from a [gdcm::File](#) This filter will loop over all known sequence (public and private) that may contains an `IconImage` and retrieve them. The filter will fails with a value of false if no icon can be found Since it handle both public and private icon type, one should not assume the icon is in uncompress form, some private vendor store private icon in JPEG8/JPEG12.

```
#include <gdcmIconImageFilter.h>
```

Public Member Functions

- [IconImageFilter](#) ()
- [~IconImageFilter](#) ()
- bool [Extract](#) ()
Extract all Icon found in File.
- [File](#) & [GetFile](#) ()
- const [File](#) & [GetFile](#) () const
- [IconImage](#) & [GetIconImage](#) (unsigned int i) const
- unsigned int [GetNumberOfIconImages](#) () const
Retrieve extract IconImage (need to call Extract first)
- void [SetFile](#) (const [File](#) &f)
Set/Get File.

Protected Member Functions

- void [ExtractIconImages](#) ()
- void [ExtractVeprolIconImages](#) ()

25.129.1 Detailed Description

IconImageFilter This filter will extract icons from a [gdcm::File](#) This filter will loop over all known sequence (public and private) that may contains an `IconImage` and retrieve them. The filter will fails with a value of false if no icon can be

found Since it handle both public and private icon type, one should not assume the icon is in uncompress form, some private vendor store private icon in JPEG8/JPEG12.

Implementation details: This filter supports the following Icons:

- (0088,0200) Icon [Image](#) Sequence
- (0009,10,GEIIS) GE IIS Thumbnail Sequence
- (6003,10,GEMS_Ultrasound_ImageGroup_001) GEMS [Image](#) Thumbnail Sequence
- (0055,30,VEPRO VIF 3.0 DATA) Icon Data
- (0055,30,VEPRO VIM 5.0 DATA) ICONDATA2

Warning

the icon stored in those private attribute do not conform to definition of Icon [Image](#) Sequence (do not simply copy/paste). For example some private icon can be expressed as 12bits pixel, while the DICOM standard only allow 8bits icons.

See Also

[ImageReader](#)

Examples:

[ExtractIconFromFile.cxx](#).

25.129.2 Constructor & Destructor Documentation

25.129.2.1 `gdcm::IconImageFilter::IconImageFilter ()`

25.129.2.2 `gdcm::IconImageFilter::~~IconImageFilter ()`

25.129.3 Member Function Documentation

25.129.3.1 `bool gdcm::IconImageFilter::Extract ()`

Extract all Icon found in [File](#).

Examples:

[ExtractIconFromFile.cxx](#).

25.129.3.2 `void gdcm::IconImageFilter::ExtractIconImages ()` `[protected]`

25.129.3.3 `void gdcm::IconImageFilter::ExtractVeprolconImages ()` `[protected]`

25.129.3.4 `File& gdcm::IconImageFilter::GetFile ()` `[inline]`

25.129.3.5 `const File& gdcm::IconImageFilter::GetFile () const` `[inline]`

25.129.3.6 `IconImage& gdcm::IconImageFilter::GetIconImage (unsigned int i) const`

Examples:

[ExtractIconFromFile.cxx](#).

25.129.3.7 `unsigned int gdcm::IconImageFilter::GetNumberOfIconImages () const`

Retrieve extract IconImage (need to call Extract first)

Examples:

[ExtractIconFromFile.cxx](#).

25.129.3.8 `void gdcm::IconImageFilter::SetFile (const File & f) [inline]`

Set/Get [File](#).

Examples:

[ExtractIconFromFile.cxx](#).

The documentation for this class was generated from the following file:

- [gdcmIconImageFilter.h](#)

25.130 gdcm::IconImageGenerator Class Reference

[IconImageGenerator](#) This filter will generate a valid Icon from the Pixel Data element (an instance of [gdcm::Pixmap](#)). To generate a valid Icon, one is only allowed the following Photometric Interpretation:

```
#include <gdcmIconImageGenerator.h>
```

Public Member Functions

- [IconImageGenerator](#) ()
- [~IconImageGenerator](#) ()
- void [AutoPixelMinMax](#) (bool b)
- void [ConvertRGBToPaletteColor](#) (bool b)
- bool [Generate](#) ()
Generate Icon.
- const [IconImage](#) & [GetIconImage](#) () const
Retrieve generated Icon.
- [Pixmap](#) & [GetPixmap](#) ()
- const [Pixmap](#) & [GetPixmap](#) () const
- void [SetOutputDimensions](#) (const unsigned int dims[2])
Set Target dimension of output Icon.
- void [SetOutsideValuePixel](#) (double v)
- void [SetPixelMinMax](#) (double min, double max)
- void [SetPixmap](#) (const [Pixmap](#) &p)
Set/Get File.

25.130.1 Detailed Description

[IconImageGenerator](#) This filter will generate a valid Icon from the Pixel Data element (an instance of [gdcm::Pixmap](#)). To generate a valid Icon, one is only allowed the following Photometric Interpretation:

- MONOCHROME1
- MONOCHROME2
- PALETTE_COLOR

The Pixel Bits Allocated is restricted to 8bits, therefore 16 bits image needs to be rescaled. By default the filter will use the full scalar range of 16bits image to rescale to unsigned 8bits. This may not be ideal for some situation, in which case the API `SetPixelMinMax` can be used to overwrite the default min,max interval used.

See Also

[ImageReader](#)

Examples:

[ExtractIconFromFile.cxx](#).

25.130.2 Constructor & Destructor Documentation

25.130.2.1 `gdcm::IconImageGenerator::IconImageGenerator ()`

25.130.2.2 `gdcm::IconImageGenerator::~~IconImageGenerator ()`

25.130.3 Member Function Documentation

25.130.3.1 `void gdcm::IconImageGenerator::AutoPixelMinMax (bool b)`

Instead of explicitly specifying the min/max value for the rescale operation, let the internal mechanism compute the min/max of icon and rescale to best appropriate.

Examples:

[ExtractIconFromFile.cxx](#).

25.130.3.2 `void gdcm::IconImageGenerator::ConvertRGBToPaletteColor (bool b)`

Converting from RGB to PALETTE_COLOR can be a slow operation. However DICOM standard requires that color icon be described as palette. Set this boolean to false only if you understand the consequences. true, false generates invalid Icon [Image](#) Sequence

25.130.3.3 `bool gdcm::IconImageGenerator::Generate ()`

Generate Icon.

Examples:

[ExtractIconFromFile.cxx](#).

25.130.3.4 `const IconImage& gdcm::IconImageGenerator::GetIconImage () const` `[inline]`

Retrieve generated Icon.

Examples:

[ExtractIconFromFile.cxx](#).

25.130.3.5 `Pixmap& gdcm::IconImageGenerator::GetPixmap ()` `[inline]`

25.130.3.6 `const Pixmap& gdcm::IconImageGenerator::GetPixmap () const` `[inline]`

25.130.3.7 `void gdcm::IconImageGenerator::SetOutputDimensions (const unsigned int dims[2])`

Set Target dimension of output Icon.

Examples:

[ExtractIconFromFile.cxx](#).

25.130.3.8 `void gdcm::IconImageGenerator::SetOutsideValuePixel (double v)`

Set a pixel value that should be discarded. This happen typically for CT image, where a pixel has been used to pad outside the image (see Pixel Padding [Value](#)). Requires `AutoPixelMinMax(true)`

25.130.3.9 `void gdcm::IconImageGenerator::SetPixelMinMax (double min, double max)`

Override default min/max to compute best rescale for 16bits -> 8bits downscale. Typically those value can be read from the `SmallestImagePixelValue` `LargestImagePixelValue` DICOM attribute.

25.130.3.10 `void gdcm::IconImageGenerator::SetPixmap (const Pixmap & p)` `[inline]`

Set/Get [File](#).

Examples:

[ExtractIconFromFile.cxx](#).

The documentation for this class was generated from the following file:

- [gdcmIconImageGenerator.h](#)

25.131 gdcm::ignore_char Struct Reference

```
#include <gdcmElement.h>
```

Public Member Functions

- [ignore_char](#) (char c)

Public Attributes

- char [m_char](#)

25.131.1 Constructor & Destructor Documentation

25.131.1.1 `gdcm::ignore_char::ignore_char (char c)` `[inline]`

25.131.2 Member Data Documentation

25.131.2.1 `char gdcm::ignore_char::m_char`

Referenced by `gdcm::operator>>()`.

The documentation for this struct was generated from the following file:


- [gdcmElement.h](#)

25.132 gdcm::Image Class Reference

[Image](#) This is the container for an [Image](#) in the general sense. From this container you should be able to request information like:

```
#include <gdcmImage.h>
```

Inheritance diagram for `gdcm::Image`:



- Origin
- Dimension
- [PixelFormat](#) ... But also to retrieve the image as a raw buffer (char *) Since we have to deal with both RAW data and JPEG stream (which internally encode all the above information) this API might seems redundant. One way to solve that would be to subclass [gdcm::Image](#) with [gdcm::JPEGImage](#) which would from the stream extract the header info and fill it to please [gdcm::Image](#)...well except origin for instance

Basically you can see it as a storage for the Pixel Data element (7fe0,0010).

Warning

This class does some heuristics to guess the [Spacing](#) but is not compatible with DICOM CP-586. In case of doubt use [PixmapReader](#) instead

See Also

[ImageReader](#) [PixmapReader](#)

Examples:

[CompressImage.cxx](#), [ConvertToQImage.cxx](#), [CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [csa2img.cxx](#), [ExtractIconFromFile.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GenFakelImage.cxx](#), [GetJPEGSamplePrecision.cxx](#), [GetSubSequenceData.cxx](#), [HelloVizWorld.cxx](#), [iU22tomultisc.cxx](#), [PatchFile.cxx](#), [ReadMultiTimesException.cxx](#), and [threadgdcm.cxx](#).

25.132.2 Constructor & Destructor Documentation

25.132.2.1 `gdcm::Image::Image () [inline]`

25.132.2.2 `gdcm::Image::~~Image () [inline]`

25.132.3 Member Function Documentation

25.132.3.1 `const double* gdcm::Image::GetDirectionCosines () const`

Return a 6-tuples specifying the direction cosines A default value of (1,0,0,0,1,0) will be return when the direction cosines was not specified.

25.132.3.2 `double gdcm::Image::GetDirectionCosines (unsigned int idx) const`

25.132.3.3 `double gdcm::Image::GetIntercept () const [inline]`

25.132.3.4 `const double* gdcm::Image::GetOrigin () const`

Return a 3-tuples specifying the origin Will return (0,0,0) if the origin was not specified.

Examples:

[HelloVizWorld.cxx](#).

25.132.3.5 `double gdc::Image::GetOrigin (unsigned int idx) const`

25.132.3.6 `double gdc::Image::GetSlope () const` `[inline]`

25.132.3.7 `const double* gdc::Image::GetSpacing () const`

Return a 3-tuples specifying the spacing NOTE: 3rd value can be an arbitrary 1 value when the spacing was not specified (ex. 2D image). WARNING: when the spacing is not specifier, a default value of 1 will be returned

25.132.3.8 `double gdc::Image::GetSpacing (unsigned int idx) const`

25.132.3.9 `void gdc::Image::Print (std::ostream & os) const` `[virtual]`

print

Reimplemented from [gdc::Bitmap](#).

Examples:

[CompressImage.cxx](#), and [PatchFile.cxx](#).

25.132.3.10 `void gdc::Image::SetDirectionCosines (const float * dircos)`

25.132.3.11 `void gdc::Image::SetDirectionCosines (const double * dircos)`

25.132.3.12 `void gdc::Image::SetDirectionCosines (unsigned int idx, double dircos)`

25.132.3.13 `void gdc::Image::SetIntercept (double intercept)` `[inline]`

intercept

25.132.3.14 `void gdc::Image::SetOrigin (const float * ori)`

25.132.3.15 `void gdc::Image::SetOrigin (const double * ori)`

25.132.3.16 `void gdc::Image::SetOrigin (unsigned int idx, double ori)`

25.132.3.17 `void gdc::Image::SetSlope (double slope)` `[inline]`

slope

25.132.3.18 `void gdc::Image::SetSpacing (const double * spacing)`

Examples:

[csa2img.cxx](#), and [iU22tomultisc.cxx](#).

25.132.3.19 void gdcm::Image::SetSpacing (unsigned int *idx*, double *spacing*)

The documentation for this class was generated from the following file:


- [gdcmImage.h](#)

25.133 gdcm::ImageApplyLookupTable Class Reference


[ImageApplyLookupTable](#) class It applies the LUT the PixelData (only PALETTE_COLOR images) Output will be a [PhotometricInterpretation](#)=RGB image.

```
#include <gdcmImageApplyLookupTable.h>
```

Inheritance diagram for gdcm::ImageApplyLookupTable:



Collaboration diagram for `gdcm::ImageApplyLookupTable`:



Public Member Functions

- [ImageApplyLookupTable \(\)](#)
- [~ImageApplyLookupTable \(\)](#)
- `bool` [Apply \(\)](#)

Apply.

Additional Inherited Members

25.133.1 Detailed Description

[ImageApplyLookupTable](#) class It applies the LUT the PixelData (only PALETTE_COLOR images) Output will be a [PhotometricInterpretation](#)=RGB image.

25.133.2 Constructor & Destructor Documentation

25.133.2.1 `gdcm::ImageApplyLookupTable::ImageApplyLookupTable ()` `[inline]`

25.133.2.2 `gdcm::ImageApplyLookupTable::~~ImageApplyLookupTable ()` `[inline]`

25.133.3 Member Function Documentation

25.133.3.1 `bool gdcm::ImageApplyLookupTable::Apply ()`

Apply.

The documentation for this class was generated from the following file:


- [gdcmImageApplyLookupTable.h](#)

25.134 gdcm::ImageChangePhotometricInterpretation Class Reference


[ImageChangePhotometricInterpretation](#) class Class to change the Photometric Interpretation of an input DICOM.

```
#include <gdcmImageChangePhotometricInterpretation.h>
```

Inheritance diagram for `gdcm::ImageChangePhotometricInterpretation`:



Collaboration diagram for gdcm::ImageChangePhotometricInterpretation:



Public Member Functions

- [ImageChangePhotometricInterpretation](#) ()
- [~ImageChangePhotometricInterpretation](#) ()
- [bool Change](#) ()
 Change.
- [const PhotometricInterpretation & GetPhotometricInterpretation](#) () const
- [template<typename T > void RGB2YBR](#) (T ybr[3], const T rgb[3])
- [void SetPhotometricInterpretation](#) ([PhotometricInterpretation](#) const &pi)

Set/Get requested [PhotometricInterpretation](#).

- `template<typename T >`
`void YBR2RGB (T rgb[3], const T ybr[3])`

Static Public Member Functions

- `template<typename T >`
`static void RGB2YBR (T ybr[3], const T rgb[3])`
colorspace conversion (based on CCIR Recommendation 601-2)
- `template<typename T >`
`static void YBR2RGB (T rgb[3], const T ybr[3])`

Protected Member Functions

- `bool ChangeMonochrome ()`

Additional Inherited Members

25.134.1 Detailed Description

[ImageChangePhotometricInterpretation](#) class Class to change the Photometric Interpretation of an input DICOM.

25.134.2 Constructor & Destructor Documentation

25.134.2.1 `gdcm::ImageChangePhotometricInterpretation::ImageChangePhotometricInterpretation ()` `[inline]`

25.134.2.2 `gdcm::ImageChangePhotometricInterpretation::~~ImageChangePhotometricInterpretation ()` `[inline]`

25.134.3 Member Function Documentation

25.134.3.1 `bool gdcm::ImageChangePhotometricInterpretation::Change ()`

Change.

25.134.3.2 `bool gdcm::ImageChangePhotometricInterpretation::ChangeMonochrome ()` `[protected]`

25.134.3.3 `const PhotometricInterpretation& gdcm::ImageChangePhotometricInterpretation::GetPhotometricInterpretation ()`
`const` `[inline]`

25.134.3.4 `template<typename T > static void gdcm::ImageChangePhotometricInterpretation::RGB2YBR (T ybr[3], const T rgb[3]`
`)` `[static]`

colorspace conversion (based on CCIR Recommendation 601-2)

25.134.3.5 `template<typename T > void gdcm::ImageChangePhotometricInterpretation::RGB2YBR (T ybr[3], const T rgb[3])`

25.134.3.6 void gdcm::ImageChangePhotometricInterpretation::SetPhotometricInterpretation (PhotometricInterpretation const & *pi*) [inline]

Set/Get requested [PhotometricInterpretation](#).

25.134.3.7 template<typename T > static void gdcm::ImageChangePhotometricInterpretation::YBR2RGB (T *rgb*[3], const T *ybr*[3]) [static]

25.134.3.8 template<typename T > void gdcm::ImageChangePhotometricInterpretation::YBR2RGB (T *rgb*[3], const T *ybr*[3])

The documentation for this class was generated from the following file:


- [gdcmImageChangePhotometricInterpretation.h](#)

25.135 gdcm::ImageChangePlanarConfiguration Class Reference


[ImageChangePlanarConfiguration](#) class Class to change the Planar configuration of an input DICOM By default it will change into the more usual representation: PlanarConfiguration = 0.

```
#include <gdcmImageChangePlanarConfiguration.h>
```

Inheritance diagram for gdcm::ImageChangePlanarConfiguration:



Collaboration diagram for `gdcm::ImageChangePlanarConfiguration`:



Public Member Functions

- [ImageChangePlanarConfiguration](#) ()
- [~ImageChangePlanarConfiguration](#) ()
- `bool` [Change](#) ()
 - Change.*
- `unsigned int` [GetPlanarConfiguration](#) () const
- `template<typename T >`
`size_t` [RGBPixelsToRGBPlanes](#) (T *r, T *g, T *b, const T *rgb, size_t s)
- `template<typename T >`
`size_t` [RGBPlanesToRGBPixels](#) (T *out, const T *r, const T *g, const T *b, size_t s)

- void [SetPlanarConfiguration](#) (unsigned int pc)
Set/Get requested PlanarConfiguration.

Static Public Member Functions

- template<typename T >
static size_t [RGBPixelsToRGBPlanes](#) (T *r, T *g, T *b, const T *rgb, size_t s)
- template<typename T >
static size_t [RGBPlanesToRGBPixels](#) (T *out, const T *r, const T *g, const T *b, size_t s)

Additional Inherited Members

25.135.1 Detailed Description

[ImageChangePlanarConfiguration](#) class Class to change the Planar configuration of an input DICOM By default it will change into the more usual representation: PlanarConfiguration = 0.

25.135.2 Constructor & Destructor Documentation

25.135.2.1 `gdcm::ImageChangePlanarConfiguration::ImageChangePlanarConfiguration ()` `[inline]`

25.135.2.2 `gdcm::ImageChangePlanarConfiguration::~~ImageChangePlanarConfiguration ()` `[inline]`

25.135.3 Member Function Documentation

25.135.3.1 `bool gdcm::ImageChangePlanarConfiguration::Change ()`

Change.

25.135.3.2 `unsigned int gdcm::ImageChangePlanarConfiguration::GetPlanarConfiguration () const` `[inline]`

25.135.3.3 `template<typename T > static size_t gdcm::ImageChangePlanarConfiguration::RGBPixelsToRGBPlanes (T * r, T * g, T * b, const T * rgb, size_t s)` `[static]`

Convert a regular RGB pixel image (R,G,B,R,G,B...) into a planar R,G,B image (R,R...,G,G...,B,B)

Warning

this works on a frame basis, you need to loop over all frames in multiple frames image to apply this function

25.135.3.4 `template<typename T > static size_t gdcm::ImageChangePlanarConfiguration::RGBPixelsToRGBPlanes (T * r, T * g, T * b, const T * rgb, size_t s)`

25.135.3.5 `template<typename T > static size_t gdcm::ImageChangePlanarConfiguration::RGBPlanesToRGBPixels (T * out, const T * r, const T * g, const T * b, size_t s)` `[static]`

s is the size of one plane (r,g or b). Thus the output buffer needs to be at least 3*s bytes long s can be seen as the number of RGB pixels in the output

25.135.3.6 `template<typename T> size_t gdcmm::ImageChangePlanarConfiguration::RGBPlanesToRGBPixels (T * out, const T * r, const T * g, const T * b, size_t s)`

25.135.3.7 `void gdcmm::ImageChangePlanarConfiguration::SetPlanarConfiguration (unsigned int pc) [inline]`

Set/Get requested PlanarConfiguration.

The documentation for this class was generated from the following file:


- [gdcmmImageChangePlanarConfiguration.h](#)

25.136 gdcmm::ImageChangeTransferSyntax Class Reference


[ImageChangeTransferSyntax](#) class Class to change the transfer syntax of an input DICOM.

```
#include <gdcmmImageChangeTransferSyntax.h>
```

Inheritance diagram for gdcmm::ImageChangeTransferSyntax:



Collaboration diagram for gdcm::ImageChangeTransferSyntax:



Public Member Functions

- [ImageChangeTransferSyntax](#) ()
- [~ImageChangeTransferSyntax](#) ()
- [bool Change](#) ()
Change.
- [const TransferSyntax & GetTransferSyntax](#) () const
Get Transfer Syntax.
- [void SetCompressIconImage](#) (bool b)

- void [SetForce](#) (bool f)
- void [SetTransferSyntax](#) (const [TransferSyntax](#) &ts)
Set target Transfer Syntax.
- void [SetUserCodec](#) ([ImageCodec](#) *ic)

Protected Member Functions

- bool [TryJPEG2000Codec](#) (const [DataElement](#) &pixelde, [Bitmap](#) const &input, [Bitmap](#) &output)
- bool [TryJPEGCodec](#) (const [DataElement](#) &pixelde, [Bitmap](#) const &input, [Bitmap](#) &output)
- bool [TryJPEGLSCodec](#) (const [DataElement](#) &pixelde, [Bitmap](#) const &input, [Bitmap](#) &output)
- bool [TryRAWCodec](#) (const [DataElement](#) &pixelde, [Bitmap](#) const &input, [Bitmap](#) &output)
- bool [TryRLECodec](#) (const [DataElement](#) &pixelde, [Bitmap](#) const &input, [Bitmap](#) &output)

Additional Inherited Members

25.136.1 Detailed Description

[ImageChangeTransferSyntax](#) class Class to change the transfer syntax of an input DICOM.

If only Force param is set but no input [TransferSyntax](#) is set, it is assumed that user only wants to inspect encapsulated stream (advanced dev. option).

When using UserCodec it is very important that the [TransferSyntax](#) (as set in [SetTransferSyntax](#)) is actually understood by UserCodec (ie. `UserCodec->CanCode(TransferSyntax)`). Otherwise the behavior is to use a default codec.

See Also

[JPEGCodec](#) [JPEGLSCodec](#) [JPEG2000Codec](#)

Examples:

[CompressImage.cxx](#).

25.136.2 Constructor & Destructor Documentation

25.136.2.1 `gdcm::ImageChangeTransferSyntax::ImageChangeTransferSyntax ()` `[inline]`

25.136.2.2 `gdcm::ImageChangeTransferSyntax::~ImageChangeTransferSyntax ()` `[inline]`

25.136.3 Member Function Documentation

25.136.3.1 `bool gdcm::ImageChangeTransferSyntax::Change ()`

Change.

Examples:

[CompressImage.cxx](#).

25.136.3.2 `const TransferSyntax& gdcm::ImageChangeTransferSyntax::GetTransferSyntax () const` `[inline]`

Get Transfer Syntax.

25.136.3.3 void gdcm::ImageChangeTransferSyntax::SetCompressIconImage (bool *b*) [inline]

Decide whether or not to also compress the Icon [Image](#) using the same Transfer Syntax Default is to simply decompress icon image

25.136.3.4 void gdcm::ImageChangeTransferSyntax::SetForce (bool *f*) [inline]

When target Transfer Syntax is identical to input target syntax, no operation is actually done This is an issue when someone wants to recompress using GDCM internal implementation a JPEG (for example) image

25.136.3.5 void gdcm::ImageChangeTransferSyntax::SetTransferSyntax (const TransferSyntax & *ts*) [inline]

Set target Transfer Syntax.

Examples:

[CompressImage.cxx](#).

25.136.3.6 void gdcm::ImageChangeTransferSyntax::SetUserCodec (ImageCodec * *ic*) [inline]

Allow user to specify exactly which codec to use. this is needed to specify special qualities or compression option.

Warning

is the codec 'ic' is not compatible with the [TransferSyntax](#) requested, it will not be used. It is the user responsibility to check that UserCodec->CanCode(TransferSyntax)

25.136.3.7 bool gdcm::ImageChangeTransferSyntax::TryJPEG2000Codec (const DataElement & *pixelde*, Bitmap const & *input*, Bitmap & *output*) [protected]

25.136.3.8 bool gdcm::ImageChangeTransferSyntax::TryJPEGCodec (const DataElement & *pixelde*, Bitmap const & *input*, Bitmap & *output*) [protected]

25.136.3.9 bool gdcm::ImageChangeTransferSyntax::TryJPEGLSCodec (const DataElement & *pixelde*, Bitmap const & *input*, Bitmap & *output*) [protected]

25.136.3.10 bool gdcm::ImageChangeTransferSyntax::TryRAWCodec (const DataElement & *pixelde*, Bitmap const & *input*, Bitmap & *output*) [protected]

25.136.3.11 bool gdcm::ImageChangeTransferSyntax::TryRLECodec (const DataElement & *pixelde*, Bitmap const & *input*, Bitmap & *output*) [protected]

The documentation for this class was generated from the following file:


- [gdcmImageChangeTransferSyntax.h](#)

25.137 gdcm::ImageCodec Class Reference


[ImageCodec](#).

```
#include <gdcmImageCodec.h>
```

Inheritance diagram for gdcm::ImageCodec:



Collaboration diagram for gdcm::ImageCodec:



Public Member Functions

- [ImageCodec](#) ()
- [~ImageCodec](#) ()
- bool [CanCode](#) ([TransferSyntax](#) const &) const
Return whether this coder support this transfer syntax (can code it)
- bool [CanDecode](#) ([TransferSyntax](#) const &) const
Return whether this decoder support this transfer syntax (can decode it)
- bool [Decode](#) ([DataElement](#) const &is_, [DataElement](#) &os)
Decode.
- const unsigned int * [GetDimensions](#) () const

- virtual bool [GetHeaderInfo](#) (std::istream &is_, [TransferSyntax](#) &ts)
- bool [GetLossyFlag](#) () const
- const [LookupTable](#) & [GetLUT](#) () const
- bool [GetNeedByteSwap](#) () const
- unsigned int [GetNumberOfDimensions](#) () const
- const [PhotometricInterpretation](#) & [GetPhotometricInterpretation](#) () const
- [PixelFormat](#) & [GetPixelFormat](#) ()
- const [PixelFormat](#) & [GetPixelFormat](#) () const
- unsigned int [GetPlanarConfiguration](#) () const
- bool [IsLossy](#) () const
- void [SetDimensions](#) (const unsigned int d[3])
- void [SetDimensions](#) (const std::vector< unsigned int > &d)
- void [SetLossyFlag](#) (bool l)
- void [SetLUT](#) ([LookupTable](#) const &lut)
- void [SetNeedByteSwap](#) (bool b)
- void [SetNeedOverlayCleanup](#) (bool b)
- void [SetNumberOfDimensions](#) (unsigned int dim)
- void [SetPhotometricInterpretation](#) ([PhotometricInterpretation](#) const &pi)
- virtual void [SetPixelFormat](#) ([PixelFormat](#) const &pf)
- void [SetPlanarConfiguration](#) (unsigned int pc)

Protected Types

- typedef [SmartPointer](#)< [LookupTable](#) > [LUTPtr](#)

Protected Member Functions

- bool [DecodeByStreams](#) (std::istream &is_, std::ostream &os)
- bool [DoByteSwap](#) (std::istream &is_, std::ostream &os)
- bool [DoInvertMonochrome](#) (std::istream &is_, std::ostream &os)
- bool [DoOverlayCleanup](#) (std::istream &is_, std::ostream &os)
- bool [DoPaddedCompositePixelCode](#) (std::istream &is_, std::ostream &os)
- bool [DoPlanarConfiguration](#) (std::istream &is_, std::ostream &os)
- bool [DoSimpleCopy](#) (std::istream &is_, std::ostream &os)
- bool [DoYBR](#) (std::istream &is_, std::ostream &os)
- virtual bool [IsValid](#) ([PhotometricInterpretation](#) const &pi)

Protected Attributes

- unsigned int [Dimensions](#) [3]
- bool [LossyFlag](#)
- [LUTPtr](#) [LUT](#)
- bool [NeedByteSwap](#)
- bool [NeedOverlayCleanup](#)
- unsigned int [NumberOfDimensions](#)
- [PixelFormat](#) [PF](#)
- [PhotometricInterpretation](#) [PI](#)
- unsigned int [PlanarConfiguration](#)
- bool [RequestPaddedCompositePixelCode](#)
- bool [RequestPlanarConfiguration](#)

Friends

- class [ImageChangePhotometricInterpretation](#)

25.137.1 Detailed Description

[ImageCodec](#).

Note

Main codec, this is a central place for all implementation

25.137.2 Member Typedef Documentation

25.137.2.1 `typedef SmartPointer<LookupTable> gdcm::ImageCodec::LUTPtr` `[protected]`

25.137.3 Constructor & Destructor Documentation

25.137.3.1 `gdcm::ImageCodec::ImageCodec ()`

25.137.3.2 `gdcm::ImageCodec::~~ImageCodec ()`

25.137.4 Member Function Documentation

25.137.4.1 `bool gdcm::ImageCodec::CanCode (TransferSyntax const &) const` `[inline], [virtual]`

Return whether this coder support this transfer syntax (can code it)

Implements [gdcm::Coder](#).

Reimplemented in [gdcm::JPEGCodec](#), [gdcm::RLECodec](#), [gdcm::PVRGCodec](#), [gdcm::JPEG2000Codec](#), [gdcm::JPEG-LSCoec](#), [gdcm::PNMCodec](#), [gdcm::PGXCodec](#), [gdcm::KAKADUCoec](#), and [gdcm::RAWCodec](#).

25.137.4.2 `bool gdcm::ImageCodec::CanDecode (TransferSyntax const &) const` `[inline], [virtual]`

Return whether this decoder support this transfer syntax (can decode it)

Implements [gdcm::Decoder](#).

Reimplemented in [gdcm::JPEGCodec](#), [gdcm::RLECodec](#), [gdcm::PVRGCodec](#), [gdcm::JPEG2000Codec](#), [gdcm::JPEG-LSCoec](#), [gdcm::PNMCodec](#), [gdcm::RAWCodec](#), [gdcm::PGXCodec](#), and [gdcm::KAKADUCoec](#).

25.137.4.3 `bool gdcm::ImageCodec::Decode (DataElement const & , DataElement &)` `[virtual]`

Decode.

Reimplemented from [gdcm::Decoder](#).

Reimplemented in [gdcm::JPEGCodec](#), [gdcm::RLECodec](#), [gdcm::JPEGLSCoec](#), [gdcm::PVRGCodec](#), [gdcm::JPEG2000Codec](#), [gdcm::KAKADUCoec](#), and [gdcm::RAWCodec](#).

25.137.4.4 `bool gdcm::ImageCodec::DecodeByStreams (std::istream & is, std::ostream & os)` `[protected]`,
`[virtual]`

Reimplemented from [gdcm::Decoder](#).

Reimplemented in [gdcm::JPEGCodec](#), [gdcm::JPEG2000Codec](#), [gdcm::RLECodec](#), [gdcm::RAWCodec](#), [gdcm::JPEG12Codec](#), [gdcm::JPEG16Codec](#), and [gdcm::JPEG8Codec](#).

25.137.4.5 `bool gdcm::ImageCodec::DoByteSwap (std::istream & is, std::ostream & os)` `[protected]`

25.137.4.6 `bool gdcm::ImageCodec::DoInvertMonochrome (std::istream & is, std::ostream & os)` `[protected]`

25.137.4.7 `bool gdcm::ImageCodec::DoOverlayCleanup (std::istream & is, std::ostream & os)` `[protected]`

25.137.4.8 `bool gdcm::ImageCodec::DoPaddedCompositePixelCode (std::istream & is, std::ostream & os)` `[protected]`

25.137.4.9 `bool gdcm::ImageCodec::DoPlanarConfiguration (std::istream & is, std::ostream & os)` `[protected]`

25.137.4.10 `bool gdcm::ImageCodec::DoSimpleCopy (std::istream & is, std::ostream & os)` `[protected]`

25.137.4.11 `bool gdcm::ImageCodec::DoYBR (std::istream & is, std::ostream & os)` `[protected]`

25.137.4.12 `const unsigned int* gdcm::ImageCodec::GetDimensions () const` `[inline]`

25.137.4.13 `virtual bool gdcm::ImageCodec::GetHeaderInfo (std::istream & is, TransferSyntax & ts)` `[virtual]`

Reimplemented in [gdcm::JPEGCodec](#), [gdcm::RLECodec](#), [gdcm::JPEGLSCodec](#), [gdcm::JPEG2000Codec](#), [gdcm::PNMCodec](#), [gdcm::JPEG12Codec](#), [gdcm::JPEG16Codec](#), [gdcm::JPEG8Codec](#), [gdcm::RAWCodec](#), and [gdcm::PGXCodec](#).

25.137.4.14 `bool gdcm::ImageCodec::GetLossyFlag () const`

25.137.4.15 `const LookupTable& gdcm::ImageCodec::GetLUT () const` `[inline]`

25.137.4.16 `bool gdcm::ImageCodec::GetNeedByteSwap () const` `[inline]`

25.137.4.17 `unsigned int gdcm::ImageCodec::GetNumberOfDimensions () const`

25.137.4.18 `const PhotometricInterpretation& gdcm::ImageCodec::GetPhotometricInterpretation () const`

25.137.4.19 `PixelFormat& gdcm::ImageCodec::GetPixelFormat ()` `[inline]`

Examples:

[GetJPEGSamplePrecision.cxx](#).

25.137.4.20 `const PixelFormat& gdcm::ImageCodec::GetPixelFormat () const` `[inline]`

25.137.4.21 `unsigned int gdcm::ImageCodec::GetPlanarConfiguration () const` `[inline]`

25.137.4.22 `bool gdcm::ImageCodec::IsLossy () const`

25.137.4.23 `virtual bool gdcM::ImageCodec::IsValid (PhotometricInterpretation const & pi)` [protected],
[virtual]

Reimplemented in [gdcM::JPEGCodec](#).

25.137.4.24 `void gdcM::ImageCodec::SetDimensions (const unsigned int d[3])`

Examples:

[ExtractIconFromFile.cxx](#).

25.137.4.25 `void gdcM::ImageCodec::SetDimensions (const std::vector< unsigned int > & d)`

25.137.4.26 `void gdcM::ImageCodec::SetLossyFlag (bool l)`

25.137.4.27 `void gdcM::ImageCodec::SetLUT (LookupTable const & lut)` [inline]

Examples:

[ExtractIconFromFile.cxx](#).

25.137.4.28 `void gdcM::ImageCodec::SetNeedByteSwap (bool b)` [inline]

25.137.4.29 `void gdcM::ImageCodec::SetNeedOverlayCleanup (bool b)` [inline]

25.137.4.30 `void gdcM::ImageCodec::SetNumberOfDimensions (unsigned int dim)`

25.137.4.31 `void gdcM::ImageCodec::SetPhotometricInterpretation (PhotometricInterpretation const & pi)`

Examples:

[ExtractIconFromFile.cxx](#).

25.137.4.32 `virtual void gdcM::ImageCodec::SetPixelFormat (PixelFormat const & pf)` [inline],[virtual]

Reimplemented in [gdcM::JPEGCodec](#).

Examples:

[ExtractIconFromFile.cxx](#).

25.137.4.33 `void gdcM::ImageCodec::SetPlanarConfiguration (unsigned int pc)` [inline]

25.137.5 Friends And Related Function Documentation

25.137.5.1 `friend class ImageChangePhotometricInterpretation` [friend]

25.137.6 Member Data Documentation

- 25.137.6.1 unsigned int gdcm::ImageCodec::Dimensions[3] [protected]
- 25.137.6.2 bool gdcm::ImageCodec::LossyFlag [protected]
- 25.137.6.3 LUTPtr gdcm::ImageCodec::LUT [protected]
- 25.137.6.4 bool gdcm::ImageCodec::NeedByteSwap [protected]
- 25.137.6.5 bool gdcm::ImageCodec::NeedOverlayCleanup [protected]
- 25.137.6.6 unsigned int gdcm::ImageCodec::NumberOfDimensions [protected]
- 25.137.6.7 PixelFormat gdcm::ImageCodec::PF [protected]
- 25.137.6.8 PhotometricInterpretation gdcm::ImageCodec::PI [protected]
- 25.137.6.9 unsigned int gdcm::ImageCodec::PlanarConfiguration [protected]
- 25.137.6.10 bool gdcm::ImageCodec::RequestPaddedCompositePixelCode [protected]
- 25.137.6.11 bool gdcm::ImageCodec::RequestPlanarConfiguration [protected]

The documentation for this class was generated from the following file:

- [gdcmImageCodec.h](#)

25.138 gdcm::ImageConverter Class Reference

[Image](#) Converter.

```
#include <gdcmImageConverter.h>
```

Public Member Functions

- [ImageConverter](#) ()
- [~ImageConverter](#) ()
- void [Convert](#) ()
- const [Image](#) & [GetOutput](#) () const
- void [SetInput](#) ([Image](#) const &input)

25.138.1 Detailed Description

[Image](#) Converter.

Note

This is the class used to convert from on [gdcm::Image](#) to another This is typically used to convert let say YBR JPEG compressed [gdcm::Image](#) to a RAW RGB [gdcm::Image](#). So that the buffer can be directly pass to third party application. This filter is application level and not integrated directly in GDCM

25.138.2 Constructor & Destructor Documentation

25.138.2.1 `gdcm::ImageConverter::ImageConverter ()`

25.138.2.2 `gdcm::ImageConverter::~~ImageConverter ()`

25.138.3 Member Function Documentation

25.138.3.1 `void gdcm::ImageConverter::Convert ()`

25.138.3.2 `const Image& gdcm::ImageConverter::GetOutput () const`

25.138.3.3 `void gdcm::ImageConverter::SetInput (Image const & input)`

The documentation for this class was generated from the following file:


- [gdcmImageConverter.h](#)

25.139 gdcm::ImageFragmentSplitter Class Reference


[ImageFragmentSplitter](#) class For single frame image, DICOM standard allow splitting the frame into multiple fragments.

```
#include <gdcmImageFragmentSplitter.h>
```

Inheritance diagram for `gdcm::ImageFragmentSplitter`:



Collaboration diagram for gdcm::ImageFragmentSplitter:



Public Member Functions

- [ImageFragmentSplitter](#) ()
- [~ImageFragmentSplitter](#) ()
- unsigned int [GetFragmentSizeMax](#) () const
- void [SetForce](#) (bool f)
- void [SetFragmentSizeMax](#) (unsigned int fragsize)
FragmentSizeMax needs to be an even number.
- bool [Split](#) ()
Split.

Additional Inherited Members

25.139.1 Detailed Description

[ImageFragmentSplitter](#) class For single frame image, DICOM standard allow splitting the frame into multiple fragments.

25.139.2 Constructor & Destructor Documentation

25.139.2.1 `gdcm::ImageFragmentSplitter::ImageFragmentSplitter ()` [\[inline\]](#)

25.139.2.2 `gdcm::ImageFragmentSplitter::~~ImageFragmentSplitter ()` [\[inline\]](#)

25.139.3 Member Function Documentation

25.139.3.1 `unsigned int gdcm::ImageFragmentSplitter::GetFragmentSizeMax () const` [\[inline\]](#)

25.139.3.2 `void gdcm::ImageFragmentSplitter::SetForce (bool f)` [\[inline\]](#)

When file already has all it's segment < FragmentSizeMax there is not need to run the filter. Unless the user explicitly say 'force' recomputation !

25.139.3.3 `void gdcm::ImageFragmentSplitter::SetFragmentSizeMax (unsigned int fragsize)`

FragmentSizeMax needs to be an even number.

25.139.3.4 `bool gdcm::ImageFragmentSplitter::Split ()`

Split.

The documentation for this class was generated from the following file:

- [gdcmImageFragmentSplitter.h](#)

25.140 gdcm::ImageHelper Class Reference

[ImageHelper](#) (internal class, not intended for user level)

```
#include <gdcmImageHelper.h>
```

Static Public Member Functions

- static bool [ComputeSpacingFromImagePositionPatient](#) (const std::vector< double > &imageposition, std::vector< double > &spacing)
DO NOT USE.
- static std::vector< unsigned int > [GetDimensionsValue](#) (const [File](#) &f)
- static bool [GetDirectionCosinesFromDataSet](#) ([DataSet](#) const &ds, std::vector< double > &dircos)
- static std::vector< double > [GetDirectionCosinesValue](#) ([File](#) const &f)
- static bool [GetForcePixelSpacing](#) ()
- static bool [GetForceRescaleInterceptSlope](#) ()

- static [SmartPointer](#)< [LookupTable](#) > [GetLUT](#) ([File](#) const &f)
- static std::vector< double > [GetOriginValue](#) ([File](#) const &f)
Set/Get Origin (IPP) from/to a file.
- static [PhotometricInterpretation](#) [GetPhotometricInterpretationValue](#) ([File](#) const &f)
- static [PixelFormat](#) [GetPixelFormatValue](#) (const [File](#) &f)
- static unsigned int [GetPlanarConfigurationValue](#) (const [File](#) &f)
- static const [ByteValue](#) * [GetPointerFromElement](#) ([Tag](#) const &tag, [File](#) const &f)
Moved from PixampReader to here. Generally used for photometric interpretation.
- static std::vector< double > [GetRescaleInterceptSlopeValue](#) ([File](#) const &f)
- static std::vector< double > [GetSpacingValue](#) ([File](#) const &f)
Set/Get [Spacing](#) from/to a [File](#).
- static void [SetDimensionsValue](#) ([File](#) &f, const [Image](#) &img)
- static void [SetDirectionCosinesValue](#) ([DataSet](#) &ds, const std::vector< double > &dircos)
- static void [SetForcePixelSpacing](#) (bool)
- static void [SetForceRescaleInterceptSlope](#) (bool)
- static void [SetOriginValue](#) ([DataSet](#) &ds, const [Image](#) &img)
- static void [SetRescaleInterceptSlopeValue](#) ([File](#) &f, const [Image](#) &img)
- static void [SetSpacingValue](#) ([DataSet](#) &ds, const std::vector< double > &spacing)

Static Protected Member Functions

- static [Tag](#) [GetSpacingTagFromMediaStorage](#) ([MediaStorage](#) const &ms)
- static [Tag](#) [GetZSpacingTagFromMediaStorage](#) ([MediaStorage](#) const &ms)

25.140.1 Detailed Description

[ImageHelper](#) (internal class, not intended for user level)

Helper for writing World images in DICOM. DICOM has a 'template' approach to image where MR [Image](#) Storage are distinct object from Enhanced MR [Image](#) Storage. For example the Pixel [Spacing](#) in one object is not at the same position (ie [Tag](#)) as in the other this class is the central (read: fragile) place where all the dispatching is done from a unified view of a world image (typically VTK or ITK point of view) down to the low level DICOM point of view.

Warning

: do not expect the API of this class to be maintained at any point, since as Modalities are added the API might have to be augmented or behavior changed to cope with new modalities.

25.140.2 Member Function Documentation

- 25.140.2.1 static bool gdcm::ImageHelper::ComputeSpacingFromImagePositionPatient (const std::vector< double > & *imageposition*, std::vector< double > & *spacing*) [static]

DO NOT USE.

25.140.2.2 `static std::vector<unsigned int> gdcm::ImageHelper::GetDimensionsValue (const File & f) [static]`

This function checks tags (0x0028, 0x0010) and (0x0028, 0x0011) for the rows and columns of the image in pixels (as opposed to actual distances). The output is {col , row}

Examples:

[Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), and [StreamImageReaderTest.cxx](#).

25.140.2.3 `static bool gdcm::ImageHelper::GetDirectionCosinesFromDataSet (DataSet const & ds, std::vector< double > & dircos) [static]`

25.140.2.4 `static std::vector<double> gdcm::ImageHelper::GetDirectionCosinesValue (File const & f) [static]`

Get Direction Cosines (IOP) from/to a file Requires a file because mediastorage must be known

25.140.2.5 `static bool gdcm::ImageHelper::GetForcePixelSpacing () [static]`

25.140.2.6 `static bool gdcm::ImageHelper::GetForceRescaleInterceptSlope () [static]`

25.140.2.7 `static SmartPointer<LookupTable> gdcm::ImageHelper::GetLUT (File const & f) [static]`

25.140.2.8 `static std::vector<double> gdcm::ImageHelper::GetOriginValue (File const & f) [static]`

Set/Get Origin (IPP) from/to a file.

25.140.2.9 `static PhotometricInterpretation gdcm::ImageHelper::GetPhotometricInterpretationValue (File const & f) [static]`

25.140.2.10 `static PixelFormat gdcm::ImageHelper::GetPixelFormatValue (const File & f) [static]`

This function returns pixel information about an image from its dataset That includes samples per pixel and bit depth (in that order)

25.140.2.11 `static unsigned int gdcm::ImageHelper::GetPlanarConfigurationValue (const File & f) [static]`

25.140.2.12 `static const ByteValue* gdcm::ImageHelper::GetPointerFromElement (Tag const & tag, File const & f) [static]`

Moved from PixampReader to here. Generally used for photometric interpretation.

25.140.2.13 `static std::vector<double> gdcm::ImageHelper::GetRescaleInterceptSlopeValue (File const & f) [static]`

Set/Get shift/scale from/to a file

Warning

this function reads/sets the Slope/Intercept in appropriate class storage, but also Grid Scaling in RT Dose Storage Can't take a dataset because the mediastorage of the file must be known

25.140.2.14 `static Tag gdcm::ImageHelper::GetSpacingTagFromMediaStorage (MediaStorage const & ms) [static], [protected]`

25.140.2.15 `static std::vector<double> gdcm::ImageHelper::GetSpacingValue (File const & f) [static]`

Set/Get [Spacing](#) from/to a [File](#).

25.140.2.16 `static Tag gdcm::ImageHelper::GetZSpacingTagFromMediaStorage (MediaStorage const & ms) [static], [protected]`

25.140.2.17 `static void gdcm::ImageHelper::SetDimensionsValue (File & f, const Image & img) [static]`

25.140.2.18 `static void gdcm::ImageHelper::SetDirectionCosinesValue (DataSet & ds, const std::vector< double > & dircos) [static]`

Set Direction Cosines (IOP) from/to a file When [IOD](#) does not defines what is IOP (eg. typically Secondary Capture [Image](#) Storage) this call will simply remove the IOP attribute. Else in case of MR/CT image storage, this call will properly lookup the correct attribute to store the IOP.

25.140.2.19 `static void gdcm::ImageHelper::SetForcePixelSpacing (bool) [static]`

GDCM 1.x compatibility issue: When using ReWrite an MR [Image](#) Storage would be rewritten as Secondary Capture [Object](#) while still having a Pixel [Spacing](#) tag (0028,0030). If you have deal with those files, use this very special flag to handle them Unless explicitly set elsewhere by the standard, it will use value from 0028,0030 / 0018,0088 for the Pixel [Spacing](#) of the [Image](#)

25.140.2.20 `static void gdcm::ImageHelper::SetForceRescaleInterceptSlope (bool) [static]`

GDCM 1.x compatibility issue: when using ReWrite an MR [Image](#) Storage would be rewritten with a Rescale Slope/- Intercept while the standard would prohibit this (Philips Medical [System](#) is still doing that) Unless explicitly set elsewhere by the standard, it will use value from 0028,1052 / 0028,1053 for the Rescale Slope & Rescale Intercept values

25.140.2.21 `static void gdcm::ImageHelper::SetOriginValue (DataSet & ds, const Image & img) [static]`

25.140.2.22 `static void gdcm::ImageHelper::SetRescaleInterceptSlopeValue (File & f, const Image & img) [static]`

25.140.2.23 `static void gdcm::ImageHelper::SetSpacingValue (DataSet & ds, const std::vector< double > & spacing) [static]`

The documentation for this class was generated from the following file:


- [gdcmImageHelper.h](#)

25.141 gdcm::ImageReader Class Reference


[ImageReader](#).

```
#include <gdcmImageReader.h>
```

Inheritance diagram for `gdcm::ImageReader`:



Collaboration diagram for gdcm::ImageReader:



Public Member Functions

- [ImageReader](#) ()
- virtual [~ImageReader](#) ()
- const [Image](#) & [GetImage](#) () const
Return the read image.
- [Image](#) & [GetImage](#) ()
- virtual bool [Read](#) ()

Protected Member Functions

- bool [ReadACRNEMAIImage](#) ()
- bool [ReadImage](#) ([MediaStorage](#) const &ms)

Additional Inherited Members

25.141.1 Detailed Description

[ImageReader](#).

Note

its role is to convert the DICOM [DataSet](#) into a [gdcm::Image](#) representation [Image](#) is different from [Pixmap](#) has it has a position and a direction in Space.

See Also

[Image](#)

Examples:

[CheckBigEndianBug.cxx](#), [CompressImage.cxx](#), [ConvertToQImage.cxx](#), [ExtractIconFromFile.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GetJPEGSamplePrecision.cxx](#), [HelloVizWorld.cxx](#), [MergeTwoFiles.cxx](#), [MrProtocol.cxx](#), [PatchFile.cxx](#), [ReadMultiTimesException.cxx](#), and [threadgdcm.cxx](#).

25.141.2 Constructor & Destructor Documentation

25.141.2.1 [gdcm::ImageReader::ImageReader \(\)](#)

25.141.2.2 [virtual gdcm::ImageReader::~~ImageReader \(\)](#) [virtual]

25.141.3 Member Function Documentation

25.141.3.1 [const Image& gdcm::ImageReader::GetImage \(\)](#) const

Return the read image.

Examples:

[CompressImage.cxx](#), [ConvertToQImage.cxx](#), [ExtractIconFromFile.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GetJPEGSamplePrecision.cxx](#), [HelloVizWorld.cxx](#), [MergeTwoFiles.cxx](#), [PatchFile.cxx](#), [ReadMultiTimesException.cxx](#), and [threadgdcm.cxx](#).

25.141.3.2 [Image& gdcm::ImageReader::GetImage \(\)](#)

25.141.3.3 [virtual bool gdcm::ImageReader::Read \(\)](#) [virtual]

Read the DICOM image. There are two reason for failure:

1. The input filename is not DICOM
2. The input DICOM file does not contains an [Image](#).

Reimplemented from [gdcm::PixmapReader](#).

Reimplemented in [gdcm::ImageRegionReader](#).

Examples:

[CheckBigEndianBug.cxx](#), [CompressImage.cxx](#), [ConvertToQImage.cxx](#), [ExtractIconFromFile.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GetJPEGSamplePrecision.cxx](#), [HelloVizWorld.cxx](#), [MergeTwoFiles.cxx](#), [MrProtocol.cxx](#), [PatchFile.cxx](#), [ReadMultiTimesException.cxx](#), and [threadgdcm.cxx](#).

25.141.3.4 `bool gdcm::ImageReader::ReadACRNEMAImage () [protected],[virtual]`

Reimplemented from [gdcm::PixmapReader](#).

25.141.3.5 `bool gdcm::ImageReader::ReadImage (MediaStorage const & ms) [protected],[virtual]`

Reimplemented from [gdcm::PixmapReader](#).

The documentation for this class was generated from the following file:


- [gdcmImageReader.h](#)

25.142 gdcm::ImageRegionReader Class Reference


[ImageRegionReader](#).

```
#include <gdcmImageRegionReader.h>
```

Inheritance diagram for `gdcm::ImageRegionReader`:



Collaboration diagram for `gdcm::ImageRegionReader`:



Public Member Functions

- `ImageRegionReader ()`
- `~ImageRegionReader ()`
- `size_t ComputeBufferLength () const`
- `Region const & GetRegion () const`
- `bool ReadInformation ()`
- `bool ReadIntoBuffer (char *inreadbuffer, size_t buflen)`
- `void SetRegion (Region const ®ion)`

Set/Get `Region` to be read.

Protected Member Functions

- bool [Read](#) ()

To prevent user from calling super class [Read\(\)](#) function.

Additional Inherited Members

25.142.1 Detailed Description

[ImageRegionReader](#).

See Also

[ImageReader](#)

25.142.2 Constructor & Destructor Documentation

25.142.2.1 `gdcm::ImageRegionReader::ImageRegionReader ()`

25.142.2.2 `gdcm::ImageRegionReader::~~ImageRegionReader ()`

25.142.3 Member Function Documentation

25.142.3.1 `size_t gdcm::ImageRegionReader::ComputeBufferLength () const`

Explicit call which will compute the minimal buffer length that can hold the whole uncompressed image as defined by [Region](#) region.

Returns

0 upon error

25.142.3.2 `Region const& gdcm::ImageRegionReader::GetRegion () const`

25.142.3.3 `bool gdcm::ImageRegionReader::Read () [protected],[virtual]`

To prevent user from calling super class [Read\(\)](#) function.

Reimplemented from [gdcm::ImageReader](#).

25.142.3.4 `bool gdcm::ImageRegionReader::ReadInformation ()`

Read meta information (not Pixel Data) from the DICOM file.

Returns

false upon error

25.142.3.5 `bool gdcM::ImageRegionReader::ReadIntoBuffer (char * inreadbuffer, size_t buflen)`

Read into buffer:

Returns

false upon error

25.142.3.6 `void gdcM::ImageRegionReader::SetRegion (Region const & region)`

Set/Get [Region](#) to be read.

The documentation for this class was generated from the following file:


- [gdcMImageRegionReader.h](#)

25.143 gdcM::ImageToImageFilter Class Reference


[ImageToImageFilter](#) class Super class for all filter taking an image and producing an output image.

```
#include <gdcMImageToImageFilter.h>
```

Inheritance diagram for gdcM::ImageToImageFilter:



Collaboration diagram for gdcm::ImageToImageFilter:



Public Member Functions

- [ImageToImageFilter](#) ()
- [~ImageToImageFilter](#) ()
- [Image](#) & [GetInput](#) ()
- const [Image](#) & [GetOutput](#) () const

Get Output image.

Additional Inherited Members

25.143.1 Detailed Description

[ImageToImageFilter](#) class Super class for all filter taking an image and producing an output image.

25.143.2 Constructor & Destructor Documentation

25.143.2.1 `gdcm::ImageToImageFilter::ImageToImageFilter ()`

25.143.2.2 `gdcm::ImageToImageFilter::~~ImageToImageFilter ()` `[inline]`

25.143.3 Member Function Documentation

25.143.3.1 `Image& gdcm::ImageToImageFilter::GetInput ()`

25.143.3.2 `const Image& gdcm::ImageToImageFilter::GetOutput () const`

Get Output image.

Examples:

[CompressImage.cxx](#).

The documentation for this class was generated from the following file:


- [gdcmImageToImageFilter.h](#)

25.144 gdcm::ImageWriter Class Reference


[ImageWriter](#).

```
#include <gdcmImageWriter.h>
```

Inheritance diagram for `gdcm::ImageWriter`:



Collaboration diagram for gdcm::ImageWriter:



Public Member Functions

- [ImageWriter](#) ()
- [~ImageWriter](#) ()
- const [Image](#) & [GetImage](#) () const
- [Image](#) & [GetImage](#) ()
- bool [Write](#) ()

Write.

Additional Inherited Members

25.144.1 Detailed Description

[ImageWriter](#).

Examples:

[CompressImage.cxx](#), [CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [csa2img.cxx](#), [GenFakeImage.cxx](#), [GetSubSequenceData.cxx](#), [HelloVizWorld.cxx](#), [iU22tomultisc.cxx](#), and [MergeTwoFiles.cxx](#).

25.144.2 Constructor & Destructor Documentation

25.144.2.1 `gdcm::ImageWriter::ImageWriter ()`

25.144.2.2 `gdcm::ImageWriter::~~ImageWriter ()`

25.144.3 Member Function Documentation

25.144.3.1 `const Image& gdcm::ImageWriter::GetImage () const` `[inline],[virtual]`

Set/Get [Image](#) to be written It will overwrite anything [Image](#) infos found in [DataSet](#) (see parent class to see how to pass dataset)

Reimplemented from [gdcm::PixmapWriter](#).

Examples:

[CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [csa2img.cxx](#), and [iU22tomultisc.cxx](#).

25.144.3.2 `Image& gdcm::ImageWriter::GetImage ()` `[inline],[virtual]`

Reimplemented from [gdcm::PixmapWriter](#).

25.144.3.3 `bool gdcm::ImageWriter::Write ()` `[virtual]`

Write.

Reimplemented from [gdcm::Writer](#).

Examples:

[CompressImage.cxx](#), [CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [csa2img.cxx](#), [GenFakeImage.cxx](#), [HelloVizWorld.cxx](#), [iU22tomultisc.cxx](#), and [MergeTwoFiles.cxx](#).

The documentation for this class was generated from the following file:

- [gdcmImageWriter.h](#)

25.145 gdcm::network::ImplementationClassUIDSub Class Reference

[ImplementationClassUIDSub](#) PS 3.7 [Table D.3-1 IMPLEMENTATION CLASS UID SUB-ITEM FIELDS \(A-ASSOCIATE-RQ\)](#)

```
#include <gdcmImplementationClassUIDSub.h>
```

Public Member Functions

- [ImplementationClassUIDSub](#) ()
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.145.1 Detailed Description

[ImplementationClassUIDSub](#) PS 3.7 [Table D.3-1 IMPLEMENTATION CLASS UID SUB-ITEM FIELDS \(A-ASSOCIATE-RQ\)](#)

25.145.2 Constructor & Destructor Documentation

25.145.2.1 `gdcm::network::ImplementationClassUIDSub::ImplementationClassUIDSub ()`

25.145.3 Member Function Documentation

25.145.3.1 `void gdcm::network::ImplementationClassUIDSub::Print (std::ostream & os) const`

25.145.3.2 `std::istream& gdcm::network::ImplementationClassUIDSub::Read (std::istream & is)`

25.145.3.3 `size_t gdcm::network::ImplementationClassUIDSub::Size () const`

25.145.3.4 `const std::ostream& gdcm::network::ImplementationClassUIDSub::Write (std::ostream & os) const`

The documentation for this class was generated from the following file:

- [gdcmImplementationClassUIDSub.h](#)

25.146 gdcm::network::ImplementationUIDSub Class Reference

[ImplementationUIDSub](#) [Table D.3-2 IMPLEMENTATION UID SUB-ITEM FIELDS \(A-ASSOCIATE-AC\)](#)

```
#include <gdcmImplementationUIDSub.h>
```

Public Member Functions

- [ImplementationUIDSub](#) ()
- const std::ostream & [Write](#) (std::ostream &os) const

25.146.1 Detailed Description

[ImplementationUIDSub Table](#) D.3-2 IMPLEMENTATION UID SUB-ITEM FIELDS (A-ASSOCIATE-AC)

25.146.2 Constructor & Destructor Documentation

25.146.2.1 `gdcm::network::ImplementationUIDSub::ImplementationUIDSub ()`

25.146.3 Member Function Documentation

25.146.3.1 `const std::ostream& gdcm::network::ImplementationUIDSub::Write (std::ostream & os) const`

The documentation for this class was generated from the following file:

- [gdcmImplementationUIDSub.h](#)

25.147 gdcm::network::ImplementationVersionNameSub Class Reference

[ImplementationVersionNameSub Table](#) D.3-3 IMPLEMENTATION VERSION NAME SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

```
#include <gdcmImplementationVersionNameSub.h>
```

Public Member Functions

- [ImplementationVersionNameSub](#) ()
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.147.1 Detailed Description

[ImplementationVersionNameSub Table](#) D.3-3 IMPLEMENTATION VERSION NAME SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

25.147.2 Constructor & Destructor Documentation

25.147.2.1 `gdcm::network::ImplementationVersionNameSub::ImplementationVersionNameSub ()`

25.147.3 Member Function Documentation

25.147.3.1 `void gdcm::network::ImplementationVersionNameSub::Print (std::ostream & os) const`

25.147.3.2 `std::istream& gdcm::network::ImplementationVersionNameSub::Read (std::istream & is)`

25.147.3.3 `size_t gdcm::network::ImplementationVersionNameSub::Size () const`

25.147.3.4 `const std::ostream& gdcm::network::ImplementationVersionNameSub::Write (std::ostream & os) const`

The documentation for this class was generated from the following file:


- [gdcmImplementationVersionNameSub.h](#)

25.148 gdcm::ImplicitDataElement Class Reference


Class to represent an *Implicit VR Data Element*.

```
#include <gdcmImplicitDataElement.h>
```

Inheritance diagram for gdcm::ImplicitDataElement:



Collaboration diagram for gdcm::ImplicitDataElement:



Public Member Functions

- [VL GetLength](#) () const
- template<typename TSwap > std::istream & [Read](#) (std::istream &is)
- template<typename TSwap > std::istream & [ReadPreValue](#) (std::istream &is)
- template<typename TSwap > std::istream & [ReadValue](#) (std::istream &is)
- template<typename TSwap > std::istream & [ReadWithLength](#) (std::istream &is, [VL](#) &length)
- template<typename TSwap > const std::ostream & [Write](#) (std::ostream &os) const

Additional Inherited Members

25.148.1 Detailed Description

Class to represent an *Implicit VR* Data [Element](#).

Note

bla

Examples:

[ReadExplicitLengthSQIVR.cxx](#).

25.148.2 Member Function Documentation

25.148.2.1 [VL gdcm::ImplicitDataElement::GetLength](#) () const

25.148.2.2 [template<typename TSwap > std::istream& gdcm::ImplicitDataElement::Read](#) (std::istream & *is*)

25.148.2.3 [template<typename TSwap > std::istream& gdcm::ImplicitDataElement::ReadPreValue](#) (std::istream & *is*)

25.148.2.4 [template<typename TSwap > std::istream& gdcm::ImplicitDataElement::ReadValue](#) (std::istream & *is*)

25.148.2.5 [template<typename TSwap > std::istream& gdcm::ImplicitDataElement::ReadWithLength](#) (std::istream & *is*, [VL](#) & *length*)

25.148.2.6 [template<typename TSwap > const std::ostream& gdcm::ImplicitDataElement::Write](#) (std::ostream & *os*) const


The documentation for this class was generated from the following file:

- [gdcmImplicitDataElement.h](#)


25.149 gdcm::InitializeEvent Class Reference

```
#include <gdcmEvent.h>
```

Inheritance diagram for gdcm::InitializeEvent:



Collaboration diagram for gdcm::InitializeEvent:



Additional Inherited Members

The documentation for this class was generated from the following file:

- [gdcmEvent.h](#)

25.150 gdcm::IOD Class Reference

Class for representing a [IOD](#).

```
#include <gdcmIOD.h>
```

Public Types

- typedef std::vector< [IODEntry](#) > [MapIODEntry](#)
- typedef MapIODEntry::size_type [SizeType](#)

Public Member Functions

- [IOD](#) ()
- void [AddIODEntry](#) (const [IODEntry](#) &iode)
- void [Clear](#) ()
- const [IODEntry](#) & [GetIODEntry](#) ([SizeType](#) idx) const
- [SizeType](#) [GetNumberOfIODs](#) () const
- [Type](#) [GetTypeFromTag](#) (const [Defs](#) &defs, const [Tag](#) &tag) const

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [IOD](#) &_val)

25.150.1 Detailed Description

Class for representing a [IOD](#).

Note

bla

See Also

[Dict](#)

Examples:

[TraverseModules.cxx](#).

25.150.2 Member Typedef Documentation

25.150.2.1 typedef std::vector<[IODEntry](#)> [gdcm::IOD::MapIODEntry](#)

25.150.2.2 typedef MapIODEntry::size_type [gdcm::IOD::SizeType](#)

25.150.3 Constructor & Destructor Documentation

25.150.3.1 [gdcm::IOD::IOD](#) () `[inline]`

25.150.4 Member Function Documentation

25.150.4.1 void gdcm::IOD::AddIODEntry (const IODEntry & *iode*) [inline]

25.150.4.2 void gdcm::IOD::Clear () [inline]

25.150.4.3 const IODEntry& gdcm::IOD::GetIODEntry (SizeType *idx*) const [inline]

Examples:

[TraverseModules.cxx](#).

25.150.4.4 SizeType gdcm::IOD::GetNumberOfIODs () const [inline]

Examples:

[TraverseModules.cxx](#).

25.150.4.5 Type gdcm::IOD::GetTypeFromTag (const Defs & *defs*, const Tag & *tag*) const

25.150.5 Friends And Related Function Documentation

25.150.5.1 std::ostream& operator<< (std::ostream & *_os*, const IOD & *_val*) [friend]

The documentation for this class was generated from the following file:

- [gdcmIOD.h](#)

25.151 gdcm::IODEntry Class Reference

Class for representing a [IODEntry](#).

```
#include <gdcmIODEntry.h>
```

Public Member Functions

- [IODEntry](#) (const char **name*="", const char **ref*="", const char **usag*="")
- const char * [GetIE](#) () const
- const char * [GetName](#) () const
- const char * [GetRef](#) () const
- const char * [GetUsage](#) () const
- [Usage::UsageType](#) [GetUsageType](#) () const
- void [SetIE](#) (const char **ie*)
- void [SetName](#) (const char **name*)
- void [SetRef](#) (const char **ref*)
- void [SetUsage](#) (const char **usag*)

Friends

- `std::ostream & operator<< (std::ostream &_os, const IODEntry &_val)`

25.151.1 Detailed Description

Class for representing a [IODEntry](#).

Note

A.1.3 [IOD Module Table](#) and Functional Group [Macro Table](#) This Section of each [IOD](#) defines in a tabular form the [Modules](#) comprising the [IOD](#). The following information must be specified for each [Module](#) in the table:

- The name of the [Module](#) or Functional Group
- A reference to the Section in Annex C which defines the [Module](#) or Functional Group
- The usage of the [Module](#) or Functional Group; whether it is:
 - Mandatory (see A.1.3.1) , abbreviated M
 - Conditional (see A.1.3.2) , abbreviated C
 - User Option (see A.1.3.3) , abbreviated U
- The [Modules](#) referenced are defined in Annex C. A.1.3.1 MANDATORY MODULES For each [IOD](#), Mandatory [Modules](#) shall be supported per the definitions, semantics and requirements defined in Annex C. PS 3.3 - 2008 Page 96
- Standard - A.1.3.2 CONDITIONAL MODULES Conditional [Modules](#) are Mandatory [Modules](#) if specific conditions are met. If the specified conditions are not met, this [Module](#) shall not be supported; that is, no information defined in that [Module](#) shall be sent. A.1.3.3 USER OPTION MODULES User Option [Modules](#) may or may not be supported. If an optional [Module](#) is supported, the [Attribute](#) Types specified in the [Modules](#) in Annex C shall be supported.

See Also

[DictEntry](#)

Examples:

[TraverseModules.cxx](#).

25.151.2 Constructor & Destructor Documentation

25.151.2.1 `gdcmm::IODEntry::IODEntry (const char * name = " ", const char * ref = " ", const char * usag = " ") [inline]`

25.151.3 Member Function Documentation

25.151.3.1 `const char* gdcmm::IODEntry::GetIE () const [inline]`

25.151.3.2 `const char* gdcmm::IODEntry::GetName () const [inline]`

25.151.3.3 `const char* gdcmm::IODEntry::GetRef () const [inline]`

Examples:

[TraverseModules.cxx](#).

25.151.3.4 `const char* gdcm::IODEntry::GetUsage () const` `[inline]`

25.151.3.5 `Usage::UsageType gdcm::IODEntry::GetUsageType () const`

25.151.3.6 `void gdcm::IODEntry::SetIE (const char * ie)` `[inline]`

25.151.3.7 `void gdcm::IODEntry::SetName (const char * name)` `[inline]`

25.151.3.8 `void gdcm::IODEntry::SetRef (const char * ref)` `[inline]`

25.151.3.9 `void gdcm::IODEntry::SetUsage (const char * usag)` `[inline]`

25.151.4 Friends And Related Function Documentation

25.151.4.1 `std::ostream& operator<< (std::ostream & _os, const IODEntry & _val)` `[friend]`

The documentation for this class was generated from the following file:

- [gdcmIODEntry.h](#)

25.152 gdcm::IODs Class Reference

Class for representing a [IODs](#).

```
#include <gdcmIODs.h>
```

Public Types

- `typedef std::map< IODName, IOD > IODMapType`
- `typedef IODMapType::const_iterator IODMapTypeConstIterator`
- `typedef std::string IODName`

Public Member Functions

- [IODs](#) ()
- `void AddIOD (const char *name, const IOD &module)`
- `IODMapTypeConstIterator Begin () const`
- `void Clear ()`
- `IODMapTypeConstIterator End () const`
- `const IOD & GetIOD (const char *name) const`

Friends

- `std::ostream & operator<< (std::ostream & _os, const IODs & _val)`

25.152.1 Detailed Description

Class for representing a [IODs](#).

Note

bla

See Also

[IOD](#)

Examples:

[TraverseModules.cxx](#).

25.152.2 Member Typedef Documentation

25.152.2.1 `typedef std::map<IODName, IOD> gdcm::IODs::IODMapType`

25.152.2.2 `typedef IODMapType::const_iterator gdcm::IODs::IODMapTypeConstIterator`

25.152.2.3 `typedef std::string gdcm::IODs::IODName`

25.152.3 Constructor & Destructor Documentation

25.152.3.1 `gdcm::IODs::IODs ()` `[inline]`

25.152.4 Member Function Documentation

25.152.4.1 `void gdcm::IODs::AddIOD (const char * name, const IOD & module)` `[inline]`

25.152.4.2 `IODMapTypeConstIterator gdcm::IODs::Begin () const` `[inline]`

25.152.4.3 `void gdcm::IODs::Clear ()` `[inline]`

25.152.4.4 `IODMapTypeConstIterator gdcm::IODs::End () const` `[inline]`

25.152.4.5 `const IOD& gdcm::IODs::GetIOD (const char * name) const` `[inline]`

25.152.5 Friends And Related Function Documentation

25.152.5.1 `std::ostream& operator<< (std::ostream & _os, const IODs & _val)` `[friend]`

The documentation for this class was generated from the following file:


- [gdcmIODs.h](#)

25.153 gdcm::IPPSorter Class Reference


[IPPSorter](#) Implement a simple [Image](#) Position ([Patient](#)) sorter, along the [Image Orientation](#) ([Patient](#)) direction. This algorithm does NOT support duplicate and will FAIL in case of duplicate IPP.

```
#include <gdcmIPPSorter.h>
```

Inheritance diagram for gdcm::IPPSorter:



Collaboration diagram for gdcm::IPPSorter:



Public Member Functions

- [IPPSorter\(\)](#)
- [~IPPSorter\(\)](#)
- [GetDirectionCosinesTolerance\(\)](#) const
- [GetZSpacing\(\)](#) const
- [GetZSpacingTolerance\(\)](#) const
- [SetComputeZSpacing\(bool b\)](#)
- [SetDirectionCosinesTolerance\(double tol\)](#)
- [SetDropDuplicatePositions\(bool b\)](#)

- void [SetZSpacingTolerance](#) (double tol)
- virtual bool [Sort](#) (std::vector< std::string > const &filenames)

Protected Attributes

- bool [ComputeZSpacing](#)
- double [DirCosTolerance](#)
- bool [DropDuplicatePositions](#)
- double [ZSpacing](#)
- double [ZTolerance](#)

Additional Inherited Members

25.153.1 Detailed Description

[IPPSorter](#) Implement a simple [Image](#) Position ([Patient](#)) sorter, along the [Image Orientation](#) ([Patient](#)) direction. This algorithm does NOT support duplicate and will FAIL in case of duplicate IPP.

Warning

See special note for [SetZSpacingTolerance](#) when computing the ZSpacing from the IPP of each DICOM files (default tolerance for constant spacing is: 1e-6mm)

For more information on [Spacing](#), and how it is defined in DICOM, advanced users may refer to:

http://gdcm.sourceforge.net/wiki/index.php/Imager_Pixel_Spacing

Bug There are currently a couple of bugs in this implementation:

- Gantry Tilt is not considered

Examples:

[gdcmorthoplanes.cxx](#), [reslicesphere.cxx](#), and [VolumeSorter.cxx](#).

25.153.2 Constructor & Destructor Documentation

25.153.2.1 `gdcm::IPPSorter::IPPSorter ()`

25.153.2.2 `gdcm::IPPSorter::~~IPPSorter ()`

25.153.3 Member Function Documentation

25.153.3.1 `double gdcm::IPPSorter::GetDirectionCosinesTolerance () const` `[inline]`

25.153.3.2 `double gdcm::IPPSorter::GetZSpacing () const` `[inline]`

Read-only function to provide access to the computed value for the Z-Spacing The [ComputeZSpacing](#) must have been set to true before execution of sort algorithm. Call this function *after* calling [Sort\(\)](#); Z-Spacing will be 0 on 2 occasions:

- Sorting simply failed, potentially duplicate IPP => ZSpacing = 0

- ZSpacing could not be computed (Z-Spacing is not constant, or ZTolerance is too low)

Examples:

[gdcmorthoplanes.cxx](#), and [reslicesphere.cxx](#).

25.153.3.3 double gdcm::IPPSorter::GetZSpacingTolerance () const [inline]

25.153.3.4 void gdcm::IPPSorter::SetComputeZSpacing (bool b) [inline]

Functions related to Z-Spacing computation Set to true when sort algorithm should also perform a regular Z-Spacing computation using the [Image Position \(Patient\)](#) Potential reason for failure:

1. ALL slices are taken into account, if one slice is missing then ZSpacing will be set to 0 since the spacing will not be found to be regular along the [Series](#)

Examples:

[gdcmorthoplanes.cxx](#), [reslicesphere.cxx](#), and [VolumeSorter.cxx](#).

25.153.3.5 void gdcm::IPPSorter::SetDirectionCosinesTolerance (double tol) [inline]

Sometimes IOP along a series is slightly changing for example: "0.999081\0.0426953\0.00369272\0.0419025\0.955059\0.293439", "0.999081\0.0426953\0.00369275\0.0419025\0.955059\0.293439", "0.999081\0.0426952\0.00369272\0.0419025\0.955059\0.293439", We need an API to define the tolerance which is allowed. Internally the cross vector of each direction cosines is computed. The tolerance then define the the distance in between 1. to the dot product of those cross vectors. In a perfect world this dot product is of course 1.0 which imply a [DirectionCosines](#) tolerance of exactly 0.0 (default).

25.153.3.6 void gdcm::IPPSorter::SetDropDuplicatePositions (bool b) [inline]

Makes the [IPPSorter](#) ignore multiple images located at the same position. Only the first occurrence will be kept. Drop-DuplicatePositions defaults to false.

25.153.3.7 void gdcm::IPPSorter::SetZSpacingTolerance (double tol) [inline]

1. Another reason for failure is that that Z-Spacing is only slightly changing (eg 1e-3) along the serie, a human can determine that this is ok and change the tolerance from its default value: 1e-6

Examples:

[gdcmorthoplanes.cxx](#), and [reslicesphere.cxx](#).

25.153.3.8 virtual bool gdcm::IPPSorter::Sort (std::vector< std::string > const & filenames) [virtual]

Main entry point to the sorter. It will execute the filter, option should be set before running this function (SetZSpacingTolerance, ...) Return value indicate if sorting could be achieved. Warning this does *NOT* imply that spacing is constant, it only means the file are sorted according to IPP You should check if ZSpacing is 0 or not to deduce if file are actually a 3D volume

Reimplemented from [gdcm::Sorter](#).

Examples:

[gdcmmorthoplanes.cxx](#), [reslicesphere.cxx](#), and [VolumeSorter.cxx](#).

25.153.4 Member Data Documentation

25.153.4.1 `bool gdcmm::IPPSorter::ComputeZSpacing` [protected]

25.153.4.2 `double gdcmm::IPPSorter::DirCosTolerance` [protected]

25.153.4.3 `bool gdcmm::IPPSorter::DropDuplicatePositions` [protected]

25.153.4.4 `double gdcmm::IPPSorter::ZSpacing` [protected]

25.153.4.5 `double gdcmm::IPPSorter::ZTolerance` [protected]

The documentation for this class was generated from the following file:


- [gdcmmIPPSorter.h](#)

25.154 gdcmm::Item Class Reference


Class to represent an [Item](#). A component of the value of a Data [Element](#) that is of [Value](#) Representation Sequence of Items. An [Item](#) contains a Data Set . See PS 3.5 7.5.1 [Item](#) Encoding Rules. Each [Item](#) of a Data [Element](#) of VR SQ shall be encoded as a DICOM Standard Data [Element](#) with a specific Data [Element](#) Tag of [Value](#) (FFFE,E000). The [Item](#) Tag is followed by a 4 byte [Item](#) Length field encoded in one of the following two ways Explicit/ Implicit.

```
#include <gdcmmItem.h>
```

Inheritance diagram for gdcmm::Item:



Collaboration diagram for gdcm::Item:



Public Member Functions

- `Item ()`
- `Item (Item const &val)`
- `void Clear ()`
- `bool FindDataElement (const Tag &t) const`
- `const DataElement & GetDataElement (const Tag &t) const`
- `template<typename TDE >`
`VL GetLength () const`
- `const DataSet & GetNestedDataSet () const`
- `DataSet & GetNestedDataSet ()`
- `void InsertDataElement (const DataElement &de)`
- `template<typename TDE , typename TSwap >`
`std::istream & Read (std::istream &is)`
- `void SetNestedDataSet (const DataSet &nested)`
- `template<typename TDE , typename TSwap >`
`const std::ostream & Write (std::ostream &os) const`

Friends

- `std::ostream & operator<< (std::ostream &os, const Item &val)`

Additional Inherited Members

25.154.1 Detailed Description

Class to represent an [Item](#) A component of the value of a Data [Element](#) that is of [Value](#) Representation Sequence of Items. An [Item](#) contains a Data Set . See PS 3.5 7.5.1 [Item](#) Encoding Rules Each [Item](#) of a Data [Element](#) of [VR](#) SQ shall be encoded as a DICOM Standard Data [Element](#) with a specific Data [Element](#) Tag of [Value](#) (FFFE,E000). The [Item](#) Tag is followed by a 4 byte [Item](#) Length field encoded in one of the following two ways Explicit/ Implicit.

Note

ITEM: A component of the [Value](#) of a Data [Element](#) that is of [Value](#) Representation Sequence of Items. An [Item](#) contains a Data Set.

Examples:

[ChangeSequenceUltrasound.cxx](#), [DumpGEMSMovieGroup.cxx](#), [ExtractEncryptedContent.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetSequenceUltrasound.cxx](#), [GetSubSequenceData.cxx](#), and [LargeVRDSExplicit.cxx](#).

25.154.2 Constructor & Destructor Documentation

25.154.2.1 `gdcm::Item::Item ()` `[inline]`

25.154.2.2 `gdcm::Item::Item (Item const & val)` `[inline]`

25.154.3 Member Function Documentation

25.154.3.1 `void gdcm::Item::Clear ()` `[inline]`

References `gdcm::DataElement::Clear()`.

Referenced by `gdcm::SequenceOfItems::Read()`.

25.154.3.2 `bool gdcm::Item::FindDataElement (const Tag & t) const` `[inline]`

Examples:

[ReadAndDumpDICOMDIR.cxx](#).

25.154.3.3 `const DataElement& gdcm::Item::GetDataElement (const Tag & t) const` `[inline]`

Examples:

[ReadAndDumpDICOMDIR.cxx](#).

25.154.3.4 `template<typename TDE > VL gdcm::Item::GetLength () const`

25.154.3.5 `const DataSet& gdcm::Item::GetNestedDataSet () const` `[inline]`

Examples:

[ChangeSequenceUltrasound.cxx](#), [DumpGEMSMovieGroup.cxx](#), [ExtractEncryptedContent.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GenAllVR-](#)

[R.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenSeqs.cxx](#), [GetSequenceUltrasound.cxx](#), [GetSubSequenceData.cxx](#), and [LargeVRDSExplicit.cxx](#).

Referenced by `gdcm::SequenceOfItems::Read()`.

25.154.3.6 `DataSet& gdcm::Item::GetNestedDataSet () [inline]`

25.154.3.7 `void gdcm::Item::InsertDataElement (const DataElement & de) [inline]`

25.154.3.8 `template<typename TDE , typename TSwap > std::istream& gdcm::Item::Read (std::istream & is) [inline]`

References `gdcm::DataSet::Clear()`, `gdcmDebugMacro`, `gdcmErrorMacro`, `gdcmWarningMacro`, `gdcm::DataSet::IsEmpty()`, and `gdcm::SwapperDoOp::Swap()`.

Referenced by `gdcm::SequenceOfItems::Read()`.

25.154.3.9 `void gdcm::Item::SetNestedDataSet (const DataSet & nested) [inline]`

25.154.3.10 `template<typename TDE , typename TSwap > const std::ostream& gdcm::Item::Write (std::ostream & os) const [inline]`

References `gdcmWarningMacro`, `gdcm::VL::GetLength()`, `gdcm::VL::Write()`, and `gdcm::Tag::Write()`.

25.154.4 Friends And Related Function Documentation

25.154.4.1 `std::ostream& operator<< (std::ostream & os, const Item & val) [friend]`


The documentation for this class was generated from the following file:

- [gdcmItem.h](#)


25.155 gdcm::IterationEvent Class Reference

```
#include <gdcmEvent.h>
```

Inheritance diagram for `gdcM::IterationEvent`:



Collaboration diagram for `gdcM::IterationEvent`:



Additional Inherited Members

The documentation for this class was generated from the following file:


- [gdcMEvent.h](#)

25.156 gdcm::JPEG12Codec Class Reference


Class to do JPEG 12bits (lossy & lossless)

```
#include <gdcmJPEG12Codec.h>
```

Inheritance diagram for gdcm::JPEG12Codec:



Collaboration diagram for gdcm::JPEG12Codec:



Public Member Functions

- [JPEG12Codec\(\)](#)
- [~JPEG12Codec\(\)](#)

- bool [DecodeByStreams](#) (std::istream &is, std::ostream &os)
- bool [GetHeaderInfo](#) (std::istream &is, [TransferSyntax](#) &ts)
- bool [InternalCode](#) (const char *input, unsigned long len, std::ostream &os)

Protected Member Functions

- bool [IsStateSuspension](#) () const

Additional Inherited Members

25.156.1 Detailed Description

Class to do JPEG 12bits (lossy & lossless)

Note

internal class

25.156.2 Constructor & Destructor Documentation

25.156.2.1 `gdcm::JPEG12Codec::JPEG12Codec ()`

25.156.2.2 `gdcm::JPEG12Codec::~~JPEG12Codec ()`

25.156.3 Member Function Documentation

25.156.3.1 `bool gdcm::JPEG12Codec::DecodeByStreams (std::istream & is, std::ostream & os)` `[virtual]`

Reimplemented from [gdcm::ImageCodec](#).

25.156.3.2 `bool gdcm::JPEG12Codec::GetHeaderInfo (std::istream & is, TransferSyntax & ts)` `[virtual]`

Reimplemented from [gdcm::JPEGCodec](#).

25.156.3.3 `bool gdcm::JPEG12Codec::InternalCode (const char * input, unsigned long len, std::ostream & os)` `[virtual]`

Reimplemented from [gdcm::Coder](#).

25.156.3.4 `bool gdcm::JPEG12Codec::IsStateSuspension () const` `[protected]`, `[virtual]`

Reimplemented from [gdcm::JPEGCodec](#).

The documentation for this class was generated from the following file:


- [gdcmJPEG12Codec.h](#)

25.157 gdcm::JPEG16Codec Class Reference


Class to do JPEG 16bits (lossless)

```
#include <gdcmJPEG16Codec.h>
```

Inheritance diagram for gdcm::JPEG16Codec:



Collaboration diagram for gdcm::JPEG16Codec:



Public Member Functions

- [JPEG16Codec\(\)](#)
- [~JPEG16Codec\(\)](#)

- bool [DecodeByStreams](#) (std::istream &is, std::ostream &os)
- bool [GetHeaderInfo](#) (std::istream &is, [TransferSyntax](#) &ts)
- bool [InternalCode](#) (const char *input, unsigned long len, std::ostream &os)

Protected Member Functions

- bool [IsStateSuspension](#) () const

Additional Inherited Members

25.157.1 Detailed Description

Class to do JPEG 16bits (lossless)

Note

internal class

25.157.2 Constructor & Destructor Documentation

25.157.2.1 [gdcm::JPEG16Codec::JPEG16Codec](#) ()

25.157.2.2 [gdcm::JPEG16Codec::~~JPEG16Codec](#) ()

25.157.3 Member Function Documentation

25.157.3.1 bool [gdcm::JPEG16Codec::DecodeByStreams](#) (std::istream & *is*, std::ostream & *os*) [virtual]

Reimplemented from [gdcm::ImageCodec](#).

25.157.3.2 bool [gdcm::JPEG16Codec::GetHeaderInfo](#) (std::istream & *is*, [TransferSyntax](#) & *ts*) [virtual]

Reimplemented from [gdcm::JPEGCodec](#).

25.157.3.3 bool [gdcm::JPEG16Codec::InternalCode](#) (const char * *input*, unsigned long *len*, std::ostream & *os*) [virtual]

Reimplemented from [gdcm::Coder](#).

25.157.3.4 bool [gdcm::JPEG16Codec::IsStateSuspension](#) () const [protected],[virtual]

Reimplemented from [gdcm::JPEGCodec](#).

The documentation for this class was generated from the following file:


- [gdcmJPEG16Codec.h](#)

25.158 gdcm::JPEG2000Codec Class Reference


Class to do JPEG 2000.

```
#include <gdcmJPEG2000Codec.h>
```

Inheritance diagram for gdcm::JPEG2000Codec:



Collaboration diagram for gdcm::JPEG2000Codec:



Public Member Functions

- [JPEG2000Codec](#) ()
- [~JPEG2000Codec](#) ()
- bool [CanCode](#) ([TransferSyntax](#) const &ts) const
Return whether this coder support this transfer syntax (can code it)
- bool [CanDecode](#) ([TransferSyntax](#) const &ts) const

Return whether this decoder support this transfer syntax (can decode it)

- bool [Code](#) ([DataElement](#) const &in, [DataElement](#) &out)

Code.

- bool [Decode](#) ([DataElement](#) const &is, [DataElement](#) &os)

Decode.

- virtual bool [GetHeaderInfo](#) (std::istream &is, [TransferSyntax](#) &ts)
- double [GetQuality](#) (unsigned int idx=0) const
- double [GetRate](#) (unsigned int idx=0) const
- void [SetNumberOfResolutions](#) (unsigned int nres)
- void [SetQuality](#) (unsigned int idx, double q)
- void [SetRate](#) (unsigned int idx, double rate)
- void [SetReversible](#) (bool res)
- void [SetTileSize](#) (unsigned int tx, unsigned int ty)

Protected Member Functions

- bool [DecodeByStreams](#) (std::istream &is, std::ostream &os)
- bool [DecodeExtent](#) (char *buffer, unsigned int xmin, unsigned int xmax, unsigned int ymin, unsigned int ymax, unsigned int zmin, unsigned int zmax, std::istream &is)

Friends

- class [Bitmap](#)
- class [ImageRegionReader](#)

Additional Inherited Members

25.158.1 Detailed Description

Class to do JPEG 2000.

Note

the class will produce JPC (JPEG 2000 codestream), since some private implementor are using full jp2 file the decoder tolerate jp2 input this is an implementation of an [ImageCodec](#)

25.158.2 Constructor & Destructor Documentation

25.158.2.1 `gdcm::JPEG2000Codec::JPEG2000Codec ()`

25.158.2.2 `gdcm::JPEG2000Codec::~~JPEG2000Codec ()`

25.158.3 Member Function Documentation

25.158.3.1 `bool gdcm::JPEG2000Codec::CanCode (TransferSyntax const &) const` [virtual]

Return whether this coder support this transfer syntax (can code it)

Reimplemented from [gdcm::ImageCodec](#).

25.158.3.2 `bool gdcm::JPEG2000Codec::CanDecode (TransferSyntax const &) const` [virtual]

Return whether this decoder support this transfer syntax (can decode it)

Reimplemented from [gdcm::ImageCodec](#).

25.158.3.3 `bool gdcm::JPEG2000Codec::Code (DataElement const & in_, DataElement & out_)` [virtual]

Code.

Reimplemented from [gdcm::Coder](#).

25.158.3.4 `bool gdcm::JPEG2000Codec::Decode (DataElement const &, DataElement &)` [virtual]

Decode.

Reimplemented from [gdcm::ImageCodec](#).

25.158.3.5 `bool gdcm::JPEG2000Codec::DecodeByStreams (std::istream & is, std::ostream & os)` [protected],
[virtual]

Reimplemented from [gdcm::ImageCodec](#).

25.158.3.6 `bool gdcm::JPEG2000Codec::DecodeExtent (char * buffer, unsigned int xmin, unsigned int xmax, unsigned int ymin,
unsigned int ymax, unsigned int zmin, unsigned int zmax, std::istream & is)` [protected]

25.158.3.7 `virtual bool gdcm::JPEG2000Codec::GetHeaderInfo (std::istream & is, TransferSyntax & ts)` [virtual]

Reimplemented from [gdcm::ImageCodec](#).

25.158.3.8 `double gdcm::JPEG2000Codec::GetQuality (unsigned int idx = 0) const`

25.158.3.9 `double gdcm::JPEG2000Codec::GetRate (unsigned int idx = 0) const`

25.158.3.10 `void gdcm::JPEG2000Codec::SetNumberOfResolutions (unsigned int nres)`

25.158.3.11 `void gdcm::JPEG2000Codec::SetQuality (unsigned int idx, double q)`

25.158.3.12 `void gdcm::JPEG2000Codec::SetRate (unsigned int idx, double rate)`

25.158.3.13 `void gdcm::JPEG2000Codec::SetReversible (bool res)`

25.158.3.14 `void gdcm::JPEG2000Codec::SetTileSize (unsigned int tx, unsigned int ty)`

25.158.4 Friends And Related Function Documentation

25.158.4.1 `friend class Bitmap` [friend]

25.158.4.2 `friend class ImageRegionReader` [friend]

The documentation for this class was generated from the following file:


- [gdcmJPEG2000Codec.h](#)

25.159 gdcm::JPEG8Codec Class Reference


Class to do JPEG 8bits (lossy & lossless)

```
#include <gdcmJPEG8Codec.h>
```

Inheritance diagram for gdcm::JPEG8Codec:



Collaboration diagram for gdcm::JPEG8Codec:



Public Member Functions

- [JPEG8Codec](#) ()
- [~JPEG8Codec](#) ()
- bool [DecodeByStreams](#) (std::istream &is, std::ostream &os)
- bool [GetHeaderInfo](#) (std::istream &is, [TransferSyntax](#) &ts)
- bool [InternalCode](#) (const char *input, unsigned long len, std::ostream &os)

Protected Member Functions

- bool [IsStateSuspension](#) () const

Additional Inherited Members

25.159.1 Detailed Description

Class to do JPEG 8bits (lossy & lossless)

Note

internal class

25.159.2 Constructor & Destructor Documentation

25.159.2.1 `gdcm::JPEG8Codec::JPEG8Codec ()`

25.159.2.2 `gdcm::JPEG8Codec::~~JPEG8Codec ()`

25.159.3 Member Function Documentation

25.159.3.1 `bool gdcm::JPEG8Codec::DecodeByStreams (std::istream & is, std::ostream & os)` [virtual]

Reimplemented from [gdcm::ImageCodec](#).

25.159.3.2 `bool gdcm::JPEG8Codec::GetHeaderInfo (std::istream & is, TransferSyntax & ts)` [virtual]

Reimplemented from [gdcm::JPEGCodec](#).

25.159.3.3 `bool gdcm::JPEG8Codec::InternalCode (const char * input, unsigned long len, std::ostream & os)` [virtual]

Reimplemented from [gdcm::Coder](#).

25.159.3.4 `bool gdcm::JPEG8Codec::IsStateSuspension () const` [protected],[virtual]

Reimplemented from [gdcm::JPEGCodec](#).

The documentation for this class was generated from the following file:


- [gdcmJPEG8Codec.h](#)

25.160 gdcm::JPEGCodec Class Reference


JPEG codec Class to do JPEG (8bits, 12bits, 16bits lossy & lossless). It redispatch in between the different codec implementation: [gdcm::JPEG8Codec](#), [gdcm::JPEG12Codec](#) & [gdcm::JPEG16Codec](#). It also support inconsistency in between DICOM header and JPEG compressed stream [ImageCodec](#) implementation for the JPEG case.

```
#include <gdcmJPEGCodec.h>
```

Inheritance diagram for `gdcm::JPEGCodec`:



Collaboration diagram for `gdcm::JPEGCodec`:



Public Member Functions

- [JPEGCodec](#) ()
- [~JPEGCodec](#) ()
- bool [CanCode](#) ([TransferSyntax](#) const &ts) const

Return whether this coder support this transfer syntax (can code it)

- bool [CanDecode](#) ([TransferSyntax](#) const &ts) const
Return whether this decoder support this transfer syntax (can decode it)
- bool [Code](#) ([DataElement](#) const &in, [DataElement](#) &out)
Compress into JPEG.
- void [ComputeOffsetTable](#) (bool b)
Compute the offset table:
- bool [Decode](#) ([DataElement](#) const &is, [DataElement](#) &os)
Decode.
- virtual bool [GetHeaderInfo](#) (std::istream &is, [TransferSyntax](#) &ts)
- bool [GetLossless](#) () const
- double [GetQuality](#) () const
- void [SetLossless](#) (bool l)
- void [SetPixelFormat](#) ([PixelFormat](#) const &pf)
- void [SetQuality](#) (double q)

Protected Member Functions

- bool [DecodeByStreams](#) (std::istream &is, std::ostream &os)
- bool [DecodeExtent](#) (char *buffer, unsigned int xmin, unsigned int xmax, unsigned int ymin, unsigned int ymax, unsigned int zmin, unsigned int zmax, std::istream &is)
- virtual bool [IsStateSuspension](#) () const
- bool [IsValid](#) ([PhotometricInterpretation](#) const &pi)
- void [SetBitSample](#) (int bit)

Protected Attributes

- int [BitSample](#)
- bool [Lossless](#)
- int [Quality](#)

Friends

- class [ImageRegionReader](#)

Additional Inherited Members

25.160.1 Detailed Description

JPEG codec Class to do JPEG (8bits, 12bits, 16bits lossy & lossless). It redispach in between the different codec implementation: [gdcm::JPEG8Codec](#), [gdcm::JPEG12Codec](#) & [gdcm::JPEG16Codec](#) It also support inconsistency in between DICOM header and JPEG compressed stream [ImageCodec](#) implementation for the JPEG case.

Note

Things you should know if you ever want to dive into DICOM/JPEG world (among other):

- http://groups.google.com/group/comp.protocols.dicom/browse_thread/thread/625e46919f
- http://groups.google.com/group/comp.protocols.dicom/browse_thread/thread/75fdfccc65
- http://groups.google.com/group/comp.protocols.dicom/browse_thread/thread/2d525ef6a2
- http://groups.google.com/group/comp.protocols.dicom/browse_thread/thread/6b93af410f

Examples:

[GetJPEGSamplePrecision.cxx](#).

25.160.2 Constructor & Destructor Documentation

25.160.2.1 `gdcm::JPEGCodec::JPEGCodec ()`

25.160.2.2 `gdcm::JPEGCodec::~~JPEGCodec ()`

25.160.3 Member Function Documentation

25.160.3.1 `bool gdcm::JPEGCodec::CanCode (TransferSyntax const &) const` `[virtual]`

Return whether this coder support this transfer syntax (can code it)

Reimplemented from [gdcm::ImageCodec](#).

25.160.3.2 `bool gdcm::JPEGCodec::CanDecode (TransferSyntax const &) const` `[virtual]`

Return whether this decoder support this transfer syntax (can decode it)

Reimplemented from [gdcm::ImageCodec](#).

25.160.3.3 `bool gdcm::JPEGCodec::Code (DataElement const & in, DataElement & out)` `[virtual]`

Compress into JPEG.

Reimplemented from [gdcm::Coder](#).

25.160.3.4 `void gdcm::JPEGCodec::ComputeOffsetTable (bool b)`

Compute the offset table:

25.160.3.5 `bool gdcm::JPEGCodec::Decode (DataElement const & , DataElement &)` `[virtual]`

Decode.

Reimplemented from [gdcm::ImageCodec](#).

25.160.3.6 `bool gdcm::JPEGCodec::DecodeByStreams (std::istream & is, std::ostream & os)` `[protected]`, `[virtual]`

Reimplemented from [gdcm::ImageCodec](#).

25.160.3.7 `bool gdcm::JPEGCodec::DecodeExtent (char * buffer, unsigned int xmin, unsigned int xmax, unsigned int ymin, unsigned int ymax, unsigned int zmin, unsigned int zmax, std::istream & is)` [protected]

25.160.3.8 `virtual bool gdcm::JPEGCodec::GetHeaderInfo (std::istream & is, TransferSyntax & ts)` [virtual]

Reimplemented from [gdcm::ImageCodec](#).

Reimplemented in [gdcm::JPEG12Codec](#), [gdcm::JPEG16Codec](#), and [gdcm::JPEG8Codec](#).

Examples:

[GetJPEGSamplePrecision.cxx](#).

25.160.3.9 `bool gdcm::JPEGCodec::GetLossless () const`

25.160.3.10 `double gdcm::JPEGCodec::GetQuality () const`

25.160.3.11 `virtual bool gdcm::JPEGCodec::IsStateSuspension () const` [protected],[virtual]

Reimplemented in [gdcm::JPEG12Codec](#), [gdcm::JPEG16Codec](#), and [gdcm::JPEG8Codec](#).

25.160.3.12 `bool gdcm::JPEGCodec::IsValid (PhotometricInterpretation const & pi)` [protected],[virtual]

Reimplemented from [gdcm::ImageCodec](#).

25.160.3.13 `void gdcm::JPEGCodec::SetBitSample (int bit)` [protected]

25.160.3.14 `void gdcm::JPEGCodec::SetLossless (bool l)`

25.160.3.15 `void gdcm::JPEGCodec::SetPixelFormat (PixelFormat const & pf)` [virtual]

Reimplemented from [gdcm::ImageCodec](#).

Examples:

[GetJPEGSamplePrecision.cxx](#).

25.160.3.16 `void gdcm::JPEGCodec::SetQuality (double q)`

25.160.4 Friends And Related Function Documentation

25.160.4.1 `friend class ImageRegionReader` [friend]

25.160.5 Member Data Documentation

25.160.5.1 `int gdcm::JPEGCodec::BitSample` [protected]

25.160.5.2 `bool gdcm::JPEGCodec::Lossless` [protected]

Public Member Functions

- [JPEGLSCodec](#) ()
- [~JPEGLSCodec](#) ()
- bool [CanCode](#) ([TransferSyntax](#) const &ts) const
Return whether this coder support this transfer syntax (can code it)
- bool [CanDecode](#) ([TransferSyntax](#) const &ts) const
Return whether this decoder support this transfer syntax (can decode it)
- bool [Code](#) ([DataElement](#) const &in, [DataElement](#) &out)
Code.
- bool [Decode](#) ([DataElement](#) const &is, [DataElement](#) &os)
Decode.
- bool [Decode](#) ([DataElement](#) const &in, char *outBuffer, size_t inBufferLength, uint32_t inXMin, uint32_t inXMax, uint32_t inYMin, uint32_t inYMax, uint32_t inZMin, uint32_t inZMax)
- unsigned long [GetBufferLength](#) () const
- bool [GetHeaderInfo](#) (std::istream &is, [TransferSyntax](#) &ts)
- bool [GetLossless](#) () const
- void [SetBufferLength](#) (unsigned long l)
- void [SetLossless](#) (bool l)
- void [SetLossyError](#) (int error)
[0-3] generally

Protected Member Functions

- bool [DecodeExtent](#) (char *buffer, unsigned int xmin, unsigned int xmax, unsigned int ymin, unsigned int ymax, unsigned int zmin, unsigned int zmax, std::istream &is)

Friends

- class [ImageRegionReader](#)

Additional Inherited Members

25.161.1 Detailed Description

JPEG-LS.

Note

codec that implement the JPEG-LS compression this is an implementation of [ImageCodec](#) for JPEG-LS

It uses the CharLS JPEG-LS implementation <http://charls.codeplex.com>

25.161.2 Constructor & Destructor Documentation

25.161.2.1 `gdcm::JPEGLSCodec::JPEGLSCodec ()`

25.161.2.2 `gdcm::JPEGLSCodec::~~JPEGLSCodec ()`

25.161.3 Member Function Documentation

25.161.3.1 `bool gdcm::JPEGLSCodec::CanCode (TransferSyntax const &) const` `[virtual]`

Return whether this coder support this transfer syntax (can code it)

Reimplemented from [gdcm::ImageCodec](#).

25.161.3.2 `bool gdcm::JPEGLSCodec::CanDecode (TransferSyntax const &) const` `[virtual]`

Return whether this decoder support this transfer syntax (can decode it)

Reimplemented from [gdcm::ImageCodec](#).

25.161.3.3 `bool gdcm::JPEGLSCodec::Code (DataElement const & in_, DataElement & out_)` `[virtual]`

Code.

Reimplemented from [gdcm::Coder](#).

25.161.3.4 `bool gdcm::JPEGLSCodec::Decode (DataElement const &, DataElement &)` `[virtual]`

Decode.

Reimplemented from [gdcm::ImageCodec](#).

25.161.3.5 `bool gdcm::JPEGLSCodec::Decode (DataElement const & in, char * outBuffer, size_t inBufferLength, uint32_t inXMin, uint32_t inXMax, uint32_t inYMin, uint32_t inYMax, uint32_t inZMin, uint32_t inZMax)`

25.161.3.6 `bool gdcm::JPEGLSCodec::DecodeExtent (char * buffer, unsigned int xmin, unsigned int xmax, unsigned int ymin, unsigned int ymax, unsigned int zmin, unsigned int zmax, std::istream & is)` `[protected]`

25.161.3.7 `unsigned long gdcm::JPEGLSCodec::GetBufferLength () const` `[inline]`

25.161.3.8 `bool gdcm::JPEGLSCodec::GetHeaderInfo (std::istream & is, TransferSyntax & ts)` `[virtual]`

Reimplemented from [gdcm::ImageCodec](#).

25.161.3.9 `bool gdcm::JPEGLSCodec::GetLossless () const`

25.161.3.10 `void gdcm::JPEGLSCodec::SetBufferLength (unsigned long l)` `[inline]`

25.161.3.11 `void gdcm::JPEGLSCodec::SetLossless (bool l)`

25.161.3.12 void gdcm::JPEGLSCodec::SetLossyError (int *error*)

[0-3] generally

25.161.4 Friends And Related Function Documentation

25.161.4.1 friend class ImageRegionReader [friend]

The documentation for this class was generated from the following file:


- [gdcmJPEGLSCodec.h](#)

25.162 gdcm::KAKADUCodec Class Reference


[KAKADUCodec](#).

```
#include <gdcmKAKADUCodec.h>
```

Inheritance diagram for gdcm::KAKADUCodec:



Collaboration diagram for `gdcm::KAKADUCodec`:



Public Member Functions

- `KAKADUCodec()`
- `~KAKADUCodec()`
- `bool CanCode(TransferSyntax const &ts) const`
Return whether this coder support this transfer syntax (can code it)
- `bool CanDecode(TransferSyntax const &ts) const`
Return whether this decoder support this transfer syntax (can decode it)
- `bool Code(DataElement const &in, DataElement &out)`
Code.
- `bool Decode(DataElement const &is, DataElement &os)`
Decode.

Additional Inherited Members

25.162.1 Detailed Description

[KAKADUCodec](#).

25.162.2 Constructor & Destructor Documentation

25.162.2.1 `gdcm::KAKADUCodec::KAKADUCodec()`

25.162.2.2 `gdcm::KAKADUCodec::~~KAKADUCodec()`

25.162.3 Member Function Documentation

25.162.3.1 `bool gdcm::KAKADUCodec::CanCode(TransferSyntax const &ts) const` [virtual]

Return whether this coder support this transfer syntax (can code it)

Reimplemented from [gdcm::ImageCodec](#).

25.162.3.2 `bool gdcm::KAKADUCodec::CanDecode(TransferSyntax const &ts) const` [virtual]

Return whether this decoder support this transfer syntax (can decode it)

Reimplemented from [gdcm::ImageCodec](#).

25.162.3.3 `bool gdcm::KAKADUCodec::Code (DataElement const & in_, DataElement & out_) [virtual]`

Code.

Reimplemented from [gdcm::Coder](#).

25.162.3.4 `bool gdcm::KAKADUCodec::Decode (DataElement const &, DataElement &) [virtual]`

Decode.

Reimplemented from [gdcm::ImageCodec](#).

The documentation for this class was generated from the following file:


- [gdcmKAKADUCodec.h](#)

25.163 gdcm::LO Class Reference


[LO](#).

```
#include <gdcmLO.h>
```

Inheritance diagram for gdcm::LO:



Collaboration diagram for `gdcm::LO`:



Public Types

- typedef Superclass::const_iterator [const_iterator](#)
- typedef Superclass::const_reference [const_reference](#)
- typedef Superclass::const_reverse_iterator [const_reverse_iterator](#)
- typedef Superclass::difference_type [difference_type](#)
- typedef Superclass::iterator [iterator](#)
- typedef Superclass::pointer [pointer](#)
- typedef Superclass::reference [reference](#)
- typedef Superclass::reverse_iterator [reverse_iterator](#)
- typedef Superclass::size_type [size_type](#)
- typedef [String<'\\', 64 >](#) [Superclass](#)
- typedef Superclass::value_type [value_type](#)

Public Member Functions

- [LO](#) ()
- [LO](#) (const [value_type](#) *s)
- [LO](#) (const [value_type](#) *s, [size_type](#) n)
- [LO](#) (const [Superclass](#) &s, [size_type](#) pos=0, [size_type](#) n=npos)
- bool [IsValid](#) () const

25.163.1 Detailed Description

[LO](#).

Note

TODO

25.163.2 Member Typedef Documentation

25.163.2.1 `typedef Superclass::const_iterator gdcm::LO::const_iterator`

25.163.2.2 `typedef Superclass::const_reference gdcm::LO::const_reference`

25.163.2.3 `typedef Superclass::const_reverse_iterator gdcm::LO::const_reverse_iterator`

25.163.2.4 `typedef Superclass::difference_type gdcm::LO::difference_type`

25.163.2.5 `typedef Superclass::iterator gdcm::LO::iterator`

25.163.2.6 `typedef Superclass::pointer gdcm::LO::pointer`

25.163.2.7 `typedef Superclass::reference gdcm::LO::reference`

25.163.2.8 `typedef Superclass::reverse_iterator gdcm::LO::reverse_iterator`

25.163.2.9 `typedef Superclass::size_type gdcm::LO::size_type`

25.163.2.10 `typedef String<'\',64> gdcm::LO::Superclass`

25.163.2.11 `typedef Superclass::value_type gdcm::LO::value_type`

25.163.3 Constructor & Destructor Documentation

25.163.3.1 `gdcm::LO::LO()` `[inline]`

25.163.3.2 `gdcm::LO::LO(const value_type * s)` `[inline]`

25.163.3.3 `gdcm::LO::LO(const value_type * s, size_type n)` `[inline]`

25.163.3.4 `gdcm::LO::LO(const Superclass & s, size_type pos = 0, size_type n = npos)` `[inline]`

25.163.4 Member Function Documentation

25.163.4.1 `bool gdcm::LO::IsValid()` `const` `[inline]`

The documentation for this class was generated from the following file:


- [gdcmLO.h](#)

25.164 gdcm::LookupTable Class Reference


[LookupTable](#) class.

```
#include <gdcmLookupTable.h>
```

Inheritance diagram for `gdcm::LookupTable`:



Collaboration diagram for `gdcm::LookupTable`:



Public Types

- enum `LookupTableType` {
 `RED` = 0,
 `GREEN`,
 `BLUE`,
 `GRAY`,
 `UNKNOWN` }

Public Member Functions

- `LookupTable` ()

- [LookupTable](#) ([LookupTable](#) const &lut)
- [~LookupTable](#) ()
- void [Allocate](#) (unsigned short bitsample=8)
Allocate the LUT.
- void [Clear](#) ()
Clear the LUT.
- void [Decode](#) (std::istream &is, std::ostream &os) const
Decode the LUT.
- bool [Decode](#) (char *outputbuffer, size_t outlen, const char *inputbuffer, size_t inlen) const
- unsigned short [GetBitSample](#) () const
return the bit sample
- bool [GetBufferAsRGBA](#) (unsigned char *rgba) const
return the LUT as RGBA buffer
- void [GetLUT](#) ([LookupTableType](#) type, unsigned char *array, unsigned int &length) const
- void [GetLUTDescriptor](#) ([LookupTableType](#) type, unsigned short &length, unsigned short &subscript, unsigned short &bitsize) const
- unsigned int [GetLUTLength](#) ([LookupTableType](#) type) const
- const unsigned char * [GetPointer](#) () const
return a raw pointer to the LUT
- void [InitializeBlueLUT](#) (unsigned short length, unsigned short subscript, unsigned short bitsize)
- bool [Initialized](#) () const
return whether the LUT has been initialized
- void [InitializeGreenLUT](#) (unsigned short length, unsigned short subscript, unsigned short bitsize)
- void [InitializeLUT](#) ([LookupTableType](#) type, unsigned short length, unsigned short subscript, unsigned short bitsize)
Generic interface:
- void [InitializeRedLUT](#) (unsigned short length, unsigned short subscript, unsigned short bitsize)
RED / GREEN / BLUE specific:
- void [Print](#) (std::ostream &) const
- void [SetBlueLUT](#) (const unsigned char *blue, unsigned int length)
- void [SetGreenLUT](#) (const unsigned char *green, unsigned int length)
- virtual void [SetLUT](#) ([LookupTableType](#) type, const unsigned char *array, unsigned int length)
- void [SetRedLUT](#) (const unsigned char *red, unsigned int length)
- bool [WriteBufferAsRGBA](#) (const unsigned char *rgba)
Write the LUT as RGBA.

Protected Attributes

- unsigned short [BitSample](#)
- bool [IncompleteLUT](#):1
- [LookupTableInternal](#) * [Internal](#)

Additional Inherited Members

25.164.1 Detailed Description

[LookupTable](#) class.

25.164.2 Member Enumeration Documentation

25.164.2.1 enum gdcm::LookupTable::LookupTableType

Enumerator

RED

GREEN

BLUE

GRAY

UNKNOWN

25.164.3 Constructor & Destructor Documentation

25.164.3.1 gdcm::LookupTable::LookupTable ()

25.164.3.2 gdcm::LookupTable::~~LookupTable ()

25.164.3.3 gdcm::LookupTable::LookupTable (LookupTable const & lut) [inline]

25.164.4 Member Function Documentation

25.164.4.1 void gdcm::LookupTable::Allocate (unsigned short *bitsample* = 8)

Allocate the LUT.

25.164.4.2 void gdcm::LookupTable::Clear ()

Clear the LUT.

25.164.4.3 void gdcm::LookupTable::Decode (std::istream & *is*, std::ostream & *os*) const

Decode the LUT.

25.164.4.4 bool gdcm::LookupTable::Decode (char * *outputbuffer*, size_t *outlen*, const char * *inputbuffer*, size_t *inlen*) const

Decode the LUT outputbuffer will contains the RGB decoded PALETTE COLOR input image of size inlen the outputbuffer should be at least 3 times the size of inlen

25.164.4.5 unsigned short gdcm::LookupTable::GetBitSample () const [inline]

return the bit sample

25.164.4.6 bool gdcm::LookupTable::GetBufferAsRGBA (unsigned char * *rgba*) const

return the LUT as RGBA buffer

25.164.4.7 void gdcmm::LookupTable::GetLUT (LookupTableType *type*, unsigned char * *array*, unsigned int & *length*) const

25.164.4.8 void gdcmm::LookupTable::GetLUTDescriptor (LookupTableType *type*, unsigned short & *length*, unsigned short & *subscript*, unsigned short & *bitsize*) const

25.164.4.9 unsigned int gdcmm::LookupTable::GetLUTLength (LookupTableType *type*) const

25.164.4.10 const unsigned char* gdcmm::LookupTable::GetPointer () const

return a raw pointer to the LUT

25.164.4.11 void gdcmm::LookupTable::InitializeBlueLUT (unsigned short *length*, unsigned short *subscript*, unsigned short *bitsize*)

25.164.4.12 bool gdcmm::LookupTable::Initialized () const

return whether the LUT has been initialized

25.164.4.13 void gdcmm::LookupTable::InitializeGreenLUT (unsigned short *length*, unsigned short *subscript*, unsigned short *bitsize*)

25.164.4.14 void gdcmm::LookupTable::InitializeLUT (LookupTableType *type*, unsigned short *length*, unsigned short *subscript*, unsigned short *bitsize*)

Generic interface:

25.164.4.15 void gdcmm::LookupTable::InitializeRedLUT (unsigned short *length*, unsigned short *subscript*, unsigned short *bitsize*)

RED / GREEN / BLUE specific:

25.164.4.16 void gdcmm::LookupTable::Print (std::ostream &) const [inline],[virtual]

Reimplemented from [gdcmm::Object](#).

Reimplemented in [gdcmm::SegmentedPaletteColorLookupTable](#).

25.164.4.17 void gdcmm::LookupTable::SetBlueLUT (const unsigned char * *blue*, unsigned int *length*)

25.164.4.18 void gdcmm::LookupTable::SetGreenLUT (const unsigned char * *green*, unsigned int *length*)

25.164.4.19 virtual void gdcmm::LookupTable::SetLUT (LookupTableType *type*, const unsigned char * *array*, unsigned int *length*) [virtual]

Reimplemented in [gdcmm::SegmentedPaletteColorLookupTable](#).

25.164.4.20 void gdcmm::LookupTable::SetRedLUT (const unsigned char * *red*, unsigned int *length*)

25.164.4.21 bool gdcmm::LookupTable::WriteBufferAsRGBA (const unsigned char * *rgba*)

Write the LUT as RGBA.

25.164.5 Member Data Documentation

25.164.5.1 unsigned short gdcm::LookupTable::BitSample [protected]

25.164.5.2 bool gdcm::LookupTable::IncompleteLUT [protected]

25.164.5.3 LookupTableInternal* gdcm::LookupTable::Internal [protected]

The documentation for this class was generated from the following file:

- [gdcmLookupTable.h](#)

25.165 gdcm::Scanner::Itstr Struct Reference

```
#include <gdcmScanner.h>
```

Public Member Functions

- bool [operator\(\)](#) (const char *s1, const char *s2) const

25.165.1 Member Function Documentation

25.165.1.1 bool gdcm::Scanner::Itstr::operator() (const char * s1, const char * s2) const [inline]

The documentation for this struct was generated from the following file:

- [gdcmScanner.h](#)

25.166 gdcm::Macro Class Reference

Class for representing a [Macro](#).

```
#include <gdcmMacro.h>
```

Public Types

- typedef std::vector< std::string > [ArrayIncludeMacrosType](#)
- typedef std::map< [Tag](#), [MacroEntry](#) > [MapModuleEntry](#)

Public Member Functions

- [Macro](#) ()
- void [AddMacroEntry](#) (const [Tag](#) &tag, const [MacroEntry](#) &module)
Will add a [ModuleEntry](#) directly at root-level. See [Macro](#) for nested-included level.
- void [Clear](#) ()
- bool [FindMacroEntry](#) (const [Tag](#) &tag) const
- const [MacroEntry](#) & [GetMacroEntry](#) (const [Tag](#) &tag) const

- const char * [GetName](#) () const
- void [SetName](#) (const char *name)
- bool [Verify](#) (const [DataSet](#) &ds, [Usage](#) const &usage) const

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [Macro](#) &_val)

25.166.1 Detailed Description

Class for representing a [Macro](#).

Note

[Attribute Macro](#): a set of Attributes that are described in a single table that is referenced by multiple [Module](#) or other tables.

See Also

[Module](#)

25.166.2 Member Typedef Documentation

25.166.2.1 `typedef std::vector<std::string> gdcm::Macro::ArrayIncludeMacroType`

25.166.2.2 `typedef std::map<Tag, MacroEntry> gdcm::Macro::MapModuleEntry`

25.166.3 Constructor & Destructor Documentation

25.166.3.1 `gdcm::Macro::Macro ()` `[inline]`

25.166.4 Member Function Documentation

25.166.4.1 `void gdcm::Macro::AddMacroEntry (const Tag &tag, const MacroEntry &module)` `[inline]`

Will add a [ModuleEntry](#) directly at root-level. See [Macro](#) for nested-included level.

25.166.4.2 `void gdcm::Macro::Clear ()` `[inline]`

25.166.4.3 `bool gdcm::Macro::FindMacroEntry (const Tag &tag) const`

Find or Get a [ModuleEntry](#). [ModuleEntry](#) are either search are root-level or within nested-macro included in module.

25.166.4.4 `const MacroEntry& gdcm::Macro::GetMacroEntry (const Tag &tag) const`

25.166.4.5 `const char* gdcm::Macro::GetName () const` `[inline]`

25.166.4.6 `void gdcm::Macro::SetName (const char *name)` `[inline]`

25.166.4.7 `bool gdcmmacro::Macro::Verify (const DataSet & ds, Usage const & usage) const`

25.166.5 Friends And Related Function Documentation

25.166.5.1 `std::ostream& operator<< (std::ostream & _os, const Macro & _val)` [*friend*]

The documentation for this class was generated from the following file:

- [gdcmmacro.h](#)

25.167 gdcmmacro::Macros Class Reference

Class for representing a [Modules](#).

```
#include <gdcmmacros.h>
```

Public Types

- `typedef std::map< std::string, Macro > ModuleMapType`

Public Member Functions

- [Macros](#) ()
- void [AddMacro](#) (const char *ref, const [Macro](#) &module)
- void [Clear](#) ()
- const [Macro](#) & [GetMacro](#) (const char *name) const
- bool [IsEmpty](#) () const

Friends

- `std::ostream & operator<< (std::ostream &_os, const Macros &_val)`

25.167.1 Detailed Description

Class for representing a [Modules](#).

Note

bla

See Also

[Module](#)

Examples:

[TraverseModules.cxx](#).

25.167.2 Member Typedef Documentation

25.167.2.1 `typedef std::map<std::string, Macro> gdcm::Macros::ModuleMapType`

25.167.3 Constructor & Destructor Documentation

25.167.3.1 `gdcm::Macros::Macros ()` `[inline]`

25.167.4 Member Function Documentation

25.167.4.1 `void gdcm::Macros::AddMacro (const char * ref, const Macro & module)` `[inline]`

25.167.4.2 `void gdcm::Macros::Clear ()` `[inline]`

25.167.4.3 `const Macro& gdcm::Macros::GetMacro (const char * name) const` `[inline]`

25.167.4.4 `bool gdcm::Macros::IsEmpty () const` `[inline]`

25.167.5 Friends And Related Function Documentation

25.167.5.1 `std::ostream& operator<< (std::ostream & _os, const Macros & _val)` `[friend]`

The documentation for this class was generated from the following file:

- [gdcmMacros.h](#)

25.168 gdcm::network::MaximumLengthSub Class Reference

[MaximumLengthSub](#) Annex D [Table D.1-1](#) MAXIMUM LENGTH SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

```
#include <gdcmMaximumLengthSub.h>
```

Public Member Functions

- [MaximumLengthSub](#) ()
- `uint32_t` [GetMaximumLength](#) () const
- `void` [Print](#) (std::ostream &os) const
- `std::istream &` [Read](#) (std::istream &is)
- `void` [SetMaximumLength](#) (uint32_t maximumlength)
- `size_t` [Size](#) () const
- `const std::ostream &` [Write](#) (std::ostream &os) const

25.168.1 Detailed Description

[MaximumLengthSub](#) Annex D [Table D.1-1](#) MAXIMUM LENGTH SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

or

[Table D.1-2](#) Maximum length sub-item fields (A-ASSOCIATE-AC)

25.168.2 Constructor & Destructor Documentation

25.168.2.1 `gdcm::network::MaximumLengthSub::MaximumLengthSub ()`

25.168.3 Member Function Documentation

25.168.3.1 `uint32_t gdcm::network::MaximumLengthSub::GetMaximumLength () const` `[inline]`

25.168.3.2 `void gdcm::network::MaximumLengthSub::Print (std::ostream & os) const`

25.168.3.3 `std::istream& gdcm::network::MaximumLengthSub::Read (std::istream & is)`

25.168.3.4 `void gdcm::network::MaximumLengthSub::SetMaximumLength (uint32_t maxlength)`

25.168.3.5 `size_t gdcm::network::MaximumLengthSub::Size () const`

25.168.3.6 `const std::ostream& gdcm::network::MaximumLengthSub::Write (std::ostream & os) const`

The documentation for this class was generated from the following file:

- [gdcmMaximumLengthSub.h](#)

25.169 gdcm::MD5 Class Reference

Class for [MD5](#).

```
#include <gdcmMD5.h>
```

Public Member Functions

- [MD5](#) ()
- [~MD5](#) ()

Static Public Member Functions

- static bool [Compute](#) (const char *buffer, unsigned long buf_len, char digest_str[33])
- static bool [ComputeFile](#) (const char *filename, char digest_str[33])

25.169.1 Detailed Description

Class for [MD5](#).

Warning

this class is able to pick from two implementations:

1. a lightweight md5 implementation (when GDCM_BUILD_TESTING is turned ON)
2. the one from OpenSSL (when GDCM_USE_SYSTEM_OPENSSL is turned ON)

In all other cases it will return an error

25.169.2 Constructor & Destructor Documentation

25.169.2.1 `gdcm::MD5::MD5 ()`

25.169.2.2 `gdcm::MD5::~~MD5 ()`

25.169.3 Member Function Documentation

25.169.3.1 `static bool gdcm::MD5::Compute (const char * buffer, unsigned long buf_len, char digest_str[33])` `[static]`

25.169.3.2 `static bool gdcm::MD5::ComputeFile (const char * filename, char digest_str[33])` `[static]`

The documentation for this class was generated from the following file:

- [gdcmMD5.h](#)

25.170 gdcm::MediaStorage Class Reference

[MediaStorage](#).

```
#include <gdcmMediaStorage.h>
```

Public Types

- enum `MSType` {
 - `MediaStorageDirectoryStorage = 0,`
 - `ComputedRadiographyImageStorage,`
 - `DigitalXRayImageStorageForPresentation,`
 - `DigitalXRayImageStorageForProcessing,`
 - `DigitalMammographyImageStorageForPresentation,`
 - `DigitalMammographyImageStorageForProcessing,`
 - `DigitalIntraoralXRayImageStorageForPresentation,`
 - `DigitalIntraoralXRayImageStorageForProcessing,`
 - `CTImageStorage,`
 - `EnhancedCTImageStorage,`
 - `UltrasoundImageStorageRetired,`
 - `UltrasoundImageStorage,`
 - `UltrasoundMultiFrameImageStorageRetired,`
 - `UltrasoundMultiFrameImageStorage,`
 - `MRImageStorage,`
 - `EnhancedMRImageStorage,`
 - `MRSpectroscopyStorage,`
 - `NuclearMedicineImageStorageRetired,`
 - `SecondaryCaptureImageStorage,`
 - `MultiframeSingleBitSecondaryCaptureImageStorage,`
 - `MultiframeGrayscaleByteSecondaryCaptureImageStorage,`
 - `MultiframeGrayscaleWordSecondaryCaptureImageStorage,`
 - `MultiframeTrueColorSecondaryCaptureImageStorage,`
 - `StandaloneOverlayStorage,`
 - `StandaloneCurveStorage,`
 - `LeadECGWaveformStorage,`
 - `GeneralECGWaveformStorage,`
 - `AmbulatoryECGWaveformStorage,`
 - `HemodynamicWaveformStorage,`
 - `CardiacElectrophysiologyWaveformStorage,`
 - `BasicVoiceAudioWaveformStorage,`
 - `StandaloneModalityLUTStorage,`
 - `StandaloneVOILUTStorage,`
 - `GrayscaleSoftcopyPresentationStateStorageSOPClass,`
 - `XRayAngiographicImageStorage,`
 - `XRayRadiofluoroscopicImageStorage,`
 - `XRayAngiographicBiPlaneImageStorageRetired,`
 - `NuclearMedicineImageStorage,`
 - `RawDataStorage,`
 - `SpacialRegistrationStorage,`
 - `SpacialFiducialsStorage,`
 - `PETImageStorage,`
 - `RTImageStorage,`
 - `RTDoseStorage,`
 - `RTStructureSetStorage,`
 - `RTPlanStorage,`
 - `CSANonImageStorage,`
 - `Philips3D,`
 - `EnhancedSR,`
 - `BasicTextSR,`
 - `HardcopyGrayscaleImageStorage,`
 - `ComprehensiveSR,`
 - `DetachedStudyManagementSOPClass,`
 - `EncapsulatedPDFStorage,`
 - `EncapsulatedCDASStorage,`
 - `StudyComponentManagementSOPClass,`
 - `DetachedVisitManagementSOPClass,`
 - `DetachedPatientManagementSOPClass,`

MS_END }

- enum `ObjectType` {
`NoObject` = 0,
`Video`,
`Waveform`,
`Audio`,
`PDF`,
`URI`,
`Segmentation`,
`ObjectEnd` }

Public Member Functions

- `MediaStorage` (`MSType` type=`MS_END`)
- const char * `GetModality` () const
- unsigned int `GetModalityDimension` () const
- const char * `GetString` () const
Return the Media `String` of the object.
- void `GuessFromModality` (const char *modality, unsigned int dimension=2)
- bool `IsUndefined` () const
- operator `MSType` () const
- bool `SetFromDataSet` (`DataSet` const &ds)
- bool `SetFromFile` (`File` const &file)
- bool `SetFromHeader` (`FileMetaInformation` const &fmi)
- bool `SetFromModality` (`DataSet` const &ds)

Static Public Member Functions

- static const char * `GetMSString` (`MSType` ts)
Return the Media `String` associated. Will return NULL for MS_END.
- static `MSType` `GetMSType` (const char *str)
- static unsigned int `GetNumberOfModality` ()
- static unsigned int `GetNumberOfMSString` ()
- static unsigned int `GetNumberOfMSType` ()
- static bool `IsImage` (`MSType` ts)

Protected Member Functions

- void `SetFromSourceImageSequence` (`DataSet` const &ds)

Friends

- std::ostream & `operator<<` (std::ostream &os, const `MediaStorage` &ms)

25.170.1 Detailed Description

[MediaStorage](#).

Note

FIXME There should not be any notion of [Image](#) and/or PDF at that point Only the codec can answer yes I support this Media Storage or not... For instance an [ImageCodec](#) will answer yes to most of them while a [PDFCodec](#) will answer only for the Encapsulated PDF

See Also

[UIDs](#)

Examples:

[CreateJPIPDataSet.cxx](#), [EncapsulateFileInRawData.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GenAllVR.cxx](#), [GenerateStandardSOPClasses.cxx](#), [GenFakeIdentifyFile.cxx](#), [GetSubSequenceData.cxx](#), [iU22tomultisc.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [Stream-ImageReaderTest.cxx](#), and [TestReader.cxx](#).

25.170.2 Member Enumeration Documentation

25.170.2.1 enum gdcm::MediaStorage::MSType

Enumerator

MediaStorageDirectoryStorage
ComputedRadiographylImageStorage
DigitalXRayImageStorageForPresentation
DigitalXRayImageStorageForProcessing
DigitalMammographylImageStorageForPresentation
DigitalMammographylImageStorageForProcessing
DigitalIntraoralXrayImageStorageForPresentation
DigitalIntraoralXRayImageStorageForProcessing
CTImageStorage
EnhancedCTImageStorage
UltrasoundImageStorageRetired
UltrasoundImageStorage
UltrasoundMultiFrameImageStorageRetired
UltrasoundMultiFrameImageStorage
MRImageStorage
EnhancedMRImageStorage
MRSpectroscopyStorage
NuclearMedicineImageStorageRetired
SecondaryCaptureImageStorage
MultiframeSingleBitSecondaryCaptureImageStorage
MultiframeGrayscaleByteSecondaryCaptureImageStorage

MultiframeGrayscaleWordSecondaryCaptureImageStorage
MultiframeTrueColorSecondaryCaptureImageStorage
StandaloneOverlayStorage
StandaloneCurveStorage
LeadECGWaveformStorage
GeneralECGWaveformStorage
AmbulatoryECGWaveformStorage
HemodynamicWaveformStorage
CardiacElectrophysiologyWaveformStorage
BasicVoiceAudioWaveformStorage
StandaloneModalityLUTStorage
StandaloneVOILUTStorage
GrayscaleSoftcopyPresentationStateStorageSOPClass
XRayAngiographicImageStorage
XRayRadiofluoroscopicImageStorage
XRayAngiographicBiPlaneImageStorageRetired
NuclearMedicineImageStorage
RawDataStorage
SpacialRegistrationStorage
SpacialFiducialsStorage
PETImageStorage
RTImageStorage
RTDoseStorage
RTStructureSetStorage
RTPlanStorage
CSANonImageStorage
Philips3D
EnhancedSR
BasicTextSR
HardcopyGrayscaleImageStorage
ComprehensiveSR
DetachedStudyManagementSOPClass
EncapsulatedPDFStorage
EncapsulatedCDASStorage
StudyComponentManagementSOPClass
DetachedVisitManagementSOPClass
DetachedPatientManagementSOPClass
VideoEndoscopicImageStorage
GeneralElectricMagneticResonanceImageStorage
GEPrivate3DModelStorage
ToshibaPrivateDataStorage
MammographyCADSR

KeyObjectSelectionDocument
HangingProtocolStorage
ModalityPerformedProcedureStepSOPClass
PhilipsPrivateMRSyntheticImageStorage
VLPhotographicImageStorage
SegmentationStorage
RTIonPlanStorage
XRay3DAngiographicImageStorage
EnhancedXAImageStorage
RTIonBeamsTreatmentRecordStorage
SurfaceSegmentationStorage
VLWholeSlideMicroscopyImageStorage
RTTreatmentSummaryRecordStorage
EnhancedUSVolumeStorage
XRayRadiationDoseSR
VLEndoscopicImageStorage
BreastTomosynthesisImageStorage
FujiPrivateCRIImageStorage
OphthalmicPhotography8BitImageStorage
OphthalmicTomographyImageStorage
MS_END

Examples:

[GenerateStandardSOPClasses.cxx](#).

25.170.2.2 enum gdcm::MediaStorage::ObjectType

Enumerator

NoObject
Video
Waveform
Audio
PDF
URI
Segmentation
ObjectEnd

25.170.3 Constructor & Destructor Documentation

25.170.3.1 `gdcm::MediaStorage::MediaStorage (MStype type = MS_END) [inline]`

25.170.4 Member Function Documentation

25.170.4.1 `const char* gdcm::MediaStorage::GetModality () const`

25.170.4.2 `unsigned int gdcm::MediaStorage::GetModalityDimension () const`

25.170.4.3 `static const char* gdcm::MediaStorage::GetMSString (MStype ts) [static]`

Return the Media [String](#) associated. Will return NULL for MS_END.

Examples:

[GenerateStandardSOPClasses.cxx](#).

Referenced by `gdcm::operator<<()`.

25.170.4.4 `static MStype gdcm::MediaStorage::GetMStype (const char * str) [static]`

Examples:

[TestReader.cxx](#).

25.170.4.5 `static unsigned int gdcm::MediaStorage::GetNumberOfModality () [static]`

25.170.4.6 `static unsigned int gdcm::MediaStorage::GetNumberOfMSString () [static]`

25.170.4.7 `static unsigned int gdcm::MediaStorage::GetNumberOfMStype () [static]`

25.170.4.8 `const char* gdcm::MediaStorage::GetString () const`

Return the Media [String](#) of the object.

Examples:

[CreateJPIPDataSet.cxx](#), [EncapsulateFileInRawData.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [GetSubSequenceData.cxx](#), [iU22tomultisc.cxx](#), and [StreamImageReaderTest.cxx](#).

25.170.4.9 `void gdcm::MediaStorage::GuessFromModality (const char * modality, unsigned int dimension = 2)`

25.170.4.10 `static bool gdcm::MediaStorage::IsImage (MStype ts) [static]`

Returns whether DICOM has a Pixel Data element (7fe0,0010)

Warning

MRSpectroscopyStorage could be image but are not

25.170.4.11 `bool gdcM::MediaStorage::IsUndefined () const [inline]`

Examples:

[TestReader.cxx](#).

25.170.4.12 `gdcM::MediaStorage::operator MType () const [inline]`

25.170.4.13 `bool gdcM::MediaStorage::SetFromDataSet (DataSet const & ds)`

Advanced user only (functions should be protected level...) Those function are lower level than SetFromFile

25.170.4.14 `bool gdcM::MediaStorage::SetFromFile (File const & file)`

Attempt to set the [MediaStorage](#) from a file: WARNING: When no [MediaStorage](#) & Modality are found BUT a PixelData element is found then [MediaStorage](#) is set to the default SecondaryCaptureImageStorage (return value is false in this case)

Examples:

[gdcMrtionplan.cxx](#), [gdcMrtplan.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), and [TestReader.cxx](#).

25.170.4.15 `bool gdcM::MediaStorage::SetFromHeader (FileMetaInformation const & fmi)`

25.170.4.16 `bool gdcM::MediaStorage::SetFromModality (DataSet const & ds)`

25.170.4.17 `void gdcM::MediaStorage::SetFromSourceImageSequence (DataSet const & ds) [protected]`

25.170.5 Friends And Related Function Documentation

25.170.5.1 `std::ostream& operator<< (std::ostream & os, const MediaStorage & ms) [friend]`

The documentation for this class was generated from the following file:


- [gdcMMediaStorage.h](#)

25.171 gdcM::MemberCommand< T > Class Template Reference


[Command](#) subclass that calls a pointer to a member function.

```
#include <gdcMCommand.h>
```

Inheritance diagram for gdcm::MemberCommand< T >:



Collaboration diagram for gdcm::MemberCommand< T >:



Public Types

- typedef [MemberCommand](#) [Self](#)
- typedef void(T::* [TConstMemberFunctionPointer](#))(const [Subject](#) *, const [Event](#) &)
- typedef void(T::* [TMemberFunctionPointer](#))(Subject *, const [Event](#) &)

Public Member Functions

- virtual void [Execute](#) ([Subject](#) *caller, const [Event](#) &event)
- virtual void [Execute](#) (const [Subject](#) *caller, const [Event](#) &event)
- void [SetCallbackFunction](#) (T *object, [TMemberFunctionPointer](#) memberFunction)
- void [SetCallbackFunction](#) (T *object, [TConstMemberFunctionPointer](#) memberFunction)

Static Public Member Functions

- static [SmartPointer](#)
 < [MemberCommand](#) > [New](#) ()

Protected Member Functions

- [MemberCommand](#) ()
- virtual [~MemberCommand](#) ()

Protected Attributes

- [TConstMemberFunctionPointer](#) [m_ConstMemberFunction](#)
- [TMemberFunctionPointer](#) [m_MemberFunction](#)
- T * [m_This](#)

25.171.1 Detailed Description

```
template<class T>class gdcmmembercommand< T >
```

[Command](#) subclass that calls a pointer to a member function.

[MemberCommand](#) calls a pointer to a member function with the same arguments as [Execute](#) on [Command](#).

25.171.2 Member Typedef Documentation

25.171.2.1 `template<class T > typedef MemberCommand gdcmmembercommand< T >::Self`

Standard class typedefs.

25.171.2.2 `template<class T> typedef void(T::* gdcM::MemberCommand< T >::TConstMemberFunctionPointer)(const Subject *, const Event &)`

25.171.2.3 `template<class T> typedef void(T::* gdcM::MemberCommand< T >::TMemberFunctionPointer)(Subject *, const Event &)`

pointer to a member function that takes a `Subject*` and the event

25.171.3 Constructor & Destructor Documentation

25.171.3.1 `template<class T> gdcM::MemberCommand< T >::MemberCommand () [inline], [protected]`

Referenced by `gdcM::MemberCommand< T >::New()`.

25.171.3.2 `template<class T> virtual gdcM::MemberCommand< T >::~MemberCommand () [inline], [protected], [virtual]`

25.171.4 Member Function Documentation

25.171.4.1 `template<class T> virtual void gdcM::MemberCommand< T >::Execute (Subject * caller, const Event & event) [inline], [virtual]`

Invoke the member function.

Implements [gdcM::Command](#).

References `gdcM::MemberCommand< T >::m_MemberFunction`.

25.171.4.2 `template<class T> virtual void gdcM::MemberCommand< T >::Execute (const Subject * caller, const Event & event) [inline], [virtual]`

Invoke the member function with a const object.

Implements [gdcM::Command](#).

References `gdcM::MemberCommand< T >::m_ConstMemberFunction`.

25.171.4.3 `template<class T> static SmartPointer<MemberCommand> gdcM::MemberCommand< T >::New () [inline], [static]`

Method for creation through the object factory.

References `gdcM::MemberCommand< T >::MemberCommand()`.

25.171.4.4 `template<class T> void gdcM::MemberCommand< T >::SetCallbackFunction (T * object, TMemberFunctionPointer memberFunction) [inline]`

Run-time type information (and related methods). Set the callback function along with the object that it will be invoked on.

References `gdcM::MemberCommand< T >::m_MemberFunction`, and `gdcM::MemberCommand< T >::m_This`.

25.171.4.5 `template<class T> void gdcm::MemberCommand< T >::SetCallbackFunction (T * object, TConstMemberFunctionPointer memberFunction) [inline]`

References `gdcm::MemberCommand< T >::m_ConstMemberFunction`, and `gdcm::MemberCommand< T >::m_This`.

25.171.5 Member Data Documentation

25.171.5.1 `template<class T> TConstMemberFunctionPointer gdcm::MemberCommand< T >::m_ConstMemberFunction [protected]`

Referenced by `gdcm::MemberCommand< T >::Execute()`, and `gdcm::MemberCommand< T >::SetCallbackFunction()`.

25.171.5.2 `template<class T> TMemberFunctionPointer gdcm::MemberCommand< T >::m_MemberFunction [protected]`

Referenced by `gdcm::MemberCommand< T >::Execute()`, and `gdcm::MemberCommand< T >::SetCallbackFunction()`.

25.171.5.3 `template<class T> T* gdcm::MemberCommand< T >::m_This [protected]`

Referenced by `gdcm::MemberCommand< T >::SetCallbackFunction()`.

The documentation for this class was generated from the following file:


- [gdcmCommand.h](#)

25.172 gdcm::MeshPrimitive Class Reference


This class defines surface mesh primitives. It is designed from surface mesh primitives macro.

```
#include <gdcmMeshPrimitive.h>
```

Inheritance diagram for `gdcm::MeshPrimitive`:



Collaboration diagram for gdcm::MeshPrimitive:



Public Types

- enum `MPType` {
`VERTEX` = 0,
`EDGE`,
`TRIANGLE`,
`TRIANGLE_STRIP`,
`TRIANGLE_FAN`,
`LINE`,
`FACET`,
`MPType_END` }
This enumeration defines primitive types.
- typedef `std::vector< DataElement >` `PrimitivesData`

Public Member Functions

- `MeshPrimitive` ()
- virtual `~MeshPrimitive` ()
- void `AddPrimitiveData` (`DataElement` const &de)
- unsigned int `GetNumberOfPrimitivesData` () const
- const `DataElement` & `GetPrimitiveData` () const
- `DataElement` & `GetPrimitiveData` ()
- const `DataElement` & `GetPrimitiveData` (const unsigned int idx) const
- `DataElement` & `GetPrimitiveData` (const unsigned int idx)
- const `PrimitivesData` & `GetPrimitivesData` () const
- `PrimitivesData` & `GetPrimitivesData` ()

- [MPTYPE](#) `GetPrimitiveType ()` const
- void [SetPrimitiveData](#) ([DataElement](#) const &de)
- void [SetPrimitiveData](#) (const unsigned int idx, [DataElement](#) const &de)
- void [SetPrimitivesData](#) ([PrimitivesData](#) const &DEs)
- void [SetPrimitiveType](#) (const [MPTYPE](#) type)

Static Public Member Functions

- static [MPTYPE](#) `GetMPTYPE` (const char *type)
- static const char * [GetMPTYPEString](#) (const [MPTYPE](#) type)

Protected Attributes

- [PrimitivesData](#) `PrimitiveData`
- [MPTYPE](#) `PrimitiveType`

Additional Inherited Members

25.172.1 Detailed Description

This class defines surface mesh primitives. It is designed from surface mesh primitives macro.

See Also

PS 3.3 C.27.4

25.172.2 Member Typedef Documentation

25.172.2.1 `typedef std::vector< DataElement > gdcm::MeshPrimitive::PrimitivesData`

25.172.3 Member Enumeration Documentation

25.172.3.1 `enum gdcm::MeshPrimitive::MPTYPE`

This enumeration defines primitive types.

See Also

PS 3.3 C.27.4.1

Enumerator

VERTEX
EDGE
TRIANGLE
TRIANGLE_STRIP
TRIANGLE_FAN
LINE
FACET
MPTYPE_END

25.172.4 Constructor & Destructor Documentation

25.172.4.1 `gdcm::MeshPrimitive::MeshPrimitive ()`

25.172.4.2 `virtual gdcm::MeshPrimitive::~~MeshPrimitive ()` `[virtual]`

25.172.5 Member Function Documentation

25.172.5.1 `void gdcm::MeshPrimitive::AddPrimitiveData (DataElement const & de)`

25.172.5.2 `static MPTYPE gdcm::MeshPrimitive::GetMPTYPE (const char * type)` `[static]`

25.172.5.3 `static const char* gdcm::MeshPrimitive::GetMPTYPEString (const MPTYPE type)` `[static]`

25.172.5.4 `unsigned int gdcm::MeshPrimitive::GetNumberOfPrimitivesData () const`

25.172.5.5 `const DataElement& gdcm::MeshPrimitive::GetPrimitiveData () const`

25.172.5.6 `DataElement& gdcm::MeshPrimitive::GetPrimitiveData ()`

25.172.5.7 `const DataElement& gdcm::MeshPrimitive::GetPrimitiveData (const unsigned int idx) const`

25.172.5.8 `DataElement& gdcm::MeshPrimitive::GetPrimitiveData (const unsigned int idx)`

25.172.5.9 `const PrimitivesData& gdcm::MeshPrimitive::GetPrimitivesData () const`

25.172.5.10 `PrimitivesData& gdcm::MeshPrimitive::GetPrimitivesData ()`

25.172.5.11 `MPTYPE gdcm::MeshPrimitive::GetPrimitiveType () const`

25.172.5.12 `void gdcm::MeshPrimitive::SetPrimitiveData (DataElement const & de)`

25.172.5.13 `void gdcm::MeshPrimitive::SetPrimitiveData (const unsigned int idx, DataElement const & de)`

25.172.5.14 `void gdcm::MeshPrimitive::SetPrimitivesData (PrimitivesData const & DEs)`

25.172.5.15 `void gdcm::MeshPrimitive::SetPrimitiveType (const MPTYPE type)`

25.172.6 Member Data Documentation

25.172.6.1 `PrimitivesData gdcm::MeshPrimitive::PrimitiveData` `[protected]`

25.172.6.2 `MPTYPE gdcm::MeshPrimitive::PrimitiveType` `[protected]`


The documentation for this class was generated from the following file:

- [gdcmMeshPrimitive.h](#)


25.173 gdcm::ModifiedEvent Class Reference

```
#include <gdcmEvent.h>
```

Inheritance diagram for `gdcm::ModifiedEvent`:



Collaboration diagram for `gdcm::ModifiedEvent`:



Additional Inherited Members

The documentation for this class was generated from the following file:

- [gdcmEvent.h](#)

25.174 gdcm::Module Class Reference

Class for representing a [Module](#).

```
#include <gdcmModule.h>
```

Public Types

- typedef std::vector< std::string > [ArrayIncludeMacrosType](#)
- typedef std::map< [Tag](#),
[ModuleEntry](#) > [MapModuleEntry](#)

Public Member Functions

- [Module](#) ()
- void [AddMacro](#) (const char *include)
- void [AddModuleEntry](#) (const [Tag](#) &tag, const [ModuleEntry](#) &module)
Will add a [ModuleEntry](#) directly at root-level. See [Macro](#) for nested-included level.
- void [Clear](#) ()
- bool [FindModuleEntryInMacros](#) ([Macros](#) const ¯os, const [Tag](#) &tag) const
- const [ModuleEntry](#) & [GetModuleEntryInMacros](#) ([Macros](#) const ¯os, const [Tag](#) &tag) const
- const char * [GetName](#) () const
- void [SetName](#) (const char *name)
- bool [Verify](#) (const [DataSet](#) &ds, [Usage](#) const &usage) const

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [Module](#) &_val)

25.174.1 Detailed Description

Class for representing a [Module](#).

Note

[Module](#): A set of Attributes within an Information Entity or Normalized [IOD](#) which are logically related to each other.

See Also

[Macro](#)

Examples:

[TraverseModules.cxx](#).

25.174.2 Member Typedef Documentation

25.174.2.1 `typedef std::vector<std::string> gdcmmodule::ArrayIncludeMacrosType`

25.174.2.2 `typedef std::map<Tag, ModuleEntry> gdcmmodule::MapModuleEntry`

25.174.3 Constructor & Destructor Documentation

25.174.3.1 `gdcmmodule::Module () [inline]`

25.174.4 Member Function Documentation

25.174.4.1 `void gdcmmodule::AddMacro (const char * include) [inline]`

25.174.4.2 `void gdcmmodule::AddModuleEntry (const Tag & tag, const ModuleEntry & module) [inline]`

Will add a [ModuleEntry](#) directly at root-level. See [Macro](#) for nested-included level.

25.174.4.3 `void gdcmmodule::Clear () [inline]`

25.174.4.4 `bool gdcmmodule::FindModuleEntryInMacros (Macros const & macros, const Tag & tag) const`

Find or Get a [ModuleEntry](#). [ModuleEntry](#) are either search are root-level or within nested-macro included in module.

Examples:

[TraverseModules.cxx](#).

25.174.4.5 `const ModuleEntry& gdcmmodule::GetModuleEntryInMacros (Macros const & macros, const Tag & tag) const`

Examples:

[TraverseModules.cxx](#).

25.174.4.6 `const char* gdcmmodule::GetName () const [inline]`

25.174.4.7 `void gdcmmodule::SetName (const char * name) [inline]`

25.174.4.8 `bool gdcmmodule::Verify (const DataSet & ds, Usage const & usage) const`

25.174.5 Friends And Related Function Documentation

25.174.5.1 `std::ostream& operator<< (std::ostream & _os, const Module & _val) [friend]`

The documentation for this class was generated from the following file:


- [gdcmmodule.h](#)

25.175 gdcm::ModuleEntry Class Reference


Class for representing a [ModuleEntry](#).

```
#include <gdcmModuleEntry.h>
```

Inheritance diagram for gdcm::ModuleEntry:



Collaboration diagram for gdcm::ModuleEntry:



Public Types

- typedef std::string [Description](#)

Public Member Functions

- [ModuleEntry](#) (const char *name="", const char *type="3", const char *description="")
- virtual [~ModuleEntry](#) ()
- const [Description](#) & [GetDescription](#) () const
- const char * [GetName](#) () const
- const [Type](#) & [GetType](#) () const
- void [SetDescription](#) (const char *d)
- void [SetName](#) (const char *name)
- void [SetType](#) (const [Type](#) &type)

Protected Attributes

- [Type](#) [DataElementType](#)
- [Description](#) [DescriptionField](#)
- std::string [Name](#)

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [ModuleEntry](#) &_val)

25.175.1 Detailed Description

Class for representing a [ModuleEntry](#).

Note

bla

See Also

[DictEntry](#)

Examples:

[TraverseModules.cxx](#).

25.175.2 Member Typedef Documentation

25.175.2.1 typedef std::string gdcm::ModuleEntry::Description

25.175.3 Constructor & Destructor Documentation

25.175.3.1 gdcm::ModuleEntry::ModuleEntry (const char * *name* = " ", const char * *type* = "3", const char * *description* = " ") [inline]

References [gdcm::Type::GetTypeType\(\)](#).

25.175.3.2 `virtual gdcm::ModuleEntry::~~ModuleEntry () [inline], [virtual]`

25.175.4 Member Function Documentation

25.175.4.1 `const Description& gdcm::ModuleEntry::GetDescription () const [inline]`

25.175.4.2 `const char* gdcm::ModuleEntry::GetName () const [inline]`

25.175.4.3 `const Type& gdcm::ModuleEntry::GetType () const [inline]`

Examples:

[TraverseModules.cxx](#).

25.175.4.4 `void gdcm::ModuleEntry::SetDescription (const char * d) [inline]`

25.175.4.5 `void gdcm::ModuleEntry::SetName (const char * name) [inline]`

25.175.4.6 `void gdcm::ModuleEntry::SetType (const Type & type) [inline]`

25.175.5 Friends And Related Function Documentation

25.175.5.1 `std::ostream& operator<< (std::ostream & _os, const ModuleEntry & _val) [friend]`

25.175.6 Member Data Documentation

25.175.6.1 `Type gdcm::ModuleEntry::DataElementType [protected]`

Referenced by `gdcm::operator<<()`.

25.175.6.2 `Description gdcm::ModuleEntry::DescriptionField [protected]`

Referenced by `gdcm::operator<<()`.

25.175.6.3 `std::string gdcm::ModuleEntry::Name [protected]`

Referenced by `gdcm::operator<<()`.

The documentation for this class was generated from the following file:

- [gdcmModuleEntry.h](#)

25.176 gdcm::Modules Class Reference

Class for representing a [Modules](#).

```
#include <gdcmModules.h>
```

Public Types

- typedef std::map< std::string, [Module](#) > [ModuleMapType](#)

Public Member Functions

- [Modules](#) ()
- void [AddModule](#) (const char *ref, const [Module](#) &module)
- void [Clear](#) ()
- const [Module](#) & [GetModule](#) (const char *name) const
- bool [IsEmpty](#) () const

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [Modules](#) &_val)

25.176.1 Detailed Description

Class for representing a [Modules](#).

Note

bla

See Also

[Module](#)

Examples:

[TraverseModules.cxx](#).

25.176.2 Member Typedef Documentation

25.176.2.1 typedef std::map<std::string, [Module](#)> [gdcm::Modules::ModuleMapType](#)

25.176.3 Constructor & Destructor Documentation

25.176.3.1 [gdcm::Modules::Modules](#) () [\[inline\]](#)

25.176.4 Member Function Documentation

25.176.4.1 void [gdcm::Modules::AddModule](#) (const char * *ref*, const [Module](#) & *module*) [\[inline\]](#)

25.176.4.2 void [gdcm::Modules::Clear](#) () [\[inline\]](#)

25.176.4.3 const [Module](#)& [gdcm::Modules::GetModule](#) (const char * *name*) const [\[inline\]](#)

25.176.4.4 bool [gdcm::Modules::IsEmpty](#) () const [\[inline\]](#)

25.176.5 Friends And Related Function Documentation

25.176.5.1 `std::ostream& operator<< (std::ostream &_os, const Modules &_val)` [friend]

The documentation for this class was generated from the following file:


- [gdcmModules.h](#)

25.177 gdcm::MovePatientRootQuery Class Reference


[MovePatientRootQuery](#) contains: the class which will produce a dataset for c-move with patient root.

```
#include <gdcmMovePatientRootQuery.h>
```

Inheritance diagram for `gdcm::MovePatientRootQuery`:



Collaboration diagram for `gdcm::MovePatientRootQuery`:



Public Member Functions

- [MovePatientRootQuery](#) ()
- [UIDs::TSName GetAbstractSyntaxUID](#) () const
- `std::vector< Tag > GetTagListByLevel (const EQueryLevel &inQueryLevel)`
- `void InitializeDataSet (const EQueryLevel &inQueryLevel)`
- `bool ValidateQuery (bool inStrict=true) const`

Friends

- class [QueryFactory](#)

Additional Inherited Members

25.177.1 Detailed Description

[MovePatientRootQuery](#) contains: the class which will produce a dataset for c-move with patient root.

25.177.2 Constructor & Destructor Documentation

25.177.2.1 `gdcm::MovePatientRootQuery::MovePatientRootQuery ()`

25.177.3 Member Function Documentation

25.177.3.1 `UIDs::TSName gdcm::MovePatientRootQuery::GetAbstractSyntaxUID () const` [virtual]

Implements [gdcm::BaseRootQuery](#).

25.177.3.2 `std::vector<Tag> gdcm::MovePatientRootQuery::GetTagListByLevel (const EQueryLevel & inQueryLevel)`
[virtual]

this function will return all tags at a given query level, so that they maybe selected for searching. The boolean forFind is true if the query is a find query, or false for a move query.

Implements [gdcm::BaseRootQuery](#).

25.177.3.3 `void gdcm::MovePatientRootQuery::InitializeDataSet (const EQueryLevel & inQueryLevel)` [virtual]

this function sets tag 8,52 to the appropriate value based on query level also fills in the right unique tags, as per the standard's requirements should allow for connection with dcmTk

Implements [gdcm::BaseRootQuery](#).

25.177.3.4 `bool gdcm::MovePatientRootQuery::ValidateQuery (bool inStrict =true) const` [virtual]

have to be able to ensure that 0x8,0x52 is set (which will be true if InitializeDataSet is called...) that the level is appropriate (ie, not setting PATIENT for a study query that the tags in the query match the right level (either required, unique, optional) by default, this function checks to see if the query is for finding, which is more permissive than for moving. For moving, only the unique tags are allowed. 10 Jan 2011: adding in the 'strict' mode. according to the

standard (at least, how I've read it), only tags for a particular level should be allowed in a particular query (ie, just series level tags in a series level query). However, it seems that dcm4chee doesn't share that interpretation. So, if 'inStrict' is false, then tags from the current level and all higher levels are now considered valid. So, if you're doing a non-strict series-level query, tags from the patient and study level can be passed along as well.

Implements [gdcm::BaseRootQuery](#).

25.177.4 Friends And Related Function Documentation

25.177.4.1 friend class QueryFactory [friend]

The documentation for this class was generated from the following file:


- [gdcmMovePatientRootQuery.h](#)

25.178 gdcm::MoveStudyRootQuery Class Reference


[MoveStudyRootQuery](#) contains: the class which will produce a dataset for C-MOVE with study root.

```
#include <gdcmMoveStudyRootQuery.h>
```

Inheritance diagram for gdcm::MoveStudyRootQuery:



Collaboration diagram for `gdcm::MoveStudyRootQuery`:



Public Member Functions

- [MoveStudyRootQuery](#) ()
- [UIDs::TSName GetAbstractSyntaxUID](#) () const
- `std::vector< Tag > GetTagListByLevel (const EQueryLevel &inQueryLevel)`
- `void InitializeDataSet (const EQueryLevel &inQueryLevel)`
- `bool ValidateQuery (bool inStrict=true) const`

Friends

- class [QueryFactory](#)

Additional Inherited Members

25.178.1 Detailed Description

[MoveStudyRootQuery](#) contains: the class which will produce a dataset for C-MOVE with study root.

25.178.2 Constructor & Destructor Documentation

25.178.2.1 `gdcm::MoveStudyRootQuery::MoveStudyRootQuery ()`

25.178.3 Member Function Documentation

25.178.3.1 `UIDs::TSName gdcm::MoveStudyRootQuery::GetAbstractSyntaxUID () const` `[virtual]`

Implements [gdcm::BaseRootQuery](#).

25.178.3.2 `std::vector<Tag> gdcm::MoveStudyRootQuery::GetTagListByLevel (const EQueryLevel & inQueryLevel)` `[virtual]`

this function will return all tags at a given query level, so that they maybe selected for searching. The boolean `forFind` is true if the query is a find query, or false for a move query.

Implements [gdcm::BaseRootQuery](#).

25.178.3.3 void gdcm::MoveStudyRootQuery::InitializeDataSet (const EQueryLevel & inQueryLevel) [virtual]

this function sets tag 8,52 to the appropriate value based on query level also fills in the right unique tags, as per the standard's requirements should allow for connection with dcmTk

Implements [gdcm::BaseRootQuery](#).

25.178.3.4 bool gdcm::MoveStudyRootQuery::ValidateQuery (bool inStrict = true) const [virtual]

have to be able to ensure that 0x8,0x52 is set (which will be true if InitializeDataSet is called...) that the level is appropriate (ie, not setting PATIENT for a study query that the tags in the query match the right level (either required, unique, optional) by default, this function checks to see if the query is for finding, which is more permissive than for moving. For moving, only the unique tags are allowed. 10 Jan 2011: adding in the 'strict' mode. according to the standard (at least, how I've read it), only tags for a particular level should be allowed in a particular query (ie, just series level tags in a series level query). However, it seems that dcm4chee doesn't share that interpretation. So, if 'inStrict' is false, then tags from the current level and all higher levels are now considered valid. So, if you're doing a non-strict series-level query, tags from the patient and study level can be passed along as well.

Implements [gdcm::BaseRootQuery](#).

25.178.4 Friends And Related Function Documentation

25.178.4.1 friend class QueryFactory [friend]

The documentation for this class was generated from the following file:


- [gdcmMoveStudyRootQuery.h](#)

25.179 gdcm::NestedModuleEntries Class Reference


Class for representing a [NestedModuleEntries](#).

```
#include <gdcmNestedModuleEntries.h>
```

Inheritance diagram for gdcm::NestedModuleEntries:



Collaboration diagram for `gdcm::NestedModuleEntries`:



Public Types

- typedef `std::vector< ModuleEntry>::size_type` [SizeType](#)

Public Member Functions

- [NestedModuleEntries](#) (`const char *name=""`, `const char *type="3"`, `const char *description=""`)
- void [AddModuleEntry](#) (`const ModuleEntry &me`)
- const [ModuleEntry](#) & [GetModuleEntry](#) ([SizeType](#) idx) const
- [ModuleEntry](#) & [GetModuleEntry](#) ([SizeType](#) idx)
- [SizeType](#) [GetNumberOfModuleEntries](#) ()

Friends

- `std::ostream & operator<< (std::ostream &_os, const NestedModuleEntries &_val)`

Additional Inherited Members

25.179.1 Detailed Description

Class for representing a [NestedModuleEntries](#).

Note

bla

See Also

[ModuleEntry](#)

25.179.2 Member Typedef Documentation

25.179.2.1 `typedef std::vector<ModuleEntry>::size_type gdcmm::NestedModuleEntries::SizeType`

25.179.3 Constructor & Destructor Documentation

25.179.3.1 `gdcmm::NestedModuleEntries::NestedModuleEntries (const char * name = " ", const char * type = "3", const char * description = " ")` `[inline]`

25.179.4 Member Function Documentation

25.179.4.1 `void gdcmm::NestedModuleEntries::AddModuleEntry (const ModuleEntry & me)` `[inline]`

25.179.4.2 `const ModuleEntry& gdcmm::NestedModuleEntries::GetModuleEntry (SizeType idx) const` `[inline]`

25.179.4.3 `ModuleEntry& gdcmm::NestedModuleEntries::GetModuleEntry (SizeType idx)` `[inline]`

25.179.4.4 `SizeType gdcmm::NestedModuleEntries::GetNumberOfModuleEntries ()` `[inline]`

25.179.5 Friends And Related Function Documentation

25.179.5.1 `std::ostream& operator<< (std::ostream & _os, const NestedModuleEntries & _val)` `[friend]`


The documentation for this class was generated from the following file:

- [gdcmmNestedModuleEntries.h](#)


25.180 gdcmm::NoEvent Class Reference

```
#include <gdcmmEvent.h>
```

Inheritance diagram for `gdcm::NoEvent`:



Collaboration diagram for `gdcm::NoEvent`:



Additional Inherited Members

25.180.1 Detailed Description

Define some common GDCM events

The documentation for this class was generated from the following file:


- [gdcmEvent.h](#)

25.181 `gdcm::Object` Class Reference

[Object.](#)

```
#include <gdcmObject.h>
```


Inheritance diagram for gdcmm::Object:



Public Member Functions

- [Object](#) ()
- [Object](#) (const [Object](#) &)
- *Special requirement for copy/cstor, assignment operator.*
- virtual [~Object](#) ()
- void [operator=](#) (const [Object](#) &)
- virtual void [Print](#) (std::ostream &) const

Protected Member Functions

- void [Register](#) ()
- void [UnRegister](#) ()

Friends

- std::ostream & [operator<<](#) (std::ostream &os, const [Object](#) &obj)
- template<class ObjectType >
class [SmartPointer](#)

25.181.1 Detailed Description

[Object](#).

Note

main superclass for object that want to use [SmartPointer](#) invasive ref counting system

See Also

[SmartPointer](#)

25.181.2 Constructor & Destructor Documentation

25.181.2.1 `gdcm::Object::Object ()` `[inline]`

25.181.2.2 `virtual gdcm::Object::~~Object ()` `[inline]`, `[virtual]`

25.181.2.3 `gdcm::Object::Object (const Object &)` `[inline]`

Special requirement for copy/cstor, assigment operator.

25.181.3 Member Function Documentation

25.181.3.1 `void gdcm::Object::operator= (const Object &)` `[inline]`

25.181.3.2 `virtual void gdcm::Object::Print (std::ostream &) const` `[inline]`, `[virtual]`

Reimplemented in [gdcm::SequenceOfFragments](#), [gdcm::ByteValue](#), [gdcm::SequenceOfItems](#), [gdcm::BaseRootQuery](#), [gdcm::Scanner](#), [gdcm::Image](#), [gdcm::Curve](#), [gdcm::Overlay](#), [gdcm::Bitmap](#), [gdcm::LookupTable](#), [gdcm::Pixmap](#), and [gdcm::SegmentedPaletteColorLookupTable](#).

Examples:

[ReadAndDumpDICOMDIR.cxx](#).

Referenced by `gdcm::operator<<()`.

25.181.3.3 `void gdcm::Object::Register ()` `[inline]`, `[protected]`

25.181.3.4 `void gdcm::Object::UnRegister ()` `[inline]`, `[protected]`

25.181.4 Friends And Related Function Documentation

25.181.4.1 `std::ostream& operator<< (std::ostream & os, const Object & obj)` `[friend]`

25.181.4.2 `template<class ObjectType > friend class SmartPointer` `[friend]`

The documentation for this class was generated from the following file:

- [gdcmObject.h](#)

25.182 gdcm::Orientation Class Reference

class to handle [Orientation](#)

```
#include <gdcmOrientation.h>
```

Public Types

- enum [OrientationType](#) {
 [UNKNOWN](#),
 [AXIAL](#),
 [CORONAL](#),
 [SAGITTAL](#),
 [OBLIQUE](#) }

Public Member Functions

- [Orientation](#) ()
- [~Orientation](#) ()
- void [Print](#) (std::ostream &) const
 Print.

Static Public Member Functions

- static const char * [GetLabel](#) ([OrientationType](#) type)
 Return the label of an Orientation.
- static double [GetObliquityThresholdCosineValue](#) ()
- static [OrientationType](#) [GetType](#) (const double dircos[6])
- static void [SetObliquityThresholdCosineValue](#) (double val)
 ObliquityThresholdCosineValue stuff.

Static Protected Member Functions

- static char [GetMajorAxisFromPatientRelativeDirectionCosine](#) (double x, double y, double z)

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [Orientation](#) &o)

25.182.1 Detailed Description

class to handle [Orientation](#)

25.182.2 Member Enumeration Documentation

25.182.2.1 enum `gdcm::Orientation::OrientationType`

Enumerator

UNKNOWN
AXIAL
CORONAL
SAGITTAL
OBLIQUE

25.182.3 Constructor & Destructor Documentation

25.182.3.1 `gdcm::Orientation::Orientation ()`

25.182.3.2 `gdcm::Orientation::~~Orientation ()`

25.182.4 Member Function Documentation

25.182.4.1 `static const char* gdcm::Orientation::GetLabel (OrientationType type)` [static]

Return the label of an [Orientation](#).

25.182.4.2 `static char gdcm::Orientation::GetMajorAxisFromPatientRelativeDirectionCosine (double x, double y, double z)` [static], [protected]

25.182.4.3 `static double gdcm::Orientation::GetObliquityThresholdCosineValue ()` [static]

25.182.4.4 `static OrientationType gdcm::Orientation::GetType (const double dircos[6])` [static]

Return the type of orientation from a direction cosines Input is an array of 6 double

25.182.4.5 `void gdcm::Orientation::Print (std::ostream &) const`

Print.

Referenced by `gdcm::operator<<()`.

25.182.4.6 `static void gdcm::Orientation::SetObliquityThresholdCosineValue (double val)` [static]

ObliquityThresholdCosineValue stuff.

25.182.5 Friends And Related Function Documentation

25.182.5.1 `std::ostream& operator<< (std::ostream &_os, const Orientation &o)` [friend]

The documentation for this class was generated from the following file:


- [gdcmOrientation.h](#)

25.183 gdcm::Overlay Class Reference


[Overlay](#) class.

```
#include <gdcmOverlay.h>
```

Inheritance diagram for gdcm::Overlay:



Collaboration diagram for gdcm::Overlay:



Public Types

- enum [OverlayType](#) {
 [Invalid](#) = 0,
 [Graphics](#) = 1,
 [ROI](#) = 2 }

Public Member Functions

- [Overlay](#) ()
- [Overlay](#) ([Overlay](#) const &ov)
- [~Overlay](#) ()

- void [Decode](#) (std::istream &is, std::ostream &os)
Do not use.
- void [Decompress](#) (std::ostream &os) const
Decode the internal OverlayData (packed bits) into unpacked representation.
- unsigned short [GetBitPosition](#) () const
return bit position
- unsigned short [GetBitsAllocated](#) () const
return bits allocated
- bool [GetBuffer](#) (char *buffer) const
Get the raw (packed bits) Overlay Data:
- unsigned short [GetColumns](#) () const
get columns
- const char * [GetDescription](#) () const
get description
- unsigned short [GetGroup](#) () const
Get Group number.
- const signed short * [GetOrigin](#) () const
get origin
- const [ByteValue](#) & [GetOverlayData](#) () const
- unsigned short [GetRows](#) () const
get rows
- const char * [GetType](#) () const
get type
- [OverlayType](#) [GetTypeAsEnum](#) () const
- bool [GetUnpackBuffer](#) (unsigned char *buffer) const
Do not use.
- bool [GetUnpackBuffer](#) (char *buffer, size_t len) const
- size_t [GetUnpackBufferLength](#) () const
- bool [GrabOverlayFromPixelData](#) ([DataSet](#) const &ds)
- bool [IsEmpty](#) () const
Return whether or not the Overlay is empty:
- bool [IsInPixelData](#) () const
return if the Overlay is stored in the pixel data or not
- void [IsInPixelData](#) (bool b)
Set whether or no the OverlayData is in the Pixel Data:
- bool [IsZero](#) () const
return true if all bits are set to 0
- void [Print](#) (std::ostream &) const
Print.
- void [SetBitPosition](#) (unsigned short bitposition)
set bit position
- void [SetBitsAllocated](#) (unsigned short bitsallocated)
set bits allocated
- void [SetColumns](#) (unsigned short columns)
set columns
- void [SetDescription](#) (const char *description)
set description

- void [SetFrameOrigin](#) (unsigned short frameorigin)
set frame origin
- void [SetGroup](#) (unsigned short group)
Set Group number.
- void [SetNumberOfFrames](#) (unsigned int numberofframes)
set number of frames
- void [SetOrigin](#) (const signed short origin[2])
set origin
- void [SetOverlay](#) (const char *array, size_t length)
set overlay from byte array + length
- void [SetRows](#) (unsigned short rows)
set rows
- void [SetType](#) (const char *type)
set type
- void [Update](#) (const [DataElement](#) &de)
Update overlay from data element de:

Static Public Member Functions

- static const char * [GetOverlayTypeAsString](#) ([OverlayType](#) ot)
- static [OverlayType](#) [GetOverlayTypeFromString](#) (const char *)

Additional Inherited Members

25.183.1 Detailed Description

[Overlay](#) class.

Note

see [AreOverlaysInPixelData](#)

Todo Is there actually any way to recognize an overlay ? On images with multiple overlay I do not see any way to differentiate them (other than the group tag).

Example:

25.183.2 Member Enumeration Documentation

25.183.2.1 enum gdcm::Overlay::OverlayType

Enumerator

Invalid

Graphics

ROI

25.183.3 Constructor & Destructor Documentation

25.183.3.1 `gdcM::Overlay::Overlay ()`

25.183.3.2 `gdcM::Overlay::~~Overlay ()`

25.183.3.3 `gdcM::Overlay::Overlay (Overlay const & ov)`

25.183.4 Member Function Documentation

25.183.4.1 `void gdcM::Overlay::Decode (std::istream & is, std::ostream & os)`

Do not use.

25.183.4.2 `void gdcM::Overlay::Decompress (std::ostream & os) const`

Decode the internal OverlayData (packed bits) into unpacked representation.

25.183.4.3 `unsigned short gdcM::Overlay::GetBitPosition () const`

return bit position

25.183.4.4 `unsigned short gdcM::Overlay::GetBitsAllocated () const`

return bits allocated

25.183.4.5 `bool gdcM::Overlay::GetBuffer (char * buffer) const`

Get the raw (packed bits) [Overlay](#) Data:

25.183.4.6 `unsigned short gdcM::Overlay::GetColumns () const`

get columns

25.183.4.7 `const char* gdcM::Overlay::GetDescription () const`

get description

25.183.4.8 `unsigned short gdcM::Overlay::GetGroup () const`

Get Group number.

25.183.4.9 `const signed short* gdcM::Overlay::GetOrigin () const`

get origin

25.183.4.10 `const ByteValue& gdcm::Overlay::GetOverlayData () const`

Return the [Overlay](#) Data as [ByteValue](#): Not thread safe

25.183.4.11 `static const char* gdcm::Overlay::GetOverlayTypeAsString (OverlayType ot) [static]`

25.183.4.12 `static OverlayType gdcm::Overlay::GetOverlayTypeFromString (const char *) [static]`

25.183.4.13 `unsigned short gdcm::Overlay::GetRows () const`

get rows

25.183.4.14 `const char* gdcm::Overlay::GetType () const`

get type

25.183.4.15 `OverlayType gdcm::Overlay::GetTypeAsEnum () const`

25.183.4.16 `bool gdcm::Overlay::GetUnpackBuffer (unsigned char * buffer) const`

Do not use.

25.183.4.17 `bool gdcm::Overlay::GetUnpackBuffer (char * buffer, size_t len) const`

Retrieve the unpack buffer for [Overlay](#). This is an error if the size is below [GetUnpackBufferLength\(\)](#)

25.183.4.18 `size_t gdcm::Overlay::GetUnpackBufferLength () const`

Retrieve the size of the buffer needed to hold the [Overlay](#) as specified by Col & Row parameters

25.183.4.19 `bool gdcm::Overlay::GrabOverlayFromPixelData (DataSet const & ds)`

25.183.4.20 `bool gdcm::Overlay::IsEmpty () const`

Return whether or not the [Overlay](#) is empty:

25.183.4.21 `bool gdcm::Overlay::IsInPixelData () const`

return if the [Overlay](#) is stored in the pixel data or not

25.183.4.22 `void gdcm::Overlay::IsInPixelData (bool b)`

Set whether or no the OverlayData is in the Pixel Data:

25.183.4.23 `bool gdcm::Overlay::IsZero () const`

return true if all bits are set to 0

25.183.4.24 void `gdcmm::Overlay::Print (std::ostream &) const` `[virtual]`

Print.

Reimplemented from [gdcmm::Object](#).

25.183.4.25 void `gdcmm::Overlay::SetBitPosition (unsigned short bitposition)`

set bit position

25.183.4.26 void `gdcmm::Overlay::SetBitsAllocated (unsigned short bitsallocated)`

set bits allocated

25.183.4.27 void `gdcmm::Overlay::SetColumns (unsigned short columns)`

set columns

25.183.4.28 void `gdcmm::Overlay::SetDescription (const char * description)`

set description

25.183.4.29 void `gdcmm::Overlay::SetFrameOrigin (unsigned short frameorigin)`

set frame origin

25.183.4.30 void `gdcmm::Overlay::SetGroup (unsigned short group)`

Set Group number.

25.183.4.31 void `gdcmm::Overlay::SetNumberOfFrames (unsigned int numberofframes)`

set number of frames

25.183.4.32 void `gdcmm::Overlay::SetOrigin (const signed short origin[2])`

set origin

25.183.4.33 void `gdcmm::Overlay::SetOverlay (const char * array, size_t length)`

set overlay from byte array + length

25.183.4.34 void `gdcmm::Overlay::SetRows (unsigned short rows)`

set rows

25.183.4.35 void gdcm::Overlay::SetType (const char * *type*)

set type

25.183.4.36 void gdcm::Overlay::Update (const DataElement & *de*)

Update overlay from data element de:

The documentation for this class was generated from the following file:


- [gdcmOverlay.h](#)

25.184 gdcm::ParseException Class Reference


[ParseException](#) Standard exception handling object.

```
#include <gdcmParseException.h>
```

Inheritance diagram for gdcm::ParseException:



Collaboration diagram for `gdcm::ParseException`:



Public Member Functions

- [ParseException](#) ()
- virtual [~ParseException](#) () throw ()
- const [DataElement](#) & [GetLastElement](#) () const
- [ParseException](#) & [operator=](#) (const [ParseException](#) &orig)
- void [SetLastElement](#) ([DataElement](#) &de)

25.184.1 Detailed Description

[ParseException](#) Standard exception handling object.

25.184.2 Constructor & Destructor Documentation

25.184.2.1 `gdcm::ParseException::ParseException ()` `[inline]`

25.184.2.2 `virtual gdcm::ParseException::~~ParseException () throw ()` `[inline], [virtual]`

25.184.3 Member Function Documentation

25.184.3.1 `const DataElement& gdcm::ParseException::GetLastElement () const` `[inline]`

25.184.3.2 `ParseException& gdcm::ParseException::operator= (const ParseException & orig)` `[inline]`

Assignment operator.

25.184.3.3 void gdcm::ParseException::SetLastElement (DataElement & de) [inline]

Equivalence operator.

Referenced by gdcm::Fragment::ReadBacktrack(), and gdcm::Fragment::ReadValue().

The documentation for this class was generated from the following file:

- [gdcmParseException.h](#)

25.185 gdcm::Parser Class Reference

[Parser](#) ala XML_Parser from expat (SAX)

```
#include <gdcmParser.h>
```

Public Types

- typedef void(* [EndElementHandler](#))(void *userData, const [Tag](#) &name)
- enum [ErrorType](#) {
[NoError](#),
[NoMemoryError](#),
[SyntaxError](#),
[NoElementsError](#),
[TagMismatchError](#),
[DuplicateAttributeError](#),
[JunkAfterDocElementError](#),
[UndefinedEntityError](#),
[UnexpectedStateError](#) }
- typedef void(* [StartElementHandler](#))(void *userData, const [Tag](#) &tag, const char *atts[])

Public Member Functions

- [Parser](#) ()
- [~Parser](#) ()
- unsigned long [GetCurrentByteIndex](#) () const
- [ErrorType](#) [GetErrorCode](#) () const
- void * [GetUserData](#) () const
- bool [Parse](#) (const char *s, int len, bool isFinal)
- void [SetElementHandler](#) ([StartElementHandler](#) start, [EndElementHandler](#) end)
- void [SetUserData](#) (void *userData)

Static Public Member Functions

- static const char * [GetErrorString](#) ([ErrorType](#) const &err)

Protected Member Functions

- char * [GetBuffer](#) (int len)
- bool [ParseBuffer](#) (int len, bool isFinal)
- [ErrorType](#) [Process](#) ()

25.185.1 Detailed Description

[Parser](#) ala XML_Parser from expat (SAX)

Detailed description here

Note

Simple API for DICOM

25.185.2 Member Typedef Documentation

25.185.2.1 `typedef void(* gdcmm::Parser::EndElementHandler)(void *userData, const Tag &name)`

25.185.2.2 `typedef void(* gdcmm::Parser::StartElementHandler)(void *userData, const Tag &tag, const char *atts[])`

25.185.3 Member Enumeration Documentation

25.185.3.1 `enum gdcmm::Parser::ErrorType`

Enumerator

NoError

NoMemoryError

SyntaxError

NoElementsError

TagMismatchError

DuplicateAttributeError

JunkAfterDocElementError

UndefinedEntityError

UnexpectedStateError

25.185.4 Constructor & Destructor Documentation

25.185.4.1 `gdcmm::Parser::Parser () [inline]`

25.185.4.2 `gdcmm::Parser::~~Parser () [inline]`

25.185.5 Member Function Documentation

25.185.5.1 `char* gdcmm::Parser::GetBuffer (int len) [protected]`

25.185.5.2 `unsigned long gdcmm::Parser::GetCurrentByteIndex () const`

25.185.5.3 `ErrorType gdcmm::Parser::GetErrorCode () const`

25.185.5.4 `static const char* gdcmm::Parser::GetErrorString (ErrorType const & err) [static]`

25.185.5.5 `void* gdcmm::Parser::GetUserData () const`

25.185.5.6 `bool gdcm::Parser::Parse (const char * s, int len, bool isFinal)`

25.185.5.7 `bool gdcm::Parser::ParseBuffer (int len, bool isFinal)` [protected]

25.185.5.8 `ErrorType gdcm::Parser::Process ()` [protected]

25.185.5.9 `void gdcm::Parser::SetElementHandler (StartElementHandler start, EndElementHandler end)`

25.185.5.10 `void gdcm::Parser::SetUserData (void * userData)`

The documentation for this class was generated from the following file:

- [gdcmParser.h](#)

25.186 gdcm::Patient Class Reference

See PS 3.3 - 2007 DICOM MODEL OF THE REAL-WORLD, p 54.

```
#include <gdcmPatient.h>
```

Public Member Functions

- [Patient \(\)](#)

25.186.1 Detailed Description

See PS 3.3 - 2007 DICOM MODEL OF THE REAL-WORLD, p 54.

25.186.2 Constructor & Destructor Documentation

25.186.2.1 `gdcm::Patient::Patient ()` [inline]

The documentation for this class was generated from the following file:


- [gdcmPatient.h](#)

25.187 gdcm::network::PDataTFPDU Class Reference


[PDataTFPDU Table](#) 9-22 P-DATA-TF PDU FIELDS.

```
#include <gdcmPDataTFPDU.h>
```

Inheritance diagram for `gdcm::network::PDataTFPDU`:



Collaboration diagram for `gdcm::network::PDataTFPDU`:



Public Types

- `typedef std::vector`
 < [PresentationDataValue](#) >
 ::size_type [SizeType](#)

Public Member Functions

- [PDataTFPDU](#) ()
- void [AddPresentationDataValue](#) ([PresentationDataValue](#) const &pdv)
- [SizeType](#) [GetNumberOfPresentationDataValues](#) () const
- [PresentationDataValue](#) const & [GetPresentationDataValue](#) ([SizeType](#) i) const
- bool [IsLastFragment](#) () const
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

Protected Member Functions

- std::istream & [ReadInto](#) (std::istream &is, std::ostream &os)

25.187.1 Detailed Description

[PDataTFPDU Table](#) 9-22 P-DATA-TF PDU FIELDS.

25.187.2 Member Typedef Documentation

25.187.2.1 `typedef std::vector<PresentationDataValue>::size_type gdcm::network::PDataTFPDU::SizeType`

25.187.3 Constructor & Destructor Documentation

25.187.3.1 `gdcm::network::PDataTFPDU::PDataTFPDU ()`

25.187.4 Member Function Documentation

25.187.4.1 `void gdcm::network::PDataTFPDU::AddPresentationDataValue (PresentationDataValue const & pdv)`
[inline]

25.187.4.2 `SizeType gdcm::network::PDataTFPDU::GetNumberOfPresentationDataValues () const` [inline]

25.187.4.3 `PresentationDataValue const& gdcm::network::PDataTFPDU::GetPresentationDataValue (SizeType i) const`
[inline]

25.187.4.4 `bool gdcm::network::PDataTFPDU::IsLastFragment () const` [virtual]

Implements [gdcm::network::BasePDU](#).

25.187.4.5 `void gdcm::network::PDataTFPDU::Print (std::ostream & os) const` [virtual]

Implements [gdcm::network::BasePDU](#).

25.187.4.6 `std::istream& gdcm::network::PDataTFPDU::Read (std::istream & is)` [virtual]

Implements [gdcm::network::BasePDU](#).

25.187.4.7 `std::istream& gdcm::network::PDataTFPDU::ReadInto (std::istream & is, std::ostream & os)` [protected]

25.187.4.8 `size_t gdcm::network::PDataTFPDU::Size () const` [virtual]

Implements [gdcm::network::BasePDU](#).

25.187.4.9 `const std::ostream& gdcm::network::PDataTFPDU::Write (std::ostream & os) const` [virtual]

Implements [gdcm::network::BasePDU](#).

The documentation for this class was generated from the following file:


- [gdcmPDataTFPDU.h](#)

25.188 gdcm::PDBelement Class Reference

Class to represent a PDB [Element](#).

```
#include <gdcmPDBelement.h>
```

Collaboration diagram for gdcm::PDBelement:



Public Member Functions

- [PDBelement](#) ()
- `const char * GetName () const`
Set/Get Name.
- `const char * GetValue () const`
Set/Get Value.
- `bool operator== (const PDBelement &de) const`
- `void SetName (const char *name)`
- `void SetValue (const char *value)`

Protected Attributes

- `std::string NameField`
- `std::string ValueField`

Friends

- `std::ostream & operator<< (std::ostream &os, const PDBElement &val)`

25.188.1 Detailed Description

Class to represent a PDB [Element](#).

See Also

[PDBHeader](#)

25.188.2 Constructor & Destructor Documentation

25.188.2.1 `gdcm::PDBElement::PDBElement ()` [\[inline\]](#)

25.188.3 Member Function Documentation

25.188.3.1 `const char* gdcm::PDBElement::GetName () const` [\[inline\]](#)

Set/Get Name.

25.188.3.2 `const char* gdcm::PDBElement::GetValue () const` [\[inline\]](#)

Set/Get [Value](#).

25.188.3.3 `bool gdcm::PDBElement::operator== (const PDBElement & de) const` [\[inline\]](#)

References [NameField](#), and [ValueField](#).

25.188.3.4 `void gdcm::PDBElement::SetName (const char * name)` [\[inline\]](#)

25.188.3.5 `void gdcm::PDBElement::SetValue (const char * value)` [\[inline\]](#)

25.188.4 Friends And Related Function Documentation

25.188.4.1 `std::ostream& operator<< (std::ostream & os, const PDBElement & val)` [\[friend\]](#)

25.188.5 Member Data Documentation

25.188.5.1 `std::string gdcm::PDBElement::NameField` [\[protected\]](#)

Referenced by `gdcm::operator<<()`, and `operator==()`.

25.188.5.2 `std::string gdcm::PDBElement::ValueField` [\[protected\]](#)

Referenced by `gdcm::operator<<()`, and `operator==()`.

The documentation for this class was generated from the following file:

- [gdcnPDBElement.h](#)

25.189 gdcnPDBHeader Class Reference

Class for [PDBHeader](#).

```
#include <gdcnPDBHeader.h>
```

Public Member Functions

- [PDBHeader](#) ()
- [~PDBHeader](#) ()
- bool [FindPDBElementByName](#) (const char *name)
Return true if the PDB element matching name is found or not.
- const [PDBElement](#) & [GetPDBElementByName](#) (const char *name)
- bool [LoadFromDataElement](#) ([DataElement](#) const &de)
Load the PDB Header from a [DataElement](#) of a [DataSet](#).
- void [Print](#) (std::ostream &os) const
Print.

Static Public Member Functions

- static const [PrivateTag](#) & [GetPDBInfoTag](#) ()
Return the Private [Tag](#) where the PDB header is stored within a DICOM [DataSet](#).

Protected Member Functions

- const [PDBElement](#) & [GetPDBEEnd](#) () const

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [PDBHeader](#) &d)

25.189.1 Detailed Description

Class for [PDBHeader](#).

GEMS MR [Image](#) have an [Attribute](#) (0025,1b,GEMS_SERS_01) which store the Acquisition parameter of the MR [Image](#). It is compressed and can therefore not be used as is. This class de-encapsulated the Protocol Data Block and allow users to query element by name.

Warning

Everything you do with this code is at your own risk, since decoding process was not written from specification documents.

: the API of this class might change.

See Also

[CSAHeader](#)

25.189.2 Constructor & Destructor Documentation

25.189.2.1 `gdcm::PDBHeader::PDBHeader ()` `[inline]`

25.189.2.2 `gdcm::PDBHeader::~~PDBHeader ()` `[inline]`

25.189.3 Member Function Documentation

25.189.3.1 `bool gdcm::PDBHeader::FindPDBElementByName (const char * name)`

Return true if the PDB element matching name is found or not.

25.189.3.2 `const PDBElement& gdcm::PDBHeader::GetPDBEEnd () const` `[protected]`

25.189.3.3 `const PDBElement& gdcm::PDBHeader::GetPDBElementByName (const char * name)`

Lookup in the PDB header if a PDB element match the name 'name':

Warning

Case Sensitive

25.189.3.4 `static const PrivateTag& gdcm::PDBHeader::GetPDBInfoTag ()` `[static]`

Return the Private [Tag](#) where the PDB header is stored within a DICOM [DataSet](#).

25.189.3.5 `bool gdcm::PDBHeader::LoadFromDataElement (DataElement const & de)`

Load the PDB Header from a [DataElement](#) of a [DataSet](#).

25.189.3.6 `void gdcm::PDBHeader::Print (std::ostream & os) const`

Print.

Referenced by `gdcm::operator<<()`.

25.189.4 Friends And Related Function Documentation

25.189.4.1 `std::ostream& operator<< (std::ostream & _os, const PDBHeader & d)` `[friend]`

The documentation for this class was generated from the following file:


- [gdcmPDBHeader.h](#)

25.190 gdcm::PDFCodec Class Reference


[PDFCodec](#) class.

```
#include <gdcmPDFCodec.h>
```

Inheritance diagram for gdcm::PDFCodec:



Collaboration diagram for gdcm::PDFCodec:



Public Member Functions

- [PDFCodec](#) ()

- [~PDFCodec](#) ()
- bool [CanCode](#) ([TransferSyntax](#) const &) const
Return whether this coder support this transfer syntax (can code it)
- bool [CanDecode](#) ([TransferSyntax](#) const &) const
Return whether this decoder support this transfer syntax (can decode it)
- bool [Decode](#) ([DataElement](#) const &is, [DataElement](#) &os)
Decode.

Additional Inherited Members

25.190.1 Detailed Description

[PDFCodec](#) class.

25.190.2 Constructor & Destructor Documentation

25.190.2.1 `gdcm::PDFCodec::PDFCodec ()`

25.190.2.2 `gdcm::PDFCodec::~~PDFCodec ()`

25.190.3 Member Function Documentation

25.190.3.1 `bool gdcm::PDFCodec::CanCode (TransferSyntax const &) const` `[inline]`, `[virtual]`

Return whether this coder support this transfer syntax (can code it)

Implements [gdcm::Coder](#).

25.190.3.2 `bool gdcm::PDFCodec::CanDecode (TransferSyntax const &) const` `[inline]`, `[virtual]`

Return whether this decoder support this transfer syntax (can decode it)

Implements [gdcm::Decoder](#).

25.190.3.3 `bool gdcm::PDFCodec::Decode (DataElement const & , DataElement &)` `[virtual]`

Decode.

Reimplemented from [gdcm::Decoder](#).

The documentation for this class was generated from the following file:

- [gdcmPDFCodec.h](#)

25.191 gdcm::network::PDUFactory Class Reference

[PDUFactory](#) basically, given an initial byte, construct the appropriate PDU. This way, the event loop doesn't have to know about all the different PDU types.

```
#include <gdcmPDUFactory.h>
```

Static Public Member Functions

- static [BasePDU](#) * [ConstructAbortPDU](#) ()
- static [BasePDU](#) * [ConstructPDU](#) (uint8_t itemtype)
- static [BasePDU](#) * [ConstructReleasePDU](#) ()
- static std::vector< [BasePDU](#) * > [CreateCEchoPDU](#) (const [ULConnection](#) &inConnection)
- static std::vector< [BasePDU](#) * > [CreateCFindPDU](#) (const [ULConnection](#) &inConnection, const [BaseRootQuery](#) *inRootQuery)
- static std::vector< [BasePDU](#) * > [CreateCMovePDU](#) (const [ULConnection](#) &inConnection, const [BaseRootQuery](#) *inRootQuery)
- static std::vector< [BasePDU](#) * > [CreateCStoreRQPDU](#) (const [ULConnection](#) &inConnection, const [File](#) &file)
- static std::vector< [BasePDU](#) * > [CreateCStoreRSPPDU](#) (const [DataSet](#) *inDataSet, const [BasePDU](#) *inPC)
- static [EEventID](#) [DetermineEventByPDU](#) (const [BasePDU](#) *inPDU)
- static std::vector< [PresentationDataValue](#) > [GetPDVs](#) (const std::vector< [BasePDU](#) * > &inDataPDUs)

25.191.1 Detailed Description

[PDUFactory](#) basically, given an initial byte, construct the appropriate PDU. This way, the event loop doesn't have to know about all the different PDU types.

25.191.2 Member Function Documentation

- 25.191.2.1 static [BasePDU](#)* [gdcmm::network::PDUFactory::ConstructAbortPDU](#) () [static]
- 25.191.2.2 static [BasePDU](#)* [gdcmm::network::PDUFactory::ConstructPDU](#) (uint8_t *itemtype*) [static]
- 25.191.2.3 static [BasePDU](#)* [gdcmm::network::PDUFactory::ConstructReleasePDU](#) () [static]
- 25.191.2.4 static std::vector<[BasePDU](#)*> [gdcmm::network::PDUFactory::CreateCEchoPDU](#) (const [ULConnection](#) &*inConnection*) [static]
- 25.191.2.5 static std::vector<[BasePDU](#)*> [gdcmm::network::PDUFactory::CreateCFindPDU](#) (const [ULConnection](#) &*inConnection*, const [BaseRootQuery](#) * *inRootQuery*) [static]
- 25.191.2.6 static std::vector<[BasePDU](#)*> [gdcmm::network::PDUFactory::CreateCMovePDU](#) (const [ULConnection](#) &*inConnection*, const [BaseRootQuery](#) * *inRootQuery*) [static]
- 25.191.2.7 static std::vector<[BasePDU](#)*> [gdcmm::network::PDUFactory::CreateCStoreRQPDU](#) (const [ULConnection](#) &*inConnection*, const [File](#) & *file*) [static]
- 25.191.2.8 static std::vector<[BasePDU](#)*> [gdcmm::network::PDUFactory::CreateCStoreRSPPDU](#) (const [DataSet](#) * *inDataSet*, const [BasePDU](#) * *inPC*) [static]
- 25.191.2.9 static [EEventID](#) [gdcmm::network::PDUFactory::DetermineEventByPDU](#) (const [BasePDU](#) * *inPDU*) [static]
- 25.191.2.10 static std::vector<[PresentationDataValue](#)> [gdcmm::network::PDUFactory::GetPDVs](#) (const std::vector<[BasePDU](#) * > &*inDataPDUs*) [static]

The documentation for this class was generated from the following file:

- [gdcmmPDUFactory.h](#)

25.192 gdcm::PersonName Class Reference

[PersonName](#) class.

```
#include <gdcmPersonName.h>
```

Public Member Functions

- unsigned int [GetMaxLength](#) () const
- unsigned int [GetNumberOfComponents](#) () const
- void [Print](#) (std::ostream &os) const
- void [SetBlob](#) (const std::vector< char > &v)
- void [SetComponents](#) (const char *comp1="", const char *comp2="", const char *comp3="", const char *comp4="", const char *comp5="")
- void [SetComponents](#) (const char *components[])

Public Attributes

- char [Component](#) [[MaxNumberOfComponents](#)][[MaxLength](#)+1]

Static Public Attributes

- static const unsigned int [MaxLength](#) = 64
- static const unsigned int [MaxNumberOfComponents](#) = 5
- static const char [Padding](#) = ' '
- static const char [Separator](#) = '^'

25.192.1 Detailed Description

[PersonName](#) class.

25.192.2 Member Function Documentation

25.192.2.1 unsigned int gdcm::PersonName::GetMaxLength () const [inline]

25.192.2.2 unsigned int gdcm::PersonName::GetNumberOfComponents () const [inline]

25.192.2.3 void gdcm::PersonName::Print (std::ostream & os) const [inline]

25.192.2.4 void gdcm::PersonName::SetBlob (const std::vector< char > & v) [inline]

25.192.2.5 void gdcm::PersonName::SetComponents (const char * comp1 = " ", const char * comp2 = " ", const char * comp3 = " ", const char * comp4 = " ", const char * comp5 = " ") [inline]

25.192.2.6 void gdcm::PersonName::SetComponents (const char * components[]) [inline]

25.192.3 Member Data Documentation

25.192.3.1 `char gdcM::PersonName::Component[MaxNumberOfComponents][MaxLength+1]`

25.192.3.2 `const unsigned int gdcM::PersonName::MaxLength = 64` `[static]`

25.192.3.3 `const unsigned int gdcM::PersonName::MaxNumberOfComponents = 5` `[static]`

25.192.3.4 `const char gdcM::PersonName::Padding = ''` `[static]`

25.192.3.5 `const char gdcM::PersonName::Separator = '^'` `[static]`

The documentation for this class was generated from the following file:


- [gdcMPersonName.h](#)

25.193 gdcM::PGXCodec Class Reference


Class to do PGX See PGX as used in JPEG 2000 implementation and reference images.

```
#include <gdcMPGXCodec.h>
```

Inheritance diagram for gdcM::PGXCodec:



Collaboration diagram for gdcm::PGXCodec:



Public Member Functions

- [PGXCodec](#) ()
- [~PGXCodec](#) ()
- bool [CanCode](#) ([TransferSyntax](#) const &ts) const
Return whether this coder support this transfer syntax (can code it)
- bool [CanDecode](#) ([TransferSyntax](#) const &ts) const
Return whether this decoder support this transfer syntax (can decode it)
- bool [GetHeaderInfo](#) (std::istream &is, [TransferSyntax](#) &ts)
- bool [Read](#) (const char *filename, [DataElement](#) &out) const
- bool [Write](#) (const char *filename, const [DataElement](#) &out) const

Additional Inherited Members

25.193.1 Detailed Description

Class to do PGX See PGX as used in JPEG 2000 implementation and reference images.

25.193.2 Constructor & Destructor Documentation

25.193.2.1 `gdcm::PGXCodec::PGXCodec ()`

25.193.2.2 `gdcm::PGXCodec::~~PGXCodec ()`

25.193.3 Member Function Documentation

25.193.3.1 `bool gdcm::PGXCodec::CanCode (TransferSyntax const &) const` `[virtual]`

Return whether this coder support this transfer syntax (can code it)

Reimplemented from [gdcm::ImageCodec](#).

25.193.3.2 `bool gdcm::PGXCodec::CanDecode (TransferSyntax const &) const` `[virtual]`

Return whether this decoder support this transfer syntax (can decode it)

Reimplemented from [gdcm::ImageCodec](#).

25.193.3.3 `bool gdcM::PGXCodec::GetHeaderInfo (std::istream & is, TransferSyntax & ts)` [virtual]

Reimplemented from [gdcM::ImageCodec](#).

25.193.3.4 `bool gdcM::PGXCodec::Read (const char * filename, DataElement & out) const`

25.193.3.5 `bool gdcM::PGXCodec::Write (const char * filename, const DataElement & out) const`

The documentation for this class was generated from the following file:

- [gdcM_PGXCodec.h](#)

25.194 gdcM::PhotometricInterpretation Class Reference

Class to represent an [PhotometricInterpretation](#).

```
#include <gdcMPhotometricInterpretation.h>
```

Public Types

- enum [PType](#) {
[UNKNOWN](#) = 0,
[MONOCHROME1](#),
[MONOCHROME2](#),
[PALETTE_COLOR](#),
[RGB](#),
[HSV](#),
[ARGB](#),
[CMYK](#),
[YBR_FULL](#),
[YBR_FULL_422](#),
[YBR_PARTIAL_422](#),
[YBR_PARTIAL_420](#),
[YBR_ICT](#),
[YBR_RCT](#),
[PI_END](#) }

Public Member Functions

- [PhotometricInterpretation](#) ([PType](#) pi=[UNKNOWN](#))
- unsigned short [GetSamplesPerPixel](#) () const
return the value for Sample Per Pixel associated with a particular Photometric Interpretation
- const char * [GetString](#) () const
- [PType](#) [GetType](#) () const
- bool [IsLossless](#) () const
- bool [IsLossy](#) () const
- bool [IsSameColorSpace](#) ([PhotometricInterpretation](#) const &pi) const
- operator [PType](#) () const

Static Public Member Functions

- static const char * [GetPIString](#) (PIType pi)
- static PIType [GetPIType](#) (const char *pi)
- static bool [IsRetired](#) (PIType pi)

Friends

- std::ostream & [operator<<](#) (std::ostream &os, const [PhotometricInterpretation](#) &pi)

25.194.1 Detailed Description

Class to represent an [PhotometricInterpretation](#).

Examples:

[CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [csa2img.cxx](#), [HelloVizWorld.cxx](#), and [iU22tomultisc.cxx](#).

25.194.2 Member Enumeration Documentation

25.194.2.1 enum gdcm::PhotometricInterpretation::PIType

Enumerator

UNKNOWN
MONOCHROME1
MONOCHROME2
PALETTE_COLOR
RGB
HSV
ARGB
CMYK
YBR_FULL
YBR_FULL_422
YBR_PARTIAL_422
YBR_PARTIAL_420
YBR_ICT
YBR_RCT
PI_END

25.194.3 Constructor & Destructor Documentation

25.194.3.1 `gdcm::PhotometricInterpretation::PhotometricInterpretation (PIType pi = UNKNOWN) [inline]`

25.194.4 Member Function Documentation

25.194.4.1 `static const char* gdcm::PhotometricInterpretation::GetPIString (PIType pi) [static]`

Referenced by `gdcm::operator<<()`.

25.194.4.2 `static PType gdcm::PhotometricInterpretation::GetPType (const char * pi)` `[static]`

25.194.4.3 `unsigned short gdcm::PhotometricInterpretation::GetSamplesPerPixel () const`

return the value for Sample Per Pixel associated with a particular Photometric Interpretation

25.194.4.4 `const char* gdcm::PhotometricInterpretation::GetString () const`

25.194.4.5 `PType gdcm::PhotometricInterpretation::GetType () const` `[inline]`

25.194.4.6 `bool gdcm::PhotometricInterpretation::IsLossless () const`

25.194.4.7 `bool gdcm::PhotometricInterpretation::IsLossy () const`

25.194.4.8 `static bool gdcm::PhotometricInterpretation::IsRetired (PType pi)` `[static]`

25.194.4.9 `bool gdcm::PhotometricInterpretation::IsSameColorSpace (PhotometricInterpretation const & pi) const`

25.194.4.10 `gdcm::PhotometricInterpretation::operator PType () const` `[inline]`

25.194.5 Friends And Related Function Documentation

25.194.5.1 `std::ostream& operator<< (std::ostream & os, const PhotometricInterpretation & pi)` `[friend]`

The documentation for this class was generated from the following file:

- [gdcmPhotometricInterpretation.h](#)

25.195 gdcm::PixelFormat Class Reference

[PixelFormat](#).

```
#include <gdcmPixelFormat.h>
```

Public Types

- enum [ScalarType](#) {
[UINT8](#),
[INT8](#),
[UINT12](#),
[INT12](#),
[UINT16](#),
[INT16](#),
[UINT32](#),
[INT32](#),
[FLOAT16](#),
[FLOAT32](#),
[FLOAT64](#),
[SINGLEBIT](#),
[UNKNOWN](#) }

Public Member Functions

- [PixelFormat](#) (unsigned short samplesperpixel=1, unsigned short bitsallocated=8, unsigned short bitsstored=8, unsigned short highbit=7, unsigned short pixelrepresentation=0)
- [PixelFormat](#) ([ScalarType](#) st)
- [~PixelFormat](#) ()
- unsigned short [GetBitsAllocated](#) () const
BitsAllocated see [Tag](#) (0028,0100) US Bits Allocated.
- unsigned short [GetBitsStored](#) () const
BitsStored see [Tag](#) (0028,0101) US Bits Stored.
- unsigned short [GetHighBit](#) () const
HighBit see [Tag](#) (0028,0102) US High Bit.
- int64_t [GetMax](#) () const
return the max possible of the pixel
- int64_t [GetMin](#) () const
return the min possible of the pixel
- unsigned short [GetPixelRepresentation](#) () const
PixelRepresentation: 0 or 1, see [Tag](#) (0028,0103) US Pixel Representation.
- uint8_t [GetPixelSize](#) () const
- unsigned short [GetSamplesPerPixel](#) () const
- [ScalarType](#) [GetScalarType](#) () const
ScalarType does not take into account the sample per pixel.
- const char * [GetScalarTypeAsString](#) () const
- bool [IsValid](#) () const
return IsValid
- [operator ScalarType](#) () const
- bool [operator!=](#) ([ScalarType](#) st) const
- bool [operator!=](#) (const [PixelFormat](#) &pf) const
- bool [operator==](#) ([ScalarType](#) st) const
- bool [operator==](#) (const [PixelFormat](#) &pf) const
- void [Print](#) (std::ostream &os) const
Print.
- void [SetBitsAllocated](#) (unsigned short ba)
- void [SetBitsStored](#) (unsigned short bs)
- void [SetHighBit](#) (unsigned short hb)
- void [SetPixelRepresentation](#) (unsigned short pr)
- void [SetSamplesPerPixel](#) (unsigned short spp)
- void [SetScalarType](#) ([ScalarType](#) st)

Protected Member Functions

- bool [Validate](#) ()
When image with 24/24/23 was read, need to validate.

Friends

- class [Bitmap](#)
- std::ostream & [operator<<](#) (std::ostream &_os, const [PixelFormat](#) &pf)

25.195.1 Detailed Description

[PixelFormat](#).

Note

By default the Pixel [Type](#) will be instantiated with the following parameters:

- SamplesPerPixel : 1
- BitsAllocated : 8
- BitsStored : 8
- HighBit : 7
- PixelRepresentation : 0

Examples:

[CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [csa2img.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GetJPEGSample-Precision.cxx](#), [iU22tomultisc.cxx](#), and [threadgdcm.cxx](#).

25.195.2 Member Enumeration Documentation

25.195.2.1 enum gdcm::PixelFormat::ScalarType

Enumerator

UINT8
INT8
UINT12
INT12
UINT16
INT16
UINT32
INT32
FLOAT16
FLOAT32
FLOAT64
SINGLEBIT
UNKNOWN

25.195.3 Constructor & Destructor Documentation

25.195.3.1 `gdcm::PixelFormat::PixelFormat (unsigned short samplesperpixel = 1, unsigned short bitsallocated = 8, unsigned short bitsstored = 8, unsigned short highbit = 7, unsigned short pixelrepresentation = 0)` `[inline]`, `[explicit]`

25.195.3.2 `gdcm::PixelFormat::PixelFormat (ScalarType st)`

25.195.3.3 `gdcm::PixelFormat::~~PixelFormat ()` `[inline]`

25.195.4 Member Function Documentation

25.195.4.1 unsigned short gdcm::PixelFormat::GetBitsAllocated () const [inline]

BitsAllocated see [Tag](#) (0028,0100) US Bits Allocated.

Examples:

[GetJPEGSamplePrecision.cxx](#).

25.195.4.2 unsigned short gdcm::PixelFormat::GetBitsStored () const [inline]

BitsStored see [Tag](#) (0028,0101) US Bits Stored.

Examples:

[GetJPEGSamplePrecision.cxx](#).

25.195.4.3 unsigned short gdcm::PixelFormat::GetHighBit () const [inline]

HighBit see [Tag](#) (0028,0102) US High Bit.

25.195.4.4 int64_t gdcm::PixelFormat::GetMax () const

return the max possible of the pixel

25.195.4.5 int64_t gdcm::PixelFormat::GetMin () const

return the min possible of the pixel

25.195.4.6 unsigned short gdcm::PixelFormat::GetPixelRepresentation () const [inline]

PixelRepresentation: 0 or 1, see [Tag](#) (0028,0103) US Pixel Representation.

25.195.4.7 uint8_t gdcm::PixelFormat::GetPixelSize () const

return the size of the pixel This is the number of words it would take to store one pixel

Warning

the return value takes into account the SamplesPerPixel
in the rare case when BitsAllocated == 12, the function assume word padding and value returned will be identical
as if BitsAllocated == 16

Examples:

[threadgdcm.cxx](#).

25.195.4.8 `unsigned short gdcm::PixelFormat::GetSamplesPerPixel () const`

Samples Per Pixel see (0028,0002) US Samples Per Pixel DICOM - only allows 1, 3 and 4 as valid value. Other value are undefined behavior.

Examples:

[threadgdcm.cxx](#).

25.195.4.9 `ScalarType gdcm::PixelFormat::GetScalarType () const`

ScalarType does not take into account the sample per pixel.

25.195.4.10 `const char* gdcm::PixelFormat::GetScalarTypeAsString () const`

25.195.4.11 `bool gdcm::PixelFormat::IsValid () const`

return IsValid

25.195.4.12 `gdcm::PixelFormat::operator ScalarType () const` `[inline]`

25.195.4.13 `bool gdcm::PixelFormat::operator!= (ScalarType st) const` `[inline]`

25.195.4.14 `bool gdcm::PixelFormat::operator!= (const PixelFormat & pf) const` `[inline]`

25.195.4.15 `bool gdcm::PixelFormat::operator== (ScalarType st) const` `[inline]`

25.195.4.16 `bool gdcm::PixelFormat::operator== (const PixelFormat & pf) const` `[inline]`

25.195.4.17 `void gdcm::PixelFormat::Print (std::ostream & os) const`

Print.

Referenced by `gdcm::operator<<()`.

25.195.4.18 `void gdcm::PixelFormat::SetBitsAllocated (unsigned short ba)` `[inline]`

25.195.4.19 `void gdcm::PixelFormat::SetBitsStored (unsigned short bs)` `[inline]`

25.195.4.20 `void gdcm::PixelFormat::SetHighBit (unsigned short hb)` `[inline]`

25.195.4.21 `void gdcm::PixelFormat::SetPixelRepresentation (unsigned short pr)` `[inline]`

25.195.4.22 `void gdcm::PixelFormat::SetSamplesPerPixel (unsigned short spp)` `[inline]`

Examples:

[CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), and [GenFakelImage.cxx](#).

References `gdcmAssertMacro`.

25.195.4.23 void gdcm::PixelFormat::SetScalarType (ScalarType st)

Set [PixelFormat](#) based only on the ScalarType

Warning

: You need to call SetScalarType *before* SetSamplesPerPixel

25.195.4.24 bool gdcm::PixelFormat::Validate () [protected]

When image with 24/24/23 was read, need to validate.

Referenced by gdcm::Bitmap::SetPixelFormat().

25.195.5 Friends And Related Function Documentation

25.195.5.1 friend class Bitmap [friend]

25.195.5.2 std::ostream& operator<< (std::ostream &_os, const PixelFormat & pf) [friend]



The documentation for this class was generated from the following file:

- [gdcmPixelFormat.h](#)

25.196 gdcm::Pixmap Class Reference

[Pixmap](#) class A bitmap based image. Used as parent for both IconImage and the main Pixel Data [Image](#) It does not contains any World Space information (IPP, IOP)

```
#include <gdcmPixmap.h>
```



- `Pixmap ()`
- `~Pixmap ()`
- `bool AreOverlaysInPixelData () const`
returns if Overlays are stored in the unused bit of the pixel data:
- `Curve & GetCurve (size_t i=0)`

Curve: group 50xx.

- const [Curve](#) & [GetCurve](#) (size_t i=0) const
- const [IconImage](#) & [GetIconImage](#) () const

Set/Get Icon Image.

- [IconImage](#) & [GetIconImage](#) ()
- size_t [GetNumberOfCurves](#) () const
- size_t [GetNumberOfOverlays](#) () const
- [Overlay](#) & [GetOverlay](#) (size_t i=0)

Overlay: group 60xx.

- const [Overlay](#) & [GetOverlay](#) (size_t i=0) const
- void [Print](#) (std::ostream &) const
- void [RemoveOverlay](#) (size_t i)
- void [SetIconImage](#) ([IconImage](#) const &ii)
- void [SetNumberOfCurves](#) (size_t n)
- void [SetNumberOfOverlays](#) (size_t n)

Protected Attributes

- std::vector< [Curve](#) > [Curves](#)
- [SmartPointer](#)< [IconImage](#) > [Icon](#)
- std::vector< [Overlay](#) > [Overlays](#)

Additional Inherited Members

25.196.1 Detailed Description

[Pixmap](#) class A bitmap based image. Used as parent for both [IconImage](#) and the main Pixel Data [Image](#) It does not contains any World Space information (IPP, IOP)

See Also

[PixmapReader](#)

25.196.2 Constructor & Destructor Documentation

25.196.2.1 `gdcm::Pixmap::Pixmap ()`

25.196.2.2 `gdcm::Pixmap::~~Pixmap ()`

25.196.3 Member Function Documentation

25.196.3.1 `bool gdcm::Pixmap::AreOverlaysInPixelData () const` `[virtual]`

returns if Overlays are stored in the unused bit of the pixel data:

Reimplemented from [gdcm::Bitmap](#).

25.196.3.2 `Curve& gdcm::Pixmap::GetCurve (size_t i = 0)` `[inline]`

[Curve](#): group 50xx.

25.196.3.3 `const Curve& gdcm::Pixmap::GetCurve (size_t i = 0) const` [inline]

25.196.3.4 `const IconImage& gdcm::Pixmap::GetIconImage () const` [inline]

Set/Get Icon [Image](#).

25.196.3.5 `IconImage& gdcm::Pixmap::GetIconImage ()` [inline]

25.196.3.6 `size_t gdcm::Pixmap::GetNumberOfCurves () const` [inline]

25.196.3.7 `size_t gdcm::Pixmap::GetNumberOfOverlays () const` [inline]

25.196.3.8 `Overlay& gdcm::Pixmap::GetOverlay (size_t i = 0)` [inline]

[Overlay](#): group 60xx.

25.196.3.9 `const Overlay& gdcm::Pixmap::GetOverlay (size_t i = 0) const` [inline]

25.196.3.10 `void gdcm::Pixmap::Print (std::ostream &) const` [virtual]

Reimplemented from [gdcm::Bitmap](#).

25.196.3.11 `void gdcm::Pixmap::RemoveOverlay (size_t i)` [inline]

25.196.3.12 `void gdcm::Pixmap::SetIconImage (IconImage const & ii)` [inline]

25.196.3.13 `void gdcm::Pixmap::SetNumberOfCurves (size_t n)` [inline]

25.196.3.14 `void gdcm::Pixmap::SetNumberOfOverlays (size_t n)` [inline]

25.196.4 Member Data Documentation

25.196.4.1 `std::vector<Curve> gdcm::Pixmap::Curves` [protected]

25.196.4.2 `SmartPointer<IconImage> gdcm::Pixmap::Icon` [protected]

25.196.4.3 `std::vector<Overlay> gdcm::Pixmap::Overlays` [protected]

The documentation for this class was generated from the following file:


- [gdcmPixmap.h](#)

25.197 gdcm::PixmapReader Class Reference


[PixmapReader](#).

```
#include <gdcmPixmapReader.h>
```

Inheritance diagram for gdcm::PixmapReader:



Collaboration diagram for `gdcm::PixmapReader`:



Public Member Functions

- [PixmapReader](#) ()
- virtual [~PixmapReader](#) ()
- const [Pixmap](#) & [GetPixmap](#) () const
Return the read image (need to call [Read\(\)](#) first)
- [Pixmap](#) & [GetPixmap](#) ()
- virtual bool [Read](#) ()

Protected Member Functions

- virtual bool [ReadACRNEMAIImage](#) ()
- virtual bool [ReadImage](#) ([MediaStorage](#) const &ms)
- bool [ReadImageInternal](#) ([MediaStorage](#) const &ms, bool handlepixeldata=true)

Protected Attributes

- [SmartPointer](#)< [Pixmap](#) > [PixelData](#)

25.197.1 Detailed Description

[PixmapReader](#).

Note

its role is to convert the DICOM [DataSet](#) into a [gdcm::Pixmap](#) representation By default it is also loading the lookup table and overlay when found as they impact the rendering of the image

See PS 3.3-2008, [Table C.7-11b IMAGE PIXEL MACRO ATTRIBUTES](#) for the list of attribute that belong to what gdcm calls a '[Pixmap](#)'

Warning

the API `ReadUpToTag` and `ReadSelectedTag`

See Also

[Pixmap](#)

25.197.2 Constructor & Destructor Documentation

25.197.2.1 `gdcm::PixmapReader::PixmapReader ()`

25.197.2.2 `virtual gdcm::PixmapReader::~~PixmapReader () [virtual]`

25.197.3 Member Function Documentation

25.197.3.1 `const Pixmap& gdcm::PixmapReader::GetPixmap () const`

Return the read image (need to call [Read\(\)](#) first)

25.197.3.2 `Pixmap& gdcm::PixmapReader::GetPixmap ()`

25.197.3.3 `virtual bool gdcm::PixmapReader::Read () [virtual]`

Read the DICOM image. There are two reason for failure:

1. The input filename is not DICOM
2. The input DICOM file does not contains an [Pixmap](#).

Reimplemented from [gdcm::Reader](#).

Reimplemented in [gdcm::ImageRegionReader](#), and [gdcm::ImageReader](#).

25.197.3.4 `virtual bool gdcm::PixmapReader::ReadACRNEMAIImage () [protected], [virtual]`

Reimplemented in [gdcm::ImageReader](#).

25.197.3.5 `virtual bool gdcm::PixmapReader::ReadImage (MediaStorage const & ms) [protected], [virtual]`

Reimplemented in [gdcm::ImageReader](#).

25.197.3.6 `bool gdcM::PixmapReader::ReadImageInternal (MediaStorage const & ms, bool handlepixeldata = true)`
`[protected]`

25.197.4 Member Data Documentation

25.197.4.1 `SmartPointer<Pixmap> gdcM::PixmapReader::PixelData` `[protected]`

The documentation for this class was generated from the following file:


- [gdcMPixmapReader.h](#)

25.198 gdcM::PixmapToPixmapFilter Class Reference


[PixmapToPixmapFilter](#) class Super class for all filter taking an image and producing an output image.

```
#include <gdcMPixmapToPixmapFilter.h>
```

Inheritance diagram for `gdcM::PixmapToPixmapFilter`:



Collaboration diagram for gdcm::PixmapToPixmapFilter:



Public Member Functions

- [PixmapToPixmapFilter \(\)](#)
- [~PixmapToPixmapFilter \(\)](#)
- [Pixmap & GetInput \(\)](#)
- [const Pixmap & GetOutput \(\) const](#)
Get Output image.
- [const Pixmap & GetOutputAsPixmap \(\) const](#)

Additional Inherited Members

25.198.1 Detailed Description

[PixmapToPixmapFilter](#) class Super class for all filter taking an image and producing an output image.

25.198.2 Constructor & Destructor Documentation

25.198.2.1 gdcm::PixmapToPixmapFilter::PixmapToPixmapFilter ()

25.198.2.2 `gdcm::PixmapToPixmapFilter::~~PixmapToPixmapFilter () [inline]`

25.198.3 Member Function Documentation

25.198.3.1 `Pixmap& gdcm::PixmapToPixmapFilter::GetInput ()`

25.198.3.2 `const Pixmap& gdcm::PixmapToPixmapFilter::GetOutput () const`

Get Output image.

25.198.3.3 `const Pixmap& gdcm::PixmapToPixmapFilter::GetOutputAsPixmap () const`

The documentation for this class was generated from the following file:


- [gdcmPixmapToPixmapFilter.h](#)

25.199 gdcm::PixmapWriter Class Reference


[PixmapWriter](#) This class will takes two inputs:

```
#include <gdcmPixmapWriter.h>
```

Inheritance diagram for `gdcm::PixmapWriter`:



Collaboration diagram for gdcm::PixmapWriter:



Public Member Functions

- [PixmapWriter](#) ()
- [~PixmapWriter](#) ()
- virtual const [Pixmap](#) & [GetImage](#) () const
- virtual [Pixmap](#) & [GetImage](#) ()
- const [Pixmap](#) & [GetPixmap](#) () const
- [Pixmap](#) & [GetPixmap](#) ()
- virtual void [SetImage](#) ([Pixmap](#) const &img)
- void [SetPixmap](#) ([Pixmap](#) const &img)
- bool [Write](#) ()

Write.

Protected Member Functions

- void [DolconImage](#) ([DataSet](#) &ds, [Pixmap](#) const &image)
- bool [PrepareWrite](#) ()

Protected Attributes

- [SmartPointer](#)< [Pixmap](#) > [PixelData](#)

25.199.1 Detailed Description

[PixmapWriter](#) This class will takes two inputs:

1. The DICOM [DataSet](#)
2. The [Image](#) input It will override any info from the [Image](#) over the [DataSet](#).

For instance when one read in a lossy compressed image and write out as unencapsulated (ie implicitly lossless) then some attribute are definitely needed to mark this dataset as Lossy (typically 0028,2114)

25.199.2 Constructor & Destructor Documentation

25.199.2.1 `gdcm::PixmapWriter::PixmapWriter ()`

25.199.2.2 `gdcm::PixmapWriter::~~PixmapWriter ()`

25.199.3 Member Function Documentation

25.199.3.1 `void gdcm::PixmapWriter::DolconImage (DataSet & ds, Pixmap const & image)` `[protected]`

25.199.3.2 `virtual const Pixmap& gdcm::PixmapWriter::GetImage () const` `[inline], [virtual]`

Set/Get [Pixmap](#) to be written It will overwrite anything [Pixmap](#) infos found in [DataSet](#) (see parent class to see how to pass dataset)

Reimplemented in [gdcm::ImageWriter](#).

25.199.3.3 `virtual Pixmap& gdcm::PixmapWriter::GetImage ()` `[inline], [virtual]`

Reimplemented in [gdcm::ImageWriter](#).

25.199.3.4 `const Pixmap& gdcm::PixmapWriter::GetPixmap () const` `[inline]`

25.199.3.5 `Pixmap& gdcm::PixmapWriter::GetPixmap ()` `[inline]`

25.199.3.6 `bool gdcm::PixmapWriter::PrepareWrite ()` `[protected]`

25.199.3.7 virtual void gdcm::PixmapWriter::SetImage (Pixmap const & *img*) [virtual]

Examples:

[CompressImage.cxx](#), [GenFakeImage.cxx](#), [GetSubSequenceData.cxx](#), [HelloVizWorld.cxx](#), and [MergeTwoFiles.cxx](#).

25.199.3.8 void gdcm::PixmapWriter::SetPixmap (Pixmap const & *img*)

25.199.3.9 bool gdcm::PixmapWriter::Write () [virtual]

Write.

Reimplemented from [gdcm::Writer](#).

25.199.4 Member Data Documentation

25.199.4.1 **SmartPointer<Pixmap>** gdcm::PixmapWriter::PixelData [protected]

The documentation for this class was generated from the following file:


- [gdcmPixmapWriter.h](#)

25.200 gdcm::PNMCodec Class Reference


Class to do PNM PNM is the Portable anymap file format. The main web page can be found at: <http://netpbm.sourceforge.net/>.

```
#include <gdcmPNMCodec.h>
```

Inheritance diagram for `gdcm::PNMCodec`:



Collaboration diagram for `gdcm::PNMCodec`:



Public Member Functions

- [PNMCodec](#) ()
- [~PNMCodec](#) ()
- bool [CanCode](#) ([TransferSyntax](#) const &ts) const
Return whether this coder support this transfer syntax (can code it)
- bool [CanDecode](#) ([TransferSyntax](#) const &ts) const
Return whether this decoder support this transfer syntax (can decode it)
- unsigned long [GetBufferLength](#) () const
- bool [GetHeaderInfo](#) (std::istream &is, [TransferSyntax](#) &ts)
- bool [Read](#) (const char *filename, [DataElement](#) &out) const
- void [SetBufferLength](#) (unsigned long l)
- bool [Write](#) (const char *filename, const [DataElement](#) &out) const

Additional Inherited Members

25.200.1 Detailed Description

Class to do PNM PNM is the Portable anymap file format. The main web page can be found at: <http://netpbm.sourceforge.net/>.

Note

Only support P5 & P6 PNM file (binary grayscale and binary rgb)

Examples:

[ExtractIconFromFile.cxx](#).

25.200.2 Constructor & Destructor Documentation

25.200.2.1 `gdcm::PNMCodec::PNMCodec ()`

25.200.2.2 `gdcm::PNMCodec::~~PNMCodec ()`

25.200.3 Member Function Documentation

25.200.3.1 `bool gdcm::PNMCodec::CanCode (TransferSyntax const &) const` [virtual]

Return whether this coder support this transfer syntax (can code it)

Reimplemented from [gdcm::ImageCodec](#).

25.200.3.2 `bool gdcm::PNMCodec::CanDecode (TransferSyntax const &) const` [virtual]

Return whether this decoder support this transfer syntax (can decode it)

Reimplemented from [gdcm::ImageCodec](#).

25.200.3.3 `unsigned long gdcm::PNMCodec::GetBufferLength () const` [inline]

25.200.3.4 `bool gdcm::PNMCodec::GetHeaderInfo (std::istream & is, TransferSyntax & ts)` [virtual]

Reimplemented from [gdcm::ImageCodec](#).

25.200.3.5 `bool gdcm::PNMCodec::Read (const char * filename, DataElement & out) const`

25.200.3.6 `void gdcm::PNMCodec::SetBufferLength (unsigned long l)` [inline]

25.200.3.7 `bool gdcm::PNMCodec::Write (const char * filename, const DataElement & out) const`

Examples:

[ExtractIconFromFile.cxx](#).

The documentation for this class was generated from the following file:

- [gdcmPNMCodec.h](#)

25.201 gdcm::Preamble Class Reference

DICOM [Preamble](#) (Part 10)

```
#include <gdcmPreamble.h>
```

Public Member Functions

- [Preamble](#) ()
- [Preamble](#) ([Preamble](#) const &)
- [~Preamble](#) ()
- void [Clear](#) ()
- void [Create](#) ()
- const char * [GetInternal](#) () const
- [VL GetLength](#) () const
- bool [IsEmpty](#) () const
- [Preamble](#) & [operator=](#) ([Preamble](#) const &)
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- void [Remove](#) ()
- void [Valid](#) ()
- std::ostream const & [Write](#) (std::ostream &os) const

Protected Member Functions

- bool [IsValid](#) () const

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [Preamble](#) &_val)

25.201.1 Detailed Description

DICOM [Preamble](#) (Part 10)

25.201.2 Constructor & Destructor Documentation

25.201.2.1 [gdcm::Preamble::Preamble](#) ()

25.201.2.2 [gdcm::Preamble::~~Preamble](#) ()

25.201.2.3 [gdcm::Preamble::Preamble](#) ([Preamble](#) const &) `[inline]`

25.201.3 Member Function Documentation

- 25.201.3.1 void gdcm::Preamble::Clear ()
- 25.201.3.2 void gdcm::Preamble::Create ()
- 25.201.3.3 const char* gdcm::Preamble::GetInternal () const [inline]
- 25.201.3.4 VL gdcm::Preamble::GetLength () const [inline]
- 25.201.3.5 bool gdcm::Preamble::IsEmpty () const [inline]
- 25.201.3.6 bool gdcm::Preamble::IsValid () const [inline],[protected]
- 25.201.3.7 Preamble& gdcm::Preamble::operator= (Preamble const &) [inline]
- 25.201.3.8 void gdcm::Preamble::Print (std::ostream & os) const
- 25.201.3.9 std::istream& gdcm::Preamble::Read (std::istream & is)
- 25.201.3.10 void gdcm::Preamble::Remove ()
- 25.201.3.11 void gdcm::Preamble::Valid ()
- 25.201.3.12 std::ostream const& gdcm::Preamble::Write (std::ostream & os) const

25.201.4 Friends And Related Function Documentation

- 25.201.4.1 std::ostream& operator<< (std::ostream &_os, const Preamble &_val) [friend]

The documentation for this class was generated from the following file:

- [gdcmPreamble.h](#)

25.202 gdcm::PresentationContext Class Reference

[PresentationContext](#).

```
#include <gdcmPresentationContext.h>
```

Public Types

- typedef
TransferSyntaxArrayType::size_type [SizeType](#)
- typedef std::vector< std::string > [TransferSyntaxArrayType](#)

Public Member Functions

- [PresentationContext](#) ()
- [PresentationContext](#) (UIDs::TSName asname, UIDs::TSName tsname=UIDs::ImplicitVRLittleEndianDefault-TransferSyntaxforDICOM)
- void [AddTransferSyntax](#) (const char *tsstr)

- `const char * GetAbstractSyntax () const`
- `SizeType GetNumberOfTransferSyntaxes () const`
- `uint8_t GetPresentationContextID () const`
- `const char * GetTransferSyntax (SizeType i) const`
- `bool operator== (const PresentationContext &pc) const`
- `void Print (std::ostream &os) const`
- `void SetAbstractSyntax (const char *as)`
- `void SetPresentationContextID (uint8_t id)`

25.202.1 Detailed Description

[PresentationContext](#).

See Also

[PresentationContextAC](#) [PresentationContextRQ](#)

25.202.2 Member Typedef Documentation

25.202.2.1 `typedef TransferSyntaxArrayType::size_type gdcm::PresentationContext::SizeType`

25.202.2.2 `typedef std::vector<std::string> gdcm::PresentationContext::TransferSyntaxArrayType`

25.202.3 Constructor & Destructor Documentation

25.202.3.1 `gdcm::PresentationContext::PresentationContext ()`

25.202.3.2 `gdcm::PresentationContext::PresentationContext (UIDs::TSName asname, UIDs::TSName tsname = UIDs::ImplicitVRLittleEndianDefaultTransferSyntaxforDICOM)`

Initialize Presentation Context with AbstractSyntax set to asname and with a single [TransferSyntax](#) set to tsname (default to Implicit [VR](#) LittleEndian when not specified).

25.202.4 Member Function Documentation

25.202.4.1 `void gdcm::PresentationContext::AddTransferSyntax (const char * tsstr)`

25.202.4.2 `const char* gdcm::PresentationContext::GetAbstractSyntax () const` `[inline]`

25.202.4.3 `SizeType gdcm::PresentationContext::GetNumberOfTransferSyntaxes () const` `[inline]`

25.202.4.4 `uint8_t gdcm::PresentationContext::GetPresentationContextID () const`

25.202.4.5 `const char* gdcm::PresentationContext::GetTransferSyntax (SizeType i) const` `[inline]`

25.202.4.6 `bool gdcm::PresentationContext::operator== (const PresentationContext & pc) const` `[inline]`

25.202.4.7 `void gdcm::PresentationContext::Print (std::ostream & os) const`

25.202.4.8 `void gdcm::PresentationContext::SetAbstractSyntax (const char * as)` `[inline]`

25.202.4.9 void gdcm::PresentationContext::SetPresentationContextID (uint8_t id)

The documentation for this class was generated from the following file:

- [gdcmPresentationContext.h](#)

25.203 gdcm::network::PresentationContextAC Class Reference

[PresentationContextAC Table](#) 9-18 PRESENTATION CONTEXT ITEM FIELDS.

```
#include <gdcmPresentationContextAC.h>
```

Public Member Functions

- [PresentationContextAC](#) ()
- uint8_t [GetPresentationContextID](#) () const
- uint8_t [GetReason](#) () const
- [TransferSyntaxSub](#) const & [GetTransferSyntax](#) () const
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- void [SetPresentationContextID](#) (uint8_t id)
- void [SetReason](#) (uint8_t r)
- void [SetTransferSyntax](#) ([TransferSyntaxSub](#) const &ts)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.203.1 Detailed Description

[PresentationContextAC Table](#) 9-18 PRESENTATION CONTEXT ITEM FIELDS.

See Also

[PresentationContext](#)

25.203.2 Constructor & Destructor Documentation

25.203.2.1 gdcm::network::PresentationContextAC::PresentationContextAC ()

25.203.3 Member Function Documentation

25.203.3.1 uint8_t gdcm::network::PresentationContextAC::GetPresentationContextID () const [inline]

25.203.3.2 uint8_t gdcm::network::PresentationContextAC::GetReason () const [inline]

25.203.3.3 [TransferSyntaxSub](#) const& gdcm::network::PresentationContextAC::GetTransferSyntax () const [inline]

25.203.3.4 void gdcm::network::PresentationContextAC::Print (std::ostream & os) const

25.203.3.5 std::istream& gdcm::network::PresentationContextAC::Read (std::istream & is)

- 25.203.3.6 void gdcmm::network::PresentationContextAC::SetPresentationContextID (uint8_t id)
- 25.203.3.7 void gdcmm::network::PresentationContextAC::SetReason (uint8_t r) [inline]
- 25.203.3.8 void gdcmm::network::PresentationContextAC::SetTransferSyntax (TransferSyntaxSub const & ts)
- 25.203.3.9 size_t gdcmm::network::PresentationContextAC::Size () const
- 25.203.3.10 const std::ostream& gdcmm::network::PresentationContextAC::Write (std::ostream & os) const

The documentation for this class was generated from the following file:

- [gdcmmPresentationContextAC.h](#)

25.204 gdcmm::PresentationContextGenerator Class Reference

[PresentationContextGenerator](#) This class is responsible for generating the proper [PresentationContext](#) that will be used in subsequent operation during a DICOM Query/Retrieve association. The step of the association is very sensible as special care need to be taken to explicitly define what instance are going to be send and how they are encoded.

```
#include <gdcmmPresentationContextGenerator.h>
```

Public Types

- typedef std::vector
 < [PresentationContext](#) > [PresentationContextArrayType](#)
- typedef
 PresentationContextArrayType::size_type [SizeType](#)

Public Member Functions

- [PresentationContextGenerator](#) ()
- bool [GenerateFromFilenames](#) (const [Directory::FilenamesType](#) &files)
- bool [GenerateFromUID](#) ([UIDs::TSName](#) asname)
 Generate the [PresentationContext](#) array from a UID (eg. VerificationSOPClass)
- [PresentationContextArrayType](#)
 const & [GetPresentationContexts](#) ()
- void [SetDefaultTransferSyntax](#) (const [TransferSyntax](#) &ts)
 Not implemented for now. GDCM internally uses Implicit Little Endian.
- void [SetMergeModeToAbstractSyntax](#) ()
- void [SetMergeModeToTransferSyntax](#) ()

Protected Member Functions

- bool [AddPresentationContext](#) (const char *as, const char *ts)
- const char * [GetDefaultTransferSyntax](#) () const

25.204.1 Detailed Description

[PresentationContextGenerator](#) This class is responsible for generating the proper [PresentationContext](#) that will be used in subsequent operation during a DICOM Query/Retrieve association. The step of the association is very sensible as special care need to be taken to explicitly define what instance are going to be send and how they are encoded.

For example a [PresentationContext](#) will express that negotiation requires that CT [Image](#) Storage are send using JPEG Lossless, while US [Image](#) Storage are sent using RLE Transfer Syntax.

Two very different API are exposed one which will always default to little endian transfer syntax see [GenerateFromUID\(\)](#) This API is used for C-ECHO, C-FIND and C-MOVE (SCU). Another API: [GenerateFromFileNames\(\)](#) is used for C-STORE (SCU) as it will loop over all filenames argument to detect the actual encoding. and therefore find the proper encoding to be used.

Two modes are available. The default mode (SetMergeModeToAbstractSyntax) append [PresentationContext](#) (one AbstractSyntax and one [TransferSyntax](#)), as long a they are different. Eg MR [Image](#) Storage/JPEG2000 and MR [Image](#) Storage/JPEGLossless would be considered different. the other mode SetMergeModeToTransferSyntax merge any new [TransferSyntax](#) to the already existing [PresentationContext](#) in order to re-use the same AbstractSyntax.

See Also

[PresentationContext](#)

Examples:

[CStoreQtProgress.cxx](#).

25.204.2 Member Typedef Documentation

25.204.2.1 `typedef std::vector<PresentationContext> gdcmm::PresentationContextGenerator::PresentationContextArrayType`

25.204.2.2 `typedef PresentationContextArrayType::size_type gdcmm::PresentationContextGenerator::SizeType`

25.204.3 Constructor & Destructor Documentation

25.204.3.1 `gdcmm::PresentationContextGenerator::PresentationContextGenerator ()`

25.204.4 Member Function Documentation

25.204.4.1 `bool gdcmm::PresentationContextGenerator::AddPresentationContext (const char * as, const char * ts)`
[protected]

25.204.4.2 `bool gdcmm::PresentationContextGenerator::GenerateFromFileNames (const Directory::FileNamesType & files)`

Generate the [PresentationContext](#) array from a File-Set. [File](#) specified needs to be valid DICOM files. Used for C-STORE operations

Examples:

[CStoreQtProgress.cxx](#).

25.204.4.3 `bool gdcmm::PresentationContextGenerator::GenerateFromUID (UIDs::TSName asname)`

Generate the [PresentationContext](#) array from a UID (eg. VerificationSOPClass)

25.204.4.4 `const char* gdcm::PresentationContextGenerator::GetDefaultTransferSyntax () const` [protected]

25.204.4.5 `PresentationContextArrayType const& gdcm::PresentationContextGenerator::GetPresentationContexts ()`
[inline]

Examples:

[CStoreQtProgress.cxx](#).

25.204.4.6 `void gdcm::PresentationContextGenerator::SetDefaultTransferSyntax (const TransferSyntax & ts)`

Not implemented for now. GDCM internally uses Implicit Little Endian.

25.204.4.7 `void gdcm::PresentationContextGenerator::SetMergeModeToAbstractSyntax ()`

25.204.4.8 `void gdcm::PresentationContextGenerator::SetMergeModeToTransferSyntax ()`

The documentation for this class was generated from the following file:

- [gdcmPresentationContextGenerator.h](#)

25.205 gdcm::network::PresentationContextRQ Class Reference

[PresentationContextRQ](#) Table 9-13 PRESENTATION CONTEXT ITEM FIELDS.

```
#include <gdcmPresentationContextRQ.h>
```

Public Types

- typedef std::vector
 < [TransferSyntaxSub](#) >
 ::size_type [SizeType](#)

Public Member Functions

- [PresentationContextRQ](#) ()
- [PresentationContextRQ](#) (UIDs::TSName asname, UIDs::TSName tsname=UIDs::ImplicitVRLittleEndianDefaultTransferSyntaxforDICOM)
- [PresentationContextRQ](#) (const [PresentationContext](#) &pc)
- void [AddTransferSyntax](#) ([TransferSyntaxSub](#) const &ts)
- [AbstractSyntax](#) const & [GetAbstractSyntax](#) () const
- [AbstractSyntax](#) & [GetAbstractSyntax](#) ()
- [SizeType](#) [GetNumberOfTransferSyntaxes](#) () const
- uint8_t [GetPresentationContextID](#) () const
- [TransferSyntaxSub](#) const & [GetTransferSyntax](#) ([SizeType](#) i) const
- [TransferSyntaxSub](#) & [GetTransferSyntax](#) ([SizeType](#) i)
- std::vector< [TransferSyntaxSub](#) >
 const & [GetTransferSyntaxes](#) () const
- bool [operator==](#) (const [PresentationContextRQ](#) &pc) const

- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- void [SetAbstractSyntax](#) ([AbstractSyntax](#) const &as)
- void [SetPresentationContextID](#) (uint8_t id)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.205.1 Detailed Description

[PresentationContextRQ](#) Table 9-13 PRESENTATION CONTEXT ITEM FIELDS.

See Also

[PresentationContextAC](#)

25.205.2 Member Typedef Documentation

25.205.2.1 `typedef std::vector<TransferSyntaxSub>::size_type gdcm::network::PresentationContextRQ::SizeType`

25.205.3 Constructor & Destructor Documentation

25.205.3.1 `gdcm::network::PresentationContextRQ::PresentationContextRQ ()`

25.205.3.2 `gdcm::network::PresentationContextRQ::PresentationContextRQ (UIDs::TSName asname, UIDs::TSName tsname = UIDs::ImplicitVRLittleEndianDefaultTransferSyntaxforDICOM)`

Initialize Presentation Context with [AbstractSyntax](#) set to *asname* and with a single [TransferSyntax](#) set to *tsname* (default to Implicit [VR](#) LittleEndian when not specified).

25.205.3.3 `gdcm::network::PresentationContextRQ::PresentationContextRQ (const PresentationContext & pc)`

25.205.4 Member Function Documentation

25.205.4.1 `void gdcm::network::PresentationContextRQ::AddTransferSyntax (TransferSyntaxSub const & ts)`

25.205.4.2 `AbstractSyntax const& gdcm::network::PresentationContextRQ::GetAbstractSyntax () const` `[inline]`

25.205.4.3 `AbstractSyntax& gdcm::network::PresentationContextRQ::GetAbstractSyntax ()` `[inline]`

25.205.4.4 `SizeType gdcm::network::PresentationContextRQ::GetNumberOfTransferSyntaxes () const` `[inline]`

25.205.4.5 `uint8_t gdcm::network::PresentationContextRQ::GetPresentationContextID () const`

25.205.4.6 `TransferSyntaxSub const& gdcm::network::PresentationContextRQ::GetTransferSyntax (SizeType i) const` `[inline]`

25.205.4.7 `TransferSyntaxSub& gdcm::network::PresentationContextRQ::GetTransferSyntax (SizeType i)` `[inline]`

25.205.4.8 `std::vector<TransferSyntaxSub> const& gdcm::network::PresentationContextRQ::GetTransferSyntaxes () const` `[inline]`

```

25.205.4.9  bool gdcmm::network::PresentationContextRQ::operator== ( const PresentationContextRQ & pc ) const
            [inline]

25.205.4.10 void gdcmm::network::PresentationContextRQ::Print ( std::ostream & os ) const

25.205.4.11 std::istream& gdcmm::network::PresentationContextRQ::Read ( std::istream & is )

25.205.4.12 void gdcmm::network::PresentationContextRQ::SetAbstractSyntax ( AbstractSyntax const & as )

25.205.4.13 void gdcmm::network::PresentationContextRQ::SetPresentationContextID ( uint8_t id )

25.205.4.14 size_t gdcmm::network::PresentationContextRQ::Size ( ) const

25.205.4.15 const std::ostream& gdcmm::network::PresentationContextRQ::Write ( std::ostream & os ) const

```

The documentation for this class was generated from the following file:

- [gdcmmPresentationContextRQ.h](#)

25.206 gdcmm::network::PresentationDataValue Class Reference

[PresentationDataValue Table](#) 9-23 PRESENTATION-DATA-VALUE ITEM FIELDS.

```
#include <gdcmmPresentationDataValue.h>
```

Public Member Functions

- [PresentationDataValue](#) ()
- const std::string & [GetBlob](#) () const
- bool [GetIsCommand](#) () const
- bool [GetIsLastFragment](#) () const
- uint8_t [GetMessageHeader](#) () const
- uint8_t [GetPresentationContextID](#) () const
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- std::istream & [ReadInto](#) (std::istream &is, std::ostream &os)
- void [SetBlob](#) (const std::string &partialblob)
- void [SetCommand](#) (bool inCommand)
- void [SetDataSet](#) (const [DataSet](#) &ds)
- void [SetLastFragment](#) (bool inLast)
- void [SetMessageHeader](#) (uint8_t messageheader)
- void [SetPresentationContextID](#) (uint8_t id)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

Static Public Member Functions

- static [DataSet](#) [ConcatenatePDVBlobs](#) (const std::vector< [PresentationDataValue](#) > &inPDVs)

25.206.1 Detailed Description

[PresentationDataValue Table](#) 9-23 PRESENTATION-DATA-VALUE ITEM FIELDS.

25.206.2 Constructor & Destructor Documentation

25.206.2.1 `gdcm::network::PresentationDataValue::PresentationDataValue ()`

25.206.3 Member Function Documentation

25.206.3.1 `static DataSet gdcm::network::PresentationDataValue::ConcatenatePDVBlobs (const std::vector< PresentationDataValue > & inPDVs) [static]`

Warning

[DataSet](#) will be read as Implicit Little Endian TS

25.206.3.2 `const std::string& gdcm::network::PresentationDataValue::GetBlob () const`

25.206.3.3 `bool gdcm::network::PresentationDataValue::GetIsCommand () const`

25.206.3.4 `bool gdcm::network::PresentationDataValue::GetIsLastFragment () const`

25.206.3.5 `uint8_t gdcm::network::PresentationDataValue::GetMessageHeader () const [inline]`

25.206.3.6 `uint8_t gdcm::network::PresentationDataValue::GetPresentationContextID () const [inline]`

25.206.3.7 `void gdcm::network::PresentationDataValue::Print (std::ostream & os) const`

25.206.3.8 `std::istream& gdcm::network::PresentationDataValue::Read (std::istream & is)`

25.206.3.9 `std::istream& gdcm::network::PresentationDataValue::ReadInto (std::istream & is, std::ostream & os)`

25.206.3.10 `void gdcm::network::PresentationDataValue::SetBlob (const std::string & partialblob)`

25.206.3.11 `void gdcm::network::PresentationDataValue::SetCommand (bool inCommand)`

25.206.3.12 `void gdcm::network::PresentationDataValue::SetDataSet (const DataSet & ds)`

Set [DataSet](#). Write [DataSet](#) in implicit.

Warning

size of dataset should be below maxpdusize

25.206.3.13 `void gdcm::network::PresentationDataValue::SetLastFragment (bool inLast)`

25.206.3.14 `void gdcm::network::PresentationDataValue::SetMessageHeader (uint8_t messageheader) [inline]`

25.206.3.15 `void gdcmm::network::PresentationDataValue::SetPresentationContextID (uint8_t id) [inline]`

25.206.3.16 `size_t gdcmm::network::PresentationDataValue::Size () const`

25.206.3.17 `const std::ostream& gdcmm::network::PresentationDataValue::Write (std::ostream & os) const`

The documentation for this class was generated from the following file:


- [gdcmmPresentationDataValue.h](#)

25.207 gdcmm::Printer Class Reference


[Printer](#) class.

```
#include <gdcmmPrinter.h>
```

Inheritance diagram for gdcmm::Printer:



Collaboration diagram for gdcmm::Printer:



Public Types

- enum `PrintStyles` {
`VERBOSE_STYLE = 0`,
`CONDENSED_STYLE`,
`XML` }

Public Member Functions

- `Printer()`
- `~Printer()`
- `PrintStyles GetPrintStyle() const`
Get PrintStyle value.
- `void Print(std::ostream &os)`
Print.
- `void PrintDataSet(const DataSet &ds, std::ostream &os, const std::string &s="")`
Print an individual dataset.
- `void SetColor(bool c)`
Set color mode or not.
- `void SetFile(File const &f)`
Set file.
- `void SetStyle(PrintStyles ps)`
Set PrintStyle value.

Protected Member Functions

- [VR PrintDataElement](#) (std::ostream &os, const [Dicts](#) &dicts, const [DataSet](#) &ds, const [DataElement](#) &de, std::ostream &out, std::string const &indent)
- void [PrintSQ](#) (const [SequenceOfItems](#) *sqi, std::ostream &os, std::string const &indent)

Protected Attributes

- const [File](#) * F
- [VL MaxPrintLength](#)
- [PrintStyles](#) PrintStyle

25.207.1 Detailed Description

[Printer](#) class.

25.207.2 Member Enumeration Documentation

25.207.2.1 enum gdcm::Printer::PrintStyles

Enumerator

VERBOSE_STYLE
CONDENSED_STYLE
XML

25.207.3 Constructor & Destructor Documentation

25.207.3.1 gdcm::Printer::Printer ()

25.207.3.2 gdcm::Printer::~~Printer ()

25.207.4 Member Function Documentation

25.207.4.1 [PrintStyles](#) gdcm::Printer::GetPrintStyle () const [inline]

Get PrintStyle value.

25.207.4.2 void gdcm::Printer::Print (std::ostream & os)

Print.

25.207.4.3 VR gdcm::Printer::PrintDataElement (std::ostream & os, const [Dicts](#) & *dicts*, const [DataSet](#) & *ds*, const [DataElement](#) & *de*, std::ostream & *out*, std::string const & *indent*) [protected]

25.207.4.4 void gdcm::Printer::PrintDataSet (const [DataSet](#) & *ds*, std::ostream & *os*, const std::string & *s* = " ")

Print an individual dataset.

25.207.4.5 void gdcm::Printer::PrintSQ (const SequenceOfItems * *sqi*, std::ostream & *os*, std::string const & *indent*)
[protected]

25.207.4.6 void gdcm::Printer::SetColor (bool *c*)

Set color mode or not.

25.207.4.7 void gdcm::Printer::SetFile (File const & *f*) [inline]

Set file.

25.207.4.8 void gdcm::Printer::SetStyle (PrintStyles *ps*) [inline]

Set PrintStyle value.

25.207.5 Member Data Documentation

25.207.5.1 const File* gdcm::Printer::F [protected]

25.207.5.2 VL gdcm::Printer::MaxPrintLength [protected]

25.207.5.3 PrintStyles gdcm::Printer::PrintStyle [protected]

The documentation for this class was generated from the following file:

- [gdcmPrinter.h](#)

25.208 gdcm::PrivateDict Class Reference

Private [Dict](#).

```
#include <gdcmDict.h>
```

Public Member Functions

- [PrivateDict](#) ()
- [~PrivateDict](#) ()
- void [AddDictEntry](#) (const [PrivateTag](#) &tag, const [DictEntry](#) &de)
- bool [FindDictEntry](#) (const [PrivateTag](#) &tag) const
- const [DictEntry](#) & [GetDictEntry](#) (const [PrivateTag](#) &tag) const
- bool [IsEmpty](#) () const
- void [PrintXML](#) () const
- bool [RemoveDictEntry](#) (const [PrivateTag](#) &tag)

Protected Member Functions

- void [LoadDefault](#) ()

Friends

- class [Dicts](#)
- `std::ostream & operator<< (std::ostream &os, const PrivateDict &val)`

25.208.1 Detailed Description

Private [Dict](#).

25.208.2 Constructor & Destructor Documentation

25.208.2.1 `gdcm::PrivateDict::PrivateDict ()` `[inline]`

25.208.2.2 `gdcm::PrivateDict::~~PrivateDict ()` `[inline]`

25.208.3 Member Function Documentation

25.208.3.1 `void gdcm::PrivateDict::AddDictEntry (const PrivateTag &tag, const DictEntry &de)` `[inline]`

References `gdcm::DictEntry::GetVM()`, `gdcm::DictEntry::GetVR()`, `gdcm::DictEntry::SetVR()`, and `gdcm::VR::UN`.

25.208.3.2 `bool gdcm::PrivateDict::FindDictEntry (const PrivateTag &tag) const` `[inline]`

25.208.3.3 `const DictEntry& gdcm::PrivateDict::GetDictEntry (const PrivateTag &tag) const` `[inline]`

25.208.3.4 `bool gdcm::PrivateDict::IsEmpty () const` `[inline]`

25.208.3.5 `void gdcm::PrivateDict::LoadDefault ()` `[protected]`

25.208.3.6 `void gdcm::PrivateDict::PrintXML () const` `[inline]`

References `gdcm::Tag::GetElement()`, `gdcm::Tag::GetGroup()`, `gdcm::DictEntry::GetName()`, `gdcm::PrivateTag::GetOwner()`, `gdcm::DictEntry::GetVM()`, and `gdcm::DictEntry::GetVR()`.

25.208.3.7 `bool gdcm::PrivateDict::RemoveDictEntry (const PrivateTag &tag)` `[inline]`

Remove entry 'tag'. Return true on success (element was found and remove). return false if element was not found.

25.208.4 Friends And Related Function Documentation

25.208.4.1 `friend class Dicts` `[friend]`

25.208.4.2 `std::ostream& operator<< (std::ostream &os, const PrivateDict &val)` `[friend]`

The documentation for this class was generated from the following file:


- [gdcmDict.h](#)

25.209 gdcm::PrivateTag Class Reference


Class to represent a Private DICOM Data [Element](#) ([Attribute](#)) [Tag](#) (Group, [Element](#), Owner)

```
#include <gdcmPrivateTag.h>
```

Inheritance diagram for gdcm::PrivateTag:



Collaboration diagram for gdcm::PrivateTag:



Public Member Functions

- [PrivateTag](#) (uint16_t group=0, uint16_t element=0, const char *owner="")
- const char * [GetOwner](#) () const
- bool [operator<](#) (const [PrivateTag](#) &_val) const
- bool [ReadFromCommaSeparatedString](#) (const char *str)
- void [SetOwner](#) (const char *owner)

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [PrivateTag](#) &_val)

25.209.1 Detailed Description

Class to represent a Private DICOM Data [Element](#) ([Attribute](#)) [Tag](#) (Group, [Element](#), Owner)

Note

private tag have element value in: [0x10,0xff], for instance 0x0009,0x0000 is NOT a private tag

Examples:

[csa2img.cxx](#), [DumpADAC.cxx](#), [DumpGEMSMovieGroup.cxx](#), [DumpImageHeaderInfo.cxx](#), [ELSCINT1WaveToText.cxx](#), [GetSubSequenceData.cxx](#), [iU22tomultisc.cxx](#), [MrProtocol.cxx](#), [pmsct_rgb1.cxx](#), [PublicDict.cxx](#), [ReadGEMSS-DO.cxx](#), and [rle2img.cxx](#).

25.209.2 Constructor & Destructor Documentation

25.209.2.1 `gdcm::PrivateTag::PrivateTag (uint16_t group = 0, uint16_t element = 0, const char * owner = " ") [inline]`

25.209.3 Member Function Documentation

25.209.3.1 `const char* gdcm::PrivateTag::GetOwner () const [inline]`

Examples:

[PublicDict.cxx](#).

Referenced by `gdcm::PrivateDict::PrintXML()`.

25.209.3.2 `bool gdcm::PrivateTag::operator< (const PrivateTag & _val) const`

25.209.3.3 `bool gdcm::PrivateTag::ReadFromCommaSeparatedString (const char * str)`

Read [PrivateTag](#) from a string. [Element](#) number will be truncated to 8bits. Eg: "1234,5678,GDCM" is private tag: (1234,78,"GDCM")

25.209.3.4 `void gdcm::PrivateTag::SetOwner (const char * owner) [inline]`

25.209.4 Friends And Related Function Documentation

25.209.4.1 `std::ostream& operator<< (std::ostream & _os, const PrivateTag & _val) [friend]`

The documentation for this class was generated from the following file:


- [gdcmPrivateTag.h](#)

25.210 gdcm::ProgressEvent Class Reference


[ProgressEvent](#) Special type of event triggered during.

```
#include <gdcmProgressEvent.h>
```

Inheritance diagram for gdcm::ProgressEvent:



Collaboration diagram for gdcm::ProgressEvent:



Public Types

- typedef [ProgressEvent](#) Self
- typedef [AnyEvent](#) Superclass

Public Member Functions

- [ProgressEvent](#) (double p=0)

- [ProgressEvent](#) (const [Self](#) &s)
- virtual [~ProgressEvent](#) ()
- virtual bool [CheckEvent](#) (const [::gdcm::Event](#) *e) const
- virtual const char * [GetEventName](#) () const
- double [GetProgress](#) () const
- virtual [::gdcm::Event](#) * [MakeObject](#) () const
- void [SetProgress](#) (double p)

25.210.1 Detailed Description

[ProgressEvent](#) Special type of event triggered during.

See Also

[AnyEvent](#)

25.210.2 Member Typedef Documentation

25.210.2.1 `typedef ProgressEvent gdcm::ProgressEvent::Self`

25.210.2.2 `typedef AnyEvent gdcm::ProgressEvent::Superclass`

25.210.3 Constructor & Destructor Documentation

25.210.3.1 `gdcm::ProgressEvent::ProgressEvent (double p = 0) [inline]`

25.210.3.2 `virtual gdcm::ProgressEvent::~~ProgressEvent () [inline],[virtual]`

25.210.3.3 `gdcm::ProgressEvent::ProgressEvent (const Self & s) [inline]`

25.210.4 Member Function Documentation

25.210.4.1 `virtual bool gdcm::ProgressEvent::CheckEvent (const ::gdcm::Event * e) const [inline],[virtual]`

25.210.4.2 `virtual const char* gdcm::ProgressEvent::GetEventName () const [inline],[virtual]`

Return the StringName associated with the event.

Implements [gdcm::Event](#).

25.210.4.3 `double gdcm::ProgressEvent::GetProgress () const [inline]`

25.210.4.4 `virtual ::gdcm::Event* gdcm::ProgressEvent::MakeObject () const [inline],[virtual]`

Create an [Event](#) of this type This method work as a Factory for creating events of each particular type.

Implements [gdcm::Event](#).

25.210.4.5 `void gdcm::ProgressEvent::SetProgress (double p) [inline]`

The documentation for this class was generated from the following file:


- [gdcmProgressEvent.h](#)

25.211 gdcm::PVRGCodec Class Reference


[PVRGCodec](#).

```
#include <gdcmPVRGCodec.h>
```

Inheritance diagram for gdcm::PVRGCodec:



Collaboration diagram for gdcm::PVRGCodec:



Public Member Functions

- [PVRGCodec\(\)](#)
- [~PVRGCodec\(\)](#)

- bool [CanCode](#) ([TransferSyntax](#) const &ts) const
Return whether this coder support this transfer syntax (can code it)
- bool [CanDecode](#) ([TransferSyntax](#) const &ts) const
Return whether this decoder support this transfer syntax (can decode it)
- bool [Code](#) ([DataElement](#) const &in, [DataElement](#) &out)
Code.
- bool [Decode](#) ([DataElement](#) const &is, [DataElement](#) &os)
Decode.

Additional Inherited Members

25.211.1 Detailed Description

[PVRGCodec](#).

Note

pvr is a broken implementation of the JPEG standard. It is known to have a bug in the 16bits lossless implementation of the standard.

In an ideal world, you should not need this codec at all. But to support some broken file such as:

PHILIPS_Gyrosan-12-Jpeg_Extended_Process_2_4.dcm

we have to...

25.211.2 Constructor & Destructor Documentation

25.211.2.1 `gdcm::PVRGCodec::PVRGCodec ()`

25.211.2.2 `gdcm::PVRGCodec::~~PVRGCodec ()`

25.211.3 Member Function Documentation

25.211.3.1 `bool gdcm::PVRGCodec::CanCode (TransferSyntax const &) const` `[virtual]`

Return whether this coder support this transfer syntax (can code it)

Reimplemented from [gdcm::ImageCodec](#).

25.211.3.2 `bool gdcm::PVRGCodec::CanDecode (TransferSyntax const &) const` `[virtual]`

Return whether this decoder support this transfer syntax (can decode it)

Reimplemented from [gdcm::ImageCodec](#).

25.211.3.3 `bool gdcm::PVRGCodec::Code (DataElement const & in_, DataElement & out_)` `[virtual]`

Code.

Reimplemented from [gdcm::Coder](#).

25.211.3.4 `bool gdcm::PVRGCodec::Decode (DataElement const & , DataElement &) [virtual]`

Decode.

Reimplemented from [gdcm::ImageCodec](#).

The documentation for this class was generated from the following file:

- [gdcmPVRGCodec.h](#)

25.212 gdcm::PythonFilter Class Reference

[PythonFilter](#) [PythonFilter](#) is the class that make gdcm2.x looks more like gdcm1 and transform the binary blob contained in a [DataElement](#) into a string, typically this is a nice feature to have for wrapped language.

```
#include <gdcmPythonFilter.h>
```

Public Member Functions

- [PythonFilter](#) ()
- [~PythonFilter](#) ()
- [File](#) & [GetFile](#) ()
- const [File](#) & [GetFile](#) () const
- void [SetDicts](#) (const [Dicts](#) &dicts)
- void [SetFile](#) (const [File](#) &f)
- PyObject * [ToPyObject](#) (const [Tag](#) &t) const
- void [UseDictAlways](#) (bool use)

25.212.1 Detailed Description

[PythonFilter](#) [PythonFilter](#) is the class that make gdcm2.x looks more like gdcm1 and transform the binary blob contained in a [DataElement](#) into a string, typically this is a nice feature to have for wrapped language.

25.212.2 Constructor & Destructor Documentation

25.212.2.1 `gdcm::PythonFilter::PythonFilter ()`

25.212.2.2 `gdcm::PythonFilter::~~PythonFilter ()`

25.212.3 Member Function Documentation

25.212.3.1 `File& gdcm::PythonFilter::GetFile () [inline]`

25.212.3.2 `const File& gdcm::PythonFilter::GetFile () const [inline]`

25.212.3.3 `void gdcm::PythonFilter::SetDicts (const Dicts &dicts)`

25.212.3.4 `void gdcm::PythonFilter::SetFile (const File &f) [inline]`

25.212.3.5 `PyObject* gdcm::PythonFilter::ToPyObject (const Tag &t) const`

25.212.3.6 void `gdcm::PythonFilter::UseDictAlways` (bool *use*) [inline]

The documentation for this class was generated from the following file:


- [gdcmPythonFilter.h](#)

25.213 gdcm::QueryBase Class Reference

[QueryBase](#) contains: the base class for constructing a query dataset for a C-FIND and a C-MOVE.

```
#include <gdcmQueryBase.h>
```

Inheritance diagram for `gdcm::QueryBase`:



Public Member Functions

- virtual [~QueryBase](#) ()
- std::vector< [Tag](#) > [GetAllRequiredTags](#) (const [ERootType](#) &inRootType) const
- std::vector< [Tag](#) > [GetAllTags](#) (const [ERootType](#) &inRootType) const
- virtual std::vector< [Tag](#) > [GetHierachicalSearchTags](#) (const [ERootType](#) &inRootType) const =0
Return all Unique Key for a particular Query Root type (from the same level and above).
- virtual const char * [GetName](#) () const =0
- virtual std::vector< [Tag](#) > [GetOptionalTags](#) (const [ERootType](#) &inRootType) const =0
- virtual [DataElement](#) [GetQueryLevel](#) () const =0
- virtual std::vector< [Tag](#) > [GetRequiredTags](#) (const [ERootType](#) &inRootType) const =0
- virtual std::vector< [Tag](#) > [GetUniqueTags](#) (const [ERootType](#) &inRootType) const =0

25.213.1 Detailed Description

[QueryBase](#) contains: the base class for constructing a query dataset for a C-FIND and a C-MOVE.

There are four levels of C-FIND and C-MOVE query:

- [Patient](#)
- [Study](#)
- [Series](#)
- [Image](#)

Each one has its own required and optional tags. This class provides an interface for getting those tags. This is an interface class.

See 3.4 C 6.1 and 3.4 C 6.2 for the patient and study root query types. These sections define the tags allowed by a particular query. The caller must pass in which root type they want, patient or study. A third root type, Modality Worklist Query, isn't yet supported.

This class (or rather it's derived classes) will be held in the RootQuery types. These query types actually make the dataset, and will use this dataset to list the required, unique, and optional tags for each type of query. This design is somewhat overly complicated, but is kept so that if we ever wanted to try to guess the query type from the given tags, we could do so.

25.213.2 Constructor & Destructor Documentation

25.213.2.1 `virtual gdcm::QueryBase::~QueryBase () [inline],[virtual]`

25.213.3 Member Function Documentation

25.213.3.1 `std::vector<Tag> gdcm::QueryBase::GetAllRequiredTags (const ERootType & inRootType) const`

In order to validate a query dataset we need to check that there exists at least one required (or unique) key

25.213.3.2 `std::vector<Tag> gdcm::QueryBase::GetAllTags (const ERootType & inRootType) const`

In order to validate a query dataset, just check for the presence of a tag, not it's requirement level in the spec

25.213.3.3 `virtual std::vector<Tag> gdcm::QueryBase::GetHierachicalSearchTags (const ERootType & inRootType) const [pure virtual]`

Return all Unique Key for a particular Query Root type (from the same level and above).

Implemented in [gdcm::QueryImage](#), [gdcm::QueryPatient](#), [gdcm::QuerySeries](#), and [gdcm::QueryStudy](#).

25.213.3.4 `virtual const char* gdcm::QueryBase::GetName () const [pure virtual]`

Implemented in [gdcm::QueryImage](#), [gdcm::QueryPatient](#), [gdcm::QuerySeries](#), and [gdcm::QueryStudy](#).

25.213.3.5 `virtual std::vector<Tag> gdcm::QueryBase::GetOptionalTags (const ERootType & inRootType) const [pure virtual]`

Implemented in [gdcm::QueryImage](#), [gdcm::QueryPatient](#), [gdcm::QuerySeries](#), and [gdcm::QueryStudy](#).

25.213.3.6 `virtual DataElement gdcm::QueryBase::GetQueryLevel () const [pure virtual]`

Implemented in [gdcm::QueryImage](#), [gdcm::QueryPatient](#), [gdcm::QuerySeries](#), and [gdcm::QueryStudy](#).

25.213.3.7 `virtual std::vector<Tag> gdcm::QueryBase::GetRequiredTags (const ERootType & inRootType) const [pure virtual]`

Implemented in [gdcm::QueryImage](#), [gdcm::QueryPatient](#), [gdcm::QuerySeries](#), and [gdcm::QueryStudy](#).

25.213.3.8 `virtual std::vector<Tag> gdcmm::QueryBase::GetUniqueTags (const ERootType & inRootType) const` [pure virtual]

Implemented in [gdcmm::QueryImage](#), [gdcmm::QueryPatient](#), [gdcmm::QuerySeries](#), and [gdcmm::QueryStudy](#).

The documentation for this class was generated from the following file:

- [gdcmmQueryBase.h](#)

25.214 gdcmm::QueryFactory Class Reference

QueryFactory.h.

```
#include <gdcmmQueryFactory.h>
```

Static Public Member Functions

- static [ECharSet](#) [GetCharacterFromCurrentLocale](#) ()
- static void [ListCharSets](#) (std::ostream &os)
List all possible CharSet.
- static [DataElement](#) [ProduceCharacterSetDataElement](#) (const std::vector< [ECharSet](#) > &inCharSetType)
- static [BaseRootQuery](#) * [ProduceQuery](#) ([ERootType](#) inRootType, [EQueryType](#) inQueryType, [EQueryLevel](#) inQueryLevel)

25.214.1 Detailed Description

QueryFactory.h.

Note

contains: a class to produce a query based off of user-entered information

Essentially, this class is used to construct a query based off of user input (typically from the command line; if in code directly, the query itself could just be instantiated)

In theory, could also be used as the interface to validate incoming datasets as belonging to a particular query style

25.214.2 Member Function Documentation

25.214.2.1 `static ECharSet gdcmm::QueryFactory::GetCharacterFromCurrentLocale ()` [static]

This function will return the corresponding ECharSet associated with the current locale of the running system (based on the value of locale()).

25.214.2.2 `static void gdcmm::QueryFactory::ListCharSets (std::ostream & os)` [static]

List all possible CharSet.

25.214.2.3 **static DataElement** gdcm::QueryFactory::ProduceCharacterSetDataElement (**const** std::vector< **ECharSet** > & *inCharSetType*) [static]

This function will produce the appropriate dataelement given a list of charsets. The first charset will be used directly, while the second and subsequent will be prepended with "ISO2022 ". Redundant character sets are not permitted, so if they are encountered, they will just be skipped. if UTF8 or GB18030 is used, no subsequent character sets will be used if the vector passed in is empty, then the dataelement that's passed out will be empty and Latin1 is the presumed encoding

25.214.2.4 **static BaseRootQuery*** gdcm::QueryFactory::ProduceQuery (**ERootType** *inRootType*, **EQueryType** *inQueryType*, **EQueryLevel** *inQueryLevel*) [static]

this function will produce a query (basically, a wrapper to a dataset that can validate whether or not the query is a valid cfind/cmove query) and the level of the query (patient, study, series, image). If the user provides an invalid instantiation (ie, study root type, query level of patient), then the result is NULL.

The documentation for this class was generated from the following file:


- [gdcmQueryFactory.h](#)

25.215 gdcm::QueryImage Class Reference


[QueryImage](#) contains: class to construct an image-based query for C-FIND and C-MOVE.

```
#include <gdcmQueryImage.h>
```

Inheritance diagram for gdcm::QueryImage:



Collaboration diagram for `gdcm::QueryImage`:



Public Member Functions

- `std::vector< Tag > GetHierachicalSearchTags (const ERootType &inRootType) const`
Return all Unique Key for a particular Query Root type (from the same level and above).
- `const char * GetName () const`
- `std::vector< Tag > GetOptionalTags (const ERootType &inRootType) const`
- `DataElement GetQueryLevel () const`
- `std::vector< Tag > GetRequiredTags (const ERootType &inRootType) const`
- `std::vector< Tag > GetUniqueTags (const ERootType &inRootType) const`

25.215.1 Detailed Description

[QueryImage](#) contains: class to construct an image-based query for C-FIND and C-MOVE.

25.215.2 Member Function Documentation

25.215.2.1 `std::vector<Tag> gdcm::QueryImage::GetHierachicalSearchTags (const ERootType & inRootType) const` `[virtual]`

Return all Unique Key for a particular Query Root type (from the same level and above).

Implements [gdcm::QueryBase](#).

25.215.2.2 `const char* gdcm::QueryImage::GetName () const` `[virtual]`

Implements [gdcm::QueryBase](#).

25.215.2.3 `std::vector<Tag> gdcm::QueryImage::GetOptionalTags (const ERootType & inRootType) const` `[virtual]`

Implements [gdcm::QueryBase](#).

25.215.2.4 `DataElement gdcm::QueryImage::GetQueryLevel () const` [virtual]

Implements [gdcm::QueryBase](#).

25.215.2.5 `std::vector<Tag> gdcm::QueryImage::GetRequiredTags (const ERootType & inRootType) const` [virtual]

Implements [gdcm::QueryBase](#).

25.215.2.6 `std::vector<Tag> gdcm::QueryImage::GetUniqueTags (const ERootType & inRootType) const` [virtual]

Implements [gdcm::QueryBase](#).

The documentation for this class was generated from the following file:


- [gdcmQueryImage.h](#)

25.216 gdcm::QueryPatient Class Reference


[QueryPatient](#) contains: class to construct a patient-based query for c-find and c-move.

```
#include <gdcmQueryPatient.h>
```

Inheritance diagram for `gdcm::QueryPatient`:



Collaboration diagram for `gdcm::QueryPatient`:



Public Member Functions

- `std::vector< Tag > GetHierachicalSearchTags (const ERootType &inRootType) const`
Return all Unique Key for a particular Query Root type (from the same level and above).
- `const char * GetName () const`
- `std::vector< Tag > GetOptionalTags (const ERootType &inRootType) const`
- `DataElement GetQueryLevel () const`
- `std::vector< Tag > GetRequiredTags (const ERootType &inRootType) const`
- `std::vector< Tag > GetUniqueTags (const ERootType &inRootType) const`

25.216.1 Detailed Description

`QueryPatient` contains: class to construct a patient-based query for c-find and c-move.

25.216.2 Member Function Documentation

25.216.2.1 `std::vector<Tag> gdcm::QueryPatient::GetHierachicalSearchTags (const ERootType & inRootType) const` `[virtual]`

Return all Unique Key for a particular Query Root type (from the same level and above).

Implements `gdcm::QueryBase`.

25.216.2.2 `const char* gdcm::QueryPatient::GetName () const` `[virtual]`

Implements `gdcm::QueryBase`.

25.216.2.3 `std::vector<Tag> gdcm::QueryPatient::GetOptionalTags (const ERootType & inRootType) const` `[virtual]`

Implements `gdcm::QueryBase`.

25.216.2.4 `DataElement` `gdcm::QueryPatient::GetQueryLevel () const` `[virtual]`

Implements [gdcm::QueryBase](#).

25.216.2.5 `std::vector<Tag>` `gdcm::QueryPatient::GetRequiredTags (const ERootType & inRootType) const` `[virtual]`

Implements [gdcm::QueryBase](#).

25.216.2.6 `std::vector<Tag>` `gdcm::QueryPatient::GetUniqueTags (const ERootType & inRootType) const` `[virtual]`

Implements [gdcm::QueryBase](#).

The documentation for this class was generated from the following file:


- [gdcmQueryPatient.h](#)

25.217 gdcm::QuerySeries Class Reference


[QuerySeries](#) contains: class to construct a series-based query for c-find and c-move.

```
#include <gdcmQuerySeries.h>
```

Inheritance diagram for `gdcm::QuerySeries`:



Collaboration diagram for `gdc::QuerySeries`:



Public Member Functions

- `std::vector< Tag > GetHierachicalSearchTags (const ERootType &inRootType) const`
Return all Unique Key for a particular Query Root type (from the same level and above).
- `const char * GetName () const`
- `std::vector< Tag > GetOptionalTags (const ERootType &inRootType) const`
- `DataElement GetQueryLevel () const`
- `std::vector< Tag > GetRequiredTags (const ERootType &inRootType) const`
- `std::vector< Tag > GetUniqueTags (const ERootType &inRootType) const`

25.217.1 Detailed Description

`QuerySeries` contains: class to construct a series-based query for c-find and c-move.

25.217.2 Member Function Documentation

25.217.2.1 `std::vector<Tag> gdc::QuerySeries::GetHierachicalSearchTags (const ERootType & inRootType) const` `[virtual]`

Return all Unique Key for a particular Query Root type (from the same level and above).

Implements `gdc::QueryBase`.

25.217.2.2 `const char* gdc::QuerySeries::GetName () const` `[virtual]`

Implements `gdc::QueryBase`.

25.217.2.3 `std::vector<Tag> gdc::QuerySeries::GetOptionalTags (const ERootType & inRootType) const` `[virtual]`

Implements `gdc::QueryBase`.

25.217.2.4 `DataElement` `gdcm::QuerySeries::GetQueryLevel () const` [virtual]

Implements [gdcm::QueryBase](#).

25.217.2.5 `std::vector<Tag>` `gdcm::QuerySeries::GetRequiredTags (const ERootType & inRootType) const` [virtual]

Implements [gdcm::QueryBase](#).

25.217.2.6 `std::vector<Tag>` `gdcm::QuerySeries::GetUniqueTags (const ERootType & inRootType) const` [virtual]

Implements [gdcm::QueryBase](#).

The documentation for this class was generated from the following file:


- [gdcmQuerySeries.h](#)

25.218 gdcm::QueryStudy Class Reference


QueryStudy.h contains: class to construct a study-based query for C-FIND and C-MOVE.

```
#include <gdcmQueryStudy.h>
```

Inheritance diagram for `gdcm::QueryStudy`:



Collaboration diagram for `gdcM::QueryStudy`:



Public Member Functions

- `std::vector< Tag > GetHierachicalSearchTags (const ERootType &inRootType) const`
Return all Unique Key for a particular Query Root type (from the same level and above).
- `const char * GetName () const`
- `std::vector< Tag > GetOptionalTags (const ERootType &inRootType) const`
- `DataElement GetQueryLevel () const`
- `std::vector< Tag > GetRequiredTags (const ERootType &inRootType) const`
- `std::vector< Tag > GetUniqueTags (const ERootType &inRootType) const`

25.218.1 Detailed Description

`QueryStudy.h` contains: class to construct a study-based query for C-FIND and C-MOVE.

25.218.2 Member Function Documentation

25.218.2.1 `std::vector<Tag> gdcM::QueryStudy::GetHierachicalSearchTags (const ERootType & inRootType) const` `[virtual]`

Return all Unique Key for a particular Query Root type (from the same level and above).

Implements `gdcM::QueryBase`.

25.218.2.2 `const char* gdcM::QueryStudy::GetName () const` `[virtual]`

Implements `gdcM::QueryBase`.

25.218.2.3 `std::vector<Tag> gdcM::QueryStudy::GetOptionalTags (const ERootType & inRootType) const` `[virtual]`

Implements `gdcM::QueryBase`.

25.218.2.4 `DataElement gdcm::QueryStudy::GetQueryLevel () const` [virtual]

Implements [gdcm::QueryBase](#).

25.218.2.5 `std::vector<Tag> gdcm::QueryStudy::GetRequiredTags (const ERootType & inRootType) const` [virtual]

Implements [gdcm::QueryBase](#).

25.218.2.6 `std::vector<Tag> gdcm::QueryStudy::GetUniqueTags (const ERootType & inRootType) const` [virtual]

Implements [gdcm::QueryBase](#).

The documentation for this class was generated from the following file:


- [gdcmQueryStudy.h](#)

25.219 gdcm::RAWCodec Class Reference


[RAWCodec](#) class.

```
#include <gdcmRAWCodec.h>
```

Inheritance diagram for `gdcm::RAWCodec`:



Collaboration diagram for `gdcm::RAWCodec`:



Public Member Functions

- [RAWCodec](#) ()
- [~RAWCodec](#) ()
- bool [CanCode](#) ([TransferSyntax](#) const &ts) const
Return whether this coder support this transfer syntax (can code it)
- bool [CanDecode](#) ([TransferSyntax](#) const &ts) const
Return whether this decoder support this transfer syntax (can decode it)
- bool [Code](#) ([DataElement](#) const &in, [DataElement](#) &out)
Code.
- bool [Decode](#) ([DataElement](#) const &is, [DataElement](#) &os)
Decode.
- bool [DecodeBytes](#) (const char *inBytes, size_t inBufferLength, char *outBytes, size_t inOutBufferLength)
- bool [GetHeaderInfo](#) (std::istream &is, [TransferSyntax](#) &ts)

Protected Member Functions

- bool [DecodeByStreams](#) (std::istream &is, std::ostream &os)

Additional Inherited Members

25.219.1 Detailed Description

[RAWCodec](#) class.

25.219.2 Constructor & Destructor Documentation

25.219.2.1 `gdcm::RAWCodec::RAWCodec ()`

25.219.2.2 `gdcm::RAWCodec::~~RAWCodec ()`

25.219.3 Member Function Documentation

25.219.3.1 `bool gdcm::RAWCodec::CanCode (TransferSyntax const &) const` [virtual]

Return whether this coder support this transfer syntax (can code it)

Reimplemented from [gdcm::ImageCodec](#).

25.219.3.2 `bool gdcm::RAWCodec::CanDecode (TransferSyntax const &) const` [virtual]

Return whether this decoder support this transfer syntax (can decode it)

Reimplemented from [gdcm::ImageCodec](#).

25.219.3.3 `bool gdcm::RAWCodec::Code (DataElement const & in_, DataElement & out_)` [virtual]

Code.

Reimplemented from [gdcm::Coder](#).

25.219.3.4 `bool gdcm::RAWCodec::Decode (DataElement const &, DataElement &)` [virtual]

Decode.

Reimplemented from [gdcm::ImageCodec](#).

25.219.3.5 `bool gdcm::RAWCodec::DecodeByStreams (std::istream & is, std::ostream & os)` [protected],[virtual]

Reimplemented from [gdcm::ImageCodec](#).

25.219.3.6 `bool gdcm::RAWCodec::DecodeBytes (const char * inBytes, size_t inBufferLength, char * outBytes, size_t inOutBufferLength)`

Used by the ImageStreamReader– converts a read in buffer into one with the proper encodings.

25.219.3.7 `bool gdcm::RAWCodec::GetHeaderInfo (std::istream & is, TransferSyntax & ts)` [virtual]

Reimplemented from [gdcm::ImageCodec](#).

The documentation for this class was generated from the following file:


- [gdcmRAWCodec.h](#)

25.220 gdcm::Reader Class Reference


[Reader](#) ala DOM (Document [Object](#) Model)

```
#include <gdcmReader.h>
```

Inheritance diagram for `gdcm::Reader`:



Collaboration diagram for `gdcm::Reader`:



Public Member Functions

- [Reader](#) ()
- virtual [~Reader](#) ()
- bool [CanRead](#) () const
- const [File](#) & [GetFile](#) () const
Set/Get File.
- [File](#) & [GetFile](#) ()
Set/Get File.
- virtual bool [Read](#) ()
Main function to read a file.
- bool [ReadSelectedTags](#) (std::set< [Tag](#) > const &tags)
Will only read the specified selected tags.
- bool [ReadUpToTag](#) (const [Tag](#) &tag, std::set< [Tag](#) > const &skiptags=std::set< [Tag](#) >())
- void [SetFile](#) ([File](#) &file)
Set/Get File.
- void [SetFileName](#) (const char *filename_native)
- void [SetStream](#) (std::istream &input_stream)
Set the open-ed stream directly.

Protected Member Functions

- std::istream * [GetStreamPtr](#) () const
- bool [ReadDataSet](#) ()
- bool [ReadMetaInformation](#) ()
- bool [ReadPreamble](#) ()

Protected Attributes

- [SmartPointer](#)< [File](#) > F

Friends

- class [StreamImageReader](#)

25.220.1 Detailed Description

[Reader](#) ala DOM (Document [Object](#) Model)

This class is a non-validating reader, it will only performs well- formedness check only, and to some extent catch known error (non well-formed document).

Detailed description here

A [DataSet](#) DOES NOT contains group 0x0002 (see [FileMetaInformation](#))

This is really a [DataSet](#) reader. This will not make sure the dataset conform to any [IOD](#) at all. This is a completely different step. The reasoning was that user could control the [IOD](#) there lib would handle and thus we would not be able to read a [DataSet](#) if the [IOD](#) was not found Instead we separate the reading from the validation.

Note

From GDCM1.x. Users will realize that one feature is missing from this DOM implementation. In GDCM 1.x user used to be able to control the size of the [Value](#) to be read. By default it was 0xffff. The main author of GDCM2 thought this was too dangerous and harmful and therefore this feature did not make it into GDCM2

Warning

GDCM will not produce warning for unordered (non-alphabetical order).

See Also

[Writer FileMetaInformation DataSet File](#)

Examples:

[ChangeSequenceUltrasound.cxx](#), [ClinicalTrialAnnotate.cxx](#), [csa2img.cxx](#), [DiffFile.cxx](#), [DumpADAC.cxx](#), [DumpGEMSMovieGroup.cxx](#), [DumpImageHeaderInfo.cxx](#), [DuplicatePCDE.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [FixBrokenJ2K.cxx](#), [gdcmrtonplan.cxx](#), [gdcmrtpplan.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetSequenceUltrasound.cxx](#), [GetSubSequenceData.cxx](#), [HelloWorld.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDSEExplicit.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [ReadAndPrintAttributes.cxx](#), [ReadExplicitLengthSQIVR.cxx](#), [ReadGEMSSDO.cxx](#), [ReadUTF8QtDir.cxx](#), [rle2img.cxx](#), and [TestReader.cxx](#).

25.220.2 Constructor & Destructor Documentation

25.220.2.1 `gdcmm::Reader::Reader () [inline]`

25.220.2.2 `virtual gdcmm::Reader::~~Reader () [virtual]`

25.220.3 Member Function Documentation

25.220.3.1 `bool gdcmm::Reader::CanRead () const`

Test whether this is a DICOM file

Warning

need to call either `SetFileName` or `SetStream` first

Examples:

[ReadUTF8QtDir.cxx](#).

25.220.3.2 `const File& gdcmm::Reader::GetFile () const [inline]`

Set/Get [File](#).

Examples:

[ChangeSequenceUltrasound.cxx](#), [ClinicalTrialAnnotate.cxx](#), [CompressImage.cxx](#), [csa2img.cxx](#), [DiffFile.cxx](#), [DumpADAC.cxx](#), [DumpImageHeaderInfo.cxx](#), [DuplicatePCDE.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [ExtractIconFromFile.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAI BugJPEGLS.cxx](#), [gdcmrtonplan.cxx](#), [gdcmrtpplan.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetJPEGSamplePrecision.cxx](#), [GetSequenceUltrasound.cxx](#), [HelloWorld.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDSEExplicit.cxx](#), [MergeTwoFiles.cxx](#), [MrProtocol.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [ReadAndPrintAttributes.cxx](#), [ReadExplicitLengthSQIVR.cxx](#), [ReadGEMSSDO.cxx](#), [rle2img.cxx](#), and [TestReader.cxx](#).

25.220.3.3 **File**& gdcm::Reader::GetFile () [inline]

Set/Get [File](#).

25.220.3.4 std::istream* gdcm::Reader::GetStreamPtr () const [inline],[protected]

25.220.3.5 virtual bool gdcm::Reader::Read () [virtual]

Main function to read a file.

Reimplemented in [gdcm::ImageRegionReader](#), [gdcm::PixmapReader](#), [gdcm::ImageReader](#), [gdcm::SegmentReader](#), and [gdcm::SurfaceReader](#).

Examples:

[ChangeSequenceUltrasound.cxx](#), [ClinicalTrialAnnotate.cxx](#), [csa2img.cxx](#), [DiffFile.cxx](#), [DumpADAC.cxx](#), [DumpImageHeaderInfo.cxx](#), [DuplicatePCDE.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [FixBrokenJ2K.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetSequenceUltrasound.cxx](#), [HelloWorld.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDSExplicit.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [ReadAndPrintAttributes.cxx](#), [ReadExplicitLengthSQIVR.cxx](#), [ReadGEMSSDO.cxx](#), [rle2img.cxx](#), and [TestReader.cxx](#).

25.220.3.6 bool gdcm::Reader::ReadDataSet () [protected]

25.220.3.7 bool gdcm::Reader::ReadMetaInformation () [protected]

25.220.3.8 bool gdcm::Reader::ReadPreamble () [protected]

25.220.3.9 bool gdcm::Reader::ReadSelectedTags (std::set< Tag > const & tags)

Will only read the specified selected tags.

25.220.3.10 bool gdcm::Reader::ReadUpToTag (const Tag & tag, std::set< Tag > const & skiptags = std::set< Tag >())

Will read only up to [Tag](#)

Parameters

<i>tag</i>	and skipping any tag specified in
<i>skiptags</i>	

25.220.3.11 void gdcm::Reader::SetFile (File & file) [inline]

Set/Get [File](#).

25.220.3.12 void gdcm::Reader::SetFileName (const char * filename_native)

Set the filename to open. This will create a std::ifstream internally See SetStream if you are dealing with different std::istream object

Examples:

[ChangeSequenceUltrasound.cxx](#), [CheckBigEndianBug.cxx](#), [ClinicalTrialAnnotate.cxx](#), [CompressImage.cxx](#), [ConvertToQImage.cxx](#), [csa2img.cxx](#), [DiffFile.cxx](#), [DumpADAC.cxx](#), [DumpGEMSMovieGroup.cxx](#), [DumplImageHeaderInfo.cxx](#), [DuplicatePCDE.cxx](#), [ELSCINT1WaveToText.cxx](#), [ExtractEncryptedContent.cxx](#), [ExtractIconFromFile.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAI BugJPEGLS.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetJPEGSamplePrecision.cxx](#), [GetSequenceUltrasound.cxx](#), [GetSubSequenceData.cxx](#), [HelloVizWorld.cxx](#), [HelloWorld.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDSExplicit.cxx](#), [MergeTwoFiles.cxx](#), [MrProtocol.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [ReadAndPrintAttributes.cxx](#), [ReadExplicitLength-SQIVR.cxx](#), [ReadGEMSSDO.cxx](#), [ReadMultiTimesException.cxx](#), [ReadUTF8QtDir.cxx](#), [rle2img.cxx](#), [TestReader.cxx](#), and [threadgdcm.cxx](#).

25.220.3.13 `void gdcm::Reader::SetStream (std::istream & input_stream)` `[inline]`

Set the open-ed stream directly.

Examples:

[ReadUTF8QtDir.cxx](#).

25.220.4 Friends And Related Function Documentation

25.220.4.1 `friend class StreamImageReader` `[friend]`

25.220.5 Member Data Documentation

25.220.5.1 `SmartPointer<File> gdcm::Reader::F` `[protected]`

The documentation for this class was generated from the following file:


- [gdcmReader.h](#)

25.221 gdcm::Region Class Reference

Class for manipulation region.

```
#include <gdcmRegion.h>
```

Inheritance diagram for gdcm::Region:



Public Member Functions

- [Region](#) ()
- virtual [~Region](#) ()
- virtual `size_t` [Area](#) () const =0
compute the area
- virtual [Region](#) * [Clone](#) () const =0
- virtual [BoxRegion](#) [ComputeBoundingBox](#) ()=0
Return the Axis-Aligned minimum bounding box for all regions.
- virtual `bool` [Empty](#) () const =0
return whether this domain is empty:
- virtual `bool` [IsValid](#) () const =0
return whether this is valid domain
- virtual void [Print](#) (std::ostream &os=std::cout) const
Print.

25.221.1 Detailed Description

Class for manipulation region.

25.221.2 Constructor & Destructor Documentation

25.221.2.1 `gdcm::Region::Region ()`

25.221.2.2 `virtual gdcm::Region::~~Region ()` [virtual]

25.221.3 Member Function Documentation

25.221.3.1 `virtual size_t gdcm::Region::Area () const` [pure virtual]

compute the area

Implemented in [gdcm::BoxRegion](#).

25.221.3.2 `virtual Region* gdcm::Region::Clone () const [pure virtual]`

Implemented in [gdcm::BoxRegion](#).

25.221.3.3 `virtual BoxRegion gdcm::Region::ComputeBoundingBox () [pure virtual]`

Return the Axis-Aligned minimum bounding box for all regions.

Implemented in [gdcm::BoxRegion](#).

25.221.3.4 `virtual bool gdcm::Region::Empty () const [pure virtual]`

return whether this domain is empty:

Implemented in [gdcm::BoxRegion](#).

25.221.3.5 `virtual bool gdcm::Region::IsValid () const [pure virtual]`

return whether this is valid domain

Implemented in [gdcm::BoxRegion](#).

25.221.3.6 `virtual void gdcm::Region::Print (std::ostream & os = std::cout) const [virtual]`

Print.

Reimplemented in [gdcm::BoxRegion](#).

Referenced by `gdcm::operator<<()`.

The documentation for this class was generated from the following file:

- [gdcmRegion.h](#)

25.222 gdcm::Rescaler Class Reference

Rescale class This class is meant to apply the linear transform of Stored Pixel [Value](#) to Real World [Value](#). This is mostly found in CT or PET dataset, where the value are stored using one type, but need to be converted to another scale using a linear transform. There are basically two cases: In CT: the linear transform is generally integer based. E.g. the Stored Pixel [Type](#) is unsigned short 12bits, but to get Hounsfield unit, one need to apply the linear transform:

$$RWV = 1. * SV - 1024$$

So the best scalar to store the Real World [Value](#) will be 16 bits signed type.

```
#include <gdcmRescaler.h>
```

Public Member Functions

- [Rescaler \(\)](#)
- [~Rescaler \(\)](#)
- [PixelFormat::ScalarType ComputeInterceptSlopePixelFormat \(\)](#)

- [PixelFormat ComputePixelTypeFromMinMax](#) ()
- double [GetIntercept](#) () const
- double [GetSlope](#) () const
- bool [InverseRescale](#) (char *out, const char *in, size_t n)
Inverse transform.
- bool [Rescale](#) (char *out, const char *in, size_t n)
Direct transform.
- void [SetIntercept](#) (double i)
Set Intercept: used for both direct&inverse transformation.
- void [SetMinMaxForPixelFormat](#) (double min, double max)
- void [SetPixelFormat](#) ([PixelFormat](#) const &pf)
Set Pixel Format of input data.
- void [SetSlope](#) (double s)
Set Slope: user for both direct&inverse transformation.
- void [SetTargetPixelFormat](#) ([PixelFormat](#) const &targetst)
- void [SetUseTargetPixelFormat](#) (bool b)
Override default behavior of Rescale.

Protected Member Functions

- template<typename TIn >
void [InverseRescaleFunctionIntoBestFit](#) (char *out, const TIn *in, size_t n)
- template<typename TIn >
void [RescaleFunctionIntoBestFit](#) (char *out, const TIn *in, size_t n)

25.222.1 Detailed Description

Rescale class This class is meant to apply the linear transform of Stored Pixel [Value](#) to Real World [Value](#). This is mostly found in CT or PET dataset, where the value are stored using one type, but need to be converted to another scale using a linear transform. There are basically two cases: In CT: the linear transform is generally integer based. E.g. the Stored Pixel [Type](#) is unsigned short 12bits, but to get Hounsfield unit, one need to apply the linear transform:

$$RWV = 1. * SV - 1024$$

So the best scalar to store the Real World [Value](#) will be 16 bits signed type.

In PET: the linear transform is generally floating point based. Since the dynamic range can be quite high, the Rescale Slope / Rescale Intercept can be changing throughout the [Series](#). So it is important to read all linear transform and deduce the best Pixel [Type](#) only at the end (when all the images to be read have been parsed).

Warning

Internally any time a floating point value is found either in the Rescale Slope or the Rescale Intercept it is assumed that the best matching output pixel type is FLOAT64 (in previous implementation it was FLOAT32). Because [VR:DS](#) is closer to a 64bits floating point type FLOAT64 is thus a best matching pixel type for the floating point transformation.

Example: Let say input is FLOAT64, and we want UINT16 as ouput, we would do:

```
Rescaler ir;
ir.SetIntercept( 0 );
ir.SetSlope( 5.6789 );
ir.SetPixelFormat( FLOAT64 );
ir.SetMinMaxForPixelFormat( ((PixelFormat)UINT16).GetMin(), ((PixelFormat)UINT16).GetMax() );
ir.InverseRescale(output,input,numberofbytes );
```

Note

handle floating point transformation back and forth to integer properly (no loss)

See Also

[Unpacker12Bits](#)

25.222.2 Constructor & Destructor Documentation

25.222.2.1 `gdcm::Rescaler::Rescaler ()` `[inline]`

25.222.2.2 `gdcm::Rescaler::~~Rescaler ()` `[inline]`

25.222.3 Member Function Documentation

25.222.3.1 `PixelFormat::ScalarType gdcm::Rescaler::ComputeInterceptSlopePixelType ()`

Compute the Pixel Format of the output data Used for direct transformation

25.222.3.2 `PixelFormat gdcm::Rescaler::ComputePixelTypeFromMinMax ()`

Compute the Pixel Format of the output data Used for inverse transformation

25.222.3.3 `double gdcm::Rescaler::GetIntercept () const` `[inline]`

25.222.3.4 `double gdcm::Rescaler::GetSlope () const` `[inline]`

25.222.3.5 `bool gdcm::Rescaler::InverseRescale (char * out, const char * in, size_t n)`

Inverse transform.

25.222.3.6 `template<typename TIn > void gdcm::Rescaler::InverseRescaleFunctionIntoBestFit (char * out, const TIn * in, size_t n)` `[protected]`

25.222.3.7 `bool gdcm::Rescaler::Rescale (char * out, const char * in, size_t n)`

Direct transform.

25.222.3.8 `template<typename TIn > void gdcm::Rescaler::RescaleFunctionIntoBestFit (char * out, const TIn * in, size_t n)` `[protected]`

25.222.3.9 `void gdcm::Rescaler::SetIntercept (double i)` `[inline]`

Set Intercept: used for both direct&inverse transformation.

25.222.3.10 `void gdcm::Rescaler::SetMinMaxForPixelType (double min, double max)` `[inline]`

Set target interval for output data. A best match will be computed (if possible) Used for inverse transformation

25.222.3.11 void gdcm::Rescaler::SetPixelFormat (PixelFormat const & *pf*) [inline]

Set Pixel Format of input data.

25.222.3.12 void gdcm::Rescaler::SetSlope (double *s*) [inline]

Set Slope: user for both direct&inverse transformation.

25.222.3.13 void gdcm::Rescaler::SetTargetPixelType (PixelFormat const & *targetst*)

By default (when UseTargetPixelType is false), a best matching Target Pixel [Type](#) is computed. However user can override this auto selection by switching UseTargetPixelType:true and also specifying the specifix Target Pixel [Type](#)

25.222.3.14 void gdcm::Rescaler::SetUseTargetPixelType (bool *b*)

Override default behavior of Rescale.

The documentation for this class was generated from the following file:


- [gdcmRescaler.h](#)

25.223 gdcm::RLECodec Class Reference


Class to do RLE.

```
#include <gdcmRLECodec.h>
```

Inheritance diagram for `gdcm::RLECodec`:



Collaboration diagram for `gdcm::RLECodec`:



Public Member Functions

- [RLECodec](#) ()
- [~RLECodec](#) ()
- bool [CanCode](#) ([TransferSyntax](#) const &ts) const
Return whether this coder support this transfer syntax (can code it)
- bool [CanDecode](#) ([TransferSyntax](#) const &ts) const
Return whether this decoder support this transfer syntax (can decode it)
- bool [Code](#) ([DataElement](#) const &in, [DataElement](#) &out)
Code.
- bool [Decode](#) ([DataElement](#) const &is, [DataElement](#) &os)
Decode.

- unsigned long [GetBufferLength](#) () const
- bool [GetHeaderInfo](#) (std::istream &is, [TransferSyntax](#) &ts)
- void [SetBufferLength](#) (unsigned long l)
- void [SetLength](#) (unsigned long l)

Protected Member Functions

- bool [DecodeByStreams](#) (std::istream &is, std::ostream &os)
- bool [DecodeExtent](#) (char *buffer, unsigned int XMin, unsigned int XMax, unsigned int YMin, unsigned int YMax, unsigned int ZMin, unsigned int ZMax, std::istream &is)

Friends

- class [ImageRegionReader](#)

Additional Inherited Members

25.223.1 Detailed Description

Class to do RLE.

Note

ANSI X3.9 A.4.2 RLE Compression Annex G defines a RLE Compression Transfer Syntax. This transfer Syntax is identified by the UID value "1.2.840.10008.1.2.5". If the object allows multi-frame images in the pixel data field, then each frame shall be encoded separately. Each frame shall be encoded in one and only one [Fragment](#) (see PS 3.5.8.2).

25.223.2 Constructor & Destructor Documentation

25.223.2.1 [gdcm::RLECodec::RLECodec](#) ()

25.223.2.2 [gdcm::RLECodec::~~RLECodec](#) ()

25.223.3 Member Function Documentation

25.223.3.1 [bool gdcm::RLECodec::CanCode](#) ([TransferSyntax](#) const &) const [virtual]

Return whether this coder support this transfer syntax (can code it)

Reimplemented from [gdcm::ImageCodec](#).

25.223.3.2 [bool gdcm::RLECodec::CanDecode](#) ([TransferSyntax](#) const &) const [virtual]

Return whether this decoder support this transfer syntax (can decode it)

Reimplemented from [gdcm::ImageCodec](#).

25.223.3.3 `bool gdcM::RLECodec::Code (DataElement const & in_, DataElement & out_) [virtual]`

Code.

Reimplemented from [gdcM::Coder](#).

25.223.3.4 `bool gdcM::RLECodec::Decode (DataElement const &, DataElement &) [virtual]`

Decode.

Reimplemented from [gdcM::ImageCodec](#).

25.223.3.5 `bool gdcM::RLECodec::DecodeByStreams (std::istream & is, std::ostream & os) [protected], [virtual]`

Reimplemented from [gdcM::ImageCodec](#).

25.223.3.6 `bool gdcM::RLECodec::DecodeExtent (char * buffer, unsigned int XMin, unsigned int XMax, unsigned int YMin, unsigned int YMax, unsigned int ZMin, unsigned int ZMax, std::istream & is) [protected]`

25.223.3.7 `unsigned long gdcM::RLECodec::GetBufferLength () const [inline]`

25.223.3.8 `bool gdcM::RLECodec::GetHeaderInfo (std::istream & is, TransferSyntax & ts) [virtual]`

Reimplemented from [gdcM::ImageCodec](#).

25.223.3.9 `void gdcM::RLECodec::SetBufferLength (unsigned long l) [inline]`

25.223.3.10 `void gdcM::RLECodec::SetLength (unsigned long l) [inline]`

25.223.4 Friends And Related Function Documentation

25.223.4.1 `friend class ImageRegionReader [friend]`

The documentation for this class was generated from the following file:

- [gdcMRLECodec.h](#)

25.224 gdcM::network::RoleSelectionSub Class Reference

[RoleSelectionSub](#) PS 3.7 [Table D.3-9](#) SCP/SCU ROLE SELECTION SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

```
#include <gdcMRoleSelectionSub.h>
```

Public Member Functions

- [RoleSelectionSub](#) ()
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- void [SetTuple](#) (const char *uid, uint8_t scurole, uint8_t scprole)

- `size_t Size () const`
- `const std::ostream & Write (std::ostream &os) const`

25.224.1 Detailed Description

[RoleSelectionSub](#) PS 3.7 [Table D.3-9](#) SCP/SCU ROLE SELECTION SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

25.224.2 Constructor & Destructor Documentation

25.224.2.1 `gdcm::network::RoleSelectionSub::RoleSelectionSub ()`

25.224.3 Member Function Documentation

25.224.3.1 `void gdcm::network::RoleSelectionSub::Print (std::ostream & os) const`

25.224.3.2 `std::istream& gdcm::network::RoleSelectionSub::Read (std::istream & is)`

25.224.3.3 `void gdcm::network::RoleSelectionSub::SetTuple (const char * uid, uint8_t scurole, uint8_t scprole)`

25.224.3.4 `size_t gdcm::network::RoleSelectionSub::Size () const`

25.224.3.5 `const std::ostream& gdcm::network::RoleSelectionSub::Write (std::ostream & os) const`


The documentation for this class was generated from the following file:

- [gdcmRoleSelectionSub.h](#)

25.225 gdcm::SerieHelper::Rule Struct Reference

```
#include <gdcmSerieHelper.h>
```

Collaboration diagram for `gdcm::SerieHelper::Rule`:



Public Attributes

- `uint16_t` [elem](#)
- `uint16_t` [group](#)
- `int` [op](#)
- `std::string` [value](#)

25.225.1 Member Data Documentation

25.225.1.1 `uint16_t` `gdcm::SerieHelper::Rule::elem`

25.225.1.2 `uint16_t` `gdcm::SerieHelper::Rule::group`

25.225.1.3 `int` `gdcm::SerieHelper::Rule::op`

25.225.1.4 `std::string` `gdcm::SerieHelper::Rule::value`

The documentation for this struct was generated from the following file:


- [gdcmSerieHelper.h](#)

25.226 gdcm::Scanner Class Reference


[Scanner](#) This filter is meant for quickly browsing a [FileSet](#) (a set of files on disk). Special consideration are taken so as to read the minimum amount of information in each file in order to retrieve the user specified set of DICOM [Attribute](#).

```
#include <gdcmmScanner.h>
```

Inheritance diagram for gdcmm::Scanner:



Collaboration diagram for gdcmm::Scanner:



Classes

- struct [ltstr](#)

Public Types

- typedef MappingType::const_iterator [ConstIterator](#)

- typedef std::map< const char *, [TagToValue](#), [ltstr](#) > [MappingType](#)
- typedef std::map< [Tag](#), const char * > [TagToValue](#)
- typedef [TagToValue](#)::value_type [TagToValueValueType](#)
- typedef std::set< std::string > [ValuesType](#)

Public Member Functions

- [Scanner](#) ()
- [~Scanner](#) ()
- void [AddPrivateTag](#) ([PrivateTag](#) const &t)
- void [AddSkipTag](#) ([Tag](#) const &t)
Add a tag that will need to be skipped. Those are root level skip tags.
- void [AddTag](#) ([Tag](#) const &t)
Add a tag that will need to be read. Those are root level skip tags.
- [ConstIterator](#) [Begin](#) () const
- void [ClearSkipTags](#) ()
- void [ClearTags](#) ()
- [ConstIterator](#) [End](#) () const
- [Directory::FilenamesType](#) [GetAllFilenamesFromTagToValue](#) ([Tag](#) const &t, const char *valueref) const
- const char * [GetFilenameFromTagToValue](#) ([Tag](#) const &t, const char *valueref) const
- [Directory::FilenamesType](#) const & [GetFilenames](#) () const
- [Directory::FilenamesType](#) [GetKeys](#) () const
- [TagToValue](#) const & [GetMapping](#) (const char *filename) const
Get the std::map mapping filenames to value for file 'filename'.
- [TagToValue](#) const & [GetMappingFromTagToValue](#) ([Tag](#) const &t, const char *value) const
See [GetFilenameFromTagToValue\(\)](#). This is simply [GetFilenameFromTagToValue](#) followed.
- [MappingType](#) const & [GetMappings](#) () const
Mappings are the mapping from a particular tag to the map, mapping filename to value:
- [Directory::FilenamesType](#) [GetOrderedValues](#) ([Tag](#) const &t) const
- const char * [GetValue](#) (const char *filename, [Tag](#) const &t) const
- [ValuesType](#) const & [GetValues](#) () const
Get all the values found (in lexicographic order)
- [ValuesType](#) [GetValues](#) ([Tag](#) const &t) const
Get all the values found (in lexicographic order) associated with [Tag](#) 't'.
- bool [IsKey](#) (const char *filename) const
- void [Print](#) (std::ostream &os) const
Print result.
- bool [Scan](#) ([Directory::FilenamesType](#) const &filenames)
Start the scan !

Static Public Member Functions

- static [SmartPointer](#)< [Scanner](#) > [New](#) ()
for wrapped language: instantiate a reference counted object

Protected Member Functions

- void [ProcessPublicTag](#) ([StringFilter](#) &sf, const char *filename)

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [Scanner](#) &s)

25.226.1 Detailed Description

[Scanner](#) This filter is meant for quickly browsing a [FileSet](#) (a set of files on disk). Special consideration are taken so as to read the minimum amount of information in each file in order to retrieve the user specified set of DICOM [Attribute](#).

This filter is dealing with both VRASCII and VRBINARY element, thanks to the help of [gdcm::StringFilter](#)

Warning

IMPORTANT In case of file where tags are not ordered (illegal as per DICOM specification), the output will be missing information

Note

implementation details. All values are stored in a std::set of std::string. Then the address of the cstring underlying the std::string is used in the std::map.

This class implement the Subject/Observer pattern trigger the following events:

- [ProgressEvent](#)
- [StartEvent](#)
- [EndEvent](#)

Examples:

[DiscriminateVolume.cxx](#), [DumpToSQLITE3.cxx](#), [SimpleScanner.cxx](#), [SortImage.cxx](#), and [VolumeSorter.cxx](#).

25.226.2 Member Typedef Documentation

25.226.2.1 typedef MappingType::const_iterator **gdcm::Scanner::ConstIterator**

25.226.2.2 typedef std::map<const char *, TagToValue, Itstr> **gdcm::Scanner::MappingType**

25.226.2.3 typedef std::map<Tag, const char*> **gdcm::Scanner::TagToValue**

struct to map a filename to a value Implementation note: all std::map in this class will be using const char * and not std::string since we are pointing to existing std::string (hold in a std::vector) this avoid an extra copy of the byte array. [Tag](#) are used as [Tag](#) class since sizeof(tag) <= sizeof(pointer)

25.226.2.4 `typedef TagToValue::value_type gdcmm::Scanner::TagToValueValueType`

25.226.2.5 `typedef std::set< std::string > gdcmm::Scanner::ValuesType`

25.226.3 Constructor & Destructor Documentation

25.226.3.1 `gdcmm::Scanner::Scanner ()` `[inline]`

25.226.3.2 `gdcmm::Scanner::~~Scanner ()`

25.226.4 Member Function Documentation

25.226.4.1 `void gdcmm::Scanner::AddPrivateTag (PrivateTag const & t)`

25.226.4.2 `void gdcmm::Scanner::AddSkipTag (Tag const & t)`

Add a tag that will need to be skipped. Those are root level skip tags.

25.226.4.3 `void gdcmm::Scanner::AddTag (Tag const & t)`

Add a tag that will need to be read. Those are root level skip tags.

Examples:

[DiscriminateVolume.cxx](#), [DumpToSQLITE3.cxx](#), [SimpleScanner.cxx](#), [SortImage.cxx](#), and [VolumeSorter.cxx](#).

25.226.4.4 `ConstIterator gdcmm::Scanner::Begin () const` `[inline]`

25.226.4.5 `void gdcmm::Scanner::ClearSkipTags ()`

25.226.4.6 `void gdcmm::Scanner::ClearTags ()`

25.226.4.7 `ConstIterator gdcmm::Scanner::End () const` `[inline]`

25.226.4.8 `Directory::FileNamesType gdcmm::Scanner::GetAllFileNamesFromTagToValue (Tag const & t, const char * valuref) const`

Will loop over all files and return a vector of std::strings of filenames where value match the reference value 'valuref'

25.226.4.9 `const char* gdcmm::Scanner::GetFilenameFromTagToValue (Tag const & t, const char * valuref) const`

Will loop over all files and return the first file where value match the reference value 'valuref'

25.226.4.10 `Directory::FileNamesType const& gdcmm::Scanner::GetFileNames () const` `[inline]`

25.226.4.11 `Directory::FileNamesType gdcmm::Scanner::GetKeys () const`

Return the list of filename that are key in the internal map, which means those filename were properly parsed

Examples:

[VolumeSorter.cxx](#).

25.226.4.12 TagToValue const& gdcm::Scanner::GetMapping (const char * *filename*) const

Get the std::map mapping filenames to value for file 'filename'.

Examples:

[DumpToSQLITE3.cxx](#), and [SimpleScanner.cxx](#).

25.226.4.13 TagToValue const& gdcm::Scanner::GetMappingFromTagToValue (Tag const & *t*, const char * *value*) const

See [GetFilenameFromTagToValue\(\)](#). This is simply GetFilenameFromTagToValue followed.

25.226.4.14 MappingType const& gdcm::Scanner::GetMappings () const [inline]

Mappings are the mapping from a particular tag to the map, mapping filename to value:

25.226.4.15 Directory::FileNamesType gdcm::Scanner::GetOrderedValues (Tag const & *t*) const

Get all the values found (in a vector) associated with Tag 't' This function is identical to GetValues, but is accessible from the wrapped layer (python, C#, java)

25.226.4.16 const char* gdcm::Scanner::GetValue (const char * *filename*, Tag const & *t*) const

Retrieve the value found for tag: t associated with file: filename This is meant for a single short call. If multiple calls (multiple tags) should be done, prefer the GetMapping function, and then reuse the TagToValue hash table.

Warning

Tag 't' should have been added via [AddTag\(\)](#) prior to the [Scan\(\)](#) call !

25.226.4.17 ValuesType const& gdcm::Scanner::GetValues () const [inline]

Get all the values found (in lexicographic order)

Examples:

[SortImage.cxx](#), and [VolumeSorter.cxx](#).

25.226.4.18 ValuesType gdcm::Scanner::GetValues (Tag const & *t*) const

Get all the values found (in lexicographic order) associated with Tag 't'.

25.226.4.19 `bool gdcM::Scanner::IsKey (const char * filename) const`

Check if filename is a key in the Mapping table. returns true only if file can be found, which means the file was indeed a DICOM file that could be processed

Examples:

[DumpToSQLITE3.cxx](#), and [SimpleScanner.cxx](#).

25.226.4.20 `static SmartPointer<Scanner> gdcM::Scanner::New () [inline],[static]`

for wrapped language: instantiate a reference counted object

25.226.4.21 `void gdcM::Scanner::Print (std::ostream & os) const [virtual]`

Print result.

Reimplemented from [gdcM::Object](#).

Referenced by `gdcM::operator<<()`.

25.226.4.22 `void gdcM::Scanner::ProcessPublicTag (StringFilter & sf, const char * filename) [protected]`

25.226.4.23 `bool gdcM::Scanner::Scan (Directory::FileNamesType const & filenames)`

Start the scan !

Examples:

[DiscriminateVolume.cxx](#), [DumpToSQLITE3.cxx](#), [SimpleScanner.cxx](#), [SortImage.cxx](#), and [VolumeSorter.cxx](#).

25.226.5 Friends And Related Function Documentation

25.226.5.1 `std::ostream& operator<< (std::ostream & _os, const Scanner & s) [friend]`

The documentation for this class was generated from the following file:


- [gdcMScanner.h](#)

25.227 gdcM::Segment Class Reference


This class defines a segment. It mainly contains attributes of group 0x0062. In addition, it can be associated with surface.

```
#include <gdcMSegment.h>
```

Inheritance diagram for gdcm::Segment:



Collaboration diagram for gdcm::Segment:



Public Types

- enum `ALGOType` {
`MANUAL` = 0,
`AUTOMATIC`,
`ALGOType_END` }
- typedef `std::vector`
`< SmartPointer< Surface > >` `SurfaceVector`

Public Member Functions

- `Segment` ()
- virtual `~Segment` ()
- void `AddSurface` (`SmartPointer< Surface >` surface)
- `SegmentHelper::BasicCodedEntry`
`const & GetAnatomicRegion` () const
- `SegmentHelper::BasicCodedEntry` & `GetAnatomicRegion` ()
- `SegmentHelper::BasicCodedEntry`
`const & GetPropertyCategory` () const
- `SegmentHelper::BasicCodedEntry` & `GetPropertyCategory` ()
- `SegmentHelper::BasicCodedEntry`
`const & GetPropertyType` () const

- [SegmentHelper::BasicCodedEntry](#) & [GetPropertyType](#) ()
- const char * [GetSegmentAlgorithmName](#) () const
- [ALGOType](#) [GetSegmentAlgorithmType](#) () const
- const char * [GetSegmentDescription](#) () const
- const char * [GetSegmentLabel](#) () const
- unsigned short [GetSegmentNumber](#) () const
- [SmartPointer< Surface >](#) [GetSurface](#) (const unsigned int idx=0) const
- unsigned long [GetSurfaceCount](#) ()
- [SurfaceVector](#) const & [GetSurfaces](#) () const
- [SurfaceVector](#) & [GetSurfaces](#) ()
- void [SetAnatomicRegion](#) ([SegmentHelper::BasicCodedEntry](#) const &BSE)
- void [SetPropertyCategory](#) ([SegmentHelper::BasicCodedEntry](#) const &BSE)
- void [SetPropertyType](#) ([SegmentHelper::BasicCodedEntry](#) const &BSE)
- void [SetSegmentAlgorithmName](#) (const char *name)
- void [SetSegmentAlgorithmType](#) ([ALGOType](#) type)
- void [SetSegmentAlgorithmType](#) (const char *typeStr)
- void [SetSegmentDescription](#) (const char *description)
- void [SetSegmentLabel](#) (const char *label)
- void [SetSegmentNumber](#) (const unsigned short num)
- void [SetSurfaceCount](#) (const unsigned long nb)

Static Public Member Functions

- static [ALGOType](#) [GetALGOType](#) (const char *type)
- static const char * [GetALGOTypeString](#) ([ALGOType](#) type)

Protected Attributes

- [SegmentHelper::BasicCodedEntry](#) [AnatomicRegion](#)
- [SegmentHelper::BasicCodedEntry](#) [PropertyCategory](#)
- [SegmentHelper::BasicCodedEntry](#) [PropertyType](#)
- std::string [SegmentAlgorithmName](#)
- [ALGOType](#) [SegmentAlgorithmType](#)
- std::string [SegmentDescription](#)
- std::string [SegmentLabel](#)
- unsigned short [SegmentNumber](#)
- unsigned long [SurfaceCount](#)
- [SurfaceVector](#) [Surfaces](#)

Additional Inherited Members

25.227.1 Detailed Description

This class defines a segment. It mainly contains attributes of group 0x0062. In addition, it can be associated with surface.

See Also

PS 3.3 C.8.20.2 and C.8.23

25.227.2 Member Typedef Documentation

25.227.2.1 `typedef std::vector< SmartPointer< Surface > > gdcm::Segment::SurfaceVector`

25.227.3 Member Enumeration Documentation

25.227.3.1 `enum gdcm::Segment::ALGOType`

Enumerator

MANUAL

AUTOMATIC

ALGOType_END

25.227.4 Constructor & Destructor Documentation

25.227.4.1 `gdcm::Segment::Segment ()`

25.227.4.2 `virtual gdcm::Segment::~~Segment () [virtual]`

25.227.5 Member Function Documentation

25.227.5.1 `void gdcm::Segment::AddSurface (SmartPointer< Surface > surface)`

25.227.5.2 `static ALGOType gdcm::Segment::GetALGOType (const char * type) [static]`

25.227.5.3 `static const char* gdcm::Segment::GetALGOTypeString (ALGOType type) [static]`

25.227.5.4 `SegmentHelper::BasicCodedEntry const& gdcm::Segment::GetAnatomicRegion () const`

25.227.5.5 `SegmentHelper::BasicCodedEntry& gdcm::Segment::GetAnatomicRegion ()`

25.227.5.6 `SegmentHelper::BasicCodedEntry const& gdcm::Segment::GetPropertyCategory () const`

25.227.5.7 `SegmentHelper::BasicCodedEntry& gdcm::Segment::GetPropertyCategory ()`

25.227.5.8 `SegmentHelper::BasicCodedEntry const& gdcm::Segment::GetPropertyType () const`

25.227.5.9 `SegmentHelper::BasicCodedEntry& gdcm::Segment::GetPropertyType ()`

25.227.5.10 `const char* gdcm::Segment::GetSegmentAlgorithmName () const`

25.227.5.11 `ALGOType gdcm::Segment::GetSegmentAlgorithmType () const`

25.227.5.12 `const char* gdcm::Segment::GetSegmentDescription () const`

25.227.5.13 `const char* gdcm::Segment::GetSegmentLabel () const`

25.227.5.14 `unsigned short gdcm::Segment::GetSegmentNumber () const`

25.227.5.15 `SmartPointer< Surface > gdcm::Segment::GetSurface (const unsigned int idx = 0) const`

- 25.227.5.16 `unsigned long gdcM::Segment::GetSurfaceCount ()`
- 25.227.5.17 `SurfaceVector const& gdcM::Segment::GetSurfaces () const`
- 25.227.5.18 `SurfaceVector& gdcM::Segment::GetSurfaces ()`
- 25.227.5.19 `void gdcM::Segment::SetAnatomicRegion (SegmentHelper::BasicCodedEntry const & BSE)`
- 25.227.5.20 `void gdcM::Segment::SetPropertyCategory (SegmentHelper::BasicCodedEntry const & BSE)`
- 25.227.5.21 `void gdcM::Segment::SetPropertyType (SegmentHelper::BasicCodedEntry const & BSE)`
- 25.227.5.22 `void gdcM::Segment::SetSegmentAlgorithmName (const char * name)`
- 25.227.5.23 `void gdcM::Segment::SetSegmentAlgorithmType (ALGOType type)`
- 25.227.5.24 `void gdcM::Segment::SetSegmentAlgorithmType (const char * typeStr)`
- 25.227.5.25 `void gdcM::Segment::SetSegmentDescription (const char * description)`
- 25.227.5.26 `void gdcM::Segment::SetSegmentLabel (const char * label)`
- 25.227.5.27 `void gdcM::Segment::SetSegmentNumber (const unsigned short num)`
- 25.227.5.28 `void gdcM::Segment::SetSurfaceCount (const unsigned long nb)`

25.227.6 Member Data Documentation

- 25.227.6.1 `SegmentHelper::BasicCodedEntry gdcM::Segment::AnatomicRegion` [protected]
- 25.227.6.2 `SegmentHelper::BasicCodedEntry gdcM::Segment::PropertyCategory` [protected]
- 25.227.6.3 `SegmentHelper::BasicCodedEntry gdcM::Segment::PropertyType` [protected]
- 25.227.6.4 `std::string gdcM::Segment::SegmentAlgorithmName` [protected]
- 25.227.6.5 `ALGOType gdcM::Segment::SegmentAlgorithmType` [protected]
- 25.227.6.6 `std::string gdcM::Segment::SegmentDescription` [protected]
- 25.227.6.7 `std::string gdcM::Segment::SegmentLabel` [protected]
- 25.227.6.8 `unsigned short gdcM::Segment::SegmentNumber` [protected]
- 25.227.6.9 `unsigned long gdcM::Segment::SurfaceCount` [protected]
- 25.227.6.10 `SurfaceVector gdcM::Segment::Surfaces` [protected]

The documentation for this class was generated from the following file:


- [gdcMSegment.h](#)

25.228 gdcm::SegmentedPaletteColorLookupTable Class Reference


[SegmentedPaletteColorLookupTable](#) class.

```
#include <gdcmSegmentedPaletteColorLookupTable.h>
```

Inheritance diagram for gdcm::SegmentedPaletteColorLookupTable:



Collaboration diagram for gdcm::SegmentedPaletteColorLookupTable:



Public Member Functions

- [SegmentedPaletteColorLookupTable](#) ()
- [~SegmentedPaletteColorLookupTable](#) ()
- void [Print](#) (std::ostream &) const
- void [SetLUT](#) ([LookupTableType](#) type, const unsigned char *array, unsigned int length)

Initialize a [SegmentedPaletteColorLookupTable](#).

Additional Inherited Members

25.228.1 Detailed Description

[SegmentedPaletteColorLookupTable](#) class.

25.228.2 Constructor & Destructor Documentation

25.228.2.1 `gdcm::SegmentedPaletteColorLookupTable::SegmentedPaletteColorLookupTable ()`

25.228.2.2 `gdcm::SegmentedPaletteColorLookupTable::~~SegmentedPaletteColorLookupTable ()`

25.228.3 Member Function Documentation

25.228.3.1 `void gdcm::SegmentedPaletteColorLookupTable::Print (std::ostream &) const` `[inline]`, `[virtual]`

Reimplemented from [gdcm::LookupTable](#).

25.228.3.2 `void gdcm::SegmentedPaletteColorLookupTable::SetLUT (LookupTableType type, const unsigned char * array, unsigned int length)` `[virtual]`

Initialize a [SegmentedPaletteColorLookupTable](#).

Reimplemented from [gdcm::LookupTable](#).

The documentation for this class was generated from the following file:


- [gdcmSegmentedPaletteColorLookupTable.h](#)

25.229 gdcm::SegmentReader Class Reference


This class defines a segment reader. It reads attributes of group 0x0062.

```
#include <gdcmSegmentReader.h>
```


Inheritance diagram for gdcm::SegmentReader:



Collaboration diagram for gdcm::SegmentReader:



Public Types

- typedef `std::vector< SmartPointer< Segment > >` `SegmentVector`

Public Member Functions

- [SegmentReader](#) ()
- virtual [~SegmentReader](#) ()
- const [SegmentVector](#) [GetSegments](#) () const
- [SegmentVector](#) [GetSegments](#) ()
- virtual bool [Read](#) ()

Read.

Protected Types

- typedef std::map< unsigned long, [SmartPointer](#)< [Segment](#) > > [SegmentMap](#)

Protected Member Functions

- bool [ReadSegment](#) (const [Item](#) &segmentItem, const unsigned int idx)
- bool [ReadSegments](#) ()

Protected Attributes

- [SegmentMap](#) [Segments](#)

25.229.1 Detailed Description

This class defines a segment reader. It reads attributes of group 0x0062.

See Also

PS 3.3 C.8.20.2 and C.8.23

25.229.2 Member Typedef Documentation

25.229.2.1 `typedef std::map< unsigned long, SmartPointer< Segment > > gdcm::SegmentReader::SegmentMap [protected]`

25.229.2.2 `typedef std::vector< SmartPointer< Segment > > gdcm::SegmentReader::SegmentVector`

25.229.3 Constructor & Destructor Documentation

25.229.3.1 `gdcm::SegmentReader::SegmentReader ()`

25.229.3.2 `virtual gdcm::SegmentReader::~SegmentReader () [virtual]`

25.229.4 Member Function Documentation

25.229.4.1 `const SegmentVector gdcm::SegmentReader::GetSegments () const`

25.229.4.2 `SegmentVector` `gdcm::SegmentReader::GetSegments ()`

25.229.4.3 `virtual bool` `gdcm::SegmentReader::Read ()` `[virtual]`

Read.

Reimplemented from [gdcm::Reader](#).

Reimplemented in [gdcm::SurfaceReader](#).

25.229.4.4 `bool` `gdcm::SegmentReader::ReadSegment (const Item & segmentItem, const unsigned int idx)` `[protected]`

25.229.4.5 `bool` `gdcm::SegmentReader::ReadSegments ()` `[protected]`

25.229.5 Member Data Documentation

25.229.5.1 `SegmentMap` `gdcm::SegmentReader::Segments` `[protected]`

The documentation for this class was generated from the following file:


- [gdcmSegmentReader.h](#)

25.230 gdcm::SegmentWriter Class Reference


This class defines a segment writer. It writes attributes of group 0x0062.

```
#include <gdcmSegmentWriter.h>
```

Inheritance diagram for `gdcm::SegmentWriter`:



Collaboration diagram for `gdcm::SegmentWriter`:



Public Types

- typedef `std::vector`
`< SmartPointer< Segment > > SegmentVector`

Public Member Functions

- [SegmentWriter](#) ()
- virtual `~SegmentWriter` ()
- void [AddSegment](#) ([SmartPointer](#)< [Segment](#) > segment)
- unsigned int [GetNumberOfSegments](#) () const
- [SmartPointer](#)< [Segment](#) > [GetSegment](#) (const unsigned int idx=0) const
- const [SegmentVector](#) & [GetSegments](#) () const
- [SegmentVector](#) & [GetSegments](#) ()
- void [SetNumberOfSegments](#) (const unsigned int size)
- void [SetSegments](#) ([SegmentVector](#) &segments)
- bool [Write](#) ()

Write.

Protected Member Functions

- bool [PrepareWrite](#) ()

Protected Attributes

- [SegmentVector](#) [Segments](#)

25.230.1 Detailed Description

This class defines a segment writer. It writes attributes of group 0x0062.

See Also

PS 3.3 C.8.20.2 and C.8.23

25.230.2 Member Typedef Documentation

25.230.2.1 `typedef std::vector< SmartPointer< Segment > > gdcm::SegmentWriter::SegmentVector`

25.230.3 Constructor & Destructor Documentation

25.230.3.1 `gdcm::SegmentWriter::SegmentWriter ()`

25.230.3.2 `virtual gdcm::SegmentWriter::~~SegmentWriter () [virtual]`

25.230.4 Member Function Documentation

25.230.4.1 `void gdcm::SegmentWriter::AddSegment (SmartPointer< Segment > segment)`

25.230.4.2 `unsigned int gdcm::SegmentWriter::GetNumberOfSegments () const`

25.230.4.3 `SmartPointer< Segment > gdcm::SegmentWriter::GetSegment (const unsigned int idx = 0) const`

25.230.4.4 `const SegmentVector& gdcm::SegmentWriter::GetSegments () const`

25.230.4.5 `SegmentVector& gdcm::SegmentWriter::GetSegments ()`

25.230.4.6 `bool gdcm::SegmentWriter::PrepareWrite () [protected]`

25.230.4.7 `void gdcm::SegmentWriter::SetNumberOfSegments (const unsigned int size)`

25.230.4.8 `void gdcm::SegmentWriter::SetSegments (SegmentVector & segments)`

25.230.4.9 `bool gdcm::SegmentWriter::Write () [virtual]`

Write.

Reimplemented from [gdcm::Writer](#).

Reimplemented in [gdcm::SurfaceWriter](#).

25.230.5 Member Data Documentation

25.230.5.1 `SegmentVector gdcm::SegmentWriter::Segments [protected]`

The documentation for this class was generated from the following file:


- [gdcmSegmentWriter.h](#)

25.231 gdcm::SequenceOfFragments Class Reference


Class to represent a Sequence Of Fragments.

```
#include <gdcmSequenceOfFragments.h>
```

Inheritance diagram for `gdcM::SequenceOfFragments`:



Collaboration diagram for `gdcM::SequenceOfFragments`:



Public Types

- typedef `FragmentVector::const_iterator` [ConstIterator](#)
- typedef `std::vector< Fragment >` [FragmentVector](#)
- typedef `FragmentVector::iterator` [Iterator](#)
- typedef `FragmentVector::size_type` [SizeType](#)

Public Member Functions

- [SequenceOfFragments](#) ()
constructor (UndefinedLength by default)
- void [AddFragment](#) ([Fragment](#) const &item)
Appends a [Fragment](#) to the already added ones.
- [Iterator Begin](#) ()
- [ConstIterator Begin](#) () const
- void [Clear](#) ()
Clear.
- unsigned long [ComputeByteLength](#) () const
- [VL ComputeLength](#) () const
- [Iterator End](#) ()
- [ConstIterator End](#) () const
- bool [GetBuffer](#) (char *buffer, unsigned long length) const
- bool [GetFragBuffer](#) (unsigned int fragNb, char *buffer, unsigned long &length) const
- const [Fragment](#) & [GetFragment](#) ([SizeType](#) num) const
- [VL GetLength](#) () const
Returns the SQ length, as read from disk.
- [SizeType GetNumberOfFragments](#) () const
- const [BasicOffsetTable](#) & [GetTable](#) () const
- [BasicOffsetTable](#) & [GetTable](#) ()
- bool [operator==](#) (const [Value](#) &val) const
- void [Print](#) (std::ostream &os) const
- template<typename TSwap >
std::istream & [Read](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadPreValue](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadValue](#) (std::istream &is)
- void [SetLength](#) ([VL](#) length)
Sets the actual SQ length.
- template<typename TSwap >
std::ostream const & [Write](#) (std::ostream &os) const
- bool [WriteBuffer](#) (std::ostream &os) const

Static Public Member Functions

- static [SmartPointer](#)
< [SequenceOfFragments](#) > [New](#) ()

Additional Inherited Members

25.231.1 Detailed Description

Class to represent a Sequence Of Fragments.

Todo I do not enforce that Sequence of Fragments ends with a SQ end del

Examples:

[FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), and [GetJPEGSamplePrecision.cxx](#).

25.231.2 Member Typedef Documentation

25.231.2.1 `typedef FragmentVector::const_iterator gdcmm::SequenceOfFragments::ConstIterator`

25.231.2.2 `typedef std::vector<Fragment> gdcmm::SequenceOfFragments::FragmentVector`

25.231.2.3 `typedef FragmentVector::iterator gdcmm::SequenceOfFragments::Iterator`

25.231.2.4 `typedef FragmentVector::size_type gdcmm::SequenceOfFragments::SizeType`

25.231.3 Constructor & Destructor Documentation

25.231.3.1 `gdcmm::SequenceOfFragments::SequenceOfFragments () [inline]`

constructor (UndefinedLength by default)

25.231.4 Member Function Documentation

25.231.4.1 `void gdcmm::SequenceOfFragments::AddFragment (Fragment const & item)`

Appends a [Fragment](#) to the already added ones.

Examples:

[FixBrokenJ2K.cxx](#).

25.231.4.2 `Iterator gdcmm::SequenceOfFragments::Begin () [inline]`

25.231.4.3 `ConstIterator gdcmm::SequenceOfFragments::Begin () const [inline]`

25.231.4.4 `void gdcmm::SequenceOfFragments::Clear () [virtual]`

Clear.

Implements [gdcmm::Value](#).

25.231.4.5 `unsigned long gdcmm::SequenceOfFragments::ComputeByteLength () const`

25.231.4.6 `VL gdcmm::SequenceOfFragments::ComputeLength () const`

25.231.4.7 `Iterator gdcmm::SequenceOfFragments::End () [inline]`

25.231.4.8 `ConstIterator gdcmm::SequenceOfFragments::End () const [inline]`

25.231.4.9 `bool gdcmm::SequenceOfFragments::GetBuffer (char * buffer, unsigned long length) const`

25.231.4.10 `bool gdcmm::SequenceOfFragments::GetFragBuffer (unsigned int fragNb, char * buffer, unsigned long & length) const`

25.231.4.11 `const Fragment& gdcm::SequenceOfFragments::GetFragment (SizeType num) const`

Examples:

[FixBrokenJ2K.cxx](#), and [FixJAIBugJPEGLS.cxx](#).

25.231.4.12 `VL gdcm::SequenceOfFragments::GetLength () const [inline],[virtual]`

Returns the SQ length, as read from disk.

Implements [gdcm::Value](#).

25.231.4.13 `SizeType gdcm::SequenceOfFragments::GetNumberOfFragments () const`

Examples:

[FixJAIBugJPEGLS.cxx](#).

25.231.4.14 `const BasicOffsetTable& gdcm::SequenceOfFragments::GetTable () const [inline]`

25.231.4.15 `BasicOffsetTable& gdcm::SequenceOfFragments::GetTable () [inline]`

25.231.4.16 `static SmartPointer<SequenceOfFragments> gdcm::SequenceOfFragments::New () [inline],
[static]`

25.231.4.17 `bool gdcm::SequenceOfFragments::operator== (const Value & val) const [inline],[virtual]`

Implements [gdcm::Value](#).

25.231.4.18 `void gdcm::SequenceOfFragments::Print (std::ostream & os) const [inline],[virtual]`

Reimplemented from [gdcm::Object](#).

25.231.4.19 `template<typename TSwap > std::istream& gdcm::SequenceOfFragments::Read (std::istream & is) [inline]`

25.231.4.20 `template<typename TSwap > std::istream& gdcm::SequenceOfFragments::ReadPreValue (std::istream & is)
[inline]`

References [gdcmDebugMacro](#), and [gdcm::DataElement::SetByteValue\(\)](#).

25.231.4.21 `template<typename TSwap > std::istream& gdcm::SequenceOfFragments::ReadValue (std::istream & is)
[inline]`

References [gdcmAssertAlwaysMacro](#), [gdcmDebugMacro](#), [gdcmWarningMacro](#), [gdcm::Tag::GetElement\(\)](#), [gdcm::Tag::GetGroup\(\)](#), [gdcm::ByteValue::GetLength\(\)](#), [gdcm::ByteValue::GetPointer\(\)](#), [gdcm::DataElement::GetTag\(\)](#), [gdcm::DataElement::GetVL\(\)](#), [gdcm::Fragment::Read\(\)](#), [gdcm::Fragment::ReadBacktrack\(\)](#), and [gdcm::Exception::what\(\)](#).

25.231.4.22 `void gdcM::SequenceOfFragments::SetLength (VL length) [inline],[virtual]`

Sets the actual SQ length.

Implements [gdcM::Value](#).

25.231.4.23 `template<typename TSwap > std::ostream const& gdcM::SequenceOfFragments::Write (std::ostream & os) const [inline]`

References [gdcM::VL::Write\(\)](#), and [gdcM::Tag::Write\(\)](#).

25.231.4.24 `bool gdcM::SequenceOfFragments::WriteBuffer (std::ostream & os) const`

Examples:

[GetJPEGSamplePrecision.cxx](#).

The documentation for this class was generated from the following file:


- [gdcMSequenceOfFragments.h](#)

25.232 gdcM::SequenceOfItems Class Reference


Class to represent a Sequence Of Items (value representation : SQ)

```
#include <gdcMSequenceOfItems.h>
```

Inheritance diagram for `gdcM::SequenceOfItems`:



Collaboration diagram for gdcm::SequenceOfItems:



Public Types

- typedef `ItemVector::const_iterator` [ConstIterator](#)
- typedef `std::vector< Item >` [ItemVector](#)
- typedef `ItemVector::iterator` [Iterator](#)
- typedef `ItemVector::size_type` [SizeType](#)

Public Member Functions

- [SequenceOfItems](#) ()
constructor (UndefinedLength by default)
- void [AddItem](#) ([Item](#) const &item)
Appends an Item to the already added ones.
- [Iterator](#) [Begin](#) ()
- [ConstIterator](#) [Begin](#) () const
- void [Clear](#) ()
- template<typename TDE >
[VL](#) [ComputeLength](#) () const
- [Iterator](#) [End](#) ()
- [ConstIterator](#) [End](#) () const
- bool [FindDataElement](#) (const [Tag](#) &t) const

- const [Item](#) & [GetItem](#) ([SizeType](#) position) const
- [Item](#) & [GetItem](#) ([SizeType](#) position)
- [VL GetLength](#) () const
Returns the SQ length, as read from disk.
- [SizeType GetNumberOfItems](#) () const
- bool [IsUndefinedLength](#) () const
return if [Value](#) Length if of undefined length
- [SequenceOfItems](#) & [operator=](#) (const [SequenceOfItems](#) &val)
- bool [operator==](#) (const [Value](#) &val) const
- void [Print](#) (std::ostream &os) const
- template<typename TDE , typename TSwap >
std::istream & [Read](#) (std::istream &is)
- void [SetLength](#) ([VL](#) length)
Sets the actual SQ length.
- void [SetLengthToUndefined](#) ()
Properly set the Sequence of [Item](#) to be undefined length.
- void [SetNumberOfItems](#) ([SizeType](#) n)
- template<typename TDE , typename TSwap >
std::ostream const & [Write](#) (std::ostream &os) const

Static Public Member Functions

- static [SmartPointer](#)
< [SequenceOfItems](#) > [New](#) ()

Public Attributes

- [ItemVector Items](#)
Vector of Sequence Items.
- [VL SequenceLengthField](#)
Total length of the Sequence (or 0xffffffff) if undefined.

Additional Inherited Members

25.232.1 Detailed Description

Class to represent a Sequence Of Items (value representation : SQ)

- a [Value](#) Representation for Data Elements that contains a sequence of Data Sets.
- Sequence of [Item](#) allows for Nested Data Sets

See PS 3.5, 7.4.6 Data [Element Type](#) Within a Sequence

Note

SEQUENCE OF ITEMS (VALUE REPRESENTATION SQ) A [Value](#) Representation for Data Elements that contain a sequence of Data Sets. Sequence of Items allows for Nested Data Sets.

Examples:

[DumpGEMSMovieGroup.cxx](#), [ExtractEncryptedContent.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetSequenceUltrasound.cxx](#), and [ReadExplicitLengthSQIVR.cxx](#).

25.232.2 Member Typedef Documentation

25.232.2.1 `typedef ItemVector::const_iterator gdcm::SequenceOfItems::ConstIterator`

25.232.2.2 `typedef std::vector< Item > gdcm::SequenceOfItems::ItemVector`

25.232.2.3 `typedef ItemVector::iterator gdcm::SequenceOfItems::Iterator`

25.232.2.4 `typedef ItemVector::size_type gdcm::SequenceOfItems::SizeType`

25.232.3 Constructor & Destructor Documentation

25.232.3.1 `gdcm::SequenceOfItems::SequenceOfItems () [inline]`

constructor (UndefinedLength by default)

25.232.4 Member Function Documentation

25.232.4.1 `void gdcm::SequenceOfItems::AddItem (Item const & item)`

Appends an [Item](#) to the already added ones.

Examples:

[Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [GenAllVR.cxx](#), [GenLongSeqs.cxx](#), and [GenSeqs.cxx](#).

25.232.4.2 `Iterator gdcm::SequenceOfItems::Begin () [inline]`

25.232.4.3 `ConstIterator gdcm::SequenceOfItems::Begin () const [inline]`

25.232.4.4 `void gdcm::SequenceOfItems::Clear () [inline],[virtual]`

Implements [gdcm::Value](#).

25.232.4.5 `template<typename TDE > VL gdcm::SequenceOfItems::ComputeLength () const`

25.232.4.6 `Iterator gdcm::SequenceOfItems::End () [inline]`

25.232.4.7 **ConstIterator** `gdcmm::SequenceOfItems::End () const` `[inline]`

25.232.4.8 **bool** `gdcmm::SequenceOfItems::FindDataElement (const Tag & t) const`

25.232.4.9 **const Item&** `gdcmm::SequenceOfItems::GetItem (SizeType position) const`

Examples:

[ChangeSequenceUltrasound.cxx](#), [DumpGEMSMovieGroup.cxx](#), [ExtractEncryptedContent.cxx](#), [gdcmmrtionplan.cxx](#), [gdcmmrtplan.cxx](#), [GetSequenceUltrasound.cxx](#), [LargeVRDSExplicit.cxx](#), and [ReadAndDumpDICOMDIR.cxx](#).

25.232.4.10 **Item&** `gdcmm::SequenceOfItems::GetItem (SizeType position)`

25.232.4.11 **VL** `gdcmm::SequenceOfItems::GetLength () const` `[inline],[virtual]`

Returns the SQ length, as read from disk.

Implements [gdcmm::Value](#).

25.232.4.12 **SizeType** `gdcmm::SequenceOfItems::GetNumberOfItems () const` `[inline]`

Examples:

[ChangeSequenceUltrasound.cxx](#), [DumpGEMSMovieGroup.cxx](#), [ExtractEncryptedContent.cxx](#), [gdcmmrtionplan.cxx](#), [gdcmmrtplan.cxx](#), [GetSequenceUltrasound.cxx](#), and [LargeVRDSExplicit.cxx](#).

25.232.4.13 **bool** `gdcmm::SequenceOfItems::IsUndefinedLength () const` `[inline]`

return if [Value](#) Length if of undefined length

25.232.4.14 **static SmartPointer<SequenceOfItems>** `gdcmm::SequenceOfItems::New ()` `[inline],[static]`

25.232.4.15 **SequenceOfItems&** `gdcmm::SequenceOfItems::operator= (const SequenceOfItems & val)` `[inline]`

References Items, and SequenceLengthField.

25.232.4.16 **bool** `gdcmm::SequenceOfItems::operator==(const Value & val) const` `[inline],[virtual]`

Implements [gdcmm::Value](#).

References Items, and SequenceLengthField.

25.232.4.17 **void** `gdcmm::SequenceOfItems::Print (std::ostream & os) const` `[inline],[virtual]`

Reimplemented from [gdcmm::Object](#).

25.232.4.18 `template<typename TDE , typename TSwap > std::istream& gdcmm::SequenceOfItems::Read (std::istream & is)`
`[inline]`

Examples:

[ReadExplicitLengthSQIVR.cxx](#).

References `gdcmm::Item::Clear()`, `gdcmmDebugMacro`, `gdcmmWarningMacro`, `gdcmm::Exception::GetDescription()`, `gdcmm::Item::GetNestedDataSet()`, `gdcmm::DataElement::GetTag()`, `gdcmm::DataElement::GetVL()`, `gdcmm::Item::Read()`, and `gdcmm::DataSet::Size()`.

25.232.4.19 `void gdcmm::SequenceOfItems::SetLength (VL length)` `[inline]`, `[virtual]`

Sets the actual SQ length.

Implements [gdcmm::Value](#).

Examples:

[ReadExplicitLengthSQIVR.cxx](#).

25.232.4.20 `void gdcmm::SequenceOfItems::SetLengthToUndefined ()`

Properly set the Sequence of [Item](#) to be undefined length.

Examples:

[Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [GenAllIVR.cxx](#), [GenLongSeqs.cxx](#), and [GenSeqs.cxx](#).

25.232.4.21 `void gdcmm::SequenceOfItems::SetNumberOfItems (SizeType n)` `[inline]`

25.232.4.22 `template<typename TDE , typename TSwap > std::ostream const& gdcmm::SequenceOfItems::Write (std::ostream & os) const` `[inline]`

References `gdcmm::VL::Write()`, and `gdcmm::Tag::Write()`.

25.232.5 Member Data Documentation

25.232.5.1 ItemVector `gdcmm::SequenceOfItems::Items`

Vector of Sequence Items.

Referenced by `operator=()`, and `operator==()`.

25.232.5.2 VL `gdcmm::SequenceOfItems::SequenceLengthField`

Total length of the Sequence (or 0xffffffff) if undefined.

Referenced by `operator=()`, and `operator==()`.

The documentation for this class was generated from the following file:


- [gdcmSequenceOfItems.h](#)

25.233 gdcm::SerieHelper Class Reference

[SerieHelper](#) DO NOT USE this class, it is only a temporary solution for ITK migration from GDCM 1.x to GDCM 2.x It will disappear soon, you've been warned.

```
#include <gdcmSerieHelper.h>
```

Collaboration diagram for gdcm::SerieHelper:



Classes

- struct [Rule](#)

Public Member Functions

- [SerieHelper](#) ()
- [~SerieHelper](#) ()
- void [AddRestriction](#) (const std::string &tag)
- void [AddRestriction](#) (uint16_t group, uint16_t elem, std::string const &value, int op)
- void [Clear](#) ()
- void [CreateDefaultUniqueSeriesIdentifier](#) ()
- std::string [CreateUniqueSeriesIdentifier](#) (File *inFile)
- FileList * [GetFirstSingleSerieUIDFileSet](#) ()
- FileList * [GetNextSingleSerieUIDFileSet](#) ()

- void [OrderFileList](#) ([FileList](#) *fileSet)
- void [SetDirectory](#) (std::string const &dir, bool recursive=false)
- void [SetLoadMode](#) (int)
- void [SetUseSeriesDetails](#) (bool useSeriesDetails)

Protected Types

- typedef std::vector< [Rule](#) > [SerieRestrictions](#)
- typedef std::map< std::string, [FileList](#) * > [SingleSerieUIDFileSetmap](#)

Protected Member Functions

- bool [AddFile](#) ([FileWithName](#) &header)
- void [AddFileName](#) (std::string const &filename)
- void [AddRestriction](#) (const [Tag](#) &tag)
- bool [FileNameOrdering](#) ([FileList](#) *fileList)
- bool [ImagePositionPatientOrdering](#) ([FileList](#) *fileSet)
- bool [UserOrdering](#) ([FileList](#) *fileSet)

Protected Attributes

- [SingleSerieUIDFileSetmap::iterator](#) [ItFileSetHt](#)
- [SingleSerieUIDFileSetmap](#) [SingleSerieUIDFileSetHT](#)

25.233.1 Detailed Description

[SerieHelper](#) DO NOT USE this class, it is only a temporary solution for ITK migration from GDCM 1.x to GDCM 2.x It will disappear soon, you've been warned.

Instead see [gdcm::ImageHelper](#) or [gdcm::IPPSorter](#)

25.233.2 Member Typedef Documentation

25.233.2.1 typedef std::vector<[Rule](#)> [gdcm::SerieHelper::SerieRestrictions](#) [protected]

25.233.2.2 typedef std::map<std::string, [FileList](#) *> [gdcm::SerieHelper::SingleSerieUIDFileSetmap](#) [protected]

25.233.3 Constructor & Destructor Documentation

25.233.3.1 [gdcm::SerieHelper::SerieHelper](#) ()

25.233.3.2 [gdcm::SerieHelper::~~SerieHelper](#) ()

25.233.4 Member Function Documentation

25.233.4.1 bool [gdcm::SerieHelper::AddFile](#) ([FileWithName](#) & *header*) [protected]

```

25.233.4.2 void gdcm::SerieHelper::AddFileName ( std::string const & filename ) [protected]

25.233.4.3 void gdcm::SerieHelper::AddRestriction ( const std::string & tag )

25.233.4.4 void gdcm::SerieHelper::AddRestriction ( uint16_t group, uint16_t elem, std::string const & value, int op )

25.233.4.5 void gdcm::SerieHelper::AddRestriction ( const Tag & tag ) [protected]

25.233.4.6 void gdcm::SerieHelper::Clear ( )

25.233.4.7 void gdcm::SerieHelper::CreateDefaultUniqueSeriesIdentifier ( )

25.233.4.8 std::string gdcm::SerieHelper::CreateUniqueSeriesIdentifier ( File * inFile )

25.233.4.9 bool gdcm::SerieHelper::FileNameOrdering ( FileList * fileList ) [protected]

25.233.4.10 FileList* gdcm::SerieHelper::GetFirstSingleSerieUIDFileSet ( )

25.233.4.11 FileList* gdcm::SerieHelper::GetNextSingleSerieUIDFileSet ( )

25.233.4.12 bool gdcm::SerieHelper::ImagePositionPatientOrdering ( FileList * fileSet ) [protected]

25.233.4.13 void gdcm::SerieHelper::OrderFileList ( FileList * fileSet )

25.233.4.14 void gdcm::SerieHelper::SetDirectory ( std::string const & dir, bool recursive = false )

25.233.4.15 void gdcm::SerieHelper::SetLoadMode ( int ) [inline]

25.233.4.16 void gdcm::SerieHelper::SetUseSeriesDetails ( bool useSeriesDetails )

25.233.4.17 bool gdcm::SerieHelper::UserOrdering ( FileList * fileSet ) [protected]

```

25.233.5 Member Data Documentation

```

25.233.5.1 SingleSerieUIDFileSetmap::iterator gdcm::SerieHelper::ItFileSetHt [protected]

25.233.5.2 SingleSerieUIDFileSetmap gdcm::SerieHelper::SingleSerieUIDFileSetHT [protected]

```

The documentation for this class was generated from the following file:

- [gdcmSerieHelper.h](#)

25.234 gdcm::Series Class Reference

[Series.](#)

```
#include <gdcmSeries.h>
```

Public Member Functions

- [Series \(\)](#)

25.234.1 Detailed Description

[Series](#).

25.234.2 Constructor & Destructor Documentation

25.234.2.1 gdcm::Series::Series () [inline]

The documentation for this class was generated from the following file:

- [gdcmSeries.h](#)

25.235 gdcm::network::ServiceClassApplicationInformation Class Reference

```
#include <gdcmServiceClassApplicationInformation.h>
```

Public Member Functions

- [ServiceClassApplicationInformation](#) ()
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- void [SetTuple](#) (uint8_t levelofsupport, uint8_t levelofdigitalsig, uint8_t elementcoercion)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.235.1 Detailed Description

PS 3.4 [Table B.3-1](#) SERVICE-CLASS-APPLICATION-INFORMATION (A-ASSOCIATE-RQ)

25.235.2 Constructor & Destructor Documentation

25.235.2.1 gdcm::network::ServiceClassApplicationInformation::ServiceClassApplicationInformation ()

25.235.3 Member Function Documentation

25.235.3.1 void gdcm::network::ServiceClassApplicationInformation::Print (std::ostream & os) const

25.235.3.2 std::istream& gdcm::network::ServiceClassApplicationInformation::Read (std::istream & is)

25.235.3.3 void gdcm::network::ServiceClassApplicationInformation::SetTuple (uint8_t *levelofsupport*, uint8_t *levelofdigitalsig*, uint8_t *elementcoercion*)

25.235.3.4 size_t gdcm::network::ServiceClassApplicationInformation::Size () const

25.235.3.5 const std::ostream& gdcm::network::ServiceClassApplicationInformation::Write (std::ostream & os) const

The documentation for this class was generated from the following file:


- [gdcmServiceClassApplicationInformation.h](#)

25.236 gdcm::ServiceClassUser Class Reference


[ServiceClassUser](#).

```
#include <gdcmServiceClassUser.h>
```

Inheritance diagram for gdcm::ServiceClassUser:



Collaboration diagram for gdcm::ServiceClassUser:



Public Member Functions

- [ServiceClassUser](#) ()

- [~ServiceClassUser](#) ()
- const char * [GetAETitle](#) () const
- const char * [GetCalledAETitle](#) () const
- double [GetTimeout](#) () const
- bool [InitializeConnection](#) ()
- bool [IsPresentationContextAccepted](#) (const [PresentationContext](#) &pc) const
Return if the passed in presentation was accepted during association negotiation.
- bool [SendEcho](#) ()
C-ECHO.
- bool [SendFind](#) (const [BaseRootQuery](#) *query, std::vector< [DataSet](#) > &retDatasets)
C-FIND a query, return result are in retDatasets.
- bool [SendMove](#) (const [BaseRootQuery](#) *query, const char *outputdir)
Execute a C-MOVE, based on query, return files are written in outputdir.
- bool [SendMove](#) (const [BaseRootQuery](#) *query, std::vector< [DataSet](#) > &retDatasets)
Execute a C-MOVE, based on query, returned dataset are Implicit.
- bool [SendMove](#) (const [BaseRootQuery](#) *query, std::vector< [File](#) > &retFile)
Execute a C-MOVE, based on query, returned Files are stored in vector.
- bool [SendStore](#) (const char *filename)
Execute a C-STORE on file on disk, named filename.
- bool [SendStore](#) ([File](#) const &file)
- bool [SendStore](#) ([DataSet](#) const &ds)
Execute a C-STORE on a DataSet, the transfer syntax used will be Implicit.
- void [SetAETitle](#) (const char *aetitle)
set calling ae title
- void [SetCalledAETitle](#) (const char *aetitle)
set called ae title
- void [SetHostname](#) (const char *hostname)
Set the name of the called hostname (hostname or IP address)
- void [SetPort](#) (uint16_t port)
Set port of remote host (called application)
- void [SetPortSCP](#) (uint16_t portscp)
Set the port for any incoming C-STORE-SCP operation (typically in a return of C-MOVE)
- void [SetPresentationContexts](#) (std::vector< [PresentationContext](#) > const &pcs)
Set the Presentation Context used for the Association.
- void [SetTimeout](#) (double t)
set/get Timeout
- bool [StartAssociation](#) ()
Start the association. Need to call SetPresentationContexts before.
- bool [StopAssociation](#) ()
Stop the running association.

Additional Inherited Members

25.236.1 Detailed Description

[ServiceClassUser](#).

Examples:

[CStoreQtProgress.cxx](#).

25.236.2 Constructor & Destructor Documentation

25.236.2.1 `gdcmm::ServiceClassUser::ServiceClassUser ()`

Construct a SCU with default:

- hostname = localhost
- port = 104

25.236.2.2 `gdcmm::ServiceClassUser::~~ServiceClassUser ()`

25.236.3 Member Function Documentation

25.236.3.1 `const char* gdcmm::ServiceClassUser::GetAETitle () const`

25.236.3.2 `const char* gdcmm::ServiceClassUser::GetCalledAETitle () const`

25.236.3.3 `double gdcmm::ServiceClassUser::GetTimeout () const`

25.236.3.4 `bool gdcmm::ServiceClassUser::InitializeConnection ()`

Will try to connect This will setup the actual timeout used during the whole connection time. Need to call SetTimeout first

Examples:

[CStoreQtProgress.cxx](#).

25.236.3.5 `bool gdcmm::ServiceClassUser::IsPresentationContextAccepted (const PresentationContext & pc) const`

Return if the passed in presentation was accepted during association negotiation.

25.236.3.6 `bool gdcmm::ServiceClassUser::SendEcho ()`

C-ECHO.

25.236.3.7 `bool gdcmm::ServiceClassUser::SendFind (const BaseRootQuery * query, std::vector< DataSet > & retDatasets)`

C-FIND a query, return result are in retDatasets.

25.236.3.8 `bool gdcmm::ServiceClassUser::SendMove (const BaseRootQuery * query, const char * outputdir)`

Execute a C-MOVE, based on query, return files are written in outputdir.

25.236.3.9 `bool gdcmm::ServiceClassUser::SendMove (const BaseRootQuery * query, std::vector< DataSet > & retDatasets)`

Execute a C-MOVE, based on query, returned dataset are Implicit.

25.236.3.10 `bool gdcm::ServiceClassUser::SendMove (const BaseRootQuery * query, std::vector< File > & retFile)`

Execute a C-MOVE, based on query, returned Files are stored in vector.

25.236.3.11 `bool gdcm::ServiceClassUser::SendStore (const char * filename)`

Execute a C-STORE on file on disk, named filename.

Examples:

[CStoreQtProgress.cxx](#).

25.236.3.12 `bool gdcm::ServiceClassUser::SendStore (File const & file)`

Execute a C-STORE on a [File](#), the transfer syntax used for the query is based on the file.

25.236.3.13 `bool gdcm::ServiceClassUser::SendStore (DataSet const & ds)`

Execute a C-STORE on a [DataSet](#), the transfer syntax used will be Implicit.

25.236.3.14 `void gdcm::ServiceClassUser::SetAETitle (const char * aetitle)`

set calling ae title

25.236.3.15 `void gdcm::ServiceClassUser::SetCalledAETitle (const char * aetitle)`

set called ae title

Examples:

[CStoreQtProgress.cxx](#).

25.236.3.16 `void gdcm::ServiceClassUser::SetHostname (const char * hostname)`

Set the name of the called hostname (hostname or IP address)

Examples:

[CStoreQtProgress.cxx](#).

25.236.3.17 `void gdcm::ServiceClassUser::SetPort (uint16_t port)`

Set port of remote host (called application)

Examples:

[CStoreQtProgress.cxx](#).

25.236.3.18 void `gdcm::ServiceClassUser::SetPortSCP (uint16_t portscp)`

Set the port for any incoming C-STORE-SCP operation (typically in a return of C-MOVE)

25.236.3.19 void `gdcm::ServiceClassUser::SetPresentationContexts (std::vector< PresentationContext > const & pcs)`

Set the Presentation Context used for the Association.

Examples:

[CStoreQtProgress.cxx](#).

25.236.3.20 void `gdcm::ServiceClassUser::SetTimeout (double t)`

set/get Timeout

Examples:

[CStoreQtProgress.cxx](#).

25.236.3.21 bool `gdcm::ServiceClassUser::StartAssociation ()`

Start the association. Need to call `SetPresentationContexts` before.

Examples:

[CStoreQtProgress.cxx](#).

25.236.3.22 bool `gdcm::ServiceClassUser::StopAssociation ()`

Stop the running association.

Examples:

[CStoreQtProgress.cxx](#).

The documentation for this class was generated from the following file:

- [gdcmServiceClassUser.h](#)

25.237 gdcm::SHA1 Class Reference

Class for [SHA1](#).

```
#include <gdcmSHA1.h>
```

Public Member Functions

- [SHA1](#) ()
- [~SHA1](#) ()

Static Public Member Functions

- static bool [Compute](#) (const char *buffer, unsigned long buf_len, char digest_str[20 *2+1])
- static bool [ComputeFile](#) (const char *filename, char digest_str[20 *2+1])

25.237.1 Detailed Description

Class for [SHA1](#).

Warning

this class is able to pick from one implementation:

1. the one from OpenSSL (when GDCM_USE_SYSTEM_OPENSSL is turned ON)

In all other cases it will return an error

25.237.2 Constructor & Destructor Documentation

25.237.2.1 `gdcm::SHA1::SHA1 ()`

25.237.2.2 `gdcm::SHA1::~~SHA1 ()`

25.237.3 Member Function Documentation

25.237.3.1 `static bool gdcm::SHA1::Compute (const char * buffer, unsigned long buf_len, char digest_str[20 *2+1])`
[static]

25.237.3.2 `static bool gdcm::SHA1::ComputeFile (const char * filename, char digest_str[20 *2+1])` [static]

The documentation for this class was generated from the following file:


- [gdcmSHA1.h](#)

25.238 gdcm::SimpleMemberCommand< T > Class Template Reference


[Command](#) subclass that calls a pointer to a member function.

```
#include <gdcmCommand.h>
```

Inheritance diagram for `gdcm::SimpleMemberCommand< T >`:



Collaboration diagram for `gdcm::SimpleMemberCommand< T >`:



Public Types

- typedef [SimpleMemberCommand Self](#)
- typedef void(T::* [TMemberFunctionPointer](#))()

Public Member Functions

- virtual void [Execute](#) ([Subject](#) *, const [Event](#) &)
- virtual void [Execute](#) (const [Subject](#) *, const [Event](#) &)
- void [SetCallbackFunction](#) (T *object, [TMemberFunctionPointer](#) memberFunction)

Static Public Member Functions

- static [SmartPointer](#)
< [SimpleMemberCommand](#) > [New](#) ()

Protected Member Functions

- [SimpleMemberCommand](#) ()
- virtual [~SimpleMemberCommand](#) ()

Protected Attributes

- [TMemberFunctionPointer m_MemberFunction](#)
- T * [m_This](#)

25.238.1 Detailed Description

template<typename T>class gdcm::SimpleMemberCommand< T >

[Command](#) subclass that calls a pointer to a member function.

[SimpleMemberCommand](#) calls a pointer to a member function with no arguments.

25.238.2 Member Typedef Documentation

25.238.2.1 template<typename T > typedef [SimpleMemberCommand](#) gdcm::SimpleMemberCommand< T >::Self

Standard class typedefs.

25.238.2.2 template<typename T > typedef void(T::* [gdcm::SimpleMemberCommand](#)< T >::TMemberFunctionPointer)()

A method callback.

25.238.3 Constructor & Destructor Documentation

25.238.3.1 `template<typename T > gdcm::SimpleMemberCommand< T >::SimpleMemberCommand ()`
`[inline], [protected]`

Referenced by `gdcm::SimpleMemberCommand< T >::New()`.

25.238.3.2 `template<typename T > virtual gdcm::SimpleMemberCommand< T >::~~SimpleMemberCommand ()`
`[inline], [protected], [virtual]`

25.238.4 Member Function Documentation

25.238.4.1 `template<typename T > virtual void gdcm::SimpleMemberCommand< T >::Execute (Subject *, const Event &)` `[inline], [virtual]`

Invoke the callback function.

Implements [gdcm::Command](#).

References `gdcm::SimpleMemberCommand< T >::m_MemberFunction`.

25.238.4.2 `template<typename T > virtual void gdcm::SimpleMemberCommand< T >::Execute (const Subject * caller, const Event & event)` `[inline], [virtual]`

Abstract method that defines the action to be taken by the command. This variant is expected to be used when requests comes from a [const Object](#)

Implements [gdcm::Command](#).

References `gdcm::SimpleMemberCommand< T >::m_MemberFunction`.

25.238.4.3 `template<typename T > static SmartPointer<SimpleMemberCommand> gdcm::SimpleMemberCommand< T >::New ()` `[inline], [static]`

Run-time type information (and related methods). Method for creation through the object factory.

References `gdcm::SimpleMemberCommand< T >::SimpleMemberCommand()`.

25.238.4.4 `template<typename T > void gdcm::SimpleMemberCommand< T >::SetCallbackFunction (T * object, TMemberFunctionPointer memberFunction)` `[inline]`

Specify the callback function.

References `gdcm::SimpleMemberCommand< T >::m_MemberFunction`, and `gdcm::SimpleMemberCommand< T >::m_This`.

25.238.5 Member Data Documentation

25.238.5.1 `template<typename T > TMemberFunctionPointer gdcm::SimpleMemberCommand< T >::m_MemberFunction` `[protected]`

Referenced by `gdcm::SimpleMemberCommand< T >::Execute()`, and `gdcm::SimpleMemberCommand< T >::SetCallbackFunction()`.

25.238.5.2 `template<typename T> T* gdcm::SimpleMemberCommand< T >::m_This` [protected]

Referenced by `gdcm::SimpleMemberCommand< T >::SetCallbackFunction()`.

The documentation for this class was generated from the following file:

- [gdcmCommand.h](#)

25.239 gdcm::SimpleSubjectWatcher Class Reference

[SimpleSubjectWatcher](#) This is a typical [Subject](#) Watcher class. It will observe all events.

```
#include <gdcmSimpleSubjectWatcher.h>
```

Public Member Functions

- [SimpleSubjectWatcher](#) ([Subject](#) *s, const char *comment="")
- virtual [~SimpleSubjectWatcher](#) ()

Protected Member Functions

- virtual void [EndFilter](#) ()
- virtual void [ShowAbort](#) ()
- virtual void [ShowAnonymization](#) ([Subject](#) *caller, const [Event](#) &evt)
- virtual void [ShowData](#) ([Subject](#) *caller, const [Event](#) &evt)
- virtual void [ShowDataSet](#) ([Subject](#) *caller, const [Event](#) &evt)
- virtual void [ShowIteration](#) ()
- virtual void [ShowProgress](#) ([Subject](#) *caller, const [Event](#) &evt)
- virtual void [StartFilter](#) ()
- void [TestAbortOff](#) ()
- void [TestAbortOn](#) ()

25.239.1 Detailed Description

[SimpleSubjectWatcher](#) This is a typical [Subject](#) Watcher class. It will observe all events.

25.239.2 Constructor & Destructor Documentation

25.239.2.1 `gdcm::SimpleSubjectWatcher::SimpleSubjectWatcher (Subject * s, const char * comment = " ")`

25.239.2.2 `virtual gdcm::SimpleSubjectWatcher::~SimpleSubjectWatcher ()` [virtual]

25.239.3 Member Function Documentation

25.239.3.1 `virtual void gdcm::SimpleSubjectWatcher::EndFilter ()` [protected],[virtual]

25.239.3.2 `virtual void gdcm::SimpleSubjectWatcher::ShowAbort ()` [protected],[virtual]

- 25.239.3.3 `virtual void gdcM::SimpleSubjectWatcher::ShowAnonymization (Subject * caller, const Event & evt)` [protected], [virtual]
- 25.239.3.4 `virtual void gdcM::SimpleSubjectWatcher::ShowData (Subject * caller, const Event & evt)` [protected], [virtual]
- 25.239.3.5 `virtual void gdcM::SimpleSubjectWatcher::ShowDataSet (Subject * caller, const Event & evt)` [protected], [virtual]
- 25.239.3.6 `virtual void gdcM::SimpleSubjectWatcher::ShowIteration ()` [protected], [virtual]
- 25.239.3.7 `virtual void gdcM::SimpleSubjectWatcher::ShowProgress (Subject * caller, const Event & evt)` [protected], [virtual]
- 25.239.3.8 `virtual void gdcM::SimpleSubjectWatcher::StartFilter ()` [protected], [virtual]
- 25.239.3.9 `void gdcM::SimpleSubjectWatcher::TestAbortOff ()` [protected]
- 25.239.3.10 `void gdcM::SimpleSubjectWatcher::TestAbortOn ()` [protected]

The documentation for this class was generated from the following file:


- [gdcMSimpleSubjectWatcher.h](#)

25.240 `gdcM::SmartPointer< ObjectType >` Class Template Reference

Class for Smart Pointer.

```
#include <gdcMObject.h>
```

Inheritance diagram for gdcM::SmartPointer< ObjectType >:



Public Member Functions

- `SmartPointer()`
- `SmartPointer(const SmartPointer< ObjectType > &p)`
- `SmartPointer(ObjectType *p)`
- `SmartPointer(ObjectType const &p)`
- `~SmartPointer()`
- `ObjectType * GetPointer() const`
Explicit function to retrieve the pointer.
- `operator ObjectType*() const`
Return pointer to object.
- `ObjectType & operator*() const`
- `ObjectType * operator->() const`
Overload operator ->
- `SmartPointer & operator=(SmartPointer const &r)`

Overload operator assignment.

- `SmartPointer` & `operator=` (ObjectType *r)

Overload operator assignment.

- `SmartPointer` & `operator=` (ObjectType const &r)

25.240.1 Detailed Description

```
template<class ObjectType>class gdcmm::SmartPointer< ObjectType >
```

Class for Smart Pointer.

Will only work for subclass of `gdcmm::Object` See `tr1/shared_ptr` for a more general approach (not invasive) `#include <tr1/memory> { shared_ptr<Bla> b(new Bla); }`

Note

Class partly based on post by Bill Hubauer: <http://groups.google.com/group/comp.lang.c++.msg/173ddc38a827a930>

See Also

<http://www.davethehat.com/articles/smartp.htm>

and `itk::SmartPointer`

Examples:

[ChangeSequenceUltrasound.cxx](#), [CStoreQtProgress.cxx](#), [DumpGEMSMovieGroup.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [FixBrokenJ2K.cxx](#), [gdcmmrtionplan.cxx](#), [gdcmmrtplan.cxx](#), [Gen-AllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetSubSequenceData.cxx](#), [LargeVRDS-Explicit.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), and [ReadExplicitLengthSQIVR.cxx](#).

25.240.2 Constructor & Destructor Documentation

25.240.2.1 `template<class ObjectType> gdcmm::SmartPointer< ObjectType >::SmartPointer () [inline]`

25.240.2.2 `template<class ObjectType> gdcmm::SmartPointer< ObjectType >::SmartPointer (const SmartPointer< ObjectType > & p) [inline]`

25.240.2.3 `template<class ObjectType> gdcmm::SmartPointer< ObjectType >::SmartPointer (ObjectType * p) [inline]`

25.240.2.4 `template<class ObjectType> gdcmm::SmartPointer< ObjectType >::SmartPointer (ObjectType const & p) [inline]`

25.240.2.5 `template<class ObjectType> gdcmm::SmartPointer< ObjectType >::~~SmartPointer () [inline]`

25.240.3 Member Function Documentation

25.240.3.1 `template<class ObjectType> ObjectType* gdcmm::SmartPointer< ObjectType >::GetPointer () const [inline]`

Explicit function to retrieve the pointer.

25.240.3.2 `template<class ObjectType> gdcm::SmartPointer< ObjectType >::operator ObjectType * () const`
`[inline]`

Return pointer to object.

25.240.3.3 `template<class ObjectType> ObjectType& gdcm::SmartPointer< ObjectType >::operator* () const`
`[inline]`

25.240.3.4 `template<class ObjectType> ObjectType* gdcm::SmartPointer< ObjectType >::operator-> () const`
`[inline]`

Overload operator ->

25.240.3.5 `template<class ObjectType> SmartPointer& gdcm::SmartPointer< ObjectType >::operator= (SmartPointer< ObjectType > const & r)` `[inline]`

Overload operator assignment.

Referenced by `gdcm::SmartPointer< Value >::operator=()`.

25.240.3.6 `template<class ObjectType> SmartPointer& gdcm::SmartPointer< ObjectType >::operator= (ObjectType * r)`
`[inline]`

Overload operator assignment.

25.240.3.7 `template<class ObjectType> SmartPointer& gdcm::SmartPointer< ObjectType >::operator= (ObjectType const & r)` `[inline]`

The documentation for this class was generated from the following files:

- [gdcmObject.h](#)
- [gdcmSmartPointer.h](#)

25.241 gdcm::network::SOPClassExtendedNegociationSub Class Reference

[SOPClassExtendedNegociationSub](#) PS 3.7 [Table D.3-11](#) SOP CLASS EXTENDED NEGOTIATION SUB-ITEM FIELDS (A-ASSOCIATE-RQ and A-ASSOCIATE-AC)

```
#include <gdcmSOPClassExtendedNegociationSub.h>
```

Public Member Functions

- [SOPClassExtendedNegociationSub](#) ()
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- void [SetTuple](#) (const char *uid, uint8_t levelofsupport=3, uint8_t levelofdignalsig=0, uint8_t elementcoercion=2)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.241.1 Detailed Description

[SOPClassExtendedNegociationSub](#) PS 3.7 [Table D.3-11](#) SOP CLASS EXTENDED NEGOTIATION SUB-ITEM FIELDS (A-ASSOCIATE-RQ and A-ASSOCIATE-AC)

25.241.2 Constructor & Destructor Documentation

25.241.2.1 `gdcm::network::SOPClassExtendedNegociationSub::SOPClassExtendedNegociationSub ()`

25.241.3 Member Function Documentation

25.241.3.1 `void gdcm::network::SOPClassExtendedNegociationSub::Print (std::ostream & os) const`

25.241.3.2 `std::istream& gdcm::network::SOPClassExtendedNegociationSub::Read (std::istream & is)`

25.241.3.3 `void gdcm::network::SOPClassExtendedNegociationSub::SetTuple (const char * uid, uint8_t levelofsupport = 3, uint8_t levelofdigitalsig = 0, uint8_t elementcoercion = 2)`

25.241.3.4 `size_t gdcm::network::SOPClassExtendedNegociationSub::Size () const`

25.241.3.5 `const std::ostream& gdcm::network::SOPClassExtendedNegociationSub::Write (std::ostream & os) const`

The documentation for this class was generated from the following file:

- [gdcmSOPClassExtendedNegociationSub.h](#)

25.242 gdcm::SOPClassUIDToIOD Class Reference

Class convert a class SOP Class UID into [IOD](#).

```
#include <gdcmSOPClassUIDToIOD.h>
```

Public Types

- typedef const char * [const](#) (SOPClassUIDToIODType)[2]

Static Public Member Functions

- static [const](#) char * [GetIOD](#) (UIDs [const](#) &uid)
- static [const](#) char * [GetIODFromSOPClassUID](#) ([const](#) char *sopclassuid)
- static unsigned int [GetNumberOfSOPClassToIOD](#) ()
Return the number of SOP Class UID listed internally.
- static [const](#) char * [GetSOPClassUIDFromIOD](#) ([const](#) char *iod)
- static SOPClassUIDToIODType & [GetSOPClassUIDToIOD](#) (unsigned int i)
- static SOPClassUIDToIODType * [GetSOPClassUIDToIODs](#) ()

25.242.1 Detailed Description

Class convert a class SOP Class UID into [IOD](#).

Reference PS 3.4 [Table B.5-1 STANDARD SOP CLASSES](#)

25.242.2 Member Typedef Documentation

25.242.2.1 `typedef const char* gdcm::SOPClassUIDToIOD::const(SOPClassUIDToIODType)[2]`

25.242.3 Member Function Documentation

25.242.3.1 `static const char* gdcm::SOPClassUIDToIOD::GetIOD (UIDs const & uid) [static]`

Return the associated [IOD](#) based on a SOP Class UID uid (there is a one-to-one mapping from SOP Class UID to matching [IOD](#))

Examples:

[GenerateStandardSOPClasses.cxx](#).

25.242.3.2 `static const char* gdcm::SOPClassUIDToIOD::GetIODFromSOPClassUID (const char * sopclassuid) [static]`

25.242.3.3 `static unsigned int gdcm::SOPClassUIDToIOD::GetNumberOfSOPClassToIOD () [static]`

Return the number of SOP Class UID listed internally.

25.242.3.4 `static const char* gdcm::SOPClassUIDToIOD::GetSOPClassUIDFromIOD (const char * iod) [static]`

25.242.3.5 `static SOPClassUIDToIODType& gdcm::SOPClassUIDToIOD::GetSOPClassUIDToIOD (unsigned int i) [static]`

25.242.3.6 `static SOPClassUIDToIODType* gdcm::SOPClassUIDToIOD::GetSOPClassUIDToIODs () [static]`

The documentation for this class was generated from the following file:


- [gdcmSOPClassUIDToIOD.h](#)

25.243 gdcm::Sorter Class Reference


[Sorter](#) General class to do sorting using a custom function You simply need to provide a function of type: [Sorter::Sort-Function](#).

```
#include <gdcmSorter.h>
```

Inheritance diagram for `gdcm::Sorter`:



Collaboration diagram for `gdcm::Sorter`:



Public Types

- typedef `bool(* SortFunction)(DataSet const &, DataSet const &)`
Set the sort function which compares one dataset to the other.

Public Member Functions

- `Sorter()`
- virtual `~Sorter()`
- bool `AddSelect(Tag const &tag, const char *value)`
UNSUPPORTED FOR NOW.
- const `std::vector< std::string > & GetFilenames()` const
- void `Print(std::ostream &os)` const

Print.

- void [SetSortFunction](#) ([SortFunction](#) f)
- virtual bool [Sort](#) (std::vector< std::string > const &filenames)

Typically the output of [gdcm::Directory::GetFilenames\(\)](#)

- virtual bool [StableSort](#) (std::vector< std::string > const &filenames)

Protected Types

- typedef std::map< [Tag](#),
std::string > [SelectionMap](#)

Protected Attributes

- std::vector< std::string > [Filenames](#)
- std::map< [Tag](#), std::string > [Selection](#)
- [SortFunction](#) SortFunc

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [Sorter](#) &s)

25.243.1 Detailed Description

[Sorter](#) General class to do sorting using a custom function You simply need to provide a function of type: [Sorter::SortFunction](#).

Warning

implementation details. For now there is no cache mechanism. Which means that everytime you call Sort, all files specified as input paramater are *read*

See Also

[Scanner](#)

Examples:

[SortImage.cxx](#), and [VolumeSorter.cxx](#).

25.243.2 Member Typedef Documentation

25.243.2.1 typedef std::map<[Tag](#),std::string> [gdcm::Sorter::SelectionMap](#) [protected]

25.243.2.2 typedef bool(* [gdcm::Sorter::SortFunction](#))([DataSet](#) const &, [DataSet](#) const &)

Set the sort function which compares one dataset to the other.

25.243.3 Constructor & Destructor Documentation

25.243.3.1 `gdcmm::Sorter::Sorter ()`

25.243.3.2 `virtual gdcmm::Sorter::~~Sorter ()` `[virtual]`

25.243.4 Member Function Documentation

25.243.4.1 `bool gdcmm::Sorter::AddSelect (Tag const & tag, const char * value)`

UNSUPPORTED FOR NOW.

25.243.4.2 `const std::vector<std::string>& gdcmm::Sorter::GetFileNames () const` `[inline]`

Return the list of filenames as sorted by the specific algorithm used. Empty by default (before [Sort\(\)](#) is called)

Examples:

[gdcmmorthoplanes.cxx](#), [reslicesphere.cxx](#), [SortImage.cxx](#), and [VolumeSorter.cxx](#).

25.243.4.3 `void gdcmm::Sorter::Print (std::ostream & os) const`

Print.

Examples:

[gdcmmorthoplanes.cxx](#), [SortImage.cxx](#), and [VolumeSorter.cxx](#).

Referenced by `gdcmm::operator<<()`.

25.243.4.4 `void gdcmm::Sorter::SetSortFunction (SortFunction f)`

Examples:

[SortImage.cxx](#), and [VolumeSorter.cxx](#).

25.243.4.5 `virtual bool gdcmm::Sorter::Sort (std::vector< std::string > const & filenames)` `[virtual]`

Typically the output of `gdcmm::Directory::GetFileNames()`

Reimplemented in `gdcmm::IPPSorter`.

Examples:

[SortImage.cxx](#).

25.243.4.6 `virtual bool gdcmm::Sorter::StableSort (std::vector< std::string > const & filenames)` `[virtual]`

Examples:

[SortImage.cxx](#), and [VolumeSorter.cxx](#).

25.243.5 Friends And Related Function Documentation

25.243.5.1 `std::ostream& operator<< (std::ostream & _os, const Sorter & s)` `[friend]`

25.243.6 Member Data Documentation

25.243.6.1 `std::vector<std::string> gdcmm::Sorter::FileNames` `[protected]`

25.243.6.2 `std::map<Tag,std::string> gdcmm::Sorter::Selection` `[protected]`

25.243.6.3 **SortFunction** `gdcmm::Sorter::SortFunc` `[protected]`

The documentation for this class was generated from the following file:

- [gdcmmSorter.h](#)

25.244 gdcmm::Spacing Class Reference

Class for [Spacing](#).

```
#include <gdcmmSpacing.h>
```

Public Types

- enum [SpacingType](#) {
[DETECTOR](#) = 0,
[MAGNIFIED](#),
[CALIBRATED](#),
[UNKNOWN](#) }

Public Member Functions

- [Spacing](#) ()
- [~Spacing](#) ()

Static Public Member Functions

- static [Attribute](#)< 0x28, 0x34 > [ComputePixelAspectRatioFromPixelSpacing](#) (const [Attribute](#)< 0x28, 0x30 > &pixelspacing)

25.244.1 Detailed Description

Class for [Spacing](#).

It all began with a mail to WG6:

Subject: Imager Pixel [Spacing](#) vs Pixel [Spacing](#) **Body:** [Apologies for the duplicate post, namely to David Clunie & OFFIS team]

I have been trying to understand CP-586 in the following two cases:

On the one hand:

- DISCIMG/IMAGES/CRIMAGE taken from <http://dclunie.com/images/pixelspacingtestimages.zip>

And on the other hand:

- http://gdcm.sourceforge.net/thingies/cr_pixelspacing.dcm

If I understand correctly the CP, one is required to use Pixel [Spacing](#) for measurement ('true size' print) instead of Imager Pixel [Spacing](#), since the two attributes are present and Pixel [Spacing](#) is different from Imager Pixel [Spacing](#).

If this is correct, then the test data DISCIMG/IMAGES/CRIMAGE is incorrect. If this is incorrect (ie. I need to use Imager Pixel [Spacing](#)), then the display of cr_pixelspacing.dcm for measurement will be incorrect.

Could someone please let me know what am I missing here? I could not find any information in any header that would allow me to differentiate those.

Thank you for your time,

Ref: <http://lists.nema.org/scripts/lyris.pl?sub=488573&id=400720477> See PS 3.3-2008, [Table C.7-11b IMAGE PIXEL MACRO ATTRIBUTES](#)

Ratio of the vertical size and horizontal size of the pixels in the image specified by a pair of integer values where the first value is the vertical pixel size, and the second value is the horizontal pixel size. Required if the aspect ratio values do not have a ratio of 1:1 and the physical pixel spacing is not specified by Pixel [Spacing](#) (0028,0030), or Imager Pixel [Spacing](#) (0018,1164) or Nominal Scanned Pixel [Spacing](#) (0018,2010), either for the entire [Image](#) or per-frame in a Functional Group [Macro](#). See C.7.6.3.1.7.

PS 3.3-2008 10.7.1.3 Pixel [Spacing Value](#) Order and Valid Values All pixel spacing related attributes shall have non-zero values, except when there is only a single row or column or pixel of data present, in which case the corresponding value may be zero.

Ref: http://gdcm.sourceforge.net/wiki/index.php/Imager_Pixel_Spacing

25.244.2 Member Enumeration Documentation

25.244.2.1 enum gdcm::Spacing::SpacingType

Enumerator

DETECTOR
MAGNIFIED
CALIBRATED
UNKNOWN

25.244.3 Constructor & Destructor Documentation

25.244.3.1 gdcm::Spacing::Spacing ()

25.244.3.2 gdcm::Spacing::~~Spacing ()

25.244.4 Member Function Documentation

25.244.4.1 static Attribute<0x28,0x34> gdcm::Spacing::ComputePixelAspectRatioFromPixelSpacing (const Attribute< 0x28, 0x30 > & pixelspacing) [static]

The documentation for this class was generated from the following file:

- [gdcmSpacing.h](#)

25.245 gdcm::Spectroscopy Class Reference

[Spectroscopy](#) class.

```
#include <gdcmSpectroscopy.h>
```

Public Member Functions

- [Spectroscopy](#) ()

25.245.1 Detailed Description

[Spectroscopy](#) class.

25.245.2 Constructor & Destructor Documentation

25.245.2.1 [gdcm::Spectroscopy::Spectroscopy](#) () `[inline]`

The documentation for this class was generated from the following file:

- [gdcmSpectroscopy.h](#)

25.246 gdcm::SplitMosaicFilter Class Reference

[SplitMosaicFilter](#) class Class to reshuffle bytes for a SIEMENS Mosaic image Siemens CSA [Image](#) Header CSA:= Common Siemens Architecture, sometimes also known as Common syngo Architecture.

```
#include <gdcmSplitMosaicFilter.h>
```

Public Member Functions

- [SplitMosaicFilter](#) ()
- [~SplitMosaicFilter](#) ()
- bool [ComputeMOSAICDimensions](#) (unsigned int dims[3])
- [File](#) & [GetFile](#) ()
- const [File](#) & [GetFile](#) () const
- const [Image](#) & [GetImage](#) () const
- [Image](#) & [GetImage](#) ()
- void [SetFile](#) (const [File](#) &f)
- void [SetImage](#) (const [Image](#) &image)
- bool [Split](#) ()

Split the SIEMENS MOSAIC image.

25.246.1 Detailed Description

[SplitMosaicFilter](#) class Class to reshuffle bytes for a SIEMENS Mosaic image Siemens CSA [Image](#) Header CSA:= Common Siemens Architecture, sometimes also known as Common syngo Architecture.

25.246.2 Constructor & Destructor Documentation

25.246.2.1 `gdcm::SplitMosaicFilter::SplitMosaicFilter ()`

25.246.2.2 `gdcm::SplitMosaicFilter::~~SplitMosaicFilter ()`

25.246.3 Member Function Documentation

25.246.3.1 `bool gdcm::SplitMosaicFilter::ComputeMOSAICDimensions (unsigned int dims[3])`

Compute the new dimensions according to private information stored in the MOSAIC header.

25.246.3.2 `File& gdcm::SplitMosaicFilter::GetFile ()` `[inline]`

25.246.3.3 `const File& gdcm::SplitMosaicFilter::GetFile () const` `[inline]`

25.246.3.4 `const Image& gdcm::SplitMosaicFilter::GetImage () const` `[inline]`

25.246.3.5 `Image& gdcm::SplitMosaicFilter::GetImage ()` `[inline]`

25.246.3.6 `void gdcm::SplitMosaicFilter::SetFile (const File & f)` `[inline]`

25.246.3.7 `void gdcm::SplitMosaicFilter::SetImage (const Image & image)`

25.246.3.8 `bool gdcm::SplitMosaicFilter::Split ()`

Split the SIEMENS MOSAIC image.


The documentation for this class was generated from the following file:

- [gdcmSplitMosaicFilter.h](#)


25.247 gdcm::StartEvent Class Reference

```
#include <gdcmEvent.h>
```

Inheritance diagram for gdcm::StartEvent:



Collaboration diagram for gdcm::StartEvent:



Additional Inherited Members

The documentation for this class was generated from the following file:

- [gdcmEvent.h](#)

25.248 `gdcm::static_assert_test< x >` Struct Template Reference

```
#include <gdcmStaticAssert.h>
```

The documentation for this struct was generated from the following file:

- [gdcmStaticAssert.h](#)

25.249 `gdcm::STATIC_ASSERTION_FAILURE< x >` Struct Template Reference

```
#include <gdcmStaticAssert.h>
```

The documentation for this struct was generated from the following file:

- [gdcmStaticAssert.h](#)

25.250 `gdcm::STATIC_ASSERTION_FAILURE< true >` Struct Template Reference

```
#include <gdcmStaticAssert.h>
```

Public Types

- enum { [value](#) = 1 }

25.250.1 Member Enumeration Documentation

25.250.1.1 anonymous enum

Enumerator

value

The documentation for this struct was generated from the following file:

- [gdcmStaticAssert.h](#)

25.251 `gdcm::StreamImageReader` Class Reference

[StreamImageReader](#).

```
#include <gdcmStreamImageReader.h>
```

Public Member Functions

- [StreamImageReader](#) ()
- virtual [~StreamImageReader](#) ()
- bool [CanReadImage](#) () const

- void [DefinePixelExtent](#) (uint16_t inXMin, uint16_t inXMax, uint16_t inYMin, uint16_t inYMax, uint16_t inZMin=0, uint16_t inZMax=1)
- uint32_t [DefineProperBufferLength](#) () const
- std::vector< unsigned int > [GetDimensionsValueForResolution](#) (unsigned int)
- [File](#) const & [GetFile](#) () const
- bool [Read](#) (char *inReadBuffer, const std::size_t &inBufferLength)
- virtual bool [ReadImageInformation](#) ()
- void [SetFileName](#) (const char *inFileName)
- void [SetStream](#) (std::istream &inStream)

25.251.1 Detailed Description

[StreamImageReader](#).

Note

its role is to convert the DICOM [DataSet](#) into a [gdcmm::Image](#) representation via an ITK streaming (ie, multithreaded) interface [Image](#) is different from [Pixmap](#) has it has a position and a direction in Space. Currently, this class is thread safe in that it can read a single extent in a single thread. Multiple versions can be used for multiple extents/threads.

See Also

[Image](#)

Examples:

[StreamImageReaderTest.cxx](#).

25.251.2 Constructor & Destructor Documentation

25.251.2.1 [gdcmm::StreamImageReader::StreamImageReader](#) ()

25.251.2.2 [virtual gdcmm::StreamImageReader::~~StreamImageReader](#) () `[virtual]`

25.251.3 Member Function Documentation

25.251.3.1 [bool gdcmm::StreamImageReader::CanReadImage](#) () const

Only RAW images are currently readable by the stream reader. As more streaming codecs are added, then this function will be updated to reflect those changes. Calling this function prior to reading will ensure that only streamable files are streamed. Make sure to call [ReadImageInformation](#) prior to calling this function.

Examples:

[StreamImageReaderTest.cxx](#).

25.251.3.2 [void gdcmm::StreamImageReader::DefinePixelExtent](#) (uint16_t *inXMin*, uint16_t *inXMax*, uint16_t *inYMin*, uint16_t *inYMax*, uint16_t *inZMin* = 0, uint16_t *inZMax* = 1)

Defines an image extent for the Read function. DICOM states that an image can have no more than 2^{16} pixels per edge (as of 2009) In this case, the pixel extents ignore the direction cosines entirely, and assumes that the origin of the image is at location 0,0 (regardless of the definition in space per the tags). So, if the first 100 pixels of the first row are to be read in, this function should be called with [DefinePixelExtent](#)(0, 100, 0, 1), regardless of pixel size or orientation.

Examples:

[StreamImageReaderTest.cxx](#).

25.251.3.3 `uint32_t gdcM::StreamImageReader::DefineProperBufferLength () const`

Paying attention to the pixel format and so forth, define the proper buffer length for the user. The return amount is in bytes. Call this function to determine the size of the `char*` buffer that will need to be passed in to `ReadImageSubregion()`. If the return is 0, then that means that the pixel extent was not defined prior

Examples:

[StreamImageReaderTest.cxx](#).

25.251.3.4 `std::vector<unsigned int> gdcM::StreamImageReader::GetDimensionsValueForResolution (unsigned int)`

25.251.3.5 `File const& gdcM::StreamImageReader::GetFile () const`

Returns the dataset read by `ReadImageInformation` Couple this with the [ImageHelper](#) to get statistics about the image, like pixel extent, to be able to initialize buffers for reading

Examples:

[StreamImageReaderTest.cxx](#).

25.251.3.6 `bool gdcM::StreamImageReader::Read (char * inReadBuffer, const std::size_t & inBufferLength)`

Read the DICOM image. There are three reasons for failure:

1. The extent is not set
2. the conversion from `char*` to `std::ostream` (internally) fails
3. the given buffer isn't large enough to accommodate the desired pixel extent. This method has been implemented to look similar to the `metainageio` in `itk` MUST have an extent defined, or else `Read` will return false. If no particular extent is required, use [ImageReader](#) instead.

Examples:

[StreamImageReaderTest.cxx](#).

25.251.3.7 `virtual bool gdcM::StreamImageReader::ReadImageInformation () [virtual]`

Set the spacing and dimension information for the set filename. returns false if the file is not initialized or not an image, with the pixel (7fe0,0010) tag.

Examples:

[StreamImageReaderTest.cxx](#).

25.251.3.8 void gdcm::StreamImageReader::SetFileName (const char * *inFileName*)

One of either SetFileName or SetStream must be called prior to any other functions. These initialize an internal [Reader](#) class to be able to get non-pixel image information.

Examples:

[StreamImageReaderTest.cxx](#).

25.251.3.9 void gdcm::StreamImageReader::SetStream (std::istream & *inStream*)

The documentation for this class was generated from the following file:


- [gdcmStreamImageReader.h](#)

25.252 gdcm::StreamImageWriter Class Reference

[StreamImageReader](#).

```
#include <gdcmStreamImageWriter.h>
```

Collaboration diagram for `gdcm::StreamImageWriter`:



Public Member Functions

- [StreamImageWriter](#) ()
- virtual [~StreamImageWriter](#) ()
- bool [CanWriteFile](#) () const
- void [DefinePixelExtent](#) (uint16_t inXMin, uint16_t inXMax, uint16_t inYMin, uint16_t inYMax, uint16_t inZMin=0, uint16_t inZMax=1)
- uint32_t [DefineProperBufferLength](#) ()

- void [SetFile](#) (const [File](#) &inFile)
- void [SetFileName](#) (const char *inFileName)
- void [SetStream](#) (std::ostream &inStream)
- bool [Write](#) (void *inWriteBuffer, const std::size_t &inBufferLength)
- virtual bool [WriteImageInformation](#) ()

Protected Member Functions

- virtual bool [WriteImageSubregionRAW](#) (char *inWriteBuffer, const std::size_t &inBufferLength)
- int [WriteRawHeader](#) ([RAWCodec](#) *inCodec, std::ostream *inStream)

Protected Attributes

- int [mElementOffsets](#)
- int [mElementOffsets1](#)
- [SmartPointer](#)< [File](#) > [mspFile](#)
- [Writer](#) [mWriter](#)
- uint16_t [mXMax](#)
- uint16_t [mXMin](#)
- uint16_t [mYMax](#)
- uint16_t [mYMin](#)
- uint16_t [mZMax](#)
- uint16_t [mZMin](#)

25.252.1 Detailed Description

[StreamImageReader](#).

Note

its role is to convert the DICOM [DataSet](#) into a [gdcm::Image](#) representation via an ITK streaming (ie, multithreaded) interface [Image](#) is different from [Pixmap](#) has it has a position and a direction in Space. Currently, this class is threadsafe in that it can read a single extent in a single thread. Multiple versions can be used for multiple extents/threads.

See Also

[Image](#)

Examples:

[Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), and [StreamImageReaderTest.cxx](#).

25.252.2 Constructor & Destructor Documentation

25.252.2.1 [gdcm::StreamImageWriter::StreamImageWriter](#) ()

25.252.2.2 [virtual gdcm::StreamImageWriter::~~StreamImageWriter](#) () `[virtual]`

25.252.3 Member Function Documentation

25.252.3.1 `bool gdcm::StreamImageWriter::CanWriteFile () const`

This function determines if a file can even be written using the streaming writer unlike the reader, can be called before `WriteImageInformation`, but must be called after `SetFile`.

Examples:

[Extracting_All_Resolution.cxx](#), and [Fake_Image_Using_Stream_Image_Writer.cxx](#).

25.252.3.2 `void gdcm::StreamImageWriter::DefinePixelExtent (uint16_t inXMin, uint16_t inXMax, uint16_t inYMin, uint16_t inYMax, uint16_t inZMin = 0, uint16_t inZMax = 1)`

Defines an image extent for the `Read` function. DICOM states that an image can have no more than 2^{16} pixels per edge (as of 2009) In this case, the pixel extents ignore the direction cosines entirely, and assumes that the origin of the image is at location 0,0 (regardless of the definition in space per the tags). So, if the first 100 pixels of the first row are to be read in, this function should be called with `DefinePixelExtent(0, 100, 0, 1)`, regardless of pixel size or orientation.
15 nov 2010: added z dimension, defaults to being 1 plane large

Examples:

[Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), and [StreamImageReaderTest.cxx](#).

25.252.3.3 `uint32_t gdcm::StreamImageWriter::DefineProperBufferLength ()`

Paying attention to the pixel format and so forth, define the proper buffer length for the user. The return amount is in bytes. If the return is 0, then that means that the pixel extent was not defined prior this return is for RAW inputs which are then encoded by the writer, but are used to ensure that the writer gets the proper buffer size

Examples:

[Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), and [StreamImageReaderTest.cxx](#).

25.252.3.4 `void gdcm::StreamImageWriter::SetFile (const File & inFile)`

Set the image information to be written to disk that is everything but the pixel information: (7fe0,0010) `PixelData`

Examples:

[Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), and [StreamImageReaderTest.cxx](#).

25.252.3.5 `void gdcm::StreamImageWriter::SetFileName (const char * inFileName)`

One of either `SetFileName` or `SetStream` must be called prior to any other functions. These initialize an internal [Reader](#) class to be able to get non-pixel image information.

25.252.3.6 `void gdcm::StreamImageWriter::SetStream (std::ostream & inStream)`

Examples:

[Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), and [StreamImageReaderTest.cxx](#).

25.252.3.7 `bool gdcm::StreamImageWriter::Write (void * inWriteBuffer, const std::size_t & inBufferLength)`

Read the DICOM image. There are three reasons for failure:

1. The extent is not set
2. the conversion from void* to std::ostream (internally) fails
3. the given buffer isn't large enough to accomodate the desired pixel extent. This method has been implemented to look similar to the metainageio in itk MUST have an extent defined, or else Read will return false. If no particular extent is required, use [ImageReader](#) instead.

Examples:

[Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), and [StreamImageReaderTest.cxx](#).

25.252.3.8 `virtual bool gdcm::StreamImageWriter::WriteImageInformation () [virtual]`

Write the header information to disk, and a bunch of zeros for the actual pixel information Of course, if we're doing a non-compressed format, that works but if it's compressed, we have to force the ordering of chunks that are written.

Examples:

[Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), and [StreamImageReaderTest.cxx](#).

25.252.3.9 `virtual bool gdcm::StreamImageWriter::WriteImageSubregionRAW (char * inWriteBuffer, const std::size_t & inBufferLength) [protected], [virtual]`

Using the min, max, etc set by DefinePixelExtent, this will fill the given buffer Make sure to call DefinePixelExtent and to initialize the buffer with the amount given by DefineProperBufferLength prior to calling this. reads by the RAW codec; other codecs are added once implemented

25.252.3.10 `int gdcm::StreamImageWriter::WriteRawHeader (RAWCodec * inCodec, std::ostream * inStream) [protected]`

when writing a raw file, we know the full extent, and can just write the first 12 bytes out (the tag, the [VR](#), and the size) when we do compressed files, we'll do it in chunks, as described in 2009-3, part 5, Annex A, section 4. Pass the raw codec so that in the rare case of a bigendian explicit raw, the first 12 bytes written out should still be kosher. returns -1 if there's any failure, or the complete offset (12 bytes) if it works. Those 12 bytes are then added to the position in order to determine where to write.

25.252.4 Member Data Documentation

25.252.4.1 `int gdcm::StreamImageWriter::mElementOffsets [protected]`

The result of WriteRawHeader (or another header, when that's implemented) This result is saved so that the first N bytes aren't constantly being rewritten for each chunk that's passed in. For compressed data, the offset table will require rewrites of data.

- 25.252.4.2 `int gdcM::StreamImageWriter::mElementOffsets1` [protected]
- 25.252.4.3 `SmartPointer<File> gdcM::StreamImageWriter::mspFile` [protected]
- 25.252.4.4 `Writer gdcM::StreamImageWriter::mWriter` [protected]
- 25.252.4.5 `uint16_t gdcM::StreamImageWriter::mXMax` [protected]
- 25.252.4.6 `uint16_t gdcM::StreamImageWriter::mXMin` [protected]
- 25.252.4.7 `uint16_t gdcM::StreamImageWriter::mYMax` [protected]
- 25.252.4.8 `uint16_t gdcM::StreamImageWriter::mYMin` [protected]
- 25.252.4.9 `uint16_t gdcM::StreamImageWriter::mZMax` [protected]
- 25.252.4.10 `uint16_t gdcM::StreamImageWriter::mZMin` [protected]

The documentation for this class was generated from the following file:


- [gdcMStreamImageWriter.h](#)

25.253 `gdcM::String< TDelimiter, TMaxLength, TPadChar >` Class Template Reference


[String.](#)

```
#include <gdcMString.h>
```

Inheritance diagram for `gdcM::String< TDelimiter, TMaxLength, TPadChar >`:



Collaboration diagram for gdcmm::String< TDelimiter, TMaxLength, TPadChar >:



Public Types

- typedef `std::string::const_iterator` [const_iterator](#)
- typedef `std::string::const_reference` [const_reference](#)
- typedef `std::string::const_reverse_iterator` [const_reverse_iterator](#)
- typedef `std::string::difference_type` [difference_type](#)
- typedef `std::string::iterator` [iterator](#)
- typedef `std::string::pointer` [pointer](#)
- typedef `std::string::reference` [reference](#)
- typedef `std::string::reverse_iterator` [reverse_iterator](#)
- typedef `std::string::size_type` [size_type](#)
- typedef `std::string::value_type` [value_type](#)

Public Member Functions

- [String](#) ()
String constructors.
- [String](#) (const [value_type](#) *s)
- [String](#) (const [value_type](#) *s, [size_type](#) n)
- [String](#) (const std::string &s, [size_type](#) pos=0, [size_type](#) n=npos)
- bool [IsValid](#) () const
return if string is valid
- [operator const char *](#) () const

WARNING: Trailing \0 might be lost in this operation:

- `std::string Trim () const`
- `gdcmm::String< TDelimiter, TMaxLength, TPadChar > Truncate () const`

Static Public Member Functions

- `static std::string Trim (const char *input)`

25.253.1 Detailed Description

```
template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = ' '>class gdcmm::String< TDelimiter, TMaxLength, TPadChar >
```

[String.](#)

Note

TDelimiter template parameter is used to separate multiple [String](#) (VM1 >) TMaxLength is only a hint. Noone actually respect the max length TPadChar is the string padding (0 or space)

25.253.2 Member Typedef Documentation

25.253.2.1 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = ' '> typedef std::string::const_iterator gdcmm::String< TDelimiter, TMaxLength, TPadChar >::const_iterator`

25.253.2.2 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = ' '> typedef std::string::const_reference gdcmm::String< TDelimiter, TMaxLength, TPadChar >::const_reference`

25.253.2.3 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = ' '> typedef std::string::const_reverse_iterator gdcmm::String< TDelimiter, TMaxLength, TPadChar >::const_reverse_iterator`

25.253.2.4 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = ' '> typedef std::string::difference_type gdcmm::String< TDelimiter, TMaxLength, TPadChar >::difference_type`

25.253.2.5 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = ' '> typedef std::string::iterator gdcmm::String< TDelimiter, TMaxLength, TPadChar >::iterator`

25.253.2.6 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = ' '> typedef std::string::pointer gdcmm::String< TDelimiter, TMaxLength, TPadChar >::pointer`

25.253.2.7 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = ' '> typedef std::string::reference gdcmm::String< TDelimiter, TMaxLength, TPadChar >::reference`

25.253.2.8 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = ' '> typedef std::string::reverse_iterator gdcmm::String< TDelimiter, TMaxLength, TPadChar >::reverse_iterator`

25.253.2.9 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = ' '> typedef std::string::size_type gdcmm::String< TDelimiter, TMaxLength, TPadChar >::size_type`

25.253.2.10 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = '> typedef std::string::value_type gdcmm::String< TDelimiter, TMaxLength, TPadChar >::value_type`

25.253.3 Constructor & Destructor Documentation

25.253.3.1 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = '> gdcmm::String< TDelimiter, TMaxLength, TPadChar >::String () [inline]`

[String](#) constructors.

25.253.3.2 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = '> gdcmm::String< TDelimiter, TMaxLength, TPadChar >::String (const value_type * s) [inline]`

25.253.3.3 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = '> gdcmm::String< TDelimiter, TMaxLength, TPadChar >::String (const value_type * s, size_type n) [inline]`

25.253.3.4 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = '> gdcmm::String< TDelimiter, TMaxLength, TPadChar >::String (const std::string & s, size_type pos = 0, size_type n = npos) [inline]`

25.253.4 Member Function Documentation

25.253.4.1 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = '> bool gdcmm::String< TDelimiter, TMaxLength, TPadChar >::IsValid () const [inline]`

return if string is valid

Referenced by `gdcmm::String< TDelimiter, TMaxLength, TPadChar >::Truncate()`.

25.253.4.2 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = '> gdcmm::String< TDelimiter, TMaxLength, TPadChar >::operator const char * () const [inline]`

WARNING: Trailing \0 might be lost in this operation:

25.253.4.3 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = '> std::string gdcmm::String< TDelimiter, TMaxLength, TPadChar >::Trim () const [inline]`

Trim function is required to return a `std::string` object, otherwise we could not create a [gdcmm::String](#) object with an odd number of bytes...

25.253.4.4 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = '> static std::string gdcmm::String< TDelimiter, TMaxLength, TPadChar >::Trim (const char * input) [inline],[static]`

25.253.4.5 `template<char TDelimiter = '\\', unsigned int TMaxLength = 64, char TPadChar = '> gdcmm::String< TDelimiter, TMaxLength, TPadChar > gdcmm::String< TDelimiter, TMaxLength, TPadChar >::Truncate () const [inline]`

References `gdcmm::String< TDelimiter, TMaxLength, TPadChar >::IsValid()`.

The documentation for this class was generated from the following file:

- [gdcmmString.h](#)

25.254 gdcmm::StringFilter Class Reference

[StringFilter](#) [StringFilter](#) is the class that make gdcmm2.x looks more like gdcmm1 and transform the binary blob contained in a [DataElement](#) into a string, typically this is a nice feature to have for wrapped language.

```
#include <gdcmmStringFilter.h>
```

Public Member Functions

- [StringFilter](#) ()
- [~StringFilter](#) ()
- bool [ExecuteQuery](#) (std::string const &query, std::string &value) const
- std::string [FromString](#) (const [Tag](#) &t, const char *value, [VL](#) const &vl)
DEPRECATED: NEVER USE IT.
- std::string [FromString](#) (const [Tag](#) &t, const char *value, size_t len)
- [File](#) & [GetFile](#) ()
- const [File](#) & [GetFile](#) () const
- void [SetDicts](#) (const [Dicts](#) &dicts)
Allow user to pass in there own dicts.
- void [SetFile](#) (const [File](#) &f)
Set/Get File.
- std::string [ToString](#) (const [Tag](#) &t) const
Convert to string the ByteValue contained in a DataElement.
- std::pair< std::string,
std::string > [ToStringPair](#) (const [Tag](#) &t) const
- void [UseDictAlways](#) (bool)

Protected Member Functions

- bool [ExecuteQuery](#) (std::string const &query, [DataSet](#) const &ds, std::string &value) const
- std::pair< std::string,
std::string > [ToStringPair](#) (const [Tag](#) &t, [DataSet](#) const &ds) const

25.254.1 Detailed Description

[StringFilter](#) [StringFilter](#) is the class that make gdcmm2.x looks more like gdcmm1 and transform the binary blob contained in a [DataElement](#) into a string, typically this is a nice feature to have for wrapped language.

Examples:

[ReadAndPrintAttributes.cxx](#).

25.254.2 Constructor & Destructor Documentation

25.254.2.1 [gdcmm::StringFilter::StringFilter](#) ()

25.254.2.2 [gdcmm::StringFilter::~~StringFilter](#) ()

25.254.3 Member Function Documentation

25.254.3.1 `bool gdcm::StringFilter::ExecuteQuery (std::string const & query, std::string & value) const`

Execute the XPATH query to find a value (as string) return false when attribute is not found (or an error in the XPATH query) You need to make sure that your XPATH query is syntatically correct

25.254.3.2 `bool gdcm::StringFilter::ExecuteQuery (std::string const & query, DataSet const & ds, std::string & value) const`
`[protected]`

25.254.3.3 `std::string gdcm::StringFilter::FromString (const Tag & t, const char * value, VL const & vl)`

DEPRECATED: NEVER USE IT.

25.254.3.4 `std::string gdcm::StringFilter::FromString (const Tag & t, const char * value, size_t len)`

25.254.3.5 `File& gdcm::StringFilter::GetFile ()` `[inline]`

25.254.3.6 `const File& gdcm::StringFilter::GetFile () const` `[inline]`

25.254.3.7 `void gdcm::StringFilter::SetDicts (const Dicts & dicts)`

Allow user to pass in there own dicts.

25.254.3.8 `void gdcm::StringFilter::SetFile (const File & f)` `[inline]`

Set/Get [File](#).

Examples:

[ReadAndPrintAttributes.cxx](#).

25.254.3.9 `std::string gdcm::StringFilter::ToString (const Tag & t) const`

Convert to string the [ByteValue](#) contained in a [DataElement](#).

Examples:

[ReadAndPrintAttributes.cxx](#).

25.254.3.10 `std::pair<std::string, std::string> gdcm::StringFilter::ToStringPair (const Tag & t) const`

Convert to string the [ByteValue](#) contained in a [DataElement](#) the returned elements are: pair.first : the name as found in the dictionary of [DataElement](#) pari.second : the value encoded into a string (US,UL...) are properly converted

Examples:

[ReadAndPrintAttributes.cxx](#).

25.254.3.11 `std::pair<std::string, std::string> gdcM::StringFilter::ToStringPair (const Tag & t, DataSet const & ds) const`
[protected]

25.254.3.12 `void gdcM::StringFilter::UseDictAlways (bool)` [inline]

The documentation for this class was generated from the following file:

- [gdcMStringFilter.h](#)

25.255 gdcM::Study Class Reference

[Study.](#)

```
#include <gdcMStudy.h>
```

Public Member Functions

- [Study \(\)](#)

25.255.1 Detailed Description

[Study.](#)

25.255.2 Constructor & Destructor Documentation

25.255.2.1 `gdcM::Study::Study ()` [inline]

The documentation for this class was generated from the following file:


- [gdcMStudy.h](#)

25.256 gdcM::Subject Class Reference


[Subject.](#)

```
#include <gdcMSubject.h>
```

Inheritance diagram for gdcm::Subject:



Collaboration diagram for gdcm::Subject:



Public Member Functions

- [Subject](#) ()
- [~Subject](#) ()
- unsigned long [AddObserver](#) (const [Event](#) &event, [Command](#) *)
- unsigned long [AddObserver](#) (const [Event](#) &event, [Command](#) *) const
- [Command](#) * [GetCommand](#) (unsigned long tag)
- bool [HasObserver](#) (const [Event](#) &event) const
- void [InvokeEvent](#) (const [Event](#) &)
- void [InvokeEvent](#) (const [Event](#) &) const
- void [RemoveAllObservers](#) ()
- void [RemoveObserver](#) (unsigned long tag)

Additional Inherited Members

25.256.1 Detailed Description

[Subject](#).

See Also

[Command Event](#)

25.256.2 Constructor & Destructor Documentation

25.256.2.1 `gdcmm::Subject::Subject ()`

25.256.2.2 `gdcmm::Subject::~~Subject ()`

25.256.3 Member Function Documentation

25.256.3.1 `unsigned long gdcmm::Subject::AddObserver (const Event & event, Command *)`

Allow people to add/remove/invoke observers (callbacks) to any GDCM object. This is an implementation of the subject/observer design pattern. An observer is added by specifying an event to respond to and an [gdcmm::Command](#) to execute. It returns an unsigned long tag which can be used later to remove the event or retrieve the command. The memory for the [Command](#) becomes the responsibility of this object, so don't pass the same instance of a command to two different objects

25.256.3.2 `unsigned long gdcmm::Subject::AddObserver (const Event & event, Command *) const`

25.256.3.3 `Command* gdcmm::Subject::GetCommand (unsigned long tag)`

Get the command associated with the given tag. NOTE: This returns a pointer to a [Command](#), but it is safe to assign this to a `Command::Pointer`. Since [Command](#) inherits from `LightObject`, at this point in the code, only a pointer or a reference to the [Command](#) can be used.

25.256.3.4 `bool gdcmm::Subject::HasObserver (const Event & event) const`

Return true if an observer is registered for this event.

25.256.3.5 `void gdcmm::Subject::InvokeEvent (const Event &)`

Call `Execute` on all the `Commands` observing this event id.

25.256.3.6 `void gdcmm::Subject::InvokeEvent (const Event &) const`

Call `Execute` on all the `Commands` observing this event id. The actions triggered by this call doesn't modify this object.

25.256.3.7 `void gdcmm::Subject::RemoveAllObservers ()`

Remove all observers .

25.256.3.8 `void gdcmm::Subject::RemoveObserver (unsigned long tag)`

Remove the observer with this tag value.

The documentation for this class was generated from the following file:


- [gdcmSubject.h](#)

25.257 gdcm::Surface Class Reference


This class defines a SURFACE IE. This members are taken from required surface mesh module attributes.

```
#include <gdcmSurface.h>
```

Inheritance diagram for gdcm::Surface:



Collaboration diagram for gdcm::Surface:



Public Types

- enum [STATES](#) {
 [NO](#) = 0,
 [YES](#),
 [UNKNOWN](#),
 [STATES_END](#) }
- enum [VIEWType](#) {

```

SURFACE = 0,
WIREFRAME,
POINTS,
VIEWType_END }

```

Enumeration for Recommended Presentation *Type*.

Public Member Functions

- [Surface](#) ()
- virtual [~Surface](#) ()
- [SegmentHelper::BasicCodedEntry](#)
const & [GetAlgorithmFamily](#) () const
- [SegmentHelper::BasicCodedEntry](#) & [GetAlgorithmFamily](#) ()
- const char * [GetAlgorithmName](#) () const
- const char * [GetAlgorithmVersion](#) () const
- const float * [GetAxisOfRotation](#) () const
- const float * [GetCenterOfRotation](#) () const
- [STATES](#) [GetFiniteVolume](#) () const
- [STATES](#) [GetManifold](#) () const
- float [GetMaximumPointDistance](#) () const
- float [GetMeanPointDistance](#) () const
- [MeshPrimitive](#) const & [GetMeshPrimitive](#) () const
- [MeshPrimitive](#) & [GetMeshPrimitive](#) ()
- unsigned long [GetNumberOfSurfacePoints](#) () const
- unsigned long [GetNumberOfVectors](#) () const
- const [DataElement](#) & [GetPointCoordinatesData](#) () const
- [DataElement](#) & [GetPointCoordinatesData](#) ()
- const float * [GetPointPositionAccuracy](#) () const
- const float * [GetPointsBoundingBoxCoordinates](#) () const
- [SegmentHelper::BasicCodedEntry](#)
const & [GetProcessingAlgorithm](#) () const
- [SegmentHelper::BasicCodedEntry](#) & [GetProcessingAlgorithm](#) ()
- const unsigned short * [GetRecommendedDisplayCIELabValue](#) () const
- unsigned short [GetRecommendedDisplayCIELabValue](#) (const unsigned int idx) const
- unsigned short [GetRecommendedDisplayGrayscaleValue](#) () const
- float [GetRecommendedPresentationOpacity](#) () const
- [VIEWType](#) [GetRecommendedPresentationType](#) () const
- const char * [GetSurfaceComments](#) () const
- unsigned long [GetSurfaceNumber](#) () const
- bool [GetSurfaceProcessing](#) () const
- const char * [GetSurfaceProcessingDescription](#) () const
- float [GetSurfaceProcessingRatio](#) () const
- const float * [GetVectorAccuracy](#) () const
- const [DataElement](#) & [GetVectorCoordinateData](#) () const
- [DataElement](#) & [GetVectorCoordinateData](#) ()
- unsigned short [GetVectorDimensionality](#) () const
- void [SetAlgorithmFamily](#) ([SegmentHelper::BasicCodedEntry](#) const &BSE)
- void [SetAlgorithmName](#) (const char *str)
- void [SetAlgorithmVersion](#) (const char *str)
- void [SetAxisOfRotation](#) (const float *axis)

- void [SetCenterOfRotation](#) (const float *center)
- void [SetFiniteVolume](#) ([STATES](#) state)
- void [SetManifold](#) ([STATES](#) state)
- void [SetMaximumPointDistance](#) (float maximum)
- void [SetMeanPointDistance](#) (float average)
- void [SetMeshPrimitive](#) ([MeshPrimitive](#) &mp)
- void [SetNumberOfSurfacePoints](#) (const unsigned long nb)
- void [SetNumberOfVectors](#) (const unsigned long nb)
- void [SetPointCoordinatesData](#) ([DataElement](#) const &de)
- void [SetPointPositionAccuracy](#) (const float *accuracies)
- void [SetPointsBoundingBoxCoordinates](#) (const float *coordinates)
- void [SetProcessingAlgorithm](#) ([SegmentHelper::BasicCodedEntry](#) const &BSE)
- void [SetRecommendedDisplayCIELabValue](#) (const unsigned short vl[3])
- void [SetRecommendedDisplayCIELabValue](#) (const unsigned short vl, const unsigned int idx=0)
- void [SetRecommendedDisplayCIELabValue](#) (const std::vector< unsigned short > &vl)
- void [SetRecommendedDisplayGrayscaleValue](#) (const unsigned short vl)
- void [SetRecommendedPresentationOpacity](#) (const float opacity)
- void [SetRecommendedPresentationType](#) ([VIEWType](#) type)
- void [SetSurfaceComments](#) (const char *comment)
- void [SetSurfaceNumber](#) (const unsigned long nb)
- void [SetSurfaceProcessing](#) (bool b)
- void [SetSurfaceProcessingDescription](#) (const char *description)
- void [SetSurfaceProcessingRatio](#) (const float ratio)
- void [SetVectorAccuracy](#) (const float *accuracy)
- void [SetVectorCoordinateData](#) ([DataElement](#) const &de)
- void [SetVectorDimensionality](#) (const unsigned short dim)

Static Public Member Functions

- static [STATES](#) [GetSTATES](#) (const char *state)
- static const char * [GetSTATESString](#) ([STATES](#) state)
- static [VIEWType](#) [GetVIEWType](#) (const char *type)
- static const char * [GetVIEWTypeString](#) ([VIEWType](#) type)

Additional Inherited Members

25.257.1 Detailed Description

This class defines a SURFACE IE. This members are taken from required surface mesh module attributes.

See Also

PS 3.3 A.1.2.18 , A.57 and C.27

25.257.2 Member Enumeration Documentation

25.257.2.1 enum gdcm::Surface::STATES

Enumerator

NO

YES

UNKNOWN

STATES_END

25.257.2.2 enum gdcm::Surface::VIEWType

Enumeration for Recommended Presentation [Type](#).

See Also

Tag(0x0066, 0x000D) and PS 3.3 C.27.1.1.3

Enumerator

SURFACE

WIREFRAME

POINTS

VIEWType_END

25.257.3 Constructor & Destructor Documentation

25.257.3.1 gdcm::Surface::Surface ()

25.257.3.2 virtual gdcm::Surface::~~Surface () [virtual]

25.257.4 Member Function Documentation

25.257.4.1 SegmentHelper::BasicCodedEntry const& gdcm::Surface::GetAlgorithmFamily () const

25.257.4.2 SegmentHelper::BasicCodedEntry& gdcm::Surface::GetAlgorithmFamily ()

25.257.4.3 const char* gdcm::Surface::GetAlgorithmName () const

25.257.4.4 const char* gdcm::Surface::GetAlgorithmVersion () const

25.257.4.5 const float* gdcm::Surface::GetAxisOfRotation () const

Note

Pointer is null if undefined

25.257.4.6 `const float* gdcm::Surface::GetCenterOfRotation () const`

Note

Pointer is null if undefined

25.257.4.7 `STATES gdcm::Surface::GetFiniteVolume () const`

25.257.4.8 `STATES gdcm::Surface::GetManifold () const`

25.257.4.9 `float gdcm::Surface::GetMaximumPointDistance () const`

25.257.4.10 `float gdcm::Surface::GetMeanPointDistance () const`

25.257.4.11 `MeshPrimitive const& gdcm::Surface::GetMeshPrimitive () const`

25.257.4.12 `MeshPrimitive& gdcm::Surface::GetMeshPrimitive ()`

25.257.4.13 `unsigned long gdcm::Surface::GetNumberOfSurfacePoints () const`

25.257.4.14 `unsigned long gdcm::Surface::GetNumberOfVectors () const`

25.257.4.15 `const DataElement& gdcm::Surface::GetPointCoordinatesData () const`

25.257.4.16 `DataElement& gdcm::Surface::GetPointCoordinatesData ()`

25.257.4.17 `const float* gdcm::Surface::GetPointPositionAccuracy () const`

Note

Pointer is null if undefined

25.257.4.18 `const float* gdcm::Surface::GetPointsBoundingBoxCoordinates () const`

Note

Pointer is null if undefined

25.257.4.19 `SegmentHelper::BasicCodedEntry const& gdcm::Surface::GetProcessingAlgorithm () const`

25.257.4.20 `SegmentHelper::BasicCodedEntry& gdcm::Surface::GetProcessingAlgorithm ()`

25.257.4.21 `const unsigned short* gdcm::Surface::GetRecommendedDisplayCIELabValue () const`

25.257.4.22 `unsigned short gdcm::Surface::GetRecommendedDisplayCIELabValue (const unsigned int idx) const`

25.257.4.23 `unsigned short gdcm::Surface::GetRecommendedDisplayGrayscaleValue () const`

25.257.4.24 `float gdcm::Surface::GetRecommendedPresentationOpacity () const`

- 25.257.4.25 **VIEWType** gdcm::Surface::GetRecommendedPresentationType () const
- 25.257.4.26 static **STATES** gdcm::Surface::GetSTATES (const char * *state*) [static]
- 25.257.4.27 static const char* gdcm::Surface::GetSTATESString (**STATES** *state*) [static]
- 25.257.4.28 const char* gdcm::Surface::GetSurfaceComments () const
- 25.257.4.29 unsigned long gdcm::Surface::GetSurfaceNumber () const
- 25.257.4.30 bool gdcm::Surface::GetSurfaceProcessing () const
- 25.257.4.31 const char* gdcm::Surface::GetSurfaceProcessingDescription () const
- 25.257.4.32 float gdcm::Surface::GetSurfaceProcessingRatio () const
- 25.257.4.33 const float* gdcm::Surface::GetVectorAccuracy () const
- 25.257.4.34 const **DataElement**& gdcm::Surface::GetVectorCoordinateData () const
- 25.257.4.35 **DataElement**& gdcm::Surface::GetVectorCoordinateData ()
- 25.257.4.36 unsigned short gdcm::Surface::GetVectorDimensionality () const
- 25.257.4.37 static **VIEWType** gdcm::Surface::GetVIEWType (const char * *type*) [static]
- 25.257.4.38 static const char* gdcm::Surface::GetVIEWTypeString (**VIEWType** *type*) [static]
- 25.257.4.39 void gdcm::Surface::SetAlgorithmFamily (**SegmentHelper::BasicCodedEntry** const & *BSE*)
- 25.257.4.40 void gdcm::Surface::SetAlgorithmName (const char * *str*)
- 25.257.4.41 void gdcm::Surface::SetAlgorithmVersion (const char * *str*)
- 25.257.4.42 void gdcm::Surface::SetAxisOfRotation (const float * *axis*)
- 25.257.4.43 void gdcm::Surface::SetCenterOfRotation (const float * *center*)
- 25.257.4.44 void gdcm::Surface::SetFiniteVolume (**STATES** *state*)
- 25.257.4.45 void gdcm::Surface::SetManifold (**STATES** *state*)
- 25.257.4.46 void gdcm::Surface::SetMaximumPointDistance (float *maximum*)
- 25.257.4.47 void gdcm::Surface::SetMeanPointDistance (float *average*)
- 25.257.4.48 void gdcm::Surface::SetMeshPrimitive (**MeshPrimitive** & *mp*)
- 25.257.4.49 void gdcm::Surface::SetNumberOfSurfacePoints (const unsigned long *nb*)
- 25.257.4.50 void gdcm::Surface::SetNumberOfVectors (const unsigned long *nb*)

- 25.257.4.51 void gdcm::Surface::SetPointCoordinatesData (DataElement const & *de*)
- 25.257.4.52 void gdcm::Surface::SetPointPositionAccuracy (const float * *accuracies*)
- 25.257.4.53 void gdcm::Surface::SetPointsBoundingBoxCoordinates (const float * *coordinates*)
- 25.257.4.54 void gdcm::Surface::SetProcessingAlgorithm (SegmentHelper::BasicCodedEntry const & *BSE*)
- 25.257.4.55 void gdcm::Surface::SetRecommendedDisplayCIELabValue (const unsigned short *vl[3]*)
- 25.257.4.56 void gdcm::Surface::SetRecommendedDisplayCIELabValue (const unsigned short *vl*, const unsigned int *idx* = 0)
- 25.257.4.57 void gdcm::Surface::SetRecommendedDisplayCIELabValue (const std::vector< unsigned short > & *vl*)
- 25.257.4.58 void gdcm::Surface::SetRecommendedDisplayGrayscaleValue (const unsigned short *vl*)
- 25.257.4.59 void gdcm::Surface::SetRecommendedPresentationOpacity (const float *opacity*)
- 25.257.4.60 void gdcm::Surface::SetRecommendedPresentationType (VIEWType *type*)
- 25.257.4.61 void gdcm::Surface::SetSurfaceComments (const char * *comment*)
- 25.257.4.62 void gdcm::Surface::SetSurfaceNumber (const unsigned long *nb*)
- 25.257.4.63 void gdcm::Surface::SetSurfaceProcessing (bool *b*)
- 25.257.4.64 void gdcm::Surface::SetSurfaceProcessingDescription (const char * *description*)
- 25.257.4.65 void gdcm::Surface::SetSurfaceProcessingRatio (const float *ratio*)
- 25.257.4.66 void gdcm::Surface::SetVectorAccuracy (const float * *accuracy*)
- 25.257.4.67 void gdcm::Surface::SetVectorCoordinateData (DataElement const & *de*)
- 25.257.4.68 void gdcm::Surface::SetVectorDimensionality (const unsigned short *dim*)

The documentation for this class was generated from the following file:

- [gdcmSurface.h](#)

25.258 gdcm::SurfaceHelper Class Reference

[SurfaceHelper](#) Helper class for [Surface](#) object.

```
#include <gdcmSurfaceHelper.h>
```

Public Types

- typedef std::vector< unsigned short > [ColorArray](#)

Public Member Functions

- `template<typename T , typename U >`
`std::vector< T > RecommendedDisplayCIELabToRGB` (const [ColorArray](#) &CIELab, const U rangeMax)
- `template<typename U >`
`std::vector< float > RecommendedDisplayCIELabToRGB` (const [ColorArray](#) &CIELab, const U rangeMax)
- `template<typename T , typename U >`
[SurfaceHelper::ColorArray](#) `RGBToRecommendedDisplayCIELab` (const std::vector< T > &RGB, const U rangeMax)
- `template<typename T , typename U >`
`unsigned short RGBToRecommendedDisplayGrayscale` (const std::vector< T > &RGB, const U rangeMax)

Static Public Member Functions

- `template<typename T , typename U >`
`static std::vector< T > RecommendedDisplayCIELabToRGB` (const [ColorArray](#) &CIELab, const U rangeMax=255)
Convert a DICOM CIE-Lab (after reading) color into RGB.
- `template<typename U >`
`static std::vector< float > RecommendedDisplayCIELabToRGB` (const [ColorArray](#) &CIELab, const U rangeMax=255)
Convert a DICOM CIE-Lab (after reading) color into RGB.
- `template<typename T , typename U >`
`static ColorArray RGBToRecommendedDisplayCIELab` (const std::vector< T > &RGB, const U rangeMax=255)
Convert a RGB color into DICOM CIE-Lab (ready to write).
- `template<typename T , typename U >`
`static unsigned short RGBToRecommendedDisplayGrayscale` (const std::vector< T > &RGB, const U rangeMax=255)
Convert a RGB color into DICOM grayscale (ready to write).

25.258.1 Detailed Description

[SurfaceHelper](#) Helper class for [Surface](#) object.

25.258.2 Member Typedef Documentation

25.258.2.1 `typedef std::vector< unsigned short > gdcm::SurfaceHelper::ColorArray`

25.258.3 Member Function Documentation

25.258.3.1 `template<typename T , typename U > static std::vector<T> gdcm::SurfaceHelper::RecommendedDisplayCIELabToRGB`
 (const [ColorArray](#) & *CIELab*, const U *rangeMax* = 255) [static]

Convert a DICOM CIE-Lab (after reading) color into RGB.

See Also

PS 3.3 C.10.7.1.1

Parameters

<i>CIELab</i>	DICOM CIE-Lab array.
<i>rangeMax</i>	Max value of the RGB range.

Template Parameters

<i>T</i>	Type of CIELab components.
<i>U</i>	Type of rangeMax value.

25.258.3.2 `template<typename U > static std::vector<float> gdcm::SurfaceHelper::RecommendedDisplayCIELabToRGB (const ColorArray & CIELab, const U rangeMax = 255) [static]`

Convert a DICOM CIE-Lab (after reading) color into RGB.

See Also

PS 3.3 C.10.7.1.1

Parameters

<i>CIELab</i>	DICOM CIE-Lab array.
<i>rangeMax</i>	Max value of the RGB range.

Template Parameters

<i>U</i>	Type of rangeMax value.
----------	---

25.258.3.3 `template<typename T , typename U > std::vector<T> gdcm::SurfaceHelper::RecommendedDisplayCIELabToRGB (const ColorArray & CIELab, const U rangeMax)`

25.258.3.4 `template<typename U > std::vector<float> gdcm::SurfaceHelper::RecommendedDisplayCIELabToRGB (const ColorArray & CIELab, const U rangeMax)`

25.258.3.5 `template<typename T , typename U > static ColorArray gdcm::SurfaceHelper::RGBToRecommendedDisplayCIELab (const std::vector< T > & RGB, const U rangeMax = 255) [static]`

Convert a RGB color into DICOM CIE-Lab (ready to write).

See Also

PS 3.3 C.10.7.1.1

Parameters

<i>RGB</i>	RGB array.
<i>rangeMax</i>	Max value of the RGB range.

Template Parameters

<i>T</i>	Type of RGB components.
<i>U</i>	Type of rangeMax value.

25.258.3.6 `template<typename T , typename U > SurfaceHelper::ColorArray gdcm::SurfaceHelper::RGBToRecommendedDisplayCIELab (const std::vector< T > & RGB, const U rangeMax)`

25.258.3.7 `template<typename T , typename U > static unsigned short gdcm::SurfaceHelper::RGBToRecommendedDisplayGrayscale (const std::vector< T > & RGB, const U rangeMax = 255) [static]`

Convert a RGB color into DICOM grayscale (ready to write).

See Also

PS 3.3 C.27.1 tag(0062,000C)

Parameters

<i>RGB</i>	RGB array.
<i>rangeMax</i>	Max value of the RGB range.

Template Parameters

<i>T</i>	Type of RGB components.
<i>U</i>	Type of rangeMax value.

25.258.3.8 `template<typename T , typename U > unsigned short gdcm::SurfaceHelper::RGBToRecommendedDisplayGrayscale (const std::vector< T > & RGB, const U rangeMax)`

The documentation for this class was generated from the following file:


- [gdcmSurfaceHelper.h](#)

25.259 gdcm::SurfaceReader Class Reference


This class defines a SURFACE IE reader. It reads surface mesh module attributes.

```
#include <gdcmSurfaceReader.h>
```

Inheritance diagram for gdcm::SurfaceReader:



Collaboration diagram for gdcm::SurfaceReader:



Public Member Functions

- [SurfaceReader](#) ()
- virtual [~SurfaceReader](#) ()
- unsigned long [GetNumberOfSurfaces](#) () const
- virtual bool [Read](#) ()

Read.

Protected Member Functions

- bool [ReadPointMacro](#) ([SmartPointer](#)< [Surface](#) > surface, const [DataSet](#) &surfaceDS)
- bool [ReadSurface](#) (const [Item](#) &surfacerItem, const unsigned long idx)
- bool [ReadSurfaces](#) ()

Additional Inherited Members

25.259.1 Detailed Description

This class defines a SURFACE IE reader. It reads surface mesh module attributes.

See Also

PS 3.3 A.1.2.18 , A.57 and C.27

25.259.2 Constructor & Destructor Documentation

25.259.2.1 `gdcm::SurfaceReader::SurfaceReader ()`

25.259.2.2 `virtual gdcm::SurfaceReader::~~SurfaceReader ()` [virtual]

25.259.3 Member Function Documentation

25.259.3.1 `unsigned long gdcm::SurfaceReader::GetNumberOfSurfaces ()` const

25.259.3.2 `virtual bool gdcm::SurfaceReader::Read ()` [virtual]

Read.

Reimplemented from [gdcm::SegmentReader](#).

25.259.3.3 `bool gdcm::SurfaceReader::ReadPointMacro (SmartPointer< Surface > surface, const DataSet & surfaceDS)`
[protected]

25.259.3.4 `bool gdcm::SurfaceReader::ReadSurface (const Item & surfacerItem, const unsigned long idx)` [protected]

25.259.3.5 `bool gdcm::SurfaceReader::ReadSurfaces ()` [protected]

The documentation for this class was generated from the following file:


- [gdcmSurfaceReader.h](#)

25.260 gdcm::SurfaceWriter Class Reference


This class defines a SURFACE IE writer. It writes surface mesh module attributes.

```
#include <gdcmSurfaceWriter.h>
```

Inheritance diagram for gdcm::SurfaceWriter:



Collaboration diagram for gdcm::SurfaceWriter:



Public Member Functions

- [SurfaceWriter](#) ()
- virtual [~SurfaceWriter](#) ()
- unsigned long [GetNumberOfSurfaces](#) ()
- void [SetNumberOfSurfaces](#) (const unsigned long nb)
- bool [Write](#) ()

Write.

Protected Member Functions

- void [ComputeNumberOfSurfaces](#) ()
- bool [PrepareWrite](#) ()
- bool [PrepareWritePointMacro](#) (SmartPointer< Surface > surface, DataSet &surfaceDS, const TransferSyntax &ts)

Protected Attributes

- unsigned long [NumberOfSurfaces](#)

Additional Inherited Members

25.260.1 Detailed Description

This class defines a SURFACE IE writer. It writes surface mesh module attributes.

See Also

PS 3.3 A.1.2.18 , A.57 and C.27

25.260.2 Constructor & Destructor Documentation

25.260.2.1 `gdcmm::SurfaceWriter::SurfaceWriter ()`

25.260.2.2 `virtual gdcmm::SurfaceWriter::~~SurfaceWriter () [virtual]`

25.260.3 Member Function Documentation

25.260.3.1 `void gdcmm::SurfaceWriter::ComputeNumberOfSurfaces () [protected]`

25.260.3.2 `unsigned long gdcmm::SurfaceWriter::GetNumberOfSurfaces ()`

25.260.3.3 `bool gdcmm::SurfaceWriter::PrepareWrite () [protected]`

25.260.3.4 `bool gdcmm::SurfaceWriter::PrepareWritePointMacro (SmartPointer< Surface > surface, DataSet & surfaceDS, const TransferSyntax & ts) [protected]`

25.260.3.5 `void gdcmm::SurfaceWriter::SetNumberOfSurfaces (const unsigned long nb)`

25.260.3.6 `bool gdcmm::SurfaceWriter::Write () [virtual]`

Write.

Reimplemented from [gdcmm::SegmentWriter](#).

25.260.4 Member Data Documentation

25.260.4.1 `unsigned long gdcmm::SurfaceWriter::NumberOfSurfaces [protected]`

The documentation for this class was generated from the following file:

- [gdcmmSurfaceWriter.h](#)

25.261 gdcmm::SwapCode Class Reference

[SwapCode](#) representation.

```
#include <gdcmSwapCode.h>
```

Public Types

- enum [SwapCodeType](#) {
 [Unknown](#) = 0,
 [LittleEndian](#) = 1234,
 [BigEndian](#) = 4321,
 [BadLittleEndian](#) = 3412,
 [BadBigEndian](#) = 2143 }

Public Member Functions

- [SwapCode](#) ([SwapCodeType](#) sc=[Unknown](#))
- [operator SwapCode::SwapCodeType](#) () const

Static Public Member Functions

- static const char * [GetSwapCodeString](#) ([SwapCode](#) const &sc)

Static Protected Member Functions

- static int [GetIndex](#) ([SwapCode](#) const &sc)

Friends

- std::ostream & [operator<<](#) (std::ostream &os, const [SwapCode](#) &sc)

25.261.1 Detailed Description

[SwapCode](#) representation.

Examples:

[TestByteSwap.cxx](#).

25.261.2 Member Enumeration Documentation

25.261.2.1 enum gdcm::SwapCode::SwapCodeType

Enumerator

Unknown

LittleEndian

BigEndian

BadLittleEndian

BadBigEndian

25.261.3 Constructor & Destructor Documentation

25.261.3.1 `gdcm::SwapCode::SwapCode (SwapCodeType sc = Unknown)` `[inline]`

25.261.4 Member Function Documentation

25.261.4.1 `static int gdcm::SwapCode::GetIndex (SwapCode const & sc)` `[static], [protected]`

25.261.4.2 `static const char* gdcm::SwapCode::GetSwapCodeString (SwapCode const & sc)` `[static]`

Referenced by `gdcm::operator<<()`.

25.261.4.3 `gdcm::SwapCode::operator SwapCode::SwapCodeType () const` `[inline]`

25.261.5 Friends And Related Function Documentation

25.261.5.1 `std::ostream& operator<< (std::ostream & os, const SwapCode & sc)` `[friend]`

The documentation for this class was generated from the following file:

- [gdcmSwapCode.h](#)

25.262 gdcm::SwapperDoOp Class Reference

```
#include <gdcmSwapper.h>
```

Static Public Member Functions

- `template<typename T >`
`static T Swap (T val)`
- `template<typename T >`
`static void SwapArray (T *array, size_t n)`

25.262.1 Member Function Documentation

25.262.1.1 `template<typename T > static T gdcm::SwapperDoOp::Swap (T val)` `[static]`

Referenced by `gdcm::Item::Read()`.

25.262.1.2 `template<typename T > static void gdcm::SwapperDoOp::SwapArray (T * array, size_t n)` `[inline], [static]`

The documentation for this class was generated from the following file:

- [gdcmSwapper.h](#)

25.263 gdcm::SwapperNoOp Class Reference

```
#include <gdcmSwapper.h>
```

Static Public Member Functions

- template<typename T >
static T [Swap](#) (T val)
- template<typename T >
static void [SwapArray](#) (T *, size_t)

25.263.1 Detailed Description

Examples:

[ReadExplicitLengthSQIVR.cxx](#).

25.263.2 Member Function Documentation

25.263.2.1 template<typename T > static T gdcm::SwapperNoOp::Swap (T val) [inline], [static]

Referenced by gdcm::EncodingImplementation< VR::VRBINARY >::Write().

25.263.2.2 template<typename T > static void gdcm::SwapperNoOp::SwapArray (T *, size_t) [inline], [static]

Referenced by gdcm::EncodingImplementation< VR::VRBINARY >::Read().

The documentation for this class was generated from the following file:

- [gdcmSwapper.h](#)

25.264 gdcm::System Class Reference

Class to do system operation.

```
#include <gdcmSystem.h>
```

Static Public Member Functions

- static bool [DeleteDirectory](#) (const char *source)
remove a directory named source
- static size_t [EncodeBytes](#) (char *out, const unsigned char *data, int size)
- static bool [FileExists](#) (const char *filename)
Check whether the specified file exist on the sytem.
- static bool [FileIsDirectory](#) (const char *name)
Check whether the file specified is a directory:
- static bool [FileIsSymlink](#) (const char *name)
Check whether name is a symlink.

- static size_t [FileSize](#) (const char *filename)
- static time_t [FileTime](#) (const char *filename)
- static bool [FormatDateTime](#) (char date[22], time_t t, long milliseconds=0)
- static bool [GetCurrentDateTime](#) (char date[22])
- static const char * [GetCurrentModuleFileName](#) ()
- static const char * [GetCurrentProcessFileName](#) ()
- static const char * [GetCurrentResourcesDirectory](#) ()
- static const char * [GetCWD](#) ()
- static bool [GetHostName](#) (char hostname[255])
- static const char * [GetLastError](#) ()
- Return the last error.*
- static const char * [GetLocaleCharSet](#) ()
- return locale charmap*
- static const char * [GetTimezoneOffsetFromUTC](#) ()
- static bool [MakeDirectory](#) (const char *path)
- Create a directory name path.*
- static bool [ParseDateTime](#) (time_t &timep, const char date[22])
- Parse a date stored as ASCII text into a time_t structured (discard millisecond if any)*
- static bool [ParseDateTime](#) (time_t &timep, long &milliseconds, const char date[22])
- static bool [RemoveFile](#) (const char *source)
- remove a file named source*
- static int [StrCaseCmp](#) (const char *s1, const char *s2)
- consistent func for C99 spec of strcasecmp/strncasecmp*
- static int [StrNCaseCmp](#) (const char *s1, const char *s2, size_t n)
- static char * [StrTokR](#) (char *ptr, const char *sep, char **end)
- strtok_r*

Static Protected Member Functions

- static bool [GetPermissions](#) (const char *file, unsigned short &mode)
- NOT THREAD SAFE.*
- static bool [SetPermissions](#) (const char *file, unsigned short mode)

25.264.1 Detailed Description

Class to do system operation.

OS independent functionalities

25.264.2 Member Function Documentation

25.264.2.1 static bool [gdcm::System::DeleteDirectory](#) (const char * *source*) [static]

remove a directory named source

25.264.2.2 static size_t [gdcm::System::EncodeBytes](#) (char * *out*, const unsigned char * *data*, int *size*) [static]

Used internally by the [UIDGenerator](#) class to convert a uuid tape to a DICOM [VR:UI](#) type

25.264.2.3 static bool gdcm::System::FileExists (const char * *filename*) [static]

Check whether the specified file exist on the sytem.

Examples:

[EncapsulateFileInRawData.cxx](#), [gdcmorthoplanes.cxx](#), and [MagnifyFile.cxx](#).

25.264.2.4 static bool gdcm::System::FilesDirectory (const char * *name*) [static]

Check whether the file specified is a directory:

Examples:

[gdcmorthoplanes.cxx](#), and [threadgdcm.cxx](#).

25.264.2.5 static bool gdcm::System::FilesSymlink (const char * *name*) [static]

Check whether name is a symlink.

25.264.2.6 static size_t gdcm::System::FileSize (const char * *filename*) [static]

Return the filesize. 0 if file does not exist.

Warning

you need to use FileExists to differentiate between empty file and missing file.
for very large size file and on system where size_t is not appropriate to store off_t value the function will return 0.

Examples:

[CheckBigEndianBug.cxx](#), [CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), and [EncapsulateFileInRawData.cxx](#).

25.264.2.7 static time_t gdcm::System::FileTime (const char * *filename*) [static]

Return the time of last modification of file 0 if the file does not exist

25.264.2.8 static bool gdcm::System::FormatDateTime (char *date[22]*, time_t *t*, long *milliseconds* = 0) [static]

format as ASCII text a time_t with milliseconds See [VR::DT](#) from DICOM PS 3.5 milliseconds is in the range [0, 999999]

25.264.2.9 static bool gdcm::System::GetCurrentDateTime (char *date[22]*) [static]

Return the current data time, and format it as ASCII text. This is simply a call to gettimeofday + FormatDateTime, since WIN32 do not have an implementation for gettimeofday, this is more portable. The call time(0) is not precise for our resolution

25.264.2.10 `static const char* gdcmm::System::GetCurrentModuleFileName () [static]`

Return the directory the current module is located: NOT THREAD SAFE

25.264.2.11 `static const char* gdcmm::System::GetCurrentProcessFileName () [static]`

Return the directory the current process (executable) is located: NOT THREAD SAFE

25.264.2.12 `static const char* gdcmm::System::GetCurrentResourcesDirectory () [static]`

On some system (Apple) return the path to the current bundled 'Resources' directory NOT THREAD SAFE

25.264.2.13 `static const char* gdcmm::System::GetCurrentWorkingDirectory () [static]`

Return current working directory Warning: if current working path is too long (>2048 bytes) the call will fail and call will return NULL NOT THREAD SAFE

25.264.2.14 `static bool gdcmm::System::GetHostName (char hostname[255]) [static]`

Retrieve the hostname, only the first 255 byte are copied. This may come handy to specify the Station Name

25.264.2.15 `static const char* gdcmm::System::GetLastError () [static]`

Return the last error.

25.264.2.16 `static const char* gdcmm::System::GetLocaleCharSet () [static]`

return locale charmap

25.264.2.17 `static bool gdcmm::System::GetPermissions (const char * file, unsigned short & mode) [static],
[protected]`

NOT THREAD SAFE.

25.264.2.18 `static const char* gdcmm::System::GetTimezoneOffsetFromUTC () [static]`

Return the value for Timezone Offset From UTC as string.

Warning

not thread safe

25.264.2.19 `static bool gdcmm::System::MakeDirectory (const char * path) [static]`

Create a directory name path.

25.264.2.20 `static bool gdcm::System::ParseDateTime (time_t & timep, const char date[22]) [static]`

Parse a date stored as ASCII text into a time_t structured (discard millisecond if any)

25.264.2.21 `static bool gdcm::System::ParseDateTime (time_t & timep, long & milliseconds, const char date[22]) [static]`

Parse a date stored as ASCII text into a time_t structured and millisecond

See Also

[FormatDateTime](#)

25.264.2.22 `static bool gdcm::System::RemoveFile (const char * source) [static]`

remove a file named source

25.264.2.23 `static bool gdcm::System::SetPermissions (const char * file, unsigned short mode) [static],
[protected]`

25.264.2.24 `static int gdcm::System::StrCaseCmp (const char * s1, const char * s2) [static]`

consistent func for C99 spec of strcasecmp/strncasecmp

25.264.2.25 `static int gdcm::System::StrNCaseCmp (const char * s1, const char * s2, size_t n) [static]`

Precondition

`n != 0`

25.264.2.26 `static char* gdcm::System::StrTokR (char * ptr, const char * sep, char ** end) [static]`

strtok_r

The documentation for this class was generated from the following file:

- [gdcmSystem.h](#)

25.265 gdcm::Table Class Reference

[Table.](#)

```
#include <gdcmTable.h>
```

Public Types

- `typedef std::map< Tag, TableEntry > MapTableEntry`

Public Member Functions

- [Table](#) ()
- [~Table](#) ()
- const [TableEntry](#) & [GetTableEntry](#) (const [Tag](#) &tag) const
- void [InsertEntry](#) ([Tag](#) const &tag, [TableEntry](#) const &te)

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [Table](#) &_val)

25.265.1 Detailed Description

[Table](#).

25.265.2 Member Typedef Documentation

25.265.2.1 typedef std::map<[Tag](#), [TableEntry](#)> [gdcm::Table::MapTableEntry](#)

25.265.3 Constructor & Destructor Documentation

25.265.3.1 [gdcm::Table::Table](#) () `[inline]`

25.265.3.2 [gdcm::Table::~~Table](#) () `[inline]`

25.265.4 Member Function Documentation

25.265.4.1 const [TableEntry](#)& [gdcm::Table::GetTableEntry](#) (const [Tag](#) & *tag*) const `[inline]`

25.265.4.2 void [gdcm::Table::InsertEntry](#) ([Tag](#) const & *tag*, [TableEntry](#) const & *te*) `[inline]`

25.265.5 Friends And Related Function Documentation

25.265.5.1 std::ostream& [operator<<](#) (std::ostream &_os, const [Table](#) &_val) `[friend]`

The documentation for this class was generated from the following file:

- [gdcmTable.h](#)

25.266 gdcm::TableEntry Class Reference

[TableEntry](#).

```
#include <gdcmTableEntry.h>
```

Public Member Functions

- [TableEntry](#) (const char *attribute=0, [Type](#) const &type=[Type](#)(), const char *des=0)
- [~TableEntry](#) ()

25.266.1 Detailed Description

[TableEntry](#).

25.266.2 Constructor & Destructor Documentation

25.266.2.1 `gdcm::TableEntry::TableEntry (const char * attribute = 0, Type const & type = Type (), const char * des = 0)`
`[inline]`

25.266.2.2 `gdcm::TableEntry::~~TableEntry ()` `[inline]`

The documentation for this class was generated from the following file:


- [gdcmTableEntry.h](#)

25.267 gdcm::TableReader Class Reference

Class for representing a [TableReader](#).

```
#include <gdcmTableReader.h>
```

Inheritance diagram for `gdcm::TableReader`:



Public Member Functions

- [TableReader](#) ([Defs](#) &defs)
- virtual [~TableReader](#) ()
- virtual void [CharacterDataHandler](#) (const char *data, int length)
- virtual void [EndElement](#) (const char *name)
- const [Defs](#) & [GetDefs](#) () const
- const char * [GetFilename](#) ()
- void [HandleIOD](#) (const char **atts)
- void [HandleIOEntry](#) (const char **atts)
- void [HandleMacro](#) (const char **atts)
- void [HandleMacroEntry](#) (const char **atts)
- void [HandleMacroEntryDescription](#) (const char **atts)

- void [HandleModule](#) (const char **atts)
- void [HandleModuleEntry](#) (const char **atts)
- void [HandleModuleEntryDescription](#) (const char **atts)
- void [HandleModuleInclude](#) (const char **atts)
- int [Read](#) ()
- void [SetFilename](#) (const char *filename)
- virtual void [StartElement](#) (const char *name, const char **atts)

25.267.1 Detailed Description

Class for representing a [TableReader](#).

Note

This class is an empty shell meant to be derived

25.267.2 Constructor & Destructor Documentation

25.267.2.1 `gdcmm::TableReader::TableReader (Defs & defs) [inline]`

25.267.2.2 `virtual gdcmm::TableReader::~~TableReader () [inline],[virtual]`

25.267.3 Member Function Documentation

25.267.3.1 `virtual void gdcmm::TableReader::CharacterDataHandler (const char * data, int length) [virtual]`

Reimplemented in [gdcmm::XMLDictReader](#), and [gdcmm::XMLPrivateDictReader](#).

25.267.3.2 `virtual void gdcmm::TableReader::EndElement (const char * name) [virtual]`

Reimplemented in [gdcmm::XMLDictReader](#), and [gdcmm::XMLPrivateDictReader](#).

25.267.3.3 `const Defs& gdcmm::TableReader::GetDefs () const [inline]`

25.267.3.4 `const char* gdcmm::TableReader::GetFilename () [inline]`

25.267.3.5 `void gdcmm::TableReader::HandleIOD (const char ** atts)`

25.267.3.6 `void gdcmm::TableReader::HandleIODEntry (const char ** atts)`

25.267.3.7 `void gdcmm::TableReader::HandleMacro (const char ** atts)`

25.267.3.8 `void gdcmm::TableReader::HandleMacroEntry (const char ** atts)`

25.267.3.9 `void gdcmm::TableReader::HandleMacroEntryDescription (const char ** atts)`

25.267.3.10 `void gdcmm::TableReader::HandleModule (const char ** atts)`

25.267.3.11 `void gdcmm::TableReader::HandleModuleEntry (const char ** atts)`

25.267.3.12 void gdcm::TableReader::HandleModuleEntryDescription (const char ** *atts*)

25.267.3.13 void gdcm::TableReader::HandleModuleInclude (const char ** *atts*)

25.267.3.14 int gdcm::TableReader::Read ()

25.267.3.15 void gdcm::TableReader::SetFilename (const char * *filename*) [inline]

25.267.3.16 virtual void gdcm::TableReader::StartElement (const char * *name*, const char ** *atts*) [virtual]

Reimplemented in [gdcm::XMLDictReader](#), and [gdcm::XMLPrivateDictReader](#).


The documentation for this class was generated from the following file:

- [gdcmTableReader.h](#)

25.268 gdcm::network::TableRow Class Reference

```
#include <gdcmULTransitionTable.h>
```

Collaboration diagram for gdcm::network::TableRow:



Public Member Functions

- [TableRow](#) ()
- [~TableRow](#) ()

Public Attributes

- [Transition](#) * [transitions](#) [[cMaxStateID](#)]

25.268.1 Constructor & Destructor Documentation

25.268.1.1 `gdcm::network::TableRow::TableRow () [inline]`

References `gdcm::network::cMaxStateID`, and transitions.

25.268.1.2 `gdcm::network::TableRow::~~TableRow () [inline]`

References `gdcm::network::cMaxStateID`, and transitions.

25.268.2 Member Data Documentation

25.268.2.1 `Transition* gdcm::network::TableRow::transitions[cMaxStateID]`

Referenced by `TableRow()`, and `~TableRow()`.

The documentation for this class was generated from the following file:


- [gdcmULTransitionTable.h](#)

25.269 gdcm::Tag Class Reference

Class to represent a DICOM Data [Element](#) ([Attribute](#)) [Tag](#) (Group, [Element](#)). Basically an `uint32_t` which can also be expressed as two `uint16_t` (group and element)

```
#include <gdcmTag.h>
```

Inheritance diagram for `gdcm::Tag`:



Public Member Functions

- [Tag](#) (`uint16_t` group, `uint16_t` element)
*Constructor with 2*uint16_t.*
- [Tag](#) (`uint32_t` tag=0)
*Constructor with 1*uint32_t Prefer the ctor that takes two uint16_t.*

- [Tag](#) (const [Tag](#) &_val)
- [uint16_t GetElement](#) () const
Returns the 'Element number' of the given Tag.
- [uint32_t GetElementTag](#) () const
Returns the full tag value of the given Tag.
- [uint16_t GetGroup](#) () const
Returns the 'Group number' of the given Tag.
- [uint32_t GetLength](#) () const
return the length of tag (read: size on disk)
- [Tag GetPrivateCreator](#) () const
Return the Private Creator Data Element tag of a private data element.
- [bool IsGroupLength](#) () const
return whether the tag correspond to a group length tag:
- [bool IsGroupXX](#) (const [Tag](#) &t) const
e.g 6002,3000 belong to groupXX: 6000,3000
- [bool IsIllegal](#) () const
return if the tag is considered to be an illegal tag
- [bool IsPrivate](#) () const
- [bool IsPrivateCreator](#) () const
- [bool IsPublic](#) () const
- [bool operator!=](#) (const [Tag](#) &_val) const
- [bool operator<](#) (const [Tag](#) &_val) const
- [bool operator<=](#) (const [Tag](#) &t2) const
- [Tag & operator=](#) (const [Tag](#) &_val)
- [bool operator==](#) (const [Tag](#) &_val) const
- [const uint16_t & operator\[\]](#) (const unsigned int &_id) const
Returns the Group or Element of the given Tag, depending on id (0/1)
- [uint16_t & operator\[\]](#) (const unsigned int &_id)
Returns the Group or Element of the given Tag, depending on id (0/1)
- [std::string PrintAsPipeSeparatedString](#) () const
- [template<typename TSwap >](#)
[std::istream & Read](#) (std::istream &is)
Read a tag from binary representation.
- [bool ReadFromCommaSeparatedString](#) (const char *str)
- [bool ReadFromPipeSeparatedString](#) (const char *str)
- [void SetElement](#) (uint16_t element)
Sets the 'Element number' of the given Tag.
- [void SetElementTag](#) (uint16_t group, uint16_t element)
Sets the 'Group number' & 'Element number' of the given Tag.
- [void SetElementTag](#) (uint32_t tag)
Sets the full tag value of the given Tag.
- [void SetGroup](#) (uint16_t group)
Sets the 'Group number' of the given Tag.
- [void SetPrivateCreator](#) ([Tag](#) const &t)
Set private creator:
- [template<typename TSwap >](#)
[const std::ostream & Write](#) (std::ostream &os) const
Write a tag in binary rep.

Friends

- `std::ostream & operator<< (std::ostream &_os, const Tag &_val)`
- `std::istream & operator>> (std::istream &_is, Tag &_val)`

25.269.1 Detailed Description

Class to represent a DICOM Data [Element](#) ([Attribute](#)) [Tag](#) (Group, [Element](#)). Basically an `uint32_t` which can also be expressed as two `uint16_t` (group and element)

Note

DATA ELEMENT TAG: A unique identifier for a Data [Element](#) composed of an ordered pair of numbers (a Group Number followed by an [Element](#) Number). GROUP NUMBER: The first number in the ordered pair of numbers that makes up a Data [Element](#) [Tag](#). ELEMENT NUMBER: The second number in the ordered pair of numbers that makes up a Data [Element](#) [Tag](#).

Examples:

[ChangeSequenceUltrasound.cxx](#), [ClinicalTrialAnnotate.cxx](#), [CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [CreateJPIPDataSet.cxx](#), [DumpToSQLITE3.cxx](#), [DuplicatePCDE.cxx](#), [EncapsulateFileInRawData.cxx](#), [Extract-EncryptedContent.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [FixBroken-J2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [gdcmrtionplan.cxx](#), [gdcmrtplan.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenFakeImage.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [GetJPEGSamplePrecision.cxx](#), [GetSequenceUltrasound.cxx](#), [GetSubSequenceData.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDSExplicit.cxx](#), [MergeTwoFiles.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [PublicDict.cxx](#), [ReadAndDumpDICOMDIR.cxx](#), [ReadAndPrintAttributes.cxx](#), [ReadExplicitLength-SQIVR.cxx](#), [rle2img.cxx](#), [SimpleScanner.cxx](#), [SortImage.cxx](#), [StreamImageReaderTest.cxx](#), [TraverseModules.cxx](#), and [VolumeSorter.cxx](#).

25.269.2 Constructor & Destructor Documentation

25.269.2.1 `gdcm::Tag::Tag (uint16_t group, uint16_t element) [inline]`

Constructor with 2*`uint16_t`.

25.269.2.2 `gdcm::Tag::Tag (uint32_t tag = 0) [inline]`

Constructor with 1*`uint32_t` Prefer the ctor that takes two `uint16_t`.

25.269.2.3 `gdcm::Tag::Tag (const Tag &_val) [inline]`

References tag.

25.269.3 Member Function Documentation

25.269.3.1 `uint16_t gdcm::Tag::GetElement () const [inline]`

Returns the '[Element](#) number' of the given [Tag](#).

Examples:

[DuplicatePCDE.cxx](#), and [PublicDict.cxx](#).

Referenced by `gdcm::DataSet::ComputeGroupLength()`, `IsGroupXX()`, `gdcm::PrivateDict::PrintXML()`, `gdcm::SequenceOfFragments::ReadValue()`, and `SetPrivateCreator()`.

25.269.3.2 `uint32_t gdcm::Tag::GetElementTag () const [inline]`

Returns the full tag value of the given [Tag](#).

25.269.3.3 `uint16_t gdcm::Tag::GetGroup () const [inline]`

Returns the 'Group number' of the given [Tag](#).

Examples:

[DuplicatePCDE.cxx](#), and [GenAllVR.cxx](#).

Referenced by `gdcm::DataSet::ComputeGroupLength()`, `gdcm::CommandDataSet::Insert()`, `gdcm::FileMetaInformation::Insert()`, `gdcm::DataSet::Insert()`, `IsGroupXX()`, `gdcm::PrivateDict::PrintXML()`, `gdcm::SequenceOfFragments::ReadValue()`, `gdcm::Attribute< Group, Element, TVR, TVM >::SetFromDataElement()`, `gdcm::Attribute< Group, Element, TVR, VM::VM1 >::SetFromDataElement()`, and `gdcm::Attribute< Group, Element, TVR, VM::VM1_n >::SetFromDataElement()`.

25.269.3.4 `uint32_t gdcm::Tag::GetLength () const [inline]`

return the length of tag (read: size on disk)

25.269.3.5 `Tag gdcm::Tag::GetPrivateCreator () const [inline]`

Return the Private Creator Data [Element](#) tag of a private data element.

References `SetElement()`.

25.269.3.6 `bool gdcm::Tag::IsGroupLength () const [inline]`

return whether the tag correspond to a group length tag:

25.269.3.7 `bool gdcm::Tag::IsGroupXX (const Tag & t) const [inline]`

e.g 6002,3000 belong to groupXX: 6000,3000

References `GetElement()`, `GetGroup()`, and `IsPrivate()`.

25.269.3.8 `bool gdcm::Tag::IsIllegal () const [inline]`

return if the tag is considered to be an illegal tag

25.269.3.9 `bool gdcm::Tag::IsPrivate () const [inline]`

PRIVATE DATA ELEMENT: Additional Data [Element](#), defined by an implementor, to communicate information that is not contained in Standard Data Elements. Private Data elements have odd Group Numbers.

Examples:

[DuplicatePCDE.cxx](#).

Referenced by `IsGroupXX()`, and `SetPrivateCreator()`.

25.269.3.10 `bool gdcm::Tag::IsPrivateCreator () const [inline]`

Returns if tag is a Private Creator (xxxx,00yy), where xxxx is odd number and yy in [0x10,0xFF]

Examples:

[DuplicatePCDE.cxx](#).

25.269.3.11 `bool gdcm::Tag::IsPublic () const [inline]`

STANDARD DATA ELEMENT: A Data [Element](#) defined in the DICOM Standard, and therefore listed in the DICOM Data [Element](#) Dictionary in PS 3.6. Is the [Tag](#) from the Public dict...well the implementation is buggy it does not prove the element is indeed in the dict...

25.269.3.12 `bool gdcm::Tag::operator!= (const Tag &_val) const [inline]`

References tag.

25.269.3.13 `bool gdcm::Tag::operator< (const Tag &_val) const [inline]`

DICOM Standard expects the Data [Element](#) to be sorted by Tags All other comparison can be constructed from this one and operator ==

References tag, and tags.

25.269.3.14 `bool gdcm::Tag::operator<= (const Tag &t2) const [inline]`

25.269.3.15 `Tag& gdcm::Tag::operator= (const Tag &_val) [inline]`

References tag.

25.269.3.16 `bool gdcm::Tag::operator== (const Tag &_val) const [inline]`

References tag.

25.269.3.17 `const uint16_t& gdcm::Tag::operator[] (const unsigned int &_id) const [inline]`

Returns the Group or [Element](#) of the given [Tag](#), depending on id (0/1)

25.269.3.18 `uint16_t& gdcm::Tag::operator[] (const unsigned int &_id) [inline]`

Returns the Group or [Element](#) of the given [Tag](#), depending on id (0/1)

25.269.3.19 `std::string gdcm::Tag::PrintAsPipeSeparatedString () const`

Print as a pipe separated string (GDCM 1.x compat only). Do not use in newer code

See Also

[ReadFromPipeSeparatedString](#)

25.269.3.20 `template<typename TSwap> std::istream& gdcm::Tag::Read (std::istream & is) [inline]`

Read a tag from binary representation.

25.269.3.21 `bool gdcm::Tag::ReadFromCommaSeparatedString (const char * str)`

Read from a comma separated string. This is a highly user oriented function, the string should be formatted as: 1234,5678 to specify the tag (0x1234,0x5678) The notation comes from the DICOM standard, and is handy to use from a command line program

25.269.3.22 `bool gdcm::Tag::ReadFromPipeSeparatedString (const char * str)`

Read from a pipe separated string (GDCM 1.x compat only). Do not use in newer code

See Also

[ReadFromCommaSeparatedString](#)

25.269.3.23 `void gdcm::Tag::SetElement (uint16_t element) [inline]`

Sets the '[Element](#) number' of the given [Tag](#).

Examples:

[DuplicatePCDE.cxx](#), and [PublicDict.cxx](#).

Referenced by `GetPrivateCreator()`, and `gdcm::operator>>()`.

25.269.3.24 `void gdcm::Tag::SetElementTag (uint16_t group, uint16_t element) [inline]`

Sets the 'Group number' & '[Element](#) number' of the given [Tag](#).

25.269.3.25 `void gdcm::Tag::SetElementTag (uint32_t tag) [inline]`

Sets the full tag value of the given [Tag](#).

25.269.3.26 `void gdcm::Tag::SetGroup (uint16_t group) [inline]`

Sets the 'Group number' of the given [Tag](#).

Referenced by `gdcm::operator>>()`.

25.269.3.27 `void gdcM::Tag::SetPrivateCreator (Tag const & t) [inline]`

Set private creator:

Examples:

[DuplicatePCDE.cxx](#).

References `GetElement()`, and `IsPrivate()`.

25.269.3.28 `template<typename TSwap > const std::ostream& gdcM::Tag::Write (std::ostream & os) const [inline]`

Write a tag in binary rep.

Referenced by `gdcM::SequenceOfItems::Write()`, `gdcM::Item::Write()`, and `gdcM::SequenceOfFragments::Write()`.

25.269.4 Friends And Related Function Documentation

25.269.4.1 `std::ostream& operator<< (std::ostream & _os, const Tag & _val) [friend]`

25.269.4.2 `std::istream& operator>> (std::istream & _is, Tag & _val) [friend]`

25.269.5 Member Data Documentation

25.269.5.1 `char gdcM::Tag::bytes[4]`

25.269.5.2 `uint32_t gdcM::Tag::tag`

Referenced by `operator!=()`, `operator<()`, `operator=()`, `operator==()`, and `Tag()`.

25.269.5.3 `uint16_t gdcM::Tag::tags[2]`

Referenced by `operator<()`.

The documentation for this class was generated from the following file:

- [gdcMTag.h](#)

25.270 gdcM::TagPath Class Reference

class to handle a path of tag.

```
#include <gdcMTagPath.h>
```

Public Member Functions

- [TagPath \(\)](#)
- [~TagPath \(\)](#)
- bool [ConstructFromString](#) (const char *path)
- bool [ConstructFromTagList](#) (Tag const *l, unsigned int n)

Construct from a list of tags.

- void [Print](#) (std::ostream &) const
- bool [Push](#) (Tag const &t)
- bool [Push](#) (unsigned int itemnum)

Static Public Member Functions

- static bool [IsValid](#) (const char *path)

Return if path is valid or not.

25.270.1 Detailed Description

class to handle a path of tag.

Any Resemblance to Existing XPath is Purely Coincidental ftp://medical.nema.org/medical/dicom/supps/sup118-_pc.pdf

25.270.2 Constructor & Destructor Documentation

25.270.2.1 `gdcm::TagPath::TagPath ()`

25.270.2.2 `gdcm::TagPath::~~TagPath ()`

25.270.3 Member Function Documentation

25.270.3.1 `bool gdcm::TagPath::ConstructFromString (const char * path)`

"/0018,0018/"... No space allowed, comma is use to separate tag group from tag element and slash is used to separate tag return false if invalid

25.270.3.2 `bool gdcm::TagPath::ConstructFromTagList (Tag const * l, unsigned int n)`

Construct from a list of tags.

25.270.3.3 `static bool gdcm::TagPath::IsValid (const char * path) [static]`

Return if path is valid or not.

25.270.3.4 `void gdcm::TagPath::Print (std::ostream &) const`

25.270.3.5 `bool gdcm::TagPath::Push (Tag const & t)`

25.270.3.6 `bool gdcm::TagPath::Push (unsigned int itemnum)`

The documentation for this class was generated from the following file:

- [gdcmTagPath.h](#)

25.271 gdcm::Testing Class Reference

class for testing

```
#include <gdcmTesting.h>
```

Public Types

- typedef const char *const (* [MD5DataImagesType](#))[2]
- typedef const char *const (* [MediaStorageDataFilesType](#))[2]
return the table that map the media storage (as string) of a filename (gdcmData)

Public Member Functions

- [Testing](#) ()
- [~Testing](#) ()
- void [Print](#) (std::ostream &os=std::cout)
Print.

Static Public Member Functions

- static bool [ComputeFileMD5](#) (const char *filename, char digest_str[33])
- static bool [ComputeMD5](#) (const char *buffer, unsigned long buf_len, char digest_str[33])
- static const char * [GetDataExtraRoot](#) ()
Return the GDCM DATA EXTRA ROOT.
- static const char * [GetDataRoot](#) ()
Return the GDCM DATA ROOT.
- static const char * [GetFileName](#) (unsigned int file)
- static const char *const * [GetFileNames](#) ()
return the table of fullpath to gdcmData DICOM files:
- static int [GetLossyFlagFromFile](#) (const char *filepath)
- static const char *const * [GetMD5DataImage](#) (unsigned int file)
- static [MD5DataImagesType](#) [GetMD5DataImages](#) ()
- static const char * [GetMD5FromBrokenFile](#) (const char *filepath)
- static const char * [GetMD5FromFile](#) (const char *filepath)
- static const char *const * [GetMediaStorageDataFile](#) (unsigned int file)
- static [MediaStorageDataFilesType](#) [GetMediaStorageDataFiles](#) ()
- static const char * [GetMediaStorageFromFile](#) (const char *filepath)
- static unsigned int [GetNumberOfFileNames](#) ()
- static unsigned int [GetNumberOfMD5DataImages](#) ()
- static unsigned int [GetNumberOfMediaStorageDataFiles](#) ()
- static const char * [GetPixelSpacingDataRoot](#) ()
Return the GDCM PIXEL SPACING DATA ROOT (See David Clunie website for dataset)
- static std::streamoff [GetSelectedTagsOffsetFromFile](#) (const char *filepath)
- static const char * [GetSourceDirectory](#) ()
- static std::streamoff [GetStreamOffsetFromFile](#) (const char *filepath)
- static const char * [GetTempDirectory](#) (const char *subdir=0)
- static const wchar_t * [GetTempDirectoryW](#) (const wchar_t *subdir=0)

NOT THREAD SAFE.

- static const char * [GetTempFilename](#) (const char *filename, const char *subdir=0)

NOT THREAD SAFE.

- static const wchar_t * [GetTempFilenameW](#) (const wchar_t *filename, const wchar_t *subdir=0)

NOT THREAD SAFE.

25.271.1 Detailed Description

class for testing

this class is used for the nightly regression system for GDCM It makes heavily use of md5 computation

See Also

[gdcm::MD5](#) class for md5 computation

25.271.2 Member Typedef Documentation

25.271.2.1 `typedef const char* const(* gdcm::Testing::MD5DataImagesType)[2]`

return the table that map the md5 (as in md5sum) of the Pixel Data associated to a filename

25.271.2.2 `typedef const char* const(* gdcm::Testing::MediaStorageDataFileType)[2]`

return the table that map the media storage (as string) of a filename (gdcmData)

25.271.3 Constructor & Destructor Documentation

25.271.3.1 `gdcm::Testing::Testing () [inline]`

25.271.3.2 `gdcm::Testing::~~Testing () [inline]`

25.271.4 Member Function Documentation

25.271.4.1 `static bool gdcm::Testing::ComputeFileMD5 (const char * filename, char digest_str[33]) [static]`

25.271.4.2 `static bool gdcm::Testing::ComputeMD5 (const char * buffer, unsigned long buf_len, char digest_str[33]) [static]`

[MD5](#) stuff digest_str needs to be at least : strlen = [2*16+1]; string will be \0 padded. (md5 are 32 bytes long) [Testing](#) is not meant to be shipped with an installed GDCM release, always prefer the [gdcm::MD5](#) API when doing md5 computation.

25.271.4.3 `static const char* gdcm::Testing::GetDataExtraRoot () [static]`

Return the GDCM DATA EXTRA ROOT.

Examples:

[DiscriminateVolume.cxx](#), [reslicesphere.cxx](#), and [VolumeSorter.cxx](#).

25.271.4.4 `static const char* gdcm::Testing::GetDataRoot () [static]`

Return the GDCM DATA ROOT.

Examples:

[Convert16BitsTo8Bits.cxx](#), [ConvertMultiFrameToSingleFrame.cxx](#), [ConvertRGBToLuminance.cxx](#), and [Magnify-File.cxx](#).

25.271.4.5 `static const char* gdcm::Testing::GetFileName (unsigned int file) [static]`

25.271.4.6 `static const char* const* gdcm::Testing::GetFileNames () [static]`

return the table of fullpath to gdcmData DICOM files:

Examples:

[TestReader.cxx](#).

25.271.4.7 `static int gdcm::Testing::GetLossyFlagFromFile (const char * filepath) [static]`

Return the lossy flag of the given filename -1 -> Error 0 -> Lossless 1 -> Lossy

25.271.4.8 `static const char* const* gdcm::Testing::GetMD5DataImage (unsigned int file) [static]`

25.271.4.9 `static MD5DataImagesType gdcm::Testing::GetMD5DataImages () [static]`

25.271.4.10 `static const char* gdcm::Testing::GetMD5FromBrokenFile (const char * filepath) [static]`

Return what should have been the md5 of file 'filepath' This is based on current GDCM implementation to decipher a broken DICOM file.

25.271.4.11 `static const char* gdcm::Testing::GetMD5FromFile (const char * filepath) [static]`

25.271.4.12 `static const char* const* gdcm::Testing::GetMediaStorageDataFile (unsigned int file) [static]`

25.271.4.13 `static MediaStorageDataFilesType gdcm::Testing::GetMediaStorageDataFiles () [static]`

25.271.4.14 `static const char* gdcm::Testing::GetMediaStorageFromFile (const char * filepath) [static]`

Examples:

[TestReader.cxx](#).

25.271.4.15 `static unsigned int gdcm::Testing::GetNumberOfFileNames () [static]`

25.271.4.16 `static unsigned int gdcm::Testing::GetNumberOfMD5DataImages () [static]`

25.271.4.17 `static unsigned int gdcm::Testing::GetNumberOfMediaStorageDataFiles () [static]`

25.271.4.18 `static const char* gdcm::Testing::GetPixelSpacingDataRoot () [static]`

Return the GDCM PIXEL SPACING DATA ROOT (See David Clunie website for dataset)

25.271.4.19 `static std::streamoff gdcm::Testing::GetSelectedTagsOffsetFromFile (const char * filepath) [static]`

Return the offset just after Pixel Data Length (7fe0,0000) if found. Otherwise the offset of the very first pixel cell in Pixel Data -1 if not found

25.271.4.20 `static const char* gdcm::Testing::GetSourceDirectory () [static]`

25.271.4.21 `static std::streamoff gdcm::Testing::GetStreamOffsetFromFile (const char * filepath) [static]`

Return the offset of the very first pixel cell in the PixelData -1 if not found

25.271.4.22 `static const char* gdcm::Testing::GetTempDirectory (const char * subdir = 0) [static]`

NOT THREAD SAFE Returns the temp directory as used in testing needing to output data:

25.271.4.23 `static const wchar_t* gdcm::Testing::GetTempDirectoryW (const wchar_t * subdir = 0) [static]`

NOT THREAD SAFE.

25.271.4.24 `static const char* gdcm::Testing::GetTempFilename (const char * filename, const char * subdir = 0) [static]`

NOT THREAD SAFE.

25.271.4.25 `static const wchar_t* gdcm::Testing::GetTempFilenameW (const wchar_t * filename, const wchar_t * subdir = 0) [static]`

NOT THREAD SAFE.

25.271.4.26 `void gdcm::Testing::Print (std::ostream & os = std::cout)`

Print.

The documentation for this class was generated from the following file:

- [gdcmTesting.h](#)

25.272 gdcm::Trace Class Reference

[Trace.](#)

```
#include <gdcmTrace.h>
```

Public Member Functions

- [Trace](#) ()
- [~Trace](#) ()

Static Public Member Functions

- static void [DebugOff](#) ()
- static void [DebugOn](#) ()
- static void [ErrorOff](#) ()
- static void [ErrorOn](#) ()
- static bool [GetDebugFlag](#) ()
- static std::ostream & [GetDebugStream](#) ()
- static bool [GetErrorFlag](#) ()
- static std::ostream & [GetErrorStream](#) ()
- static std::ostream & [GetStream](#) ()
- static bool [GetWarningFlag](#) ()
- static std::ostream & [GetWarningStream](#) ()
- static void [SetDebug](#) (bool debug)
Turn debug messages on (default: false)
- static void [SetDebugStream](#) (std::ostream &os)
Explicitly set the stream which receive Debug messages:
- static void [SetError](#) (bool debug)
Turn error messages on (default: true)
- static void [SetErrorStream](#) (std::ostream &os)
Explicitly set the stream which receive Error messages:
- static void [SetStream](#) (std::ostream &os)
- static void [SetStreamToFile](#) (const char *filename)
- static void [SetWarning](#) (bool debug)
Turn warning messages on (default: true)
- static void [SetWarningStream](#) (std::ostream &os)
Explicitly set the stream which receive Warning messages:
- static void [WarningOff](#) ()
- static void [WarningOn](#) ()

25.272.1 Detailed Description

[Trace](#).

Debug / Warning and Error are encapsulated in this class by default the [Trace](#) class will redirect any debug/warning/error to std::cerr. Unless SetStream was specified with another (open) stream or SetStreamToFile was specified to a writable file on the system.

Warning

All string messages are removed during compilation time when compiled with CMAKE_BUILD_TYPE being set to either:

- Release
- MinSizeRel It is recommended to compile with RelWithDebInfo and/or Debug during prototyping of applications.

25.272.2 Constructor & Destructor Documentation

25.272.2.1 `gdcm::Trace::Trace ()`

25.272.2.2 `gdcm::Trace::~~Trace ()`

25.272.3 Member Function Documentation

25.272.3.1 `static void gdcm::Trace::DebugOff () [static]`

Examples:

[TestReader.cxx](#).

25.272.3.2 `static void gdcm::Trace::DebugOn () [static]`

Examples:

[Fake_Image_Using_Stream_Image_Writer.cxx](#), and [StreamImageReaderTest.cxx](#).

25.272.3.3 `static void gdcm::Trace::ErrorOff () [static]`

25.272.3.4 `static void gdcm::Trace::ErrorOn () [static]`

25.272.3.5 `static bool gdcm::Trace::GetDebugFlag () [static]`

25.272.3.6 `static std::ostream& gdcm::Trace::GetDebugStream () [static]`

25.272.3.7 `static bool gdcm::Trace::GetErrorFlag () [static]`

25.272.3.8 `static std::ostream& gdcm::Trace::GetErrorStream () [static]`

25.272.3.9 `static std::ostream& gdcm::Trace::GetStream () [static]`

25.272.3.10 `static bool gdcm::Trace::GetWarningFlag () [static]`

25.272.3.11 `static std::ostream& gdcm::Trace::GetWarningStream () [static]`

25.272.3.12 `static void gdcm::Trace::SetDebug (bool debug) [static]`

Turn debug messages on (default: false)

Examples:

[DumpToSQLITE3.cxx](#).

25.272.3.13 `static void gdcm::Trace::SetDebugStream (std::ostream & os) [static]`

Explicitely set the stream which receive Debug messages:

25.272.3.14 `static void gdcm::Trace::SetError (bool debug) [static]`

Turn error messages on (default: true)

25.272.3.15 `static void gdcm::Trace::SetErrorStream (std::ostream & os) [static]`

Explicitely set the stream which receive Error messages:

Examples:

[CStoreQtProgress.cxx](#).

25.272.3.16 `static void gdcm::Trace::SetStream (std::ostream & os) [static]`

Explicitely set the ostream for [gdcm::Trace](#) to report to This will set the DebugStream, WarningStream and ErrorStream at once:

25.272.3.17 `static void gdcm::Trace::SetStreamToFile (const char * filename) [static]`

Explicitely set the filename for [gdcm::Trace](#) to report to The file will be created (it will not append to existing file)

25.272.3.18 `static void gdcm::Trace::SetWarning (bool debug) [static]`

Turn warning messages on (default: true)

Examples:

[DumpToSQLITE3.cxx](#).

25.272.3.19 `static void gdcm::Trace::SetWarningStream (std::ostream & os) [static]`

Explicitely set the stream which receive Warning messages:

25.272.3.20 `static void gdcm::Trace::WarningOff () [static]`

Examples:

[TestReader.cxx](#).

25.272.3.21 `static void gdcm::Trace::WarningOn () [static]`

Examples:

[Fake_Image_Using_Stream_Image_Writer.cxx](#), and [StreamImageReaderTest.cxx](#).

The documentation for this class was generated from the following file:

- [gdcmTrace.h](#)

25.273 gdcm::TransferSyntax Class Reference

Class to manipulate Transfer Syntax.

```
#include <gdcmTransferSyntax.h>
```

Public Types

- enum [NegociatedType](#) {
 [Unknown](#) = 0,
 [Explicit](#),
 [Implicit](#) }
- enum [TSType](#) {
 [ImplicitVRLittleEndian](#) = 0,
 [ImplicitVRBigEndianPrivateGE](#),
 [ExplicitVRLittleEndian](#),
 [DeflatedExplicitVRLittleEndian](#),
 [ExplicitVRBigEndian](#),
 [JPEGBaselineProcess1](#),
 [JPEGExtendedProcess2_4](#),
 [JPEGExtendedProcess3_5](#),
 [JPEGSpectralSelectionProcess6_8](#),
 [JPEGFullProgressionProcess10_12](#),
 [JPEGLosslessProcess14](#),
 [JPEGLosslessProcess14_1](#),
 [JPEGLSLossless](#),
 [JPEGLSNearLossless](#),
 [JPEG2000Lossless](#),
 [JPEG2000](#),
 [JPEG2000Part2Lossless](#),
 [JPEG2000Part2](#),
 [RLELossless](#),
 [MPEG2MainProfile](#),
 [ImplicitVRBigEndianACRNEMA](#),
 [CT_private_ELE](#),
 [JPIPReferenced](#),
 [TS_END](#) }

Public Member Functions

- [TransferSyntax](#) ([TSType](#) type=[ImplicitVRLittleEndian](#))
- bool [CanStoreLossy](#) () const
- [NegociatedType](#) [GetNegociatedType](#) () const
- const char * [GetString](#) () const
- [SwapCode](#) [GetSwapCode](#) () const
- bool [IsEncapsulated](#) () const
- bool [IsEncoded](#) () const
- bool [IsExplicit](#) () const
- bool [IsImplicit](#) () const
- bool [IsLossless](#) () const
- bool [IsLossy](#) () const
- bool [IsValid](#) () const
- [operator TSType](#) () const

Static Public Member Functions

- static const char * [GetTSSString](#) (TSType ts)
- static [TSType](#) [GetTSType](#) (const char *str)

Friends

- std::ostream & [operator<<](#) (std::ostream &os, const [TransferSyntax](#) &ts)

25.273.1 Detailed Description

Class to manipulate Transfer Syntax.

Note

TRANSFER SYNTAX (Standard and Private): A set of encoding rules that allow Application Entities to unambiguously negotiate the encoding techniques (e.g., Data [Element](#) structure, byte ordering, compression) they are able to support, thereby allowing these Application Entities to communicate.

Todo : The implementation is completely retarded -> see [gdcm::UIDs](#) for a replacement We need: IsSupported We need preprocess of raw/xml file We need GetFullName()

Need a notion of Private Syntax. As defined in PS 3.5. Section 9.2

See Also

[UIDs](#)

Examples:

[GetJPEGSamplePrecision.cxx](#), and [LargeVRDSExplicit.cxx](#).

25.273.2 Member Enumeration Documentation

25.273.2.1 enum [gdcm::TransferSyntax::NegociatedType](#)

Enumerator

Unknown

Explicit

Implicit

25.273.2.2 enum [gdcm::TransferSyntax::TSType](#)

Enumerator

ImplicitVRLittleEndian

ImplicitVRBigEndianPrivateGE

ExplicitVRLittleEndian

DeflatedExplicitVRLittleEndian

ExplicitVRBigEndian
JPEGBaselineProcess1
JPEGExtendedProcess2_4
JPEGExtendedProcess3_5
JPEGSpectralSelectionProcess6_8
JPEGFullProgressionProcess10_12
JPEGLosslessProcess14
JPEGLosslessProcess14_1
JPEGLSLossless
JPEGLSNearLossless
JPEG2000Lossless
JPEG2000
JPEG2000Part2Lossless
JPEG2000Part2
RLELossless
MPEG2MainProfile
ImplicitVRBigEndianACRNEMA
CT_private_ELE
JPIPReferenced
TS_END

25.273.3 Constructor & Destructor Documentation

25.273.3.1 `gdcm::TransferSyntax::TransferSyntax (TSType type = ImplicitVRLittleEndian) [inline]`

25.273.4 Member Function Documentation

25.273.4.1 `bool gdcm::TransferSyntax::CanStoreLossy () const`

return if TransFer Syntax Allow storing of Lossy Pixel Data

25.273.4.2 `NegotiatedType gdcm::TransferSyntax::GetNegociatedType () const`

25.273.4.3 `const char* gdcm::TransferSyntax::GetString () const [inline]`

References `GetTSString()`.

25.273.4.4 `SwapCode gdcm::TransferSyntax::GetSwapCode () const`

Deprecated Return the [SwapCode](#) associated with the Transfer Syntax. Be careful with the special GE private syntax the [DataSet](#) is written in little endian but the Pixel Data is in Big Endian.

25.273.4.5 `static const char* gdcm::TransferSyntax::GetTSString (TSType ts) [static]`

Examples:

[LargeVRDSExplicit.cxx.](#)

Referenced by `GetString()`, and `gdcm::operator<<()`.

25.273.4.6 `static TSType gdcm::TransferSyntax::GetTSType (const char * str) [static]`

25.273.4.7 `bool gdcm::TransferSyntax::IsEncapsulated () const`

Examples:

[ExtractIconFromFile.cxx.](#)

25.273.4.8 `bool gdcm::TransferSyntax::IsEncoded () const`

25.273.4.9 `bool gdcm::TransferSyntax::IsExplicit () const`

25.273.4.10 `bool gdcm::TransferSyntax::IsImplicit () const`

25.273.4.11 `bool gdcm::TransferSyntax::IsLossless () const`

Return if the transfer syntax algorithm is a lossless algorithm

25.273.4.12 `bool gdcm::TransferSyntax::IsLossy () const`

Return if the transfer syntax algorithm is a lossy algorithm

25.273.4.13 `bool gdcm::TransferSyntax::IsValid () const [inline]`

25.273.4.14 `gdcm::TransferSyntax::operator TSType () const [inline]`

25.273.5 Friends And Related Function Documentation

25.273.5.1 `std::ostream& operator<< (std::ostream & os, const TransferSyntax & ts) [friend]`

The documentation for this class was generated from the following file:

- [gdcmTransferSyntax.h](#)

25.274 gdcm::network::TransferSyntaxSub Class Reference

[TransferSyntaxSub](#) Table 9-15 TRANSFER SYNTAX SUB-ITEM FIELDS.

```
#include <gdcmTransferSyntaxSub.h>
```


Public Member Functions

- [TransferSyntaxSub](#) ()
- const char * [GetName](#) () const
- bool [operator==](#) (const [TransferSyntaxSub](#) &ts) const
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- void [SetName](#) (const char *name)
- void [SetNameFromUID](#) (UIDs::TSName tsname)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.274.1 Detailed Description

[TransferSyntaxSub](#) Table 9-15 TRANSFER SYNTAX SUB-ITEM FIELDS.

TODO what is the goal of :

[Table](#) 9-19 TRANSFER SYNTAX SUB-ITEM FIELDS

25.274.2 Constructor & Destructor Documentation

25.274.2.1 `gdcm::network::TransferSyntaxSub::TransferSyntaxSub ()`

25.274.3 Member Function Documentation

25.274.3.1 `const char* gdcm::network::TransferSyntaxSub::GetName () const` `[inline]`

25.274.3.2 `bool gdcm::network::TransferSyntaxSub::operator== (const TransferSyntaxSub & ts) const` `[inline]`

25.274.3.3 `void gdcm::network::TransferSyntaxSub::Print (std::ostream & os) const`

25.274.3.4 `std::istream& gdcm::network::TransferSyntaxSub::Read (std::istream & is)`

25.274.3.5 `void gdcm::network::TransferSyntaxSub::SetName (const char * name)`

25.274.3.6 `void gdcm::network::TransferSyntaxSub::SetNameFromUID (UIDs::TSName tsname)`

25.274.3.7 `size_t gdcm::network::TransferSyntaxSub::Size () const`

25.274.3.8 `const std::ostream& gdcm::network::TransferSyntaxSub::Write (std::ostream & os) const`


The documentation for this class was generated from the following file:

- [gdcmTransferSyntaxSub.h](#)

25.275 gdcm::network::Transition Struct Reference

```
#include <gdcmULTransitionTable.h>
```

Collaboration diagram for `gdcmm::network::Transition`:



Public Member Functions

- [Transition](#) ()
- [Transition](#) (int inEndState, [ULAction](#) *inAction)
- [~Transition](#) ()

Static Public Member Functions

- static [Transition](#) * [MakeNew](#) (int inEndState, [ULAction](#) *inAction)

Public Attributes

- [ULAction](#) * [mAction](#)
- int [mEnd](#)

25.275.1 Constructor & Destructor Documentation

25.275.1.1 `gdcmm::network::Transition::Transition ()` [`inline`]

References `gdcmm::network::eStaDoesNotExist`, `mAction`, and `mEnd`.

Referenced by `MakeNew()`.

25.275.1.2 `gdcmm::network::Transition::~~Transition ()` [`inline`]

References `mAction`.

25.275.1.3 `gdcmm::network::Transition::Transition (int inEndState, ULAction * inAction)` [`inline`]

References `mAction`, and `mEnd`.

25.275.2 Member Function Documentation

25.275.2.1 static `Transition*` `gdcm::network::Transition::MakeNew` (`int` *inEndState*, `ULAction *` *inAction*) `[inline]`,
`[static]`

References `Transition()`.

25.275.3 Member Data Documentation

25.275.3.1 `ULAction*` `gdcm::network::Transition::mAction`

Referenced by `Transition()`, and `~Transition()`.

25.275.3.2 `int` `gdcm::network::Transition::mEnd`

Referenced by `Transition()`.

The documentation for this struct was generated from the following file:

- [gdcmULTransitionTable.h](#)

25.276 gdcm::Type Class Reference

Type.

```
#include <gdcmType.h>
```

Public Types

- enum `TypeType` {
 `T1` = 0,
 `T1C`,
 `T2`,
 `T2C`,
 `T3`,
 `UNKNOWN` }

Public Member Functions

- `Type` (`TypeType` *type*=`UNKNOWN`)
- `operator TypeType` () const

Static Public Member Functions

- static const char * `GetTypeString` (`TypeType` *type*)
- static `TypeType` `GetTypeType` (const char **type*)

Friends

- `std::ostream & operator<< (std::ostream &os, const Type &vr)`

25.276.1 Detailed Description

[Type](#).

Note

PS 3.5 7.4 DATA ELEMENT TYPE 7.4.1 TYPE 1 REQUIRED DATA ELEMENTS 7.4.2 TYPE 1C CONDITIONAL DATA ELEMENTS 7.4.3 TYPE 2 REQUIRED DATA ELEMENTS 7.4.4 TYPE 2C CONDITIONAL DATA ELEMENTS 7.4.5 TYPE 3 OPTIONAL DATA ELEMENTS

The intent of [Type](#) 2 Data Elements is to allow a zero length to be conveyed when the operator or application does not know its value or has a specific reason for not specifying its value. It is the intent that the device should support these Data Elements.

Examples:

[TraverseModules.cxx](#).

25.276.2 Member Enumeration Documentation

25.276.2.1 enum `gdcm::Type::TypeType`

Enumerator

T1
T1C
T2
T2C
T3
UNKNOWN

25.276.3 Constructor & Destructor Documentation

25.276.3.1 `gdcm::Type::Type (TypeType type = UNKNOWN) [inline]`

25.276.4 Member Function Documentation

25.276.4.1 `static const char* gdcm::Type::GetTypeString (TypeType type) [static]`

Referenced by `gdcm::operator<<()`.

25.276.4.2 `static TypeType gdcm::Type::GetTypeType (const char * type) [static]`

Referenced by `gdcm::ModuleEntry::ModuleEntry()`.

25.276.4.3 `gdcm::Type::operator TypeType () const` `[inline]`

25.276.5 Friends And Related Function Documentation

25.276.5.1 `std::ostream& operator<< (std::ostream & os, const Type & vr)` `[friend]`

The documentation for this class was generated from the following file:

- [gdcmType.h](#)

25.277 gdcm::UI Struct Reference

```
#include <gdcmVR.h>
```

Public Attributes

- char [Internal](#) [64+1]

Friends

- `std::ostream & operator<< (std::ostream &_os, const UI &_val)`

25.277.1 Friends And Related Function Documentation

25.277.1.1 `std::ostream& operator<< (std::ostream &_os, const UI &_val)` `[friend]`

25.277.2 Member Data Documentation

25.277.2.1 `char gdcm::UI::Internal[64+1]`

Referenced by `gdcm::operator<<()`.

The documentation for this struct was generated from the following file:

- [gdcmVR.h](#)

25.278 gdcm::UIDGenerator Class Reference

Class for generating unique UID.

```
#include <gdcmUIDGenerator.h>
```

Public Member Functions

- [UIDGenerator](#) ()
By default the root of a UID is a GDCM Root...
- const char * [Generate](#) ()

Static Public Member Functions

- static const char * [GetGDCMUID](#) ()
Return the default (GDCM) root UID:
- static const char * [GetRoot](#) ()
- static bool [IsValid](#) (const char *uid)
- static void [SetRoot](#) (const char *root)

Static Protected Member Functions

- static bool [GenerateUUID](#) (unsigned char *uuid_data)

25.278.1 Detailed Description

Class for generating unique UID.

Note

bla [Usage](#): When constructing a [Series](#) or [Study](#) UID, user *has* to keep around the UID, otherwise the UID Generator will simply forget the value and create a new UID.

Examples:

[CreateJPIPDataset.cxx](#), [EncapsulateFileInRawData.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenFakeImage.cxx](#), [GetSubSequenceData.cxx](#), [StreamImageReaderTest.cxx](#), and [uid_unique.cxx](#).

25.278.2 Constructor & Destructor Documentation

25.278.2.1 `gdcm::UIDGenerator::UIDGenerator () [inline]`

By default the root of a UID is a GDCM Root...

25.278.3 Member Function Documentation

25.278.3.1 `const char* gdcm::UIDGenerator::Generate ()`

Internally uses a `std::string`, so two calls have the same pointer ! save into a `std::string` In summary do not write code like that: `const char *uid1 = uid.Generate(); const char *uid2 = uid.Generate();` since `uid1 == uid2`

Examples:

[CreateJPIPDataset.cxx](#), [EncapsulateFileInRawData.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenFakeImage.cxx](#), [StreamImageReaderTest.cxx](#), and [uid_unique.cxx](#).

25.278.3.2 `static bool gdcm::UIDGenerator::GenerateUUID (unsigned char * uuid_data) [static], [protected]`

25.278.3.3 `static const char* gdcm::UIDGenerator::GetGDCMUID () [static]`

Return the default (GDCM) root UID:

25.278.3.4 `static const char* gdcm::UIDGenerator::GetRoot () [static]`

25.278.3.5 `static bool gdcm::UIDGenerator::IsValid (const char * uid) [static]`

Find out if the string is a valid UID or not

Todo : Move that in DataStructureAndEncoding (see FileMetaInformation::CheckFileMetaInformation)

25.278.3.6 `static void gdcm::UIDGenerator::SetRoot (const char * root) [static]`

The current implementation in GDCM make use of the UUID implementation (RFC 4122) and has been successfully been tested for a root of size 26 bytes. Any longer root should work (the `::Generate()` function will return a string), but will truncate the high bits of the 128bits UUID until the generated string fits on 64 bits. The authors disclaims any responsibility for guaranteeing uniqueness of [UIDs](#) when the root is longer than 26 bytes.

Examples:

[uid_unique.cxx](#).

The documentation for this class was generated from the following file:

- [gdcmUIDGenerator.h](#)

25.279 gdcm::UIDs Class Reference

all known uids

```
#include <gdcmUIDs.h>
```

Public Types

- `typedef const char *const (* TransferSyntaxStringsType)[2]`
- `enum TSName {`

```
VerificationSOPClass = 1,  
ImplicitVRLittleEndianDefaultTransferSyntaxforDICOM = 2,  
ExplicitVRLittleEndian = 3,  
DeflatedExplicitVRLittleEndian = 4,  
ExplicitVRBigEndian = 5,  
JPEGBaselineProcess1DefaultTransferSyntaxforLossyJPEG8BitImageCompression = 6,  
JPEGExtendedProcess24DefaultTransferSyntaxforLossyJPEG12BitImageCompressionProcess4only = 7,  
JPEGExtendedProcess35Retired = 8,  
JPEGsSpectralSelectionNonHierarchicalProcess68Retired = 9,  
JPEGsSpectralSelectionNonHierarchicalProcess79Retired = 10,  
JPEGFullProgressionNonHierarchicalProcess1012Retired = 11,  
JPEGFullProgressionNonHierarchicalProcess1113Retired = 12,  
JPEGLosslessNonHierarchicalProcess14 = 13,  
JPEGLosslessNonHierarchicalProcess15Retired = 14,  
JPEGExtendedHierarchicalProcess1618Retired = 15,  
JPEGExtendedHierarchicalProcess1719Retired = 16,  
JPEGsSpectralSelectionHierarchicalProcess2022Retired = 17,  
JPEGsSpectralSelectionHierarchicalProcess2123Retired = 18,  
JPEGFullProgressionHierarchicalProcess2426Retired = 19,  
JPEGFullProgressionHierarchicalProcess2527Retired = 20,  
JPEGLosslessHierarchicalProcess28Retired = 21,  
JPEGLosslessHierarchicalProcess29Retired = 22,  
JPEGLosslessNonHierarchicalFirstOrderPredictionProcess14SelectionValue1DefaultTransferSyntaxforLossless-
```


JPEGImageCompression = 23,
JPEGLSLosslessImageCompression = 24,
JPEGLSLossyNearLosslessImageCompression = 25,
JPEG2000ImageCompressionLosslessOnly = 26,
JPEG2000ImageCompression = 27,
JPEG2000Part2MulticomponentImageCompressionLosslessOnly = 28,
JPEG2000Part2MulticomponentImageCompression = 29,
JPIPReferenced = 30,
JPIPReferencedDeflate = 31,
MPEG2MainProfileMainLevel = 32,
RLELossless = 33,
RFC2557MIMEencapsulation = 34,
XMLEncoding = 35,
MediaStorageDirectoryStorage = 36,
TalairachBrainAtlasFrameofReference = 37,
SPM2T1FrameofReference = 38,
SPM2T2FrameofReference = 39,
SPM2PDFFrameofReference = 40,
SPM2EPIFrameofReference = 41,
SPM2FILT1FrameofReference = 42,
SPM2PETFrameofReference = 43,
SPM2TRANSMFrameofReference = 44,
SPM2SPECTFrameofReference = 45,
SPM2GRAYFrameofReference = 46,
SPM2WHITEFrameofReference = 47,
SPM2CSFFFrameofReference = 48,
SPM2BRAINMASKFrameofReference = 49,
SPM2AVG305T1FrameofReference = 50,
SPM2AVG152T1FrameofReference = 51,
SPM2AVG152T2FrameofReference = 52,
SPM2AVG152PDFFrameofReference = 53,
SPM2SINGLESUBJT1FrameofReference = 54,
ICBM452T1FrameofReference = 55,
ICBMSingleSubjectMRIFrameofReference = 56,
BasicStudyContentNotificationSOPClassRetired = 57,
StorageCommitmentPushModelSOPClass = 58,
StorageCommitmentPushModelSOPInstance = 59,
StorageCommitmentPullModelSOPClassRetired = 60,
StorageCommitmentPullModelSOPInstanceRetired = 61,
ProceduralEventLoggingSOPClass = 62,
ProceduralEventLoggingSOPInstance = 63,
SubstanceAdministrationLoggingSOPClass = 64,
SubstanceAdministrationLoggingSOPInstance = 65,
DICOMUIDRegistry = 66,
DICOMControlledTerminology = 67,
DICOMApplicationContextName = 68,
DetachedPatientManagementSOPClassRetired = 69,
DetachedPatientManagementMetaSOPClassRetired = 70,
DetachedVisitManagementSOPClassRetired = 71,
DetachedStudyManagementSOPClassRetired = 72,
StudyComponentManagementSOPClassRetired = 73,
ModalityPerformedProcedureStepSOPClass = 74,
ModalityPerformedProcedureStepRetrieveSOPClass = 75,
ModalityPerformedProcedureStepNotificationSOPClass = 76,
DetachedResultsManagementSOPClassRetired = 77,
DetachedResultsManagementMetaSOPClassRetired = 78,
DetachedStudyManagementMetaSOPClassRetired = 79,
DetachedInterpretationManagementSOPClassRetired = 80,
StorageServiceClass = 81,
BasicFilmSessionSOPClass = 82,

[BreastTomosynthesisImageStorage](#) }

• enum [TSType](#) {

```
uid_1_2_840_10008_1_1 = 1,  
uid_1_2_840_10008_1_2 = 2,  
uid_1_2_840_10008_1_2_1 = 3,  
uid_1_2_840_10008_1_2_1_99 = 4,  
uid_1_2_840_10008_1_2_2 = 5,  
uid_1_2_840_10008_1_2_4_50 = 6,  
uid_1_2_840_10008_1_2_4_51 = 7,  
uid_1_2_840_10008_1_2_4_52 = 8,  
uid_1_2_840_10008_1_2_4_53 = 9,  
uid_1_2_840_10008_1_2_4_54 = 10,  
uid_1_2_840_10008_1_2_4_55 = 11,  
uid_1_2_840_10008_1_2_4_56 = 12,  
uid_1_2_840_10008_1_2_4_57 = 13,  
uid_1_2_840_10008_1_2_4_58 = 14,  
uid_1_2_840_10008_1_2_4_59 = 15,  
uid_1_2_840_10008_1_2_4_60 = 16,  
uid_1_2_840_10008_1_2_4_61 = 17,  
uid_1_2_840_10008_1_2_4_62 = 18,  
uid_1_2_840_10008_1_2_4_63 = 19,  
uid_1_2_840_10008_1_2_4_64 = 20,  
uid_1_2_840_10008_1_2_4_65 = 21,  
uid_1_2_840_10008_1_2_4_66 = 22,  
uid_1_2_840_10008_1_2_4_70 = 23,  
uid_1_2_840_10008_1_2_4_80 = 24,  
uid_1_2_840_10008_1_2_4_81 = 25,  
uid_1_2_840_10008_1_2_4_90 = 26,  
uid_1_2_840_10008_1_2_4_91 = 27,  
uid_1_2_840_10008_1_2_4_92 = 28,  
uid_1_2_840_10008_1_2_4_93 = 29,  
uid_1_2_840_10008_1_2_4_94 = 30,  
uid_1_2_840_10008_1_2_4_95 = 31,  
uid_1_2_840_10008_1_2_4_100 = 32,  
uid_1_2_840_10008_1_2_5 = 33,  
uid_1_2_840_10008_1_2_6_1 = 34,  
uid_1_2_840_10008_1_2_6_2 = 35,  
uid_1_2_840_10008_1_3_10 = 36,  
uid_1_2_840_10008_1_4_1_1 = 37,  
uid_1_2_840_10008_1_4_1_2 = 38,  
uid_1_2_840_10008_1_4_1_3 = 39,  
uid_1_2_840_10008_1_4_1_4 = 40,  
uid_1_2_840_10008_1_4_1_5 = 41,  
uid_1_2_840_10008_1_4_1_6 = 42,  
uid_1_2_840_10008_1_4_1_7 = 43,  
uid_1_2_840_10008_1_4_1_8 = 44,  
uid_1_2_840_10008_1_4_1_9 = 45,  
uid_1_2_840_10008_1_4_1_10 = 46,  
uid_1_2_840_10008_1_4_1_11 = 47,  
uid_1_2_840_10008_1_4_1_12 = 48,  
uid_1_2_840_10008_1_4_1_13 = 49,  
uid_1_2_840_10008_1_4_1_14 = 50,  
uid_1_2_840_10008_1_4_1_15 = 51,  
uid_1_2_840_10008_1_4_1_16 = 52,  
uid_1_2_840_10008_1_4_1_17 = 53,  
uid_1_2_840_10008_1_4_1_18 = 54,  
uid_1_2_840_10008_1_4_2_1 = 55,  
uid_1_2_840_10008_1_4_2_2 = 56,  
uid_1_2_840_10008_1_9 = 57,  
uid_1_2_840_10008_1_20_1 = 58,  
uid_1_2_840_10008_1_20_1_1 = 59,  
uid_1_2_840_10008_1_20_2 = 60,
```

```
uid_1_2_840_10008_5_1_4_1_1_13_1_3 }
```

Public Member Functions

- const char * [GetName](#) () const
- const char * [GetString](#) () const
- [operator TSType](#) () const
- bool [SetFromUID](#) (const char *str)

Static Public Member Functions

- static unsigned int [GetNumberOfTransferSyntaxStrings](#) ()
- static const char *const * [GetTransferSyntaxString](#) (unsigned int ts)
- static [TransferSyntaxStringsType](#) [GetTransferSyntaxStrings](#) ()
- static const char * [GetUIDName](#) (unsigned int ts)
- static const char * [GetUIDString](#) (unsigned int ts)

25.279.1 Detailed Description

all known uids

Examples:

[GenerateStandardSOPClasses.cxx](#).

25.279.2 Member Typedef Documentation

25.279.2.1 `typedef const char* const(* gdcmm::UIDs::TransferSyntaxStringsType)[2]`

25.279.3 Member Enumeration Documentation

25.279.3.1 `enum gdcmm::UIDs::TSName`

Enumerator

VerificationSOPClass

ImplicitVRLittleEndianDefaultTransferSyntaxforDICOM

ExplicitVRLittleEndian

DeflatedExplicitVRLittleEndian

ExplicitVRBigEndian

JPEGBaselineProcess1DefaultTransferSyntaxforLossyJPEG8BitImageCompression

JPEGExtendedProcess24DefaultTransferSyntaxforLossyJPEG12BitImageCompressionProcess4only

JPEGExtendedProcess35Retired

JPEGSpectralSelectionNonHierarchicalProcess68Retired

JPEGSpectralSelectionNonHierarchicalProcess79Retired

JPEGFullProgressionNonHierarchicalProcess1012Retired

JPEGFullProgressionNonHierarchicalProcess1113Retired

JPEGLosslessNonHierarchicalProcess14
JPEGLosslessNonHierarchicalProcess15Retired
JPEGExtendedHierarchicalProcess1618Retired
JPEGExtendedHierarchicalProcess1719Retired
JPEGSpectralSelectionHierarchicalProcess2022Retired
JPEGSpectralSelectionHierarchicalProcess2123Retired
JPEGFullProgressionHierarchicalProcess2426Retired
JPEGFullProgressionHierarchicalProcess2527Retired
JPEGLosslessHierarchicalProcess28Retired
JPEGLosslessHierarchicalProcess29Retired
JPEGLosslessNonHierarchicalFirstOrderPredictionProcess14SelectionValue1DefaultTransferSyntaxforLosslessJPEGImage

JPEGLSLosslessImageCompression
JPEGLSLossyNearLosslessImageCompression
JPEG2000ImageCompressionLosslessOnly
JPEG2000ImageCompression
JPEG2000Part2MulticomponentImageCompressionLosslessOnly
JPEG2000Part2MulticomponentImageCompression
JPIPRreferenced
JPIPRreferencedDeflate
MPEG2MainProfileMainLevel
RLELossless
RFC2557MIMEencapsulation
XMLEncoding
MediaStorageDirectoryStorage
TalairachBrainAtlasFrameofReference
SPM2T1FrameofReference
SPM2T2FrameofReference
SPM2PDFFrameofReference
SPM2EPIFrameofReference
SPM2FIL T1FrameofReference
SPM2PETFrameofReference
SPM2TRANSMFrameofReference
SPM2SPECTFrameofReference
SPM2GRAYFrameofReference
SPM2WHITEFrameofReference
SPM2CSFFFrameofReference
SPM2BRAINMASKFrameofReference
SPM2AVG305T1FrameofReference
SPM2AVG152T1FrameofReference
SPM2AVG152T2FrameofReference
SPM2AVG152PDFFrameofReference

SPM2SINGLESUBJT1FrameofReference
ICBM452T1FrameofReference
ICBMSingleSubjectMRIFrameofReference
BasicStudyContentNotificationSOPClassRetired
StorageCommitmentPushModelSOPClass
StorageCommitmentPushModelSOPInstance
StorageCommitmentPullModelSOPClassRetired
StorageCommitmentPullModelSOPInstanceRetired
ProceduralEventLoggingSOPClass
ProceduralEventLoggingSOPInstance
SubstanceAdministrationLoggingSOPClass
SubstanceAdministrationLoggingSOPInstance
DICOMUIDRegistry
DICOMControlledTerminology
DICOMApplicationContextName
DetachedPatientManagementSOPClassRetired
DetachedPatientManagementMetaSOPClassRetired
DetachedVisitManagementSOPClassRetired
DetachedStudyManagementSOPClassRetired
StudyComponentManagementSOPClassRetired
ModalityPerformedProcedureStepSOPClass
ModalityPerformedProcedureStepRetrieveSOPClass
ModalityPerformedProcedureStepNotificationSOPClass
DetachedResultsManagementSOPClassRetired
DetachedResultsManagementMetaSOPClassRetired
DetachedStudyManagementMetaSOPClassRetired
DetachedInterpretationManagementSOPClassRetired
StorageServiceClass
BasicFilmSessionSOPClass
BasicFilmBoxSOPClass
BasicGrayscaleImageBoxSOPClass
BasicColorImageBoxSOPClass
ReferencedImageBoxSOPClassRetired
BasicGrayscalePrintManagementMetaSOPClass
ReferencedGrayscalePrintManagementMetaSOPClassRetired
PrintJobSOPClass
BasicAnnotationBoxSOPClass
PrinterSOPClass
PrinterConfigurationRetrievalSOPClass
PrinterSOPInstance
PrinterConfigurationRetrievalSOPInstance
BasicColorPrintManagementMetaSOPClass

ReferencedColorPrintManagementMetaSOPClassRetired
VOILUTBoxSOPClass
PresentationLUTSOPClass
ImageOverlayBoxSOPClassRetired
BasicPrintImageOverlayBoxSOPClassRetired
PrintQueueSOPInstanceRetired
PrintQueueManagementSOPClassRetired
StoredPrintStorageSOPClassRetired
HardcopyGrayscaleImageStorageSOPClassRetired
HardcopyColorImageStorageSOPClassRetired
PullPrintRequestSOPClassRetired
PullStoredPrintManagementMetaSOPClassRetired
MediaCreationManagementSOPClassUID
ComputedRadiographyImageStorage
DigitalXRayImageStorageForPresentation
DigitalXRayImageStorageForProcessing
DigitalMammographyXRayImageStorageForPresentation
DigitalMammographyXRayImageStorageForProcessing
DigitalIntraoralXRayImageStorageForPresentation
DigitalIntraoralXRayImageStorageForProcessing
CTImageStorage
EnhancedCTImageStorage
UltrasoundMultiframeImageStorageRetired
UltrasoundMultiframeImageStorage
MRIImageStorage
EnhancedMRIImageStorage
MRSpectroscopyStorage
NuclearMedicineImageStorageRetired
UltrasoundImageStorageRetired
UltrasoundImageStorage
SecondaryCaptureImageStorage
MultiframeSingleBitSecondaryCaptureImageStorage
MultiframeGrayscaleByteSecondaryCaptureImageStorage
MultiframeGrayscaleWordSecondaryCaptureImageStorage
MultiframeTrueColorSecondaryCaptureImageStorage
StandaloneOverlayStorageRetired
StandaloneCurveStorageRetired
WaveformStorageTrialRetired
GeneralECGWaveformStorage
AmbulatoryECGWaveformStorage
HemodynamicWaveformStorage
CardiacElectrophysiologyWaveformStorage

BasicVoiceAudioWaveformStorage
StandaloneModalityLUTStorageRetired
StandaloneVOILUTStorageRetired
GrayscaleSoftcopyPresentationStateStorageSOPClass
ColorSoftcopyPresentationStateStorageSOPClass
PseudoColorSoftcopyPresentationStateStorageSOPClass
BlendingSoftcopyPresentationStateStorageSOPClass
XRayAngiographicImageStorage
EnhancedXAImageStorage
XRayRadiofluoroscopicImageStorage
EnhancedXRImageStorage
XRay3DAngiographicImageStorage
XRay3DCraniofacialImageStorage
XRayAngiographicBiPlaneImageStorageRetired
NuclearMedicineImageStorage
RawDataStorage
SpatialRegistrationStorage
SpatialFiducialsStorage
DeformableSpatialRegistrationStorage
SegmentationStorage
RealWorldValueMappingStorage
VLImageStorageTrialRetired
VLMultiframeImageStorageTrialRetired
VLEndoscopicImageStorage
VideoEndoscopicImageStorage
VLMicroscopicImageStorage
VideoMicroscopicImageStorage
VLSlideCoordinatesMicroscopicImageStorage
VLPhotographicImageStorage
VideoPhotographicImageStorage
OphthalmicPhotography8BitImageStorage
OphthalmicPhotography16BitImageStorage
StereometricRelationshipStorage
OphthalmicTomographyImageStorage
TextSRStorageTrialRetired
AudioSRStorageTrialRetired
DetailSRStorageTrialRetired
ComprehensiveSRStorageTrialRetired
BasicTextSRStorage
EnhancedSRStorage
ComprehensiveSRStorage
ProcedureLogStorage

MammographyCADSRStorage
KeyObjectSelectionDocumentStorage
ChestCADSRStorage
XRayRadiationDoseSRStorage
EncapsulatedPDFStorage
EncapsulatedCDASStorage
PositronEmissionTomographyImageStorage
StandalonePETCurveStorageRetired
RTImageStorage
RTDoseStorage
RTStructureSetStorage
RTBeamsTreatmentRecordStorage
RTPlanStorage
RTBrachyTreatmentRecordStorage
RTTreatmentSummaryRecordStorage
RTIonPlanStorage
RTIonBeamsTreatmentRecordStorage
PatientRootQueryRetrieveInformationModelFIND
PatientRootQueryRetrieveInformationModelMOVE
PatientRootQueryRetrieveInformationModelGET
StudyRootQueryRetrieveInformationModelFIND
StudyRootQueryRetrieveInformationModelMOVE
StudyRootQueryRetrieveInformationModelGET
PatientStudyOnlyQueryRetrieveInformationModelFINDRetired
PatientStudyOnlyQueryRetrieveInformationModelMOVERetired
PatientStudyOnlyQueryRetrieveInformationModelGETRetired
ModalityWorklistInformationModelFIND
GeneralPurposeWorklistInformationModelFIND
GeneralPurposeScheduledProcedureStepSOPClass
GeneralPurposePerformedProcedureStepSOPClass
GeneralPurposeWorklistManagementMetaSOPClass
InstanceAvailabilityNotificationSOPClass
RTBeamsDeliveryInstructionStorageSupplement74FrozenDraft
RTConventionalMachineVerificationSupplement74FrozenDraft
RTIonMachineVerificationSupplement74FrozenDraft
UnifiedWorklistandProcedureStepServiceClass
UnifiedProcedureStepPushSOPClass
UnifiedProcedureStepWatchSOPClass
UnifiedProcedureStepPullSOPClass
UnifiedProcedureStepEventSOPClass
UnifiedWorklistandProcedureStepSOPInstance
GeneralRelevantPatientInformationQuery

BreastImagingRelevantPatientInformationQuery
CardiacRelevantPatientInformationQuery
HangingProtocolStorage
HangingProtocolInformationModelFIND
HangingProtocolInformationModelMOVE
ProductCharacteristicsQuerySOPClass
SubstanceApprovalQuerySOPClass
dicomDeviceName
dicomDescription
dicomManufacturer
dicomManufacturerModelName
dicomSoftwareVersion
dicomVendorData
dicomAETitle
dicomNetworkConnectionReference
dicomApplicationCluster
dicomAssociationInitiator
dicomAssociationAcceptor
dicomHostname
dicomPort
dicomSOPClass
dicomTransferRole
dicomTransferSyntax
dicomPrimaryDeviceType
dicomRelatedDeviceReference
dicomPreferredCalledAETitle
dicomTLSCyphersuite
dicomAuthorizedNodeCertificateReference
dicomThisNodeCertificateReference
dicomInstalled
dicomStationName
dicomDeviceSerialNumber
dicomInstitutionName
dicomInstitutionAddress
dicomInstitutionDepartmentName
dicomIssuerOfPatientID
dicomPreferredCallingAETitle
dicomSupportedCharacterSet
dicomConfigurationRoot
dicomDevicesRoot
dicomUniqueAETitlesRegistryRoot
dicomDevice

dicomNetworkAE
dicomNetworkConnection
dicomUniqueAETitle
dicomTransferCapability
VLWholeSlideMicroscopyImageStorage
EnhancedUSVolumeStorage
SurfaceSegmentationStorage
BreastTomosynthesisImageStorage

25.279.3.2 enum gdcmm::UIDs::TSType

Enumerator

uid_1_2_840_10008_1_1
uid_1_2_840_10008_1_2
uid_1_2_840_10008_1_2_1
uid_1_2_840_10008_1_2_1_99
uid_1_2_840_10008_1_2_2
uid_1_2_840_10008_1_2_4_50
uid_1_2_840_10008_1_2_4_51
uid_1_2_840_10008_1_2_4_52
uid_1_2_840_10008_1_2_4_53
uid_1_2_840_10008_1_2_4_54
uid_1_2_840_10008_1_2_4_55
uid_1_2_840_10008_1_2_4_56
uid_1_2_840_10008_1_2_4_57
uid_1_2_840_10008_1_2_4_58
uid_1_2_840_10008_1_2_4_59
uid_1_2_840_10008_1_2_4_60
uid_1_2_840_10008_1_2_4_61
uid_1_2_840_10008_1_2_4_62
uid_1_2_840_10008_1_2_4_63
uid_1_2_840_10008_1_2_4_64
uid_1_2_840_10008_1_2_4_65
uid_1_2_840_10008_1_2_4_66
uid_1_2_840_10008_1_2_4_70
uid_1_2_840_10008_1_2_4_80
uid_1_2_840_10008_1_2_4_81
uid_1_2_840_10008_1_2_4_90
uid_1_2_840_10008_1_2_4_91
uid_1_2_840_10008_1_2_4_92
uid_1_2_840_10008_1_2_4_93

uid_1_2_840_10008_1_2_4_94
uid_1_2_840_10008_1_2_4_95
uid_1_2_840_10008_1_2_4_100
uid_1_2_840_10008_1_2_5
uid_1_2_840_10008_1_2_6_1
uid_1_2_840_10008_1_2_6_2
uid_1_2_840_10008_1_3_10
uid_1_2_840_10008_1_4_1_1
uid_1_2_840_10008_1_4_1_2
uid_1_2_840_10008_1_4_1_3
uid_1_2_840_10008_1_4_1_4
uid_1_2_840_10008_1_4_1_5
uid_1_2_840_10008_1_4_1_6
uid_1_2_840_10008_1_4_1_7
uid_1_2_840_10008_1_4_1_8
uid_1_2_840_10008_1_4_1_9
uid_1_2_840_10008_1_4_1_10
uid_1_2_840_10008_1_4_1_11
uid_1_2_840_10008_1_4_1_12
uid_1_2_840_10008_1_4_1_13
uid_1_2_840_10008_1_4_1_14
uid_1_2_840_10008_1_4_1_15
uid_1_2_840_10008_1_4_1_16
uid_1_2_840_10008_1_4_1_17
uid_1_2_840_10008_1_4_1_18
uid_1_2_840_10008_1_4_2_1
uid_1_2_840_10008_1_4_2_2
uid_1_2_840_10008_1_9
uid_1_2_840_10008_1_20_1
uid_1_2_840_10008_1_20_1_1
uid_1_2_840_10008_1_20_2
uid_1_2_840_10008_1_20_2_1
uid_1_2_840_10008_1_40
uid_1_2_840_10008_1_40_1
uid_1_2_840_10008_1_42
uid_1_2_840_10008_1_42_1
uid_1_2_840_10008_2_6_1
uid_1_2_840_10008_2_16_4
uid_1_2_840_10008_3_1_1_1
uid_1_2_840_10008_3_1_2_1_1
uid_1_2_840_10008_3_1_2_1_4
uid_1_2_840_10008_3_1_2_2_1

uid_1_2_840_10008_3_1_2_3_1
uid_1_2_840_10008_3_1_2_3_2
uid_1_2_840_10008_3_1_2_3_3
uid_1_2_840_10008_3_1_2_3_4
uid_1_2_840_10008_3_1_2_3_5
uid_1_2_840_10008_3_1_2_5_1
uid_1_2_840_10008_3_1_2_5_4
uid_1_2_840_10008_3_1_2_5_5
uid_1_2_840_10008_3_1_2_6_1
uid_1_2_840_10008_4_2
uid_1_2_840_10008_5_1_1_1
uid_1_2_840_10008_5_1_1_2
uid_1_2_840_10008_5_1_1_4
uid_1_2_840_10008_5_1_1_4_1
uid_1_2_840_10008_5_1_1_4_2
uid_1_2_840_10008_5_1_1_9
uid_1_2_840_10008_5_1_1_9_1
uid_1_2_840_10008_5_1_1_14
uid_1_2_840_10008_5_1_1_15
uid_1_2_840_10008_5_1_1_16
uid_1_2_840_10008_5_1_1_16_376
uid_1_2_840_10008_5_1_1_17
uid_1_2_840_10008_5_1_1_17_376
uid_1_2_840_10008_5_1_1_18
uid_1_2_840_10008_5_1_1_18_1
uid_1_2_840_10008_5_1_1_22
uid_1_2_840_10008_5_1_1_23
uid_1_2_840_10008_5_1_1_24
uid_1_2_840_10008_5_1_1_24_1
uid_1_2_840_10008_5_1_1_25
uid_1_2_840_10008_5_1_1_26
uid_1_2_840_10008_5_1_1_27
uid_1_2_840_10008_5_1_1_29
uid_1_2_840_10008_5_1_1_30
uid_1_2_840_10008_5_1_1_31
uid_1_2_840_10008_5_1_1_32
uid_1_2_840_10008_5_1_1_33
uid_1_2_840_10008_5_1_4_1_1_1
uid_1_2_840_10008_5_1_4_1_1_1_1
uid_1_2_840_10008_5_1_4_1_1_1_1_1
uid_1_2_840_10008_5_1_4_1_1_1_2
uid_1_2_840_10008_5_1_4_1_1_1_2_1

uid_1_2_840_10008_5_1_4_1_1_1_3
uid_1_2_840_10008_5_1_4_1_1_1_3_1
uid_1_2_840_10008_5_1_4_1_1_2
uid_1_2_840_10008_5_1_4_1_1_2_1
uid_1_2_840_10008_5_1_4_1_1_3
uid_1_2_840_10008_5_1_4_1_1_3_1
uid_1_2_840_10008_5_1_4_1_1_4
uid_1_2_840_10008_5_1_4_1_1_4_1
uid_1_2_840_10008_5_1_4_1_1_4_2
uid_1_2_840_10008_5_1_4_1_1_5
uid_1_2_840_10008_5_1_4_1_1_6
uid_1_2_840_10008_5_1_4_1_1_6_1
uid_1_2_840_10008_5_1_4_1_1_7
uid_1_2_840_10008_5_1_4_1_1_7_1
uid_1_2_840_10008_5_1_4_1_1_7_2
uid_1_2_840_10008_5_1_4_1_1_7_3
uid_1_2_840_10008_5_1_4_1_1_7_4
uid_1_2_840_10008_5_1_4_1_1_8
uid_1_2_840_10008_5_1_4_1_1_9
uid_1_2_840_10008_5_1_4_1_1_9_1
uid_1_2_840_10008_5_1_4_1_1_9_1_1
uid_1_2_840_10008_5_1_4_1_1_9_1_2
uid_1_2_840_10008_5_1_4_1_1_9_1_3
uid_1_2_840_10008_5_1_4_1_1_9_2_1
uid_1_2_840_10008_5_1_4_1_1_9_3_1
uid_1_2_840_10008_5_1_4_1_1_9_4_1
uid_1_2_840_10008_5_1_4_1_1_10
uid_1_2_840_10008_5_1_4_1_1_11
uid_1_2_840_10008_5_1_4_1_1_11_1
uid_1_2_840_10008_5_1_4_1_1_11_2
uid_1_2_840_10008_5_1_4_1_1_11_3
uid_1_2_840_10008_5_1_4_1_1_11_4
uid_1_2_840_10008_5_1_4_1_1_12_1
uid_1_2_840_10008_5_1_4_1_1_12_1_1
uid_1_2_840_10008_5_1_4_1_1_12_2
uid_1_2_840_10008_5_1_4_1_1_12_2_1
uid_1_2_840_10008_5_1_4_1_1_13_1_1
uid_1_2_840_10008_5_1_4_1_1_13_1_2
uid_1_2_840_10008_5_1_4_1_1_12_3
uid_1_2_840_10008_5_1_4_1_1_20
uid_1_2_840_10008_5_1_4_1_1_66
uid_1_2_840_10008_5_1_4_1_1_66_1

uid_1_2_840_10008_5_1_4_1_1_66_2
uid_1_2_840_10008_5_1_4_1_1_66_3
uid_1_2_840_10008_5_1_4_1_1_66_4
uid_1_2_840_10008_5_1_4_1_1_67
uid_1_2_840_10008_5_1_4_1_1_77_1
uid_1_2_840_10008_5_1_4_1_1_77_2
uid_1_2_840_10008_5_1_4_1_1_77_1_1
uid_1_2_840_10008_5_1_4_1_1_77_1_1_1
uid_1_2_840_10008_5_1_4_1_1_77_1_2
uid_1_2_840_10008_5_1_4_1_1_77_1_2_1
uid_1_2_840_10008_5_1_4_1_1_77_1_3
uid_1_2_840_10008_5_1_4_1_1_77_1_4
uid_1_2_840_10008_5_1_4_1_1_77_1_4_1
uid_1_2_840_10008_5_1_4_1_1_77_1_5_1
uid_1_2_840_10008_5_1_4_1_1_77_1_5_2
uid_1_2_840_10008_5_1_4_1_1_77_1_5_3
uid_1_2_840_10008_5_1_4_1_1_77_1_5_4
uid_1_2_840_10008_5_1_4_1_1_88_1
uid_1_2_840_10008_5_1_4_1_1_88_2
uid_1_2_840_10008_5_1_4_1_1_88_3
uid_1_2_840_10008_5_1_4_1_1_88_4
uid_1_2_840_10008_5_1_4_1_1_88_11
uid_1_2_840_10008_5_1_4_1_1_88_22
uid_1_2_840_10008_5_1_4_1_1_88_33
uid_1_2_840_10008_5_1_4_1_1_88_40
uid_1_2_840_10008_5_1_4_1_1_88_50
uid_1_2_840_10008_5_1_4_1_1_88_59
uid_1_2_840_10008_5_1_4_1_1_88_65
uid_1_2_840_10008_5_1_4_1_1_88_67
uid_1_2_840_10008_5_1_4_1_1_104_1
uid_1_2_840_10008_5_1_4_1_1_104_2
uid_1_2_840_10008_5_1_4_1_1_128
uid_1_2_840_10008_5_1_4_1_1_129
uid_1_2_840_10008_5_1_4_1_1_481_1
uid_1_2_840_10008_5_1_4_1_1_481_2
uid_1_2_840_10008_5_1_4_1_1_481_3
uid_1_2_840_10008_5_1_4_1_1_481_4
uid_1_2_840_10008_5_1_4_1_1_481_5
uid_1_2_840_10008_5_1_4_1_1_481_6
uid_1_2_840_10008_5_1_4_1_1_481_7
uid_1_2_840_10008_5_1_4_1_1_481_8
uid_1_2_840_10008_5_1_4_1_1_481_9

uid_1_2_840_10008_5_1_4_1_2_1_1
uid_1_2_840_10008_5_1_4_1_2_1_2
uid_1_2_840_10008_5_1_4_1_2_1_3
uid_1_2_840_10008_5_1_4_1_2_2_1
uid_1_2_840_10008_5_1_4_1_2_2_2
uid_1_2_840_10008_5_1_4_1_2_2_3
uid_1_2_840_10008_5_1_4_1_2_3_1
uid_1_2_840_10008_5_1_4_1_2_3_2
uid_1_2_840_10008_5_1_4_1_2_3_3
uid_1_2_840_10008_5_1_4_31
uid_1_2_840_10008_5_1_4_32_1
uid_1_2_840_10008_5_1_4_32_2
uid_1_2_840_10008_5_1_4_32_3
uid_1_2_840_10008_5_1_4_32
uid_1_2_840_10008_5_1_4_33
uid_1_2_840_10008_5_1_4_34_1
uid_1_2_840_10008_5_1_4_34_2
uid_1_2_840_10008_5_1_4_34_3
uid_1_2_840_10008_5_1_4_34_4
uid_1_2_840_10008_5_1_4_34_4_1
uid_1_2_840_10008_5_1_4_34_4_2
uid_1_2_840_10008_5_1_4_34_4_3
uid_1_2_840_10008_5_1_4_34_4_4
uid_1_2_840_10008_5_1_4_34_5
uid_1_2_840_10008_5_1_4_37_1
uid_1_2_840_10008_5_1_4_37_2
uid_1_2_840_10008_5_1_4_37_3
uid_1_2_840_10008_5_1_4_38_1
uid_1_2_840_10008_5_1_4_38_2
uid_1_2_840_10008_5_1_4_38_3
uid_1_2_840_10008_5_1_4_41
uid_1_2_840_10008_5_1_4_42
uid_1_2_840_10008_15_0_3_1
uid_1_2_840_10008_15_0_3_2
uid_1_2_840_10008_15_0_3_3
uid_1_2_840_10008_15_0_3_4
uid_1_2_840_10008_15_0_3_5
uid_1_2_840_10008_15_0_3_6
uid_1_2_840_10008_15_0_3_7
uid_1_2_840_10008_15_0_3_8
uid_1_2_840_10008_15_0_3_9
uid_1_2_840_10008_15_0_3_10


```

uid_1_2_840_10008_15_0_3_11
uid_1_2_840_10008_15_0_3_12
uid_1_2_840_10008_15_0_3_13
uid_1_2_840_10008_15_0_3_14
uid_1_2_840_10008_15_0_3_15
uid_1_2_840_10008_15_0_3_16
uid_1_2_840_10008_15_0_3_17
uid_1_2_840_10008_15_0_3_18
uid_1_2_840_10008_15_0_3_19
uid_1_2_840_10008_15_0_3_20
uid_1_2_840_10008_15_0_3_21
uid_1_2_840_10008_15_0_3_22
uid_1_2_840_10008_15_0_3_23
uid_1_2_840_10008_15_0_3_24
uid_1_2_840_10008_15_0_3_25
uid_1_2_840_10008_15_0_3_26
uid_1_2_840_10008_15_0_3_27
uid_1_2_840_10008_15_0_3_28
uid_1_2_840_10008_15_0_3_29
uid_1_2_840_10008_15_0_3_30
uid_1_2_840_10008_15_0_3_31
uid_1_2_840_10008_15_0_4_1
uid_1_2_840_10008_15_0_4_2
uid_1_2_840_10008_15_0_4_3
uid_1_2_840_10008_15_0_4_4
uid_1_2_840_10008_15_0_4_5
uid_1_2_840_10008_15_0_4_6
uid_1_2_840_10008_15_0_4_7
uid_1_2_840_10008_15_0_4_8
uid_1_2_840_10008_5_1_4_1_1_77_1_6
uid_1_2_840_10008_5_1_4_1_1_6_2
uid_1_2_840_10008_5_1_4_1_1_66_5
uid_1_2_840_10008_5_1_4_1_1_13_1_3

```

25.279.4 Member Function Documentation

25.279.4.1 const char* gdcm::UIDs::GetName () const

When object is Initialize function return the well known name associated with uid return NULL when not initialized

Examples:

[GenerateStandardSOPClasses.cxx](#).

Referenced by `gdcm::operator<<()`.

25.279.4.2 `static unsigned int gdcmm::UIDs::GetNumberOfTransferSyntaxStrings () [static]`

25.279.4.3 `const char* gdcmm::UIDs::GetString () const`

When object is Initialize function return the uid return NULL when not initialized

Examples:

[GenerateStandardSOPClasses.cxx.](#)

Referenced by `gdcmm::operator<<()`.

25.279.4.4 `static const char* const* gdcmm::UIDs::GetTransferSyntaxString (unsigned int ts) [static]`

25.279.4.5 `static TransferSyntaxStringsType gdcmm::UIDs::GetTransferSyntaxStrings () [static]`

25.279.4.6 `static const char* gdcmm::UIDs::GetUIDName (unsigned int ts) [static]`

25.279.4.7 `static const char* gdcmm::UIDs::GetUIDString (unsigned int ts) [static]`

25.279.4.8 `gdcmm::UIDs::operator TSType () const [inline]`

25.279.4.9 `bool gdcmm::UIDs::SetFromUID (const char * str)`

Initialize object from a string (a uid number) return false on error, and internal state is set to 0

Examples:

[GenerateStandardSOPClasses.cxx.](#)

The documentation for this class was generated from the following file:


- [gdcmmUIDs.h](#)

25.280 gdcmm::network::ULAction Class Reference

ULAction A [ULConnection](#) in a given ULState can perform certain ULActions. This base class provides the interface for running those ULActions on a given [ULConnection](#).

```
#include <gdcmmULAction.h>
```

Inheritance diagram for gdcmm::network::ULAction:



Public Member Functions

- [ULAction](#) ()
- virtual [~ULAction](#) ()

- virtual [EStateID PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)=0

25.280.1 Detailed Description

[ULAction](#) A [ULConnection](#) in a given [ULState](#) can perform certain [ULActions](#). This base class provides the interface for running those [ULActions](#) on a given [ULConnection](#).

Essentially, the [ULConnectionManager](#) will take this object, determined from the current [ULState](#) of the [ULConnection](#), and pass the [ULConnection](#) object to the [ULAction](#). The [ULAction](#) will then invoke whatever necessary commands are required by a given action.

The result of a [ULAction](#) is a [ULEvent](#) (ie, what happened as a result of the action).

This [ULEvent](#) is passed to the [ULState](#), so that the transition to the next state can occur.

Actions are associated with Payloads— be thos filestreams, AETitles to establish connections, whatever. The actual parameters that the user will pass via an action will come through a Payload object, which should, in itself, be some gdcmm-based object (but not all objects can be payloads; sending a single dataelement as a payload isn't meaningful). As such, each action has its own particular payload.

For the sake of keeping files together, both the particular payload class and the action class will be defined in the same header file. Payloads should JUST be data (or streams), NO METHODS.

Some actions perform changes that should raise events on the local system, and some actions perform changes that will require waiting for events from the remote system.

Therefore, this base action has been modified so that those events are set by each action. When the event loop runs an action, it will then test to see if a local event was raised by the action, and if so, perform the appropriate subsequent action. If the action requires waiting for a response from the remote system, then the event loop will sit there (presumably with the ARTIM timer running) and wait for a response from the remote system. Once a response is obtained, then the the rest of the state transitions can happen.

25.280.2 Constructor & Destructor Documentation

25.280.2.1 `gdcmm::network::ULAction::ULAction () [inline]`

25.280.2.2 `virtual gdcmm::network::ULAction::~~ULAction () [inline],[virtual]`

25.280.3 Member Function Documentation

25.280.3.1 `virtual EStateID gdcmm::network::ULAction::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent) [pure virtual]`

Implemented in [gdcmm::network::ULActionAR10](#), [gdcmm::network::ULActionAR9](#), [gdcmm::network::ULActionAE8](#), [gdcmm::network::ULActionAA8](#), [gdcmm::network::ULActionAR8](#), [gdcmm::network::ULActionAE7](#), [gdcmm::network::ULActionAA7](#), [gdcmm::network::ULActionAR7](#), [gdcmm::network::ULActionAE6](#), [gdcmm::network::ULActionAA6](#), [gdcmm::network::ULActionAR6](#), [gdcmm::network::ULActionAA5](#), [gdcmm::network::ULActionAE5](#), [gdcmm::network::ULActionAR5](#), [gdcmm::network::ULActionAA4](#), [gdcmm::network::ULActionAE4](#), [gdcmm::network::ULActionAR4](#), [gdcmm::network::ULActionAA3](#), [gdcmm::network::ULActionAE3](#), [gdcmm::network::ULActionAR3](#), [gdcmm::network::ULActionAA2](#), [gdcmm::network::ULActionAE2](#), [gdcmm::network::ULActionAR2](#), [gdcmm::network::ULActionDT2](#), [gdcmm::network::ULActionAA1](#), [gdcmm::network::ULActionAE1](#), [gdcmm::network::ULActionAR1](#), and [gdcmm::network::ULActionDT1](#).


The documentation for this class was generated from the following file:

- [gdcmmULAction.h](#)


25.281 gdcmm::network::ULActionAA1 Class Reference

```
#include <gdcmmULActionAA.h>
```

Inheritance diagram for gdcmm::network::ULActionAA1:



Collaboration diagram for gdcmm::network::ULActionAA1:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.281.1 Member Function Documentation

25.281.1.1 **EStateID** gdcmm::network::ULActionAA1::PerformAction (**Subject** * s, **ULEvent** & *inEvent*, **ULConnection** & *inConnection*, bool & *outWaitingForEvent*, **EEventID** & *outRaisedEvent*) [virtual]

Implements [gdcmm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAA.h](#)


25.282 gdcm::network::ULActionAA2 Class Reference

```
#include <gdcmULActionAA.h>
```

Inheritance diagram for gdcm::network::ULActionAA2:



Collaboration diagram for gdcm::network::ULActionAA2:



Public Member Functions

- [EStateID](#) [PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.282.1 Member Function Documentation

25.282.1.1 `EStateID` `gdcm::network::ULActionAA2::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent)` [virtual]

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAA.h](#)


25.283 gdcm::network::ULActionAA3 Class Reference

```
#include <gdcmULActionAA.h>
```

Inheritance diagram for `gdcm::network::ULActionAA3`:



Collaboration diagram for `gdcm::network::ULActionAA3`:



Public Member Functions

- [EStateID](#) [PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.283.1 Member Function Documentation

25.283.1.1 `EStateID gdcmm::network::ULActionAA3::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent) [virtual]`

Implements [gdcmm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmmULActionAA.h](#)


25.284 gdcmm::network::ULActionAA4 Class Reference

```
#include <gdcmmULActionAA.h>
```

Inheritance diagram for gdcmm::network::ULActionAA4:



Collaboration diagram for gdcmm::network::ULActionAA4:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULError](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.284.1 Member Function Documentation

25.284.1.1 [EStateID](#) `gdcm::network::ULActionAA4::PerformAction (Subject * s, ULError & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent)` `[virtual]`

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAA.h](#)


25.285 gdcm::network::ULActionAA5 Class Reference

```
#include <gdcmULActionAA.h>
```

Inheritance diagram for `gdcm::network::ULActionAA5`:



Collaboration diagram for `gdcmm::network::ULActionAA5`:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULError](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.285.1 Member Function Documentation

25.285.1.1 **EStateID** `gdcmm::network::ULActionAA5::PerformAction (Subject * s, ULError & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent)` [virtual]

Implements [gdcmm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmmULActionAA.h](#)


25.286 gdcmm::network::ULActionAA6 Class Reference

```
#include <gdcmmULActionAA.h>
```

Inheritance diagram for gdcmm::network::ULActionAA6:



Collaboration diagram for gdcmm::network::ULActionAA6:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULError](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.286.1 Member Function Documentation

25.286.1.1 [EStateID gdcmm::network::ULActionAA6::PerformAction](#) ([Subject](#) * s, [ULError](#) & *inEvent*, [ULConnection](#) & *inConnection*, bool & *outWaitingForEvent*, [EEventID](#) & *outRaisedEvent*) [virtual]

Implements [gdcmm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmmULActionAA.h](#)


25.287 gdcmm::network::ULActionAA7 Class Reference

```
#include <gdcmmULActionAA.h>
```

Inheritance diagram for gdcmm::network::ULActionAA7:



Collaboration diagram for gdcmm::network::ULActionAA7:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.287.1 Member Function Documentation

25.287.1.1 `EStateID gdcmm::network::ULActionAA7::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent) [virtual]`

Implements [gdcmm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAA.h](#)


25.288 gdcm::network::ULActionAA8 Class Reference

```
#include <gdcmULActionAA.h>
```

Inheritance diagram for gdcm::network::ULActionAA8:



Collaboration diagram for gdcm::network::ULActionAA8:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.288.1 Member Function Documentation

25.288.1.1 **EStateID** `gdcm::network::ULActionAA8::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent)` [virtual]

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAA.h](#)


25.289 `gdcm::network::ULActionAE1` Class Reference

```
#include <gdcmULActionAE.h>
```

Inheritance diagram for `gdcm::network::ULActionAE1`:



Collaboration diagram for `gdcm::network::ULActionAE1`:



Public Member Functions

- [EStateID](#) [PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.289.1 Member Function Documentation

25.289.1.1 `EStateID` `gdcm::network::ULActionAE1::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent)` `[virtual]`

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAE.h](#)


25.290 gdcm::network::ULActionAE2 Class Reference

```
#include <gdcmULActionAE.h>
```

Inheritance diagram for `gdcm::network::ULActionAE2`:



Collaboration diagram for `gdcm::network::ULActionAE2`:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULError](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.290.1 Member Function Documentation

25.290.1.1 [EStateID](#) `gdcm::network::ULActionAE2::PerformAction (Subject * s, ULError & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent)` [virtual]

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAE.h](#)


25.291 [gdcm::network::ULActionAE3](#) Class Reference

```
#include <gdcmULActionAE.h>
```

Inheritance diagram for `gdcm::network::ULActionAE3`:



Collaboration diagram for gdcm::network::ULActionAE3:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.291.1 Member Function Documentation

25.291.1.1 `EStateID gdcm::network::ULActionAE3::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent) [virtual]`

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAE.h](#)


25.292 gdcm::network::ULActionAE4 Class Reference

```
#include <gdcmULActionAE.h>
```

Inheritance diagram for `gdcn::network::ULActionAE4`:



Collaboration diagram for `gdcn::network::ULActionAE4`:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [UEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.292.1 Member Function Documentation

25.292.1.1 **EStateID** `gdcn::network::ULActionAE4::PerformAction` ([Subject](#) *s, [UEvent](#) & *inEvent*, [ULConnection](#) & *inConnection*, bool & *outWaitingForEvent*, [EEventID](#) & *outRaisedEvent*) [[virtual](#)]

Implements [gdcn::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcnULActionAE.h](#)


25.293 gdcmm::network::ULActionAE5 Class Reference

```
#include <gdcmmULActionAE.h>
```

Inheritance diagram for gdcmm::network::ULActionAE5:



Collaboration diagram for gdcmm::network::ULActionAE5:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.293.1 Member Function Documentation

25.293.1.1 [EStateID gdcmm::network::ULActionAE5::PerformAction](#) ([Subject](#) * s, [ULEvent](#) & *inEvent*, [ULConnection](#) & *inConnection*, bool & *outWaitingForEvent*, [EEventID](#) & *outRaisedEvent*) `[virtual]`

Implements [gdcmm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAE.h](#)


25.294 gdcm::network::ULActionAE6 Class Reference

```
#include <gdcmULActionAE.h>
```

Inheritance diagram for gdcm::network::ULActionAE6:



Collaboration diagram for gdcm::network::ULActionAE6:



Public Member Functions

- [EStateID](#) [PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.294.1 Member Function Documentation

25.294.1.1 `EStateID` `gdcm::network::ULActionAE6::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent)` [virtual]

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAE.h](#)


25.295 gdcm::network::ULActionAE7 Class Reference

```
#include <gdcmULActionAE.h>
```

Inheritance diagram for `gdcm::network::ULActionAE7`:



Collaboration diagram for `gdcm::network::ULActionAE7`:



Public Member Functions

- [EStateID](#) [PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.295.1 Member Function Documentation

25.295.1.1 `EStateID gdcmm::network::ULActionAE7::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent) [virtual]`

Implements [gdcmm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmmULActionAE.h](#)


25.296 gdcmm::network::ULActionAE8 Class Reference

```
#include <gdcmmULActionAE.h>
```

Inheritance diagram for gdcmm::network::ULActionAE8:



Collaboration diagram for gdcmm::network::ULActionAE8:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULError](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.296.1 Member Function Documentation

25.296.1.1 [EStateID](#) `gdcm::network::ULActionAR1::PerformAction (Subject * s, ULError & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent)` [virtual]

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAR.h](#)


25.297 gdcm::network::ULActionAR1 Class Reference

```
#include <gdcmULActionAR.h>
```

Inheritance diagram for `gdcm::network::ULActionAR1`:



Collaboration diagram for `gdcmm::network::ULActionAR1`:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULError](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.297.1 Member Function Documentation

25.297.1.1 `EStateID gdcmm::network::ULActionAR1::PerformAction (Subject * s, ULError & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent) [virtual]`

Implements [gdcmm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmmULActionAR.h](#)


25.298 gdcmm::network::ULActionAR10 Class Reference

```
#include <gdcmmULActionAR.h>
```


Inheritance diagram for gdcn::network::ULActionAR10:



Collaboration diagram for gdcn::network::ULActionAR10:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULError](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.298.1 Member Function Documentation

25.298.1.1 [EStateID gdcn::network::ULActionAR10::PerformAction](#) ([Subject](#) * s, [ULError](#) & *inEvent*, [ULConnection](#) & *inConnection*, bool & *outWaitingForEvent*, [EEventID](#) & *outRaisedEvent*) `[virtual]`

Implements [gdcn::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcnULActionAR.h](#)


25.299 gdcmm::network::ULActionAR2 Class Reference

```
#include <gdcmmULActionAR.h>
```

Inheritance diagram for gdcmm::network::ULActionAR2:



Collaboration diagram for gdcmm::network::ULActionAR2:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.299.1 Member Function Documentation

25.299.1.1 `EStateID gdcmm::network::ULActionAR2::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent) [virtual]`

Implements [gdcmm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmmULActionAR.h](#)


25.300 gdcmm::network::ULActionAR3 Class Reference

```
#include <gdcmmULActionAR.h>
```

Inheritance diagram for gdcmm::network::ULActionAR3:



Collaboration diagram for gdcmm::network::ULActionAR3:



Public Member Functions

- [EStateID](#) [PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.300.1 Member Function Documentation

25.300.1.1 **EStateID** `gdcm::network::ULActionAR3::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent)` [virtual]

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAR.h](#)


25.301 `gdcm::network::ULActionAR4` Class Reference

```
#include <gdcmULActionAR.h>
```

Inheritance diagram for `gdcm::network::ULActionAR4`:



Collaboration diagram for `gdcm::network::ULActionAR4`:



Public Member Functions

- **EStateID** `PerformAction` (`Subject` *s, `ULEvent` &inEvent, `ULConnection` &inConnection, `bool` &outWaitingForEvent, `EEventID` &outRaisedEvent)

25.301.1 Member Function Documentation

25.301.1.1 **EStateID** gdcm::network::ULActionAR4::PerformAction (**Subject** * *s*, **ULError** & *inEvent*, **ULConnection** & *inConnection*, **bool** & *outWaitingForEvent*, **EEventID** & *outRaisedEvent*) [virtual]

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAR.h](#)


25.302 gdcm::network::ULActionAR5 Class Reference

```
#include <gdcmULActionAR.h>
```

Inheritance diagram for gdcm::network::ULActionAR5:



Collaboration diagram for gdcm::network::ULActionAR5:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULError](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.302.1 Member Function Documentation

25.302.1.1 [EStateID](#) `gdcm::network::ULActionAR5::PerformAction (Subject * s, ULError & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent)` [virtual]

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAR.h](#)


25.303 gdcm::network::ULActionAR6 Class Reference

```
#include <gdcmULActionAR.h>
```

Inheritance diagram for `gdcm::network::ULActionAR6`:



Collaboration diagram for gdcm::network::ULActionAR6:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.303.1 Member Function Documentation

25.303.1.1 `EStateID gdcm::network::ULActionAR6::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent) [virtual]`

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAR.h](#)


25.304 gdcm::network::ULActionAR7 Class Reference

```
#include <gdcmULActionAR.h>
```

Inheritance diagram for `gdcn::network::ULActionAR7`:



Collaboration diagram for `gdcn::network::ULActionAR7`:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULError](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.304.1 Member Function Documentation

25.304.1.1 [EStateID gdcn::network::ULActionAR7::PerformAction](#) ([Subject](#) * s, [ULError](#) & *inEvent*, [ULConnection](#) & *inConnection*, bool & *outWaitingForEvent*, [EEventID](#) & *outRaisedEvent*) [[virtual](#)]

Implements [gdcn::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcnULActionAR.h](#)


25.305 gdcm::network::ULActionAR8 Class Reference

```
#include <gdcmULActionAR.h>
```

Inheritance diagram for gdcm::network::ULActionAR8:



Collaboration diagram for gdcm::network::ULActionAR8:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.305.1 Member Function Documentation

25.305.1.1 **EStateID** `gdcm::network::ULActionAR8::PerformAction` (`Subject` * s, `ULEvent` & *inEvent*, `ULConnection` & *inConnection*, bool & *outWaitingForEvent*, `EEventID` & *outRaisedEvent*) `[virtual]`

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmlActionAR.h](#)


25.306 gdcml::network::ULActionAR9 Class Reference

```
#include <gdcmlActionAR.h>
```

Inheritance diagram for gdcml::network::ULActionAR9:



Collaboration diagram for gdcml::network::ULActionAR9:



Public Member Functions

- [EStateID](#) [PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.306.1 Member Function Documentation

25.306.1.1 `EStateID` `gdcm::network::ULActionAR9::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent)` [virtual]

Implements [gdcm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmULActionAR.h](#)


25.307 gdcm::network::ULActionDT1 Class Reference

```
#include <gdcmULActionDT.h>
```

Inheritance diagram for `gdcm::network::ULActionDT1`:



Collaboration diagram for `gdcm::network::ULActionDT1`:



Public Member Functions

- [EStateID](#) [PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.307.1 Member Function Documentation

25.307.1.1 `EStateID gdcmm::network::ULActionDT1::PerformAction (Subject * s, ULEvent & inEvent, ULConnection & inConnection, bool & outWaitingForEvent, EEventID & outRaisedEvent) [virtual]`

Implements [gdcmm::network::ULAction](#).


The documentation for this class was generated from the following file:

- [gdcmmULActionDT.h](#)


25.308 gdcmm::network::ULActionDT2 Class Reference

```
#include <gdcmmULActionDT.h>
```

Inheritance diagram for gdcmm::network::ULActionDT2:



Collaboration diagram for gdcmm::network::ULActionDT2:



Public Member Functions

- [EStateID PerformAction](#) ([Subject](#) *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [EEventID](#) &outRaisedEvent)

25.308.1 Member Function Documentation

25.308.1.1 [EStateID](#) [gdcm::network::ULActionDT2::PerformAction](#) ([Subject](#) * s, [ULEvent](#) & *inEvent*, [ULConnection](#) & *inConnection*, bool & *outWaitingForEvent*, [EEventID](#) & *outRaisedEvent*) `[virtual]`

Implements [gdcm::network::ULAction](#).

The documentation for this class was generated from the following file:


- [gdcmULActionDT.h](#)

25.309 gdcm::network::ULBasicCallback Class Reference


[ULBasicCallback](#) This is the most basic of callbacks for how the [ULConnectionManager](#) handles incoming datasets. DataSets are just concatenated to the mDataSets vector, and the result can be pulled out of the vector by later code. Alternatives to this method include progress updates, saving to disk, etc. This class is NOT THREAD SAFE. Access the dataset vector after the entire set of datasets has been returned by the [ULConnectionManager](#).

```
#include <gdcmULBasicCallback.h>
```

Inheritance diagram for [gdcm::network::ULBasicCallback](#):



Collaboration diagram for `gdcm::network::ULBasicCallback`:



Public Member Functions

- [ULBasicCallback](#) ()
- virtual [~ULBasicCallback](#) ()
- `std::vector< DataSet > const & GetDataSets () const`
- `std::vector< DataSet > const & GetResponses () const`
- virtual void [HandleDataSet](#) (const [DataSet](#) &inDataSet)
- virtual void [HandleResponse](#) (const [DataSet](#) &inDataSet)

Additional Inherited Members

25.309.1 Detailed Description

[ULBasicCallback](#) This is the most basic of callbacks for how the [ULConnectionManager](#) handles incoming datasets. DataSets are just concatenated to the `mDataSets` vector, and the result can be pulled out of the vector by later code. Alternatives to this method include progress updates, saving to disk, etc. This class is NOT THREAD SAFE. Access the dataset vector after the entire set of datasets has been returned by the [ULConnectionManager](#).

25.309.2 Constructor & Destructor Documentation

25.309.2.1 `gdcm::network::ULBasicCallback::ULBasicCallback ()` `[inline]`

25.309.2.2 `virtual gdcm::network::ULBasicCallback::~~ULBasicCallback ()` `[inline], [virtual]`

25.309.3 Member Function Documentation

25.309.3.1 `std::vector<DataSet> const& gdcm::network::ULBasicCallback::GetDataSets () const`

25.309.3.2 `std::vector<DataSet> const& gdcm::network::ULBasicCallback::GetResponses () const`

25.309.3.3 `virtual void gdcm::network::ULBasicCallback::HandleDataSet (const DataSet & inDataSet)` `[virtual]`

Implements [gdcm::network::ULConnectionCallback](#).

25.309.3.4 virtual void gdcm::network::ULBasicCallback::HandleResponse (const DataSet & inDataSet) [virtual]

Implements [gdcm::network::ULConnectionCallback](#).

The documentation for this class was generated from the following file:

- [gdcmULBasicCallback.h](#)

25.310 gdcm::network::ULConnection Class Reference

[ULConnection](#) This is the class that contains the socket to another machine, and passes data through itself, as well as maintaining a sense of state.

```
#include <gdcmULConnection.h>
```

Public Member Functions

- [ULConnection](#) (const [ULConnectionInfo](#) &inUserInformation)
- virtual [~ULConnection](#) ()
- void [AddAcceptedPresentationContext](#) (const [PresentationContextAC](#) &inPC)
- [PresentationContextRQ FindContext](#) (const [DataElement](#) &de) const
- std::vector
< [PresentationContextAC](#) >
const & [GetAcceptedPresentationContexts](#) () const
- std::vector
< [PresentationContextAC](#) > & [GetAcceptedPresentationContexts](#) ()
- const [ULConnectionInfo](#) & [GetConnectionInfo](#) () const
- uint32_t [GetMaxPDUSize](#) () const
- const [PresentationContextAC](#) * [GetPresentationContextACByID](#) (uint8_t id) const
- uint8_t [GetPresentationContextIDFromPresentationContext](#) ([PresentationContextRQ](#) const &pc) const
return 0 upon error
- const [PresentationContextRQ](#) * [GetPresentationContextRQByID](#) (uint8_t id) const
- std::vector
< [PresentationContextRQ](#) >
const & [GetPresentationContexts](#) () const
- std::iostream * [GetProtocol](#) ()
- [EStateID](#) [GetState](#) () const
- [ARTIMTimer](#) & [GetTimer](#) ()
- bool [InitializeConnection](#) ()
used to establish scu connections
- bool [InitializeIncomingConnection](#) ()
used to establish scp connections
- void [SetMaxPDUSize](#) (uint32_t inSize)
- void [SetPresentationContexts](#) (const std::vector< [PresentationContextRQ](#) > &inContexts)
- void [SetPresentationContexts](#) (const std::vector< [PresentationContext](#) > &inContexts)
- void [SetState](#) (const [EStateID](#) &inState)
- void [StopProtocol](#) ()

25.310.1 Detailed Description

ULConnection This is the class that contains the socket to another machine, and passes data through itself, as well as maintaining a sense of state.

The **ULConnectionManager** tells the **ULConnection** what data can actually be sent.

This class is done this way so that it can be eventually be replaced with a **ULSecureConnection**, if such a protocol is warranted, so that all data that passes through can be managed through a secure connection. For now, this class provides a simple pass-through mechanism to the socket itself.

So, for instance, a **gdcm** object will be passes to this object, and it will then get passed along the connection, if that connection is in the proper state to do so.

For right now, this class is not directly intended to be inherited from, but the potential for future **ULSecureConnection** warrants the addition, rather than having everything be managed from within the **ULConnectionManager** (or this class) without a wrapper.

25.310.2 Constructor & Destructor Documentation

25.310.2.1 **gdcm::network::ULConnection::ULConnection (const ULConnectionInfo & *inUserInfo*)**

25.310.2.2 **virtual gdcm::network::ULConnection::~~ULConnection () [virtual]**

25.310.3 Member Function Documentation

25.310.3.1 **void gdcm::network::ULConnection::AddAcceptedPresentationContext (const PresentationContextAC & *inPC*)**

25.310.3.2 **PresentationContextRQ gdcm::network::ULConnection::FindContext (const DataElement & *de*) const**

25.310.3.3 **std::vector<PresentationContextAC> const& gdcm::network::ULConnection::GetAcceptedPresentationContexts () const**

25.310.3.4 **std::vector<PresentationContextAC>& gdcm::network::ULConnection::GetAcceptedPresentationContexts ()**

25.310.3.5 **const ULConnectionInfo& gdcm::network::ULConnection::GetConnectionInfo () const**

25.310.3.6 **uint32_t gdcm::network::ULConnection::GetMaxPDUSize () const**

25.310.3.7 **const PresentationContextAC* gdcm::network::ULConnection::GetPresentationContextACByID (uint8_t *id*) const**

25.310.3.8 **uint8_t gdcm::network::ULConnection::GetPresentationContextIDFromPresentationContext (PresentationContextRQ const & *pc*) const**

return 0 upon error

25.310.3.9 **const PresentationContextRQ* gdcm::network::ULConnection::GetPresentationContextRQByID (uint8_t *id*) const**

25.310.3.10 **std::vector<PresentationContextRQ> const& gdcm::network::ULConnection::GetPresentationContexts () const**

25.310.3.11 **std::iostream* gdcm::network::ULConnection::GetProtocol ()**

25.310.3.12 **EStateID gdcm::network::ULConnection::GetState () const**

25.310.3.13 **ARTIMTimer&** gdcm::network::ULConnection::GetTimer ()

25.310.3.14 **bool** gdcm::network::ULConnection::InitializeConnection ()

used to establish scu connections

25.310.3.15 **bool** gdcm::network::ULConnection::InitializeIncomingConnection ()

used to establish scp connections

25.310.3.16 **void** gdcm::network::ULConnection::SetMaxPDUSize (**uint32_t** *inSize*)

25.310.3.17 **void** gdcm::network::ULConnection::SetPresentationContexts (**const** **std::vector**< **PresentationContextRQ** > & *inContexts*)

25.310.3.18 **void** gdcm::network::ULConnection::SetPresentationContexts (**const** **std::vector**< **PresentationContext** > & *inContexts*)

25.310.3.19 **void** gdcm::network::ULConnection::SetState (**const** **EStateID** & *inState*)

25.310.3.20 **void** gdcm::network::ULConnection::StopProtocol ()


The documentation for this class was generated from the following file:

- [gdcmULConnection.h](#)

25.311 gdcm::network::ULConnectionCallback Class Reference

```
#include <gdcmULConnectionCallback.h>
```

Inheritance diagram for gdcm::network::ULConnectionCallback:



Public Member Functions

- [ULConnectionCallback](#) ()

- virtual [~ULConnectionCallback](#) ()
- bool [DataSetHandles](#) () const
- virtual void [HandleDataSet](#) (const [DataSet](#) &inDataSet)=0
- virtual void [HandleResponse](#) (const [DataSet](#) &inDataSet)=0
- void [ResetHandledDataSet](#) ()

Protected Member Functions

- void [DataSetHandled](#) ()

25.311.1 Detailed Description

When a dataset comes back from a query/move/etc, the result can either be stored entirely in memory, or could be stored on disk. This class provides a mechanism to indicate what the [ULConnectionManager](#) should do with datasets that are produced through query results. The [ULConnectionManager](#) will call the [HandleDataSet](#) function during the course of receiving datasets. Particular implementations should fill in what that function does, including updating progress, etc. NOTE: since cmove requires that multiple event loops be employed, the callback function MUST set [mHandledDataSet](#) to true. otherwise, the cmove event loop handler will not know data was received, and proceed to end the loop prematurely.

25.311.2 Constructor & Destructor Documentation

25.311.2.1 `gdcmm::network::ULConnectionCallback::ULConnectionCallback ()` `[inline]`

25.311.2.2 `virtual gdcmm::network::ULConnectionCallback::~~ULConnectionCallback ()` `[inline]`, `[virtual]`

25.311.3 Member Function Documentation

25.311.3.1 `void gdcmm::network::ULConnectionCallback::DataSetHandled ()` `[inline]`, `[protected]`

25.311.3.2 `bool gdcmm::network::ULConnectionCallback::DataSetHandles ()` `const` `[inline]`

25.311.3.3 `virtual void gdcmm::network::ULConnectionCallback::HandleDataSet (const DataSet & inDataSet)` `[pure virtual]`

Implemented in [gdcmm::network::ULBasicCallback](#), and [gdcmm::network::ULWritingCallback](#).

25.311.3.4 `virtual void gdcmm::network::ULConnectionCallback::HandleResponse (const DataSet & inDataSet)` `[pure virtual]`

Implemented in [gdcmm::network::ULBasicCallback](#), and [gdcmm::network::ULWritingCallback](#).

25.311.3.5 `void gdcmm::network::ULConnectionCallback::ResetHandledDataSet ()` `[inline]`

The documentation for this class was generated from the following file:

- [gdcmmULConnectionCallback.h](#)

25.312 gdcm::network::ULConnectionInfo Class Reference

[ULConnectionInfo](#) this class contains all the information about a particular connection as established by the user. That is, it's: User Information Calling AE Title Called AE Title IP address/computer name IP Port A connection must be established with this information, that's subsequently placed into various primitives for actual communication.

```
#include <gdcmULConnectionInfo.h>
```

Public Member Functions

- [ULConnectionInfo](#) ()
- const char * [GetCalledAETitle](#) () const
- std::string [GetCalledComputerName](#) () const
- unsigned long [GetCalledIPAddress](#) () const
- int [GetCalledIPPort](#) () const
- const char * [GetCallingAETitle](#) () const
- unsigned long [GetMaxPDULength](#) () const
- bool [Initialize](#) ([UserInformation](#) const &inUserInformation, const char *inCalledAETitle, const char *inCallingAETitle, unsigned long inCalledIPAddress, int inCalledIPPort, std::string inCalledComputerName)
- void [SetMaxPDULength](#) (unsigned long inMaxPDULength)

25.312.1 Detailed Description

[ULConnectionInfo](#) this class contains all the information about a particular connection as established by the user. That is, it's: User Information Calling AE Title Called AE Title IP address/computer name IP Port A connection must be established with this information, that's subsequently placed into various primitives for actual communication.

25.312.2 Constructor & Destructor Documentation

25.312.2.1 `gdcm::network::ULConnectionInfo::ULConnectionInfo ()`

25.312.3 Member Function Documentation

25.312.3.1 `const char* gdcm::network::ULConnectionInfo::GetCalledAETitle () const`

25.312.3.2 `std::string gdcm::network::ULConnectionInfo::GetCalledComputerName () const`

25.312.3.3 `unsigned long gdcm::network::ULConnectionInfo::GetCalledIPAddress () const`

25.312.3.4 `int gdcm::network::ULConnectionInfo::GetCalledIPPort () const`

25.312.3.5 `const char* gdcm::network::ULConnectionInfo::GetCallingAETitle () const`

25.312.3.6 `unsigned long gdcm::network::ULConnectionInfo::GetMaxPDULength () const`

25.312.3.7 `bool gdcm::network::ULConnectionInfo::Initialize (UserInformation const & inUserInformation, const char * inCalledAETitle, const char * inCallingAETitle, unsigned long inCalledIPAddress, int inCalledIPPort, std::string inCalledComputerName)`

25.312.3.8 void gdcn::network::ULConnectionInfo::SetMaxPDULength (unsigned long *inMaxPDULength*)

The documentation for this class was generated from the following file:


- [gdcnULConnectionInfo.h](#)

25.313 gdcn::network::ULConnectionManager Class Reference


[ULConnectionManager](#) The [ULConnectionManager](#) performs actions on the [ULConnection](#) given inputs from the user and from the state of what's going on around the connection (ie, timeouts of the ARTIM timer, responses from the peer across the connection, etc).

```
#include <gdcnULConnectionManager.h>
```

Inheritance diagram for gdcn::network::ULConnectionManager:



Collaboration diagram for gdcm::network::ULConnectionManager:



Public Member Functions

- [ULConnectionManager](#) ()
- [~ULConnectionManager](#) ()
- bool [BreakConnection](#) (const double &inTimeout)
- void [BreakConnectionNow](#) ()
- bool [EstablishConnection](#) (const std::string &inAETitle, const std::string &inConnectAETitle, const std::string &inComputerName, long inIPAddress, uint16_t inConnectPort, double inTimeout, std::vector< [PresentationContext](#) > const &pcVector)
- bool [EstablishConnectionMove](#) (const std::string &inAETitle, const std::string &inConnectAETitle, const std::string &inComputerName, long inIPAddress, uint16_t inConnectPort, double inTimeout, uint16_t inReturnPort, std::vector< [PresentationContext](#) > const &pcVector)
- std::vector< [PresentationDataValue](#) > [SendEcho](#) ()
- std::vector< [DataSet](#) > [SendFind](#) (const [BaseRootQuery](#) *inRootQuery)
- void [SendFind](#) (const [BaseRootQuery](#) *inRootQuery, [ULConnectionCallback](#) *inCallback)
- std::vector< [DataSet](#) > [SendMove](#) (const [BaseRootQuery](#) *inRootQuery)
- bool [SendMove](#) (const [BaseRootQuery](#) *inRootQuery, [ULConnectionCallback](#) *inCallback)
return false upon error
- std::vector< [DataSet](#) > [SendStore](#) (const [File](#) &file)
- void [SendStore](#) (const [File](#) &file, [ULConnectionCallback](#) *inCallback)
callback based API

Additional Inherited Members

25.313.1 Detailed Description

[ULConnectionManager](#) The [ULConnectionManager](#) performs actions on the [ULConnection](#) given inputs from the user and from the state of what's going on around the connection (ie, timeouts of the ARTIM timer, responses from the peer across the connection, etc).

Its inputs are ULEvents, and it performs ULActions.

25.313.2 Constructor & Destructor Documentation

25.313.2.1 `gdcmm::network::ULConnectionManager::ULConnectionManager ()`

25.313.2.2 `gdcmm::network::ULConnectionManager::~~ULConnectionManager ()`

25.313.3 Member Function Documentation

25.313.3.1 `bool gdcmm::network::ULConnectionManager::BreakConnection (const double & inTimeout)`

25.313.3.2 `void gdcmm::network::ULConnectionManager::BreakConnectionNow ()`

25.313.3.3 `bool gdcmm::network::ULConnectionManager::EstablishConnection (const std::string & inAETitle, const std::string & inConnectAETitle, const std::string & inComputerName, long inIPAddress, uint16_t inConnectPort, double inTimeout, std::vector< PresentationContext > const & pcVector)`

returns true if a connection of the given AETitle (ie, 'this' program) is able to connect to the given AETitle and Port in a certain amount of time providing the connection type will establish the proper exchange syntax with a server; if a different functionality is required, a different connection should be established. returns false if the connection type is 'move'— have to give a return port for move to work as specified.

25.313.3.4 `bool gdcmm::network::ULConnectionManager::EstablishConnectionMove (const std::string & inAETitle, const std::string & inConnectAETitle, const std::string & inComputerName, long inIPAddress, uint16_t inConnectPort, double inTimeout, uint16_t inReturnPort, std::vector< PresentationContext > const & pcVector)`

returns true for above reasons, but contains the special 'move' port

25.313.3.5 `std::vector<PresentationDataValue> gdcmm::network::ULConnectionManager::SendEcho ()`

25.313.3.6 `std::vector<DataSet> gdcmm::network::ULConnectionManager::SendFind (const BaseRootQuery * inRootQuery)`

25.313.3.7 `void gdcmm::network::ULConnectionManager::SendFind (const BaseRootQuery * inRootQuery, ULConnectionCallback * inCallback)`

25.313.3.8 `std::vector<DataSet> gdcmm::network::ULConnectionManager::SendMove (const BaseRootQuery * inRootQuery)`

25.313.3.9 `bool gdcmm::network::ULConnectionManager::SendMove (const BaseRootQuery * inRootQuery, ULConnectionCallback * inCallback)`

return false upon error

25.313.3.10 `std::vector<DataSet> gdcmm::network::ULConnectionManager::SendStore (const File & file)`

25.313.3.11 void gdcm::network::ULConnectionManager::SendStore (const File & file, ULConnectionCallback * inCallback)

callback based API

The documentation for this class was generated from the following file:

- [gdcmULConnectionManager.h](#)

25.314 gdcm::network::ULEvent Class Reference

[ULEvent](#) base class for network events.

```
#include <gdcmULEvent.h>
```

Public Member Functions

- [ULEvent](#) (const [EEventID](#) &inEventID, std::vector< [BasePDU](#) * > const &inBasePDU)
- [ULEvent](#) (const [EEventID](#) &inEventID, [BasePDU](#) *inBasePDU)
- [~ULEvent](#) ()
- [EEventID](#) [GetEvent](#) () const
- std::vector< [BasePDU](#) * > const & [GetPDUs](#) () const
- void [SetEvent](#) (const [EEventID](#) &inEvent)
- void [SetPDU](#) (std::vector< [BasePDU](#) * > const &inPDU)

25.314.1 Detailed Description

[ULEvent](#) base class for network events.

An event consists of the event ID and the data associated with that event.

Note that once a PDU is created, it is now the responsibility of the associated event to destroy it!

25.314.2 Constructor & Destructor Documentation

25.314.2.1 gdcm::network::ULEvent::ULEvent (const [EEventID](#) & inEventID, std::vector< [BasePDU](#) * > const & inBasePDU)
[inline]

25.314.2.2 gdcm::network::ULEvent::ULEvent (const [EEventID](#) & inEventID, [BasePDU](#) * inBasePDU) [inline]

25.314.2.3 gdcm::network::ULEvent::~~ULEvent () [inline]

25.314.3 Member Function Documentation

25.314.3.1 [EEventID](#) gdcm::network::ULEvent::GetEvent () const [inline]

25.314.3.2 std::vector<[BasePDU](#)*> const& gdcm::network::ULEvent::GetPDUs () const [inline]

25.314.3.3 void gdcm::network::ULEvent::SetEvent (const [EEventID](#) & inEvent) [inline]

25.314.3.4 void gdcmm::network::ULEvent::SetPDU (std::vector< BasePDU * > const & inPDU) [inline]

The documentation for this class was generated from the following file:

- [gdcmmULEvent.h](#)

25.315 gdcmm::network::ULTransitionTable Class Reference

[ULTransitionTable](#) The transition table of all the ULEvents, new ULActions, and ULStates.

```
#include <gdcmmULTransitionTable.h>
```

Public Member Functions

- [ULTransitionTable](#) ()
- void [HandleEvent](#) (Subject *s, [ULEvent](#) &inEvent, [ULConnection](#) &inConnection, bool &outWaitingForEvent, [E-EventID](#) &outRaisedEvent) const
- void [PrintTable](#) () const

25.315.1 Detailed Description

[ULTransitionTable](#) The transition table of all the ULEvents, new ULActions, and ULStates.

Based roughly on the solutions in player2.cpp in the boost examples and this so question: <http://stackoverflow.com/questions/1647631/c-state-machine-design>

The transition table is constructed of TableRows. Each row is based on an event, and an event handler in the TransitionTable object takes a given event, and then finds the given row.

Then, given the current state of the connection, determines the appropriate action to take and then the state to transition to next.

25.315.2 Constructor & Destructor Documentation

25.315.2.1 gdcmm::network::ULTransitionTable::ULTransitionTable ()

25.315.3 Member Function Documentation

25.315.3.1 void gdcmm::network::ULTransitionTable::HandleEvent (Subject * s, [ULEvent](#) & inEvent, [ULConnection](#) & inConnection, bool & outWaitingForEvent, [EEventID](#) & outRaisedEvent) const

25.315.3.2 void gdcmm::network::ULTransitionTable::PrintTable () const


The documentation for this class was generated from the following file:

- [gdcmmULTransitionTable.h](#)


25.316 gdcmm::network::ULWritingCallback Class Reference

```
#include <gdcmmULWritingCallback.h>
```


Inheritance diagram for gdcm::network::ULWritingCallback:



Collaboration diagram for gdcm::network::ULWritingCallback:



Public Member Functions

- [ULWritingCallback](#) ()
- virtual [~ULWritingCallback](#) ()
- virtual void [HandleDataSet](#) (const [DataSet](#) &inDataSet)
- virtual void [HandleResponse](#) (const [DataSet](#) &inDataSet)
- void [SetDirectory](#) (const std::string &inDirectoryName)

provide the directory into which all files are written.

Additional Inherited Members

25.316.1 Constructor & Destructor Documentation

25.316.1.1 `gdcm::network::ULWritingCallback::ULWritingCallback ()` `[inline]`

25.316.1.2 `virtual gdcm::network::ULWritingCallback::~~ULWritingCallback ()` `[inline],[virtual]`

25.316.2 Member Function Documentation

25.316.2.1 `virtual void gdcm::network::ULWritingCallback::HandleDataSet (const DataSet & inDataSet)` `[virtual]`

Implements [gdcm::network::ULConnectionCallback](#).

25.316.2.2 `virtual void gdcm::network::ULWritingCallback::HandleResponse (const DataSet & inDataSet)` `[virtual]`

Implements [gdcm::network::ULConnectionCallback](#).

25.316.2.3 `void gdcm::network::ULWritingCallback::SetDirectory (const std::string & inDirectoryName)` `[inline]`

provide the directory into which all files are written.

The documentation for this class was generated from the following file:


- [gdcmULWritingCallback.h](#)

25.317 gdcm::UNExplicitDataElement Class Reference


Class to read/write a [DataElement](#) as UNExplicit Data [Element](#).

```
#include <gdcmUNExplicitDataElement.h>
```

Inheritance diagram for `gdcm::UNExplicitDataElement`:



Collaboration diagram for gdcm::UNExplicitDataElement:



Public Member Functions

- [VL GetLength](#) () const
- template<typename TSwap >
std::istream & [Read](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadPreValue](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadValue](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadWithLength](#) (std::istream &is, [VL](#) &length)

Additional Inherited Members

25.317.1 Detailed Description

Class to read/write a [DataElement](#) as UNExplicit Data [Element](#).

Note

bla

25.317.2 Member Function Documentation

25.317.2.1 VL gdcm::UNExplicitDataElement::GetLength () const

25.317.2.2 `template<typename TSwap > std::istream& gdcm::UNExplicitDataElement::Read (std::istream & is)`

25.317.2.3 `template<typename TSwap > std::istream& gdcm::UNExplicitDataElement::ReadPreValue (std::istream & is)`

25.317.2.4 `template<typename TSwap > std::istream& gdcm::UNExplicitDataElement::ReadValue (std::istream & is)`

25.317.2.5 `template<typename TSwap > std::istream& gdcm::UNExplicitDataElement::ReadWithLength (std::istream & is, VL & length)`

The documentation for this class was generated from the following file:


- [gdcmUNExplicitDataElement.h](#)

25.318 gdcm::UNExplicitImplicitDataElement Class Reference


Class to read/write a [DataElement](#) as ExplicitImplicit Data [Element](#) This class gather two known bugs:

```
#include <gdcmUNExplicitImplicitDataElement.h>
```

Inheritance diagram for gdcm::UNExplicitImplicitDataElement:



Collaboration diagram for gdcM::UNExplicitImplicitDataElement:



Public Member Functions

- [VL GetLength](#) () const
- template<typename TSwap >
std::istream & [Read](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadPreValue](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadValue](#) (std::istream &is)

Additional Inherited Members

25.318.1 Detailed Description

Class to read/write a [DataElement](#) as ExplicitImplicit Data [Element](#) This class gather two known bugs:

1. GDCM 1.2.0 would rewrite [VR](#)=UN [Value](#) Length on 2 bytes instead of 4 bytes
2. GDCM 1.2.0 would also rewrite [DataElement](#) as Implicit when the [VR](#) would not be known this would only happen in some very rare cases. gdcM 2.X design could handle bug #1 or #2 exclusively, this class can now handle file which have both issues. See: gdcMData/TherapysGDCM120Bug.dcm

25.318.2 Member Function Documentation

25.318.2.1 VL gdcM::UNExplicitImplicitDataElement::GetLength () const

25.318.2.2 `template<typename TSwap > std::istream& gdcm::UNExplicitImplicitDataElement::Read (std::istream & is)`

25.318.2.3 `template<typename TSwap > std::istream& gdcm::UNExplicitImplicitDataElement::ReadPreValue (std::istream & is)`

25.318.2.4 `template<typename TSwap > std::istream& gdcm::UNExplicitImplicitDataElement::ReadValue (std::istream & is)`

The documentation for this class was generated from the following file:

- [gdcmUNExplicitImplicitDataElement.h](#)

25.319 gdcm::Unpacker12Bits Class Reference

Pack/Unpack 12 bits pixel into 16bits.

```
#include <gdcmUnpacker12Bits.h>
```

Static Public Member Functions

- static bool [Pack](#) (char *out, const char *in, size_t n)
- static bool [Unpack](#) (char *out, const char *in, size_t n)

25.319.1 Detailed Description

Pack/Unpack 12 bits pixel into 16bits.

- You can only pack an even number of 16bits, which means a multiple of 4 (expressed in bytes)
- You can only unpack a multiple of 3 bytes

This class has no purpose in general purpose DICOM implementation. However to be able to cope with some early ACR-NEMA file generated by a well-known private vendor, one would need to unpack 12bits Stored Pixel [Value](#) into a more standard 16bits Stored Pixel [Value](#).

See Also

[Rescaler](#)

25.319.2 Member Function Documentation

25.319.2.1 `static bool gdcm::Unpacker12Bits::Pack (char * out, const char * in, size_t n) [static]`

Pack an array of 16bits where all values are 12bits into a pack form. n is the length in bytes of array in, out will be a fake 8bits array of size $(n / 2) * 3$

25.319.2.2 `static bool gdcm::Unpacker12Bits::Unpack (char * out, const char * in, size_t n) [static]`

Unpack an array of 'packed' 12bits data into a more conventional 16bits array. n is the length in bytes of array in, out will be a 16bits array of size $(n / 3) * 2$

The documentation for this class was generated from the following file:

- [gdcmUnpacker12Bits.h](#)

25.320 gdcmm::Usage Class Reference

Usage.

```
#include <gdcmmUsage.h>
```

Public Types

- enum [UsageType](#) {
[Mandatory](#),
[Conditional](#),
[UserOption](#),
[Invalid](#) }

Public Member Functions

- [Usage](#) ([UsageType](#) type=[Invalid](#))
- [operator UsageType](#) () const

Static Public Member Functions

- static const char * [GetUsageString](#) ([UsageType](#) type)
- static [UsageType](#) [GetUsageType](#) (const char *type)

Friends

- std::ostream & [operator<<](#) (std::ostream &os, const [Usage](#) &vr)

25.320.1 Detailed Description

Usage.

Note

A.1.3 [IOD Module Table](#) and Functional Group [Macro Table](#) This Section of each [IOD](#) defines in a tabular form the [Modules](#) comprising the [IOD](#). The following information must be specified for each [Module](#) in the table:

- The name of the [Module](#) or Functional Group
 - A reference to the Section in Annex C which defines the [Module](#) or Functional Group
 - The usage of the [Module](#) or Functional Group; whether it is:
 - Mandatory (see A.1.3.1) , abbreviated M
 - Conditional (see A.1.3.2) , abbreviated C
 - User Option (see A.1.3.3) , abbreviated U
- The [Modules](#) referenced are defined in Annex C. A.1.3.1 MANDATORY MODULES For each [IOD](#), Mandatory [Modules](#) shall be supported per the definitions, semantics and requirements defined in Annex C.

A.1.3.2 CONDITIONAL MODULES Conditional [Modules](#) are Mandatory [Modules](#) if specific conditions are met. If the specified conditions are not met, this [Module](#) shall not be supported; that is, no information defined in that [Module](#) shall be sent. A.1.3.3 USER OPTION MODULES User Option [Modules](#) may or may not be supported. If an optional [Module](#) is supported, the [Attribute](#) Types specified in the [Modules](#) in Annex C shall be supported.

25.320.2 Member Enumeration Documentation

25.320.2.1 enum gdcm::Usage::UsageType

Enumerator

Mandatory

Conditional

UserOption

Invalid

25.320.3 Constructor & Destructor Documentation

25.320.3.1 gdcm::Usage::Usage (UsageType type = Invalid) [inline]

25.320.4 Member Function Documentation

25.320.4.1 static const char* gdcm::Usage::GetUsageString (UsageType type) [static]

Referenced by gdcm::operator<<().

25.320.4.2 static UsageType gdcm::Usage::GetUsageType (const char * type) [static]

25.320.4.3 gdcm::Usage::operator UsageType () const [inline]

25.320.5 Friends And Related Function Documentation

25.320.5.1 std::ostream& operator<< (std::ostream & os, const Usage & vr) [friend]


The documentation for this class was generated from the following file:

- [gdcmUsage.h](#)


25.321 gdcm::UserEvent Class Reference

```
#include <gdcmEvent.h>
```


Inheritance diagram for gdcm::UserEvent:



Collaboration diagram for gdcm::UserEvent:



Additional Inherited Members

The documentation for this class was generated from the following file:

- [gdcmEvent.h](#)

25.322 gdcm::network::UserInformation Class Reference

[UserInformation Table 9-16](#) USER INFORMATION ITEM FIELDS.

```
#include <gdcmUserInformation.h>
```

Public Member Functions

- [UserInformation](#) ()
- [~UserInformation](#) ()
- void [AddRoleSelectionSub](#) ([RoleSelectionSub](#) const &r)
- void [AddSOPClassExtendedNegociationSub](#) ([SOPClassExtendedNegociationSub](#) const &s)
- const [MaximumLengthSub](#) & [GetMaximumLengthSub](#) () const
- [MaximumLengthSub](#) & [GetMaximumLengthSub](#) ()
- [UserInformation](#) & [operator=](#) (const [UserInformation](#) &)
- void [Print](#) (std::ostream &os) const
- std::istream & [Read](#) (std::istream &is)
- size_t [Size](#) () const
- const std::ostream & [Write](#) (std::ostream &os) const

25.322.1 Detailed Description

[UserInformation Table 9-16](#) USER INFORMATION ITEM FIELDS.

TODO what is the goal of :

[Table 9-20](#) USER INFORMATION ITEM FIELDS

25.322.2 Constructor & Destructor Documentation

25.322.2.1 `gdcm::network::UserInformation::UserInformation ()`

25.322.2.2 `gdcm::network::UserInformation::~~UserInformation ()`

25.322.3 Member Function Documentation

25.322.3.1 `void gdcm::network::UserInformation::AddRoleSelectionSub (RoleSelectionSub const & r)`

25.322.3.2 `void gdcm::network::UserInformation::AddSOPClassExtendedNegociationSub (SOPClassExtendedNegociationSub const & s)`

25.322.3.3 `const MaximumLengthSub& gdcm::network::UserInformation::GetMaximumLengthSub () const` `[inline]`

25.322.3.4 `MaximumLengthSub& gdcm::network::UserInformation::GetMaximumLengthSub ()` `[inline]`

25.322.3.5 `UserInformation& gdcm::network::UserInformation::operator= (const UserInformation &)`

25.322.3.6 `void gdcm::network::UserInformation::Print (std::ostream & os) const`

25.322.3.7 `std::istream& gdcm::network::UserInformation::Read (std::istream & is)`

25.322.3.8 `size_t gdcm::network::UserInformation::Size () const`

25.322.3.9 `const std::ostream& gdcm::network::UserInformation::Write (std::ostream & os) const`

The documentation for this class was generated from the following file:


- [gdcmUserInformation.h](#)

25.323 gdcm::Validate Class Reference

[Validate](#) class.

```
#include <gdcmValidate.h>
```

Collaboration diagram for gdcm::Validate:



Public Member Functions

- [Validate](#) ()
- [~Validate](#) ()
- const [File](#) & [GetValidatedFile](#) ()
- void [SetFile](#) ([File](#) const &f)
- void [Validation](#) ()

Protected Attributes

- const [File](#) * [F](#)
- [File](#) [V](#)

25.323.1 Detailed Description

[Validate](#) class.

25.323.2 Constructor & Destructor Documentation

25.323.2.1 `gdcm::Validate::Validate ()`

25.323.2.2 `gdcm::Validate::~~Validate ()`

25.323.3 Member Function Documentation

25.323.3.1 `const File& gdcm::Validate::GetValidatedFile ()` `[inline]`

25.323.3.2 `void gdcm::Validate::SetFile (File const & f)` `[inline]`

25.323.3.3 `void gdcm::Validate::Validation ()`

25.323.4 Member Data Documentation

25.323.4.1 `const File* gdcm::Validate::F` `[protected]`

25.323.4.2 `File gdcm::Validate::V` `[protected]`

The documentation for this class was generated from the following file:


- [gdcmValidate.h](#)

25.324 gdcm::Value Class Reference


Class to represent the value of a Data [Element](#).

```
#include <gdcmValue.h>
```

Inheritance diagram for `gdcm::Value`:



Collaboration diagram for gdcm::Value:



Public Member Functions

- [Value](#) ()
- [~Value](#) ()
- virtual void [Clear](#) ()=0
- virtual [VL GetLength](#) () const =0
- virtual bool [operator==](#) (const [Value](#) &val) const =0
- virtual void [SetLength](#) ([VL](#) l)=0

Additional Inherited Members

25.324.1 Detailed Description

Class to represent the value of a Data [Element](#).

Note

VALUE: A component of a [Value](#) Field. A [Value](#) Field may consist of one or more of these components.

25.324.2 Constructor & Destructor Documentation

25.324.2.1 `gdcm::Value::Value ()` `[inline]`

25.324.2.2 `gdcm::Value::~~Value ()` `[inline]`

25.324.3 Member Function Documentation

25.324.3.1 `virtual void gdcm::Value::Clear ()` `[pure virtual]`

Implemented in [gdcm::ByteValue](#), [gdcm::SequenceOfItems](#), and [gdcm::SequenceOfFragments](#).

25.324.3.2 virtual VL gdcM::Value::GetLength () const [pure virtual]

Implemented in [gdcM::ByteValue](#), [gdcM::SequenceOfItems](#), and [gdcM::SequenceOfFragments](#).

Referenced by [gdcM::DataSet::InsertDataElement\(\)](#), and [gdcM::DataElement::SetValue\(\)](#).

25.324.3.3 virtual bool gdcM::Value::operator== (const Value & val) const [pure virtual]

Implemented in [gdcM::SequenceOfFragments](#), [gdcM::SequenceOfItems](#), and [gdcM::ByteValue](#).

25.324.3.4 virtual void gdcM::Value::SetLength (VL /) [pure virtual]

Implemented in [gdcM::ByteValue](#), [gdcM::SequenceOfItems](#), and [gdcM::SequenceOfFragments](#).

The documentation for this class was generated from the following file:

- [gdcMValue.h](#)

25.325 gdcM::ValueIO< TDE, TSwap, TType > Class Template Reference

Class to dispatch template calls.

```
#include <gdcMValueIO.h>
```

Static Public Member Functions

- static std::istream & [Read](#) (std::istream &is, [Value](#) &v)
- static const std::ostream & [Write](#) (std::ostream &os, const [Value](#) &v)

25.325.1 Detailed Description

```
template<typename TDE, typename TSwap, typename TType = uint8_t>class gdcM::ValueIO< TDE, TSwap, TType >
```

Class to dispatch template calls.

25.325.2 Member Function Documentation

25.325.2.1 template<typename TDE , typename TSwap , typename TType = uint8_t> static std::istream& gdcM::ValueIO< TDE, TSwap, TType >::Read (std::istream & is, [Value](#) & v) [static]

25.325.2.2 template<typename TDE , typename TSwap , typename TType = uint8_t> static const std::ostream& gdcM::ValueIO< TDE, TSwap, TType >::Write (std::ostream & os, const [Value](#) & v) [static]

The documentation for this class was generated from the following file:

- [gdcMValueIO.h](#)

25.326 gdcm::Version Class Reference

major/minor and build version

```
#include <gdcmVersion.h>
```

Public Member Functions

- [Version](#) ()
- [~Version](#) ()
- void [Print](#) (std::ostream &os=std::cout) const

Static Public Member Functions

- static int [GetBuildVersion](#) ()
- static int [GetMajorVersion](#) ()
- static int [GetMinorVersion](#) ()
- static const char * [GetVersion](#) ()

Friends

- std::ostream & [operator<<](#) (std::ostream &_os, const [Version](#) &v)

25.326.1 Detailed Description

major/minor and build version

25.326.2 Constructor & Destructor Documentation

25.326.2.1 `gdcm::Version::Version ()` [inline]

25.326.2.2 `gdcm::Version::~~Version ()` [inline]

25.326.3 Member Function Documentation

25.326.3.1 `static int gdcm::Version::GetBuildVersion ()` [static]

25.326.3.2 `static int gdcm::Version::GetMajorVersion ()` [static]

25.326.3.3 `static int gdcm::Version::GetMinorVersion ()` [static]

25.326.3.4 `static const char* gdcm::Version::GetVersion ()` [static]

25.326.3.5 `void gdcm::Version::Print (std::ostream & os = std::cout) const`

Referenced by `gdcm::operator<<()`.

25.326.4 Friends And Related Function Documentation

25.326.4.1 `std::ostream& operator<< (std::ostream & _os, const Version & v)` [*friend*]

The documentation for this class was generated from the following file:

- [gdcVersion.h](#)

25.327 gdc::VL Class Reference

Value Length.

```
#include <gdcVL.h>
```

Public Types

- typedef uint32_t [Type](#)

Public Member Functions

- [VL](#) (uint32_t vl=0)
- [VL GetLength](#) () const
- bool [IsOdd](#) () const
Return whether or not the [VL](#) is odd or not.
- bool [IsUndefined](#) () const
- [operator uint32_t](#) () const
- [VL & operator++](#) ()
- [VL operator++](#) (int)
- [VL & operator+=](#) ([VL](#) const &vl)
+= operator
- template<typename TSwap >
std::istream & [Read](#) (std::istream &is)
- template<typename TSwap >
std::istream & [Read16](#) (std::istream &is)
- void [SetToUndefined](#) ()
- template<typename TSwap >
const std::ostream & [Write](#) (std::ostream &os) const
- template<typename TSwap >
const std::ostream & [Write16](#) (std::ostream &os) const

Static Public Member Functions

- static uint16_t [GetVL16Max](#) ()
- static uint32_t [GetVL32Max](#) ()

Friends

- std::ostream & [operator<<](#) (std::ostream &os, const [VL](#) &vl)

25.327.1 Detailed Description

Value Length.

Warning

this is a 4bytes value ! Do not try to use it for 2bytes value length

Examples:

[rle2img.cxx](#).

25.327.2 Member Typedef Documentation

25.327.2.1 `typedef uint32_t gdcmm::VL::Type`

25.327.3 Constructor & Destructor Documentation

25.327.3.1 `gdcmm::VL::VL (uint32_t vl = 0) [inline]`

25.327.4 Member Function Documentation

25.327.4.1 `VL gdcmm::VL::GetLength () const [inline]`

Referenced by `gdcmm::FileMetaInformation::GetFullLength()`, `gdcmm::Fragment::GetLength()`, and `gdcmm::Item::Write()`.

25.327.4.2 `static uint16_t gdcmm::VL::GetVL16Max () [inline], [static]`

25.327.4.3 `static uint32_t gdcmm::VL::GetVL32Max () [inline], [static]`

25.327.4.4 `bool gdcmm::VL::IsOdd () const [inline]`

Return whether or not the [VL](#) is odd or not.

Referenced by `gdcmm::ByteValue::SetLength()`.

25.327.4.5 `bool gdcmm::VL::IsUndefined () const [inline]`

Referenced by `gdcmm::ByteValue::SetLength()`.

25.327.4.6 `gdcmm::VL::operator uint32_t () const [inline]`

25.327.4.7 `VL& gdcmm::VL::operator++ () [inline]`

25.327.4.8 `VL gdcmm::VL::operator++ (int) [inline]`

25.327.4.9 `VL& gdcmm::VL::operator+= (VL const & vl) [inline]`

`+=` operator

25.327.4.10 `template<typename TSwap > std::istream& gdcM::VL::Read (std::istream & is) [inline]`

25.327.4.11 `template<typename TSwap > std::istream& gdcM::VL::Read16 (std::istream & is) [inline]`

25.327.4.12 `void gdcM::VL::SetToUndefined () [inline]`

25.327.4.13 `template<typename TSwap > const std::ostream& gdcM::VL::Write (std::ostream & os) const [inline]`

Referenced by `gdcM::Fragment::Write()`, `gdcM::SequenceOfItems::Write()`, `gdcM::Item::Write()`, and `gdcM::SequenceOfFragments::Write()`.

25.327.4.14 `template<typename TSwap > const std::ostream& gdcM::VL::Write16 (std::ostream & os) const [inline]`

25.327.5 Friends And Related Function Documentation

25.327.5.1 `std::ostream& operator<< (std::ostream & os, const VL & vl) [friend]`

The documentation for this class was generated from the following file:

- [gdcMVL.h](#)

25.328 gdcM::VM Class Reference

Value Multiplicity Looking at the DICOMV3 dict only there is very few cases: 1 2 3 4 5 6 8 16 24 1-2 1-3 1-8 1-32 1-99 1-n 2-2n 2-n 3-3n 3-n.

```
#include <gdcMVM.h>
```

Public Types

- enum [VMType](#) {
 - [VM0](#) = 0,
 - [VM1](#) = 1,
 - [VM2](#) = 2,
 - [VM3](#) = 4,
 - [VM4](#) = 8,
 - [VM5](#) = 16,
 - [VM6](#) = 32,
 - [VM8](#) = 64,
 - [VM9](#) = 128,
 - [VM10](#) = 256,
 - [VM12](#) = 512,
 - [VM16](#) = 1024,
 - [VM18](#) = 2048,
 - [VM24](#) = 4096,
 - [VM28](#) = 8192,
 - [VM32](#) = 16384,
 - [VM35](#) = 32768,
 - [VM99](#) = 65536,
 - [VM256](#) = 131072,
 - [VM1_2](#) = VM1 | VM2,
 - [VM1_3](#) = VM1 | VM2 | VM3,
 - [VM1_4](#) = VM1 | VM2 | VM3 | VM4,
 - [VM1_5](#) = VM1 | VM2 | VM3 | VM4 | VM5,
 - [VM1_8](#) = VM1 | VM2 | VM3 | VM4 | VM5 | VM6 | VM8,
 - [VM1_32](#) = VM1 | VM2 | VM3 | VM4 | VM5 | VM6 | VM8 | VM9 | VM16 | VM24 | VM32,
 - [VM1_99](#) = VM1 | VM2 | VM3 | VM4 | VM5 | VM6 | VM8 | VM9 | VM16 | VM24 | VM32 | VM99,
 - [VM1_n](#) = VM1 | VM2 | VM3 | VM4 | VM5 | VM6 | VM8 | VM9 | VM16 | VM24 | VM32 | VM99 | VM256,
 - [VM2_2n](#) = VM2 | VM4 | VM6 | VM8 | VM16 | VM24 | VM32 | VM256,
 - [VM2_n](#) = VM2 | VM3 | VM4 | VM5 | VM6 | VM8 | VM9 | VM16 | VM24 | VM32 | VM99 | VM256,
 - [VM3_4](#) = VM3 | VM4,
 - [VM3_3n](#) = VM3 | VM6 | VM9 | VM24 | VM99 | VM256,
 - [VM3_n](#) = VM3 | VM4 | VM5 | VM6 | VM8 | VM9 | VM16 | VM24 | VM32 | VM99 | VM256,
 - [VM4_4n](#) = VM4 | VM16 | VM24 | VM32 | VM256,
 - [VM6_6n](#) = VM6 | VM12 | VM18 | VM24,
 - [VM7_7n](#),
 - [VM30_30n](#),
 - [VM47_47n](#),
 - [VM_END](#) = VM1_n + 1 }

Public Member Functions

- [VM](#) ([VMType](#) type=[VM0](#))
- bool [Compatible](#) ([VM](#) const &vm) const
- unsigned int [GetLength](#) () const
- operator [VMType](#) () const

Static Public Member Functions

- static unsigned int [GetNumberOfElementsFromArray](#) (const char *array, unsigned int length)

- static const char * [GetVMString](#) ([VMType](#) vm)
- static [VMType](#) [GetVMType](#) (const char *vm)
- static [VMType](#) [GetVMTypeFromLength](#) (unsigned int length, unsigned int size)
- static bool [IsValid](#) (int vm1, [VMType](#) vm2)

Static Protected Member Functions

- static unsigned int [GetIndex](#) ([VMType](#) vm)

Friends

- std::ostream & [operator<<](#) (std::ostream &os, const [VM](#) &vm)

25.328.1 Detailed Description

[Value](#) Multiplicity Looking at the DICOMV3 dict only there is very few cases: 1 2 3 4 5 6 8 16 24 1-2 1-3 1-8 1-32 1-99 1-n 2-2n 2-n 3-3n 3-n.

Some private dict define some more: 4-4n 1-4 1-5 256 9 3-4

even more:

7-7n 10 18 12 35 47_47n 30_30n 28

6-6n

25.328.2 Member Enumeration Documentation

25.328.2.1 enum `gdcm::VM::VMType`

Enumerator

VM0
VM1
VM2
VM3
VM4
VM5
VM6
VM8
VM9
VM10
VM12
VM16
VM18
VM24
VM28
VM32

VM35
VM99
VM256
VM1_2
VM1_3
VM1_4
VM1_5
VM1_8
VM1_32
VM1_99
VM1_n
VM2_2n
VM2_n
VM3_4
VM3_3n
VM3_n
VM4_4n
VM6_6n
VM7_7n
VM30_30n
VM47_47n
VM_END

25.328.3 Constructor & Destructor Documentation

25.328.3.1 `gdcm::VM::VM (VMType type = VM0) [inline]`

25.328.4 Member Function Documentation

25.328.4.1 `bool gdcm::VM::Compatible (VM const & vm) const`

WARNING: Implementation deficiency The Compatible function is poorly implemented, the reference vm should be coming from the dictionary, while the passed in value is the value guess from the file.

25.328.4.2 `static unsigned int gdcm::VM::GetIndex (VMType vm) [static], [protected]`

25.328.4.3 `unsigned int gdcm::VM::GetLength () const`

25.328.4.4 `static unsigned int gdcm::VM::GetNumberOfElementsFromArray (const char * array, unsigned int length) [static]`

25.328.4.5 `static const char* gdcm::VM::GetVMString (VMType vm) [static]`

Return the string as written in the official DICOM dict from a custom enum type

Referenced by `gdcm::operator<<()`.

25.328.4.6 `static VMType gdcM::VM::GetVMType (const char * vm) [static]`

25.328.4.7 `static VMType gdcM::VM::GetVMTypeFromLength (unsigned int length, unsigned int size) [static]`

25.328.4.8 `static bool gdcM::VM::IsValid (int vm1, VMType vm2) [static]`

Check if *vm1* is valid compare to *vm2*, i.e *vm1* is element of *vm2* *vm1* is typically deduce from counting in a ValueField

25.328.4.9 `gdcM::VM::operator VMType () const [inline]`

25.328.5 Friends And Related Function Documentation

25.328.5.1 `std::ostream& operator<< (std::ostream & os, const VM & vm) [friend]`

The documentation for this class was generated from the following file:

- [gdcMVM.h](#)

25.329 gdcM::VMToLength< T > Struct Template Reference

```
#include <gdcMVM.h>
```

The documentation for this struct was generated from the following file:

- [gdcMVM.h](#)

25.330 gdcM::VR Class Reference

VR class This is adapted from DICOM standard The biggest difference is the INVALID **VR** and the composite one that differ from standard (more like an addition) This allow us to represent all the possible case express in the DICOMV3 dict.

```
#include <gdcMVR.h>
```

Public Types

- enum [VRType](#) {
 - [INVALID](#) = 0,
 - [AE](#) = 1,
 - [AS](#) = 2,
 - [AT](#) = 4,
 - [CS](#) = 8,
 - [DA](#) = 16,
 - [DS](#) = 32,
 - [DT](#) = 64,
 - [FD](#) = 128,
 - [FL](#) = 256,
 - [IS](#) = 512,
 - [LO](#) = 1024,
 - [LT](#) = 2048,
 - [OB](#) = 4096,
 - [OF](#) = 8192,
 - [OW](#) = 16384,
 - [PN](#) = 32768,
 - [SH](#) = 65536,
 - [SL](#) = 131072,
 - [SQ](#) = 262144,
 - [SS](#) = 524288,
 - [ST](#) = 1048576,
 - [TM](#) = 2097152,
 - [UI](#) = 4194304,
 - [UL](#) = 8388608,
 - [UN](#) = 16777216,
 - [US](#) = 33554432,
 - [UT](#) = 67108864,
 - [OB_OW](#) = OB | OW,
 - [US_SS](#) = US | SS,
 - [US_SS_OW](#) = US | SS | OW,
 - [VL16](#) = AE | AS | AT | CS | DA | DS | DT | FD | FL | IS | LO | LT | PN | SH | SL | SS | ST | TM | UI | UL | US,
 - [VL32](#) = OB | OW | OF | SQ | UN | UT,
 - [VRASCII](#) = AE | AS | CS | DA | DS | DT | IS | LO | LT | PN | SH | ST | TM | UI | UT,
 - [VRBINARY](#) = AT | FL | FD | OB | OF | OW | SL | SQ | SS | UL | UN | US,
 - [VR_VM1](#) = AS | LT | ST | UT | SQ | OF | OW | OB | UN,
 - [VRALL](#) = VRASCII | VRBINARY,
 - [VR_END](#) = UT+1 }

Public Member Functions

- [VR](#) ([VRType](#) vr=[INVALID](#))
- bool [Compatible](#) ([VR](#) const &vr) const
- int [GetLength](#) () const
- unsigned int [GetSize](#) () const
- unsigned int [GetSizeof](#) () const
- bool [IsDual](#) () const
- bool [IsVRFile](#) () const
- [operator VRType](#) () const
- std::istream & [Read](#) (std::istream &is)

- `const std::ostream & Write (std::ostream &os) const`

Static Public Member Functions

- static `bool CanDisplay (VRType vr)`
- static `uint32_t GetLength (VRType vr)`
- static `const char * GetVRString (VRType vr)`
- static `const char * GetVRStringFromFile (VRType vr)`
- static `VRType GetVRType (const char *vr)`
- static `VRType GetVRTypeFromFile (const char *vr)`
- static `bool IsASCII (VRType vr)`
- static `bool IsASCII2 (VRType vr)`
- static `bool IsBinary (VRType vr)`
- static `bool IsBinary2 (VRType vr)`
- static `bool IsSwap (const char *vr)`
- static `bool IsValid (const char *vr)`
- static `bool IsValid (const char *vr1, VRType vr2)`

Friends

- `std::ostream & operator<< (std::ostream &os, const VR &vr)`

25.330.1 Detailed Description

VR class This is adapted from DICOM standard The biggest difference is the INVALID **VR** and the composite one that differ from standard (more like an addition) This allow us to represent all the possible case express in the DICOMV3 dict.

Note

VALUE REPRESENTATION (**VR**) Specifies the data type and format of the Value(s) contained in the **Value** Field of a Data **Element**. VALUE REPRESENTATION FIELD: The field where the **Value** Representation of a Data **Element** is stored in the encoding of a Data **Element** structure with explicit **VR**.

Examples:

[GenAllVR.cxx](#), and [GenFakeIdentifyFile.cxx](#).

25.330.2 Member Enumeration Documentation

25.330.2.1 `enum gdcm::VR::VRType`

Enumerator

INVALID
AE
AS
AT
CS
DA

DS
DT
FD
FL
IS
LO
LT
OB
OF
OW
PN
SH
SL
SQ
SS
ST
TM
UI
UL
UN
US
UT
OB_OW
US_SS
US_SS_OW
VL16
VL32
VRASCII
VRBINARY
VR_VM1
VRALL
VR_END

25.330.3 Constructor & Destructor Documentation

25.330.3.1 `gdcmm::VR::VR (VRType vr = INVALID) [inline]`

25.330.4 Member Function Documentation

25.330.4.1 `static bool gdcmm::VR::CanDisplay (VRType vr) [static]`

25.330.4.2 `bool gdcmm::VR::Compatible (VR const & vr) const`

25.330.4.3 `int gdcm::VR::GetLength () const [inline]`

25.330.4.4 `static uint32_t gdcm::VR::GetLength (VRType vr) [inline], [static]`

25.330.4.5 `unsigned int gdcm::VR::GetSize () const [inline]`

References AE, US_SS, and VRTypeTemplateCase.

25.330.4.6 `unsigned int gdcm::VR::GetSizeof () const`

25.330.4.7 `static const char* gdcm::VR::GetVRString (VRType vr) [static]`

Referenced by `gdcm::operator<<()`.

25.330.4.8 `static const char* gdcm::VR::GetVRStringFromFile (VRType vr) [static]`

25.330.4.9 `static VRType gdcm::VR::GetVRType (const char * vr) [static]`

25.330.4.10 `static VRType gdcm::VR::GetVRTypeFromFile (const char * vr) [static]`

25.330.4.11 `static bool gdcm::VR::IsASCII (VRType vr) [static]`

25.330.4.12 `static bool gdcm::VR::IsASCII2 (VRType vr) [static]`

25.330.4.13 `static bool gdcm::VR::IsBinary (VRType vr) [static]`

25.330.4.14 `static bool gdcm::VR::IsBinary2 (VRType vr) [static]`

25.330.4.15 `bool gdcm::VR::IsDual () const`

25.330.4.16 `static bool gdcm::VR::IsSwap (const char * vr) [static]`

25.330.4.17 `static bool gdcm::VR::IsValid (const char * vr) [static]`

25.330.4.18 `static bool gdcm::VR::IsValid (const char * vr1, VRType vr2) [static]`

25.330.4.19 `bool gdcm::VR::IsVRFile () const`

Referenced by `gdcm::DataElement::SetVR()`.

25.330.4.20 `gdcm::VR::operator VRType () const [inline]`

25.330.4.21 `std::istream& gdcm::VR::Read (std::istream & is) [inline]`

References `gdcmDebugMacro`, `INVALID`, and `VR_END`.

25.330.4.22 `const std::ostream& gdcm::VR::Write (std::ostream & os) const [inline]`

References `gdcmAssertAlwaysMacro`, and `INVALID`.

25.330.5 Friends And Related Function Documentation

25.330.5.1 `std::ostream& operator<< (std::ostream & os, const VR & vr)` [friend]

The documentation for this class was generated from the following file:


- [gdcmVR.h](#)

25.331 gdcm::VR16ExplicitDataElement Class Reference


Class to read/write a [DataElement](#) as Explicit Data [Element](#).

```
#include <gdcmVR16ExplicitDataElement.h>
```

Inheritance diagram for gdcm::VR16ExplicitDataElement:



Collaboration diagram for `gdcm::VR16ExplicitDataElement`:



Public Member Functions

- [VL GetLength](#) () const
- template<typename TSwap >
std::istream & [Read](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadPreValue](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadValue](#) (std::istream &is)
- template<typename TSwap >
std::istream & [ReadWithLength](#) (std::istream &is, [VL](#) &length)

Additional Inherited Members

25.331.1 Detailed Description

Class to read/write a [DataElement](#) as Explicit Data [Element](#).

Note

This class support 16 bits when finding an unkown [VR](#): For instance: Siemens_CT_Sensation64_has_VR_RT.dcm

25.331.2 Member Function Documentation

25.331.2.1 VL `gdcm::VR16ExplicitDataElement::GetLength` () const

25.331.2.2 `template<typename TSwap > std::istream& gdcm::VR16ExplicitDataElement::Read (std::istream & is)`

25.331.2.3 `template<typename TSwap > std::istream& gdcm::VR16ExplicitDataElement::ReadPreValue (std::istream & is)`

25.331.2.4 `template<typename TSwap > std::istream& gdcm::VR16ExplicitDataElement::ReadValue (std::istream & is)`

25.331.2.5 `template<typename TSwap > std::istream& gdcm::VR16ExplicitDataElement::ReadWithLength (std::istream & is, VL & length)`

The documentation for this class was generated from the following file:

- [gdcmVR16ExplicitDataElement.h](#)

25.332 gdcm::VRToEncoding< T > Struct Template Reference

```
#include <gdcmVR.h>
```


The documentation for this struct was generated from the following file:

- [gdcmVR.h](#)

25.333 gdcm::VRToType< T > Struct Template Reference

```
#include <gdcmVR.h>
```

Inheritance diagram for gdcm::VRToType< T >:



25.333.1 Detailed Description

```
template<int T>struct gdcm::VRToType< T >
```

Examples:

[DumpGEMSMovieGroup.cxx.](#)

The documentation for this struct was generated from the following file:

- [gdcmVR.h](#)

25.334 `gdcm::VRVLSize< T >` Class Template Reference

```
#include <gdcmAttribute.h>
```

The documentation for this class was generated from the following file:

- [gdcmAttribute.h](#)

25.335 `gdcm::VRVLSize< 0 >` Class Template Reference

```
#include <gdcmAttribute.h>
```

Static Public Member Functions

- static uint16_t [Read](#) (std::istream &_is)
- static void [Write](#) (std::ostream &os)

25.335.1 Member Function Documentation

25.335.1.1 static uint16_t `gdcm::VRVLSize< 0 >::Read (std::istream &_is)` [inline], [static]

25.335.1.2 static void `gdcm::VRVLSize< 0 >::Write (std::ostream &os)` [inline], [static]

The documentation for this class was generated from the following file:

- [gdcmAttribute.h](#)

25.336 `gdcm::VRVLSize< 1 >` Class Template Reference

```
#include <gdcmAttribute.h>
```

Static Public Member Functions

- static uint32_t [Read](#) (std::istream &_is)
- static void [Write](#) (std::ostream &os)

25.336.1 Member Function Documentation

25.336.1.1 static uint32_t `gdcm::VRVLSize< 1 >::Read (std::istream &_is)` [inline], [static]

25.336.1.2 static void `gdcm::VRVLSize< 1 >::Write (std::ostream &os)` [inline], [static]


The documentation for this class was generated from the following file:

- [gdcmAttribute.h](#)


25.337 vtkGDCMImageReader Class Reference

```
#include <vtkGDCMImageReader.h>
```

Inheritance diagram for vtkGDCMImageReader:



Collaboration diagram for vtkGDCMImageReader:



Public Member Functions

- virtual int [CanReadFile](#) (const char *fname)
- virtual const char * [GetDescriptiveName](#) ()
- virtual const char * [GetFileExtensions](#) ()
- vtkImageData * [GetIconImage](#) ()

- vtkImageData * [GetOverlay](#) (int i)
- virtual void [PrintSelf](#) (ostream &os, vtkIndent indent)
- virtual void [SetCurve](#) (vtkPolyData *pd)
- virtual void [SetFileNames](#) (vtkStringArray *)
- virtual void [SetMedicalImageProperties](#) (vtkMedicalImageProperties *pd)
- [vtkBooleanMacro](#) (LoadOverlays, int)
- [vtkBooleanMacro](#) (LoadIconImage, int)
- [vtkBooleanMacro](#) (LossyFlag, int)
- [vtkBooleanMacro](#) (ApplyLookupTable, int)
- int [vtkBooleanMacro](#) (ApplyYBRToRGB, int)
- [vtkGetMacro](#) (LoadOverlays, int)
- [vtkGetMacro](#) (LoadIconImage, int)
- [vtkGetMacro](#) (LossyFlag, int)
- [vtkGetMacro](#) (NumberOfOverlays, int)
- [vtkGetMacro](#) (NumberOfIconImages, int)
- [vtkGetMacro](#) (ApplyLookupTable, int)
- [vtkGetMacro](#) (ApplyYBRToRGB, int) [vtkSetMacro](#)(ApplyYBRToRGB
- [vtkGetMacro](#) (ImageFormat, int)
- [vtkGetMacro](#) (PlanarConfiguration, int)
- [vtkGetMacro](#) (Shift, double)
- [vtkGetMacro](#) (Scale, double)
- [vtkGetObjectMacro](#) (DirectionCosines, vtkMatrix4x4)
- [vtkGetObjectMacro](#) (MedicalImageProperties, vtkMedicalImageProperties)
- [vtkGetObjectMacro](#) (FileNames, vtkStringArray)
- [vtkGetObjectMacro](#) (Curve, vtkPolyData)
- [vtkGetVector3Macro](#) (ImagePositionPatient, double)
- [vtkGetVector6Macro](#) (ImageOrientationPatient, double)
- [vtkSetMacro](#) (LoadOverlays, int)
- [vtkSetMacro](#) (LoadIconImage, int)
- [vtkSetMacro](#) (LossyFlag, int)
- [vtkSetMacro](#) (ApplyLookupTable, int)
- [vtkTypeRevisionMacro](#) (vtkGDCMImageReader, vtkMedicalImageReader2)

Static Public Member Functions

- static [vtkGDCMImageReader](#) * [New](#) ()

Protected Member Functions

- [vtkGDCMImageReader](#) ()
- [~vtkGDCMImageReader](#) ()
- void [ExecuteData](#) (vtkDataObject *out)
- void [ExecuteInformation](#) ()
- void [FillMedicalImageInformation](#) (const [gdcmm::ImageReader](#) &reader)
- int [LoadSingleFile](#) (const char *filename, char *pointer, unsigned long &outlen)
- int [RequestDataCompat](#) ()
- int [RequestInformationCompat](#) ()
- void [SetFilePattern](#) (const char *)
- void [SetFilePrefix](#) (const char *)
- [vtkGetStringMacro](#) (FilePrefix)
- [vtkGetStringMacro](#) (FilePattern)
- [vtkSetVector6Macro](#) (ImageOrientationPatient, double)

Protected Attributes

- int [ApplyInverseVideo](#)
- int [ApplyLookupTable](#)
- int [ApplyPlanarConfiguration](#)
- int [ApplyShiftScale](#)
- int [ApplyYBRToRGB](#)
- vtkPolyData * [Curve](#)
- vtkMatrix4x4 * [DirectionCosines](#)
- vtkStringArray * [FileNames](#)
- int [ForceRescale](#)
- int [IconDataScalarType](#)
- int [IconImageDataExtent](#) [6]
- int [IconNumberOfScalarComponents](#)
- int [ImageFormat](#)
- double [ImageOrientationPatient](#) [6]
- double [ImagePositionPatient](#) [3]
- int [LoadIconImage](#)
- int [LoadOverlays](#)
- int [LossyFlag](#)
- vtkMedicalImageProperties * [MedicalImageProperties](#)
- int [NumberOfIconImages](#)
- int [NumberOfOverlays](#)
- int [PlanarConfiguration](#)
- double [Scale](#)
- double [Shift](#)

25.337.1 Detailed Description

Examples:

[AWTMedical3.java](#), [Convert16BitsTo8Bits.cxx](#), [ConvertMultiFrameToSingleFrame.cxx](#), [ConvertRGBToLuminance.cxx](#), [ConvertSingleBitTo8Bits.cxx](#), [gdcmmorthoplanes.cxx](#), [gdcmmreslice.cxx](#), [gdcmmtexture.cxx](#), [gdcmmvolume.cxx](#), [HelloActiviz.cs](#), [HelloActiviz2.cs](#), [HelloActiviz3.cs](#), [HelloActiviz4.cs](#), [HelloActiviz5.cs](#), [HelloVTKWorld.cs](#), [HelloVTKWorld.java](#), [MagnifyFile.cxx](#), [MetaImageMD5Activiz.cs](#), [MIPViewer.java](#), [MPRViewer.java](#), [MPRViewer2.java](#), [offscreenimage.cxx](#), [ReadSeriesIntoVTK.java](#), [RefCounting.cs](#), and [reslicesphere.cxx](#).

25.337.2 Constructor & Destructor Documentation

25.337.2.1 `vtkGDCMImageReader::vtkGDCMImageReader ()` [protected]

Examples:

[HelloActiviz2.cs](#).

25.337.2.2 `vtkGDCMImageReader::~~vtkGDCMImageReader ()` [protected]

25.337.3 Member Function Documentation

25.337.3.1 `virtual int vtkGDCMImageReader::CanReadFile (const char * fname)` [virtual]

Examples:

[MetalImageMD5Activiz.cs](#).

25.337.3.2 `void vtkGDCMImageReader::ExecuteData (vtkDataObject * out)` [protected]

25.337.3.3 `void vtkGDCMImageReader::ExecuteInformation ()` [protected]

25.337.3.4 `void vtkGDCMImageReader::FillMedicalImageInformation (const gdcm::ImageReader & reader)`
[protected]

25.337.3.5 `virtual const char* vtkGDCMImageReader::GetDescriptiveName ()` [inline],[virtual]

25.337.3.6 `virtual const char* vtkGDCMImageReader::GetFileExtensions ()` [inline],[virtual]

25.337.3.7 `vtkImageData* vtkGDCMImageReader::GetIconImage ()`

25.337.3.8 `vtkImageData* vtkGDCMImageReader::GetOverlay (int i)`

25.337.3.9 `int vtkGDCMImageReader::LoadSingleFile (const char * filename, char * pointer, unsigned long & outlen)`
[protected]

25.337.3.10 `static vtkGDCMImageReader* vtkGDCMImageReader::New ()` [static]

Examples:

[Convert16BitsTo8Bits.cxx](#), [ConvertMultiFrameToSingleFrame.cxx](#), [ConvertRGBToLuminance.cxx](#), [ConvertSingle-BitTo8Bits.cxx](#), [gdcmorthoplanes.cxx](#), [gdcmreslice.cxx](#), [gdcmtexture.cxx](#), [gdcmvolume.cxx](#), [HelloActiviz.cs](#), [Hello-Activiz3.cs](#), [HelloActiviz4.cs](#), [HelloActiviz5.cs](#), [HelloVTKWorld.cs](#), [MagnifyFile.cxx](#), [MetalImageMD5Activiz.cs](#), [offscreenimage.cxx](#), [RefCounting.cs](#), and [reslicesphere.cxx](#).

25.337.3.11 `virtual void vtkGDCMImageReader::PrintSelf (ostream & os, vtkIndent indent)` [virtual]

Reimplemented in [vtkGDCMThreadedImageReader](#).

25.337.3.12 `int vtkGDCMImageReader::RequestDataCompat ()` [protected]

25.337.3.13 `int vtkGDCMImageReader::RequestInformationCompat ()` [protected]

25.337.3.14 `virtual void vtkGDCMImageReader::SetCurve (vtkPolyData * pd)` [virtual]

25.337.3.15 `virtual void vtkGDCMImageReader::SetFileNames (vtkStringArray *)` [virtual]

Examples:

[gdcmortoplanes.cxx](#), [HelloActiviz3.cs](#), [HelloActiviz4.cs](#), [HelloActiviz5.cs](#), [MIPViewer.java](#), [MPRViewer.java](#), [MPRViewer2.java](#), and [ReadSeriesIntoVTK.java](#).

25.337.3.16 `void vtkGDCMImageReader::SetFilePattern (const char *)` [inline],[protected]

25.337.3.17 `void vtkGDCMImageReader::SetFilePrefix (const char *)` [inline],[protected]

25.337.3.18 `virtual void vtkGDCMImageReader::SetMedicalImageProperties (vtkMedicalImageProperties * pd)` [virtual]

25.337.3.19 `vtkGDCMImageReader::vtkBooleanMacro (LoadOverlays , int)`

25.337.3.20 `vtkGDCMImageReader::vtkBooleanMacro (LoadIconImage , int)`

25.337.3.21 `vtkGDCMImageReader::vtkBooleanMacro (LossyFlag , int)`

25.337.3.22 `vtkGDCMImageReader::vtkBooleanMacro (ApplyLookupTable , int)`

25.337.3.23 `int vtkGDCMImageReader::vtkBooleanMacro (ApplyYBRToRGB , int)`

25.337.3.24 `vtkGDCMImageReader::vtkGetMacro (LoadOverlays , int)`

25.337.3.25 `vtkGDCMImageReader::vtkGetMacro (LoadIconImage , int)`

25.337.3.26 `vtkGDCMImageReader::vtkGetMacro (LossyFlag , int)`

25.337.3.27 `vtkGDCMImageReader::vtkGetMacro (NumberOfOverlays , int)`

25.337.3.28 `vtkGDCMImageReader::vtkGetMacro (NumberOfIconImages , int)`

25.337.3.29 `vtkGDCMImageReader::vtkGetMacro (ApplyLookupTable , int)`

25.337.3.30 `vtkGDCMImageReader::vtkGetMacro (ApplyYBRToRGB , int)`

25.337.3.31 `vtkGDCMImageReader::vtkGetMacro (ImageFormat , int)`

25.337.3.32 `vtkGDCMImageReader::vtkGetMacro (PlanarConfiguration , int)`

25.337.3.33 `vtkGDCMImageReader::vtkGetMacro (Shift , double)`

25.337.3.34 `vtkGDCMImageReader::vtkGetMacro (Scale , double)`

25.337.3.35 `vtkGDCMImageReader::vtkGetObjectMacro (DirectionCosines , vtkMatrix4x4)`

25.337.3.36 `vtkGDCMImageReader::vtkGetObjectMacro (MedicalImageProperties , vtkMedicalImageProperties)`

25.337.3.37 `vtkGDCMImageReader::vtkGetObjectMacro (FileNames , vtkStringArray)`

- 25.337.3.38 `vtkGDCMImageReader::vtkGetObjectMacro (Curve , vtkPolyData)`
- 25.337.3.39 `vtkGDCMImageReader::vtkGetStringMacro (FilePrefix)` [protected]
- 25.337.3.40 `vtkGDCMImageReader::vtkGetStringMacro (FilePattern)` [protected]
- 25.337.3.41 `vtkGDCMImageReader::vtkGetVector3Macro (ImagePositionPatient , double)`
- 25.337.3.42 `vtkGDCMImageReader::vtkGetVector6Macro (ImageOrientationPatient , double)`
- 25.337.3.43 `vtkGDCMImageReader::vtkSetMacro (LoadOverlays , int)`
- 25.337.3.44 `vtkGDCMImageReader::vtkSetMacro (LoadIconImage , int)`
- 25.337.3.45 `vtkGDCMImageReader::vtkSetMacro (LossyFlag , int)`
- 25.337.3.46 `vtkGDCMImageReader::vtkSetMacro (ApplyLookupTable , int)`
- 25.337.3.47 `vtkGDCMImageReader::vtkSetVector6Macro (ImageOrientationPatient , double)` [protected]
- 25.337.3.48 `vtkGDCMImageReader::vtkTypeRevisionMacro (vtkGDCMImageReader , vtkMedicalImageReader2)`

25.337.4 Member Data Documentation

- 25.337.4.1 `int vtkGDCMImageReader::ApplyInverseVideo` [protected]
- 25.337.4.2 `int vtkGDCMImageReader::ApplyLookupTable` [protected]
- 25.337.4.3 `int vtkGDCMImageReader::ApplyPlanarConfiguration` [protected]
- 25.337.4.4 `int vtkGDCMImageReader::ApplyShiftScale` [protected]
- 25.337.4.5 `int vtkGDCMImageReader::ApplyYBRToRGB` [protected]
- 25.337.4.6 `vtkPolyData* vtkGDCMImageReader::Curve` [protected]
- 25.337.4.7 `vtkMatrix4x4* vtkGDCMImageReader::DirectionCosines` [protected]
- 25.337.4.8 `vtkStringArray* vtkGDCMImageReader::FileNames` [protected]
- 25.337.4.9 `int vtkGDCMImageReader::ForceRescale` [protected]
- 25.337.4.10 `int vtkGDCMImageReader::IconDataScalarType` [protected]
- 25.337.4.11 `int vtkGDCMImageReader::IconImageDataExtent[6]` [protected]
- 25.337.4.12 `int vtkGDCMImageReader::IconNumberOfScalarComponents` [protected]
- 25.337.4.13 `int vtkGDCMImageReader::ImageFormat` [protected]
- 25.337.4.14 `double vtkGDCMImageReader::ImageOrientationPatient[6]` [protected]

- 25.337.4.15 `double vtkGDCMImageReader::ImagePositionPatient[3]` [protected]
- 25.337.4.16 `int vtkGDCMImageReader::LoadIconImage` [protected]
- 25.337.4.17 `int vtkGDCMImageReader::LoadOverlays` [protected]
- 25.337.4.18 `int vtkGDCMImageReader::LossyFlag` [protected]
- 25.337.4.19 `vtkMedicalImageProperties* vtkGDCMImageReader::MedicalImageProperties` [protected]
- 25.337.4.20 `int vtkGDCMImageReader::NumberOfIconImages` [protected]
- 25.337.4.21 `int vtkGDCMImageReader::NumberOfOverlays` [protected]
- 25.337.4.22 `int vtkGDCMImageReader::PlanarConfiguration` [protected]
- 25.337.4.23 `double vtkGDCMImageReader::Scale` [protected]
- 25.337.4.24 `double vtkGDCMImageReader::Shift` [protected]


The documentation for this class was generated from the following file:

- [vtkGDCMImageReader.h](#)


25.338 vtkGDCMImageWriter Class Reference

```
#include <vtkGDCMImageWriter.h>
```

Inheritance diagram for vtkGDCMImageWriter:



Collaboration diagram for vtkGDCMImageWriter:



Public Types

- enum `CompressionTypes` {
`NO_COMPRESSION` = 0,
`JPEG_COMPRESSION`,
`JPEG2000_COMPRESSION`,
`JPEGLS_COMPRESSION`,
`RLE_COMPRESSION` }

Public Member Functions

- virtual const char * `GetDescriptiveName` ()
- virtual const char * `GetFileExtensions` ()
- virtual void `PrintSelf` (ostream &os, vtkIndent indent)
- virtual void `SetDirectionCosines` (vtkMatrix4x4 *matrix)
- virtual void `SetDirectionCosinesFromImageOrientationPatient` (const double dircos[6])
- virtual void `SetFileNames` (vtkStringArray *)
- virtual void `SetMedicalImageProperties` (vtkMedicalImageProperties *)
- `vtkBooleanMacro` (LossyFlag, int)
- `vtkBooleanMacro` (FileLowerLeft, int)
- `vtkGetMacro` (LossyFlag, int)
- `vtkGetMacro` (Shift, double)
- `vtkGetMacro` (Scale, double)
- `vtkGetMacro` (ImageFormat, int)
- `vtkGetMacro` (FileLowerLeft, int)
- `vtkGetMacro` (PlanarConfiguration, int)
- `vtkGetMacro` (CompressionType, int)
- `vtkGetObjectMacro` (MedicalImageProperties, vtkMedicalImageProperties)
- `vtkGetObjectMacro` (FileNames, vtkStringArray)
- `vtkGetObjectMacro` (DirectionCosines, vtkMatrix4x4)
- `vtkGetStringMacro` (StudyUID)
- `vtkGetStringMacro` (SeriesUID)
- `vtkSetMacro` (LossyFlag, int)
- `vtkSetMacro` (Shift, double)

- [vtkSetMacro](#) (Scale, double)
- [vtkSetMacro](#) (ImageFormat, int)
- [vtkSetMacro](#) (FileLowerLeft, int)
- [vtkSetMacro](#) (PlanarConfiguration, int)
- [vtkSetMacro](#) (CompressionType, int)
- [vtkSetStringMacro](#) (StudyUID)
- [vtkSetStringMacro](#) (SeriesUID)
- [vtkTypeRevisionMacro](#) ([vtkGDCMImageWriter](#), [vtkImageWriter](#))
- virtual void [Write](#) ()

Static Public Member Functions

- static [vtkGDCMImageWriter](#) * [New](#) ()

Protected Member Functions

- [vtkGDCMImageWriter](#) ()
- [~vtkGDCMImageWriter](#) ()
- virtual char * [GetFileName](#) ()
- int [WriteGDCMData](#) (vtkImageData *data, int timeStep)
- void [WriteSlice](#) (vtkImageData *data)

25.338.1 Detailed Description

Examples:

[Convert16BitsTo8Bits.cxx](#), [ConvertMultiFrameToSingleFrame.cxx](#), [ConvertRGBToLuminance.cxx](#), [ConvertSingleBitTo8Bits.cxx](#), [gdcmmorthoplanes.cxx](#), [HelloActiviz.cs](#), [HelloActiviz2.cs](#), [HelloVTKWorld.cs](#), [HelloVTKWorld.java](#), [HelloVTKWorld2.cs](#), [MagnifyFile.cxx](#), and [RefCounting.cs](#).

25.338.2 Member Enumeration Documentation

25.338.2.1 enum [vtkGDCMImageWriter::CompressionTypes](#)

Enumerator

NO_COMPRESSION
JPEG_COMPRESSION
JPEG2000_COMPRESSION
JPEGLS_COMPRESSION
RLE_COMPRESSION

25.338.3 Constructor & Destructor Documentation

25.338.3.1 [vtkGDCMImageWriter::vtkGDCMImageWriter](#) () [protected]

25.338.3.2 [vtkGDCMImageWriter::~~vtkGDCMImageWriter](#) () [protected]

25.338.4 Member Function Documentation

25.338.4.1 `virtual const char* vtkGDCMImageWriter::GetDescriptiveName ()` [inline],[virtual]

25.338.4.2 `virtual const char* vtkGDCMImageWriter::GetFileExtensions ()` [inline],[virtual]

25.338.4.3 `virtual char* vtkGDCMImageWriter::GetFileName ()` [protected],[virtual]

25.338.4.4 `static vtkGDCMImageWriter* vtkGDCMImageWriter::New ()` [static]

Examples:

[Convert16BitsTo8Bits.cxx](#), [ConvertMultiFrameToSingleFrame.cxx](#), [ConvertRGBToLuminance.cxx](#), [ConvertSingleBitTo8Bits.cxx](#), [gdcmorphoplanes.cxx](#), [HelloActiviz.cs](#), [HelloVTKWorld.cs](#), [HelloVTKWorld2.cs](#), [MagnifyFile.cxx](#), and [RefCounting.cs](#).

25.338.4.5 `virtual void vtkGDCMImageWriter::PrintSelf (ostream & os, vtkIndent indent)` [virtual]

25.338.4.6 `virtual void vtkGDCMImageWriter::SetDirectionCosines (vtkMatrix4x4 * matrix)` [virtual]

Examples:

[Convert16BitsTo8Bits.cxx](#), [ConvertRGBToLuminance.cxx](#), [ConvertSingleBitTo8Bits.cxx](#), [gdcmorphoplanes.cxx](#), [HelloActiviz2.cs](#), [HelloVTKWorld.cs](#), [HelloVTKWorld.java](#), and [MagnifyFile.cxx](#).

25.338.4.7 `virtual void vtkGDCMImageWriter::SetDirectionCosinesFromImageOrientationPatient (const double dircos[6])` [virtual]

25.338.4.8 `virtual void vtkGDCMImageWriter::SetFileNames (vtkStringArray *)` [virtual]

Examples:

[ConvertMultiFrameToSingleFrame.cxx](#).

25.338.4.9 `virtual void vtkGDCMImageWriter::SetMedicalImageProperties (vtkMedicalImageProperties *)` [virtual]

Examples:

[Convert16BitsTo8Bits.cxx](#), [ConvertRGBToLuminance.cxx](#), [ConvertSingleBitTo8Bits.cxx](#), [gdcmorphoplanes.cxx](#), [HelloActiviz.cs](#), [HelloActiviz2.cs](#), [HelloVTKWorld.cs](#), [HelloVTKWorld.java](#), and [MagnifyFile.cxx](#).

25.338.4.10 `vtkGDCMImageWriter::vtkBooleanMacro (LossyFlag , int)`

25.338.4.11 `vtkGDCMImageWriter::vtkBooleanMacro (FileLowerLeft , int)`

25.338.4.12 `vtkGDCMImageWriter::vtkGetMacro (LossyFlag , int)`

25.338.4.13 `vtkGDCMImageWriter::vtkGetMacro (Shift , double)`

25.338.4.14 `vtkGDCMImageWriter::vtkGetMacro (Scale , double)`

- 25.338.4.15 `vtkGDCMImageWriter::vtkGetMacro (ImageFormat , int)`
- 25.338.4.16 `vtkGDCMImageWriter::vtkGetMacro (FileLowerLeft , int)`
- 25.338.4.17 `vtkGDCMImageWriter::vtkGetMacro (PlanarConfiguration , int)`
- 25.338.4.18 `vtkGDCMImageWriter::vtkGetMacro (CompressionType , int)`
- 25.338.4.19 `vtkGDCMImageWriter::vtkGetObjectMacro (MedicalImageProperties , vtkMedicalImageProperties)`
- 25.338.4.20 `vtkGDCMImageWriter::vtkGetObjectMacro (FileNames , vtkStringArray)`
- 25.338.4.21 `vtkGDCMImageWriter::vtkGetObjectMacro (DirectionCosines , vtkMatrix4x4)`
- 25.338.4.22 `vtkGDCMImageWriter::vtkGetStringMacro (StudyUID)`
- 25.338.4.23 `vtkGDCMImageWriter::vtkGetStringMacro (SeriesUID)`
- 25.338.4.24 `vtkGDCMImageWriter::vtkSetMacro (LossyFlag , int)`
- 25.338.4.25 `vtkGDCMImageWriter::vtkSetMacro (Shift , double)`
- 25.338.4.26 `vtkGDCMImageWriter::vtkSetMacro (Scale , double)`
- 25.338.4.27 `vtkGDCMImageWriter::vtkSetMacro (ImageFormat , int)`
- 25.338.4.28 `vtkGDCMImageWriter::vtkSetMacro (FileLowerLeft , int)`
- 25.338.4.29 `vtkGDCMImageWriter::vtkSetMacro (PlanarConfiguration , int)`
- 25.338.4.30 `vtkGDCMImageWriter::vtkSetMacro (CompressionType , int)`
- 25.338.4.31 `vtkGDCMImageWriter::vtkSetStringMacro (StudyUID)`
- 25.338.4.32 `vtkGDCMImageWriter::vtkSetStringMacro (SeriesUID)`
- 25.338.4.33 `vtkGDCMImageWriter::vtkTypeRevisionMacro (vtkGDCMImageWriter , vtkImageWriter)`
- 25.338.4.34 `virtual void vtkGDCMImageWriter::Write () [virtual]`

Examples:

[Convert16BitsTo8Bits.cxx](#), [ConvertMultiFrameToSingleFrame.cxx](#), [ConvertRGBToLuminance.cxx](#), [ConvertSingle-BitTo8Bits.cxx](#), [gdcmorthoplanes.cxx](#), [HelloActiviz.cs](#), [HelloActiviz2.cs](#), [HelloVTKWorld.cs](#), [HelloVTKWorld.java](#), [HelloVTKWorld2.cs](#), and [MagnifyFile.cxx](#).

- 25.338.4.35 `int vtkGDCMImageWriter::WriteGDCMData (vtkImageData * data , int timeStep) [protected]`
- 25.338.4.36 `void vtkGDCMImageWriter::WriteSlice (vtkImageData * data) [protected]`


The documentation for this class was generated from the following file:

- [vtkGDCMImageWriter.h](#)


25.339 vtkGDCMMedicalImageProperties Class Reference

```
#include <vtkGDCMMedicalImageProperties.h>
```

Inheritance diagram for vtkGDCMMedicalImageProperties:



Collaboration diagram for vtkGDCMMedicalImageProperties:



Public Member Functions

- virtual void [Clear](#) ()
- void [PrintSelf](#) (ostream &os, vtkIndent indent)
- [vtkTypeRevisionMacro](#) ([vtkGDCMMedicalImageProperties](#), vtkMedicalImageProperties)

Static Public Member Functions

- static
[vtkGDCMMedicalImageProperties * New](#) ()

Protected Member Functions

- [vtkGDCMMedicalImageProperties](#) ()
- [~vtkGDCMMedicalImageProperties](#) ()
- [gdcmm::File](#) const & [GetFile](#) (unsigned int t)
- void [PushBackFile](#) ([gdcmm::File](#) const &f)

Friends

- class [vtkGDCMImageReader](#)
- class [vtkGDCMImageWriter](#)

25.339.1 Constructor & Destructor Documentation

25.339.1.1 [vtkGDCMMedicalImageProperties::vtkGDCMMedicalImageProperties](#) () [protected]

25.339.1.2 [vtkGDCMMedicalImageProperties::~~vtkGDCMMedicalImageProperties](#) () [protected]

25.339.2 Member Function Documentation

25.339.2.1 virtual void [vtkGDCMMedicalImageProperties::Clear](#) () [virtual]

25.339.2.2 [gdcmm::File](#) const& [vtkGDCMMedicalImageProperties::GetFile](#) (unsigned int t) [protected]

25.339.2.3 static [vtkGDCMMedicalImageProperties*](#) [vtkGDCMMedicalImageProperties::New](#) () [static]

25.339.2.4 void [vtkGDCMMedicalImageProperties::PrintSelf](#) (ostream & os, vtkIndent indent)

25.339.2.5 void [vtkGDCMMedicalImageProperties::PushBackFile](#) ([gdcmm::File](#) const & f) [protected]

25.339.2.6 [vtkGDCMMedicalImageProperties::vtkTypeRevisionMacro](#) ([vtkGDCMMedicalImageProperties](#) , [vtkMedicalImageProperties](#))

25.339.3 Friends And Related Function Documentation

25.339.3.1 friend class [vtkGDCMImageReader](#) [friend]

25.339.3.2 friend class [vtkGDCMImageWriter](#) [friend]


The documentation for this class was generated from the following file:

- [vtkGDCMMedicalImageProperties.h](#)


25.340 vtkGDCMPolyDataReader Class Reference

```
#include <vtkGDCMPolyDataReader.h>
```

Inheritance diagram for vtkGDCMPolyDataReader:



Collaboration diagram for vtkGDCMPolyDataReader:



Public Member Functions

- virtual void [PrintSelf](#) (ostream &os, vtkIndent indent)
- [vtkGetObjectMacro](#) ([MedicalImageProperties](#), vtkMedicalImageProperties)
- [vtkGetObjectMacro](#) ([RTStructSetProperties](#), [vtkRTStructSetProperties](#))
- [vtkGetStringMacro](#) ([FileName](#))
- [vtkSetStringMacro](#) ([FileName](#))
- [vtkTypeRevisionMacro](#) ([vtkGDCMPolyDataReader](#), vtkPolyDataAlgorithm)

Static Public Member Functions

- static [vtkGDCMPolyDataReader](#) * [New](#) ()

Protected Member Functions

- [vtkGDCMPolyDataReader \(\)](#)
- [~vtkGDCMPolyDataReader \(\)](#)
- void [FillMedicalImageInformation](#) (const [gdcmm::Reader](#) &reader)
- int [RequestData](#) (vtkInformation *, vtkInformationVector **, vtkInformationVector *)
- int [RequestData_HemodynamicWaveformStorage](#) ([gdcmm::Reader](#) const &reader, vtkInformationVector *outputVector)
- int [RequestData_RTStructureSetStorage](#) ([gdcmm::Reader](#) const &reader, vtkInformationVector *outputVector)
- int [RequestInformation](#) (vtkInformation *vtkNotUsed(request), vtkInformationVector **vtkNotUsed(inputVector), vtkInformationVector *outputVector)
- int [RequestInformation_HemodynamicWaveformStorage](#) ([gdcmm::Reader](#) const &reader)
- int [RequestInformation_RTStructureSetStorage](#) ([gdcmm::Reader](#) const &reader)

Protected Attributes

- char * [FileName](#)
- vtkMedicalImageProperties * [MedicalImageProperties](#)
- [vtkRTStructSetProperties](#) * [RTStructSetProperties](#)

25.340.1 Detailed Description

Examples:

[gdcmscene.cxx](#), [GenerateRTSTRUCT.cxx](#), and [rtstructapp.cxx](#).

25.340.2 Constructor & Destructor Documentation

25.340.2.1 `vtkGDCMPolyDataReader::vtkGDCMPolyDataReader ()` [protected]

25.340.2.2 `vtkGDCMPolyDataReader::~~vtkGDCMPolyDataReader ()` [protected]

25.340.3 Member Function Documentation

25.340.3.1 `void vtkGDCMPolyDataReader::FillMedicalImageInformation (const gdcmm::Reader & reader)` [protected]

25.340.3.2 `static vtkGDCMPolyDataReader* vtkGDCMPolyDataReader::New ()` [static]

Examples:

[gdcmscene.cxx](#), [GenerateRTSTRUCT.cxx](#), and [rtstructapp.cxx](#).

25.340.3.3 `virtual void vtkGDCMPolyDataReader::PrintSelf (ostream & os, vtkIndent indent)` [virtual]

25.340.3.4 `int vtkGDCMPolyDataReader::RequestData (vtkInformation *, vtkInformationVector **, vtkInformationVector *)` [protected]

25.340.3.5 `int vtkGDCMPolyDataReader::RequestData_HemodynamicWaveformStorage (gdcmm::Reader const & reader, vtkInformationVector * outputVector)` [protected]

- 25.340.3.6 `int vtkGDCMPolyDataReader::RequestData_RTStructureSetStorage (gdcm::Reader const & reader, vtkInformationVector * outputVector)` [protected]
- 25.340.3.7 `int vtkGDCMPolyDataReader::RequestInformation (vtkInformation * vtkNotUsed(request), vtkInformationVector ** vtkNotUsed(inputVector), vtkInformationVector * outputVector)` [protected]
- 25.340.3.8 `int vtkGDCMPolyDataReader::RequestInformation_HemodynamicWaveformStorage (gdcm::Reader const & reader)` [protected]
- 25.340.3.9 `int vtkGDCMPolyDataReader::RequestInformation_RTStructureSetStorage (gdcm::Reader const & reader)` [protected]
- 25.340.3.10 `vtkGDCMPolyDataReader::vtkGetObjectMacro (MedicalImageProperties , vtkMedicalImageProperties)`
- 25.340.3.11 `vtkGDCMPolyDataReader::vtkGetObjectMacro (RTStructSetProperties , vtkRTStructSetProperties)`
- 25.340.3.12 `vtkGDCMPolyDataReader::vtkGetStringMacro (FileName)`
- 25.340.3.13 `vtkGDCMPolyDataReader::vtkSetStringMacro (FileName)`
- 25.340.3.14 `vtkGDCMPolyDataReader::vtkTypeRevisionMacro (vtkGDCMPolyDataReader , vtkPolyDataAlgorithm)`

25.340.4 Member Data Documentation

- 25.340.4.1 `char* vtkGDCMPolyDataReader::FileName` [protected]
- 25.340.4.2 `vtkMedicalImageProperties* vtkGDCMPolyDataReader::MedicalImageProperties` [protected]
- 25.340.4.3 `vtkRTStructSetProperties* vtkGDCMPolyDataReader::RTStructSetProperties` [protected]


The documentation for this class was generated from the following file:

- [vtkGDCMPolyDataReader.h](#)


25.341 vtkGDCMPolyDataWriter Class Reference

```
#include <vtkGDCMPolyDataWriter.h>
```

Inheritance diagram for vtkGDCMPolyDataWriter:



Collaboration diagram for vtkGDCMPolyDataWriter:



Public Member Functions

- void [InitializeRTStructSet](#) (vtkStdString inDirectory, vtkStdString inStructLabel, vtkStdString inStructName, vtkStringArray *inROINames, vtkStringArray *inROIAlgorithmName, vtkStringArray *inROIType)
- virtual void [PrintSelf](#) (ostream &os, vtkIndent indent)
- virtual void [SetMedicalImageProperties](#) (vtkMedicalImageProperties *pd)
- void [SetNumberOfInputPorts](#) (int n)
- virtual void [SetRTStructSetProperties](#) (vtkRTStructSetProperties *pd)
- [vtkTypeRevisionMacro](#) (vtkGDCMPolyDataWriter, vtkPolyDataWriter)

Static Public Member Functions

- static [vtkGDCMPolyDataWriter](#) * [New](#) ()

Protected Member Functions

- [vtkGDCMPolyDataWriter](#) ()
- [~vtkGDCMPolyDataWriter](#) ()
- void [WriteData](#) ()
- void [WriteRTSTRUCTData](#) (gdcmm::File &file, int num)
- void [WriteRTSTRUCTInfo](#) (gdcmm::File &file)

Protected Attributes

- [vtkMedicalImageProperties](#) * [MedicalImageProperties](#)
- [vtkRTStructSetProperties](#) * [RTStructSetProperties](#)

25.341.1 Detailed Description

Examples:

[GenerateRTSTRUCT.cxx](#), and [rtstructapp.cxx](#).

25.341.2 Constructor & Destructor Documentation

25.341.2.1 [vtkGDCMPolyDataWriter::vtkGDCMPolyDataWriter](#) () [protected]

25.341.2.2 [vtkGDCMPolyDataWriter::~~vtkGDCMPolyDataWriter](#) () [protected]

25.341.3 Member Function Documentation

25.341.3.1 void [vtkGDCMPolyDataWriter::InitializeRTStructSet](#) ([vtkStdString](#) *inDirectory*, [vtkStdString](#) *inStructLabel*, [vtkStdString](#) *inStructName*, [vtkStringArray](#) * *inROINames*, [vtkStringArray](#) * *inROIAlgorithmName*, [vtkStringArray](#) * *inROIType*)

Examples:

[GenerateRTSTRUCT.cxx](#).

25.341.3.2 static [vtkGDCMPolyDataWriter*](#) [vtkGDCMPolyDataWriter::New](#) () [static]

Examples:

[GenerateRTSTRUCT.cxx](#), and [rtstructapp.cxx](#).

25.341.3.3 virtual void [vtkGDCMPolyDataWriter::PrintSelf](#) ([ostream](#) & *os*, [vtkIndent](#) *indent*) [virtual]

25.341.3.4 virtual void [vtkGDCMPolyDataWriter::SetMedicalImageProperties](#) ([vtkMedicalImageProperties](#) * *pd*) [virtual]

Examples:

[GenerateRTSTRUCT.cxx](#), and [rtstructapp.cxx](#).

25.341.3.5 void vtkGDCMPolyDataWriter::SetNumberOfInputPorts (int *n*)

Examples:

[GenerateRTSTRUCT.cxx](#), and [rtstructapp.cxx](#).

25.341.3.6 virtual void vtkGDCMPolyDataWriter::SetRTStructSetProperties (vtkRTStructSetProperties * *pd*) [virtual]

Examples:

[GenerateRTSTRUCT.cxx](#), and [rtstructapp.cxx](#).

25.341.3.7 vtkGDCMPolyDataWriter::vtkTypeRevisionMacro (vtkGDCMPolyDataWriter , vtkPolyDataWriter)

25.341.3.8 void vtkGDCMPolyDataWriter::WriteData () [protected]

25.341.3.9 void vtkGDCMPolyDataWriter::WriteRTSTRUCTData (gdcm::File & *file*, int *num*) [protected]

25.341.3.10 void vtkGDCMPolyDataWriter::WriteRTSTRUCTInfo (gdcm::File & *file*) [protected]

25.341.4 Member Data Documentation

25.341.4.1 vtkMedicalImageProperties* vtkGDCMPolyDataWriter::MedicalImageProperties [protected]

25.341.4.2 vtkRTStructSetProperties* vtkGDCMPolyDataWriter::RTStructSetProperties [protected]


The documentation for this class was generated from the following file:

- [vtkGDCMPolyDataWriter.h](#)


25.342 vtkGDCMTesting Class Reference

```
#include <vtkGDCMTesting.h>
```

Inheritance diagram for vtkGDCMTesting:



Collaboration diagram for vtkGDCMTesting:



Public Types

- typedef const char *const (* [MD5MetalmagesType](#))[3]

Public Member Functions

- void [PrintSelf](#) (ostream &os, vtkIndent indent)
- [vtkTypeRevisionMacro](#) (vtkGDCMTesting, vtkObject)

Static Public Member Functions

- static const char * [GetGDCMDataRoot](#) ()
- static const char *const * [GetMD5MetalImage](#) (unsigned int file)
- static const char * [GetMHDMD5FromFile](#) (const char *filepath)
- static unsigned int [GetNumberOfMD5MetalImages](#) ()
- static const char * [GetRAWMD5FromFile](#) (const char *filepath)
- static const char * [GetVTKDataRoot](#) ()
- static [vtkGDCMTesting](#) * [New](#) ()

Protected Member Functions

- [vtkGDCMTesting](#) ()
- [~vtkGDCMTesting](#) ()

25.342.1 Detailed Description

Examples:

[HelloActiviz5.cs](#), [HelloVTKWorld2.cs](#), [MetalImageMD5Activiz.cs](#), [ReadSeriesIntoVTK.java](#), and [RefCounting.cs](#).

25.342.2 Member Typedef Documentation

25.342.2.1 `typedef const char* const(* vtkGDCMTesting::MD5MetalmagesType)[3]`

25.342.3 Constructor & Destructor Documentation

25.342.3.1 `vtkGDCMTesting::vtkGDCMTesting ()` [protected]

25.342.3.2 `vtkGDCMTesting::~~vtkGDCMTesting ()` [protected]

25.342.4 Member Function Documentation

25.342.4.1 `static const char* vtkGDCMTesting::GetGDCMDataRoot ()` [static]

Examples:

[HelloActiviz5.cs](#), and [ReadSeriesIntoVTK.java](#).

25.342.4.2 `static const char* const* vtkGDCMTesting::GetMD5Metalmage (unsigned int file)` [static]

25.342.4.3 `static const char* vtkGDCMTesting::GetMHMD5FromFile (const char * filepath)` [static]

Examples:

[MetalmageMD5Activiz.cs](#).

25.342.4.4 `static unsigned int vtkGDCMTesting::GetNumberOfMD5Metalmages ()` [static]

25.342.4.5 `static const char* vtkGDCMTesting::GetRAWMD5FromFile (const char * filepath)` [static]

Examples:

[MetalmageMD5Activiz.cs](#).

25.342.4.6 `static const char* vtkGDCMTesting::GetVTKDataRoot ()` [static]

Examples:

[HelloActiviz5.cs](#), and [HelloVTKWorld2.cs](#).

25.342.4.7 `static vtkGDCMTesting* vtkGDCMTesting::New ()` [static]

Examples:

[RefCounting.cs](#).

25.342.4.8 void vtkGDCMTesting::PrintSelf (ostream & *os*, vtkIndent *indent*)

25.342.4.9 vtkGDCMTesting::vtkTypeRevisionMacro (vtkGDCMTesting , vtkObject)


The documentation for this class was generated from the following file:

- [vtkGDCMTesting.h](#)


25.343 vtkGDCMThreadedImageReader Class Reference

```
#include <vtkGDCMThreadedImageReader.h>
```

Inheritance diagram for vtkGDCMThreadedImageReader:



Collaboration diagram for vtkGDCMThreadedImageReader:



Public Member Functions

- virtual void [PrintSelf](#) (ostream &os, vtkIndent indent)
- [vtkBooleanMacro](#) (UseShiftScale, int)
- [vtkGetMacro](#) (UseShiftScale, int)
- [vtkSetMacro](#) (Shift, double)
- [vtkSetMacro](#) (Scale, double)
- [vtkSetMacro](#) (UseShiftScale, int)
- [vtkTypeRevisionMacro](#) (vtkGDCMThreadedImageReader, vtkGDCMImageReader)

Static Public Member Functions

- static [vtkGDCMThreadedImageReader * New](#) ()

Protected Member Functions

- [vtkGDCMThreadedImageReader](#) ()
- [~vtkGDCMThreadedImageReader](#) ()
- void [ExecuteData](#) (vtkDataObject *out)
- void [ExecuteInformation](#) ()
- void [ReadFiles](#) (unsigned int nfiles, const char *filenames[])
- void [RequestDataCompat](#) ()

Additional Inherited Members

25.343.1 Constructor & Destructor Documentation

25.343.1.1 `vtkGDCMThreadedImageReader::vtkGDCMThreadedImageReader ()` [protected]

25.343.1.2 `vtkGDCMThreadedImageReader::~~vtkGDCMThreadedImageReader ()` [protected]

25.343.2 Member Function Documentation

25.343.2.1 `void vtkGDCMThreadedImageReader::ExecuteData (vtkDataObject * out)` [protected]

25.343.2.2 `void vtkGDCMThreadedImageReader::ExecuteInformation ()` [protected]

25.343.2.3 `static vtkGDCMThreadedImageReader* vtkGDCMThreadedImageReader::New ()` [static]

25.343.2.4 `virtual void vtkGDCMThreadedImageReader::PrintSelf (ostream & os, vtkIndent indent)` [virtual]

Reimplemented from [vtkGDCMImageReader](#).

25.343.2.5 `void vtkGDCMThreadedImageReader::ReadFiles (unsigned int nfiles, const char * filenames[])` [protected]

25.343.2.6 `void vtkGDCMThreadedImageReader::RequestDataCompat ()` [protected]

25.343.2.7 `vtkGDCMThreadedImageReader::vtkBooleanMacro (UseShiftScale , int)`

25.343.2.8 `vtkGDCMThreadedImageReader::vtkGetMacro (UseShiftScale , int)`

25.343.2.9 `vtkGDCMThreadedImageReader::vtkSetMacro (Shift , double)`

25.343.2.10 `vtkGDCMThreadedImageReader::vtkSetMacro (Scale , double)`

25.343.2.11 `vtkGDCMThreadedImageReader::vtkSetMacro (UseShiftScale , int)`

25.343.2.12 `vtkGDCMThreadedImageReader::vtkTypeRevisionMacro (vtkGDCMThreadedImageReader ,
vtkGDCMImageReader)`


The documentation for this class was generated from the following file:

- [vtkGDCMThreadedImageReader.h](#)


25.344 vtkGDCMThreadedImageReader2 Class Reference

```
#include <vtkGDCMThreadedImageReader2.h>
```

Inheritance diagram for vtkGDCMThreadedImageReader2:



Collaboration diagram for vtkGDCMThreadedImageReader2:



Public Member Functions

- virtual const char * [GetFileName](#) (int i=0)
- virtual void [PrintSelf](#) (ostream &os, vtkIndent indent)
- virtual void [SetFileName](#) (const char *filename)
- virtual void [SetFileNames](#) (vtkStringArray *)
- int [SplitExtent](#) (int splitExt[6], int startExt[6], int num, int total)
- [vtkBooleanMacro](#) (FileLowerLeft, int)
- [vtkBooleanMacro](#) (LoadOverlays, int)
- [vtkBooleanMacro](#) (UseShiftScale, int)
- [vtkGetMacro](#) (FileLowerLeft, int)
- [vtkGetMacro](#) (NumberOfOverlays, int)
- [vtkGetMacro](#) (DataScalarType, int)
- [vtkGetMacro](#) (NumberOfScalarComponents, int)
- [vtkGetMacro](#) (LoadOverlays, int)
- [vtkGetMacro](#) (Shift, double)
- [vtkGetMacro](#) (Scale, double)

- [vtkGetMacro](#) (UseShiftScale, int)
- [vtkGetObjectMacro](#) (FileNames, vtkStringArray)
- [vtkGetVector3Macro](#) (DataOrigin, double)
- [vtkGetVector3Macro](#) (DataSpacing, double)
- [vtkGetVector6Macro](#) (DataExtent, int)
- [vtkSetMacro](#) (FileLowerLeft, int)
- [vtkSetMacro](#) (DataScalarType, int)
- [vtkSetMacro](#) (NumberOfScalarComponents, int)
- [vtkSetMacro](#) (LoadOverlays, int)
- [vtkSetMacro](#) (Shift, double)
- [vtkSetMacro](#) (Scale, double)
- [vtkSetMacro](#) (UseShiftScale, int)
- [vtkSetVector3Macro](#) (DataOrigin, double)
- [vtkSetVector3Macro](#) (DataSpacing, double)
- [vtkSetVector6Macro](#) (DataExtent, int)
- [vtkTypeRevisionMacro](#) ([vtkGDCMThreadedImageReader2](#), [vtkThreadedImageAlgorithm](#))

Static Public Member Functions

- static
[vtkGDCMThreadedImageReader2](#) * [New](#) ()

Protected Member Functions

- [vtkGDCMThreadedImageReader2](#) ()
- [~vtkGDCMThreadedImageReader2](#) ()
- int [RequestInformation](#) (vtkInformation *request, vtkInformationVector **inputVector, vtkInformationVector *outputVector)
- void [ThreadedRequestData](#) (vtkInformation *request, vtkInformationVector **inputVector, vtkInformationVector *outputVector, vtkImageData ***inData, vtkImageData **outData, int outExt[6], int id)

25.344.1 Constructor & Destructor Documentation

25.344.1.1 [vtkGDCMThreadedImageReader2::vtkGDCMThreadedImageReader2](#) () [protected]

25.344.1.2 [vtkGDCMThreadedImageReader2::~~vtkGDCMThreadedImageReader2](#) () [protected]

25.344.2 Member Function Documentation

25.344.2.1 virtual const char* [vtkGDCMThreadedImageReader2::GetFileName](#) (int *i* = 0) [virtual]

25.344.2.2 static [vtkGDCMThreadedImageReader2](#)* [vtkGDCMThreadedImageReader2::New](#) () [static]

25.344.2.3 virtual void [vtkGDCMThreadedImageReader2::PrintSelf](#) (ostream & *os*, vtkIndent *indent*) [virtual]

25.344.2.4 int [vtkGDCMThreadedImageReader2::RequestInformation](#) (vtkInformation * *request*, vtkInformationVector ** *inputVector*, vtkInformationVector * *outputVector*) [protected]

25.344.2.5 virtual void [vtkGDCMThreadedImageReader2::SetFileName](#) (const char * *filename*) [virtual]

- 25.344.2.6 virtual void vtkGDCMThreadedImageReader2::SetFileNames (vtkStringArray *) [virtual]
- 25.344.2.7 int vtkGDCMThreadedImageReader2::SplitExtent (int *splitExt*[6], int *startExt*[6], int *num*, int *total*)
- 25.344.2.8 void vtkGDCMThreadedImageReader2::ThreadedRequestData (vtkInformation * *request*, vtkInformationVector ** *inputVector*, vtkInformationVector * *outputVector*, vtkImageData *** *inData*, vtkImageData ** *outData*, int *outExt*[6], int *id*) [protected]
- 25.344.2.9 vtkGDCMThreadedImageReader2::vtkBooleanMacro (FileLowerLeft , int)
- 25.344.2.10 vtkGDCMThreadedImageReader2::vtkBooleanMacro (LoadOverlays , int)
- 25.344.2.11 vtkGDCMThreadedImageReader2::vtkBooleanMacro (UseShiftScale , int)
- 25.344.2.12 vtkGDCMThreadedImageReader2::vtkGetMacro (FileLowerLeft , int)
- 25.344.2.13 vtkGDCMThreadedImageReader2::vtkGetMacro (NumberOfOverlays , int)
- 25.344.2.14 vtkGDCMThreadedImageReader2::vtkGetMacro (DataScalarType , int)
- 25.344.2.15 vtkGDCMThreadedImageReader2::vtkGetMacro (NumberOfScalarComponents , int)
- 25.344.2.16 vtkGDCMThreadedImageReader2::vtkGetMacro (LoadOverlays , int)
- 25.344.2.17 vtkGDCMThreadedImageReader2::vtkGetMacro (Shift , double)
- 25.344.2.18 vtkGDCMThreadedImageReader2::vtkGetMacro (Scale , double)
- 25.344.2.19 vtkGDCMThreadedImageReader2::vtkGetMacro (UseShiftScale , int)
- 25.344.2.20 vtkGDCMThreadedImageReader2::vtkGetObjectMacro (FileNames , vtkStringArray)
- 25.344.2.21 vtkGDCMThreadedImageReader2::vtkGetVector3Macro (DataOrigin , double)
- 25.344.2.22 vtkGDCMThreadedImageReader2::vtkGetVector3Macro (DataSpacing , double)
- 25.344.2.23 vtkGDCMThreadedImageReader2::vtkGetVector6Macro (DataExtent , int)
- 25.344.2.24 vtkGDCMThreadedImageReader2::vtkSetMacro (FileLowerLeft , int)
- 25.344.2.25 vtkGDCMThreadedImageReader2::vtkSetMacro (DataScalarType , int)
- 25.344.2.26 vtkGDCMThreadedImageReader2::vtkSetMacro (NumberOfScalarComponents , int)
- 25.344.2.27 vtkGDCMThreadedImageReader2::vtkSetMacro (LoadOverlays , int)
- 25.344.2.28 vtkGDCMThreadedImageReader2::vtkSetMacro (Shift , double)
- 25.344.2.29 vtkGDCMThreadedImageReader2::vtkSetMacro (Scale , double)
- 25.344.2.30 vtkGDCMThreadedImageReader2::vtkSetMacro (UseShiftScale , int)

25.344.2.31 `vtkGDCMThreadedImageReader2::vtkSetVector3Macro (DataOrigin , double)`

25.344.2.32 `vtkGDCMThreadedImageReader2::vtkSetVector3Macro (DataSpacing , double)`

25.344.2.33 `vtkGDCMThreadedImageReader2::vtkSetVector6Macro (DataExtent , int)`

25.344.2.34 `vtkGDCMThreadedImageReader2::vtkTypeRevisionMacro (vtkGDCMThreadedImageReader2 ,
vtkThreadedImageAlgorithm)`


The documentation for this class was generated from the following file:

- [vtkGDCMThreadedImageReader2.h](#)


25.345 vtkImageColorViewer Class Reference

```
#include <vtkImageColorViewer.h>
```

Inheritance diagram for `vtkImageColorViewer`:



Collaboration diagram for vtkImageColorViewer:



Public Types

- enum {
[SLICE_ORIENTATION_YZ](#) = 0,
[SLICE_ORIENTATION_XZ](#) = 1,
[SLICE_ORIENTATION_XY](#) = 2 }

Public Member Functions

- virtual void [AddInput](#) (vtkImageData *input)
- virtual void [AddInputConnection](#) (vtkAlgorithmOutput *input)
- virtual double [GetColorLevel](#) ()
- virtual double [GetColorWindow](#) ()
- virtual vtkImageData * [GetInput](#) ()
- virtual int [GetOffScreenRendering](#) ()
- double [GetOverlayVisibility](#) ()
- virtual int * [GetPosition](#) ()
- virtual int * [GetSize](#) ()
- virtual int [GetSliceMax](#) ()
- virtual int [GetSliceMin](#) ()
- virtual void [GetSliceRange](#) (int range[2])
- virtual void [GetSliceRange](#) (int &min, int &max)
- virtual int * [GetSliceRange](#) ()
- virtual const char * [GetWindowName](#) ()
- void [PrintSelf](#) (ostream &os, vtkIndent indent)
- virtual void [Render](#) (void)
- virtual void [SetColorLevel](#) (double s)

- virtual void [SetColorWindow](#) (double s)
- virtual void [SetDisplayId](#) (void *a)
- virtual void [SetInput](#) (vtkImageData *in)
- virtual void [SetInputConnection](#) (vtkAlgorithmOutput *input)
- virtual void [SetOffScreenRendering](#) (int)
- void [SetOverlayVisibility](#) (double vis)
- virtual void [SetParentId](#) (void *a)
- virtual void [SetPosition](#) (int a, int b)
- virtual void [SetPosition](#) (int a[2])
- virtual void [SetRenderer](#) (vtkRenderer *arg)
- virtual void [SetRenderWindow](#) (vtkRenderWindow *arg)
- virtual void [SetSize](#) (int a, int b)
- virtual void [SetSize](#) (int a[2])
- virtual void [SetSlice](#) (int s)
- virtual void [SetSliceOrientation](#) (int orientation)
- virtual void [SetSliceOrientationToXY](#) ()
- virtual void [SetSliceOrientationToXZ](#) ()
- virtual void [SetSliceOrientationToYZ](#) ()
- virtual void [SetupInteractor](#) (vtkRenderWindowInteractor *)
- virtual void [SetWindowId](#) (void *a)
- virtual void [UpdateDisplayExtent](#) ()
- [VTK_LEGACY](#) (int GetWholeZMin())
- [VTK_LEGACY](#) (int GetWholeZMax())
- [VTK_LEGACY](#) (int GetZSlice())
- [VTK_LEGACY](#) (void SetZSlice(int))
- [vtkBooleanMacro](#) (OffScreenRendering, int)
- [vtkGetMacro](#) (SliceOrientation, int)
- [vtkGetMacro](#) (Slice, int)
- [vtkGetObjectMacro](#) (RenderWindow, vtkRenderWindow)
- [vtkGetObjectMacro](#) (Renderer, vtkRenderer)
- [vtkGetObjectMacro](#) (ImageActor, vtkImageActor)
- [vtkGetObjectMacro](#) (WindowLevel, vtkImageMapToWindowLevelColors2)
- [vtkGetObjectMacro](#) (InteractorStyle, vtkInteractorStyleImage)
- [vtkTypeRevisionMacro](#) (vtkImageColorViewer, vtkObject)

Static Public Member Functions

- static [vtkImageColorViewer](#) * [New](#) ()

Protected Member Functions

- [vtkImageColorViewer](#) ()
- [~vtkImageColorViewer](#) ()
- virtual void [InstallPipeline](#) ()
- virtual void [UnInstallPipeline](#) ()
- virtual void [UpdateOrientation](#) ()

Protected Attributes

- int [FirstRender](#)
- vtkImageActor * [ImageActor](#)
- vtkRenderWindowInteractor * [Interactor](#)
- vtkInteractorStyleImage * [InteractorStyle](#)
- vtkImageActor * [OverlayImageActor](#)
- vtkRenderer * [Renderer](#)
- vtkRenderWindow * [RenderWindow](#)
- int [Slice](#)
- int [SliceOrientation](#)
- [vtkImageMapToWindowLevelColors2](#) * [WindowLevel](#)

25.345.1 Detailed Description

Examples:

[gdcmrtionplan.cxx](#), and [gdcmrtplan.cxx](#).

25.345.2 Member Enumeration Documentation

25.345.2.1 anonymous enum

Enumerator

SLICE_ORIENTATION_YZ

SLICE_ORIENTATION_XZ

SLICE_ORIENTATION_XY

25.345.3 Constructor & Destructor Documentation

25.345.3.1 `vtkImageColorViewer::vtkImageColorViewer ()` [protected]

25.345.3.2 `vtkImageColorViewer::~~vtkImageColorViewer ()` [protected]

25.345.4 Member Function Documentation

25.345.4.1 `virtual void vtkImageColorViewer::AddInput (vtkImageData * input)` [virtual]

25.345.4.2 `virtual void vtkImageColorViewer::AddInputConnection (vtkAlgorithmOutput * input)` [virtual]

25.345.4.3 `virtual double vtkImageColorViewer::GetColorLevel ()` [virtual]

25.345.4.4 `virtual double vtkImageColorViewer::GetColorWindow ()` [virtual]

25.345.4.5 `virtual vtkImageData* vtkImageColorViewer::GetInput ()` [virtual]

25.345.4.6 `virtual int vtkImageColorViewer::GetOffScreenRendering ()` [virtual]

25.345.4.7 `double vtkImageColorViewer::GetOverlayVisibility ()`

```

25.345.4.8  virtual int* vtkImageColorViewer::GetPosition ( ) [virtual]

25.345.4.9  virtual int* vtkImageColorViewer::GetSize ( ) [virtual]

25.345.4.10 virtual int vtkImageColorViewer::GetSliceMax ( ) [virtual]

25.345.4.11 virtual int vtkImageColorViewer::GetSliceMin ( ) [virtual]

25.345.4.12 virtual void vtkImageColorViewer::GetSliceRange ( int range[2] ) [inline],[virtual]

25.345.4.13 virtual void vtkImageColorViewer::GetSliceRange ( int & min, int & max ) [virtual]

25.345.4.14 virtual int* vtkImageColorViewer::GetSliceRange ( ) [virtual]

25.345.4.15 virtual const char* vtkImageColorViewer::GetWindowName ( ) [virtual]

25.345.4.16 virtual void vtkImageColorViewer::InstallPipeline ( ) [protected],[virtual]

25.345.4.17 static vtkImageColorViewer* vtkImageColorViewer::New ( ) [static]

```

Examples:

[gdcmrtionplan.cxx](#), and [gdcmrtplan.cxx](#).

```

25.345.4.18 void vtkImageColorViewer::PrintSelf ( ostream & os, vtkIndent indent )

25.345.4.19 virtual void vtkImageColorViewer::Render ( void ) [virtual]

```

Examples:

[gdcmrtionplan.cxx](#), and [gdcmrtplan.cxx](#).

```

25.345.4.20 virtual void vtkImageColorViewer::SetColorLevel ( double s ) [virtual]

25.345.4.21 virtual void vtkImageColorViewer::SetColorWindow ( double s ) [virtual]

25.345.4.22 virtual void vtkImageColorViewer::SetDisplayId ( void * a ) [virtual]

25.345.4.23 virtual void vtkImageColorViewer::SetInput ( vtkImageData * in ) [virtual]

```

Examples:

[gdcmrtionplan.cxx](#), and [gdcmrtplan.cxx](#).

```

25.345.4.24 virtual void vtkImageColorViewer::SetInputConnection ( vtkAlgorithmOutput * input ) [virtual]

25.345.4.25 virtual void vtkImageColorViewer::SetOffScreenRendering ( int ) [virtual]

25.345.4.26 void vtkImageColorViewer::SetOverlayVisibility ( double vis )

```

25.345.4.27 virtual void vtkImageColorViewer::SetParentId (void * *a*) [virtual]

25.345.4.28 virtual void vtkImageColorViewer::SetPosition (int *a*, int *b*) [virtual]

25.345.4.29 virtual void vtkImageColorViewer::SetPosition (int *a[2]*) [inline],[virtual]

References SetPosition().

Referenced by SetPosition().

25.345.4.30 virtual void vtkImageColorViewer::SetRenderer (vtkRenderer * *arg*) [virtual]

25.345.4.31 virtual void vtkImageColorViewer::SetRenderWindow (vtkRenderWindow * *arg*) [virtual]

25.345.4.32 virtual void vtkImageColorViewer::SetSize (int *a*, int *b*) [virtual]

Examples:

[gdcmrtionplan.cxx](#), and [gdcmrtplan.cxx](#).

25.345.4.33 virtual void vtkImageColorViewer::SetSize (int *a[2]*) [inline],[virtual]

References SetSize().

Referenced by SetSize().

25.345.4.34 virtual void vtkImageColorViewer::SetSlice (int *s*) [virtual]

25.345.4.35 virtual void vtkImageColorViewer::SetSliceOrientation (int *orientation*) [virtual]

25.345.4.36 virtual void vtkImageColorViewer::SetSliceOrientationToXY () [inline],[virtual]

References SLICE_ORIENTATION_XY.

25.345.4.37 virtual void vtkImageColorViewer::SetSliceOrientationToXZ () [inline],[virtual]

References SLICE_ORIENTATION_XZ.

25.345.4.38 virtual void vtkImageColorViewer::SetSliceOrientationToYZ () [inline],[virtual]

References SLICE_ORIENTATION_YZ.

25.345.4.39 virtual void vtkImageColorViewer::SetupInteractor (vtkRenderWindowInteractor *) [virtual]

Examples:

[gdcmrtionplan.cxx](#), and [gdcmrtplan.cxx](#).

- 25.345.4.40 `virtual void vtkImageColorViewer::SetWindowId (void * a)` [virtual]
- 25.345.4.41 `virtual void vtkImageColorViewer::UnInstallPipeline ()` [protected],[virtual]
- 25.345.4.42 `virtual void vtkImageColorViewer::UpdateDisplayExtent ()` [virtual]
- 25.345.4.43 `virtual void vtkImageColorViewer::UpdateOrientation ()` [protected],[virtual]
- 25.345.4.44 `vtkImageColorViewer::VTK_LEGACY (int GetWholeZMin())`
- 25.345.4.45 `vtkImageColorViewer::VTK_LEGACY (int GetWholeZMax())`
- 25.345.4.46 `vtkImageColorViewer::VTK_LEGACY (int GetZSlice())`
- 25.345.4.47 `vtkImageColorViewer::VTK_LEGACY (void SetZSliceint)`
- 25.345.4.48 `vtkImageColorViewer::vtkBooleanMacro (OffScreenRendering , int)`
- 25.345.4.49 `vtkImageColorViewer::vtkGetMacro (SliceOrientation , int)`
- 25.345.4.50 `vtkImageColorViewer::vtkGetMacro (Slice , int)`
- 25.345.4.51 `vtkImageColorViewer::vtkGetObjectMacro (RenderWindow , vtkRenderWindow)`
- 25.345.4.52 `vtkImageColorViewer::vtkGetObjectMacro (Renderer , vtkRenderer)`
- 25.345.4.53 `vtkImageColorViewer::vtkGetObjectMacro (ImageActor , vtkImageActor)`
- 25.345.4.54 `vtkImageColorViewer::vtkGetObjectMacro (WindowLevel , vtkImageMapToWindowLevelColors2)`
- 25.345.4.55 `vtkImageColorViewer::vtkGetObjectMacro (InteractorStyle , vtkInteractorStyleImage)`
- 25.345.4.56 `vtkImageColorViewer::vtkTypeRevisionMacro (vtkImageColorViewer , vtkObject)`

25.345.5 Member Data Documentation

- 25.345.5.1 `int vtkImageColorViewer::FirstRender` [protected]
- 25.345.5.2 `vtkImageActor* vtkImageColorViewer::ImageActor` [protected]
- 25.345.5.3 `vtkRenderWindowInteractor* vtkImageColorViewer::Interactor` [protected]
- 25.345.5.4 `vtkInteractorStyleImage* vtkImageColorViewer::InteractorStyle` [protected]
- 25.345.5.5 `vtkImageActor* vtkImageColorViewer::OverlayImageActor` [protected]
- 25.345.5.6 `vtkRenderer* vtkImageColorViewer::Renderer` [protected]
- 25.345.5.7 `vtkRenderWindow* vtkImageColorViewer::RenderWindow` [protected]
- 25.345.5.8 `int vtkImageColorViewer::Slice` [protected]

25.345.5.9 `int vtkImageColorViewer::SliceOrientation` `[protected]`

25.345.5.10 `vtkImageMapToWindowLevelColors2* vtkImageColorViewer::WindowLevel` `[protected]`


The documentation for this class was generated from the following file:

- [vtkImageColorViewer.h](#)


25.346 vtkImageMapToColors16 Class Reference

```
#include <vtkImageMapToColors16.h>
```

Inheritance diagram for vtkImageMapToColors16:



Collaboration diagram for vtkImageMapToColors16:



Public Member Functions

- virtual unsigned long [GetMTime](#) ()
- void [PrintSelf](#) (ostream &os, vtkIndent indent)
- virtual void [SetLookupTable](#) (vtkScalarsToColors *)

- void [SetOutputFormatToLuminance](#) ()
- void [SetOutputFormatToLuminanceAlpha](#) ()
- void [SetOutputFormatToRGB](#) ()
- void [SetOutputFormatToRGBA](#) ()
- [vtkBooleanMacro](#) ([PassAlphaToOutput](#), int)
- [vtkGetMacro](#) ([OutputFormat](#), int)
- [vtkGetMacro](#) ([ActiveComponent](#), int)
- [vtkGetMacro](#) ([PassAlphaToOutput](#), int)
- [vtkGetObjectMacro](#) ([LookupTable](#), [vtkScalarsToColors](#))
- [vtkSetMacro](#) ([OutputFormat](#), int)
- [vtkSetMacro](#) ([ActiveComponent](#), int)
- [vtkSetMacro](#) ([PassAlphaToOutput](#), int)
- [vtkTypeRevisionMacro](#) ([vtkImageMapToColors16](#), [vtkThreadedImageAlgorithm](#))

Static Public Member Functions

- static [vtkImageMapToColors16](#) * [New](#) ()

Protected Member Functions

- [vtkImageMapToColors16](#) ()
- [~vtkImageMapToColors16](#) ()
- virtual int [RequestData](#) ([vtkInformation](#) *request, [vtkInformationVector](#) **inputVector, [vtkInformationVector](#) *outputVector)
- virtual int [RequestInformation](#) ([vtkInformation](#) *, [vtkInformationVector](#) **, [vtkInformationVector](#) *)
- void [ThreadedRequestData](#) ([vtkInformation](#) *request, [vtkInformationVector](#) **inputVector, [vtkInformationVector](#) *outputVector, [vtkImageData](#) ***inData, [vtkImageData](#) **outData, int extent[6], int id)

Protected Attributes

- int [ActiveComponent](#)
- int [DataWasPassed](#)
- [vtkScalarsToColors](#) * [LookupTable](#)
- int [OutputFormat](#)
- int [PassAlphaToOutput](#)

25.346.1 Constructor & Destructor Documentation

25.346.1.1 [vtkImageMapToColors16::vtkImageMapToColors16](#) () [[protected](#)]

25.346.1.2 [vtkImageMapToColors16::~~vtkImageMapToColors16](#) () [[protected](#)]

25.346.2 Member Function Documentation

25.346.2.1 virtual unsigned long [vtkImageMapToColors16::GetMTime](#) () [[virtual](#)]

25.346.2.2 static [vtkImageMapToColors16](#)* [vtkImageMapToColors16::New](#) () [[static](#)]

- 25.346.2.3 void vtkImageMapToColors16::PrintSelf (ostream & *os*, vtkIndent *indent*)
- 25.346.2.4 virtual int vtkImageMapToColors16::RequestData (vtkInformation * *request*, vtkInformationVector ** *inputVector*, vtkInformationVector * *outputVector*) [protected],[virtual]
- 25.346.2.5 virtual int vtkImageMapToColors16::RequestInformation (vtkInformation * , vtkInformationVector ** , vtkInformationVector *) [protected],[virtual]
- 25.346.2.6 virtual void vtkImageMapToColors16::SetLookupTable (vtkScalarsToColors *) [virtual]
- 25.346.2.7 void vtkImageMapToColors16::SetOutputFormatToLuminance () [inline]
- 25.346.2.8 void vtkImageMapToColors16::SetOutputFormatToLuminanceAlpha () [inline]
- 25.346.2.9 void vtkImageMapToColors16::SetOutputFormatToRGB () [inline]
- 25.346.2.10 void vtkImageMapToColors16::SetOutputFormatToRGBA () [inline]
- 25.346.2.11 void vtkImageMapToColors16::ThreadedRequestData (vtkInformation * *request*, vtkInformationVector ** *inputVector*, vtkInformationVector * *outputVector*, vtkImageData *** *inData*, vtkImageData ** *outData*, int *extent*[6], int *id*) [protected]
- 25.346.2.12 vtkImageMapToColors16::vtkBooleanMacro (PassAlphaToOutput , int)
- 25.346.2.13 vtkImageMapToColors16::vtkGetMacro (OutputFormat , int)
- 25.346.2.14 vtkImageMapToColors16::vtkGetMacro (ActiveComponent , int)
- 25.346.2.15 vtkImageMapToColors16::vtkGetMacro (PassAlphaToOutput , int)
- 25.346.2.16 vtkImageMapToColors16::vtkGetObjectMacro (LookupTable , vtkScalarsToColors)
- 25.346.2.17 vtkImageMapToColors16::vtkSetMacro (OutputFormat , int)
- 25.346.2.18 vtkImageMapToColors16::vtkSetMacro (ActiveComponent , int)
- 25.346.2.19 vtkImageMapToColors16::vtkSetMacro (PassAlphaToOutput , int)
- 25.346.2.20 vtkImageMapToColors16::vtkTypeRevisionMacro (vtkImageMapToColors16 , vtkThreadedImageAlgorithm)

25.346.3 Member Data Documentation

- 25.346.3.1 int vtkImageMapToColors16::ActiveComponent [protected]
- 25.346.3.2 int vtkImageMapToColors16::DataWasPassed [protected]
- 25.346.3.3 vtkScalarsToColors* vtkImageMapToColors16::LookupTable [protected]
- 25.346.3.4 int vtkImageMapToColors16::OutputFormat [protected]

25.346.3.5 int vtkImageMapToColors16::PassAlphaToOutput [protected]


The documentation for this class was generated from the following file:

- [vtkImageMapToColors16.h](#)


25.347 vtkImageMapToWindowLevelColors2 Class Reference

```
#include <vtkImageMapToWindowLevelColors2.h>
```

Inheritance diagram for vtkImageMapToWindowLevelColors2:



Collaboration diagram for vtkImageMapToWindowLevelColors2:



Public Member Functions

- void [PrintSelf](#) (ostream &os, vtkIndent indent)
- [vtkGetMacro](#) ([Window](#), double)
- [vtkGetMacro](#) ([Level](#), double)

- [vtkSetMacro](#) ([Window](#), double)
- [vtkSetMacro](#) ([Level](#), double)
- [vtkTypeRevisionMacro](#) ([vtkImageMapToWindowLevelColors2](#), vtkImageMapToColors)

Static Public Member Functions

- static
[vtkImageMapToWindowLevelColors2](#) * [New](#) ()

Protected Member Functions

- [vtkImageMapToWindowLevelColors2](#) ()
- [~vtkImageMapToWindowLevelColors2](#) ()
- virtual int [RequestData](#) (vtkInformation *request, vtkInformationVector **inputVector, vtkInformationVector *outputVector)
- virtual int [RequestInformation](#) (vtkInformation *, vtkInformationVector **, vtkInformationVector *)
- void [ThreadedRequestData](#) (vtkInformation *request, vtkInformationVector **inputVector, vtkInformationVector *outputVector, vtkImageData ***inData, vtkImageData **outData, int extent[6], int id)

Protected Attributes

- double [Level](#)
- double [Window](#)

25.347.1 Constructor & Destructor Documentation

25.347.1.1 [vtkImageMapToWindowLevelColors2::vtkImageMapToWindowLevelColors2](#) () [protected]

25.347.1.2 [vtkImageMapToWindowLevelColors2::~~vtkImageMapToWindowLevelColors2](#) () [protected]

25.347.2 Member Function Documentation

25.347.2.1 static [vtkImageMapToWindowLevelColors2* vtkImageMapToWindowLevelColors2::New](#) () [static]

25.347.2.2 void [vtkImageMapToWindowLevelColors2::PrintSelf](#) (ostream & os, vtkIndent indent)

25.347.2.3 virtual int [vtkImageMapToWindowLevelColors2::RequestData](#) (vtkInformation * *request*, vtkInformationVector ** *inputVector*, vtkInformationVector * *outputVector*) [protected], [virtual]

25.347.2.4 virtual int [vtkImageMapToWindowLevelColors2::RequestInformation](#) (vtkInformation *, vtkInformationVector **, vtkInformationVector *) [protected], [virtual]

25.347.2.5 void [vtkImageMapToWindowLevelColors2::ThreadedRequestData](#) (vtkInformation * *request*, vtkInformationVector ** *inputVector*, vtkInformationVector * *outputVector*, vtkImageData *** *inData*, vtkImageData ** *outData*, int *extent*[6], int *id*) [protected]

25.347.2.6 [vtkImageMapToWindowLevelColors2::vtkGetMacro](#) ([Window](#) , double)

25.347.2.7 [vtkImageMapToWindowLevelColors2::vtkGetMacro](#) ([Level](#) , double)

25.347.2.8 `vtkImageMapToWindowLevelColors2::vtkSetMacro (Window , double)`

25.347.2.9 `vtkImageMapToWindowLevelColors2::vtkSetMacro (Level , double)`

25.347.2.10 `vtkImageMapToWindowLevelColors2::vtkTypeRevisionMacro (vtkImageMapToWindowLevelColors2 ,
vtkImageMapToColors)`

25.347.3 Member Data Documentation

25.347.3.1 `double vtkImageMapToWindowLevelColors2::Level` `[protected]`

25.347.3.2 `double vtkImageMapToWindowLevelColors2::Window` `[protected]`


The documentation for this class was generated from the following file:

- [vtkImageMapToWindowLevelColors2.h](#)


25.348 vtkImagePlanarComponentsToComponents Class Reference

```
#include <vtkImagePlanarComponentsToComponents.h>
```

Inheritance diagram for `vtkImagePlanarComponentsToComponents`:



Collaboration diagram for vtkImagePlanarComponentsToComponents:



Public Member Functions

- void [PrintSelf](#) (ostream &os, vtkIndent indent)
- [vtkTypeRevisionMacro](#) ([vtkImagePlanarComponentsToComponents](#), vtkImageAlgorithm)

Static Public Member Functions

- static
[vtkImagePlanarComponentsToComponents](#) * [New](#) ()

Protected Member Functions

- [vtkImagePlanarComponentsToComponents](#) ()
- [~vtkImagePlanarComponentsToComponents](#) ()
- virtual int [RequestData](#) (vtkInformation *, vtkInformationVector **, vtkInformationVector *)

25.348.1 Constructor & Destructor Documentation

25.348.1.1 [vtkImagePlanarComponentsToComponents::vtkImagePlanarComponentsToComponents \(\)](#) [protected]

25.348.1.2 [vtkImagePlanarComponentsToComponents::~~vtkImagePlanarComponentsToComponents \(\)](#) [inline], [protected]

25.348.2 Member Function Documentation

25.348.2.1 static [vtkImagePlanarComponentsToComponents*](#) [vtkImagePlanarComponentsToComponents::New \(\)](#) [static]

25.348.2.2 void [vtkImagePlanarComponentsToComponents::PrintSelf \(ostream & os, vtkIndent indent \)](#)

25.348.2.3 `virtual int vtkImagePlanarComponentsToComponents::RequestData (vtkInformation *, vtkInformationVector **, vtkInformationVector *) [protected],[virtual]`

25.348.2.4 `vtkImagePlanarComponentsToComponents::vtkTypeRevisionMacro (vtkImagePlanarComponentsToComponents, vtkImageAlgorithm)`


The documentation for this class was generated from the following file:

- [vtkImagePlanarComponentsToComponents.h](#)


25.349 vtkImageRGBToYBR Class Reference

```
#include <vtkImageRGBToYBR.h>
```

Inheritance diagram for vtkImageRGBToYBR:



Collaboration diagram for vtkImageRGBToYBR:



Public Member Functions

- void [PrintSelf](#) (ostream &os, vtkIndent indent)

- [vtkTypeRevisionMacro](#) ([vtkImageRGBToYBR](#), [vtkThreadedImageAlgorithm](#))

Static Public Member Functions

- static [vtkImageRGBToYBR](#) * [New](#) ()

Protected Member Functions

- [vtkImageRGBToYBR](#) ()
- [~vtkImageRGBToYBR](#) ()
- void [ThreadedExecute](#) ([vtkImageData](#) **inData*, [vtkImageData](#) **outData*, int *ext*[6], int *id*)

25.349.1 Constructor & Destructor Documentation

25.349.1.1 [vtkImageRGBToYBR::vtkImageRGBToYBR](#) () [[protected](#)]

25.349.1.2 [vtkImageRGBToYBR::~~vtkImageRGBToYBR](#) () [[inline](#)], [[protected](#)]

25.349.2 Member Function Documentation

25.349.2.1 static [vtkImageRGBToYBR](#)* [vtkImageRGBToYBR::New](#) () [[static](#)]

25.349.2.2 void [vtkImageRGBToYBR::PrintSelf](#) ([ostream](#) & *os*, [vtkIndent](#) *indent*)

25.349.2.3 void [vtkImageRGBToYBR::ThreadedExecute](#) ([vtkImageData](#) * *inData*, [vtkImageData](#) * *outData*, int *ext*[6], int *id*)
[[protected](#)]

25.349.2.4 [vtkImageRGBToYBR::vtkTypeRevisionMacro](#) ([vtkImageRGBToYBR](#) , [vtkThreadedImageAlgorithm](#))


The documentation for this class was generated from the following file:

- [vtkImageRGBToYBR.h](#)


25.350 vtkImageYBRToRGB Class Reference

```
#include <vtkImageYBRToRGB.h>
```

Inheritance diagram for `vtkImageYBRToRGB`:



Collaboration diagram for `vtkImageYBRToRGB`:



Public Member Functions

- void [PrintSelf](#) (ostream &os, vtkIndent indent)
- [vtkTypeRevisionMacro](#) ([vtkImageYBRToRGB](#), vtkThreadedImageAlgorithm)

Static Public Member Functions

- static [vtkImageYBRToRGB](#) * [New](#) ()

Protected Member Functions

- [vtkImageYBRToRGB](#) ()
- [~vtkImageYBRToRGB](#) ()
- void [ThreadedExecute](#) (vtkImageData *inData, vtkImageData *outData, int ext[6], int id)

25.350.1 Constructor & Destructor Documentation

25.350.1.1 `vtkImageYBRTToRGB::vtkImageYBRTToRGB ()` `[protected]`

25.350.1.2 `vtkImageYBRTToRGB::~~vtkImageYBRTToRGB ()` `[inline], [protected]`

25.350.2 Member Function Documentation

25.350.2.1 `static vtkImageYBRTToRGB* vtkImageYBRTToRGB::New ()` `[static]`

25.350.2.2 `void vtkImageYBRTToRGB::PrintSelf (ostream & os, vtkIndent indent)`

25.350.2.3 `void vtkImageYBRTToRGB::ThreadedExecute (vtkImageData * inData, vtkImageData * outData, int ext[6], int id)`
`[protected]`

25.350.2.4 `vtkImageYBRTToRGB::vtkTypeRevisionMacro (vtkImageYBRTToRGB , vtkThreadedImageAlgorithm)`


The documentation for this class was generated from the following file:

- [vtkImageYBRTToRGB.h](#)


25.351 vtkLookupTable16 Class Reference

```
#include <vtkLookupTable16.h>
```

Inheritance diagram for vtkLookupTable16:



Collaboration diagram for vtkLookupTable16:



Public Member Functions

- void [Build](#) ()
- unsigned short * [GetPointer](#) (const vtkIdType id)
- void [PrintSelf](#) (ostream &os, vtkIndent indent)
- void [SetNumberOfTableValues](#) (vtkIdType number)
- [vtkTypeRevisionMacro](#) ([vtkLookupTable16](#), vtkLookupTable)
- unsigned char * [WritePointer](#) (const vtkIdType id, const int number)

Static Public Member Functions

- static [vtkLookupTable16](#) * [New](#) ()

Protected Member Functions

- [vtkLookupTable16](#) (int size=256, int ext=256)
- [~vtkLookupTable16](#) ()
- void [MapScalarsThroughTable2](#) (void *input, unsigned char *output, int inputDataType, int numberOfValues, int inputIncrement, int outputFormat)

Protected Attributes

- vtkUnsignedShortArray * [Table16](#)

25.351.1 Constructor & Destructor Documentation

25.351.1.1 `vtkLookupTable16::vtkLookupTable16 (int size = 256, int ext = 256)` [protected]

25.351.1.2 `vtkLookupTable16::~~vtkLookupTable16 ()` [protected]

25.351.2 Member Function Documentation

- 25.351.2.1 void vtkLookupTable16::Build ()
- 25.351.2.2 unsigned short* vtkLookupTable16::GetPointer (const vtkIdType *id*) [inline]
- 25.351.2.3 void vtkLookupTable16::MapScalarsThroughTable2 (void * *input*, unsigned char * *output*, int *inputDataType*, int *numberOfValues*, int *inputIncrement*, int *outputFormat*) [protected]
- 25.351.2.4 static vtkLookupTable16* vtkLookupTable16::New () [static]
- 25.351.2.5 void vtkLookupTable16::PrintSelf (ostream & *os*, vtkIndent *indent*)
- 25.351.2.6 void vtkLookupTable16::SetNumberOfTableValues (vtkIdType *number*)
- 25.351.2.7 vtkLookupTable16::vtkTypeRevisionMacro (vtkLookupTable16 , vtkLookupTable)
- 25.351.2.8 unsigned char * vtkLookupTable16::WritePointer (const vtkIdType *id*, const int *number*) [inline]

References Table16.

25.351.3 Member Data Documentation

- 25.351.3.1 vtkUnsignedShortArray* vtkLookupTable16::Table16 [protected]

Referenced by WritePointer().


The documentation for this class was generated from the following file:

- [vtkLookupTable16.h](#)


25.352 vtkRTStructSetProperties Class Reference

```
#include <vtkRTStructSetProperties.h>
```

Inheritance diagram for vtkRTStructSetProperties:



Collaboration diagram for vtkRTStructSetProperties:



Public Member Functions

- void [AddContourReferencedFrameOfReference](#) (vtkIdType pdnum, const char *classuid, const char *instanceuid)
- void [AddReferencedFrameOfReference](#) (const char *classuid, const char *instanceuid)
- void [AddStructureSetROI](#) (int roinumber, const char *refframerefid, const char *roiname, const char *ROI-GenerationAlgorithm, const char *ROIDescription=0)
- void [AddStructureSetROIObservation](#) (int refnumber, int observationnumber, const char *rtroiinterpretedtype, const char *roiinterpreter, const char *roiobservationlabel=0)
- virtual void [Clear](#) ()
- virtual void [DeepCopy](#) (vtkRTStructSetProperties *p)
- const char * [GetContourReferencedFrameOfReferenceClassUID](#) (vtkIdType pdnum, vtkIdType id)
- const char * [GetContourReferencedFrameOfReferenceInstanceUID](#) (vtkIdType pdnum, vtkIdType id)
- vtkIdType [GetNumberOfContourReferencedFrameOfReferences](#) ()
- vtkIdType [GetNumberOfContourReferencedFrameOfReferences](#) (vtkIdType pdnum)
- vtkIdType [GetNumberOfReferencedFrameOfReferences](#) ()
- vtkIdType [GetNumberOfStructureSetROIs](#) ()
- const char * [GetReferencedFrameOfReferenceClassUID](#) (vtkIdType id)
- const char * [GetReferencedFrameOfReferenceInstanceUID](#) (vtkIdType id)
- int [GetStructureSetObservationNumber](#) (vtkIdType id)
- const char * [GetStructureSetROIDescription](#) (vtkIdType id)
- const char * [GetStructureSetROIGenerationAlgorithm](#) (vtkIdType)
- const char * [GetStructureSetROIName](#) (vtkIdType)
- int [GetStructureSetROINumber](#) (vtkIdType id)
- const char * [GetStructureSetROIObservationLabel](#) (vtkIdType id)
- const char * [GetStructureSetROIRefFrameRefUID](#) (vtkIdType)
- const char * [GetStructureSetRTROIInterpretedType](#) (vtkIdType id)
- void [PrintSelf](#) (ostream &os, vtkIndent indent)
- [vtkGetStringMacro](#) (StructureSetLabel)
- [vtkGetStringMacro](#) (StructureSetName)
- [vtkGetStringMacro](#) (StructureSetDate)
- [vtkGetStringMacro](#) (StructureSetTime)
- [vtkGetStringMacro](#) (SOPInstanceUID)
- [vtkGetStringMacro](#) (StudyInstanceUID)
- [vtkGetStringMacro](#) (SeriesInstanceUID)

- [vtkGetStringMacro \(ReferenceSeriesInstanceUID\)](#)
- [vtkGetStringMacro \(ReferenceFrameOfReferenceUID\)](#)
- [vtkSetStringMacro \(StructureSetLabel\)](#)
- [vtkSetStringMacro \(StructureSetName\)](#)
- [vtkSetStringMacro \(StructureSetDate\)](#)
- [vtkSetStringMacro \(StructureSetTime\)](#)
- [vtkSetStringMacro \(SOPInstanceUID\)](#)
- [vtkSetStringMacro \(StudyInstanceUID\)](#)
- [vtkSetStringMacro \(SeriesInstanceUID\)](#)
- [vtkSetStringMacro \(ReferenceSeriesInstanceUID\)](#)
- [vtkSetStringMacro \(ReferenceFrameOfReferenceUID\)](#)
- [vtkTypeRevisionMacro \(vtkRTStructSetProperties, vtkObject\)](#)

Static Public Member Functions

- static [vtkRTStructSetProperties * New \(\)](#)

Protected Member Functions

- [vtkRTStructSetProperties \(\)](#)
- [~vtkRTStructSetProperties \(\)](#)

Protected Attributes

- [vtkRTStructSetPropertiesInternals * Internals](#)
- [char * ReferenceFrameOfReferenceUID](#)
- [char * ReferenceSeriesInstanceUID](#)
- [char * SeriesInstanceUID](#)
- [char * SOPInstanceUID](#)
- [char * StructureSetDate](#)
- [char * StructureSetLabel](#)
- [char * StructureSetName](#)
- [char * StructureSetTime](#)
- [char * StudyInstanceUID](#)

25.352.1 Detailed Description

Examples:

[GenerateRTSTRUCT.cxx](#).

25.352.2 Constructor & Destructor Documentation

25.352.2.1 [vtkRTStructSetProperties::vtkRTStructSetProperties \(\)](#) [protected]

25.352.2.2 [vtkRTStructSetProperties::~~vtkRTStructSetProperties \(\)](#) [protected]

25.352.3 Member Function Documentation

- 25.352.3.1 void vtkRTStructSetProperties::AddContourReferencedFrameOfReference (vtkIdType *pdnum*, const char * *classuid*, const char * *instanceuid*)
- 25.352.3.2 void vtkRTStructSetProperties::AddReferencedFrameOfReference (const char * *classuid*, const char * *instanceuid*)
- 25.352.3.3 void vtkRTStructSetProperties::AddStructureSetROI (int *roinumber*, const char * *refframerefid*, const char * *roiname*, const char * *ROIGenerationAlgorithm*, const char * *ROIDescription* = 0)
- 25.352.3.4 void vtkRTStructSetProperties::AddStructureSetROIObservation (int *refnumber*, int *observationnumber*, const char * *rtroiinterpretedtype*, const char * *roiinterpreter*, const char * *roiobservationlabel* = 0)
- 25.352.3.5 virtual void vtkRTStructSetProperties::Clear () [virtual]
- 25.352.3.6 virtual void vtkRTStructSetProperties::DeepCopy (vtkRTStructSetProperties * *p*) [virtual]
- 25.352.3.7 const char* vtkRTStructSetProperties::GetContourReferencedFrameOfReferenceClassUID (vtkIdType *pdnum*, vtkIdType *id*)
- 25.352.3.8 const char* vtkRTStructSetProperties::GetContourReferencedFrameOfReferenceInstanceUID (vtkIdType *pdnum*, vtkIdType *id*)
- 25.352.3.9 vtkIdType vtkRTStructSetProperties::GetNumberOfContourReferencedFrameOfReferences ()
- 25.352.3.10 vtkIdType vtkRTStructSetProperties::GetNumberOfContourReferencedFrameOfReferences (vtkIdType *pdnum*)
- 25.352.3.11 vtkIdType vtkRTStructSetProperties::GetNumberOfReferencedFrameOfReferences ()
- 25.352.3.12 vtkIdType vtkRTStructSetProperties::GetNumberOfStructureSetROIs ()
- 25.352.3.13 const char* vtkRTStructSetProperties::GetReferencedFrameOfReferenceClassUID (vtkIdType *id*)
- 25.352.3.14 const char* vtkRTStructSetProperties::GetReferencedFrameOfReferenceInstanceUID (vtkIdType *id*)
- 25.352.3.15 int vtkRTStructSetProperties::GetStructureSetObservationNumber (vtkIdType *id*)
- 25.352.3.16 const char* vtkRTStructSetProperties::GetStructureSetROIDescription (vtkIdType *id*)
- 25.352.3.17 const char* vtkRTStructSetProperties::GetStructureSetROIGenerationAlgorithm (vtkIdType)
- 25.352.3.18 const char* vtkRTStructSetProperties::GetStructureSetROIName (vtkIdType)
- 25.352.3.19 int vtkRTStructSetProperties::GetStructureSetROINumber (vtkIdType *id*)
- 25.352.3.20 const char* vtkRTStructSetProperties::GetStructureSetROIObservationLabel (vtkIdType *id*)
- 25.352.3.21 const char* vtkRTStructSetProperties::GetStructureSetROIRefFrameRefUID (vtkIdType)
- 25.352.3.22 const char* vtkRTStructSetProperties::GetStructureSetRTROIInterpretedType (vtkIdType *id*)

25.352.3.23 `static vtkRTStructSetProperties* vtkRTStructSetProperties::New ()` `[static]`

Examples:

[GenerateRTSTRUCT.cxx](#).

25.352.3.24 `void vtkRTStructSetProperties::PrintSelf (ostream & os, vtkIndent indent)`

25.352.3.25 `vtkRTStructSetProperties::vtkGetStringMacro (StructureSetLabel)`

25.352.3.26 `vtkRTStructSetProperties::vtkGetStringMacro (StructureSetName)`

25.352.3.27 `vtkRTStructSetProperties::vtkGetStringMacro (StructureSetDate)`

25.352.3.28 `vtkRTStructSetProperties::vtkGetStringMacro (StructureSetTime)`

25.352.3.29 `vtkRTStructSetProperties::vtkGetStringMacro (SOPInstanceUID)`

25.352.3.30 `vtkRTStructSetProperties::vtkGetStringMacro (StudyInstanceUID)`

25.352.3.31 `vtkRTStructSetProperties::vtkGetStringMacro (SeriesInstanceUID)`

25.352.3.32 `vtkRTStructSetProperties::vtkGetStringMacro (ReferenceSeriesInstanceUID)`

25.352.3.33 `vtkRTStructSetProperties::vtkGetStringMacro (ReferenceFrameOfReferenceUID)`

25.352.3.34 `vtkRTStructSetProperties::vtkSetStringMacro (StructureSetLabel)`

25.352.3.35 `vtkRTStructSetProperties::vtkSetStringMacro (StructureSetName)`

25.352.3.36 `vtkRTStructSetProperties::vtkSetStringMacro (StructureSetDate)`

25.352.3.37 `vtkRTStructSetProperties::vtkSetStringMacro (StructureSetTime)`

25.352.3.38 `vtkRTStructSetProperties::vtkSetStringMacro (SOPInstanceUID)`

25.352.3.39 `vtkRTStructSetProperties::vtkSetStringMacro (StudyInstanceUID)`

25.352.3.40 `vtkRTStructSetProperties::vtkSetStringMacro (SeriesInstanceUID)`

25.352.3.41 `vtkRTStructSetProperties::vtkSetStringMacro (ReferenceSeriesInstanceUID)`

25.352.3.42 `vtkRTStructSetProperties::vtkSetStringMacro (ReferenceFrameOfReferenceUID)`

25.352.3.43 `vtkRTStructSetProperties::vtkTypeRevisionMacro (vtkRTStructSetProperties , vtkObject)`

25.352.4 Member Data Documentation

25.352.4.1 `vtkRTStructSetPropertiesInternals* vtkRTStructSetProperties::Internals` `[protected]`

25.352.4.2 `char* vtkRTStructSetProperties::ReferenceFrameOfReferenceUID` `[protected]`

25.352.4.3 `char* vtkRTStructSetProperties::ReferenceSeriesInstanceUID` [protected]

25.352.4.4 `char* vtkRTStructSetProperties::SeriesInstanceUID` [protected]

25.352.4.5 `char* vtkRTStructSetProperties::SOPInstanceUID` [protected]

25.352.4.6 `char* vtkRTStructSetProperties::StructureSetDate` [protected]

25.352.4.7 `char* vtkRTStructSetProperties::StructureSetLabel` [protected]

25.352.4.8 `char* vtkRTStructSetProperties::StructureSetName` [protected]

25.352.4.9 `char* vtkRTStructSetProperties::StructureSetTime` [protected]

25.352.4.10 `char* vtkRTStructSetProperties::StudyInstanceUID` [protected]

The documentation for this class was generated from the following file:

- [vtkRTStructSetProperties.h](#)

25.353 gdcm::Waveform Class Reference

[Waveform](#) class.

```
#include <gdcmWaveform.h>
```

Public Member Functions

- [Waveform](#) ()

25.353.1 Detailed Description

[Waveform](#) class.

25.353.2 Constructor & Destructor Documentation

25.353.2.1 `gdcm::Waveform::Waveform ()` [inline]

The documentation for this class was generated from the following file:


- [gdcmWaveform.h](#)

25.354 gdcm::Writer Class Reference


[Writer](#) ala DOM (Document [Object](#) Model) This class is a non-validating writer, it will only performs well- formedness check only.

```
#include <gdcmWriter.h>
```

Inheritance diagram for gdcm::Writer:



Collaboration diagram for `gdcm::Writer`:



Public Member Functions

- [Writer](#) ()
- virtual [~Writer](#) ()
- void [CheckFileMetaInformationOff](#) ()
- void [CheckFileMetaInformationOn](#) ()
- [File](#) & [GetFile](#) ()
- void [SetCheckFileMetaInformation](#) (bool b)
Undocumented function, do not use (= leave default)
- void [SetFile](#) (const [File](#) &f)
Set/Get the DICOM file ([DataSet](#) + Header)

- void [SetFileName](#) (const char *filename_native)
Set the filename of DICOM file to write:
- void [SetStream](#) (std::ostream &output_stream)
Set user ostream buffer.
- virtual bool [Write](#) ()
Main function to tell the writer to write.

Protected Member Functions

- std::ostream * [GetStreamPtr](#) () const
- void [SetWriteDataSetOnly](#) (bool b)

Protected Attributes

- std::ofstream * [Ofstream](#)
- std::ostream * [Stream](#)

Friends

- class [StreamImageWriter](#)

25.354.1 Detailed Description

[Writer](#) ala DOM (Document [Object](#) Model) This class is a non-validating writer, it will only performs well- formedness check only.

Detailed description here To avoid GDCM being yet another broken DICOM lib we try to be user level and avoid writing illegal stuff (odd length, non-zero value for [Item](#) start/end length ...) Therefore you cannot (well unless you are really smart) write DICOM with even length tag. All the checks are consider basics:

- Correct Meta Information Header (see [gdcm::FileMetaInformation](#))
- Zero value for [Item](#) Length (0xfffe, 0xe00d/0xe0dd)
- Even length for any elements
- Alphabetical order for elements (garanteed by design of internals)
- 32bits [VR](#) will be rewritten with 00

Warning

[gdcm::Writer](#) cannot write a [DataSet](#) if no SOP Instance UID (0008,0018) is found, unless a [DICOMDIR](#) is being written out

See Also

[Reader DataSet File](#)

Examples:

[ChangeSequenceUltrasound.cxx](#), [ClinicalTrialAnnotate.cxx](#), [CreateJPIPDataSet.cxx](#), [DuplicatePCDE.cxx](#), [EncapsulateFileInRawData.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [HelloWorld.cxx](#), [LargeVRDSExplicit.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), [rle2img.cxx](#), and [StreamImageReaderTest.cxx](#).

25.354.2 Constructor & Destructor Documentation

25.354.2.1 `gdcm::Writer::Writer ()`

25.354.2.2 `virtual gdcm::Writer::~~Writer ()` `[virtual]`

25.354.3 Member Function Documentation

25.354.3.1 `void gdcm::Writer::CheckFileMetaInformationOff ()` `[inline]`

Examples:

[FixBrokenJ2K.cxx](#), and [HelloWorld.cxx](#).

25.354.3.2 `void gdcm::Writer::CheckFileMetaInformationOn ()` `[inline]`

25.354.3.3 `File& gdcm::Writer::GetFile ()` `[inline]`

Examples:

[CreateJPIPDataSet.cxx](#), [EncapsulateFileInRawData.cxx](#), [Extracting_All_Resolution.cxx](#), [Fake_Image_Using_Stream_Image_Writer.cxx](#), [GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), [iU22tomultisc.cxx](#), [pmsct_rgb1.cxx](#), [rle2img.cxx](#), and [StreamImageReaderTest.cxx](#).

25.354.3.4 `std::ostream* gdcm::Writer::GetStreamPtr () const` `[inline]`, `[protected]`

25.354.3.5 `void gdcm::Writer::SetCheckFileMetaInformation (bool b)` `[inline]`

Undocumented function, do not use (= leave default)

Examples:

[GenAllVR.cxx](#), [GenFakeIdentifyFile.cxx](#), and [PatchFile.cxx](#).

25.354.3.6 `void gdcm::Writer::SetFile (const File & f)` `[inline]`

Set/Get the DICOM file ([DataSet](#) + Header)

Examples:

[ChangeSequenceUltrasound.cxx](#), [ClinicalTrialAnnotate.cxx](#), [CompressImage.cxx](#), [DuplicatePCDE.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GenFakelImage.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [HelloWorld.cxx](#), [LargeVRDSExplicit.cxx](#), [MergeTwoFiles.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), and [rle2img.cxx](#).

25.354.3.7 void gdcm::Writer::SetFileName (const char * *filename_native*)

Set the filename of DICOM file to write:

Examples:

[ChangeSequenceUltrasound.cxx](#), [ClinicalTrialAnnotate.cxx](#), [CompressImage.cxx](#), [CreateARGBImage.cxx](#), [CreateCMYKImage.cxx](#), [CreateJPIPDataSet.cxx](#), [csa2img.cxx](#), [DuplicatePCDE.cxx](#), [EncapsulateFileInRawData.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GenAllVR.cxx](#), [GenFakelIdentifyFile.cxx](#), [GenFakelImage.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [HelloVizWorld.cxx](#), [HelloWorld.cxx](#), [iU22tomultisc.cxx](#), [LargeVRDSExplicit.cxx](#), [MergeTwoFiles.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), and [rle2img.cxx](#).

25.354.3.8 void gdcm::Writer::SetStream (std::ostream & *output_stream*) [inline]

Set user ostream buffer.

25.354.3.9 void gdcm::Writer::SetWriteDataSetOnly (bool *b*) [inline], [protected]

25.354.3.10 virtual bool gdcm::Writer::Write () [virtual]

Main function to tell the writer to write.

Reimplemented in [gdcm::PixmapWriter](#), [gdcm::ImageWriter](#), [gdcm::SurfaceWriter](#), and [gdcm::SegmentWriter](#).

Examples:

[ChangeSequenceUltrasound.cxx](#), [ClinicalTrialAnnotate.cxx](#), [CreateJPIPDataSet.cxx](#), [DuplicatePCDE.cxx](#), [EncapsulateFileInRawData.cxx](#), [FixBrokenJ2K.cxx](#), [FixJAIBugJPEGLS.cxx](#), [GenAllVR.cxx](#), [GenFakelIdentifyFile.cxx](#), [GenLongSeqs.cxx](#), [GenSeqs.cxx](#), [HelloWorld.cxx](#), [LargeVRDSExplicit.cxx](#), [PatchFile.cxx](#), [pmsct_rgb1.cxx](#), and [rle2img.cxx](#).

25.354.4 Friends And Related Function Documentation

25.354.4.1 friend class StreamImageWriter [friend]

25.354.5 Member Data Documentation

25.354.5.1 std::ofstream* gdcm::Writer::Ofstream [protected]

25.354.5.2 std::ostream* gdcm::Writer::Stream [protected]

The documentation for this class was generated from the following file:


- [gdcmWriter.h](#)

25.355 gdcM::XMLDictReader Class Reference


Class for representing a [XMLDictReader](#).

```
#include <gdcMXMLDictReader.h>
```

Inheritance diagram for gdcM::XMLDictReader:



Collaboration diagram for gdcM::XMLDictReader:



Public Member Functions

- [XMLDictReader](#) ()
- [~XMLDictReader](#) ()
- void [CharacterDataHandler](#) (const char *data, int length)
- void [EndElement](#) (const char *name)
- const [Dict](#) & [GetDict](#) ()
- void [StartElement](#) (const char *name, const char **atts)

Protected Member Functions

- void [HandleDescription](#) (const char **atts)

- void [HandleEntry](#) (const char **atts)

25.355.1 Detailed Description

Class for representing a [XMLDictReader](#).

Note

bla Will read the DICOMV3.xml file

25.355.2 Constructor & Destructor Documentation

25.355.2.1 `gdcm::XMLDictReader::XMLDictReader ()`

25.355.2.2 `gdcm::XMLDictReader::~~XMLDictReader ()` [inline]

25.355.3 Member Function Documentation

25.355.3.1 `void gdcm::XMLDictReader::CharacterDataHandler (const char * data, int length)` [virtual]

Reimplemented from [gdcm::TableReader](#).

25.355.3.2 `void gdcm::XMLDictReader::EndElement (const char * name)` [virtual]

Reimplemented from [gdcm::TableReader](#).

25.355.3.3 `const Dict& gdcm::XMLDictReader::GetDict ()` [inline]

25.355.3.4 `void gdcm::XMLDictReader::HandleDescription (const char ** atts)` [protected]

25.355.3.5 `void gdcm::XMLDictReader::HandleEntry (const char ** atts)` [protected]

25.355.3.6 `void gdcm::XMLDictReader::StartElement (const char * name, const char ** atts)` [virtual]

Reimplemented from [gdcm::TableReader](#).

The documentation for this class was generated from the following file:


- [gdcmXMLDictReader.h](#)

25.356 gdcm::XMLPrivateDictReader Class Reference


Class for representing a [XMLPrivateDictReader](#).

```
#include <gdcmXMLPrivateDictReader.h>
```

Inheritance diagram for `gdc::XMLPrivateDictReader`:



Collaboration diagram for `gdc::XMLPrivateDictReader`:



Public Member Functions

- [XMLPrivateDictReader](#) ()
- [~XMLPrivateDictReader](#) ()
- void [CharacterDataHandler](#) (const char *data, int length)
- void [EndElement](#) (const char *name)
- const [PrivateDict](#) & [GetPrivateDict](#) ()
- void [StartElement](#) (const char *name, const char **atts)

Protected Member Functions

- void [HandleDescription](#) (const char **atts)
- void [HandleEntry](#) (const char **atts)

25.356.1 Detailed Description

Class for representing a [XMLPrivateDictReader](#).

Note

bla Will read the Private.xml file

25.356.2 Constructor & Destructor Documentation

25.356.2.1 `gdcm::XMLPrivateDictReader::XMLPrivateDictReader ()`

25.356.2.2 `gdcm::XMLPrivateDictReader::~~XMLPrivateDictReader ()` `[inline]`

25.356.3 Member Function Documentation

25.356.3.1 `void gdcm::XMLPrivateDictReader::CharacterDataHandler (const char * data, int length)` `[virtual]`

Reimplemented from [gdcm::TableReader](#).

25.356.3.2 `void gdcm::XMLPrivateDictReader::EndElement (const char * name)` `[virtual]`

Reimplemented from [gdcm::TableReader](#).

25.356.3.3 `const PrivateDict& gdcm::XMLPrivateDictReader::GetPrivateDict ()` `[inline]`

25.356.3.4 `void gdcm::XMLPrivateDictReader::HandleDescription (const char ** atts)` `[protected]`

25.356.3.5 `void gdcm::XMLPrivateDictReader::HandleEntry (const char ** atts)` `[protected]`

25.356.3.6 `void gdcm::XMLPrivateDictReader::StartElement (const char * name, const char ** atts)` `[virtual]`

Reimplemented from [gdcm::TableReader](#).

The documentation for this class was generated from the following file:

- [gdcmXMLPrivateDictReader.h](#)

Chapter 26

File Documentation


26.1 gdcm2pnm.man File Reference

26.2 gdcm2vtk.man File Reference

26.3 gdcmAAbortPDU.h File Reference

```
#include "gdcmTypes.h"  
#include "gdcmBasePDU.h"
```

Include dependency graph for gdcmAAbortPDU.h:



Classes

- class `gdcm::network::AAbortPDU`

AAbortPDU Table 9-26 A-ABORT PDU FIELDS.

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.4 gdcmAAssociateACPDU.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmApplicationContext.h"
#include "gdcmPresentationContextAC.h"
#include "gdcmUserInfo.h"
#include "gdcmBasePDU.h"
#include <vector>
```

Include dependency graph for gdcmAAssociateACPDU.h:



Classes

- class [gdcm::network::AAssociateACPDU](#)
[AAssociateACPDU](#) Table 9-17 ASSOCIATE-AC PDU fields.

Namespaces

- [gdcm](#)
- [gdcm::network](#)

Constant Groups


- [gdcm](#)
- [gdcm::network](#)

26.5 gdcmAAssociateRJPDU.h File Reference

```
#include "gdcmTypes.h"
```

```
#include "gdcmBasePDU.h"
```

Include dependency graph for gdcmAAssociateRJPDU.h:



Classes

- class [gdcm::network::AAssociateRJPDU](#)
AAssociateRJPDU Table 9-21 ASSOCIATE-RJ PDU FIELDS.


Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

Include dependency graph for gdcAbstractSyntax.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdc::network::AbstractSyntax](#)
AbstractSyntax Table 9-14 ABSTRACT SYNTAX SUB-ITEM FIELDS.

Namespaces

- [gdc](#)
- [gdc::network](#)

Constant Groups

- [gdc](#)
- [gdc::network](#)


26.8 gdcmanon.man File Reference

26.9 gdcmAnonymizeEvent.h File Reference


```
#include "gdcmEvent.h"
```

```
#include "gdcmTag.h"
```

Include dependency graph for gdcmAnonymizeEvent.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::AnonymizeEvent](#)

AnonymizeEvent Special type of event triggered during the Anonymization process.

Namespaces

- **gdcm**


Constant Groups

- **gdcm**

26.10 gdcmAnonymizer.h File Reference

```
#include "gdcmFile.h"
#include "gdcmSubject.h"
#include "gdcmEvent.h"
#include "gdcmSmartPointer.h"
```

Include dependency graph for gdcmAnonymizer.h:



Classes

- class `gdcm::Anonymizer`

Anonymizer This class is a multi purpose anonymizer. It can work in 2 mode:

Namespaces

- **gdcm**


Constant Groups

- **gdcm**


26.11 gdcmApplicationContext.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmApplicationContext.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::ApplicationContext](#)

ApplicationContext Table 9-12 APPLICATION CONTEXT ITEM FIELDS Looks like Application Context can only be 64 bytes at max (see Figure 9-1 / PS 3.8 - 2009)

Namespaces


- [gdcm](#)
- [gdcm::network](#)

Constant Groups

- [gdc](#)
- [gdc::network](#)

26.12 gdcApplicationEntity.h File Reference

```
#include "gdcTypes.h"
#include <vector>
#include <stdlib.h>
Include dependency graph for gdcApplicationEntity.h:
```



Classes

- class [gdc::ApplicationEntity](#)
ApplicationEntity.

Namespaces

- [gdc](#)


Constant Groups

- [gdc](#)

26.13 gdcAReleaseRPPDU.h File Reference

```
#include "gdcTypes.h"
#include "gdcBasePDU.h"
```

Include dependency graph for gdcmAReleaseRPPDU.h:



Classes

- class [gdcm::network::AReleaseRPPDU](#)

[AReleaseRPPDU](#) Table 9-25 A-RELEASE-RP PDU fields.

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.14 gdcmAReleaseRQPDU.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmBasePDU.h"
```

Include dependency graph for gdcmAReleaseRQPDU.h:



Classes

- class [gdcm::network::AReleaseRQPDU](#)

AReleaseRQPDU Table 9-24 A-RELEASE-RQ PDU FIELDS.

Namespaces


- [gdcm](#)
- [gdcm::network](#)

Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.15 gdcmARTIMTimer.h File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::ARTIMTimer](#)

[ARTIMTimer](#) This file contains the code for the ARTIM timer.

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.16 gdcman1.h File Reference

```
#include "gdcmanTypes.h"
```

Include dependency graph for gdcman1.h:



Classes

- class [gdcman::ASN1](#)

Class for [ASN1](#).

Namespaces

- [gdcman](#)


Constant Groups

- [gdcman](#)

26.17 gdcmAsynchronousOperationsWindowSub.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmAsynchronousOperationsWindowSub.h:



Classes

- class [gdcm::network::AsynchronousOperationsWindowSub](#)

AsynchronousOperationsWindowSub PS 3.7 Table D.3-7 ASYNCHRONOUS OPERATIONS WINDOW SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)


26.18 gdcmAttribute.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmVR.h"
#include "gdcmTagToType.h"
#include "gdcmVM.h"
#include "gdcmElement.h"
#include "gdcmDataElement.h"
#include "gdcmDataSet.h"
#include "gdcmStaticAssert.h"
#include <string>
#include <vector>
#include <sstream>
```

Include dependency graph for gdcmAttribute.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::Attribute< Group, Element, TVR, TVM >`
Attribute class This class use template metaprograming tricks to let the user know when the template instanciation does not match the public dictionary.
- class `gdcm::Attribute< Group, Element, TVR, VM::VM1 >`

- class [gdcm::Attribute< Group, Element, TVR, VM::VM1_3 >](#)
- class [gdcm::Attribute< Group, Element, TVR, VM::VM1_8 >](#)
- class [gdcm::Attribute< Group, Element, TVR, VM::VM1_n >](#)
- class [gdcm::Attribute< Group, Element, TVR, VM::VM2_2n >](#)
- class [gdcm::Attribute< Group, Element, TVR, VM::VM2_n >](#)
- class [gdcm::Attribute< Group, Element, TVR, VM::VM3_3n >](#)
- class [gdcm::Attribute< Group, Element, TVR, VM::VM3_n >](#)
- class [gdcm::VRVLSize< T >](#)
- class [gdcm::VRVLSize< 0 >](#)
- class [gdcm::VRVLSize< 1 >](#)

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.19 gdcmAudioCodec.h File Reference

```
#include "gdcmCodec.h"
```

Include dependency graph for `gdcmAudioCodec.h`:



Classes

- class [gdcm::AudioCodec](#)
AudioCodec.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.20 gdcmBase64.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmBase64.h:



Classes

- class [gdcm::Base64](#)
Class for [Base64](#).

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


26.21 gdcmBaseCompositeMessage.h File Reference

```
#include "gdcmPresentationDataValue.h"
```


```
#include "gdcmBaseRootQuery.h"
```

```
#include <vector>
```

Include dependency graph for `gdcmBaseCompositeMessage.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::BaseCompositeMessage](#)

***BaseCompositeMessage** The Composite events described in section 3.7-2009 of the DICOM standard all use their own messages. These messages are constructed using Presentation Data Values, from section 3.8-2009 of the standard, and then fill in appropriate values in their datasets.*

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)


26.22 gdcmBasePDU.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmBasePDU.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::BasePDU](#)
BasePDU base class for PDUs.


Namespaces

- [gdcm](#)
- [gdcm::network](#)

Constant Groups

- [gdcm](#)
- [gdcm::network](#)

This graph shows which files directly or indirectly include this file:



Classes

- class [gdcml::BasicOffsetTable](#)
Class to represent a [BasicOffsetTable](#).

Namespaces

- [gdcml](#)

Constant Groups

- [gdcml](#)


Functions

- `std::ostream & gdcml::operator<< (std::ostream &os, const BasicOffsetTable &val)`


26.25 gdcmlBitmap.h File Reference

```
#include "gdcmlObject.h"
#include "gdcmlCurve.h"
#include "gdcmlDataElement.h"
#include "gdcmlLookupTable.h"
#include "gdcmlOverlay.h"
#include "gdcmlPhotometricInterpretation.h"
#include "gdcmlPixelFormat.h"
#include "gdcmlSmartPointer.h"
#include "gdcmlTransferSyntax.h"
#include <vector>
```

Include dependency graph for `gdcmBitmap.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::Bitmap`

Bitmap class A bitmap based image. Used as parent for both IconImage and the main Pixel Data **Image** It does not contains any World Space information (IPP, IOP)

Namespaces

- **gdcm**


Constant Groups

- **gdcm**

26.26 gdcmBitmapToBitmapFilter.h File Reference

```
#include "gdcmBitmap.h"
```


Include dependency graph for gdcmBoxRegion.h:



Classes

- class `gdcm::BoxRegion`

Class for manipulation box region This is a very simple implementation of the [Region](#) class. It only support 3D box type region. It assumes the 3D Box does not have a tilt Origin is as (0,0,0)

Namespaces

- `gdcm`

Constant Groups

- `gdcm`


26.28 gdcmByteBuffer.h File Reference

```


#include "gdcmTypes.h"
#include <vector>
#include <assert.h>
#include <string.h>

```

Include dependency graph for `gdcmByteBuffer.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::ByteBuffer`
ByteBuffer.

Namespaces


- `gdcm`

Constant Groups

- `gdcm`

26.29 gdcmByteSwap.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmSwapCode.h"
#include "gdcmByteSwap.txx"
Include dependency graph for gdcmByteSwap.h:
```



Classes

- class `gdcm::ByteSwap< T >`

ByteSwap.

Namespaces


- `gdcm`

Constant Groups

- `gdcm`

26.30 gdcmByteSwapFilter.h File Reference

```
#include "gdcmDataSet.h"
```



- class `gdcm::ByteSwapFilter`


ByteSwapFilter In place byte-swapping of a dataset **FIXME: FL status ??**

- gdc


- **gdc**

```
#include "gdcmValue.h"
#include "gdcmTrace.h"
#include "gdcmVL.h"
#include <vector>
#include <iterator>
#include <iomanip>
```


Include dependency graph for gdcmByteValue.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::ByteValue](#)
Class to represent binary value (array of bytes)

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

26.32 gdcmCEchoMessages.h File Reference

```
#include "gdcmBaseCompositeMessage.h"
```

[illegible]

- class `gdcmm::network::CEchoRQ`
CEchoRQ this file defines the messages for the cecho action.
- class `gdcmm::network::CEchoRSP`
CEchoRSP this file defines the messages for the cecho action.

- `gdcm`
- `gdcm::network`

- `gdcm`
- `gdcm::network`

```
#include "gdcmBaseCompositeMessage.h"
#include "gdcmBaseRootQuery.h"
```

- class `gdcmm::network::CFindCancelRQ`
CFindCancelRQ this file defines the messages for the cfind action.
- class `gdcmm::network::CFindRQ`
CFindRQ this file defines the messages for the cfind action.
- class `gdcmm::network::CFindRSP`
CFindRSP this file defines the messages for the cfind action.

- `gdcm`
- `gdcm::network`

- `gdcm`
- `gdcm::network`

```
#include "gdcmBaseCompositeMessage.h"
#include "gdcmBaseRootQuery.h"
```


- class `gdcm::network::CMoveCancelRq`
- class `gdcm::network::CMoveRQ`
CMoveRQ this file defines the messages for the cmove action.
- class `gdcm::network::CMoveRSP`
CMoveRSP this file defines the messages for the cmove action.

- `gdc`
- `gdc::network`


- `gdcm`
- `gdcm::network`

```
#include "gdcmCoder.h"
#include "gdcmDecoder.h"
```

Include dependency graph for gdcmCodec.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Codec](#)
Codec class.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.36 gdcmCoder.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmDataElement.h"
```

Include dependency graph for `gdcmCoder.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::Coder`
Coder.

Namespaces

- `gdcm`


Constant Groups

- `gdcm`

26.37 gdcmCodeString.h File Reference

```
#include "gdcmString.h"
```

Include dependency graph for gdcmCodeString.h:



Classes

- class [gdcm::CodeString](#)

CodeString This is an implementation of DICOM VR: CS The ctor will properly Trim so that operator== is correct.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


Functions

- bool [gdcm::operator!=](#) (const CodeString &ref, const CodeString &cs)
- std::ostream & [gdcm::operator<<](#) (std::ostream &os, const CodeString &str)
- bool [gdcm::operator==](#) (const CodeString &ref, const CodeString &cs)


26.38 gdcmCommand.h File Reference

```
#include "gdcmSubject.h"
```

Include dependency graph for `gdcMCommand.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcM::Command`
Command superclass for callback/observer methods.
- class `gdcM::MemberCommand< T >`
Command subclass that calls a pointer to a member function.
- class `gdcM::SimpleMemberCommand< T >`
Command subclass that calls a pointer to a member function.

- **gdcm**

- `gdcm`

[illegible]

- gdc

- **gdcm**

Generated on Mon Nov 4 2013 10:59:18 for GDCM by Doxygen

[illegible]

- class `gdcm::CompositeNetworkFunctions`

Composite Network Functions These functions provide a generic API to the DICOM functions implemented in GDCM. Advanced users can use this code as a template for building their own versions of these functions (for instance, to provide progress bars or some other way of handling returned query information), but for most users, these functions should be sufficient to interface with a PACS to a local machine. Note that these functions are not contained within a static class or some other class-style interface, because multiple connections can be instantiated in the same program. The DICOM standard is much more function oriented rather than class oriented in this instance, so the design of this API reflects that functional approach. These functions implements the following SCU operations:

- **gdcm**


- gdc

- class `gdcm::ConstCharWrapper`

Do not use me.

- **gdcm**

Include dependency graph for gdcmCryptographicMessageSyntax.h:



Classes

- class [gdcm::CryptographicMessageSyntax](#)

Class for [CryptographicMessageSyntax](#) encryption. This is just a simple wrapper around openssl PKCS7_encrypt functionalities.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

26.46 gdcmCSAElement.h File Reference

```

#include "gdcmTag.h"
#include "gdcmVM.h"
#include "gdcmVR.h"
#include "gdcmByteValue.h"
#include "gdcmSmartPointer.h"

```



Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const CSAElement &val)`

26.47 gdcmCSAHeader.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmDataSet.h"
#include "gdcmCSAElement.h"
```

Include dependency graph for `gdcmCSAHeader.h`:



Classes

- class `gdcm::CSAHeader`
Class for [CSAHeader](#).

Namespaces

- `gdcm`

Constant Groups

- `gdcm`


Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const CSAHeader &d)`


26.48 gdcmCSAHeaderDict.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmTag.h"
#include "gdcmCSAHeaderDictEntry.h"
#include <iostream>
#include <iomanip>
#include <set>
#include <exception>
```

Include dependency graph for gdcmCSAHeaderDict.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::CSAHeaderDict](#)
Class to represent a map of *CSAHeaderDictEntry*.
- class [gdcm::CSAHeaderDictException](#)

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const CSAHeaderDict &val)`


26.49 gdcmCSAHeaderDictEntry.h File Reference

```
#include "gdcmVR.h"
#include "gdcmVM.h"
#include <string>
#include <iostream>
#include <iomanip>
#include <cstring>
```

Include dependency graph for `gdcmCSAHeaderDictEntry.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcml::CSAHeaderDictEntry](#)

Class to represent an Entry in the [Dict](#). Does not really exist within the DICOM definition, just a way to minimize storage and have a mapping from [gdcml::Tag](#) to the needed information.

Namespaces

- [gdcml](#)

Constant Groups

- [gdcml](#)


Functions

- `std::ostream & gdcml::operator<< (std::ostream &os, const CSAHeaderDictEntry &val)`

26.50 gdcmlCStoreMessages.h File Reference

```
#include "gdcmlBaseCompositeMessage.h"
```

Include dependency graph for gdcmCStoreMessages.h:



Classes

- class [gdcm::network::CStoreRQ](#)
CStoreRQ this file defines the messages for the cecho action.
- class [gdcm::network::CStoreRSP](#)
CStoreRSP this file defines the messages for the cecho action.

Namespaces

- [gdcm](#)
- [gdcm::network](#)

Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.51 gdcmCurve.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmObject.h"
#include <vector>
```

- class `adcm::Curve`

- Curve** class to handle element, complete **Curve** data with in **Curve**. This is deprecated and fully defined in **Curve** **Curve**.


- [adem](#)

- [adem](#)


26.52 gdcmDataElement.h File Reference

```
#include "gdcmTag.h"
#include "gdcmVL.h"
#include "gdcmVR.h"
#include "gdcmByteValue.h"
#include "gdcmSmartPointer.h"
#include <set>
```

Include dependency graph for gdcmDataElement.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::DataElement](#)
Class to represent a Data [Element](#) either Implicit or Explicit.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


Functions

- bool `gdcm::operator!=` (const DataElement &lhs, const DataElement &rhs)
- std::ostream & `gdcm::operator<<` (std::ostream &os, const DataElement &val)


26.53 gdcmDataEvent.h File Reference

```
#include "gdcmEvent.h"
```

Include dependency graph for gdcmDataEvent.h:




This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::DataEvent`
DataEvent.

Include dependency graph for gdcmDataSetHelper.h:



Classes

- class [gdcm::DataSetHelper](#)
DataSetHelper (internal class, not intended for user level)

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


26.57 gdcmDecoder.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmDataElement.h"
```


26.58 gdcmDefinedTerms.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmDefinedTerms.h:



Classes

- class [gdcm::DefinedTerms](#)

Defined Terms are used when the specified explicit Values may be extended by implementors to include additional new Values. These new Values shall be specified in the Conformance Statement (see PS 3.2) and shall not have the same meaning as currently defined Values in this standard. A Data [Element](#) with Defined Terms that does not contain a [Value](#) equivalent to one of the Values currently specified in this standard shall not be considered to have an invalid value. Note: Interpretation [Type](#) ID (4008,0210) is an example of a Data [Element](#) having Defined Terms. It is defined to have a [Value](#) that may be one of the set of standard Values; REPORT or AMENDMENT (see PS 3.3). Because this Data [Element](#) has Defined Terms other Interpretation [Type](#) IDs may be defined by the implementor.

Namespaces


- [gdcm](#)

Constant Groups


- [gdcm](#)

26.59 gdcmDeflateStream.h File Reference


```
#include "zipstreamimpl.h"
```



Include dependency graph for gdcMDefs.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Defs](#)

FIXME I do not like the name 'Defs'.

Namespaces


- [gdcm](#)

Constant Groups

- [gdcm](#)

26.61 gdcmDeltaEncodingCodec.h File Reference

```
#include "gdcmImageCodec.h"
```



- class `gdcm::DeltaEncodingCodec`
DeltaEncodingCodec compression used by some private vendor.


- DeltaEncodingCodec* compression used by some private vendor.

- **gdc**

- **gdcm**

```
#include "gdcmFileSet.h"
```

Include dependency graph for gdcmDICOMDIR.h:



Classes

- class [gdcm::DICOMDIR](#)
DICOMDIR class.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.63 gdcmDICOMDIRGenerator.h File Reference

```
#include "gdcmDirectory.h"
#include "gdcmTag.h"
#include <utility>
```

Include dependency graph for `gdcmDICOMDIRGenerator.h`:



Classes

- class [gdcm::DICOMDIRGenerator](#)

[DICOMDIRGenerator](#) class This is a STD-GEN-CD [DICOMDIR](#) generator. ref: PS 3.11-2008 Annex D (Normative) - General Purpose CD-R and DVD Interchange Profiles.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

26.64 gdcmDict.h File Reference

```

#include "gdcmTypes.h"
#include "gdcmTag.h"
#include "gdcmPrivateTag.h"
#include "gdcmDictEntry.h"
#include "gdcmSystem.h"
#include <iostream>
#include <iomanip>
#include <map>

```



```

graph BT
    gdcmDicts[gdcmDicts.h] --> gdcmDict[gdcmDict.h]
    gdcmXMLDictReader[gdcmXMLDictReader.h] --> gdcmDict
    gdcmXMLPrivateDictReader[gdcmXMLPrivateDictReader.h] --> gdcmDict
    gdcmStringFilter[gdcmStringFilter.h] --> gdcmDicts
    gdcmPythonFilter[gdcmPythonFilter.h] --> gdcmDicts
  
```

- class `gdcm::Dict`
Class to represent a map of `DictEntry`.
- class `gdcm::PrivateDict`
Private `Dict`.

- gdc


- **gdcm**

- `std::ostream & gdcmm::operator<< (std::ostream &os, const Dict &val)`
- `std::ostream & gdcmm::operator<< (std::ostream &os, const PrivateDict &val)`

26.65 gdcmDictConverter.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmVR.h"
#include "gdcmVM.h"
#include <string>
```

Include dependency graph for gdcmDictConverter.h:



Classes

- class [gdcm::DictConverter](#)
Class to convert a .dic file into something else:

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.66 gdcmDictEntry.h File Reference

```
#include "gdcmVR.h"
#include "gdcmVM.h"
#include <string>
#include <iostream>
#include <iomanip>
```

Include dependency graph for gdcmDictEntry.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::DictEntry](#)

Class to represent an Entry in the [Dict](#). Does not really exist within the DICOM definition, just a way to minimize storage and have a mapping from [gdcm::Tag](#) to the needed information.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

[illegible]

```
graph BT; gdcStringFilter.h --> gdcDicts.h; gdcPythonFilter.h --> gdcDicts.h
```

- class `gdcm::Dicts`
Class to manipulate the sum of knowledge (all the dict user load)

- **gdcm**

- **gdcm**


- `std::ostream & gdcm::operator<< (std::ostream &os, const Dicts &d)`

26.69 gdcmDiff.man File Reference

26.70 gdcmDIMSE.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmDIMSE.h:



Classes

- class [gdcm::network::CEchoRQ](#)
CEchoRQ this file defines the messages for the cecho action.
- class [gdcm::network::CEchoRSP](#)
CEchoRSP this file defines the messages for the cecho action.
- class [gdcm::network::CFind](#)
- class [gdcm::network::DIMSE](#)
DIMSE PS 3.7 - 2009 Annex E [Command](#) Dictionary (Normative) E.1 REGISTRY OF DICOM COMMAND ELEMENTS
[Table E.1-1](#) COMMAND FIELDS (PART 1)

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.71 gdcmDirectionCosines.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmDirectionCosines.h:



Classes

- class [gdcm::DirectionCosines](#)
class to handle [DirectionCosines](#)

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.72 gdcmDirectory.h File Reference

```
#include "gdcmTypes.h"
#include <string>
#include <vector>
#include <iostream>
#include <assert.h>
```

Include dependency graph for `gdcmDirectory.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Directory](#)
Class for manipulation directories.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const Directory &d)`

26.73 gdcmDirectoryHelper.h File Reference

```
#include "gdcmDirectory.h"
#include "gdcmDataSet.h"
```


Include dependency graph for gdcmDirectoryHelper.h:



Classes

- class [gdcm::DirectoryHelper](#)

[DirectoryHelper](#) this class is designed to help mitigate some of the commonly performed operations on directories. namely: 1) the ability to determine the number of series in a directory by what type of series is present 2) the ability to find all ct series in a directory 3) the ability to find all mr series in a directory 4) to load a set of DataSets from a series that's already been sorted by the IPP sorter 5) For rtstruct stuff, you need to know the sopinstanceuid of each z plane, so there's a retrieval function for that 6) then a few other functions for rtstruct writeouts.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.74 gdcmDummyValueGenerator.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for `gdcmDummyValueGenerator.h`:



Classes

- class [gdcm::DummyValueGenerator](#)

Class for generating dummy value.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

26.75 gdcmdump.man File Reference

26.76 gdcmDumper.h File Reference

```
#include "gdcmPrinter.h"
```

- class `gdcm::Dumper`
Codec class.

- **gdcm**


- `gdcm`

```
#include "gdcmTypes.h"
#include "gdcmVR.h"
#include "gdcmTag.h"
#include "gdcmVM.h"
#include "gdcmByteValue.h"
#include "gdcmDataElement.h"
#include "gdcmSwapper.h"
#include <string>
#include <vector>
#include <sstream>
#include <limits>
#include <cmath>
#include <cstring>
```


- **gdcm**

- ignore_char const `gdcmm::backslash` ('\\')
- `std::istream & gdcmm::operator>>` (`std::istream &in`, ignore_char const &ic)
- `template<typename Float >`
`std::string gdcmm::to_string` (Float data)

Include dependency graph for gdcmEncapsulatedDocument.h:



- class `gdcm::EncapsulatedDocument`
EncapsulatedDocument.


- **gdcm**

- **gdcm**

26.79 gdcmEnumeratedValues.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmEnumeratedValues.h:



Classes

- class [gdcm::EnumeratedValues](#)

Element. A Data [Element](#) with Enumerated Values that does not have a [Value](#) equivalent to one of the Values specified in this standard has an invalid value within the scope of a specific Information Object/SOP Class definition. Note:

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.80 gdcmEvent.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmEvent.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::AbortEvent`
- class `gdcm::AnyEvent`
- class `gdcm::EndEvent`
- class `gdcm::Event`
superclass for callback/observer methods
- class `gdcm::ExitEvent`
- class `gdcm::InitializeEvent`
- class `gdcm::IterationEvent`
- class `gdcm::ModifiedEvent`
- class `gdcm::NoEvent`
- class `gdcm::StartEvent`
- class `gdcm::UserEvent`

Namespaces

- `gdcm`

Constant Groups

- [gdc](#)

Macros

- `#define gdcEventMacro(classname, super)`

Functions

- `std::ostream & gdc::operator<< (std::ostream &os, Event &e)`

Generic inserter operator for [Event](#) and its subclasses.

26.80.1 Macro Definition Documentation

26.80.1.1 `#define gdcEventMacro(classname, super)`


Value:

```
\
class classname : public super { \
public: \
    typedef classname Self; \
    typedef super Superclass; \
    classname() {} \
    virtual ~classname() {} \
    virtual const char * GetEventName() const { return #classname; } \
    virtual bool CheckEvent(const ::gdc::Event* e) const \
    { return dynamic_cast<const Self*>(e) ? true : false; } \
    virtual ::gdc::Event* MakeObject() const \
    { return new Self; } \
    classname(const Self&s) : super(s){}; \
private: \
    void operator=(const Self&); \
}
```


26.81 [gdcException.h](#) File Reference

```
#include <cassert>
#include <cstdlib>
#include <exception>
#include <sstream>
#include <stdexcept>
#include <string>
```


Include dependency graph for gdcmException.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Exception](#)
Exception.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

26.82 gdcmExplicitDataElement.h File Reference


```
#include "gdcmDataElement.h"
#include "gdcmExplicitDataElement.txx"
```


- class `gdc::ExplicitImplicitDataElement`
Class to read/write a `DataElement` as ExplicitImplicit Data `Element`.

- **gdcm**

- **gdcm**

```
#include "gdcmFile.h"
Include dependency graph for gdcmFiducials.h:
```



Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const File &val)`

26.86 gdcmFileAnonymizer.h File Reference

```
#include "gdcmSubject.h"
#include "gdcmEvent.h"
#include "gdcmTag.h"
#include "gdcmVL.h"
```

Include dependency graph for gdcmFileAnonymizer.h:



Classes

- class [gdcm::FileAnonymizer](#)
FileAnonymizer.

Namespaces

- [gdcm](#)

- class `gdcm::FileExplicitFilter`

Namespaces

- **gdcm**

- gdc

```
#include "gdcmPreamble.h"
#include "gdcmDataSet.h"
#include "gdcmDataElement.h"
#include "gdcmMediaStorage.h"
#include "gdcmTransferSyntax.h"
#include "gdcmExplicitDataElement.h"
```

[illegible]

- class `gdcm::FileMetaInformation`
Class to represent a [File](#) Meta Information.


- [gdc](#)

- [gdc](#)

- `std::ostream & qdcm::operator<< (std::ostream &os, const FileMetaInformation &val)`

```
#include "gdcmTypes.h"
#include <string>
```


Include dependency graph for gdcmFilename.h:



Classes

- class [gdcm::Filename](#)

Class to manipulate file name's.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


26.91 gdcmFilenameGenerator.h File Reference

```

#include "gdcmTypes.h"
#include <string>
#include <vector>

```

Include dependency graph for `gdcmlFilenameGenerator.h`:



Classes

- class `gdcml::FilenameGenerator`

FilenameGenerator.

Namespaces

- `gdcml`


Constant Groups

- `gdcml`


26.92 gdcmlFileSet.h File Reference

```
#include "gdcmlFile.h"
#include <vector>
```

Include dependency graph for gdcmFileSet.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::FileSet](#)

File-set: A File-set is a collection of DICOM Files (and possibly non-DICOM Files) that share a common naming space within which [File](#) IDs are unique.

Namespaces


- [gdcm](#)

Constant Groups


- [gdcm](#)

- `std::ostream & gdcm::operator<< (std::ostream &os, const FileSet &f)`

```
#include "gdcmBaseRootQuery.h"
Include dependency graph for gdcmFindPatientRootQuery.h:
```



This graph shows which files directly or indirectly include this file:



- class `gdcm::FindPatientRootQuery`

PatientRootQuery contains: the class which will produce a dataset for c-find with patient root.

Namespaces

- **gdcm**


Constant Groups

- **gdcm**

26.94 gdcFindStudyRootQuery.h File Reference

```
#include "gdcmBaseRootQuery.h"
```

Include dependency graph for `gdcMFindStudyRootQuery.h`:



Classes

- class `gdcm::FindStudyRootQuery`

FindStudyRootQuery contains: the class which will produce a dataset for C-FIND with study root.

Namespaces

- **gdcm**


Constant Groups

- **gdcm**


26.95 gdcmFragment.h File Reference

```
#include "gdcmDataElement.h"
```

```
#include "gdcmByteValue.h"
#include "gdcmSmartPointer.h"
#include "gdcmParseException.h"
Include dependency graph for gdcmFragment.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Fragment](#)
Class to represent a *Fragment*.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions


- `std::ostream & gdcm::operator<< (std::ostream &os, const Fragment &val)`

26.96 gdcmgendir.man File Reference

26.97 gdcmGlobal.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmGlobal.h:



Classes

- class [gdcm::Global](#)
Global.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions

- `std::ostream & gdcmm::operator<< (std::ostream &os, const Global &g)`


Variables

- static Global `gdcmm::GlobalInstance`

26.98 gdcmmGroupDict.h File Reference

```
#include "gdcmmTypes.h"
#include <assert.h>
#include <vector>
#include <string>
#include <iostream>
#include <iomanip>
```

Include dependency graph for `gdcmmGroupDict.h`:



Classes

- class `gdcmm::GroupDict`
Class to represent the mapping from group number to its abbreviation and name.

Namespaces

- `gdcmm`

Constant Groups

- `gdcmm`

Functions

- `std::ostream & gdcmm::operator<< (std::ostream &_os, const GroupDict &_val)`

- class `gdcm::IconImageGenerator`


Namespaces

- ## Constant Groups

- ## 26.102 gdcmlImage.h File Reference

Generated on Mon Nov 4 2013 10:59:18 for GDCM by Doxygen

Include dependency graph for `gdcmImageChangePhotometricInterpretation.h`:



Classes

- class [gdcm::ImageChangePhotometricInterpretation](#)

[ImageChangePhotometricInterpretation](#) class Class to change the Photometric Interpretation of an input DICOM.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.105 gdcmImageChangePlanarConfiguration.h File Reference

```
#include "gdcmImageToImageFilter.h"
```

Include dependency graph for gdcmImageChangePlanarConfiguration.h:



Classes

- class [gdcm::ImageChangePlanarConfiguration](#)

ImageChangePlanarConfiguration class Class to change the Planar configuration of an input DICOM By default it will change into the more usual representation: PlanarConfiguration = 0.

Namespaces


- [gdcm](#)

Constant Groups

- [gdcm](#)

26.106 gdcmImageChangeTransferSyntax.h File Reference

```
#include "gdcmImageToImageFilter.h"
#include "gdcmTransferSyntax.h"
```




- class `gdcm::ImageChangeTransferSyntax`

- **gdcm**

- **gdcm**

```
#include "gdcmCodec.h"
#include "gdcmPhotometricInterpretation.h"
#include "gdcmLookupTable.h"
#include "gdcmSmartPointer.h"
#include "gdcmPixelFormat.h"
```


Include dependency graph for gdcmImageCodec.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::ImageCodec](#)
ImageCodec.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.108 gdcmImageConverter.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for `gdcmImageConverter.h`:



Classes

- class [gdcm::ImageConverter](#)

Image Converter.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.109 gdcmImageFragmentSplitter.h File Reference

```
#include "gdcmImageToImageFilter.h"
```

Include dependency graph for gdcmImageFragmentSplitter.h:



Classes

- class [gdcm::ImageFragmentSplitter](#)

[ImageFragmentSplitter](#) class For single frame image, DICOM standard allow splitting the frame into multiple fragments.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.110 gdcmImageHelper.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmTag.h"
#include <vector>
#include "gdcmPixelFormat.h"
#include "gdcmPhotometricInterpretation.h"
#include "gdcmSmartPointer.h"
#include "gdcmLookupTable.h"
```

Include dependency graph for `gdcmImageHelper.h`:



Classes

- class `gdcm::ImageHelper`

ImageHelper (internal class, not intended for user level)

Namespaces

- `gdcm`


Constant Groups

- `gdcm`


26.111 gdcmImageReader.h File Reference

```
#include "gdcmPixmapReader.h"
#include "gdcmImage.h"
```

Include dependency graph for gdcmImageReader.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::ImageReader](#)
ImageReader.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.112 gdcmImageRegionReader.h File Reference

```
#include "gdcmImageReader.h"
#include "gdcmImage.h"
#include "gdcmRegion.h"
```

Include dependency graph for gdcmImageRegionReader.h:



Classes

- class [gdcm::ImageRegionReader](#)
ImageRegionReader.

Namespaces


- [gdcm](#)

Constant Groups


- [gdcm](#)

26.113 gdcmImageToImageFilter.h File Reference


```
#include "gdcmPixmapToPixmapFilter.h"
```

Include dependency graph for gdcmImplementationClassUIDSub.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::ImplementationClassUIDSub](#)

ImplementationClassUIDSub PS 3.7 [Table D.3-1](#) IMPLEMENTATION CLASS UID SUB-ITEM FIELDS (A-ASSOCIATE--RQ)

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.117 gdcmImplementationUIDSub.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmImplementationUIDSub.h:



Classes

- class [gdcm::network::ImplementationUIDSub](#)
ImplementationUIDSub Table D.3-2 IMPLEMENTATION UID SUB-ITEM FIELDS (A-ASSOCIATE-AC)

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)


26.118 gdcmImplementationVersionNameSub.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmImplementationVersionNameSub.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::ImplementationVersionNameSub](#)

ImplementationVersionNameSub Table D.3-3 IMPLEMENTATION VERSION NAME SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

Namespaces

- [gdcm](#)
- [gdcm::network](#)

Constant Groups


- [gdcm](#)
- [gdcm::network](#)

26.119 gdcmImplicitDataElement.h File Reference

```
#include "gdcmDataElement.h"
```

```
#include "gdcmImplicitDataElement.txx"
```

Include dependency graph for `gdcmImplicitDataElement.h`:



Classes

- class [gdcm::ImplicitDataElement](#)
Class to represent an Implicit *VR* Data *Element*.

Namespaces

- [gdcm](#)

Constant Groups


- [gdcm](#)

26.120 gdcminfo.man File Reference


26.121 gdcmIOD.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmTag.h"
#include "gdcmIODEntry.h"
#include <vector>
```

Include dependency graph for gdcmIOD.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcml::IOD](#)
Class for representing a [IOD](#).

Namespaces

- [gdcml](#)

Constant Groups

- [gdcml](#)


Functions

- `std::ostream & gdcml::operator<< (std::ostream &_os, const IOD &_val)`


26.122 gdcmIODEntry.h File Reference

```
#include "gdcmUsage.h"  
#include "gdcmType.h"  
#include <string>
```

Include dependency graph for gdcmIODEntry.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcml::IODEntry](#)
Class for representing a [IODEntry](#).

Namespaces

- [gdcml](#)

Constant Groups

- [gdcml](#)


Functions

- `std::ostream & gdcml::operator<< (std::ostream &_os, const IODEntry &_val)`


26.123 gdcmIODs.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmIOD.h"
#include <map>
```

Include dependency graph for gdcmIODs.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::IODs](#)
Class for representing a IODs.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions

- `std::ostream & gdcm::operator<< (std::ostream &_os, const IODs &_val)`


26.124 gdcmIPPSorter.h File Reference

```
#include "gdcmSorter.h"
```

```
#include <vector>
```

```
#include <string>
```

Include dependency graph for `gdcmIPPSorter.h`:



Classes

- class [gdcm::IPPSorter](#)

IPPSorter Implement a simple **Image Position (Patient)** sorter, along the **Image Orientation (Patient)** direction. This algorithm does NOT support duplicate and will FAIL in case of duplicate IPP.

Namespaces

- **gdcm**


Constant Groups

- **gdcm**


26.125 gdcmltem.h File Reference

```
#include "gdcmDataElement.h"
#include "gdcmDataSet.h"
#include "gdcmParseException.h"
#include "gdcmSwapper.h"
#include "gdcmItem.hxx"
```

Include dependency graph for gdcmlItem.h:



This graph shows which files directly or indirectly include this file:



Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.127 gdcmJPEG16Codec.h File Reference

```
#include "gdcmJPEGCodec.h"
```

Include dependency graph for gdcmJPEG16Codec.h:



Classes

- class [gdcm::JPEG16Codec](#)
Class to do JPEG 16bits (lossless)


Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Include dependency graph for gdcmJPEG8Codec.h:



Classes

- class [gdcm::JPEG8Codec](#)

Class to do JPEG 8bits (lossy & lossless)

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.130 gdcmJPEGCodec.h File Reference

```
#include "gdcmImageCodec.h"
```

Include dependency graph for `gdcmJPEGCodec.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::JPEGCodec](#)

JPEG codec Class to do JPEG (8bits, 12bits, 16bits lossy & lossless). It redispach in between the different codec implementation: [gdcm::JPEG8Codec](#), [gdcm::JPEG12Codec](#) & [gdcm::JPEG16Codec](#) It also support inconsistency in between DICOM header and JPEG compressed stream [ImageCodec](#) implementation for the JPEG case.


Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


```
#include "gdcmImageCodec.h"
Include dependency graph for gdcmJPEGLSCodec.h:
```



- class `gdcm::JPEGLSCodec`

JPEG-LS.

- **gdcm**

- **gdcm**

```
#include "gdcmImageCodec.h"
```




- KAKADUCodec.

- **gdcm**


- **gdcm**

```
#include "gdcmException.h"
#include "gdcmTrace.h"
```

Include dependency graph for gdcmLegacyMacro.h:



This graph shows which files directly or indirectly include this file:



Macros

- `#define GDCM_LEGACY(method) method;`
- `#define GDCM_LEGACY_BODY(method, version) gdcmWarningMacro(#method " was deprecated for " version " and will be removed in a future version.")`
- `#define GDCM_LEGACY_REPLACED_BODY(method, version, replace) gdcmWarningMacro(#method " was deprecated for " version " and will be removed in a future version. Use " #replace " instead.")`

26.133.1 Macro Definition Documentation

26.133.1.1 `#define GDCM_LEGACY(method) method;`


26.133.1.2 `#define GDCM_LEGACY_BODY(method, version) gdcmWarningMacro(#method " was deprecated for " version " and will be removed in a future version.")`

26.133.1.3 `#define GDCM_LEGACY_REPLACED_BODY(method, version, replace) gdcmWarningMacro(#method " was deprecated for " version " and will be removed in a future version. Use " #replace " instead.")`

26.134 gdcmLO.h File Reference

```
#include "gdcmString.h"
```

Include dependency graph for `gdcmLO.h`:



Classes

- class `gdcm::LO`

LO.

Namespaces

- `gdcm`

Constant Groups

- `gdcm`


26.135 `gdcmLookupTable.h` File Reference

```


#include "gdcmTypes.h"
#include "gdcmObject.h"
#include <stdlib.h>

```

Include dependency graph for gdcmLookupTable.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::LookupTable](#)
LookupTable class.

Namespaces

- [gdcm](#)

Constant Groups


- [gdcm](#)

26.136 gdcmMacro.h File Reference


```
#include "gdcmTypes.h"
```

```
#include "gdcmTag.h"
#include "gdcmMacroEntry.h"
#include <map>
#include <vector>
```

Include dependency graph for gdcmMacro.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Macro](#)
Class for representing a [Macro](#).

Namespaces

- [gdcm](#)

Constant Groups


- [gdcm](#)

Functions


- `std::ostream & gdcm::operator<< (std::ostream &_os, const Macro &_val)`

26.137 gdcmMacroEntry.h File Reference

```
#include "gdcmModuleEntry.h"  
Include dependency graph for gdcmMacroEntry.h:
```



This graph shows which files directly or indirectly include this file:



Macros

- `#define` [GDCMMACROENTRY_H](#)


26.137.1 Macro Definition Documentation

26.137.1.1 `#define` GDCMMACROENTRY_H


26.138 gdcmMacros.h File Reference

```
#include "gdcmTypes.h"  
#include "gdcmMacro.h"  
#include <map>
```

Include dependency graph for `gdcmMacros.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Macros](#)

Class for representing a [Modules](#).

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


Functions

- `std::ostream & gdcm::operator<< (std::ostream &_os, const Macros &_val)`


26.139 gdcmMaximumLengthSub.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmMaximumLengthSub.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdc::network::MaximumLengthSub](#)

MaximumLengthSub Annex D Table D.1-1 MAXIMUM LENGTH SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

Namespaces

- [gdc](#)
- [gdc::network](#)


Constant Groups

- [gdc](#)
- [gdc::network](#)

26.140 gdcMD5.h File Reference

```
#include "gdcTypes.h"
```

Include dependency graph for gdcmMD5.h:



Classes

- class [gdcm::MD5](#)

Class for MD5.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.141 gdcmMediaStorage.h File Reference

```
#include "gdcmTransferSyntax.h"
```

Include dependency graph for `gdcmMediaStorage.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::MediaStorage`
MediaStorage.

Namespaces

- `gdcm`

Constant Groups

- `gdcm`

Functions


- `std::ostream & gdcm::operator<< (std::ostream &_os, const MediaStorage &ms)`

26.142 gdcmMeshPrimitive.h File Reference


```
#include <gdcmObject.h>
```

```
#include <gdcmDataElement.h>
```

Include dependency graph for gdcmMeshPrimitive.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::MeshPrimitive](#)

This class defines surface mesh primitives. It is designed from surface mesh primitives macro.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.143 gdcmModule.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmTag.h"
#include "gdcmModuleEntry.h"
#include <map>
#include <vector>
```

Include dependency graph for gdcmModule.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Module](#)
Class for representing a [Module](#).

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


Functions

- `std::ostream & gdcm::operator<< (std::ostream &_os, const Module &_val)`


26.144 gdcmModuleEntry.h File Reference

```
#include "gdcmTypes.h"  
#include "gdcmType.h"  
#include <string>
```

Include dependency graph for gdcmModuleEntry.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::ModuleEntry](#)
Class for representing a *ModuleEntry*.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Typedefs

- typedef ModuleEntry [gdcm::MacroEntry](#)


Functions

- std::ostream & [gdcm::operator<<](#) (std::ostream &_os, const ModuleEntry &_val)


26.145 gdcmModules.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmModule.h"
#include <map>
```

Include dependency graph for gdcmModules.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Modules](#)
Class for representing a [Modules](#).

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions

- `std::ostream & gdcm::operator<< (std::ostream &_os, const Modules &_val)`

26.146 gdcmMovePatientRootQuery.h File Reference

```
#include "gdcmFindPatientRootQuery.h"
```


- class `gdcm::MoveStudyRootQuery`


Namespaces

- ## Constant Groups

- ## 26.148 gdcnNestedModuleEntries.h File Reference

Generated on Mon Nov 4 2013 10:59:18 for GDCM by Doxygen

Include dependency graph for `gdcMNestedModuleEntries.h`:



Classes

- class [gdcM::NestedModuleEntries](#)
Class for representing a *NestedModuleEntries*.

Namespaces

- [gdcM](#)

Constant Groups

- [gdcM](#)

Typedefs


- typedef NestedModuleEntries [gdcM::NestedMacroEntries](#)

Functions

- `std::ostream & gdcM::operator<< (std::ostream &_os, const NestedModuleEntries &_val)`

26.149 gdcmNetworkEvents.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- [gdcm](#)
- [gdcm::network](#)

Constant Groups

- [gdcm](#)
- [gdcm::network](#)

Enumerations

- `enum gdcm::network::EEventID {`
`gdcm::network::eAASSOCIATERequestLocalUser = 0,`
`gdcm::network::eTransportConnConfirmLocal,`
`gdcm::network::eASSOCIATE_ACPDUreceived,`
`gdcm::network::eASSOCIATE_RJPDUreceived,`
`gdcm::network::eTransportConnIndicLocal,`
`gdcm::network::eAASSOCIATE_RQPDUreceived,`
`gdcm::network::eAASSOCIATEresponseAccept,`
`gdcm::network::eAASSOCIATEresponseReject,`
`gdcm::network::ePDATArequest,`
`gdcm::network::ePDATATFPDU,`
`gdcm::network::eARELEASERequest,`
`gdcm::network::eARELEASE_RQPDUReceivedOpen,`
`gdcm::network::eARELEASE_RPPDUReceived,`
`gdcm::network::eARELEASEResponse,`
`gdcm::network::eAABORTRequest,`
`gdcm::network::eAABORTPDUReceivedOpen,`
`gdcm::network::eTransportConnectionClosed,`
`gdcm::network::eARTIMTimerExpired,`
`gdcm::network::eUnrecognizedPDUReceived,`
`}`


```
gdcmm::network::eEventDoesNotExist }
```

Variables

- const int `gdcmm::network::cMaxEventID` = eEventDoesNotExist

26.150 gdcmmNetworkStateID.h File Reference

This graph shows which files directly or indirectly include this file:



Namespaces

- `gdcmm`
- `gdcmm::network`

Constant Groups

- `gdcmm`
- `gdcmm::network`

Enumerations

- enum `gdcmm::network::EStateID` {
`gdcmm::network::eStaDoesNotExist` = 0,
`gdcmm::network::eSta1Idle` = 1,
`gdcmm::network::eSta2Open` = 2,
`gdcmm::network::eSta3WaitLocalAssoc` = 4,
`gdcmm::network::eSta4LocalAssocDone` = 8,
`gdcmm::network::eSta5WaitRemoteAssoc` = 16,
`gdcmm::network::eSta6TransferReady` = 32,
`gdcmm::network::eSta7WaitRelease` = 64,
`gdcmm::network::eSta8WaitLocalRelease` = 128,
`gdcmm::network::eSta9ReleaseCollisionRqLocal` = 256,
`gdcmm::network::eSta10ReleaseCollisionAc` = 512,
`gdcmm::network::eSta11ReleaseCollisionRq` = 1024,
`gdcmm::network::eSta12ReleaseCollisionAcLocal` = 2048,
`gdcmm::network::eSta13AwaitingClose` = 4096 }

Functions


- int [gdcm::network::GetStateIndex](#) (EStateID inState)

Variables


- const int [gdcm::network::cMaxStateID](#) = 13

26.151 gdcmObject.h File Reference

```
#include "gdcmTypes.h"
#include <assert.h>
#include <iostream>
Include dependency graph for gdcmObject.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Object](#)
Object.
- class [gdcm::SmartPointer< ObjectType >](#)
Class for Smart Pointer.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const Object &obj)`

26.152 gdcmOrientation.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for `gdcmOrientation.h`:



Classes

- class [gdcm::Orientation](#)
class to handle [Orientation](#)

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions


- `std::ostream & gdcm::operator<< (std::ostream &os, const Orientation &o)`

26.154 gdcmParseException.h File Reference


```
#include "gdcmException.h"
```

```
#include "gdcmDataElement.h"
```

Include dependency graph for gdcmParseException.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::ParseException](#)

ParseException Standard exception handling object.

Namespaces


- [gdcm](#)

Constant Groups

- [gdcm](#)

26.155 gdcmParser.h File Reference

```
#include "gdcmTag.h"
#include "gdcmByteBuffer.h"
#include <fstream>
Include dependency graph for gdcmParser.h:
```



Classes

- class [gdcm::Parser](#)
Parser ala *XML_Parser* from *expat* (*SAX*)

Namespaces


- [gdcm](#)

Constant Groups

- [gdcm](#)

26.156 gdcmPatient.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmStudy.h"
Include dependency graph for gdcmPatient.h:
```



Classes

- class [gdcm::Patient](#)

See PS 3.3 - 2007 DICOM MODEL OF THE REAL-WORLD, p 54.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.157 gdcmPDataTFPDU.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmPresentationDataValue.h"
#include "gdcmBasePDU.h"
#include <limits>
```


Include dependency graph for gdcmPDataTFPDU.h:



Classes

- class [gdcm::network::PDataTFPDU](#)

PDataTFPDU Table 9-22 P-DATA-TF PDU FIELDS.

Namespaces

- [gdcm](#)
- [gdcm::network](#)

Constant Groups

- [gdcm](#)
- [gdcm::network](#)


26.158 gdcmPDBElement.h File Reference

```


#include "gdcmTag.h"
#include "gdcmVM.h"
#include "gdcmVR.h"
#include "gdcmByteValue.h"
#include "gdcmSmartPointer.h"

```

Include dependency graph for `gdcnPDBElement.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcn::PDBElement`
Class to represent a PDB [Element](#).

Namespaces

- `gdcn`

Constant Groups

- `gdcn`

- `std::ostream & gdcmm::operator<< (std::ostream &os, const PDBelement &val)`

```
#include "gdcmTypes.h"
#include "gdcmDataSet.h"
#include "gdcmPDBelement.h"
```

- class `gdcm::PDBHeader`
Class for PDBHeader.

- **gdcm**


- **gdcm**

- `std::ostream & gdcm::operator<< (std::ostream &os, const PDBHeader &d)`

26.161 gdcmPidfCodec.h File Reference

```
#include "gdcmPidfCodec.h"
```

Include dependency graph for gdcmPidfCodec.h:



Classes

- class [gdcmPidf::PDFCodec](#)
PDFCodec class.

Namespaces

- [gdcmPidf](#)


Constant Groups

- [gdcmPidf](#)

26.162 gdcmPidfFactory.h File Reference

```
#include "gdcmPidfTypes.h"
#include "gdcmPidfNetworkEvents.h"
#include "gdcmPidfULConnection.h"
#include "gdcmPidfPresentationDataValue.h"
```

Include dependency graph for gdcmPDUFactory.h:



Classes

- class [gdcm::network::PDUFactory](#)

[PDUFactory](#) basically, given an initial byte, construct the appropriate PDU. This way, the event loop doesn't have to know about all the different PDU types.

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.163 gdcmPersonName.h File Reference

```
#include "gdcmTypes.h"
#include <vector>
#include <algorithm>
#include <string.h>
```

Include dependency graph for `gdcmPersonName.h`:



Classes

- class `gdcm::PersonName`

PersonName class.

Namespaces

- `gdcm`


Constant Groups

- `gdcm`

26.164 gdcmPGXCodec.h File Reference

```
#include "gdcmImageCodec.h"
```

Include dependency graph for gdcmPGXCodec.h:



Classes

- class [gdcm::PGXCodec](#)

Class to do PGX See PGX as used in JPEG 2000 implementation and reference images.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.165 gdcmPhotometricInterpretation.h File Reference

```
#include "gdcmTypes.h"
#include <iostream>
```

Include dependency graph for `gdcmPhotometricInterpretation.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::PhotometricInterpretation](#)
Class to represent an *PhotometricInterpretation*.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const PhotometricInterpretation &val)`

26.166 gdcmPixelFormat.h File Reference


```
#include "gdcmTypes.h"
```




```
#include <iostream>
```

```
#include <assert.h>
```

Include dependency graph for gdcmPixelFormat.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::PixelFormat](#)
PixelFormat.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const PixelFormat &pf)`

Constant Groups


- [gdcm](#)

26.168 gdcmPixmapReader.h File Reference


```
#include "gdcmReader.h"
```

```
#include "gdcmPixmap.h"
```

Include dependency graph for gdcmPixmapReader.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::PixmapReader](#)
PixmapReader.

Constant Groups


- **gdcm**

26.170 gdcmPixmapWriter.h File Reference


```
#include "gdcmWriter.h"
```

```
#include "gdcmPixmap.h"
```

Include dependency graph for gdcmPixmapWriter.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::PixmapWriter`


PixmapWriter This class will takes two inputs:

26.172 gdcmPreamble.h File Reference


```
#include "gdcmTypes.h"
```

```
#include "gdcmVL.h"
```

Include dependency graph for gdcmPreamble.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Preamble](#)
DICOM Preamble (Part 10)

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const Preamble &val)`


26.173 gdcmPresentationContext.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmUIDs.h"
#include <vector>
```

Include dependency graph for gdcmPresentationContext.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::PresentationContext`
PresentationContext.

Namespaces


- `gdcm`

Constant Groups


- `gdcm`

26.174 gdcmPresentationContextAC.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmTransferSyntaxSub.h"
Include dependency graph for gdcmPresentationContextAC.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::PresentationContextAC](#)

PresentationContextAC Table 9-18 PRESENTATION CONTEXT ITEM FIELDS.

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.175 gdcmPresentationContextGenerator.h File Reference

```
#include "gdcmDirectory.h"
#include "gdcmPresentationContext.h"
```

Include dependency graph for gdcmPresentationContextGenerator.h:



Classes

- class [gdcm::PresentationContextGenerator](#)

***PresentationContextGenerator** This class is responsible for generating the proper [PresentationContext](#) that will be used in subsequent operation during a DICOM Query/Retrieve association. The step of the association is very sensible as special care need to be taken to explicitly define what instance are going to be send and how they are encoded.*

Namespaces


- [gdcm](#)

Constant Groups


- [gdcm](#)

26.176 gdcmPresentationContextRQ.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmAbstractSyntax.h"
#include "gdcmTransferSyntaxSub.h"
#include "gdcmDataSet.h"
Include dependency graph for gdcmPresentationContextRQ.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::PresentationContextRQ](#)

PresentationContextRQ Table 9-13 PRESENTATION CONTEXT ITEM FIELDS.

Namespaces

- [gdcm](#)
- [gdcm::network](#)

Constant Groups


- [gdcm](#)
- [gdcm::network](#)

26.177 gdcmPresentationDataValue.h File Reference


```
#include "gdcmTypes.h"
```

```
#include <vector>
```

Include dependency graph for gdcmPresentationDataValue.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::PresentationDataValue](#)

PresentationDataValue Table 9-23 PRESENTATION-DATA-VALUE ITEM FIELDS.

Namespaces


- [gdcm](#)
- [gdcm::network](#)

Constant Groups


- [gdcm](#)
- [gdcm::network](#)

26.178 gdcmPrinter.h File Reference

```
#include "gdcmFile.h"
#include "gdcmDataElement.h"
Include dependency graph for gdcmPrinter.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Printer](#)
Printer class.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.179 gdcmPrivateTag.h File Reference

```
#include "gdcmTag.h"
#include "gdcmVR.h"
#include <iostream>
#include <iomanip>
#include <string>
#include <algorithm>
#include <string.h>
#include <ctype.h>
```

Include dependency graph for gdcmPrivateTag.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::PrivateTag](#)

Class to represent a Private DICOM Data [Element](#) ([Attribute](#)) [Tag](#) (Group, [Element](#), Owner)

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const PrivateTag &val)`

26.180 gdcmProgressEvent.h File Reference

```
#include "gdcmEvent.h"
#include "gdcmTag.h"
```

Include dependency graph for `gdcProgressEvent.h`:



Classes

- class `gdc::ProgressEvent`

ProgressEvent Special type of event triggered during.

Namespaces

- `gdc`


Constant Groups

- `gdc`

26.181 gdcMPVRGCodec.h File Reference

```
#include "gdcImageCodec.h"
```


Include dependency graph for gdcmPVRGCodec.h:



Classes

- class [gdcm::PVRGCodec](#)

PVRGCodec.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.182 gdcmPythonFilter.h File Reference

```
#include <Python.h>
#include "gdcmDataElement.h"
#include "gdcmDicts.h"
#include "gdcmFile.h"
```

Include dependency graph for `gdcPythonFilter.h`:



Classes

- class `gdc::PythonFilter`

`PythonFilter` `PythonFilter` is the class that make `gdc2.x` looks more like `gdc1` and transform the binary blob contained in a `DataElement` into a string, typically this is a nice feature to have for wrapped language.

Namespaces



- `gdc`

Constant Groups

- `gdc`

26.183 gdcQueryBase.h File Reference

```
#include "gdcTag.h"
#include "gdcDataElement.h"
#include <vector>
```



- class `gdcm::QueryBase`



- **gdcm**

- **gdcm**

- enum `gdcm::ERootType` {
`gdcm::ePatientRootType`,
`gdcm::eStudyRootType` }

- enum `gdcmm::ECharSet` {
 `gdcmm::eLatin1` = 0,
 `gdcmm::eLatin2`,
 `gdcmm::eLatin3`,
 `gdcmm::eLatin4`,
 `gdcmm::eCyrillic`,
 `gdcmm::eArabic`,
 `gdcmm::eGreek`,
 `gdcmm::eHebrew`,
 `gdcmm::eLatin5`,
 `gdcmm::eJapanese`,
 `gdcmm::eThai`,
 `gdcmm::eJapaneseKanjiMultibyte`,
 `gdcmm::eJapaneseSupplementaryKanjiMultibyte`,
 `gdcmm::eKoreanHangulHanjaMultibyte`,
 `gdcmm::eUTF8`,
 `gdcmm::eGB18030` }

```
#include "gdcmQueryBase.h"
#include "gdcmDataSet.h"
Include dependency graph for gdcmQueryImage.h:
```



Classes

- class [gdcm::QueryImage](#)

QueryImage contains: class to construct an image-based query for C-FIND and C-MOVE.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.186 gdcmQueryPatient.h File Reference

```
#include "gdcmQueryBase.h"
```

Include dependency graph for gdcmQueryPatient.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::QueryPatient](#)

QueryPatient contains: class to construct a patient-based query for c-find and c-move.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.187 gdcmQuerySeries.h File Reference

```
#include "gdcmQueryBase.h"
```

Include dependency graph for gdcmQuerySeries.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::QuerySeries](#)

QuerySeries contains: class to construct a series-based query for c-find and c-move.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.188 gdcmQueryStudy.h File Reference

```
#include "gdcmQueryBase.h"
```

Include dependency graph for gdcmQueryStudy.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::QueryStudy](#)

QueryStudy.h contains: class to construct a study-based query for C-FIND and C-MOVE.

Namespaces

- [gdcm](#)

Constant Groups


- [gdcm](#)

26.189 gdcmrw.man File Reference

26.190 gdcmRAWCodec.h File Reference

```
#include "gdcmImageCodec.h"
```

Include dependency graph for gdcmRAWCodec.h:



Classes

- class [gdcm::RAWCodec](#)

RAWCodec class.

Namespaces

- [gdcm](#)

Constant Groups


- [gdcm](#)

26.191 gdcmReader.h File Reference


```
#include "gdcmFile.h"
```

```
#include <fstream>
```

Include dependency graph for gdcmReader.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Reader](#)
Reader ala DOM (Document *Object* Model)

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


26.192 gdcmRegion.h File Reference

```
#include "gdcmTypes.h"
```


```
#include <vector>
```

```
#include <iostream>
```

Include dependency graph for gdcmRegion.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Region](#)
Class for manipulation region.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions


- `std::ostream & gdcm::operator<< (std::ostream &os, const Region &r)`

26.193 gdcmRescaler.h File Reference

```
#include "gdcmTypes.h"
```

```
#include "gdcmPixelFormat.h"
```

Include dependency graph for `gdcmRescaler.h`:



Classes

- class [gdcm::Rescaler](#)
Rescale class This class is meant to apply the linear transform of Stored Pixel [Value](#) to Real World [Value](#). This is mostly found in CT or PET dataset, where the value are stored using one type, but need to be converted to another scale using

a linear transform. There are basically two cases: In CT: the linear transform is generally integer based. E.g. the Stored Pixel Type is unsigned short 12bits, but to get Hounsfield unit, one need to apply the linear transform:

$$RWV = 1.*SV - 1024$$

So the best scalar to store the Real World Value will be 16 bits signed type.

Namespaces

- **gdcm**


Constant Groups

- gdc

26.194 gdcMRLCodec.h File Reference

```
#include "gdcmImageCodec.h"
```

Include dependency graph for `gdcmRLECodec.h`:



Classes

- class `gdcm::RLECodec`

Class to do RLE.

Namespaces

- **gdcm**


Constant Groups

- [gdcm](#)

26.195 gdcmRoleSelectionSub.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmRoleSelectionSub.h:



Classes

- class [gdcm::network::RoleSelectionSub](#)

RoleSelectionSub PS 3.7 Table D.3-9 SCP/SCU ROLE SELECTION SUB-ITEM FIELDS (A-ASSOCIATE-RQ)

Namespaces

- [gdcm](#)
- [gdcm::network](#)

Constant Groups


- [gdcm](#)
- [gdcm::network](#)

26.196 gdcmScanner.h File Reference

```
#include "gdcmDirectory.h"
```

```
#include "gdcmSubject.h"
#include "gdcmTag.h"
#include "gdcmPrivateTag.h"
#include "gdcmSmartPointer.h"
#include <map>
#include <set>
#include <string>
#include <string.h>
```

Include dependency graph for gdcmScanner.h:



Classes

- struct [gdcm::Scanner::ltstr](#)
- class [gdcm::Scanner](#)

[Scanner](#) This filter is meant for quickly browsing a [FileSet](#) (a set of files on disk). Special consideration are taken so as to read the minimum amount of information in each file in order to retrieve the user specified set of DICOM [Attribute](#).

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const Scanner &s)`

26.197 gdcmscanner.man File Reference

Classes

- class [gdcm::Segment](#)

This class defines a segment. It mainly contains attributes of group 0x0062. In addition, it can be associated with surface.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.200 gdcmSegmentedPaletteColorLookupTable.h File Reference

```
#include "gdcmLookupTable.h"
```

Include dependency graph for gdcmSegmentedPaletteColorLookupTable.h:



Classes

- class [gdcm::SegmentedPaletteColorLookupTable](#)

SegmentedPaletteColorLookupTable class.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.201 gdcmSegmentHelper.h File Reference

```
#include <string>
```


Include dependency graph for gdcmSegmentHelper.h:



This graph shows which files directly or indirectly include this file:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::SegmentReader](#)

This class defines a segment reader. It reads attributes of group 0x0062.

Namespaces

- [gdcms](#)

Constant Groups

- [gdcms](#)

26.203 gdcmsSegmentWriter.h File Reference

```
#include <gdcmsWriter.h>
#include <gdcmsSegment.h>
```

```
graph BT; gdcmsurfacewriter[hdcmsurfacewriter.h] --> gdcmsegmentwriter[hdcmsegmentwriter.h];
```

- class `gdcm::SegmentWriter`

Namespaces


- **gdcm**

Constant Groups

- **gdcm**

26.204 gdcmSequenceOfFragments.h File Reference

```
#include "gdcmValue.h"
#include "gdcmVL.h"
#include "gdcmFragment.h"
#include "gdcmBasicOffsetTable.h"
Include dependency graph for gdcmSequenceOfFragments.h:
```



Classes

- class [gdcm::SequenceOfFragments](#)
Class to represent a Sequence Of Fragments.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

26.205 gdcmSequenceOfItems.h File Reference

```
#include "gdcmValue.h"
```

- class `gdc::SequenceOfItems`

Namespaces

- gdc

- **gdcm**

```
#include "gdcmTag.h"
#include "gdcmSmartPointer.h"
#include "gdcmFile.h"
#include <vector>
#include <string>
#include <map>
```

- class `gdcm::FileWithName`
FileWithName.
- struct `gdcm::SerieHelper::Rule`
- class `gdcm::SerieHelper`

Namespaces

- ## Constant Groups

- ## Typedefs

- Generated on Mon Nov 4 2013 10:59:18 for GDCM by Doxygen


Enumerations

- enum `gdcm::CompOperators` {
`gdcm::GDCM_EQUAL = 0,`
`gdcm::GDCM_DIFFERENT,`
`gdcm::GDCM_GREATER,`
`gdcm::GDCM_GREATEROREQUAL,`
`gdcm::GDCM_LESS,`
`gdcm::GDCM_LESSEQUAL` }
- enum `gdcm::LodModeType` {
`gdcm::LD_ALL = 0x00000000,`
`gdcm::LD_NOSEQ = 0x00000001,`
`gdcm::LD_NOSHADOW = 0x00000002,`
`gdcm::LD_NOSHADOWSEQ = 0x00000004` }


26.207 gdcmSeries.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for `gdcmSeries.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcmPid::Series](#)

[Series.](#)

Namespaces

- [gdcmPid](#)


Constant Groups

- [gdcmPid](#)


26.208 gdcmPidServiceClassApplicationInformation.h File Reference

```
#include "gdcmPidTypes.h"
```

Include dependency graph for gdcmServiceClassApplicationInformation.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::ServiceClassApplicationInformation](#)


Namespaces

- [gdcm](#)
- [gdcm::network](#)

Constant Groups

- [gdcm](#)
- [gdcm::network](#)

Include dependency graph for gdcmSHA1.h:



Classes

- class [gdcm::SHA1](#)

Class for [SHA1](#).

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


26.211 gdcmSimpleSubjectWatcher.h File Reference

```

#include "gdcmSubject.h"
#include "gdcmCommand.h"
#include "gdcmSmartPointer.h"
#include "gdcmAnonymizeEvent.h"
#include "gdcmDataEvent.h"

```

Include dependency graph for `gdcmsimpleSubjectWatcher.h`:



Classes

- class [gdcmsimpleSubjectWatcher](#)

SimpleSubjectWatcher This is a typical *Subject* Watcher class. It will observe all events.

Namespaces

- [gdcmsimple](#)


Constant Groups

- [gdcmsimple](#)

26.212 gdcmsmartPointer.h File Reference

```
#include "gdcmsmartPointer.h"
```

Include dependency graph for gdcmSmartPointer.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::SmartPointer< ObjectType >`
Class for Smart Pointer.

Namespaces

- `gdcm`


Constant Groups

- `gdcm`

26.213 gdcmSOPClassExtendedNegotiationSub.h File Reference

```
#include "gdcmServiceClassApplicationInformation.h"
```

Include dependency graph for `gdcmSOPClassExtendedNegociationSub.h`:



Classes

- class [gdcm::network::SOPClassExtendedNegociationSub](#)

SOPClassExtendedNegociationSub PS 3.7 Table D.3-11 SOP CLASS EXTENDED NEGOTIATION SUB-ITEM FIELDS (A-ASSOCIATE-RQ and A-ASSOCIATE-AC)

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.214 gdcmSOPClassUIDToIOD.h File Reference

```
#include "gdcmUIDs.h"
```


Include dependency graph for gdcmSOPClassUIDToIOD.h:



Classes

- class [gdcm::SOPClassUIDToIOD](#)

Class convert a class SOP Class UID into [IOD](#).

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


26.215 gdcmSorter.h File Reference

```


#include "gdcmDirectory.h"
#include "gdcmTag.h"
#include <vector>
#include <string>
#include <map>

```

Include dependency graph for `gdcmSorter.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Sorter](#)

[Sorter](#) General class to do sorting using a custom function You simply need to provide a function of type: [Sorter::Sort-Function](#).

Namespaces


- [gdcm](#)

Constant Groups

- [gdcm](#)

- `std::ostream & gdcmm::operator<< (std::ostream &os, const Sorter &s)`

```
#include "gdcmTypes.h"
#include "gdcmAttribute.h"
Include dependency graph for gdcmSpacing.h:
```




- class `gdcm::Spacing`

Class for *Spacing*.

- gdc

- **gdcm**

```
#include "gdcmFile.h"
```




- class `gdcm::Spectroscopy`
Spectroscopy class.

- **gdcm**

- **gdcm**

```
#include "gdcmFile.h"
#include "gdcmImage.h"
```

Include dependency graph for `gdcmSplitMosaicFilter.h`:



Classes

- class `gdcm::SplitMosaicFilter`

SplitMosaicFilter class Class to reshuffle bytes for a SIEMENS Mosaic image Siemens CSA *Image* Header CSA:= Common Siemens Architecture, sometimes also known as Common syngo Architecture.

Namespaces


- **gdcm**

Constant Groups

- **gdcm**

26.219 gdcmStaticAssert.h File Reference

This graph shows which files directly or indirectly include this file:



Classes

- struct `gdcm::static_assert_test< x >`
- struct `gdcm::STATIC_ASSERTION_FAILURE< x >`
- struct `gdcm::STATIC_ASSERTION_FAILURE< true >`

Namespaces

- [gdcmm](#)

Constant Groups

- [gdcmm](#)

Macros

- #define [GDCM_DO_JOIN](#)(X, Y) [GDCM_DO_JOIN2](#)(X,Y)
- #define [GDCM_DO_JOIN2](#)(X, Y) X##Y
- #define [GDCM_JOIN](#)(X, Y) [GDCM_DO_JOIN](#)(X, Y)
- #define [GDCM_STATIC_ASSERT](#)(B)

*The [GDCM_JOIN](#) + **LINE** is needed to create a uniq identifier.*

26.219.1 Macro Definition Documentation

26.219.1.1 #define [GDCM_DO_JOIN](#)(X, Y) [GDCM_DO_JOIN2](#)(X,Y)

26.219.1.2 #define [GDCM_DO_JOIN2](#)(X, Y) X##Y

26.219.1.3 #define [GDCM_JOIN](#)(X, Y) [GDCM_DO_JOIN](#)(X, Y)


26.219.1.4 #define [GDCM_STATIC_ASSERT](#)(B)

Value:

```
typedef ::gdcmm::static_assert_test<\
    sizeof(::gdcmm::STATIC_ASSERTION_FAILURE< (bool) ( B ) >>)\
    GDCM_JOIN(gdcmm_static_assert_typedef_, __LINE__)
```

The [GDCM_JOIN](#) + **LINE** is needed to create a uniq identifier.

```
#include "gdcmReader.h"
Include dependency graph for gdcmStreamImageReader.h:
```




- class `gdcm::StreamImageReader`
StreamImageReader.

- gdc

- **gdcm**


```
#include "gdcmWriter.h"
#include <iostream>
#include "gdcmDataSet.h"
```




StreamReader.

```
#include "gdcmTypes.h"
#include "gdcmStaticAssert.h"
```


Include dependency graph for gdcmString.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::String< TDelimiter, TMaxLength, TPadChar >](#)
String.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


Functions

- template<char TDelimiter, unsigned int TMaxLength, char TPadChar>
std::istream & [gdcm::operator>>](#) (std::istream &is, String< TDelimiter, TMaxLength, TPadChar > &ms)

26.223 gdcmStringFilter.h File Reference

```
#include "gdcmDataElement.h"
```

```
#include "gdcmDicts.h"
#include "gdcmFile.h"
Include dependency graph for gdcmStringFilter.h:
```



Classes

- class [gdcm::StringFilter](#)

[StringFilter](#) [StringFilter](#) is the class that make `gdcm2.x` looks more like `gdcm1` and transform the binary blob contained in a [DataElement](#) into a string, typically this is a nice feature to have for wrapped language.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)


26.224 gdcmStudy.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmSeries.h"
#include <vector>
```

Include dependency graph for gdcmStudy.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::Study`
Study.

Namespaces

- `gdcm`


Constant Groups

- `gdcm`


26.225 gdcmSubject.h File Reference

```
#include "gdcmObject.h"
```

Include dependency graph for gdcmSubject.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Subject](#)
Subject.


Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

```
#include <gdcmObject.h>
#include <gdcmDataElement.h>
#include <gdcmMeshPrimitive.h>
#include "gdcmSegmentHelper.h"
Include dependency graph for gdcmSurface.h:
```



This graph shows which files directly or indirectly include this file:



- class `gdcm::Surface`

This class defines a SURFACE IE. This members are taken from required surface mesh module attributes.

Namespaces

- [gdcm](#)


Constant Groups

- [gdcm](#)

26.227 gdcmSurfaceHelper.h File Reference

```
#include "gdcmTypes.h"
#include <vector>
#include <iostream>
```

Include dependency graph for gdcmSurfaceHelper.h:



Classes


- class [gdcm::SurfaceHelper](#)
SurfaceHelper Helper class for *Surface* object.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)




- class `gdcm::SurfaceWriter`

- **gdc**

- **gdc**

```
#include "gdcmTypes.h"
#include <iostream>
```


Include dependency graph for gdcmSwapCode.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::SwapCode`
SwapCode representation.

Namespaces

- `gdcm`

Constant Groups

- `gdcm`


Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const SwapCode &sc)`


26.231 gdcmSwapper.h File Reference

```
#include "gdcmSwapCode.h"
#include "gdcmSwapper.txx"
```

Include dependency graph for `gdcmSwapper.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::SwapperDoOp`
- class `gdcm::SwapperNoOp`

Namespaces

- `gdcm`


Constant Groups

- `gdcm`


26.232 gdcmSystem.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmSystem.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::System](#)
Class to do system operation.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)


26.233 gdcmTable.h File Reference

```

#include "gdcmTableEntry.h"
#include "gdcmTag.h"
#include <map>

```

Include dependency graph for `gdcmTable.h`:



Classes

- class `gdcm::Table`

Table.

Namespaces

- `gdcm`


Constant Groups

- `gdcm`


26.234 `gdcmTableEntry.h` File Reference

```
#include "gdcmType.h"
#include <string>
```

Include dependency graph for gdcmTableEntry.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::TableEntry`
TableEntry.

Namespaces

- `gdcm`


Constant Groups

- `gdcm`


26.235 gdcmTableReader.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmDefs.h"
#include <string>
#include <vector>
#include <map>
```

Include dependency graph for gdcmTableReader.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::TableReader](#)

Class for representing a [TableReader](#).

Namespaces


- [gdcm](#)

Constant Groups

- [gdcm](#)

26.236 gdcmTag.h File Reference

```
#include "gdcmTypes.h"
#include <iostream>
#include <iomanip>
Include dependency graph for gdcmTag.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Tag](#)

Class to represent a DICOM Data *Element* (*Attribute*) *Tag* (Group, *Element*). Basically an `uint32_t` which can also be expressed as two `uint16_t` (group and element)

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions


- `std::ostream & gdcm::operator<< (std::ostream &_os, const Tag &_val)`
- `std::istream & gdcm::operator>> (std::istream &_is, Tag &_val)`

26.237 gdcmTagPath.h File Reference

```
#include "gdcmTag.h"
```

```
#include <vector>
```

Include dependency graph for `gdcmTagPath.h`:



Classes

- class [gdcm::TagPath](#)
class to handle a path of tag.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

26.238 gdcmTagToVR.h File Reference

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions


- VR::VRType [gdcm::GetVRFromTag](#) (Tag const &tag)

26.239 gdcmtar.man File Reference

26.240 gdcmTerminal.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmTerminal.h:



Namespaces

- [gdcm](#)
- [gdcm::terminal](#)

Class for Terminal Allow one to print in color in a shell.

Constant Groups

- [gdcm](#)
- [gdcm::terminal](#)

Class for Terminal Allow one to print in color in a shell.

Enumerations

- enum `gdcmm::terminal::Attribute` {
 `gdcmm::terminal::reset` = 0,
 `gdcmm::terminal::bright` = 1,
 `gdcmm::terminal::dim` = 2,
 `gdcmm::terminal::underline` = 3,
 `gdcmm::terminal::blink` = 5,
 `gdcmm::terminal::reverse` = 7,
 `gdcmm::terminal::hidden` = 8 }
- enum `gdcmm::terminal::Color` {
 `gdcmm::terminal::black` = 0,
 `gdcmm::terminal::red`,
 `gdcmm::terminal::green`,
 `gdcmm::terminal::yellow`,
 `gdcmm::terminal::blue`,
 `gdcmm::terminal::magenta`,
 `gdcmm::terminal::cyan`,
 `gdcmm::terminal::white` }
- enum `gdcmm::terminal::Mode` {
 `gdcmm::terminal::CONSOLE` = 0,
 `gdcmm::terminal::VT100` }


Functions

- `GDCM_EXPORT std::string gdcmm::terminal::setattribute` (Attribute att)
- `GDCM_EXPORT std::string gdcmm::terminal::setbgcolor` (Color c)
- `GDCM_EXPORT std::string gdcmm::terminal::setfgcolor` (Color c)
- `GDCM_EXPORT void gdcmm::terminal::setmode` (Mode m)

26.241 gdcmmTestDriver.h File Reference

```
#include <clocale>
#include <locale>
```

Include dependency graph for gdcmTestDriver.h:




26.242 gdcmTesting.h File Reference

```
#include "gdcmTypes.h"
```

```
#include <iostream>
```

Include dependency graph for gdcmTesting.h:



Classes

- class [gdcm::Testing](#)
class for testing

Namespaces

- [gdcm](#)


Constant Groups

- [gdc](#)


26.243 gdcTrace.h File Reference

```
#include "gdcTypes.h"
#include "gdcSystem.h"
#include <iosfwd>
#include <cassert>
```

Include dependency graph for gdcTrace.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdc::Trace](#)
Trace.

Namespaces

- [gdc](#)

Constant Groups

- [gdcm](#)

Macros

- #define [GDCM_FUNCTION](#) "<unknown>"
- #define [gdcmAssertAlwaysMacro](#)(arg) [gdcmAssertMacro](#)(arg)
AssertAlways.
- #define [gdcmAssertMacro](#)(arg)
Assert.
- #define [gdcmDebugMacro](#)(msg)
Debug.
- #define [gdcmErrorMacro](#)(msg)
Error this is pretty bad, more than just warning It could mean lost of data, something not handle...
- #define [gdcmWarningMacro](#)(msg)
Warning.

26.243.1 Macro Definition Documentation

26.243.1.1 #define [GDCM_FUNCTION](#) "<unknown>"

26.243.1.2 #define [gdcmAssertAlwaysMacro](#)(arg) [gdcmAssertMacro](#)(arg)

[AssertAlways.](#)

Parameters

<i>arg</i>	argument to test An easy solution to pass also a message is to do: gdcmAssertMacro ("my message" && 2 < 3)
------------	--

Referenced by [gdcm::SequenceOfFragments::ReadValue\(\)](#), and [gdcm::VR::Write\(\)](#).

26.243.1.3 #define [gdcmAssertMacro](#)(arg)

Value:

```
{
    if( !(arg) )
    {
        std::ostringstream osmacro;
        osmacro << "Assert: In " __FILE__ ", line " << __LINE__
            << ", function " << GDCM\_FUNCTION
            << "\n\n";
        std::ostream &_os = gdcm::Trace::GetErrorStream();
        _os << osmacro.str() << std::endl;
        assert ( arg );
    }
}
```

[Assert.](#)

Parameters

<i>arg</i>	argument to test An easy solution to pass also a message is to do: <code>gdcmaAssertMacro("my message" && 2 < 3)</code>
------------	--

Referenced by `gdcma::PixelFormat::SetSamplesPerPixel()`.

26.243.1.4 `#define gdcmaDebugMacro(msg)`

Value:

```
{
    if( gdcma::Trace::GetDebugFlag() )
    {
        std::ostringstream osmacro;
        osmacro << "Debug: In " __FILE__ ", line " << __LINE__
        << ", function " << GDCM_FUNCTION << '\n'
        << "Last system error was: "
        << gdcma::System::GetLastSystemError() << '\n' << msg;
        std::ostream &_os = gdcma::Trace::GetDebugStream();
        _os << osmacro.str() << "\n\n" << std::endl;
    }
}
```

Debug.

Parameters

<i>msg</i>	message part
------------	--------------

Referenced by `gdcma::ByteValue::ByteValue()`, `gdcma::SequenceOfItems::Read()`, `gdcma::Item::Read()`, `gdcma::VR::Read()`, `gdcma::SequenceOfFragments::ReadPreValue()`, `gdcma::SequenceOfFragments::ReadValue()`, and `gdcma::ByteValue::SetLength()`.

26.243.1.5 `#define gdcmaErrorMacro(msg)`

Value:

```
{
    if( gdcma::Trace::GetErrorFlag() )
    {
        std::ostringstream osmacro;
        osmacro << "Error: In " __FILE__ ", line " << __LINE__
        << ", function " << GDCM_FUNCTION << '\n'
        << msg << "\n\n";
        std::ostream &_os = gdcma::Trace::GetErrorStream();
        _os << osmacro.str() << std::endl;
    }
}
```

Error this is pretty bad, more than just warning It could mean lost of data, something not handle...

Parameters

<i>msg</i>	second message part
------------	---------------------

Referenced by `gdcma::CommandDataSet::Insert()`, `gdcma::FileMetaInformation::Insert()`, `gdcma::DataSet::Insert()`, `gdcma::Item::Read()`, and `gdcma::Fragment::ReadBacktrack()`.

26.243.1.6 `#define gdcmaWarningMacro(msg)`

Value:

```

{
    if( gdcm::Trace::GetWarningFlag() )
    {
        std::ostringstream osmacro;
        osmacro << "Warning: In " __FILE__ ", line " << __LINE__
            << ", function " << GDCM_FUNCTION << "\n"
            << msg << "\n\n";
        std::ostream &_os = gdcm::Trace::GetWarningStream();
        _os << osmacro.str() << std::endl;
    }
}

```

Warning.

Parameters


<i>msg</i>	message part
------------	--------------

Referenced by `gdcm::DataSet::InsertDataElement()`, `gdcm::SequenceOfItems::Read()`, `gdcm::Item::Read()`, `gdcm::Fragment::ReadBacktrack()`, `gdcm::Fragment::ReadValue()`, `gdcm::SequenceOfFragments::ReadValue()`, and `gdcm::Item::Write()`.

26.244 gdcmTransferSyntax.h File Reference

```
#include "gdcmSwapCode.h"
```

Include dependency graph for `gdcmTransferSyntax.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::TransferSyntax](#)
Class to manipulate Transfer Syntax.

Namespaces

- [gdcm](#)

Constant Groups


- [gdcm](#)

Functions


- `std::ostream & gdcm::operator<< (std::ostream &_os, const TransferSyntax &ts)`

26.245 gdcmTransferSyntaxSub.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmTransferSyntax.h"
#include "gdcmUIDs.h"
Include dependency graph for gdcmTransferSyntaxSub.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::TransferSyntaxSub](#)

TransferSyntaxSub Table 9-15 TRANSFER SYNTAX SUB-ITEM FIELDS.

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)


26.246 gdcmType.h File Reference

```
#include "gdcmTypes.h"
#include <iostream>
```

Include dependency graph for `gdcmType.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::Type`
Type.

Namespaces

- [gdcm](#)

Constant Groups


- [gdcm](#)

Functions

- `std::ostream & gdcm::operator<< (std::ostream &_os, const Type &val)`

26.247 gdcmTypes.h File Reference

```
#include "gdcmConfigure.h"
#include "gdcmWin32.h"
#include "gdcmLegacyMacro.h"
Include dependency graph for gdcmTypes.h:
```




This graph shows which files directly or indirectly include this file:



26.248 gdcmUIDGenerator.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for `gdcmUIDGenerator.h`:



Classes

- class `gdcm::UIDGenerator`

Class for generating unique UID.

Namespaces

- `gdcm`


Constant Groups

- `gdcm`


26.249 gdcmUIDs.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmUIDs.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::UIDs](#)
all known uids

Namespaces

- [gdcm](#)

Constant Groups


- [gdcm](#)

Functions


- `std::ostream & gdcm::operator<< (std::ostream &_os, const UIDs &uid)`

26.250 gdcmULAction.h File Reference

```
#include "gdcmNetworkStateID.h"
#include "gdcmULEvent.h"
#include "gdcmULConnection.h"
Include dependency graph for gdcmULAction.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::ULAction](#)

[ULAction](#) A [ULConnection](#) in a given [ULState](#) can perform certain [ULActions](#). This base class provides the interface for running those [ULActions](#) on a given [ULConnection](#).

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.251 gdcmULActionAA.h File Reference

```
#include "gdcmULAction.h"
```

Include dependency graph for gdcmULActionAA.h:



Classes

- class [gdcm::network::ULActionAA1](#)
- class [gdcm::network::ULActionAA2](#)
- class [gdcm::network::ULActionAA3](#)
- class [gdcm::network::ULActionAA4](#)
- class [gdcm::network::ULActionAA5](#)
- class [gdcm::network::ULActionAA6](#)
- class [gdcm::network::ULActionAA7](#)
- class [gdcm::network::ULActionAA8](#)

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.252 gdcmULActionAE.h File Reference

```
#include "gdcmULAction.h"
```

Include dependency graph for `gdcmULActionAE.h`:



Classes

- class [gdcm::network::ULActionAE1](#)
- class [gdcm::network::ULActionAE2](#)
- class [gdcm::network::ULActionAE3](#)
- class [gdcm::network::ULActionAE4](#)
- class [gdcm::network::ULActionAE5](#)
- class [gdcm::network::ULActionAE6](#)
- class [gdcm::network::ULActionAE7](#)
- class [gdcm::network::ULActionAE8](#)

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.253 gdcmULActionAR.h File Reference

```
#include "gdcmULAction.h"
```


Include dependency graph for gdcmULActionAR.h:



Classes

- class [gdcm::network::ULActionAR1](#)
- class [gdcm::network::ULActionAR10](#)
- class [gdcm::network::ULActionAR2](#)
- class [gdcm::network::ULActionAR3](#)
- class [gdcm::network::ULActionAR4](#)
- class [gdcm::network::ULActionAR5](#)
- class [gdcm::network::ULActionAR6](#)
- class [gdcm::network::ULActionAR7](#)
- class [gdcm::network::ULActionAR8](#)
- class [gdcm::network::ULActionAR9](#)

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.254 gdcmULActionDT.h File Reference

```
#include "gdcmULAction.h"
```

Include dependency graph for `gdcmULActionDT.h`:



Classes

- class [gdcm::network::ULActionDT1](#)
- class [gdcm::network::ULActionDT2](#)

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.255 gdcmULBasicCallback.h File Reference

```
#include "gdcmULConnectionCallback.h"
#include "gdcmDataSet.h"
#include <vector>
```

Include dependency graph for gdcmULBasicCallback.h:



Classes

- class [gdcm::network::ULBasicCallback](#)

[ULBasicCallback](#) This is the most basic of callbacks for how the [ULConnectionManager](#) handles incoming datasets. Data-Sets are just concatenated to the `mDataSets` vector, and the result can be pulled out of the vector by later code. Alternatives to this method include progress updates, saving to disk, etc. This class is NOT THREAD SAFE. Access the dataset vector after the entire set of datasets has been returned by the [ULConnectionManager](#).

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)


26.256 gdcmULConnection.h File Reference

```
#include "gdcmNetworkStateID.h"
#include "gdcmARTIMTimer.h"
#include "gdcmULConnectionInfo.h"
#include "gdcmPresentationContextRQ.h"
#include "gdcmDataElement.h"
#include "gdcmPresentationContextAC.h"
#include "gdcmPresentationContext.h"
```

Include dependency graph for `gdcmULConnection.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::network::ULConnection`

ULConnection This is the class that contains the socket to another machine, and passes data through itself, as well as maintaining a sense of state.

Namespaces

- `gdcm`
- `gdcm::network`


Constant Groups

- `gdcm`
- `gdcm::network`


26.257 gdcmULConnectionCallback.h File Reference

```
#include "gdcmTypes.h"
```

Include dependency graph for gdcmULConnectionCallback.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::ULConnectionCallback](#)

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)


26.258 gdcmULConnectionInfo.h File Reference

```
#include "gdcmUserInformation.h"
#include <string>
```

Include dependency graph for `gdcmULConnectionInfo.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::ULConnectionInfo](#)

[ULConnectionInfo](#) this class contains all the information about a particular connection as established by the user. That is, it's: User Information Calling AE Title Called AE Title IP address/computer name IP Port A connection must be established with this information, that's subsequently placed into various primitives for actual communication.

Namespaces


- [gdcm](#)
- [gdcm::network](#)

Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.259 gdcmULConnectionManager.h File Reference

```
#include "gdcmULTransitionTable.h"
#include "gdcmULConnection.h"
#include "gdcmULConnectionInfo.h"
#include "gdcmPresentationDataValue.h"
#include "gdcmULConnectionCallback.h"
#include "gdcmSubject.h"
#include "gdcmPresentationContext.h"
Include dependency graph for gdcmULConnectionManager.h:
```



Classes

- class [gdcm::network::ULConnectionManager](#)

[ULConnectionManager](#) The [ULConnectionManager](#) performs actions on the [ULConnection](#) given inputs from the user and from the state of what's going on around the connection (ie, timeouts of the ARTIM timer, responses from the peer across the connection, etc).

Namespaces

- [gdcm](#)
- [gdcm::network](#)


Constant Groups

- [gdcm](#)
- [gdcm::network](#)


26.260 gdcmULEvent.h File Reference

```
#include "gdcmNetworkStateID.h"
#include "gdcmNetworkEvents.h"
#include "gdcmBasePDU.h"
#include <vector>
```

Include dependency graph for gdcmULEvent.h:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::network::ULEvent`
ULEvent base class for network events.

Namespaces

- `gdcm`
- `gdcm::network`


Constant Groups

- [gdcm](#)
- [gdcm::network](#)


26.261 gdcmULTransitionTable.h File Reference

```
#include "gdcmNetworkStateID.h"
#include "gdcmNetworkEvents.h"
#include "gdcmULAction.h"
#include <cstdlib>
```

Include dependency graph for gdcmULTransitionTable.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::network::TableRow](#)
- struct [gdcm::network::Transition](#)
- class [gdcm::network::ULTransitionTable](#)

ULTransitionTable The transition table of all the ULEvents, new ULActions, and ULStates.

Namespaces


- [gdcm](#)
- [gdcm::network](#)

Constant Groups

- [gdcm](#)
- [gdcm::network](#)

26.262 gdcmULWritingCallback.h File Reference

#include "gdcmULConnectionCallback.h"
 Include dependency graph for gdcmULWritingCallback.h:



Classes

- class [gdcm::network::ULWritingCallback](#)


Namespaces

- [gdcm](#)
- [gdcm::network](#)

Constant Groups

- [gdcm](#)
- [gdcm::network](#)

```
#include "gdcmDataElement.h"
#include "gdcmUNExplicitDataElement.txx"
Include dependency graph for gdcmUNExplicitDataElement.h:
```



- class `gdcm::UNExplicitDataElement`

Class to read/write a [DataElement](#) as UNExplicit Data [Element](#).

- **gdcm**

- gdc

```
#include "gdcmDataElement.h"
#include "gdcmUNExplicitImplicitDataElement.hxx"
```


Classes

- class [gdcm::Unpacker12Bits](#)

Pack/Unpack 12 bits pixel into 16bits.

Namespaces


- [gdcm](#)

Constant Groups


- [gdcm](#)

26.266 gdcmUsage.h File Reference

```
#include "gdcmTypes.h"  
#include <iostream>  
Include dependency graph for gdcmUsage.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcml::Usage](#)
Usage.

Namespaces

- [gdcml](#)

Constant Groups

- [gdcml](#)


Functions

- `std::ostream & gdcm::operator<< (std::ostream &_os, const Usage &val)`


26.267 gdcmUserInformation.h File Reference

```
#include "gdcmTypes.h"
#include "gdcmMaximumLengthSub.h"
#include "gdcmImplementationVersionNameSub.h"
#include "gdcmImplementationClassUIDSub.h"
```

Include dependency graph for `gdcmUserInformation.h`:



This graph shows which files directly or indirectly include this file:




Classes

- class `gdcm::network::UserInformation`


UserInformation Table 9-16 USER INFORMATION ITEM FIELDS.

26.269 gdcmValue.h File Reference

```
#include "gdcmObject.h"
#include "gdcmValue.txx"
Include dependency graph for gdcmValue.h:
```



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::Value](#)
Class to represent the value of a Data [Element](#).

Namespaces

- [gdcm](#)

Constant Groups


- [gdcm](#)

26.270 gdcmValueIO.h File Reference

```
#include "gdcmTypes.h"
```

```
#include "gdcmValueIO.txx"
```

Include dependency graph for gdcmValueIO.h:



Classes

- class `gdcm::ValueIO< TDE, TSwap, TType >`

Class to dispatch template calls.

Namespaces

- `gdcm`


Constant Groups

- `gdcm`

26.271 gdcmVersion.h File Reference

```
#include "gdcmTypes.h"
#include <iostream>
```

Include dependency graph for gdcmVersion.h:



Classes

- class [gdcm::Version](#)
major/minor and build version

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Functions


- `std::ostream & gdcm::operator<< (std::ostream &os, const Version &v)`

26.272 gdcviewer.man File Reference


26.273 gdcmVL.h File Reference

```
#include "gdcmTypes.h"
#include <iostream>
```

Include dependency graph for `gdcmVL.h`:



This graph shows which files directly or indirectly include this file:



Classes

- class `gdcm::VL`
Value Length.

Namespaces

- `gdcm`

Constant Groups

- `gdcm`


Functions

- `std::ostream & gdcm::operator<< (std::ostream &os, const VL &val)`


26.274 gdcmVM.h File Reference

```
#include "gdcmTypes.h"
#include <iostream>
```

Include dependency graph for gdcmVM.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [gdcm::VM](#)
Value Multiplicity Looking at the DICOMV3 dict only there is very few cases: 1 2 3 4 5 6 8 16 24 1-2 1-3 1-8 1-32 1-99 1-n 2-2n 2-n 3-3n 3-n.
- struct [gdcm::VMToLength< T >](#)

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Macros

- #define [TYPETOLENGTH](#)(type, length)

Functions

- std::ostream & [gdcm::operator<<](#) (std::ostream &_os, const VM &_val)

26.274.1 Macro Definition Documentation

26.274.1.1 #define TYPETOLENGTH(type, length)


Value:

```
template<> struct VMToLength<VM::type> \
{ enum { Length = length }; };
```

26.275 gdcmmVR.h File Reference

```
#include "gdcmmTag.h"
#include "gdcmmTrace.h"
#include "gdcmmString.h"
#include <iostream>
#include <fstream>
#include <assert.h>
```

Include dependency graph for gdcmmVR.h:



This graph shows which files directly or indirectly include this file:



Classes

- struct [gdcmm::UI](#)
- class [gdcmm::VR](#)

VR class This is adapted from DICOM standard The biggest difference is the INVALID VR and the composite one that differ from standard (more like an addition) This allow us to represent all the possible case express in the DICOMV3 dict.

- struct [gdcm::VRToEncoding< T >](#)
- struct [gdcm::VRToType< T >](#)

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

Macros

- #define [TYPETOENCODING](#)(type, rep, rtype)
- #define [VRTypeTemplateCase](#)(type)

Typedefs

- typedef String<'\\', 16 > [gdcm::AECComp](#)
- typedef String<'\\', 64 > [gdcm::ASComp](#)
- typedef String<'\\', 16 > [gdcm::CSComp](#)
- typedef String<'\\', 64 > [gdcm::DAComp](#)
- typedef String<'\\', 64 > [gdcm::DTComp](#)
- typedef String<'\\', 64 > [gdcm::LOComp](#)
- typedef String<'\\', 64 > [gdcm::LTComp](#)
- typedef String<'\\', 64 > [gdcm::PNComp](#)
- typedef String<'\\', 64 > [gdcm::SHComp](#)
- typedef String<'\\', 64 > [gdcm::STComp](#)
- typedef String<'\\', 16 > [gdcm::TMComp](#)
- typedef String<'\\', 64, 0 > [gdcm::UIComp](#)
- typedef String<'\\', 64 > [gdcm::UTComp](#)

Functions

- std::ostream & [gdcm::operator<<](#) (std::ostream &_os, const VR &val)
- std::ostream & [gdcm::operator<<](#) (std::ostream &_os, const UI &_val)
- [gdcm::TYPETOENCODING](#) (SQ, VRBINARY, unsigned char) TYPETOENCODING(UN


Variables

- [gdcm::VRBINARY](#)

26.277 gdcmWaveform.h File Reference

```
#include "gdcmFile.h"
```

Include dependency graph for gdcmWaveform.h:



Classes

- class [gdcm::Waveform](#)
Waveform class.

Namespaces

- [gdcm](#)

Constant Groups

- [gdcm](#)

26.278 gdcmWin32.h File Reference

This graph shows which files directly or indirectly include this file:




Macros

- #define [GDCM_EXPORT](#)

- gdc

```
#include "gdcmTableReader.h"
#include "gdcmDict.h"
#include "gdcmDictEntry.h"
#include "gdcmTag.h"
Include dependency graph for gdcmXMLDictReader.h:
```



- class `gdcm::XMLDictReader`
Class for representing a `XMLDictReader`.

- **gdcm**

- `gdcm`

```
#include "gdcmTableReader.h"
#include "gdcmDict.h"
#include "gdcmDictEntry.h"
#include "gdcmTag.h"
```

[illegible]

- class `gdcm::XMLPrivateDictReader`
Class for representing a `XMLPrivateDictReader`.


- **gdcm**

- gdc


26.283 TestsList.txt File Reference

```
#include "vtkMedicalImageReader2.h"
#include "vtkImageData.h"
```

Include dependency graph for vtkGDCMImageReader.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [vtkGDCMImageReader](#)

Namespaces

- [gdc](#)

Constant Groups

- [gdc](#)

Macros

- `#define VTK_CMYK 8`
- `#define VTK_INVERSE_LUMINANCE 5`

- `#define VTK_LOOKUP_TABLE` 6
- `#define VTK_YBR` 7

26.284.1 Macro Definition Documentation

26.284.1.1 `#define VTK_CMYK` 8

26.284.1.2 `#define VTK_INVERSE_LUMINANCE` 5


26.284.1.3 `#define VTK_LOOKUP_TABLE` 6

26.284.1.4 `#define VTK_YBR` 7

26.285 vtkGDCMImageWriter.h File Reference

```
#include "vtkImageWriter.h"
```

Include dependency graph for vtkGDCMImageWriter.h:




Classes

- class `vtkGDCMImageWriter`

26.286 vtkGDCMMedicalImageProperties.h File Reference

```
#include "vtkMedicalImageProperties.h"
```

Include dependency graph for vtkGDCMMedicalImageProperties.h:



Classes

- class [vtkGDCMMedicalImageProperties](#)

Namespaces

- [gdc](#)


Constant Groups

- [gdc](#)

26.287 vtkGDCMPolyDataReader.h File Reference

```
#include "vtkPolyDataAlgorithm.h"
```

Include dependency graph for vtkGDCMPolyDataReader.h:



Classes

- class [vtkGDCMPolyDataReader](#)

Namespaces


- [gdc](#)m

Constant Groups

- [gdc](#)m

26.288 vtkGDCMPolyDataWriter.h File Reference

```
#include "vtkPolyDataWriter.h"  
#include "vtkStringArray.h"  
#include "vtkStdString.h"  
Include dependency graph for vtkGDCMPolyDataWriter.h:
```



Classes

- class [vtkGDCMPolyDataWriter](#)

Namespaces

- [gdc](#)m


Constant Groups

- [gdc](#)m

26.289 vtkGDCMTesting.h File Reference

```
#include "vtkObject.h"
```

Include dependency graph for vtkGDCMTesting.h:




Classes

- class [vtkGDCMTesting](#)

26.290 vtkGDCMThreadedImageReader.h File Reference

```
#include "vtkGDCMImageReader.h"
```

Include dependency graph for vtkGDCMThreadedImageReader.h:




Classes

- class [vtkGDCMThreadedImageReader](#)

26.291 vtkGDCMThreadedImageReader2.h File Reference

```
#include "vtkThreadedImageAlgorithm.h"
```

Include dependency graph for vtkGDCMThreadedImageReader2.h:




Classes

- class [vtkGDCMThreadedImageReader2](#)

26.292 vtkImageColorViewer.h File Reference

```
#include "vtkObject.h"
```

Include dependency graph for vtkImageColorViewer.h:




Classes

- class [vtkImageColorViewer](#)

26.293 vtkImageMapToColors16.h File Reference

```
#include "vtkThreadedImageAlgorithm.h"
```

Include dependency graph for vtkImageMapToColors16.h:




Classes

- class [vtkImageMapToColors16](#)

26.294 vtkImageMapToWindowLevelColors2.h File Reference

```
#include "vtkImageMapToColors.h"
```

Include dependency graph for vtkImageMapToWindowLevelColors2.h:




Classes

- class [vtkImageMapToWindowLevelColors2](#)

26.295 vtkImagePlanarComponentsToComponents.h File Reference

```
#include "vtkImageAlgorithm.h"
```

Include dependency graph for vtkImagePlanarComponentsToComponents.h:




Classes

- class [vtkImagePlanarComponentsToComponents](#)

26.296 vtkImageRGBToYBR.h File Reference

```
#include "vtkThreadedImageAlgorithm.h"
```

Include dependency graph for vtkImageRGBToYBR.h:




Classes

- class [vtkImageRGBToYBR](#)

26.297 vtkImageYBRToRGB.h File Reference

```
#include "vtkThreadedImageAlgorithm.h"
```

Include dependency graph for vtkImageYBRToRGB.h:



Classes


- class [vtkImageYBRToRGB](#)

26.298 vtkLookupTable16.h File Reference

```
#include "vtkLookupTable.h"
```

```
#include "vtkUnsignedShortArray.h"
```

Include dependency graph for vtkLookupTable16.h:




Classes

- class [vtkLookupTable16](#)

26.299 vtkRTStructSetProperties.h File Reference

```
#include "vtkObject.h"
```

Include dependency graph for vtkRTStructSetProperties.h:



Classes

- class [vtkRTStructSetProperties](#)

Chapter 27

Example Documentation

27.1 AWTMedical3.java

```
/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/
package examples;

import vtk.*;
//import gdcm.*;

import vtk.util.VtkPanelContainer;
import vtk.util.VtkPanelUtil;
import vtk.util.VtkUtil;

import java.util.ArrayList;

import javax.swing.*;
import java.awt.*;
import java.io.File;

public class AWTMedical3 extends JComponent implements VtkPanelContainer {

    private vtkPanel renWin;

    vtkImageData ReadDataFile(File inSelectedFile){

        vtkImageData outImageData = null;
        Directory theDir = new Directory();

        String theInputDirectory = inSelectedFile.getPath();
        theDir.Load(theInputDirectory);

        Scanner theScanner = new Scanner();
        Tag theStudyTag = new Tag(0x0020,0x000d);
        Tag theSeriesTag = new Tag(0x0020,0x000e);
        theScanner.AddTag(theStudyTag); //get studies,
        theScanner.AddTag(theSeriesTag); //get studies,
        theScanner.Scan(theDir.GetFilenames());

        FilenamesType theStudyValues = theScanner.GetOrderedValues(theStudyTag);
        long theNumStudies = theStudyValues.size();
        //for now, take the first study, and nothing else.
        //and the return is actually not FilenamesType, just a
        //vector of strings
    }
}
```

```

    if (theNumStudies != 1)
        return outImageData;
    String theStudyVal = theStudyValues.get(0);
    //now, get all the values from the scanner that are in that
    //study, then from that get their different series
    FilenamesType theFilenames =
        theScanner.GetAllFilenamesFromTagToValue(theStudyTag, theStudyVal);

    //from that set of filenames, isolate individual series
    //conclude that singleton series = RT struct (can do further
    //checking for things like MIPs and the like)
    //and multiple series entries = volumetric data
    theScanner.Scan(theFilenames);
    FilenamesType theSeriesValues = theScanner.GetOrderedValues(theSeriesTag);
    String studyUID = theScanner.GetValue(theScanner.GetFilenames().get(0), theStudyTag);
    long theNumSeries = theSeriesValues.size();
    for (int i = 0; i < theNumSeries; i++) {
        FilenamesType theSeriesFiles =
            theScanner.GetAllFilenamesFromTagToValue(theSeriesTag, theSeriesValues.get(i));
        long theNumFilesInSeries = theSeriesFiles.size();
        if (theNumFilesInSeries > 1) { //assume it's CT or volumetric data
            //for now, assume a single volume
            //could have multiples, like PET and CT

            IPPSorter sorter = new IPPSorter();
            sorter.SetComputeZSpacing(true);
            sorter.SetZSpacingTolerance(0.001);
            Boolean sorted = sorter.Sort(theSeriesFiles);
            if (!sorted){
                //need some better way to handle failures here
                return outImageData;
            }

            FilenamesType sortedFT = sorter.GetFilenames();
            long theSize = sortedFT.size();
            vtkStringArray sa = new vtkStringArray();
            ArrayList<String> theStrings = new ArrayList<String>();

            vtkGDCMImageReader gdcmReader = new
            vtkGDCMImageReader();
            for (int j = 0; j < theSize; j++) {
                String theFileName = sortedFT.get(j);
                if (gdcmReader.CanReadFile(theFileName) > 0){
                    theStrings.add(theFileName);
                    sa.InsertNextValue(theFileName);
                } else {
                    //this is a busted series
                    //need some more appropriate error here
                    return outImageData;
                }
            }

            gdcmReader.SetFileNames(sa);

            gdcmReader.Update();

            outImageData = gdcmReader.GetOutput(); //the zeroth output should be the image
        }
    }
    String theImageInfo = "";
    if (outImageData != null){
        theImageInfo = outImageData.Print();
    }
    return outImageData;
}

//this function is a rewrite of Medical3 to see if data can
//be loaded via gdcm easily
public AWTMedical3(File inFile) {
    // Create the buttons.
    renWin = new vtkPanel();

    vtkImageData theImageData = ReadDataFile(inFile);

    // An isosurface, or contour value of 500 is known to correspond to the
    // skin of the patient. Once generated, a vtkPolyDataNormals filter is
    // is used to create normals for smooth surface shading during rendering.
    // The triangle stripper is used to create triangle strips from the
    // isosurface these render much faster on some systems.
    vtkContourFilter skinExtractor = new vtkContourFilter();
    skinExtractor.SetInput(theImageData);

```



```

skinExtractor.SetValue(0, 500);
vtkPolyDataNormals skinNormals = new vtkPolyDataNormals();
skinNormals.SetInput(skinExtractor.GetOutput());
skinNormals.SetFeatureAngle(60.0);
//      vtkStripper skinStripper = new vtkStripper();
//      skinStripper.SetInput(skinNormals.GetOutput());
vtkPolyDataMapper skinMapper = new vtkPolyDataMapper();
skinMapper.SetInput(skinNormals.GetOutput());
skinMapper.ScalarVisibilityOff();
vtkActor skin = new vtkActor();
skin.SetMapper(skinMapper);
skin.GetProperty().SetDiffuseColor(1, .49, .25);
skin.GetProperty().SetSpecular(.3);
skin.GetProperty().SetSpecularPower(20);

// An isosurface, or contour value of 1150 is known to correspond to the
// skin of the patient. Once generated, a vtkPolyDataNormals filter is
// is used to create normals for smooth surface shading during rendering.
// The triangle stripper is used to create triangle strips from the
// isosurface these render much faster on some systems.
vtkContourFilter boneExtractor = new vtkContourFilter();
boneExtractor.SetInput(theImageData);
boneExtractor.SetValue(0, 1150);
vtkPolyDataNormals boneNormals = new vtkPolyDataNormals();
boneNormals.SetInput(boneExtractor.GetOutput());
boneNormals.SetFeatureAngle(60.0);
vtkStripper boneStripper = new vtkStripper();
boneStripper.SetInput(boneNormals.GetOutput());
vtkPolyDataMapper boneMapper = new vtkPolyDataMapper();
boneMapper.SetInput(boneStripper.GetOutput());
boneMapper.ScalarVisibilityOff();
vtkActor bone = new vtkActor();
bone.SetMapper(boneMapper);
bone.GetProperty().SetDiffuseColor(1, 1, .9412);

// An outline provides context around the data.
vtkOutlineFilter outlineData = new vtkOutlineFilter();
outlineData.SetInput(theImageData);
vtkPolyDataMapper mapOutline = new vtkPolyDataMapper();
mapOutline.SetInput(outlineData.GetOutput());
vtkActor outline = new vtkActor();
outline.SetMapper(mapOutline);
outline.GetProperty().SetColor(0, 0, 0);

// Now we are creating three orthogonal planes passing through the
// volume. Each plane uses a different texture map and therefore has
// different coloration.

// Start by creating a black/white lookup table.
vtkLookupTable bwLut = new vtkLookupTable();
bwLut.SetTableRange(0, 2000);
bwLut.SetSaturationRange(0, 0);
bwLut.SetHueRange(0, 0);
bwLut.SetValueRange(0, 1);
bwLut.Build();

// Now create a lookup table that consists of the full hue circle (from
// HSV);.
vtkLookupTable hueLut = new vtkLookupTable();
hueLut.SetTableRange(0, 2000);
hueLut.SetHueRange(0, 1);
hueLut.SetSaturationRange(1, 1);
hueLut.SetValueRange(1, 1);
hueLut.Build();

// Finally, create a lookup table with a single hue but having a range
// in the saturation of the hue.
vtkLookupTable satLut = new vtkLookupTable();
satLut.SetTableRange(0, 2000);
satLut.SetHueRange(.6, .6);
satLut.SetSaturationRange(0, 1);
satLut.SetValueRange(1, 1);
satLut.Build();

// Create the first of the three planes. The filter vtkImageMapToColors
// maps the data through the corresponding lookup table created above.
// The vtkImageActor is a type of vtkProp and conveniently displays an
// image on a single quadrilateral plane. It does this using texture
// mapping and as a result is quite fast. (Note: the input image has to
// be unsigned char values, which the vtkImageMapToColors produces.);
// Note also that by specifying the DisplayExtent, the pipeline

```

```

// requests data of this extent and the vtkImageMapToColors only
// processes a slice of data.
vtkImageMapToColors saggitalColors = new vtkImageMapToColors();
saggitalColors.SetInput(theImageData);
saggitalColors.SetLookupTable(bwLut);
vtkImageActor saggital = new vtkImageActor();
saggital.SetInput(saggitalColors.GetOutput());
saggital.SetDisplayExtent(32, 32, 0, 63, 0, 92);

// Create the second (axial); plane of the three planes. We use the same
// approach as before except that the extent differs.
vtkImageMapToColors axialColors = new vtkImageMapToColors();
axialColors.SetInput(theImageData);
axialColors.SetLookupTable(hueLut);
vtkImageActor axial = new vtkImageActor();
axial.SetInput(axialColors.GetOutput());
axial.SetDisplayExtent(0, 63, 0, 63, 46, 46);

// Create the third (coronal); plane of the three planes. We use the same
// approach as before except that the extent differs.
vtkImageMapToColors coronalColors = new vtkImageMapToColors();
coronalColors.SetInput(theImageData);
coronalColors.SetLookupTable(satLut);
vtkImageActor coronal = new vtkImageActor();
coronal.SetInput(coronalColors.GetOutput());
coronal.SetDisplayExtent(0, 63, 32, 32, 0, 92);

// It is convenient to create an initial view of the data. The FocalPoint
// and Position form a vector direction. Later on (ResetCamera() method)
// this vector is used to position the camera to look at the data in
// this direction.
vtkCamera aCamera = new vtkCamera();
aCamera.SetViewUp(0, 0, -1);
aCamera.SetPosition(0, 1, 0);
aCamera.SetFocalPoint(0, 0, 0);
aCamera.ComputeViewPlaneNormal();

// Actors are added to the renderer. An initial camera view is created.
// The Dolly() method moves the camera towards the FocalPoint,
// thereby enlarging the image.
renWin.GetRenderer().AddActor(saggital);
renWin.GetRenderer().AddActor(axial);
renWin.GetRenderer().AddActor(coronal);
renWin.GetRenderer().AddActor(outline);
renWin.GetRenderer().AddActor(skin);
renWin.GetRenderer().AddActor(bone);

// Turn off bone for this example.
bone.VisibilityOff();

// Set skin to semi-transparent.
skin.GetProperty().SetOpacity(0.5);

// An initial camera view is created. The Dolly() method moves
// the camera towards the FocalPoint, thereby enlarging the image.
renWin.GetRenderer().SetActiveCamera(aCamera);
renWin.GetRenderer().ResetCamera();
aCamera.Dolly(1.5);

// Set a background color for the renderer and set the size of the
// render window (expressed in pixels).
renWin.GetRenderer().SetBackground(1, 1, 1);
VtkPanelUtil.setSize(renWin, 640, 480);

// Note that when camera movement occurs (as it does in the Dolly()
// method), the clipping planes often need adjusting. Clipping planes
// consist of two planes: near and far along the view direction. The
// near plane clips out objects in front of the plane the far plane
// clips out objects behind the plane. This way only what is drawn
// between the planes is actually rendered.
renWin.GetRenderer().ResetCameraClippingRange();

// Setup panel
setLayout(new BorderLayout());
add(renWin, BorderLayout.CENTER);
}

public vtkPanel getRenWin() {
    return renWin;
}

```

```

    }

    public static void main(String s[]) {
        if (s.length == 0){
            return; //need a filename here
        }
        File theFile = new File(s[0]);
        //File theFile = new
            File("/Users/mmroden/Documents/MVSDownloadDirectory/Documents/1.2.840.113704.1.111.3384.1271766367.5/");
        AWTMedical3 panel = new AWTMedical3(theFile);

        JFrame frame = new JFrame("AWTMedical3");
        frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        frame.getContentPane().add("Center", panel);
        frame.pack();
        frame.setVisible(true);
    }
}

```

27.2 BasicAnonymizer.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/BasicAnonymizer.exe gdcmData/012345.002.050.dcm out.dcm
 */
using System;
using gdcm;

public class MyWatcher : SimpleSubjectWatcher
{
    public MyWatcher(Subject s):base(s,"Override String"){
        protected override void StartFilter() {
            System.Console.WriteLine( "This is my start" );
        }
        protected override void EndFilter(){
            System.Console.WriteLine( "This is my end" );
        }
        protected override void ShowProgress(Subject caller, Event evt){
            ProgressEvent pe = ProgressEvent.Cast(evt);
            System.Console.WriteLine( "This is my progress: " + pe.GetProgress() );
        }
        protected override void ShowIteration(){
            System.Console.WriteLine( "This is my iteration" );
        }
        protected override void ShowAnonymization(Subject caller, Event evt){
/*
 * A couple of explanation are necessary here to understand how SWIG work
 * http://www.swig.org/Doc1.3/Java.html#adding_downcasts
 *
 * System.Console.WriteLine( "This is my Anonymization. Type: " + evt.GetEventName() );
 * System.Type type = evt.GetType();
 * System.Console.WriteLine( "This is my Anonymization. System.Type: " + type.ToString() );
 * System.Console.WriteLine( "This is my Anonymization. CheckEvent: " + ae.CheckEvent( evt ) );
 * System.Console.WriteLine( "This is my Anonymization. Processing Tag #" + ae.GetTag().toString() );
 */
            AnonymizeEvent ae = AnonymizeEvent.Cast(evt);
            if( ae != null )
            {
                Tag t = ae.GetTag();
                System.Console.WriteLine( "This is my Anonymization. Processing Tag #" + t.toString() );
            }
        }
    }
}

```

```

    }
    else
    {
        System.Console.WriteLine( "This is my Anonymization. Unhandled Event type: " + evt.GetEventName() );
    }
}
protected override void ShowAbort(){
    System.Console.WriteLine( "This is my abort" );
}
}

public class BasicAnonymizer
{
    public static int Main(string[] args)
    {
        gdcm.Global global = gdcm.Global.GetInstance();
        if( !global.LoadResourcesFiles() )
        {
            System.Console.WriteLine( "Could not LoadResourcesFiles" );
            return 1;
        }

        string file1 = args[0];
        string file2 = args[1];
        Reader reader = new Reader();
        reader.SetFileName( file1 );
        bool ret = reader.Read();
        if( !ret )
        {
            return 1;
        }

        string certpath = gdcm.Filename.Join(gdcm.Testing.GetSourceDirectory(), "
            /Testing/Source/Data/certificate.pem" );
        gdcm.CryptographicMessageSyntax cms = new gdcm.CryptographicMessageSyntax();
        if( !cms.ParseCertificateFile( certpath ) )
        {
            return 1;
        }

        //Anonymizer ano = new Anonymizer();
        SmartPtrAno sano = Anonymizer.New();
        Anonymizer ano = sano.__ref__();

        //SimpleSubjectWatcher watcher = new SimpleSubjectWatcher(ano, "Anonymizer");
        MyWatcher watcher = new MyWatcher(ano);

        ano.SetFile( reader.GetFile() );
        ano.SetCryptographicMessageSyntax( cms );
        if( !ano.BasicApplicationLevelConfidentialityProfile() )
        {
            return 1;
        }

        Writer writer = new Writer();
        writer.SetFileName( file2 );
        writer.SetFile( ano.GetFile() );
        ret = writer.Write();
        if( !ret )
        {
            return 1;
        }

        return 0;
    }
}

```

27.3 BasicImageAnonymizer.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

```

This software is distributed WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the above copyright notice for more information.

```

=====*/

/*
*/
using System;
using gdcm;

public class BasicImageAnonymizer
{
    public static int Main(string[] args)
    {
        string filename = args[0];

        // instantiate the reader:
        gdcm.ImageReader reader = new gdcm.ImageReader();
        reader.SetFileName( filename );

        if (!reader.Read()) return 1;

        Image ir = reader.GetImage();

        uint[] dims = {0, 0, 0};
        dims[0] = ir.GetDimension(0);
        dims[1] = ir.GetDimension(1);
        dims[2] = ir.GetDimension(2);
        System.Console.WriteLine( "Dim:" + dims[0] );
        System.Console.WriteLine( "Dim:" + dims[1] );
        System.Console.WriteLine( "Dim:" + dims[2] );

        // buffer to get the pixels
        byte[] buffer = new byte[ ir.GetBufferLength()];
        System.Console.WriteLine( "Dim:" + ir.GetBufferLength() );
        ir.GetBuffer( buffer );

        for (uint z = 0; z < dims[2]; z++)
        {
            for (uint y = 0; y < dims[1] / 2; y++) // only half Y
            {
                for (uint x = 0; x < dims[0] / 2; x++) // only half X
                {
                    buffer[ (z * dims[1] + y) * dims[0] + x ] = 0; // works when pixel type == UINT8
                }
            }
        }

        DataElement pixeldata = new DataElement( new Tag(0x7fe0,0x0010) );
        pixeldata.SetByteValue( buffer, new VL( (uint)buffer.Length ) );
        ir.SetDataElement( pixeldata );
        ir.SetTransferSyntax( new TransferSyntax( TransferSyntax.TSType.ExplicitVRLittleEndian ) );

        ImageChangeTransferSyntax change = new ImageChangeTransferSyntax();
        change.SetTransferSyntax( new TransferSyntax( TransferSyntax.TSType.JPEGLSLossless ) );
        change.SetInput( ir );
        if( !change.Change() )
        {
            System.Console.WriteLine( "Could not change: " + filename );
            return 1;
        }

        ImageWriter writer = new ImageWriter();
        writer.SetFileName( "out.dcm" );
        writer.SetFile( reader.GetFile() );
        writer.SetImage( change.GetOutput() );
        bool ret = writer.Write();
        if( !ret )
        {
            return 1;
        }

        return 0;
    }
}

```

27.4 CastConvertPhilips.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:
17
18     python --public /path/to/directory/
19 or
20     python --private /path/to/directory/
21
22     python --public --extension bak /path/to/directory/
23
24     rename -f 's/\.bak$/' *.bak
25
26 TODO:
27 http://docs.python.org/library/optparse.html#module-optparse
28 """
29
30 import vtkgdcm
31 import vtk
32 import sys
33 import gdcm
34
35 def ProcessOneFilePublic(filename, outfilename, tmpfile):
36     gdcm.ImageHelper.SetForceRescaleInterceptSlope(True)
37     vtkreader = vtkgdcm.vtkGDCMImageReader()
38     vtkreader.SetFileName( filename )
39     vtkreader.Update()
40
41     cast = vtk.vtkImageCast()
42     cast.SetInput( vtkreader.GetOutput() )
43     cast.SetOutputScalarTypeToUnsignedShort()
44
45     # vtkGDCMImageWriter does not support Sequence, so let's write a tmp file first:
46     # Some operation will actually be discarded (we simply need a temp storage)
47     vtkwriter = vtkgdcm.vtkGDCMImageWriter()
48     vtkwriter.SetFileName( tmpfile )
49     vtkwriter.SetMedicalImageProperties( vtkreader.GetMedicalImageProperties() )
50     vtkwriter.SetDirectionCosines( vtkreader.GetDirectionCosines() )
51     print "Format:", vtkreader.GetImageFormat()
52     vtkwriter.SetImageFormat( vtkreader.GetImageFormat() )
53     vtkwriter.SetInput( cast.GetOutput() )
54     #vtkwriter.Update()
55     vtkwriter.Write()
56
57     # ok now rewrite the exact same file as the original (keep all info)
58     # but use the Pixel Data Element from the written file
59     tmpreader = gdcm.ImageReader()
60     tmpreader.SetFileName( tmpfile )
61     if not tmpreader.Read():
62         sys.exit(1)
63
64     reader = gdcm.Reader()
65     reader.SetFileName( filename )
66     if not reader.Read():
67         sys.exit(1)
68
69     # Make sure to remove Slope/Rescale to avoid re-execution
70     ds = reader.GetFile().GetDataSet()
71     tags = [
72         gdcm.Tag(0x0028,0x1052),
73         gdcm.Tag(0x0028,0x1053),
74         gdcm.Tag(0x0028,0x1053),
75     ]
76     for tag in tags:
77         ds.Remove( tag )
78

```

```

79 writer = gdcmm.ImageWriter()
80 writer.SetFileName( outfilename )
81 # Pass image from vtk written file
82 writer.SetImage( tmpreader.GetImage() )
83 # pass dataset from initial 'reader'
84 writer.SetFile( reader.GetFile() )
85 if not writer.Write():
86     sys.exit(1)
87
88 def ProcessOneFilePrivate(filename, outfilename, tmpfile):
89     vtkreader = vtkgdcmm.vtkGDCMImageReader()
90     vtkreader.SetFileName( filename )
91     vtkreader.Update()
92
93
94 # (2005,1409)      DS      4      0.0
95 # (2005,140a)      DS      16     1.52283272283272
96
97 # (2005,0014)      LO      26     Philips MR Imaging DD 005
98 tag1 = gdcmm.PrivateTag(0x2005,0x09,"Philips MR Imaging DD 005")
99 tag2 = gdcmm.PrivateTag(0x2005,0x0a,"Philips MR Imaging DD 005")
100
101
102
103 # Need to access some private tags, reread the file (for now):
104 reader = gdcmm.Reader()
105 reader.SetFileName( filename )
106 if not reader.Read():
107     sys.exit(1)
108
109 ds = reader.GetFile().GetDataSet()
110
111 el1 = ds.GetDataElement( tag1 )
112 el2 = ds.GetDataElement( tag2 )
113
114
115 #pf = gdcmm.PythonFilter()
116 #pf.SetFile( reader.GetFile() )
117 #print el1.GetTag()
118
119 print el1.GetByteValue()
120 v1 = eval(el1.GetByteValue().GetBuffer())
121 print el2.GetByteValue()
122 v2 = eval(el2.GetByteValue().GetBuffer())
123
124 print v1
125 shift = v1
126 print v2
127 scale = v2
128
129 ss = vtk.vtkImageShiftScale()
130 ss.SetInput( vtkreader.GetOutput() )
131 # because VTK image shift / scale convention is inverted from DICOM make sure shift is 0
132 assert shift == 0
133 ss.SetShift( shift )
134 ss.SetScale( scale )
135 ss.SetOutputScalarTypeToUnsignedShort ( )
136 ss.Update()
137
138 # vtkGDCMImageWriter does not support Sequence, so let's write a tmp file first:
139 # Some operation will actually be discarded (we simply need a temp storage)
140 vtkwriter = vtkgdcmm.vtkGDCMImageWriter()
141 vtkwriter.SetFileName( tmpfile )
142 vtkwriter.SetMedicalImageProperties( vtkreader.GetMedicalImageProperties() )
143 vtkwriter.SetDirectionCosines( vtkreader.GetDirectionCosines() )
144 vtkwriter.SetImageFormat( reader.GetImageFormat() )
145 # do not pass shift/scale again
146 vtkwriter.SetInput( ss.GetOutput() )
147 #vtkwriter.Update()
148 vtkwriter.Write()
149
150 # ok now rewrite the exact same file as the original (keep all info)
151 # but use the Pixel Data Element from the written file
152 tmpreader = gdcmm.ImageReader()
153 tmpreader.SetFileName( tmpfile )
154 if not tmpreader.Read():
155     sys.exit(1)
156
157 writer = gdcmm.ImageWriter()
158 writer.SetFileName( outfilename )
159 # Pass image from vtk written file

```

```

160 writer.SetImage( tmpreader.GetImage() )
161 # pass dataset from initial 'reader'
162 writer.SetFile( reader.GetFile() )
163 if not writer.Write():
164     sys.exit(1)
165
166 if __name__ == "__main__":
167
168     gdcmm.Trace.DebugOff()
169     gdcmm.Trace.WarningOff()
170     #filename = sys.argv[1]
171     #outfilename = sys.argv[2]
172     tmpfile = "/tmp/philips_rescaled.dcm"
173     #ProcessOneFile( filename, outfilename, tmpfile )
174     rescaletype = sys.argv[1]
175     assert rescaletype == "--public" or rescaletype == "--private"
176     dirname = sys.argv[2]
177     d = gdcmm.Directory()
178     d.Load( dirname )
179
180     for f in d.GetFilenames():
181         #print f
182         ProcessOneFilePublic( f, f + ".bak", tmpfile )
183
184
185 print "success"

```

27.5 ChangeSequenceUltrasound.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmmReader.h"
#include "gdcmmWriter.h"
#include "gdcmmSmartPointer.h"
#include "gdcmmDataSetHelper.h"

/*
./ChangeSequenceUltrasound gdcmmData/D_CLUNIE_CT1_J2KI.dcm myoutput.dcm

This is the exact C++ translation of the original python example: ManipulateSequence.py
*/

int main(int argc, char* argv[] )
{
    if( argc < 0 )
    {
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];

    gdcmm::Reader reader;
    reader.SetFileName( filename );
    if (! reader.Read() )
    {
        return 1;
    }

    gdcmm::File &file = reader.GetFile();
    gdcmm::DataSet &ds = file.GetDataSet();
    gdcmm::Tag tsis(0x0008,0x2112); // SourceImageSequence
    if ( ds.FindDataElement( tsis ) )
    {
        const gdcmm::DataElement &sis = ds.GetDataElement( tsis );
        gdcmm::SmartPointer<gdcmm::SequenceOfItems> sqsis = sis.
            GetValueAsSQ();

```



```

if ( sqsis && sqsis->GetNumberOfItems() )
{
    gdc::Item &item1 = sqsis->GetItem(1);
    gdc::DataSet &nestedds = item1.GetNestedDataSet();
    gdc::Tag tprcs(0x0040,0xa170); // PurposeOfReferenceCodeSequence
    if( nestedds.FindDataElement( tprcs ) )
    {
        const gdc::DataElement &prcs = nestedds.GetDataElement( tprcs );
        gdc::SmartPointer<gdc::SequenceOfItems> sqprcs = prcs.
        GetValueAssQ();
        if ( sqprcs && sqprcs->GetNumberOfItems() )
        {
            gdc::Item &item2 = sqprcs->GetItem(1);
            gdc::DataSet &nestedds2 = item2.GetNestedDataSet();
            // (0008,0104) LO [Uncompressed predecessor] # 24, 1 CodeMeaning
            gdc::Tag tcm(0x0008,0x0104);
            if( nestedds2.FindDataElement( tcm ) )
            {
                gdc::DataElement cm = nestedds2.GetDataElement( tcm );
                std::string mystr = "GDCM was here";
                cm.SetByteValue( mystr.c_str(), (uint32_t)mystr.size() );
                nestedds2.Replace( cm );
            }
        }
    }
}

gdc::Writer writer;
writer.SetFile( file );
writer.SetFileName( outfilename );
if ( !writer.Write() )
{
    return 1;
}

return 0;
}

```

27.6 CheckBigEndianBug.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdc.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * WARNING: This is a dev tool, do not use !
 *
 * Usage: after a gdcconv, you would like to know if the conversion process is acceptable
 * sometime a vbindiff is acceptable, sometime it is not. In the case of the famous Philips
 * Little/Big Endian Explicit Transfer Syntax it is not easy to compare two files. However
 * this only impact byte ordering, thus we can compute byte-independant information to still
 * compare the files.
 */

#include "gdcmImageReader.h"
#include "gdcmImage.h"
#include "gdcmWriter.h"
#include "gdcmAttribute.h"
#include "gdcmSystem.h"

#include <iostream>
#include <fstream>

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {

```

```

    std::cerr << argv[0] << " input1.dcm input2.dcm" << std::endl;
    return 1;
}
const char *filename1 = argv[1];
const char *filename2 = argv[2];

gdcm::ImageReader reader1;
reader1.SetFileName( filename1 );
if( !reader1.Read() )
{
    std::cerr << "Could not read: " << filename1 << std::endl;
    return 1;
}

gdcm::ImageReader reader2;
reader2.SetFileName( filename2 );
if( !reader2.Read() )
{
    std::cerr << "Could not read: " << filename2 << std::endl;
    return 1;
}

// TODO: need a DataSet== operator implementation

std::cout << "Both files can be read and looks like DICOM" << std::endl;

size_t s1 = gdcm::System::FileSize(filename1);
size_t s2 = gdcm::System::FileSize(filename2);

if( s1 != s2 )
{
    std::cout << "Size mismatch: " << s1 << " != " << s2 << std::endl;
    return 1;
}
else
{
    std::cout << "Size match: " << s1 << " = " << s2 << std::endl;
}

std::ifstream is1( filename1 );
char *buffer1 = new char[s1];
is1.read(buffer1, s1);

std::ifstream is2( filename2 );
char *buffer2 = new char[s2];
is2.read(buffer2, s2);

assert( s1 == s2 );
if( memcmp(buffer1, buffer2, s1 ) == 0 )
{
    std::cout << "memcmp succeed ! File are bit identical" << std::endl;
}
else
{
    std::cout << "memcmp failed!" << std::endl;
}

// Hum...memcmp failed, for big endian/ little endian inversion the histogram of bytes
// should still be the same. So let's compute it
// buffer2[0] = 1; // let's make the test fail
std::multiset<char> set1( buffer1, buffer1 + s1 );
std::multiset<char> set2( buffer2, buffer2 + s2 );

if( set1 == set2 )
{
    std::cout << "set1 == set2. Byte histogram seems valid" << std::endl;
}
else
{
    std::cout << "set1 != set2" << std::endl;
}
delete[] buffer1;
delete[] buffer2;

return 0;
}

```

27.7 ClinicalTrialAnnotate.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * Dummy implementation of C.7.1.3 Clinical Trial Subject Module
 *
 * Usage:
 * ClinicalTrialAnnotate gdcmData/012345.002.050.dcm out.dcm
 */

#include "gdcmReader.h"
#include "gdcmWriter.h"
#include "gdcmAnonymizer.h"

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];

    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Could not read: " << filename << std::endl;
        return 1;
    }

    // The output of gdcm::Reader is a gdcm::File
    //gdcm::File &file = reader.GetFile();

    // the dataset is the the set of element we are interested in:
    //gdcm::DataSet &ds = file.GetDataSet();

    gdcm::Anonymizer ano;
    ano.SetFile( reader.GetFile() );
    ano.RemoveGroupLength();
    ano.RemovePrivateTags();

    // PS 3.3 - 2008
    // C.7.1.3 Clinical Trial Subject Module
    // <entry group="0012" element="0010" vr="LO" vm="1" name="Clinical Trial Sponsor Name"/>
    ano.Replace( gdcm::Tag(0x12,0x10), "BigCompany name" );
    // <entry group="0012" element="0020" vr="LO" vm="1" name="Clinical Trial Protocol ID"/>
    ano.Replace( gdcm::Tag(0x12,0x20), "My Clinical Trial Protocol ID" );
    // <entry group="0012" element="0021" vr="LO" vm="1" name="Clinical Trial Protocol Name"/>
    ano.Replace( gdcm::Tag(0x12,0x21), "My Clinical Trial Protocol Name" );
    // <entry group="0012" element="0030" vr="LO" vm="1" name="Clinical Trial Site ID"/>
    ano.Replace( gdcm::Tag(0x12,0x30), "My Clinical Trial Site ID" );
    // <entry group="0012" element="0031" vr="LO" vm="1" name="Clinical Trial Site Name"/>
    ano.Replace( gdcm::Tag(0x12,0x31), "My Clinical Trial Site Name" );
    // <entry group="0012" element="0040" vr="LO" vm="1" name="Clinical Trial Subject ID"/>
    ano.Replace( gdcm::Tag(0x12,0x40), "My Clinical Trial Subject ID" );
    // <entry group="0012" element="0042" vr="LO" vm="1" name="Clinical Trial Subject Reading ID"/>
    ano.Replace( gdcm::Tag(0x12,0x42), "My Clinical Trial Subject Reading ID" );

    gdcm::Writer writer;
    writer.SetFile( reader.GetFile() );
    writer.SetFileName( outfile );
    if( !writer.Write() )
    {
        return 1;
    }
}

```

```

    return 0;
}

```

27.8 ClinicalTrialIdentificationWorkflow.cs

This is a C# example on how to use [gdcm::Anonymizer](#)

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

/*
 * Typical usage on UNIX:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/ClinicalTrialIdentificationWorkflow.exe input_dir output_dir
 */
using System;
using gdcm;

public class MyWatcher : SimpleSubjectWatcher
{
    public MyWatcher(Subject s):base(s,"Override String"){
    protected override void StartFilter() {
        System.Console.WriteLine( "This is my start" );
    }
    protected override void EndFilter(){
        System.Console.WriteLine( "This is my end" );
    }
    protected override void ShowProgress(Subject caller, Event evt){
        ProgressEvent pe = ProgressEvent.Cast(evt);
        System.Console.WriteLine( "This is my progress: " + pe.GetProgress() );
    }
    protected override void ShowIteration(){
        System.Console.WriteLine( "This is my iteration" );
    }
    protected override void ShowAnonymization(Subject caller, Event evt){
/*
 * A couple of explanation are necessary here to understand how SWIG work
 * http://www.swig.org/Doc1.3/Java.html#adding_downcasts
 *
 * System.Console.WriteLine( "This is my Anonymization. Type: " + evt.GetEventName() );
 * System.Type type = evt.GetType();
 * System.Console.WriteLine( "This is my Anonymization. System.Type: " + type.ToString() );
 * System.Console.WriteLine( "This is my Anonymization. CheckEvent: " + ae.CheckEvent( evt ) );
 * System.Console.WriteLine( "This is my Anonymization. Processing Tag #" + ae.GetTag().toString() );
 */
        AnonymizeEvent ae = AnonymizeEvent.Cast(evt);
        if( ae != null )
        {
            Tag t = ae.GetTag();
            System.Console.WriteLine( "This is my Anonymization. Processing Tag #" + t.toString() );
        }
        else
        {
            System.Console.WriteLine( "This is my Anonymization. Unhandled Event type: " + evt.GetEventName() );
        }
    }
    protected override void ShowAbort(){
        System.Console.WriteLine( "This is my abort" );
    }
}

public class ClinicalTrialIdentificationWorkflow
{
    public static bool ProcessOneFile( gdcm.Anonymizer ano , string filename, string outfilename )
    {

```

```

Reader reader = new Reader();
reader.SetFileName( filename );
bool ret = reader.Read();
if( !ret )
{
    return false;
}
// Pass in the file:
ano.SetFile( reader.GetFile() );

// First step, let's protect all Patient information as per
// PS 3.15 / E.1 / Basic Application Level Confidentiality Profile
if( !ano.BasicApplicationLevelConfidentialityProfile() )
{
    return false;
}

// Now let's pass in all Clinical Trial fields
// PS 3.3 - 2008 / C.7.1.3 Clinical Trial Subject Module
/*
Clinical Trial Sponsor Name (0012,0010) 1 The name of the clinical trial sponsor. See C.7.1.3.1.1.
Clinical Trial Protocol ID (0012,0020) 1 Identifier for the noted protocol. See C.7.1.3.1.2.
Clinical Trial Protocol Name (0012,0021) 2 The name of the clinical trial protocol. See C.7.1.3.1.3.
Clinical Trial Site ID (0012,0030) 2 The identifier of the site responsible for submitting clinical
    trial data. See C.7.1.3.1.4.
Clinical Trial Site Name (0012,0031) 2 Name of the site responsible for submitting clinical trial data.
    See C.7.1.3.1.5
Clinical Trial Subject ID (0012,0040) 1C The assigned identifier for the clinical trial subject. See
    C.7.1.3.1.6. Shall be present if Clinical Trial Subject Reading ID (0012,0042) is absent. May be present
    otherwise.
Clinical Trial Subject Reading ID (0012,0042) 1C Identifies the subject for blinded evaluations. Shall
    be present if Clinical Trial Subject ID (0012,0040) is absent. May be present otherwise. See C.7.1.3.1.7.
*/
ano.Replace( new gdcm.Tag(0x0012,0x0010), "MySponsorName");
ano.Replace( new gdcm.Tag(0x0012,0x0020), "MyProtocolID");
ano.Replace( new gdcm.Tag(0x0012,0x0021), "MyProtocolName");
ano.Replace( new gdcm.Tag(0x0012,0x0030), "MySiteId");
ano.Replace( new gdcm.Tag(0x0012,0x0031), "MySiteName");
ano.Replace( new gdcm.Tag(0x0012,0x0040), "MySponsorId");
ano.Replace( new gdcm.Tag(0x0012,0x0050), "MyTPId");
ano.Replace( new gdcm.Tag(0x0012,0x0051), "MyTPDescription");

// The following two are not required as they are guaranteed to be filled in by the
// Basic Application Level Confidentiality Profile. Only override if you understand what
// you are doing
//ano.Replace( new gdcm.Tag(0x0012,0x0062), "YES");
//ano.Replace( new gdcm.Tag(0x0012,0x0063), "My Super Duper Anonymization Overload");

// We might be generating a subdirectory. Let's make sure the subdir exist:
gdcm.FileName fn = new gdcm.FileName( outfilename );
string subdir = fn.GetPath();
if( !gdcm.PosixEmulation.MakeDirectory( subdir ) )
{
    return false;
}

gdcm.FileMetaInformation fmi = ano.GetFile().GetHeader();
// The following three lines make sure to regenerate any value:
fmi.Remove( new gdcm.Tag(0x0002,0x0012) );
fmi.Remove( new gdcm.Tag(0x0002,0x0013) );
fmi.Remove( new gdcm.Tag(0x0002,0x0016) );

Writer writer = new Writer();
writer.SetFileName( outfilename );
writer.SetFile( ano.GetFile() );
ret = writer.Write();
if( !ret )
{
    return false;
}

return true;
}

public static int Main(string[] args)
{
    gdcm.FileMetaInformation.SetSourceApplicationEntityTitle( "My ClinicalTrial App" );

    // http://www.oid-info.com/get/1.3.6.1.4.17434
    string THERALYS_ORG_ROOT = "1.3.6.1.4.17434";
    gdcm.UIDGenerator.SetRoot( THERALYS_ORG_ROOT );

```

```

System.Console.WriteLine( "Root dir is now: " + gdcml.UIDGenerator.GetRoot() );

gdcml.Global global = gdcml.Global.GetInstance();
if( !global.LoadResourcesFiles() )
{
    System.Console.WriteLine( "Could not LoadResourcesFiles" );
    return 1;
}

if( args.Length != 2 )
{
    System.Console.WriteLine( "Usage:" );
    System.Console.WriteLine( "ClinicalTrialIdentificationWorkflow input_dir output_dir" );
    return 1;
}
string dir1 = args[0];
string dir2 = args[1];

// Check input is valid:
if( !gdcml.PosixEmulation.FileIsDirectory(dir1) )
{
    System.Console.WriteLine( "Input directory: " + dir1 + " does not exist. Sorry" );
    return 1;
}
if( !gdcml.PosixEmulation.FileIsDirectory(dir2) )
{
    System.Console.WriteLine( "Output directory: " + dir2 + " does not exist. Sorry" );
    return 1;
}

// Recursively search all file within this toplevel directory:
Directory d = new Directory();
uint nfiles = d.Load( dir1, true );
if(nfiles == 0) return 1;

// Let's use the pre-shipped certificate of GDCM.
string certpath = gdcml.Filename.Join(gdcml.Testing.GetSourceDirectory(), "
/Testing/Source/Data/certificate.pem" );
gdcml.CryptographicMessageSyntax cms = new gdcml.CryptographicMessageSyntax();
if( !cms.ParseCertificateFile( certpath ) )
{
    System.Console.WriteLine( "PEM Certificate : " + certpath + " could not be read. Sorry" );
    return 1;
}

//Anonymizer ano = new Anonymizer();
// A reference to an actual C++ instance is required here:
SmartPtrAno sano = Anonymizer.New();
Anonymizer ano = sano.__ref__();

//SimpleSubjectWatcher watcher = new SimpleSubjectWatcher(ano, "Anonymizer");
MyWatcher watcher = new MyWatcher(ano);

// Explicitely specify the Cryptographic Message Syntax to use:
ano.SetCryptographicMessageSyntax( cms );

// Process all filenames:
FilenamesType filenames = d.GetFilesNames();
for( uint i = 0; i < nfiles; ++i )
{
    string filename = filenames[ (int)i ];
    string outfilename = filename.Replace( dir1, dir2 );
    System.Console.WriteLine( "Filename: " + filename );
    System.Console.WriteLine( "Out Filename: " + outfilename );
    if( !ProcessOneFile( ano, filename, outfilename ) )
    {
        System.Console.WriteLine( "Could not process filename: " + filename );
        return 1;
    }
}

return 0;
}
}

```

27.9 CompressImage.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 *
 */

#include "gdcmImageReader.h"
#include "gdcmImage.h"
#include "gdcmWriter.h"
#include "gdcmAttribute.h"
#include "gdcmImageWriter.h"
#include "gdcmImageChangeTransferSyntax.h"

#include <iostream>
#include <fstream>

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];

    gdcm::ImageReader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Could not read: " << filename << std::endl;
        return 1;
    }

    // The output of gdcm::Reader is a gdcm::File
    //gdcm::File &file = reader.GetFile();

    // the dataset is the the set of element we are interested in:
    //gdcm::DataSet &ds = file.GetDataSet();

    const gdcm::Image &image = reader.GetImage();
    image.Print( std::cout );

    gdcm::ImageChangeTransferSyntax change;
    change.SetTransferSyntax(
        gdcm::TransferSyntax::JPEG2000Lossless );
    change.SetTransferSyntax(
        gdcm::TransferSyntax::JPEGLosslessProcess14_1 );
    //change.SetTransferSyntax( gdcm::TransferSyntax::JPEGBaselineProcess1 );
    //change.SetTransferSyntax( image.GetTransferSyntax() );
    change.SetInput( image );
    bool b = change.Change();
    if( !b )
    {
        std::cerr << "Could not change the Transfer Syntax" << std::endl;
        return 1;
    }

    //std::ofstream out( outfile );
    //image.GetBuffer2(out);
    //out.close();
    gdcm::ImageWriter writer;
    writer.SetImage( change.GetOutput() );
    writer.SetFile( reader.GetFile() );
    writer.SetFileName( outfile );
    if( !writer.Write() )
    {

```

```

    return 1;
}

return 0;
}

```

27.10 CompressLossyJPEG.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Perso/gdcm/debug-gcc/bin
 * $ mono bin/CompressLossyJPEG.exe input.dcm output.dcm
 */

using System;
using gdcm;

public class CompressLossyJPEG
{
    public static int Main(string[] args)
    {
        if( args.Length < 2 )
        {
            System.Console.WriteLine( " input.dcm output.dcm" );
            return 1;
        }
        string filename = args[0];
        string outfilename = args[1];

        ImageReader reader = new ImageReader();
        reader.SetFileName( filename );
        if( !reader.Read() )
        {
            System.Console.WriteLine( "Could not read: " + filename );
            return 1;
        }

        // The output of gdcm::Reader is a gdcm::File
        File file = reader.GetFile();

        // the dataset is the the set of element we are interested in:
        DataSet ds = file.GetDataSet();

        Image image = reader.GetImage();
        //image.Print( cout );

        ImageChangeTransferSyntax change = new ImageChangeTransferSyntax();
        TransferSyntax targetts = new TransferSyntax( TransferSyntax.TSType.JPEGBaselineProcess1 );
        change.SetTransferSyntax( targetts );

        // Setup our JPEGCodec, warning it should be compatible with JPEGBaselineProcess1
        JPEGCodec jpegcodec = new JPEGCodec();
        if( !jpegcodec.CanCode( targetts ) )
        {
            System.Console.WriteLine( "Something went really wrong, JPEGCodec cannot handle JPEGBaselineProcess1" );
            return 1;
        }
        jpegcodec.SetLossless( false );
        jpegcodec.SetQuality( 50 ); // poor quality !
        change.SetUserCodec( jpegcodec ); // specify the codec to use to the ImageChangeTransferSyntax

        change.SetInput( image );
        bool b = change.Change();
    }
}

```



```

    if( !b )
    {
        System.Console.WriteLine( "Could not change the Transfer Syntax" );
        return 1;
    }

    ImageWriter writer = new ImageWriter();
    writer.SetImage( (gdcm.Image)change.GetOutput() );
    writer.SetFile( reader.GetFile() );
    writer.SetFileName( outfilename );
    if( !writer.Write() )
    {
        System.Console.WriteLine( "Could not write: " + outfilename );
        return 1;
    }

    return 0;
}
}

```

27.11 Convert16BitsTo8Bits.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkGDCMImageReader.h"
#include "vtkGDCMImageWriter.h"
#include "vtkImageData.h"
#include "vtkImageCast.h"

#include "gdcmTesting.h"
// The following file is 16/16/15 but the scalar range of the image is [0,192]
// it could be safely stored as 8bits instead:
// gdcmData/012345.002.050.dcm

int main(int, char *[])
{
    const char *directory = gdcm::Testing::GetDataRoot();
    if(!directory) return 1;
    std::string file = std::string(directory) + "/012345.002.050.dcm";
    std::cout << file << std::endl;

    vtkGDCMImageReader *reader = vtkGDCMImageReader::New();
    reader->SetFileName( file.c_str() );
    reader->Update();
    //reader->GetOutput()->Print( std::cout );

    vtkImageCast *cast = vtkImageCast::New();
    cast->SetInput( reader->GetOutput() );
    cast->SetOutputScalarTypeToUnsignedChar();

    vtkGDCMImageWriter *writer = vtkGDCMImageWriter::New();
    writer->SetFileName( "/tmp/cast.dcm" );
    writer->SetInput( cast->GetOutput() );
    writer->SetImageFormat( reader->GetImageFormat() );
    writer->SetMedicalImageProperties( reader->GetMedicalImageProperties() );
    writer->SetDirectionCosines( reader->GetDirectionCosines() );
    writer->SetShift( reader->GetShift() );
    writer->SetScale( reader->GetScale() );
    writer->Write();

    reader->Delete();
    cast->Delete();
    writer->Delete();
}

```

```

    return 0;
}

```

27.12 ConvertMPL.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 display a DICOM image with matplotlib via numpy
17
18 Caveats:
19 - Does not support UINT12/INT12
20
21 Usage:
22
23   python ConvertNumpy.py "IM000000"
24
25 Thanks:
26   plotting example - Ray Schumacher 2009
27 """
28
29 import gdcm
30 import numpy
31 from pylab import *
32
33
34 def get_gdcm_to_numpy_typemap():
35     """Returns the GDCM Pixel Format to numpy array type mapping."""
36     _gdcm_np = {gdcm.PixelFormat.UINT8 :numpy.int8,
37                 gdcm.PixelFormat.INT8  :numpy.uint8,
38                 gdcm.PixelFormat.UINT16:numpy.uint16,
39                 gdcm.PixelFormat.INT16 :numpy.int16,
40                 gdcm.PixelFormat.UINT32 :numpy.uint32,
41                 gdcm.PixelFormat.INT32  :numpy.int32,
42                 gdcm.PixelFormat.FLOAT32:numpy.float32,
43                 gdcm.PixelFormat.FLOAT64:numpy.float64 }
44     return _gdcm_np
45
46 def get_numpy_array_type(gdcm_pixel_format):
47     """Returns a numpy array typecode given a GDCM Pixel Format."""
48     return get_gdcm_to_numpy_typemap()[gdcm_pixel_format]
49
50 def gdcm_to_numpy(image):
51     """Converts a GDCM image to a numpy array.
52     """
53     pf = image.GetPixelFormat().GetScalarType()
54     print 'pf', pf
55     print image.GetPixelFormat().GetScalarTypeAsString()
56     assert pf in get_gdcm_to_numpy_typemap().keys(), \
57         "Unsupported array type %s"%pf
58     d = image.GetDimension(0), image.GetDimension(1)
59     print 'Image Size: %d x %d' % (d[0], d[1])
60     dtype = get_numpy_array_type(pf)
61     gdcm_array = image.GetBuffer()
62     ## use float for accurate scaling
63     result = numpy.frombuffer(gdcm_array, dtype=dtype).astype(float)
64     ## optional gamma scaling
65     #maxV = float(result[result.argmax()])
66     #result = result + .5*(maxV-result)
67     #result = numpy.log(result+50) ## apprxx background level
68     result.shape = d
69     return result
70
71 if __name__ == "__main__":
72     import sys

```

```

73  r = gdcm.ImageReader()
74  filename = sys.argv[1]
75  r.SetFileName( filename )
76  if not r.Read(): sys.exit(1)
77  numpy_array = gdcm_to_numpy( r.GetImage() )
78
79  subplot(111)# one plot, on left
80  title(filename)
81  ## many colormaps are available
82  imshow(numpy_array, interpolation='bilinear', cmap=cm.jet)
83  ## set the plot sizes and placement
84  subplots_adjust(bottom=0.1, right=0.8, top=0.9)
85  cax = axes([0.85, 0.1, 0.075, 0.8])
86  colorbar(cax=cax)
87  title('values')
88  get_current_fig_manager().window.title('plot')
89  show()

```

27.13 ConvertMultiFrameToSingleFrame.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkGDCMImageReader.h"
#include "vtkGDCMImageWriter.h"
#include "vtkImageData.h"
#include "vtkStringArray.h"

#include "gdcmTesting.h"
#include "gdcmFilenameGenerator.h"

int main(int argc, char *argv[])
{
    std::string filename;
    if( argc <= 1 )
    {
        const char *directory = gdcm::Testing::GetDataRoot();
        if(!directory) return 1;
        std::string file = std::string(directory) + "/US-PAL-8-10x-echo.dcm";
        filename = file;
    }
    else
    {
        filename = argv[1];
    }
    std::cout << "file: " << filename << std::endl;

    vtkGDCMImageReader *reader = vtkGDCMImageReader::New();
    reader->SetFileName( filename.c_str() );
    reader->Update();
    //reader->GetOutput()->Print( std::cout );

    int dims[3];
    reader->GetOutput()->GetDimensions( dims );

    std::ostringstream os;
    os << "singleframe";
    os << "%04d.dcm";
    gdcm::FilenameGenerator fg;
    fg.SetPattern( os.str().c_str() );
    unsigned int nfiles = dims[2];
    fg.SetNumberOfFileNames( nfiles );
    bool b = fg.Generate();
    if( !b )
    {
        std::cerr << "FilenameGenerator::Generate() failed" << std::endl;
        return 1;
    }
}

```

```

    }
    if( !fg.GetNumberOfFileNames() )
    {
        std::cerr << "FilenameGenerator::Generate() failed somehow..." << std::endl;
        return 1;
    }

    // By default write them as Secondary Capture (for portability)
    vtkGDCMImageWriter *writer = vtkGDCMImageWriter::New();
    vtkStringArray *filenames = vtkStringArray::New();
    for(unsigned int i = 0; i < fg.GetNumberOfFileNames(); ++i)
    {
        filenames->InsertNextValue( fg.GetFilename(i) );
    }
    assert( filenames->GetNumberOfValues() == (int)fg.GetNumberOfFileNames() );
    writer->SetFileNames( filenames );
    filenames->Delete();
    writer->SetFileDimensionality( 2 );
    writer->SetInput( reader->GetOutput() );
    writer->SetImageFormat( reader->GetImageFormat() );
    writer->Write();

    reader->Delete();
    writer->Delete();

    return 0;
}

```

27.14 ConvertNumpy.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 This module add support for converting a gdcm.Image to a numpy array.
17
18 Caveats:
19 - Does not support UINT12/INT12
20
21 Removed:
22 - float16 is defined in GDCM API but no implementation exist for it ...
23 """
24
25 import gdcm
26 import numpy
27
28 def get_gdcm_to_numpy_tymap():
29     """Returns the GDCM Pixel Format to numpy array type mapping."""
30     _gdcm_np = {gdcm.PixelFormat.UINT8 :numpy.int8,
31                 gdcm.PixelFormat.INT8 :numpy.uint8,
32                 #gdcm.PixelFormat.UINT12 :numpy.uint12,
33                 #gdcm.PixelFormat.INT12 :numpy.int12,
34                 gdcm.PixelFormat.UINT16 :numpy.uint16,
35                 gdcm.PixelFormat.INT16 :numpy.int16,
36                 gdcm.PixelFormat.UINT32 :numpy.uint32,
37                 gdcm.PixelFormat.INT32 :numpy.int32,
38                 #gdcm.PixelFormat.FLOAT16:numpy.float16,
39                 gdcm.PixelFormat.FLOAT32:numpy.float32,
40                 gdcm.PixelFormat.FLOAT64:numpy.float64 }
41     return _gdcm_np
42
43 def get_numpy_array_type(gdcm_pixel_format):
44     """Returns a numpy array typecode given a GDCM Pixel Format."""
45     return get_gdcm_to_numpy_tymap()[gdcm_pixel_format]
46
47 def gdcm_to_numpy(image):

```

```

48     """Converts a GDCM image to a numpy array.
49     """
50     pf = image.GetPixelFormat()
51
52     assert pf.GetScalarType() in get_gdcm_to_numpy_tymap().keys(), \
53         "Unsupported array type %s"%pf
54
55     shape = image.GetDimension(0) * image.GetDimension(1), pf.GetSamplesPerPixel()
56     if image.GetNumberOfDimensions() == 3:
57         shape = shape[0] * image.GetDimension(2), shape[1]
58
59     dtype = get_numpy_array_type(pf.GetScalarType())
60     gdcm_array = image.GetBuffer()
61     result = numpy.frombuffer(gdcm_array, dtype=dtype)
62     result.shape = shape
63     return result
64
65 if __name__ == "__main__":
66     import sys
67     r = gdcm.ImageReader()
68     filename = sys.argv[1]
69     r.SetFileName( filename )
70     if not r.Read():
71         sys.exit(1)
72
73     numpy_array = gdcm_to_numpy( r.GetImage() )
74     print numpy_array

```

27.15 ConvertPIL.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 save a DICOM image with PIL via numpy
17
18 Caveats:
19 - Does not support UINT12/INT12
20
21 Usage:
22
23 python ConvertNumpy.py "IM000000"
24
25 Thanks:
26 plotting example - Ray Schumacher 2009
27 """
28
29 import gdcm
30 import numpy
31 from PIL import Image, ImageOps
32
33
34 def get_gdcm_to_numpy_tymap():
35     """Returns the GDCM Pixel Format to numpy array type mapping."""
36     _gdcm_np = {gdcm.PixelFormat.UINT8 :numpy.int8,
37                 gdcm.PixelFormat.INT8  :numpy.uint8,
38                 gdcm.PixelFormat.UINT16:numpy.uint16,
39                 gdcm.PixelFormat.INT16  :numpy.int16,
40                 gdcm.PixelFormat.UINT32 :numpy.uint32,
41                 gdcm.PixelFormat.INT32  :numpy.int32,
42                 gdcm.PixelFormat.FLOAT32:numpy.float32,
43                 gdcm.PixelFormat.FLOAT64:numpy.float64 }
44     return _gdcm_np
45
46 def get_numpy_array_type(gdcm_pixel_format):
47     """Returns a numpy array typecode given a GDCM Pixel Format."""

```

```

48     return get_gdcm_to_numpy_typemap()[gdcm_pixel_format]
49
50 def gdcm_to_numpy(image):
51     """Converts a GDCM image to a numpy array.
52     """
53     pf = image.GetPixelFormat().GetScalarType()
54     print 'pf', pf
55     print image.GetPixelFormat().GetScalarTypeAsString()
56     assert pf in get_gdcm_to_numpy_typemap().keys(), \
57         "Unsupported array type %s"%pf
58     d = image.GetDimension(0), image.GetDimension(1)
59     print 'Image Size: %d x %d' % (d[0], d[1])
60     dtype = get_numpy_array_type(pf)
61     gdcm_array = image.GetBuffer()
62     result = numpy.frombuffer(gdcm_array, dtype=dtype)
63     maxV = float(result[result.argmax()])
64     ## linear gamma adjust
65     #result = result + .5*(maxV-result)
66     ## log gamma
67     result = numpy.log(result+50) ## 50 is appr. background level
68     maxV = float(result[result.argmax()])
69     result = result*(2.**8/maxV) ## histogram stretch
70     result.shape = d
71     return result
72
73 if __name__ == "__main__":
74     import sys
75     r = gdcm.ImageReader()
76     filename = sys.argv[1]
77     r.SetFileName( filename )
78     if not r.Read(): sys.exit(1)
79     numpy_array = gdcm_to_numpy( r.GetImage() )
80     ## L is 8 bit grey
81     ## http://www.pythonware.com/library/pil/handbook/concepts.htm
82     pilImage = Image.frombuffer('L',
83                                numpy_array.shape,
84                                numpy_array.astype(numpy.uint8),
85                                'raw','L',0,1)
86     ## cutoff removes background noise and spikes
87     pilImage = ImageOps.autocontrast(pilImage, cutoff=.1)
88     pilImage.save(sys.argv[1]+' .jpg')

```

27.16 ConvertRGBToLuminance.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkGDCMImageReader.h"
#include "vtkGDCMImageWriter.h"
#include "vtkImageData.h"
#include "vtkImageLuminance.h"

#include "gdcmTesting.h"

// There is no such thing as MR Image Storage + Photometric Interpretation = RGB
// let's rewrite that into a proper single component image:
int main(int, char *[])
{
    const char *directory = gdcm::Testing::GetDataRoot();
    if(!directory) return 1;
    std::string file = std::string(directory) + "/SIEMENS-MR-RGB-16Bits.dcm";
    std::cout << file << std::endl;

    vtkGDCMImageReader *reader = vtkGDCMImageReader::New();
    reader->SetFileName( file.c_str() );
    reader->Update();
    //reader->GetOutput()->Print( std::cout );

```

```

vtkImageLuminance *luminance = vtkImageLuminance::New();
luminance->SetInput( reader->GetOutput() );

vtkGDCMImageWriter *writer = vtkGDCMImageWriter::New();
writer->SetFileName( "/tmp/bla.dcm" );
writer->SetInput( luminance->GetOutput() );
//writer->SetImageFormat( reader->GetImageFormat() ); // Do NOT pass image format
writer->SetMedicalImageProperties( reader->GetMedicalImageProperties() );
writer->SetDirectionCosines( reader->GetDirectionCosines() );
writer->SetShift( reader->GetShift() );
writer->SetScale( reader->GetScale() );
writer->Write();

// TODO:
//vtkImageAppendComponents.h

reader->Delete();
luminance->Delete();
writer->Delete();

return 0;
}

```

27.17 ConvertSingleBitTo8Bits.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkGDCMImageReader.h"
#include "vtkGDCMImageWriter.h"
#include "vtkImageData.h"
#include "vtkImageCast.h"
#include "vtkPointData.h"
#include "vtkBitArray.h"
#include "vtkUnsignedCharArray.h"

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];

    vtkGDCMImageReader *reader = vtkGDCMImageReader::New();
    reader->SetFileName( filename );
    reader->Update();
    //reader->GetOutput()->Print( std::cout );

    vtkDataArray* array = reader->GetOutput()->GetPointData()->GetScalars();
    vtkBitArray *barray = vtkBitArray::SafeDownCast( array );
    if( !barray ) return false;
    vtkIdType nvalues = array->GetNumberOfTuples();
    vtkUnsignedCharArray *uarray = vtkUnsignedCharArray::New();
    uarray->SetNumberOfTuples( nvalues );
    for( vtkIdType i = 0; i < nvalues; ++i)
    {
        uarray->SetValue( i, (unsigned char)barray->GetValue(i) );
    }

    vtkImageData *copy = vtkImageData::New();
    copy->SetScalarType( VTK_UNSIGNED_CHAR );
    copy->SetExtent( reader->GetOutput()->GetExtent() );
    copy->AllocateScalars();

```

```

//uarray->Print( std::cout );
//copy->GetPointData()->GetScalars()->Print( std::cout );
copy->GetPointData()->SetScalars( uarray );
uarray->Delete();

vtkGDCMImageWriter *writer = vtkGDCMImageWriter::New();
writer->SetFileName( outfilename );
//writer->SetInput( cast->GetOutput() );
writer->SetInput( copy );
writer->SetImageFormat( reader->GetImageFormat() );
writer->SetMedicalImageProperties( reader->GetMedicalImageProperties() );
writer->SetDirectionCosines( reader->GetDirectionCosines() );
writer->SetShift( reader->GetShift() );
writer->SetScale( reader->GetScale() );
writer->SetFileDimensionality( reader->GetFileDimensionality() );
writer->Write();

reader->Delete();
copy->Delete();
writer->Delete();

return 0;
}

```

27.18 ConvertToQImage.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/
/*
 * This example shows how to setup the pipeline from a gdcm::ImageReader into a
 * Qt QImage data structure.
 * It only handles 2D image.
 *
 * Ref:
 * http://doc.trolltech.com/4.5/qimage.html
 *
 * Usage:
 * ConvertToQImage gdcmData/012345.002.050.dcm output.png
 *
 * Thanks:
 * Sylvain ADAM (sylvain51 hotmail com) for contributing this example
 */

#include "gdcmImageReader.h"
#include <QImage>
#include <QImageWriter>

bool ConvertToFormat_RGB888(gdcm::Image const & gimage, char *buffer, QImage* &imageQt)
{
    const unsigned int* dimension = gimage.GetDimensions();

    unsigned int dimX = dimension[0];
    unsigned int dimY = dimension[1];

    gimage.GetBuffer(buffer);

    // Let's start with the easy case:
    if( gimage.GetPhotometricInterpretation() ==
        gdcm::PhotometricInterpretation::RGB )
    {
        if( gimage.GetPixelFormat() != gdcm::PixelFormat::UINT8 )
        {
            return false;
        }
        unsigned char *ubuffer = (unsigned char*)buffer;

```



```

    // QImage::Format_RGB888 13 The image is stored using a 24-bit RGB format (8-8-8).
    imageQt = new QImage((unsigned char *)ubuffer, dimX, dimY, 3*dimX, QImage::Format_RGB888);
}
else if( gimage.GetPhotometricInterpretation() ==
    gdcM::PhotometricInterpretation::MONOCHROME2 )
{
    if( gimage.GetPixelFormat() == gdcM::PixelFormat::UINT8 )
    {
        // We need to copy each individual 8bits into R / G and B:
        unsigned char *ubuffer = new unsigned char[dimX*dimY*3];
        unsigned char *pubuffer = ubuffer;
        for(unsigned int i = 0; i < dimX*dimY; i++)
        {
            *pubuffer++ = *buffer;
            *pubuffer++ = *buffer;
            *pubuffer++ = *buffer++;
        }

        imageQt = new QImage(ubuffer, dimX, dimY, QImage::Format_RGB888);
    }
    else if( gimage.GetPixelFormat() == gdcM::PixelFormat::INT16 )
    {
        // We need to copy each individual 16bits into R / G and B (truncate value)
        short *buffer16 = (short*)buffer;
        unsigned char *ubuffer = new unsigned char[dimX*dimY*3];
        unsigned char *pubuffer = ubuffer;
        for(unsigned int i = 0; i < dimX*dimY; i++)
        {
            // Scalar Range of gdcMData/012345.002.050.dcm is [0,192], we could simply do:
            // *pubuffer++ = *buffer16;
            // *pubuffer++ = *buffer16;
            // *pubuffer++ = *buffer16;
            // instead do it right:
            *pubuffer++ = (unsigned char)std::min(255, (32768 + *buffer16) / 255);
            *pubuffer++ = (unsigned char)std::min(255, (32768 + *buffer16) / 255);
            *pubuffer++ = (unsigned char)std::min(255, (32768 + *buffer16) / 255);
            buffer16++;
        }

        imageQt = new QImage(ubuffer, dimX, dimY, QImage::Format_RGB888);
    }
    else
    {
        std::cerr << "Pixel Format is: " << gimage.GetPixelFormat() << std::endl;
        return false;
    }
}
else
{
    std::cerr << "Unhandled PhotometricInterpretation: " << gimage.
        GetPhotometricInterpretation() << std::endl;
    return false;
}

return true;
}

int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];

    gdcM::ImageReader ir;
    ir.SetFileName( filename );
    if(!ir.Read())
    {
        //Read failed
        return 1;
    }

    std::cout<<"Getting image from ImageReader..."<<std::endl;

    const gdcM::Image &gimage = ir.GetImage();
    std::vector<char> vbuffer;
    vbuffer.resize( gimage.GetBufferLength() );
    char *buffer = &vbuffer[0];

```

```

 QImage *imageQt = NULL;
 if( !ConvertToFormat_RGB888( gimage, buffer, imageQt ) )
 {
     return 1;
 }

 QImageWriter writer;
 writer.setFormat("png");
 writer.setFileName( outfilename );
 if( !writer.write( *imageQt ) )
 {
     return 1;
 }

 return 0;
}

```

27.19 CreateARGBImage.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * http://www.w3.org/Graphics/PNG/inline-alpha.html
 * alphatest.png: PNG image data, 380 x 287, 8-bit/color RGBA, non-interlaced
 *
 * $ convert alphatest.png alphatest.rgb
 */

#include "gdcmImageReader.h"
#include "gdcmSequenceOfFragments.h"
#include "gdcmSystem.h"
#include "gdcmImageWriter.h"

#include <iostream>
#include <fstream>

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.rgb output.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];

    size_t len = gdcm::System::FileSize(filename);
    std::ifstream is(filename);

    char * buf = new char[len];
    is.read(buf, len);

    gdcm::ImageWriter writer;
    gdcm::Image &image = writer.GetImage();
    image.SetNumberOfDimensions( 2 );
    unsigned int dims[3] = {};
    dims[0] = 380;
    dims[1] = 287;
    image.SetDimensions( dims );
    gdcm::PixelFormat pf = gdcm::PixelFormat::UINT8;
    pf.SetSamplesPerPixel( 4 );
    image.SetPixelFormat( pf );
    gdcm::PhotometricInterpretation pi =
        gdcm::PhotometricInterpretation::ARGB;
    image.SetPhotometricInterpretation( pi );
    image.SetTransferSyntax(

```

```

        gdcmm::TransferSyntax::ExplicitVRLittleEndian );

gdcmm::DataElement pixeldata( gdcmm::Tag(0x7fe0,0x0010) );
pixeldata.SetByteValue( buf, (uint32_t)len );
image.SetDataElement( pixeldata );

writer.SetFileName( outfilename );
if( !writer.Write() )
{
    return 1;
}
delete[] buf;

return 0;
}

```

27.20 CreateCMYKImage.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * http://www.w3.org/Graphics/PNG/inline-alpha.html
 * alphatest.png: PNG image data, 380 x 287, 8-bit/color RGBA, non-interlaced
 *
 * $ convert alphatest.png alphatest.cmyk
 */

#include "gdcmmImageReader.h"
#include "gdcmmSequenceOfFragments.h"
#include "gdcmmSystem.h"
#include "gdcmmImageWriter.h"

#include <iostream>
#include <fstream>

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.cmyk output.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];

    size_t len = gdcmm::System::FileSize(filename);
    std::ifstream is(filename);

    char * buf = new char[len];
    is.read(buf, len);

    gdcmm::ImageWriter writer;
    gdcmm::Image &image = writer.GetImage();
    image.SetNumberOfDimensions( 2 );
    unsigned int dims[3] = {};
    dims[0] = 380;
    dims[1] = 287;
    image.SetDimensions( dims );
    gdcmm::PixelFormat pf = gdcmm::PixelFormat::UINT8;
    pf.SetSamplesPerPixel( 4 );
    image.SetPixelFormat( pf );
    gdcmm::PhotometricInterpretation pi =
        gdcmm::PhotometricInterpretation::CMYK;
    image.SetPhotometricInterpretation( pi );
    image.SetTransferSyntax(

```

```

        gdcm::TransferSyntax::ExplicitVRLittleEndian );

gdcm::DataElement pixeldata( gdcm::Tag(0x7fe0,0x0010) );
pixeldata.SetByteValue( buf, (uint32_t)len );
image.SetDataElement( pixeldata );

writer.SetFileName( outfilename );
if( !writer.Write() )
{
    return 1;
}
delete[] buf;

return 0;
}

```

27.21 CreateJPIPDataSet.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

/*
 * This example was created during the GSOC 2011 project for
 * JPIP
 */
#include "gdcmAnonymizer.h"
#include "gdcmWriter.h"
#include "gdcmUIDGenerator.h"
#include "gdcmFile.h"
#include "gdcmTag.h"
#include "gdcmSystem.h"
#include "gdcmAttribute.h"

int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        std::cerr << argv[0] << " output.dcm" << std::endl;
        return 1;
    }
    const char *outfilename = argv[1];

    gdcm::Writer w;
    gdcm::File &file = w.GetFile();
    gdcm::DataSet &ds = file.GetDataSet();
    //w.SetCheckFileMetaInformation( true );
    w.SetFileName( outfilename );

    file.GetHeader().SetDataSetTransferSyntax(
        gdcm::TransferSyntax::JPIPReferenced );

    gdcm::Anonymizer anon;
    anon.SetFile( file );

    gdcm::MediaStorage ms =
        gdcm::MediaStorage::SecondaryCaptureImageStorage;

    gdcm::UIDGenerator gen;
    anon.Replace( gdcm::Tag(0x0008,0x16), ms.GetString() );
    std::cout << ms.GetString() << std::endl;
    anon.Replace( gdcm::Tag(0x0008,0x18), gen.Generate() );
    //
    anon.Replace( gdcm::Tag(0x0010,0x10), "JPIP^EXAMPLE" );
    anon.Replace( gdcm::Tag(0x0010,0x20), "012345" );
    anon.Empty( gdcm::Tag(0x0010,0x30) );
    anon.Empty( gdcm::Tag(0x0010,0x40) );
    anon.Empty( gdcm::Tag(0x0008,0x20) );
}

```

```

anon.Empty( gdcM::Tag(0x0008,0x30) );
anon.Empty( gdcM::Tag(0x0008,0x90) );
anon.Empty( gdcM::Tag(0x0020,0x10) );
anon.Empty( gdcM::Tag(0x0020,0x11) );
anon.Empty( gdcM::Tag(0x0008,0x50) );
anon.Empty( gdcM::Tag(0x0020,0x0013) );
anon.Replace( gdcM::Tag(0x0020,0xd), gen.Generate() );
anon.Replace( gdcM::Tag(0x0020,0xe), gen.Generate() );
anon.Replace( gdcM::Tag(0x0008,0x64), "WSD " );

gdcM::Attribute<0x0028,0x7FE0> at;
at.SetValue( "http://dicom.example.com/jpipserver.cgi?target=img.jp2" );
ds.Insert( at.GetAsDataElement() );

// Need to retrieve the PixelFormat information from the given file

if (!w.Write() )
{
    std::cerr << "Could not write: " << outfilename << std::endl;
    return 1;
}

return 0;
}

```

27.22 CreateRAWStorage.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcM.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 <uid value="1.2.840.10008.5.1.4.1.1.66" name="Raw Data Storage" type="SOP Class" part="PS 3.4" retired=
17   "false"/>
18 """
19
20 import gdcM
21 import sys,os
22
23 if __name__ == "__main__":
24     r = gdcM.Reader()
25     # Will require Testing...
26     dataroot = gdcM.Testing.GetDataRoot()
27     filename = os.path.join( dataroot, '012345.002.050.dcm' )
28     r.SetFileName( filename )
29     r.Read()
30     f = r.GetFile()
31     ds = f.GetDataSet()
32
33     uid = "1.2.840.10008.5.1.4.1.1.66"
34     # f = gdcM.File()
35     # ds = f.GetDataSet()
36     de = gdcM.DataElement( gdcM.Tag(0x0008,0x0016) )
37     de.SetByteValue( uid, gdcM.VL(len(uid)) )
38     vr = gdcM.VR( gdcM.VR.UI )
39     de.SetVR( vr )
40     ds.Replace( de )
41
42     ano = gdcM.Anonymizer()
43     ano.SetFile( r.GetFile() )
44     ano.RemovePrivateTags()
45     ano.RemoveGroupLength()
46     taglist = [
47         gdcM.Tag(0x0008,0x0008),
48         gdcM.Tag(0x0008,0x0022),
49         gdcM.Tag(0x0008,0x0032),
50         gdcM.Tag(0x0008,0x2111),

```

```

50  gdcM.Tag(0x0008,0x1150),
51  gdcM.Tag(0x0008,0x1155),
52  gdcM.Tag(0x0008,0x0100),
53  gdcM.Tag(0x0008,0x0102),
54  gdcM.Tag(0x0008,0x0104),
55  gdcM.Tag(0x0040,0xa170),
56  gdcM.Tag(0x0008,0x2112),
57  gdcM.Tag(0x0008,0x0100),
58  gdcM.Tag(0x0008,0x0102),
59  gdcM.Tag(0x0008,0x0104),
60  gdcM.Tag(0x0008,0x9215),
61  gdcM.Tag(0x0018,0x0010),
62  gdcM.Tag(0x0018,0x0022),
63  gdcM.Tag(0x0018,0x0050),
64  gdcM.Tag(0x0018,0x0060),
65  gdcM.Tag(0x0018,0x0088),
66  gdcM.Tag(0x0018,0x0090),
67  gdcM.Tag(0x0018,0x1040),
68  gdcM.Tag(0x0018,0x1100),
69  gdcM.Tag(0x0018,0x1110),
70  gdcM.Tag(0x0018,0x1111),
71  gdcM.Tag(0x0018,0x1120),
72  gdcM.Tag(0x0018,0x1130),
73  gdcM.Tag(0x0018,0x1150),
74  gdcM.Tag(0x0018,0x1151),
75  gdcM.Tag(0x0018,0x1152),
76  gdcM.Tag(0x0018,0x1160),
77  gdcM.Tag(0x0018,0x1190),
78  gdcM.Tag(0x0018,0x1210),
79  gdcM.Tag(0x0020,0x0012),
80  gdcM.Tag(0x0020,0x0032),
81  gdcM.Tag(0x0020,0x0037),
82  gdcM.Tag(0x0020,0x1041),
83  gdcM.Tag(0x0020,0x4000),
84  gdcM.Tag(0x0028,0x0002),
85  gdcM.Tag(0x0028,0x0004),
86  gdcM.Tag(0x0028,0x0010),
87  gdcM.Tag(0x0028,0x0011),
88  gdcM.Tag(0x0028,0x0030),
89  gdcM.Tag(0x0028,0x0100),
90  gdcM.Tag(0x0028,0x0101),
91  gdcM.Tag(0x0028,0x0102),
92  gdcM.Tag(0x0028,0x0103),
93  gdcM.Tag(0x0028,0x1052),
94  gdcM.Tag(0x0028,0x1053),
95  gdcM.Tag(0x0028,0x2110),
96  gdcM.Tag(0x0028,0x2112),
97  gdcM.Tag(0x7fe0,0x0010),
98  gdcM.Tag(0x0018,0x0020),
99  gdcM.Tag(0x0018,0x0021),
100 gdcM.Tag(0x0018,0x0023),
101 gdcM.Tag(0x0018,0x0025),
102 gdcM.Tag(0x0018,0x0080),
103 gdcM.Tag(0x0018,0x0081),
104 gdcM.Tag(0x0018,0x0083),
105 gdcM.Tag(0x0018,0x0084),
106 gdcM.Tag(0x0018,0x0085),
107 gdcM.Tag(0x0018,0x0086),
108 gdcM.Tag(0x0018,0x0087),
109 gdcM.Tag(0x0018,0x0091),
110 gdcM.Tag(0x0018,0x0093),
111 gdcM.Tag(0x0018,0x0094),
112 gdcM.Tag(0x0018,0x0095),
113 gdcM.Tag(0x0018,0x1088),
114 gdcM.Tag(0x0018,0x1090),
115 gdcM.Tag(0x0018,0x1094),
116 gdcM.Tag(0x0018,0x1250),
117 gdcM.Tag(0x0018,0x1251),
118 gdcM.Tag(0x0018,0x1310),
119 gdcM.Tag(0x0018,0x1312),
120 gdcM.Tag(0x0018,0x1314),
121 gdcM.Tag(0x0018,0x1315),
122 gdcM.Tag(0x0018,0x1316),
123 gdcM.Tag(0x0020,0x0110),
124 gdcM.Tag(0x0028,0x0120),
125 gdcM.Tag(0x0028,0x1050),
126 gdcM.Tag(0x0028,0x1051)
127 ]
128 for tag in taglist:
129     #print tag
130     ano.Remove( tag )

```

```

131
132 # special handling
133 gen = gdcm.UIDGenerator()
134 ano.Replace( gdcm.Tag(0x0008,0x9123), gen.Generate() )
135 #ano.Empty( gdcm.Tag(0x0040,0x0555) )
136
137
138 #
139 # uid = gen.Generate()
140 # de.SetTag( gdcm.Tag(0x0008,0x0018) )
141 # de.SetByteValue( uid, gdcm.VL(len(uid)) )
142 # ds.Insert( de )
143
144 # init FMI now:
145 #fmi = f.GetHeader()
146 #ts = gdcm.TransferSyntax()
147 #print ts
148 #fmi.SetDataSetTransferSyntax( ts ) # default
149 #print fmi.GetDataSetTransferSyntax()
150 #de.SetTag( gdcm.Tag(0x0002,0x0010) )
151 #uid = "1.2.840.10008.1.2"
152 #de.SetByteValue( uid, gdcm.VL(len(uid)) )
153 #fmi.Insert( de )
154 # f.SetHeader( r.GetFile().GetHeader() )
155
156 writer = gdcm.Writer()
157 writer.SetFile( ano.GetFile() )
158 writer.SetFileName( "rawstorage.dcm" );
159 writer.Write()

```

27.23 csa2img.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * I do not know what the format is, just guessing from info found on the net:
 *
 * http://atonal.ucdavis.edu/matlab/fmri/spm5/spm_dicom_convert.m
 *
 * This example is an attempt at understanding the format used by SIEMENS
 * their "SIEMENS CSA NON-IMAGE" DICOM file (1.3.12.2.1107.5.9.1)
 *
 * Everything done in this code is for the sole purpose of writing interoperable
 * software under Sect. 1201 (f) Reverse Engineering exception of the DMCA.
 * If you believe anything in this code violates any law or any of your rights,
 * please contact us (gdcm-developers@lists.sourceforge.net) so that we can
 * find a solution.
 *
 */
#include "gdcmReader.h"
#include "gdcmImageReader.h"
#include "gdcmImageWriter.h"
#include "gdcmCSAHeader.h"
#include "gdcmAttribute.h"
#include "gdcmPrivateTag.h"

#include <math.h>

int main(int argc, char *argv [])
{
    if( argc < 2 ) return 1;
    // gdcmDataExtra/gdcmNonImageData/exCSA_Non-Image_Storage.dcm
    // PHANTOM.MR.CARDIO_COEUR_S_QUENCE_DE_REP_RAGE.9.257.2008.03.20.14.53.25.578125.43151705.IMA
    const char *filename = argv[1];

    gdcm::Reader reader; // Do not use ImageReader

```

```

reader.SetFileName( filename );
if( !reader.Read() )
{
    std::cerr << "Failed to read: " << filename << std::endl;
    return 1;
}

gdcm::CSAHeader csa;
const gdcm::DataSet& ds = reader.GetFile().GetDataSet();

const gdcm::PrivateTag &t1 = csa.GetCSAImageHeaderInfoTag();
//std::cout << t1 << std::endl;
//const gdcm::PrivateTag &t2 = csa.GetCSASeriesHeaderInfoTag();

if( ds.FindDataElement( t1 ) )
{
    csa.LoadFromDataElement( ds.GetDataElement( t1 ) );
    csa.Print( std::cout );
}

int dims[2] = {};
if( csa.FindCSAElementByName( "Columns" ) )
{
    const gdcm::CSAElement &cse1 = csa.GetCSAElementByName( "Columns" )
    ;
    std::cout << cse1 << std::endl;
    //const gdcm::ByteValue *bv = cse1.GetByteValue();
    gdcm::Element<gdcm::VR::IS, gdcm::VM::VM1> el;
    el.Set( cse1.GetValue() );
    dims[0] = el.GetValue();
    std::cout << "Columns:" << el.GetValue() << std::endl;
}

if( csa.FindCSAElementByName( "Rows" ) )
{
    const gdcm::CSAElement &cse2 = csa.GetCSAElementByName( "Rows" );
    std::cout << cse2 << std::endl;
    gdcm::Element<gdcm::VR::IS, gdcm::VM::VM1> el2;
    el2.Set( cse2.GetValue() );
    dims[1] = el2.GetValue();
    std::cout << "Rows:" << el2.GetValue() << std::endl;
}

double spacing[2] = { 1. , 1. };
bool spacingfound = false;
if( csa.FindCSAElementByName( "PixelSpacing" ) )
{
    const gdcm::CSAElement &cse3 = csa.GetCSAElementByName( "PixelSpacing" );
    if( !cse3.IsEmpty() )
    {
        std::cout << cse3 << std::endl;
        gdcm::Element<gdcm::VR::DS, gdcm::VM::VM2> el3;
        el3.Set( cse3.GetValue() );
        spacing[0] = el3.GetValue(0);
        spacing[1] = el3.GetValue(1);
        std::cout << "PixelSpacing:" << el3.GetValue() << "," << el3.
            GetValue(1) << std::endl;
        spacingfound = true;
    }
}

if( !spacingfound )
{
    std::cerr << "Problem with PixelSpacing" << std::endl;
    //return 1;
}

if( !dims[0] || !dims[1] )
{
    std::cerr << "Problem with dims" << std::endl;
    return 1;
}

gdcm::ImageWriter writer;

gdcm::Image &image = writer.GetImage();
image.SetNumberOfDimensions( 2 ); // good default
image.SetDimension(0, dims[0] );
image.SetDimension(1, dims[1] );
image.SetSpacing(0, spacing[0] );
image.SetSpacing(1, spacing[1] );
gdcm::PixelFormat pixeltype = gdcm::PixelFormat::INT16; //

```



```

        bytewidth = spm_type('int16','bits')/8;

//unsigned long l = image.GetBufferLength();
//const int p = 1 / (dims[0] * dims[1]);

//image.SetNumberOfDimensions( 3 );
//image.SetDimension(2, p / pixeltype.GetPixelSize() );

gdcm::PhotometricInterpretation pi;
pi = gdcm::PhotometricInterpretation::MONOCHROME2;
//pixeltype.SetSamplesPerPixel( );
image.SetPhotometricInterpretation( pi );
image.SetPixelFormat( pixeltype );
//image.SetIntercept( inputimage.GetIntercept() );
//image.SetSlope( inputimage.GetSlope() );

//gdcm::DataElement pixeldata( gdcm::Tag(0x7fe1,0x1010) );
//pixeldata.SetByteValue( &outbuf[0], outbuf.size() );
gdcm::PrivateTag csananimaget(0x7fe1,0x10,"SIEMENS CSA NON-IMAGE");
const gdcm::DataElement &pixeldata = ds.GetDataElement( csananimaget );
image.SetDataElement( pixeldata );

std::string outfilename = "outcsa.dcm";
//writer.SetFile( reader.GetFile() );
writer.SetFileName( outfilename.c_str() );
if( !writer.Write() )
{
    std::cerr << "could not write: " << outfilename << std::endl;
    return 1;
}

return 0;
}

```

27.24 CStoreQtProgress.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * This small example show how one can use the virtual function
 * mechanism of the SimpleSubjectWatcher class to redirect progress
 * report to a custom Qt classes
 *
 * http://doc.qt.nokia.com/latest/qprogressdialog.html
 *
 * Usage:
 * CStoreQtProgress dicom.example.com 11112 gdcmData/MR_Spectroscopy_SIEMENS_OF.dcm
 *
 */

#include "gdcmServiceClassUser.h"
#include "gdcmSimpleSubjectWatcher.h"
#include "gdcmProgressEvent.h"
#include "gdcmDirectory.h"
#include "gdcmPresentationContextGenerator.h"

#include <QApplication>
#include <QProgressDialog>
#include <QVBoxLayout>

namespace gdcm {
/*
 * This class is a little more complicated than what this example demonstrate
 * This watcher is capable of handling nested progress. Since the Progress
 * grows from [0 to 1] on a per file basis and we only have one instance of a

```

```

* watcher per association, we need some calculation to compute the global
* (total) progress
* In fact we simply divide the per-file progress by the number of files.
*
* This QtWatcher class will then update the progress bar according to the
* progress.
*/
class MyQtWatcher : public SimpleSubjectWatcher
{
    size_t nfiles;
    double progress;
    size_t index;
    double refprogress;
    QWidget* win;
    QProgressDialog* qtprogress;
public:
    MyQtWatcher(Subject * s, const char *comment = "", QWidget *w = NULL, QProgressDialog* p = NULL, size_t n
                = 1):
        SimpleSubjectWatcher(s,comment),nfiles(n),progress(0),index(0),refprogress(0),win(w),qtprogress(p) {}
    void ShowIteration()
    {
        index++;
        assert( index <= nfiles );
        // update refprogress (we are moving to the next file)
        refprogress = progress;
    }
    void ShowProgress(Subject *, const Event &evt)
    {
        // Retrieve the ProgressEvent:
        const ProgressEvent &pe = dynamic_cast<const ProgressEvent&>(evt);
        // compute global progress:
        progress = refprogress + (1. / (double)nfiles ) * pe.GetProgress();
        // Print Global and local progress to stdout:
        std::cout << "Global Progress: " << progress << " per file progress " << pe.GetProgress() << std::endl;
        //set progress value in the QtProgress bar
        int i = (int)(progress * 100 + 0.5); // round to next int
        qtprogress->setValue(i);
        win->show();
    }
    virtual void ShowDataSet(Subject *caller, const Event &evt)
    {
        (void)caller;
        (void)evt;
    }
};
} // end namespace gdcm

int main(int argc, char *argv[])
{
    if( argc < 4 )
    {
        std::cerr << argv[0] << " remote_server port filename" << std::endl;
        return 1;
    }
    QApplication a(argc, argv);

    std::ostringstream error_log;
    gdcm::Trace::SetErrorStream( error_log );

    const char *remote = argv[1];
    int portno = atoi(argv[2]);
    const char *filename = argv[3];

    QVBoxLayout* layout = new QVBoxLayout;
    QWidget* win = new QWidget;

    QProgressDialog* progress = new QProgressDialog("Sending data...", "Cancel", 0, 100);
    progress->setWindowModality(Qt::WindowModal);

    layout->addWidget( progress,Qt::AlignCenter);
    win->setLayout( layout);

    gdcm::SmartPointer<gdcm::ServiceClassUser> scup = new
        gdcm::ServiceClassUser;
    gdcm::ServiceClassUser &scu = *scup;
    //gdcm::SimpleSubjectWatcher w( &scu, "TestServiceClassUser" );
    // let's use a more complicated progress reported in this example
    gdcm::MyQtWatcher w( &scu, "QtWatcher", win, progress );

    scu.SetHostname( remote );
    scu.SetPort( (uint16_t)portno );

```

```

scu.SetTimeout( 1000 );
scu.SetCalledAETitle( "GDCM_STORE" );

if( !scu.InitializeConnection() )
{
    std::cerr << "Could not InitializeConnection" << std::endl;
    return 1;
}

gdcmm::Directory::FileNamesType filenames;
filenames.push_back( filename );

// setup the PC(s) based on the filenames:
gdcmm::PresentationContextGenerator generator;
if( !generator.GenerateFromFilenames(filenames) )
{
    std::cerr << "Could not GenerateFromFilenames" << std::endl;
    return 1;
}

// Setup PresentationContext(s)
scu.SetPresentationContexts( generator.
    GetPresentationContexts() );

// Start ASSOCIATION
if( !scu.StartAssociation() )
{
    std::cerr << "Could not Start" << std::endl;
    return 1;
}

// Send C-STORE
if( !scu.SendStore( filename ) )
{
    std::cerr << "Could not Store" << std::endl;
    std::cerr << "Error log is:" << std::endl;
    std::cerr << error_log.str() << std::endl;
    return 1;
}

// Stop ASSOCIATION
if( !scu.StopAssociation() )
{
    std::cerr << "Could not Stop" << std::endl;
    return 1;
}

win->show();

return a.exec();
}

```

27.25 DecompressImage.cs

This is a C# example on how to use [gdcmm::Image](#)

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcmm/debug-gcc/bin
 * $ mono bin/DecompressImage.exe gdcmmData/012345.002.050.dcm decompress.dcm
 */
using System;

```

```

using gdcm;

public class DecompressImage
{
    public static int Main(string[] args)
    {
        string file1 = args[0];
        string file2 = args[1];
        ImageReader reader = new ImageReader();
        reader.SetFileName( file1 );
        bool ret = reader.Read();
        if( !ret )
        {
            return 1;
        }

        Image image = new Image();
        Image ir = reader.GetImage();

        image.SetNumberOfDimensions( ir.GetNumberOfDimensions() );

        //Just for fun:
        //int dircos = ir.GetDirectionCosines();
        //t = gdcm.Orientation.GetType(dircos);
        //int l = gdcm.Orientation.GetLabel(t);
        //System.Console.WriteLine( "Orientation label:" + l );

        // Set the dimensions,
        // 1. either one at a time
        //image.SetDimension(0, ir.GetDimension(0) );
        //image.SetDimension(1, ir.GetDimension(1) );

        // 2. the array at once
        uint[] dims = {0, 0};
        // Just for fun let's invert the dimensions:
        dims[0] = ir.GetDimension(1);
        dims[1] = ir.GetDimension(0);
        ir.SetDimensions( dims );

        PixelFormat pixeltype = ir.GetPixelFormat();
        image.SetPixelFormat( pixeltype );

        PhotometricInterpretation pi = ir.GetPhotometricInterpretation();
        image.SetPhotometricInterpretation( pi );

        DataElement pixeldata = new DataElement( new Tag(0x7fe0,0x0010) );
        byte[] str1 = new byte[ ir.GetBufferLength()];
        ir.GetBuffer( str1 );
        //System.Console.WriteLine( ir.GetBufferLength() );
        pixeldata.SetByteValue( str1, new VL( (uint)str1.Length ) );
        //image.SetDataElement( pixeldata );
        ir.SetDataElement( pixeldata );

        ImageWriter writer = new ImageWriter();
        writer.SetFileName( file2 );
        writer.SetFile( reader.GetFile() );
        writer.SetImage( ir );
        ret = writer.Write();
        if( !ret )
        {
            return 1;
        }

        return 0;
    }
}

```

27.26 DecompressImage.java

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

```

```

    This software is distributed WITHOUT ANY WARRANTY; without even
    the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
    PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * This example will take in a DICOM file, and tries to decompress it (actually write it
 * as ImplicitVRLittleEndian Transfer Syntax).
 *
 * Compilation:
 * $ CLASSPATH=gdc.jar javac ../../gdc/Examples/Java/DecompressImage.java -d .
 *
 * Usage:
 * $ LD_LIBRARY_PATH=. CLASSPATH=gdc.jar:. java DecompressImage gdcData/012345.002.050.dcm out.dcm
 */
import gdc.*;

public class DecompressImage
{
    public static void main(String[] args) throws Exception
    {
        String file1 = args[0];
        String file2 = args[1];
        ImageReader reader = new ImageReader();
        reader.SetFileName( file1 );
        boolean ret = reader.Read();
        if( !ret )
        {
            throw new Exception("Could not read: " + file1 );
        }

        ImageChangeTransferSyntax change = new ImageChangeTransferSyntax();
        change.SetTransferSyntax( new TransferSyntax(TransferSyntax.TSType.ImplicitVRLittleEndian) );
        change.SetInput( reader.GetImage() );
        if( !change.Change() )
        {
            throw new Exception("Could not change: " + file1 );
        }

        Image out = change.GetOutput();
        System.out.println( out.toString() );

        // Set the Source Application Entity Title
        FileMetaInformation.SetSourceApplicationEntityTitle( "Just For Fun" );

        ImageWriter writer = new ImageWriter();
        writer.SetFileName( file2 );
        writer.SetFile( reader.GetFile() );
        writer.SetImage( out );
        ret = writer.Write();
        if( !ret )
        {
            throw new Exception("Could not write: " + file2 );
        }
    }
}

```

27.27 DecompressImage.py

```

1 #####
2 #
3 # Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 # Copyright (c) 2006-2011 Mathieu Malaterre
6 # All rights reserved.
7 # See Copyright.txt or http://gdc.sourceforge.net/Copyright.html for details.
8 #
9 # This software is distributed WITHOUT ANY WARRANTY; without even
10 # the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 # PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """

```

```

16 Usage:
17
18 python DecompressImage.py gdcmlData/012345.002.050.dcm decompress.dcm
19 """
20
21 import gdcml
22 import sys
23
24 if __name__ == "__main__":
25
26     file1 = sys.argv[1]
27     file2 = sys.argv[2]
28
29     r = gdcml.ImageReader()
30     r.SetFileName( file1 )
31     if not r.Read():
32         sys.exit(1)
33
34     image = gdcml.Image()
35     ir = r.GetImage()
36
37     image.SetNumberOfDimensions( ir.GetNumberOfDimensions() );
38     dims = ir.GetDimensions();
39     print ir.GetDimension(0);
40     print ir.GetDimension(1);
41     print "Dims:", dims
42
43     # Just for fun:
44     dircos = ir.GetDirectionCosines()
45     t = gdcml.Orientation.GetType(dircos)
46     l = gdcml.Orientation.GetLabel(t)
47     print "Orientation label:", l
48
49     image.SetDimension(0, ir.GetDimension(0) );
50     image.SetDimension(1, ir.GetDimension(1) );
51
52     pixeltype = ir.GetPixelFormat();
53     image.SetPixelFormat( pixeltype );
54
55     pi = ir.GetPhotometricInterpretation();
56     image.SetPhotometricInterpretation( pi );
57
58     pixeldata = gdcml.DataElement( gdcml.Tag(0x7fe0,0x0010) )
59     str1 = ir.GetBuffer()
60     #print ir.GetBufferLength()
61     pixeldata.SetByteValue( str1, gdcml.VL( len(str1) ) )
62     image.SetDataElement( pixeldata )
63
64     w = gdcml.ImageWriter()
65     w.SetFileName( file2 )
66     w.SetFile( r.GetFile() )
67     w.SetImage( image )
68     if not w.Write():
69         sys.exit(1)

```

27.28 DecompressImageMultiframe.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcml.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

/*
$ gdcminfo ~/Desktop/angiogram-06.dcm
MediaStorage is 1.2.840.10008.5.1.4.1.1.12.1 [X-Ray Angiographic Image Storage]
TransferSyntax is 1.2.840.10008.1.2.4.50 [JPEG Baseline (Process 1): Default Transfer Syntax for Lossy JPEG
8 Bit Image Compression]
NumberOfDimensions: 3

```

```

Dimensions: (512,512,355)
Origin: (0,0,0)
Spacing: (1,1,40)
DirectionCosines: (1,0,0,0,1,0)
Rescale Intercept/Slope: (0,1)
SamplesPerPixel :1
BitsAllocated :8
BitsStored :8
HighBit :7
PixelRepresentation:0
ScalarType found :UINT8
PhotometricInterpretation: MONOCHROME2
PlanarConfiguration: 0
TransferSyntax: 1.2.840.10008.1.2.4.50
Orientation Label: AXIAL
*/

/*
 * Description:
 *
 * Assume we have a file angiogram-06.dcm as described above.
 * the following program will decompress directly from the extracted jpeg stream.
 *
 * First step extract the jpeg stream (but not the Basic Offset Table):
 *
 * $ gdcmmraw -i angiogram-06.dcm -o /tmp/output/chris --split-frags --pattern %d.jpg
 *
 * Check that indeed there are 355 files, while there are 356 fragments in the original DICOM file, since
 * gdcmmraw always skip the first fragment (Basic Offset Table).
 *
 * Now from those individual jpeg stream, recreate a fake gdcm.DataElement...
 *
 * Usage:
 *
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono ./bin/DecompressImageMultiframe.exe /tmp/output
 */
using System;
using gdcm;

public class DecompressImageMultiframe
{
    public static int Main(string[] args)
    {
        string directory = args[0];
        gdcm.Directory dir = new gdcm.Directory();
        uint nfiles = dir.Load(directory);
        //System.Console.WriteLine(dir.toString());
        gdcm.FilenamesType filenames = dir.GetFilenames();

        Image image = new Image();
        image.SetNumberOfDimensions( 3 ); // important for now
        DataElement pixeldata = new DataElement( new gdcm.Tag(0x7fe0,0x0010) );

        // Create a new SequenceOfFragments C++ object, store it as a SmartPointer :
        SmartPtrFrag sq = SequenceOfFragments.New();

        // Yeah, the file are not guarantee to be in order, please adapt...
        for(uint i = 0; i < nfiles; ++i)
        {
            System.Console.WriteLine( filenames[(int)i] );
            string file = filenames[(int)i];
            System.IO.FileStream infile =
                new System.IO.FileStream(file, System.IO.FileMode.Open, System.IO.FileAccess.Read);
            uint fsize = gdcm.PosixEmulation.FileSize(file);

            byte[] jstream = new byte[fsize];
            infile.Read(jstream, 0 , jstream.Length);

            Fragment frag = new Fragment();
            frag.SetByteValue( jstream, new gdcm.VL( (uint)jstream.Length) );
            sq.AddFragment( frag );
        }

        // Pass by reference:
        pixeldata.SetValue( sq.__ref__() );

        // insert:
        image.SetDataElement( pixeldata );

        // JPEG use YBR to achieve better compression ratio by default (not RGB)
    }
}

```

```

// FIXME hardcoded:
PhotometricInterpretation pi = new PhotometricInterpretation( PhotometricInterpretation.PIType.
    MONOCHROME2 );
image.SetPhotometricInterpretation( pi );
// FIXME hardcoded:
PixelFormat pixeltype = new PixelFormat(1,8,8,7);
image.SetPixelFormat( pixeltype );

// FIXME hardcoded:
image.SetTransferSyntax( new TransferSyntax( TransferSyntax.TSType.JPEGLosslessProcess14_1 ) );
image.SetDimension(0, 512);
image.SetDimension(1, 512);
image.SetDimension(2, 355);

// Decompress !
byte[] decompressedData = new byte[(int)image.GetBufferLength()];
image.GetBuffer(decompressedData);

// Write out the decompressed bytes
System.Console.WriteLine(image.toString());
using (System.IO.Stream stream =
    System.IO.File.Open(@"tmp/dd.raw",
        System.IO.FileMode.Create))
{
    System.IO.BinaryWriter writer = new System.IO.BinaryWriter(stream);
    writer.Write(decompressedData);
}

return 0;
}
}

```

27.29 DecompressJPEGFile.cs

This is a C# example on how to use [gdcm::SequenceOfFragments](#)

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/DecompressJPEGFile.exe somejpegfile.jpg
 */
using System;
using gdcm;

public class DecompressJPEGFile
{
    public static int Main(string[] args)
    {
        string file1 = args[0];
        System.IO.FileStream infile =
            new System.IO.FileStream(file1, System.IO.FileMode.Open, System.IO.FileAccess.Read);
        uint fsize = gdcm.PosixEmulation.FileSize(file1);

        byte[] jstream = new byte[fsize];
        infile.Read(jstream, 0, jstream.Length);

        Trace.DebugOn();
        Image image = new Image();
        image.SetNumberOfDimensions( 2 ); // important for now
        DataElement pixeldata = new DataElement( new gdcm.Tag(0x7fe0,0x0010) );
    }
}

```



```

// DO NOT set a ByteValue here, JPEG is a particular kind of encapsulated syntax
// in which can one cannot use a simple byte array for storage. Instead, see
// gdcm.SequenceOfFragments
//pixeldata.SetByteValue( jstream, new gdcm.VL( (uint)jstream.Length ) );

// Create a new SequenceOfFragments C++ object, store it as a SmartPointer :
SmartPtrFrag sq = SequenceOfFragments.New();
Fragment frag = new Fragment();
frag.SetByteValue( jstream, new gdcm.VL( (uint)jstream.Length ) );
// Single file => single fragment
sq.AddFragment( frag );
// Pass by reference:
pixeldata.SetValue( sq.__ref__() );

// insert:
image.SetDataElement( pixeldata );

// JPEG use YBR to achieve better compression ratio by default (not RGB)
// FIXME hardcoded:
PhotometricInterpretation pi = new PhotometricInterpretation( PhotometricInterpretation.PIType.YBR_FULL
);
image.SetPhotometricInterpretation( pi );
// FIXME hardcoded:
PixelFormat pixeltype = new PixelFormat(3,8,8,7);
image.SetPixelFormat( pixeltype );

// FIXME hardcoded:
image.SetTransferSyntax( new TransferSyntax( TransferSyntax.TSType.JPEGLosslessProcess14_1 ) );
image.SetDimension(0, 692);
image.SetDimension(1, 721);

// Decompress !
byte[] decompressedData = new byte[(int)image.GetBufferLength()];
image.GetBuffer(decompressedData);

// Write out the decompressed bytes
System.Console.WriteLine(image.toString());
using (System.IO.Stream stream =
    System.IO.File.Open(@"tmp/dd.raw",
        System.IO.FileMode.Create))
{
    System.IO.BinaryWriter writer = new System.IO.BinaryWriter(stream);
    writer.Write(decompressedData);
}

return 0;
}
}

```

27.30 DecompressPixmap.java

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * This example will take in a DICOM file, and tries to decompress it (actually write it
 * as ImplicitVRLittleEndian Transfer Syntax).
 *
 * Compilation:
 * $ CLASSPATH=gdcm.jar javac ../../gdcm/Examples/Java/DecompressPixmap.java -d .
 *
 * Usage:
 * $ LD_LIBRARY_PATH=. CLASSPATH=gdcm.jar:. java DecompressPixmap gdcmData/012345.002.050.dcm out.dcm
 */
import gdcm.*;

```

```

public class DecompressPixmap
{
    public static void main(String[] args) throws Exception
    {
        String file1 = args[0];
        String file2 = args[1];
        PixmapReader reader = new PixmapReader();
        reader.SetFileName( file1 );
        boolean ret = reader.Read();
        if( !ret )
        {
            throw new Exception("Could not read: " + file1 );
        }

        ImageChangeTransferSyntax change = new ImageChangeTransferSyntax();
        change.SetTransferSyntax( new TransferSyntax(TransferSyntax.TSType.ImplicitVRLittleEndian) );
        PixmapToPixmapFilter filter = (PixmapToPixmapFilter)change;
        filter.SetInput( reader.GetPixmap() );
        if( !change.Change() )
        {
            throw new Exception("Could not change: " + file1 );
        }

        // The following does not work in Java/swig 2.0.7
        //Pixmap p = ((PixmapToPixmapFilter)change).GetOutput();
        Pixmap p = change.GetOutputAsPixmap(); // be explicit
        //System.out.println( p.toString() );

        // Set the Source Application Entity Title
        FileMetaInformation.SetSourceApplicationEntityTitle( "Just For Fun" );

        PixmapWriter writer = new PixmapWriter();
        writer.SetFileName( file2 );
        writer.SetFile( reader.GetFile() );
        writer.SetImage( p );
        ret = writer.Write();
        if( !ret )
        {
            throw new Exception("Could not write: " + file2 );
        }
    }
}

```

27.31 DiffFile.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/
#include "gdcmReader.h"

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input1.dcm input2.dcm" << std::endl;
        return 1;
    }
    const char *filename1 = argv[1];
    const char *filename2 = argv[2];

    gdcm::Reader reader1;
    reader1.SetFileName( filename1 );
    if( !reader1.Read() )
    {
        return 1;
    }
}

```

```

    }

    gdcM::Reader reader2;
    reader2.SetFileName( filename2 );
    if( !reader2.Read() )
    {
        return 1;
    }

    const gdcM::File &file1 = reader1.GetFile();
    const gdcM::File &file2 = reader2.GetFile();

    const gdcM::DataSet &ds1 = file1.GetDataSet();
    const gdcM::DataSet &ds2 = file2.GetDataSet();

    gdcM::DataSet::ConstIterator it1 = ds1.Begin();
    gdcM::DataSet::ConstIterator it2 = ds2.Begin();

    const gdcM::DataElement &de1 = *it1;
    const gdcM::DataElement &de2 = *it2;
    if( de1 == de2 )
    {
    }
    while( it1 != ds1.End() && it2 != ds2.End() && *it1 == *it2 )
    {
        ++it1;
        ++it2;
    }

    if( it1 != ds1.End() || it2 != ds2.End() )
    {
        std::cerr << "Problem with:" << std::endl;
        if( it1 != ds1.End() )
        {
            std::cerr << "ds1: " << *it1 << std::endl;
        }
        if( it2 != ds2.End() )
        {
            std::cerr << "ds2: " << *it2 << std::endl;
        }
        return 1;
    }

    return 0;
}

```

27.32 DiscriminateVolume.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcM.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcMScanner.h"
#include "gdcMTesting.h"
#include "gdcMIPPSorter.h"
#include "gdcMDirectionCosines.h"
#include <cmath>

/*
 * The following example is a basic sorted which should work in generic cases.
 * It sort files based on:
 * Study Instance UID
 * Series Instance UID
 * Frame of Reference UID
 * Image Orientation (Patient)
 * Image Position (Patient) (Sorting based on IPP + IOP)
 */

```

```

namespace gdcmm {
    const Tag t1(0x0020,0x000d); // Study Instance UID
    const Tag t2(0x0020,0x000e); // Series Instance UID
    const Tag t3(0x0020,0x0052); // Frame of Reference UID
    const Tag t4(0x0020,0x0037); // Image Orientation (Patient)

class DiscriminateVolume
{
private:
    std::vector< Directory::FileNamesType > SortedFiles;
    std::vector< Directory::FileNamesType > UnsortedFiles;

    Directory::FileNamesType GetAllFileNamesFromTagToValue(
        Scanner const & s, Directory::FileNamesType const & filesSubset, Tag const & t,
        const char *valueref)
    {
        Directory::FileNamesType theReturn;
        if( valueref )
        {
            size_t len = strlen( valueref );
            Directory::FileNamesType::const_iterator file = filesSubset.begin();
            for(; file != filesSubset.end(); ++file)
            {
                const char *filename = file->c_str();
                const char * value = s.GetValue(filename, t);
                if( value && strncmp(value, valueref, len ) == 0 )
                {
                    theReturn.push_back( filename );
                }
            }
        }
        return theReturn;
    }

void ProcessAIOP(Scanner const & , Directory::FileNamesType const & subset, const
    char *iopval)
{
    std::cout << "IOP: " << iopval << std::endl;
    IPPSorter ipp;
    ipp.SetComputeZSpacing( true );
    ipp.SetZSpacingTolerance( 1e-3 ); // ??
    bool b = ipp.Sort( subset );
    if( !b )
    {
        // If you reach here this means you need one more parameter to discriminat this
        // series. Eg. T1 / T2 intertwined. Multiple Echo (0018,0081)
        std::cerr << "Failed to sort: " << subset.begin()->c_str() << std::endl;
        for(
            Directory::FileNamesType::const_iterator file = subset.begin();
            file != subset.end(); ++file)
        {
            std::cerr << *file << std::endl;
        }
        UnsortedFiles.push_back( subset );
        return ;
    }
    ipp.Print( std::cout );
    SortedFiles.push_back( ipp.GetFileNames() );
}

void ProcessAFrameOfRef(Scanner const & s, Directory::FileNamesType const & subset,
    const char * frameuid)
{
    // In this subset of files (belonging to same series), let's find those
    // belonging to the same Frame ref UID:
    Directory::FileNamesType files = GetAllFileNamesFromTagToValue(
        s, subset, t3, frameuid);

    std::set< std::string > iopset;

    for(
        Directory::FileNamesType::const_iterator file = files.begin();
        file != files.end(); ++file)
    {
        //std::cout << *file << std::endl;
        const char * value = s.GetValue(file->c_str(), gdcmm::t4 );
        assert( value );
        iopset.insert( value );
    }
    size_t n = iopset.size();
    if ( n == 0 )

```

```

    {
        assert( files.empty() );
        return;
    }

    std::cout << "Frame of Ref: " << frameuid << std::endl;
    if ( n == 1 )
    {
        ProcessAIOP(s, files, iopset.begin()->c_str() );
    }
    else
    {
        const char *f = files.begin()->c_str();
        std::cerr << "More than one IOP: " << f << std::endl;
        // Make sure that there is actually 'n' different IOP
        gdcm::DirectionCosines ref;
        gdcm::DirectionCosines dc;
        for(
            std::set< std::string >::const_iterator it = iopset.begin();
            it != iopset.end(); ++it )
        {
            ref.SetFromString( it->c_str() );
            for(
                Directory::FileNamesType::const_iterator file = files.begin();
                file != files.end(); ++file )
            {
                std::string value = s.GetValue(file->c_str(), gdcm::t4 );
                if( value != it->c_str() )
                {
                    dc.SetFromString( value.c_str() );
                    const double crossdot = ref.CrossDot(dc);
                    const double eps = std::fabs( 1. - crossdot );
                    if( eps < 1e-6 )
                    {
                        std::cerr << "Problem with IOP discrimination: " << file->c_str()
                            << " " << it->c_str() << std::endl;
                        return;
                    }
                }
            }
        }
        // If we reach here this means there is actually 'n' different IOP
        for(
            std::set< std::string >::const_iterator it = iopset.begin();
            it != iopset.end(); ++it )
        {
            const char *iopvalue = it->c_str();
            Directory::FileNamesType iopfiles = GetAllFileNamesFromTagToValue(
                s, files, t4, iopvalue );
            ProcessAIOP(s, iopfiles, iopvalue );
        }
    }
}

void ProcessASeries(Scanner const & s, const char * seriesuid)
{
    std::cout << "Series: " << seriesuid << std::endl;
    // let's find all files belonging to this series:
    Directory::FileNamesType seriesfiles = GetAllFileNamesFromTagToValue(
        s, s.GetFileNames(), t2, seriesuid);

    gdcm::Scanner::ValueType vt3 = s.GetValues(t3);
    for(
        gdcm::Scanner::ValueType::const_iterator it = vt3.begin();
        it != vt3.end(); ++it )
    {
        ProcessAFrameOfRef(s, seriesfiles, it->c_str());
    }
}

void ProcessAStudy(Scanner const & s, const char * studyuid)
{
    std::cout << "Study: " << studyuid << std::endl;
    gdcm::Scanner::ValueType vt2 = s.GetValues(t2);
    for(
        gdcm::Scanner::ValueType::const_iterator it = vt2.begin();
        it != vt2.end(); ++it )
    {
        ProcessASeries(s, it->c_str());
    }
}

```

```

public:

void Print( std::ostream & os )
{
    os << "Sorted Files: " << std::endl;
    for(
        std::vector< Directory::FilenameType >::const_iterator it = SortedFiles.begin();
        it != SortedFiles.end(); ++it )
    {
        os << "Group: " << std::endl;
        for(
            Directory::FilenameType::const_iterator file = it->begin();
            file != it->end(); ++file)
        {
            os << *file << std::endl;
        }
    }
    os << "Unsorted Files: " << std::endl;
    for(
        std::vector< Directory::FilenameType >::const_iterator it = UnsortedFiles.begin();
        it != UnsortedFiles.end(); ++it )
    {
        os << "Group: " << std::endl;
        for(
            Directory::FilenameType::const_iterator file = it->begin();
            file != it->end(); ++file)
        {
            os << *file << std::endl;
        }
    }
}

std::vector< Directory::FilenameType > const & GetSortedFiles() const { return SortedFiles; }
std::vector< Directory::FilenameType > const & GetUnsortedFiles() const { return UnsortedFiles; }

void ProcessIntoVolume( Scanner const & s )
{
    gdcm::Scanner::ValueType vt1 = s.GetValues( gdcm::t1 );
    for(
        gdcm::Scanner::ValueType::const_iterator it = vt1.begin();
        ; it != vt1.end(); ++it )
    {
        ProcessAStudy( s, it->c_str() );
    }
}

};

} // namespace gdcm

int main(int argc, char *argv[])
{
    std::string dir1;
    if( argc < 2 )
    {
        const char *extradataroot = NULL;
#ifdef GDCM_BUILD_TESTING
        extradataroot = gdcm::Testing::GetDataExtraRoot();
#endif
        if( !extradataroot )
        {
            return 1;
        }
        dir1 = extradataroot;
        dir1 += "/gdcmSampleData/ForSeriesTesting/VariousIncidences/ST1";
    }
    else
    {
        dir1 = argv[1];
    }

    gdcm::Directory d;
    d.Load( dir1.c_str(), true ); // recursive !

    gdcm::Scanner s;
    s.AddTag( gdcm::t1 );
    s.AddTag( gdcm::t2 );
    s.AddTag( gdcm::t3 );
    s.AddTag( gdcm::t4 );
}

```

```

bool b = s.Scan( d.GetFilesNames() );
if( !b )
{
    std::cerr << "Scanner failed" << std::endl;
    return 1;
}

gdc::DiscriminateVolume dv;
dv.ProcessIntoVolume( s );
dv.Print( std::cout );

return 0;
}

```

27.33 DumbAnonymizer.py

```

1 #####
2 #
3 # Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 # Copyright (c) 2006-2011 Mathieu Malaterre
6 # All rights reserved.
7 # See Copyright.txt or http://gdc.sourceforge.net/Copyright.html for details.
8 #
9 # This software is distributed WITHOUT ANY WARRANTY; without even
10 # the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 # PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 This example shows how one can use the gdc::Anonymizer in 'dumb' mode.
17 This class becomes really handy when one knows which particular tag to fill in.
18
19 Usage:
20
21 python DumbAnonymizer.py gdcData/012345.002.050.dcm out.dcm
22
23 """
24
25 import gdc
26
27 # http://www.oid-info.com/get/1.3.6.1.4.17434
28 THERALYS_ORG_ROOT = "1.3.6.1.4.17434"
29
30 tag_rules={
31     # Value
32     (0x0012,0x0010):("Value","MySponsorName"),
33     (0x0012,0x0020):("Value","MyProtocolID"),
34     (0x0012,0x0021):("Value","MyProtocolName"),
35     (0x0012,0x0062):("Value","YES"),
36     (0x0012,0x0063):("Value","MyDeidentificationMethod"),
37
38     # Method
39     (0x0002,0x0003):("Method","GenerateMSOPIId"),
40     (0x0008,0x1155):("Method","GenerateMSOPIId"),
41     (0x0008,0x0018):("Method","GenerateMSOPIId"),
42     (0x0010,0x0010):("Method","GetSponsorInitials"),
43     (0x0010,0x0020):("Method","GetSponsorId"),
44     (0x0012,0x0030):("Method","GetSiteId"),
45     (0x0012,0x0031):("Method","GetSiteName"),
46     (0x0012,0x0040):("Method","GetSponsorId"),
47     (0x0012,0x0050):("Method","GetTPId"),
48     (0x0018,0x0022):("Method","KeepIfExist"),
49     (0x0018,0x1315):("Method","KeepIfExist"),
50     (0x0020,0x000d):("Method","GenerateStudyId"),
51     (0x0020,0x000e):("Method","GenerateSeriesId"),
52     (0x0020,0x1002):("Method","GetNumberOfFrames"),
53     (0x0020,0x0020):("Method","GetPatientOrientation"),
54
55     # Other:
56     (0x0012,0x0051):("Patient Field","Type Examen"),
57     (0x0018,0x1250):("Sequence Field","Receive Coil"),
58     (0x0018,0x0088):("Sequence Field","Spacing Between Slice"),
59     (0x0018,0x0095):("Sequence Field","Pixel Bandwidth"),
60     (0x0018,0x0082):("Sequence Field","Inversion Time"),
61 }

```

```

62 class MyAnon:
63     def __init__(self):
64         self.studyuid = None
65         self.seriesuid = None
66         generator = gdcms.UIDGenerator()
67         if not self.studyuid:
68             self.studyuid = generator.Generate()
69         if not self.seriesuid:
70             self.seriesuid = generator.Generate()
71     def GetSponsorInitials(self):
72         return "dummy^foobar"
73     def GenerateStudyId(self):
74         return self.studyuid
75     def GenerateSeriesId(self):
76         return self.seriesuid
77     #def GenerateMSOPIId(self):
78     def GenerateMSOPIId(self):
79         generator = gdcms.UIDGenerator()
80         return generator.Generate()
81     def GetSiteId(self):
82         return "MySiteId"
83     def GetSiteName(self):
84         return "MySiteName"
85     def GetSponsorId(self):
86         return "MySponsorId"
87     def GetTPId(self):
88         return "MyTP"
89
90 if __name__ == "__main__":
91     import sys
92     gdcms.FileMetaInformation.SetSourceApplicationEntityTitle
93     ( "DumbAnonymizer" )
94     gdcms.UIDGenerator.SetRoot( THERALYS_ORG_ROOT )
95
96     r = gdcms.Reader()
97     filename = sys.argv[1]
98     r.SetFileName( filename )
99     if not r.Read(): sys.exit(1)
100
101     obj = MyAnon()
102
103     w = gdcms.Writer()
104     ano = gdcms.Anonymizer()
105     ano.SetFile( r.GetFile() )
106     ano.RemoveGroupLength()
107     for tag,rule in tag_rules.items():
108         if rule[0] == 'Value':
109             print tag,rule
110             ano.Replace( gdcms.Tag( tag[0], tag[1] ), rule[1] )
111         elif rule[0] == 'Method':
112             print tag,rule
113             # result = locals()[rule[1]]()
114             methodname = rule[1]
115             if hasattr(obj, methodname):
116                 _member = getattr(obj, methodname)
117                 result = _member()
118                 ano.Replace( gdcms.Tag( tag[0], tag[1] ), result )
119             else:
120                 print "Problem with: ", methodname
121
122     outfilename = sys.argv[2]
123     w.SetFileName( outfilename )
124     w.SetFile( ano.GetFile() )
125     if not w.Write(): sys.exit(1)

```

27.34 DumpADAC.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcms.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR

```


PURPOSE. See the above copyright notice for more information.

```

=====*/
/*
 * the goal of this example is to mimic the behavior of disp_img_header
 * see http://www.gmecorp-usa.com/IM/NM/GC/ADAC/SV/adactechtips/Released\_01Q3.pdf
 */
#include "gdcmReader.h"
#include "gdcmPrivateTag.h"
#include "gdcmAttribute.h"
#include "gdcmImageWriter.h"

#include <iostream>
#include <fstream>
#include <vector>

#include <string.h>
#include <assert.h>
#include <stdint.h>

struct dict
{
    uint16_t key;
    const char *name;
};

dict Array[] = {
    { 0x01, "Patient name" },
    { 0x02, "Patient ID" },
    { 0x03, "Patient sex" },
    { 0x04, "Patient age" },
    { 0x05, "Patient height" },
    { 0x06, "Patient weight" },
    { 0x07, "Exam date" },
    { 0x08, "Dose admin. time" },
    { 0x09, "Unique exam key" },
    { 0x0a, "Exam procedure" },
    { 0x0b, "Referring physician" },
    { 0x0c, "Attending physician" },
    { 0x0d, "Imaging modality" },
    { 0x0e, "Hospital ID" },
    { 0x0f, "Histogram crv file" },
    { 0x10, "Acq. start time" },
    { 0x11, "Object data type" },
    { 0x12, "Image viewid" },
    { 0x13, "Imaging device name" },
    { 0x14, "Device serial number" },
    { 0x15, "Collimator" },
    { 0x16, "Software version" },
    { 0x17, "Radiopharmaceutical #1" },
    { 0x18, "Energy window #1 center" },
    { 0x19, "Radiopharmaceutical #2" },
    { 0x1a, "Energy window #1 width" },
    { 0x1b, "Isotope imaging mode" },
    { 0x1c, "Energy window #2 center" },
    { 0x1d, "Energy window #2 width" },
    { 0x1e, "Energy window #3 center" },
    { 0x1f, "Energy window #3 width" },
    { 0x20, "Energy window #4 center" },
    { 0x21, "Energy window #4 width" },
    { 0x22, "??Energy window #5 center" },
    { 0x23, "??Energy window #5 width" },
    { 0x24, "Patient orientation" },
    { 0x25, "Spatial resolution" },
    { 0x26, "Slice thickness" },
    { 0x27, "Image X dimension" },
    { 0x28, "Image Y dimension" },
    { 0x29, "Image Z dimension" },
    { 0x2a, "Image pixel width" },
    { 0x2b, "Uniformity corr. file" },
    { 0x2c, "Acquisition zoom factor" },
    { 0x2d, "Total counts in set" },
    { 0x2e, "Time / frame" },
    { 0x2f, "Total acq. time" },
    { 0x30, "Maximum pixel value" },
    { 0x31, "Minimum pixel value" },
    { 0x32, "R-R interval time" },
    { 0x33, "Percent of cycle imaged" },
    { 0x34, "# of cycles accepted" },
    { 0x35, "# of cycles rejected" },
    { 0x36, "Approximate ED frame" },

```

```

{ 0x37, "Approximate ES frame" },
{ 0x38, "Approximate EF" },
{ 0x39, "Starting angle" },
{ 0x3a, "Degrees of rotation" },
{ 0x3b, "Direction of rotation" },
{ 0x3c, "Cont. or step/shoot" },
{ 0x3d, "Lim recon start frame" },
{ 0x3e, "Upper window grey shade" },
{ 0x3f, "Lower lvl grey shade" },
{ 0x40, "Associated color map" },
{ 0x41, "Custom color map file" },
{ 0x42, "Manipulated image" },
{ 0x43, "Axis of rotation corr." },
{ 0x44, "Reorientation azimuth" },
{ 0x45, "Reorientation elevation" },
{ 0x46, "Filter type" },
{ 0x47, "Filter order" },
{ 0x48, "Filter cutoff frequency" },
{ 0x49, "Reconstruction type" },
{ 0x4a, "Attenuation coefficient" },
{ 0x4b, "Associated parent file" },
{ 0x4c, "Unique patient key" },
{ 0x52, "Normalization crv file" },
{ 0x53, "Unique object key" },
{ 0x54, "This phase of VFR is" },
{ 0x55, "True color value" },
{ 0x56, "# of sets of x,y,z grps" },
{ 0x57, "Scale factor of set" },
{ 0x6d, "Date of birth" },
{ 0x6e, "Directional orientation" },
{ 0x6f, "Number of VFR studies" },
{ 0x70, "R-R low tolerance" },
{ 0x71, "R-R high tolerance" },
{ 0x72, "Prog specific results:" },

{ 0x99, NULL }
};

void printname( int , int , uint16_t v )
{
    if( v == 0x1 )
    {
        std::cout << "DATABASE PARAMETERS" << std::endl;
        std::cout << "_____" << std::endl;
    }
    else if( v == 0x27 )
    {
        std::cout << "IMAGE PARAMETERS" << std::endl;
        std::cout << "_____" << std::endl;
    }
    else if( v == 0x13 )
    {
        std::cout << "EXTRA PARAMETERS" << std::endl;
        std::cout << "_____" << std::endl;
    }
    else if( v == 0x2e )
    {
        std::cout << "*** NOT CURRENTLY USED : " << std::endl;
    }
    static const unsigned int n = sizeof( Array ) / sizeof( *Array ) - 1;
    for( unsigned int i = 0; i < n; ++i )
    {
        if( v == Array[i].key )
        {
            std::cout << /*" " << std::dec << len << ", " << mult << " " << */ Array[i].name;
            std::cout << " : ";
            return;
        }
    }
    std::cout << /*"\t# " << std::dec << len << ", " << mult << */ std::hex << v << "\t: ";
}

uint16_t readint16(std::istream &is )
{
    uint16_t val;
    is.read( (char*)&val, sizeof( val ));
    return (uint16_t)((val>>8) | (val<<8));
}

uint32_t readint32(std::istream &is )
{

```

```

uint32_t val;
is.read( (char*)&val, sizeof( val ));
val= ((val<<8)&0xFF00FF00) | ((val>>8)&0x00FF00FF);
return (val>>16) | (val<<16);
}

float readfloat32(std::istream &is )
{
    union { uint32_t val; float f;} dual;
    dual.val = readint32(is);
    return dual.f;
}

struct el
{
    uint16_t v1;
    uint16_t v2;
    uint16_t v3;
    void read( std::istream & is )
    {
        v1 = readint16(is);
        v2 = readint16(is);
        v3 = readint16(is);
    }
    void print( std::ostream & os )
    {
        os << std::hex << v1 << "\t" << v2 << "\t" << v3 << std::endl;
    }
};

std::vector<el> Vel;

void readelement( std::istream & is )
{
    el e;
    e.read( is );
    Vel.push_back( e );
}

void printascii( uint16_t tag, const char *buffer, size_t len )
{
    std::ostream & os = std::cout;
    if( tag == 0x72 )
    {
        os << "\n ";
        for(size_t i = 0; i < len; ++i)
        {
            const char &c = buffer[i];
            if( c == 0x0 ) os << "!";
            else if( c == 0x0f ) os << " ";
            else if( c == 0x17 ) os << ":";
            else if( c == 0x14 ) os << ":";
            else if( c == 0x10 ) os << ":";
            else if( c == 0x16 ) os << ":";
            else if( c == 0x08 ) os << ":";
            else if( c == 0x0b ) os << ":";
            else if( c == 0x0e ) os << ":";
            else if( c == 0x07 ) os << ":";
            else os << c;
        }
        os << "\n";
    }
    else
    {
        (void)len;
        os << " " << buffer << "\n";
    }
}

bool DumpADAC( std::istream & is )
{
    std::ostream &os = std::cout;

    char magic[6 + 1];
    magic[6] = 0;
    is.read( magic, 6);
    // std::cout << magic << "\n";
    assert( strcmp( magic, "adac01" ) == 0 );
    int c = is.get();
    assert( c == 0 ); (void)c;
    c = is.get();
}

```

```

    assert( c == 'X' );

    uint16_t v;
    v = readint16(is);
    // std::cout << v << std::endl;
    assert( v == 512 ); (void)v; // ??

    int nel = 87;
    for (int i = 0; i <= nel; ++i )
    {
        readelement( is );
    }

    char buffer[512];
    for( int i = 0; i <= nel; ++i )
    {
        const el &e = Vel[i];
        int diff;
        if( i == nel )
        {
            diff = 2048 - e.v3;
            if( diff > 512 ) diff = 512;
        }
        else
        {
            const el &enext = Vel[i+1];
            diff = enext.v3 - e.v3;
        }
        is.seekg( e.v3, std::ios::beg );
        //std::cout << "(" << std::hex << std::setw( 2 ) << std::setfill( '0' ) << e.v1 << ")" " << std::hex <<
            std::setw( 3 ) << std::setfill( '0' ) << e.v2 << " ";
        printname( diff, 0, e.v1 );
        int mult = 1;
        if( e.v2 == 0 )
        {
            is.read( buffer, diff);
            buffer[ diff ] = 0;
            printascii( e.v1, buffer, diff);
        }
        else if( e.v2 == 0x100 )
        {
            mult = diff / 2;
            assert( diff == 2 * mult );
            for ( int ii = 0; ii < mult; ++ii )
            {
                if ( ii ) os << "\\ ";
                uint16_t val = readint16(is);
                os << " " << std::dec << val << " ";
            }
        }
        else if( e.v2 == 0x200 )
        {
            assert( diff == 4 );
            uint32_t val = readint32(is);
            os << " " << std::dec << val << " ";
        }
        else if( e.v2 == 0x300 )
        {
            assert( diff == 4 );
            float val = readfloat32(is);
            os << " " << std::dec << val << " ";
        }
        else
        {
            assert( 0 );
        }
        os << std::endl;
    }
    return true;
}

int main(int argc, char *argv[])
{
    if( argc < 2 ) return 1;
    const char *filename = argv[1];
    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Failed to read: " << filename << std::endl;
        return 1;
    }
}

```

```

    }
    const gdcm::DataSet& ds = reader.GetFile().GetDataSet();

    // (0019,1061) UN (OB) 61\64\61\63\30          # 2048,1 Ver200 ADAC Pegasys Headers
    const gdcm::PrivateTag tver200adacpegasysheaders(0x0019,0x61,"ADAC_IMG");
    if( !ds.FindDataElement( tver200adacpegasysheaders ) ) return 1;
    const gdcm::DataElement& ver200adacpegasysheaders = ds.
        GetDataElement( tver200adacpegasysheaders );
    if ( ver200adacpegasysheaders.IsEmpty() ) return 1;
    const gdcm::ByteValue * bv = ver200adacpegasysheaders.
        GetByteValue();

    // (0019,1021) US 1                          # 2,1 Ver200 Number of ADAC Headers
    // TODO

    // (0019,1041) IS [2048\221184 ] # 12,1-n Ver200 ADAC Header/Image Size
    if( bv->GetLength() != 2048 ) return 1;

    gdcm::Element<gdcm::VR::IS,gdcm::VM::VM2> el;
    const gdcm::PrivateTag tver200adacheaderimagesize(0x0019,0x41,"ADAC_IMG");
    if( !ds.FindDataElement( tver200adacheaderimagesize ) ) return 1;
    const gdcm::DataElement& ver200adacheaderimagesize = ds.
        GetDataElement( tver200adacheaderimagesize );
    el.SetFromDataElement( ver200adacheaderimagesize );
    if( el.GetValue(0) != 2048 ) return 1;

    std::iostream is;
    std::string dup( bv->GetPointer(), bv->GetLength() );
    is.str( dup );
    bool b = DumpADAC( is );
    if( !b ) return 1;

    return 0;
}

```

27.35 DumpGEMSMovieGroup.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmReader.h"
#include "gdcmImage.h"
#include "gdcmImageWriter.h"
#include "gdcmDataElement.h"
#include "gdcmPrivateTag.h"
#include "gdcmUIDGenerator.h"

#include <iostream>
#include <string>

#include <map>

bool PrintNameValueMapping( gdcm::SequenceOfItems *sqi_values,
gdcm::SequenceOfItems *sqi_names, std::string const & indent )
{
    using namespace gdcm;
    // prepare names mapping:
    typedef VRToType<VR::UL>::Type UL;
    std::map< UL, std::string > names;
    assert( sqi_names );
    assert( sqi_values );
    SequenceOfItems::SizeType s = sqi_names->
        GetNumberOfItems();
    PrivateTag tindex(0x7fe1,0x71,"GEMS_Ultrasound_MovieGroup_001");
    PrivateTag tname (0x7fe1,0x72,"GEMS_Ultrasound_MovieGroup_001");

```

```

// First sequence contains all possible names (this is a dict)
for( SequenceOfItems::SizeType i = 1; i <= s; ++i )
{
    const Item & item = sqi_names->GetItem( i );
    const DataSet & ds = item.GetNestedDataSet();
    if( !ds.FindDataElement( tindex )
        || !ds.FindDataElement( tname ) )
    {
        return false;
    }
    const DataElement & index = ds.GetDataElement( tindex );
    const DataElement & name = ds.GetDataElement( tname );
    if( index.IsEmpty() || name.IsEmpty() )
    {
        return false;
    }
    gdcmm::Element<VR::UL, VM::VM1> el1;
    el1.SetFromDataElement( index );

    gdcmm::Element<VR::LO, VM::VM1> el2;
    el2.SetFromDataElement( name );
    // std::cout << el1.GetValue() << " " << el2.GetValue() << std::endl;
    names.insert( std::make_pair( el1.GetValue(), el2.GetValue() ) );
}

SequenceOfItems::SizeType s2 = sqi_values->
    GetNumberOfItems();
assert( s2 <= s );
PrivateTag tindex2(0x7fe1,0x48,"GEMS_Ultrasound_MovieGroup_001");
for( SequenceOfItems::SizeType i = 1; i <= s2; ++i )
{
    const Item & item = sqi_values->GetItem( i );
    const DataSet & ds = item.GetNestedDataSet();
    if( !ds.FindDataElement( tindex2 ) )
    {
        return false;
    }
    const DataElement & index2 = ds.GetDataElement( tindex2 );
    if( index2.IsEmpty() )
    {
        return false;
    }
    gdcmm::Element<VR::FD, VM::VM1_2> el1;
    el1.SetFromDataElement( index2 );

    UL copy = (UL)el1.GetValue();
    #if 1
    std::cout << indent;
    std::cout << " ( " << names[ copy ];
    #endif
    // (7fe1,1052) FD 1560 # 8,1 ?
    // (7fe1,1057) LT [MscSkelSup] # 10,1 ?
    //PrivateTag tvalue(0x7fe1,0x52,"GEMS_Ultrasound_MovieGroup_001");
    PrivateTag tvalueint(0x7fe1,0x49,"GEMS_Ultrasound_MovieGroup_001"); // UL
    PrivateTag tvaluefloat1(0x7fe1,0x51,"GEMS_Ultrasound_MovieGroup_001"); // FL
    PrivateTag tvaluefloat(0x7fe1,0x52,"GEMS_Ultrasound_MovieGroup_001"); // FD
    PrivateTag tvalueu1(0x7fe1,0x53,"GEMS_Ultrasound_MovieGroup_001"); // UL
    PrivateTag tvalues1(0x7fe1,0x54,"GEMS_Ultrasound_MovieGroup_001"); // SL
    PrivateTag tvalueob(0x7fe1,0x55,"GEMS_Ultrasound_MovieGroup_001"); // OB
    PrivateTag tvaluetext(0x7fe1,0x57,"GEMS_Ultrasound_MovieGroup_001"); // LT
    PrivateTag tvaluefd(0x7fe1,0x77,"GEMS_Ultrasound_MovieGroup_001"); // FD / 1-N
    PrivateTag tvaluesl3(0x7fe1,0x79,"GEMS_Ultrasound_MovieGroup_001"); // SL / 1-N
    PrivateTag tvaluesl2(0x7fe1,0x86,"GEMS_Ultrasound_MovieGroup_001"); // SL ??
    PrivateTag tvaluefd1(0x7fe1,0x87,"GEMS_Ultrasound_MovieGroup_001"); // FD / 1-N
    PrivateTag tvaluefloat2(0x7fe1,0x88,"GEMS_Ultrasound_MovieGroup_001"); // FD ??
    #if 1
    std::cout << " ) = ";
    #endif
    if( ds.FindDataElement( tvalueint ) )
    {
        const DataElement & value = ds.GetDataElement( tvalueint );
        gdcmm::Element<VR::UL,VM::VM1> el2;
        el2.SetFromDataElement( value );
        std::cout << el2.GetValue() << std::endl;
    }
    else if( ds.FindDataElement( tvaluefloat1 ) )
    {
        const DataElement & value = ds.GetDataElement( tvaluefloat1 );
        gdcmm::Element<VR::FL,VM::VM1> el2;
        el2.SetFromDataElement( value );
        std::cout << el2.GetValue() << std::endl;
    }
}

```

```

    }
    else if( ds.FindDataElement( tvaluefloat ) )
    {
        const DataElement & value = ds.GetDataElement( tvaluefloat );
        gdcmm::Element<VR::FD,VM::VM1> el2;
        el2.SetFromDataElement( value );
        std::cout << el2.GetValue() << std::endl;
    }
    else if( ds.FindDataElement( tvaluesl ) )
    {
        const DataElement & value = ds.GetDataElement( tvaluesl );
        gdcmm::Element<VR::SL,VM::VM1> el2;
        el2.SetFromDataElement( value );
        std::cout << el2.GetValue() << std::endl;
    }
    else if( ds.FindDataElement( tvalueul ) )
    {
        const DataElement & value = ds.GetDataElement( tvalueul );
        gdcmm::Element<VR::UL,VM::VM1_n> el2;
        el2.SetFromDataElement( value );
        assert( el2.GetLength() == 1 );
        std::cout << el2.GetValue() << std::endl;
    }
    else if( ds.FindDataElement( tvalueob ) )
    {
        const DataElement & value = ds.GetDataElement( tvalueob );
        gdcmm::Element<VR::SL,VM::VM1> el2;
        // el2.SetFromDataElement( value );
        // std::cout << el2.GetValue() << std::endl;
        std::cout << value << std::endl;
    }
    else if( ds.FindDataElement( tvaluetext ) )
    {
        const DataElement & value = ds.GetDataElement( tvaluetext );
        gdcmm::Element<VR::LT,VM::VM1> el2;
        el2.SetFromDataElement( value );
        std::cout << el2.GetValue() << std::endl;
    }
    else if( ds.FindDataElement( tvaluesl2 ) )
    {
        const DataElement & value = ds.GetDataElement( tvaluesl2 );
        gdcmm::Element<VR::SL,VM::VM1_n> el2;
        el2.SetFromDataElement( value );
        el2.Print( std::cout );
        assert( el2.GetLength() == 4 );
        std::cout << std::endl;
    }
    else if( ds.FindDataElement( tvaluesl3 ) )
    {
        const DataElement & value = ds.GetDataElement( tvaluesl3 );
        gdcmm::Element<VR::SL,VM::VM1_n> el2;
        el2.SetFromDataElement( value );
        el2.Print( std::cout );
        // assert( el2.GetLength() == 4 );
        std::cout << std::endl;
    }
    else if( ds.FindDataElement( tvaluefd ) )
    {
        const DataElement & value = ds.GetDataElement( tvaluefd );
        gdcmm::Element<VR::FD,VM::VM1_n> el2;
        el2.SetFromDataElement( value );
        el2.Print( std::cout );
        // assert( el2.GetLength() == 4 || el2.GetLength() == 3 || el2.GetLength() == 8 );
        std::cout << std::endl;
    }
    else if( ds.FindDataElement( tvaluefloat2 ) )
    {
        const DataElement & value = ds.GetDataElement( tvaluefloat2 );
        gdcmm::Element<VR::FD,VM::VM1_n> el2;
        el2.SetFromDataElement( value );
        el2.Print( std::cout );
        assert( el2.GetLength() == 2 );
        std::cout << std::endl;
    }
    else if( ds.FindDataElement( tvaluefd1 ) )
    {
        const DataElement & value = ds.GetDataElement( tvaluefd1 );
        gdcmm::Element<VR::FD,VM::VM1_n> el2;
        el2.SetFromDataElement( value );
        el2.Print( std::cout );
        assert( el2.GetLength() == 4 );
    }

```

```

        std::cout << std::endl;
    }
    else
    {
        std::cout << "(no value)" << std::endl;
        //      std::cout << ds << std::endl;
        assert( ds.Size() == 2 );
    }
}
return true;
}

bool PrintNameValueMapping2( gdcm::PrivateTag const & privtag, const
    gdcm::DataSet & ds ,
gdcm::SequenceOfItems *sqi_names, std::string const & indent )
{
    if( !ds.FindDataElement( privtag ) ) return 1;
    const gdcm::DataElement& seq_values = ds.GetDataElement( privtag );
    gdcm::SmartPointer<gdcm::SequenceOfItems> sqi = seq_values.
        GetValueAsSQ();

    return PrintNameValueMapping( sqi, sqi_names, indent);
}

bool PrintNameValueMapping3( gdcm::PrivateTag const & privtag1,
    gdcm::PrivateTag const & privtag2, const gdcm::DataSet & ds ,
gdcm::SequenceOfItems *sqi_names, std::string const & indent )
{
    if( !ds.FindDataElement( privtag1 ) )
    {
        assert( 0 );
        return false;
    }
    const gdcm::DataElement& values10name = ds.GetDataElement( privtag1 );
    gdcm::Element<gdcm::VR::LO, gdcm::VM::VM1> el;
    el.SetFromDataElement( values10name );
    std::cout << std::endl;
    std::cout << " <" << el.GetValue().c_str() << ">" << std::endl;

    return PrintNameValueMapping2( privtag2, ds, sqi_names, indent);
}

bool print73( gdcm::DataSet const & ds10, gdcm::SequenceOfItems *sqi_dict
    , std::string const & indent )
{
    const gdcm::PrivateTag tseq_values73(0x7fe1, 0x73, "GEMS_Ultrasound_MovieGroup_001");
    if( !ds10.FindDataElement( tseq_values73 ) )
    {
        std::cout << indent << "No group 73" << std::endl;
        return false;
    }
    const gdcm::DataElement& seq_values73 = ds10.GetDataElement( tseq_values73
    );
    gdcm::SmartPointer<gdcm::SequenceOfItems> sqi_values73 =
        seq_values73.GetValueAsSQ();

    size_t ni3 = sqi_values73->GetNumberOfItems();
    for( size_t i3 = 1; i3 <= ni3; ++i3 )
    {
        gdcm::Item &item_73 = sqi_values73->GetItem(i3);
        gdcm::DataSet &ds73 = item_73.GetNestedDataSet();
        assert( ds73.Size() == 3 );

        const gdcm::PrivateTag tseq_values74name(0x7fe1, 0x74, "GEMS_Ultrasound_MovieGroup_001");
        const gdcm::PrivateTag tseq_values75(0x7fe1, 0x75, "GEMS_Ultrasound_MovieGroup_001");
        PrintNameValueMapping3( tseq_values74name, tseq_values75, ds73, sqi_dict, indent);
        std::cout << std::endl;
    }
    return true;
}

bool print83( gdcm::DataSet const & ds10, gdcm::SequenceOfItems *sqi_dict
    , std::string const & indent )
{
    const gdcm::PrivateTag tseq_values83(0x7fe1, 0x83, "GEMS_Ultrasound_MovieGroup_001");
    if( !ds10.FindDataElement( tseq_values83 ) )
    {
        std::cout << indent << "No group 83" << std::endl;
        return false;
    }
    const gdcm::DataElement& seq_values83 = ds10.GetDataElement( tseq_values83

```



```

    );
    gdcmm::SmartPointer<gdcmm::SequenceOfItems> sqi_values83 =
        seq_values83.GetValueAsSQ();

    size_t ni3 = sqi_values83->GetNumberOfItems();
    for( size_t i3 = 1; i3 <= ni3; ++i3 )
    {
        gdcmm::Item &item_83 = sqi_values83->GetItem(i3);
        gdcmm::DataSet &ds83 = item_83.GetNestedDataSet();
        assert( ds83.Size() == 3 );

        const gdcmm::PrivateTag tseq_values84name(0x7fe1,0x84,"GEMS_Ultrasound_MovieGroup_001");
        const gdcmm::PrivateTag tseq_values85(0x7fe1,0x85,"GEMS_Ultrasound_MovieGroup_001");
        PrintNameValueMapping3( tseq_values84name, tseq_values85, ds83, sqi_dict, indent);
        std::cout << std::endl;
    }
    return true;
}

bool PrintNameValueMapping4( gdcmm::PrivateTag const &privtag0, const
    gdcmm::DataSet &subds, gdcmm::PrivateTag const &privtag1,
    gdcmm::PrivateTag const &privtag2,
    gdcmm::SequenceOfItems *sqi_dict, std::string const &indent )
{
    (void)indent;
    if( !subds.FindDataElement( privtag0 ) )
    {
        assert( 0 );
        return 1;
    }
    const gdcmm::DataElement& seq_values10 = subds.GetDataElement( privtag0 );
    gdcmm::SmartPointer<gdcmm::SequenceOfItems> sqi_values10 =
        seq_values10.GetValueAsSQ();

    size_t nil = sqi_values10->GetNumberOfItems();
    // assert( nil == 1 );
    for( size_t i1 = 1; i1 <= nil; ++i1 )
    {
        gdcmm::Item &item_10 = sqi_values10->GetItem(i1);
        gdcmm::DataSet &ds10 = item_10.GetNestedDataSet();
        assert( ds10.Size() == 2 + 3 );
        // (7fe1,0010)
        // (7fe1,1012)
        // (7fe1,1018)
        // (7fe1,1020)
        // (7fe1,1083)

        PrintNameValueMapping3( privtag1, privtag2, ds10, sqi_dict, " " );
        std::cout << std::endl;

        const gdcmm::PrivateTag tseq_values20(0x7fe1,0x20,"GEMS_Ultrasound_MovieGroup_001");
        if( !ds10.FindDataElement( tseq_values20 ) )
        {
            assert( 0 );
            return 1;
        }
        const gdcmm::DataElement& seq_values20 = ds10.GetDataElement(
            tseq_values20 );
        gdcmm::SmartPointer<gdcmm::SequenceOfItems> sqi_values20 =
            seq_values20.GetValueAsSQ();

        size_t ni2 = sqi_values20->GetNumberOfItems();
        //assert( ni == 1 );
        for( size_t i2 = 1; i2 <= ni2; ++i2 )
        {
            gdcmm::Item &item_20 = sqi_values20->GetItem(i2);
            gdcmm::DataSet &ds20 = item_20.GetNestedDataSet();
            size_t count = ds20.Size(); (void)count;
            assert( ds20.Size() == 2 + 3 || ds20.Size() == 2 + 2 );
            // (7fe1,0010)
            // (7fe1,1024)
            // (7fe1,1026)
            // (7fe1,1036)
            // (7fe1,1083) (*)

            const gdcmm::PrivateTag tseq_values20name(0x7fe1,0x24,"GEMS_Ultrasound_MovieGroup_001"
            );
            const gdcmm::PrivateTag tseq_values26(0x7fe1,0x26,"GEMS_Ultrasound_MovieGroup_001");
            PrintNameValueMapping3( tseq_values20name, tseq_values26, ds20, sqi_dict, " " );
            std::cout << std::endl;

```

```

        print83(ds20, sqi_dict, "    ");
    }

    print83(ds10, sqi_dict, "    ");
}
return true;
}

int main(int argc, char *argv[])
{
    if( argc < 2 ) return 1;
    using namespace gdcm;
    const char *filename = argv[1];
    gdcm::Reader reader;
    reader.SetFileName( filename );
    reader.Read();

    gdcm::File &file = reader.GetFile();
    gdcm::DataSet &ds = file.GetDataSet();
    const PrivateTag tseq(0x7fe1,0x1,"GEMS_Ultrasound_MovieGroup_001");

    if( !ds.FindDataElement( tseq ) ) return 1;
    const DataElement& seq = ds.GetDataElement( tseq );

    SmartPointer<SequenceOfItems> sqi = seq.GetValueAsSQ();
    assert( sqi->GetNumberOfItems() == 1 );

    Item &item = sqi->GetItem(1);
    DataSet &subds = item.GetNestedDataSet();

    const PrivateTag tseq_dict(0x7fe1,0x70,"GEMS_Ultrasound_MovieGroup_001");
    if( !subds.FindDataElement( tseq_dict ) ) return 1;
    const DataElement& seq_dict = subds.GetDataElement( tseq_dict );
    SmartPointer<SequenceOfItems> sqi_dict = seq_dict.GetValueAsSQ();

    const PrivateTag tseq_values8(0x7fe1,0x8,"GEMS_Ultrasound_MovieGroup_001");
    if( !subds.FindDataElement( tseq_values8 ) ) return 1;
    const DataElement& seq_values8 = subds.GetDataElement( tseq_values8 );
    SmartPointer<SequenceOfItems> sqi_values8 = seq_values8.GetValueAsSQ();

    const PrivateTag tseq_values8name(0x7fe1,0x2,"GEMS_Ultrasound_MovieGroup_001");
    if( !subds.FindDataElement( tseq_values8name ) ) return 1;
    const DataElement& values8name = subds.GetDataElement( tseq_values8name );
    {
        Element<VR::LO,VM::VM1> el;
        el.SetFromDataElement( values8name );
        std::cout << el.GetValue() << std::endl;
    }

    size_t count = subds.Size(); (void)count;
    assert( subds.Size() == 3 + 2 + 1 || subds.Size() == 3 + 2 + 2 );

    // (7fe1,0010) # 30,1 Private Creator
    // (7fe1,1002) # 8,1 US MovieGroup Value 0008 Name
    // (7fe1,1003) # 4,1 ?
    // (7fe1,1008) # 8140,1 US MovieGroup Value 0008 Sequence
    // (7fe1,1010) # 1372196,1 ?
    // (7fe1,1070) # 33684,1 US MovieGroup Dict
    // (7fe1,1073) (*)
    PrintNameValueMapping( sqi_values8, sqi_dict, "    ");

    const PrivateTag tseq_values10(0x7fe1,0x10,"GEMS_Ultrasound_MovieGroup_001");
    const PrivateTag tseq_values10name(0x7fe1,0x12,"GEMS_Ultrasound_MovieGroup_001");
    const PrivateTag tseq_values18(0x7fe1,0x18,"GEMS_Ultrasound_MovieGroup_001");
    PrintNameValueMapping4( tseq_values10, subds, tseq_values10name, tseq_values18, sqi_dict, "    ");

    print73( subds, sqi_dict, "    ");

    #if 0
    gdcm::DataSet::ConstIterator it = subds.Begin();
    for( ; it != subds.End(); ++it )
    {
        const gdcm::DataElement &de = *it;
        std::cout << de.GetTag() << std::endl;
    }
    #endif

    return 0;
}

```

27.36 DumpImageHeaderInfo.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * Dump TOSHIBA MDW HEADER / Image Header Info
 */
#include "gdcmReader.h"
#include "gdcmPrivateTag.h"
#include "gdcmAttribute.h"
#include "gdcmImageWriter.h"

#include <iostream>
#include <fstream>
#include <vector>

#include <string.h>
#include <assert.h>
#include <stdint.h>

struct element
{
    std::istream & read( std::istream & is );
};

std::istream & element::read( std::istream & is )
{
    static const uint32_t ref = 0xe000fffe;
    std::ostream &os = std::cout;
    if( is.eof() )
    {
        return is;
    }
    uint32_t magic;
    if( !is.read( (char*)&magic, sizeof(magic) ) )
    {
        return is;
    }
    //os << magic << std::endl;
    assert( magic == ref );

    uint32_t l;
    is.read( (char*)&l, sizeof(l) );
    //os << l << std::endl;

    char str[17];
    str[16] = 0;
    is.read( str, 16 );
    os << str << " (" << l << ")" << std::endl;
    std::vector<char> bytes;
    bytes.resize( 1 - 16 );
    if( bytes.size() )
    {
        is.read( &bytes[0], 1 - 16 );
    }
    //os << "pos:" << is.tellg() << std::endl;

    if( strcmp(str, "TUSREMEASUREMENT") == 0 )
    {
        const char *p = &bytes[0];
        uint32_t val;
        memcpy( (char*)&val, p, sizeof(val) );
        os << " " << val << std::endl;
        p += sizeof(val);
        memcpy( (char*)&val, p, sizeof(val) );
        os << " " << val << std::endl;
        p += sizeof(val);
        memcpy( (char*)&val, p, sizeof(val) );
        os << " " << val << std::endl;
    }
}

```

```

    p += sizeof(val);
    memcpy( (char*)&val, p, sizeof(val) );
    os << " " << val << std::endl;
    p += sizeof(val);
    memcpy( (char*)&val, p, sizeof(val) );
    os << " " << val << std::endl;
    p += sizeof(val);
    memcpy( (char*)&val, p, sizeof(val) );
    os << " " << val << std::endl;
    p += sizeof(val);
    #if 0
        float f;
        memcpy( (char*)&f, p, sizeof(f) );
        os << " " << f << std::endl;
        p += sizeof(f);
    #else
        memcpy( (char*)&val, p, sizeof(val) );
        os << " " << val << std::endl;
        p += sizeof(val);
    #endif
    memcpy( (char*)&val, p, sizeof(val) );
    os << " " << val << std::endl;
    p += sizeof(val);
    char str2[17];
    memcpy( str2, p, 16 );
    str2[16] = 0;
    os << " " << str2 << std::endl;
}

#if 0
    std::ofstream out( str, std::ios::binary );
    out.write( (char*)&magic, sizeof( magic ) );
    out.write( (char*)&l, sizeof( l ) );
    out.write( str, 16 );
    out.write( &bytes[0], bytes.size() );
#endif
return is;
}

static bool DumpImageHeaderInfo( std::istream & is, size_t reflen )
{
    // TUSNONIMAGESTAM (5176)
    // TUSREMEASUREMEN (1352)
    // TUSBSINGLELAYOU (16)
    // TUSCLIPPARAMETE (104)

    element el;
    while( el.read( is ) )
    {
        //size_t pos = is.tellg();
        //assert( pos == reflen );
        (void)reflen;

        return true;
    }
}

int main(int argc, char *argv[])
{
    if( argc < 2 ) return 1;
    const char *filename = argv[1];
    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Failed to read: " << filename << std::endl;
        return 1;
    }
    const gdcm::DataSet& ds = reader.GetFile().GetDataSet();

    const gdcm::PrivateTag timageheaderinfo(0x0029,0x10,"TOSHIBA MDW HEADER");
    if( !ds.FindDataElement( timageheaderinfo ) ) return 1;
    const gdcm::DataElement& imageheaderinfo = ds.GetDataElement(
        timageheaderinfo );
    if ( imageheaderinfo.IsEmpty() ) return 1;
    const gdcm::ByteValue * bv = imageheaderinfo.GetByteValue();

    std::stringstream is;
    std::string dup( bv->GetPointer(), bv->GetLength() );
    is.str( dup );
    bool b = DumpImageHeaderInfo( is, bv->GetLength() );
}

```

```

    if( !b ) return 1;

#if 0
    const float d1 = 0.00416666668839752674; // 89 88 88 3B // 0x44c
    //const float d1 = 0.053231674455417881;
    const float d2 = 0.10828025639057159; // 0A C2 DD 3D // 0x1ac
    //const float d1 = 0.17869562069272813;
    //const unsigned int d2 = 4294967280;
    const float d3 = 0.10828025639057159; // 0A C2 DD 3D // 0x15c
    const int32_t d4 = 134;
    const uint32_t d5 = 1153476;
    std::ofstream t("/tmp/debug", std::ios::binary );
    //t.write( (char*)&d0, sizeof( d0 ) );
    t.write( (char*)&d1, sizeof( d1 ) );
    t.write( (char*)&d2, sizeof( d2 ) );
    t.write( (char*)&d3, sizeof( d3 ) );
    t.write( (char*)&d4, sizeof( d4 ) );
    t.write( (char*)&d5, sizeof( d5 ) );
    t.close();
#endif

    return 0;
}

```

27.37 DumpToSQLITE3.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * Ref:
 * http://massmail.spl.harvard.edu/public-archives/slicer-devel/2010/004408.html
 *
 * Implementation details:
 * http://www.sqlite.org/c3ref/bind_blob.html
 * http://www.adp-gmbh.ch/sqlite/bind_insert.html
 */
#include "gdcmScanner.h"
#include "gdcmDirectory.h"
#include "gdcmTag.h"
#include "gdcmTrace.h"

#include "sqlite3.h"

#include <stdio.h>
#include <time.h>

int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        return 1;
    }
    time_t time_start = time(0);

    gdcm::Trace::SetDebug( false );
    gdcm::Trace::SetWarning( false );
    const char *inputdirectory = argv[1];

    gdcm::Directory d;
    unsigned int nfiles = d.Load( inputdirectory, true);

    gdcm::Scanner s;
    using gdcm::Tag;
    s.AddTag( Tag(0x20,0xd) ); // Study Instance UID
    s.AddTag( Tag(0x20,0xe) ); // Series Instance UID

```

```

bool b0 = s.Scan( d.GetFilesNames() );
if( !b0 ) return 1;
time_t time_scanner = time(0);

std::cout << "Finished loading data from : " << nfiles << " files" << std::endl;

// MappingType const &mappings = s.GetMappings();

sqlite3* db;
sqlite3_open("./dicom.db", &db);

if(db == 0)
{
    std::cerr << "Could not open database." << std::endl;
    return 1;
}

const char sql_stmt[] = "create table browser (seriesuid, studyuid)";
int ret;

char *errmsg;
ret = sqlite3_exec(db, sql_stmt, 0, 0, &errmsg);

if(ret != SQLITE_OK)
{
    printf("Error in statement: %s [%s].\n", sql_stmt, errmsg);
    return 1;
}
using gdc::Directory;
using gdc::Scanner;
const Directory::FileNamesType& files = d.GetFilesNames();
Directory::FileNamesType::const_iterator file = files.begin();

sqlite3_stmt *stmt;
if ( sqlite3_prepare(
    db,
    "insert into browser values (?,?)", // stmt
    -1, // If than zero, then stmt is read up to the first nul terminator
    &stmt,
    0 // Pointer to unused portion of stmt
)
!= SQLITE_OK)
{
    printf("\nCould not prepare statement.");
    return 1;
}
//printf("\nThe statement has %d wildcards\n", sqlite3_bind_parameter_count(stmt));
for(; file != files.end(); ++file)
{
    const char *filename = file->c_str();
    bool b = s.IsKey(filename);
    if( b )
    {
        const Scanner::TagToValue &mapping = s.GetMapping(filename);
        Scanner::TagToValue::const_iterator it = mapping.begin();

        sqlite3_reset(stmt);

        for( int index = 1; it != mapping.end(); ++it, ++index)
        {
            //const Tag &tag = it->first;
            const char *value = it->second;

            if (sqlite3_bind_text (
                stmt,
                index, // Index of wildcard
                value,
                (int)strlen(value), // length of text
                SQLITE_STATIC // SQLite assumes that the information is in static
            )
            != SQLITE_OK)
            {
                printf("\nCould not bind int.\n");
                return 1;
            }
        }
        if (sqlite3_step(stmt) != SQLITE_DONE)
        {
            printf("\nCould not step (execute) stmt.\n");
            return 1;
        }
    }
}

```

```

    }
}

sqlite3_close(db);

time_t time_sqlite = time(0);

std::cout << "Time to scan DICOM files: " << (time_scanner - time_start) << std::endl;
std::cout << "Time to build SQLITE3: " << (time_sqlite - time_scanner) << std::endl;

return 0;
}

```

27.38 DuplicatePCDE.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcml.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmlReader.h"
#include "gdcmlWriter.h"
#include "gdcmlItem.h"
#include "gdcmlImageReader.h"
#include "gdcmlSequenceOfItems.h"
#include "gdcmlFile.h"
#include "gdcmlTag.h"
/*
Usage:
DuplicatePCDE gdcmlData/D_CLUNIE_CT1_J2KI.dcm out.dcm

aka:
medical.nema.org/medical/dicom/DataSets/WG04/IMAGES/J2KI/CT1_J2KI

See:
gdcmlConformanceTests/CT1_J2KI_DuplicatePCDE.dcm

Original thread can be found at:

http://groups.google.com/group/comp.protocols.dicom/browse_thread/thread/82f28c4db28963af

Question:
1.
There is no restriction for a specific Private Creator Data Element
(PCDE) to be unique within the same group, right ?
Decoders of Private Data would have to handle the case where a PCDE
would be repeated and should NOT stop on the first instance of a
particular PCDE, right ?

Eg. when searching for the tag associated with
(0x0029,0x0010,"SIEMENS CSA HEADER") in the following (pseudo)
dataset:

(0029,0010) LO [SIEMENS CSA HEADER] # 18, 1
PrivateCreator
(0029,0011) LO [SIEMENS MEDCOM HEADER] # 22, 1
PrivateCreator
(0029,0012) LO [SIEMENS MEDCOM HEADER2] # 22, 1
PrivateCreator
(0029,0013) LO [SIEMENS CSA HEADER] # 18, 1
PrivateCreator
(0029,1008) CS [IMAGE NUM 4] # 12, 1
CSAImageHeaderType
(0029,1009) LO [20050723] # 8, 1
CSAImageHeaderVersion
(0029,1010) OB 53\56\31\30\04\03\02\01\38\00\00\00\4d
\00\00\00\45\63\68\6f\4c\69... # 6788, 1 CSAImageHeaderInfo

```

```

(0029,1018) CS [MR] # 2, 1
CSAHeaderType
(0029,1019) LO [20050723] # 8, 1
CSAHeaderVersion
(0029,1020) OB 53\56\31\30\04\03\02\01\2c\00\00\00\4d
\00\00\00\55\73\65\64\50\61... # 51520, 1 CSAHeaderInfo
(0029,1131) LO [4.0.163088300] # 14, 1
PMTFInformation1
(0029,1132) UL 32768 # 4, 1
PMTFInformation2
(0029,1133) UL 0 # 4, 1
PMTFInformation3
(0029,1134) CS [DB TO DICOM] # 12, 1
PMTFInformation4
(0029,1260) ?? 63\6f\6d\20 # 4, 1
Unknown Tag & Data
(0029,1310) OB 53\56\31\30\04\03\02\01\38\00\00\00\4d
\00\00\00\45\63\68\6f\4c\69... # 6788, 1 CSAImageHeaderInfo

```

one should return two instances, correct ?

Answer:

I would say that this is covered in principle by the PS 3.5 7.1
 "The Data Elements ... shall occur at most once in a Data Set"
 rule, since the data element is defined by the tuple
 (private creator,gggg,ee) where xxee is the element
 number and xx is arbitrary and has no inherent meaning and
 does not serve to disambiguate the data element.

E.g.:

```

(0019,0030) Private Creator ID = "Smith"
...
(0019,0032) Private Creator ID = "Smith"
...
(0019,3015) Fractal Index = "32"
...
(0019,3215) Fractal Index = "32"

```

would be illegal because even though they are assigned different
 (completely arbitrary) blocks, with the same group, element
 number and private creator, (0019,3015) and (0019,3215) are the
 "same" data element.

*/

```

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];
    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        return 1;
    }

    gdcm::File &file = reader.GetFile();
    gdcm::DataSet &ds = file.GetDataSet();

    // Let's get all private element from group 0x9:
    /*
(0009,0010) LO [GEMS_IDEN_01] # 12,1 Private Creator
(0009,1001) LO [GE_GENESIS_FF ] # 14,1 Full fidelity
(0009,1002) SH [CT01] # 4,1 Suite id
(0009,1004) SH [HiSpeed CT/i] # 12,1 Product id
(0009,1027) SL 862399669 # 4,1 Image actual date
(0009,1030) SH (no value) # 0,1 Service id
(0009,1031) SH (no value) # 0,1 Mobile location number
(0009,10e6) SH [05] # 2,1 Genesis Version - now
(0009,10e7) UL 973283917 # 4,1 Exam Record checksum
(0009,10e9) SL 862399669 # 4,1 Actual series data time stamp
*/
    gdcm::Tag start(0x0009,0x0);
    // Create a temporary duplicate dataset, since we cannot insert data element as we go over them (std::set
    // would reorganize itself as we go over it ...)

```



```

gdcmm::DataSet dup;
gdcmm::Tag new_private(0x0009,0x0);
while (start.GetGroup() == 0x9 )
{
    const gdcmm::DataElement& de = ds.FindNextDataElement(start);
    const gdcmm::Tag &t = de.GetTag();
    if( t.IsPrivateCreator() )
    {
        std::cout << t << std::endl;
        // Ok let's duplicate into the next available attribute:
        gdcmm::DataElement duplicate = de;
        duplicate.GetTag().SetElement( (uint16_t)(t.GetElement() + 1) );
        dup.Insert( duplicate );
        new_private = duplicate.GetTag();
    }
    else if( t.IsPrivate() && !t.IsPrivateCreator() )
    {
        //std::cout << de << std::endl;
        std::string owner = ds.GetPrivateCreator( de.GetTag() );
        //std::cout << owner << std::endl;
        gdcmm::DataElement duplicate = de;
        duplicate.GetTag().SetPrivateCreator( new_private );
        if( const gdcmm::ByteValue *bv = duplicate.GetByteValue() )
        {
            // Warning: when doing : duplicate = de, only the pointer to the ByteValue is passed
            // (to avoid large memory duplicate). We need to explicitly duplicate the bytevalue ourselves:
            gdcmm::ByteValue *dupbv = new gdcmm::ByteValue( bv->GetPointer(),
                bv->GetLength() );
            // Let's recognize the duplicated ASCII-type elements:
            if( duplicate.GetVR() & gdcmm::VR::VRASCII )
                dupbv->Fill( 'X' );
            duplicate.SetValue( *dupbv );
        }
        dup.Insert( duplicate );
    }
    start = t;
    // move to next possible 'public' element
    start.SetElement( (uint16_t)(start.GetElement() + 1) );
}

gdcmm::DataSet::ConstIterator it = dup.Begin();
for( ; it != dup.End(); ++it )
{
    ds.Insert( *it );
}

gdcmm::Writer w;
w.SetFile( file );
w.SetFileName( outfilename );
if ( !w.Write() )
{
    return 1;
}

return 0;
}

```

27.39 ELSCINT1WaveToText.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmmReader.h"
#include "gdcmmPrivateTag.h"

/*
 * This example shows how to read a Wave Information tag from ELSCINT1

```

```

* The wave information is stored in Tag (01e1,18,ELSCINT1) hidden in a
* Secondary Capture Image Storage (usually a 'N' Symbol is shown)
*
* Everything done in this code is for the sole purpose of writing interoperable
* software under Sect. 1201 (f) Reverse Engineering exception of the DMCA.
* If you believe anything in this code violates any law or any of your rights,
* please contact us (gdcmm-developers@lists.sourceforge.net) so that we can
* find a solution.
*
* Everything you do with this code is at your own risk, since decompression
* algorithm was not written from specification documents.
*
* Special thanks to:
* Gauthier Bouilhol
*/

template <typename T>
bool dumpargs(std::ostream & os, T c1, T c2, T c3, T c4, T c5, T c6, T c7, T c8)
{
    static const char sep = '\t';
    os << c1 << sep << c2 << sep << c3 << sep << c4 << sep << c5 << sep << c6 << sep << c7 << sep << c8;
    os << std::endl;
    return true;
}

bool wave2stream( std::ostream &text_file, const char *in, size_t len )
{
    short * buffer = (short*)in;
    size_t length = len / sizeof( short );
    text_file << "COMPLETE_WAVE" << '\t' << "MASK" << '\t' << "AQUISITION_PROFIL" << '\t' << "
    END-INHALE" << '\t' << "END-EXHALE" << '\t' << "AQUISITION_WAVE" << '\t' << "WAVE_STATISTICS" << '\t' << "MASK"
    << std::endl;
    for (size_t i=0;i<length-76;i+=2)
    {
        if ( i < 74 )
        {
            if (buffer[i+75] == 0)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 0 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == 16384)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 0 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == 256)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 0 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == -32768)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 1 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == -16384)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 1 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == -32512)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 1 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == 0)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 0 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == 16384)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 0 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == 256)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 0 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == -32768)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 1 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == -16384)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 1 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
        }
        else
        {
            if (buffer[i+75] == 0)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 0 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == 16384)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 0 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == 256)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 0 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == -32768)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 1 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
            if (buffer[i+75] == -16384)
                text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 1 << '\t' << " " << '\t' << buffer[i] << '\t' << buffer[i+1] << std::endl;
        }
    }
}

```

```

        buffer[i+74] << '\t' << " " << '\t' << buffer[i+74] << '\t' << " " << '\t' << " "
        << std::endl;
        if (buffer[i+75] == -32512)
            text_file << buffer[i+74] << '\t' << buffer[i+75] << '\t' << 1 << '\t' << " "
            << '\t' << buffer[i+74] << '\t' << buffer[i+74] << '\t' << " " << '\t' << " "
            << std::endl;
    }
}

return true;
}

int main(int argc, char *argv [])
{
    if( argc < 3 ) return 1;
    const char *filename = argv[1];
    const char *outfilename = argv[2];
    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Failed to read: " << filename << std::endl;
        return 1;
    }
    const gdcm::DataSet& ds = reader.GetFile().GetDataSet();

    const gdcm::PrivateTag twave(0x01e1,0x18,"ELSCINT1");
    if( !ds.FindDataElement( twave ) ) return 1;
    const gdcm::DataElement& wave = ds.GetDataElement( twave );
    if ( wave.IsEmpty() ) return 1;
    const gdcm::ByteValue * bv = wave.GetByteValue();
    assert( bv );

    std::ofstream os( outfile );
    // Dump that to a CSV file:
    wave2stream( os, bv->GetPointer(), bv->GetLength() );
    os.close();

    return 0;
}

```

27.40 EncapsulateFileInRawData.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmAnonymizer.h"
#include "gdcmWriter.h"
#include "gdcmUIDGenerator.h"
#include "gdcmFile.h"
#include "gdcmTag.h"
#include "gdcmSystem.h"

#include "magic.h" // libmagic, API to file command line tool

/*
 * Let say you want to encapsulate a file type that is not defined in DICOM (exe, zip, png)
 * PNG is a bad example, unless it contains transparency (which has been deprecated).
 * It will take care of dispatching each chunk to an appropriate data item (pretty much like
 * WaveformData)
 *
 * Usage:
 * ./EncapsulateFileInRawData large_input_file.exe large_input_file.dcm
 */

// TODO:
// $ file -bi /tmp/gdcm-2.1.0.pdf

```

```

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " inputfile output.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];

    if( !gdcm::System::FileExists( filename ) ) return 1;

    size_t s = gdcm::System::FileSize(filename);
    if( !s ) return 1;

    magic_t cookie = magic_open(MAGIC_NONE);
    const char * file_type = magic_file(cookie, filename);
    if( !file_type ) return 1;
    magic_close(cookie);

    gdcm::Writer w;
    gdcm::File &file = w.GetFile();
    //gdcm::DataSet &ds = file.GetDataSet();
    //w.SetCheckFileMetaInformation( true );
    w.SetFileName( outfile );

    file.GetHeader().SetDataSetTransferSyntax(
        gdcm::TransferSyntax::ImplicitVRLittleEndian );

    gdcm::Anonymizer anon;
    anon.SetFile( file );

    gdcm::MediaStorage ms = gdcm::MediaStorage::RawDataStorage
        ;

    gdcm::UIDGenerator gen;
    anon.Replace( gdcm::Tag(0x0008,0x16), ms.GetString() );
    std::cout << ms.GetString() << std::endl;
    anon.Replace( gdcm::Tag(0x0008,0x18), gen.Generate() );

    if( !w.Write() )
    {
        std::cerr << "Could not write: " << outfile << std::endl;
        return 1;
    }

    return 0;
}

```

27.41 ExtractEncapsulatedFile.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * This example shows how one from C# context can extract a binary blob
 * and write out as a file.
 * This example is meant for pdf encapsulated file, but can be adapted for other type
 * of binary blob.
 *
 * DICOM file is:
 * ...
 * (0042,0010) ST (no value available) # 0, 0 DocumentTitle
 * (0042,0011) OB 25\50\44\46\2d\31\2e\32\20\0d\25\e2\e3\cf\d3\20\0d\31\30\20\30\20... # 40718, 1
 * EncapsulatedDocument

```

```

* (0042,0012) LO [application/pdf] # 16, 1 MIMETYPEOfEncapsulatedDocument
* ...
*
* Usage:
* $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
* $ mono bin/ExtractEncapsulatedFile.exe some_pdf_encapsulated.dcm
*/
using System;
using gdcm;

public class ExtractEncapsulatedFile
{
    public static int Main(string[] args)
    {
        string file = args[0];
        Reader reader = new Reader();
        reader.SetFileName( file );
        bool ret = reader.Read();
        if( !ret )
        {
            return 1;
        }

        File f = reader.GetFile();
        DataSet ds = f.GetDataSet();
        Tag tencapsulated_stream = new Tag(0x0042,0x0011); // Encapsulated Document
        if( !ds.FindDataElement( tencapsulated_stream ) )
        {
            return 1;
        }
        // else
        DataElement de = ds.GetDataElement( tencapsulated_stream );
        ByteValue bv = de.GetByteValue();
        uint len = bv.GetLength();
        byte[] encapsulated_stream = new byte[len];
        bv.GetBuffer( encapsulated_stream, len );

        // Write out the decompressed bytes
        //System.Console.WriteLine(image.toString());
        using (System.IO.Stream stream =
            System.IO.File.Open(@"tmp/dd.pdf",
                System.IO.FileMode.Create))
        {
            System.IO.BinaryWriter writer = new System.IO.BinaryWriter(stream);
            writer.Write( encapsulated_stream );
        }

        return 0;
    }
}

```

27.42 ExtractEncryptedContent.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmReader.h"

#include <fstream>

/*

openssl smime -encrypt -binary -aes256 -in outputfile.dcm -inform DER -out outputfile.der -outform DER ../
trunk/Testing/Source/Data/certificate.pem

openssl smime -decrypt -binary -in out.der -inform DER -out outputfile.dcm -outform DER -inkey ../trunk/

```

```

        Testing/Source/Data/privatekey.pem ../trunk/Testing/Source/Data/certificate.pem

    */

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.der" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];

    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        return 1;
    }

    gdcm::File &file = reader.GetFile();
    gdcm::DataSet &ds = file.GetDataSet();

    const gdcm::DataElement &EncryptedAttributesSequence = ds.
        GetDataElement( gdcm::Tag( 0x0400,0x0500 ) );

    gdcm::SequenceOfItems *sqi = EncryptedAttributesSequence.
        GetValueAsSQ();

    if ( !sqi || sqi->GetNumberOfItems() != 1 ) return 1;

    gdcm::Item &item = sqi->GetItem(1);

    gdcm::DataSet &nesteddds = item.GetNestedDataSet();

    if( ! nesteddds.FindDataElement( gdcm::Tag( 0x0400,0x0520 ) ) ) return 1;

    const gdcm::DataElement &EncryptedContent = nesteddds.
        GetDataElement( gdcm::Tag( 0x0400,0x0520 ) );

    const gdcm::ByteValue *bv = EncryptedContent.GetByteValue();

    std::ofstream of( outfile );
    of.write( bv->GetPointer(), bv->GetLength() );
    of.close();

    return 0;
}

```

27.43 ExtractIconFromFile.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * This example shows how to either retrieve an Icon if present somewhere
 * in the file, or else generate one.
 */
#include "gdcmImageReader.h"
#include "gdcmPNMCodec.h"
#include "gdcmIconImageFilter.h"
#include "gdcmIconImageGenerator.h"

bool WriteIconAsPNM(const char* filename, const gdcm::IconImage& icon)
{
    gdcm::PNMCodec pnm;

```

```

pnm.SetDimensions( icon.GetDimensions() );
pnm.SetPixelFormat( icon.GetPixelFormat() );
pnm.SetPhotometricInterpretation( icon.
    GetPhotometricInterpretation() );
pnm.SetLUT( icon.GetLUT() );
const gdcm::DataElement& in = icon.GetDataElement();
bool b = pnm.Write( filename, in );
assert( b ); (void)b;
return true;
}

int main(int argc, char *argv [])
{
    if( argc < 2 ) return 1;
    const char *filename = argv[1];
    gdcm::ImageReader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Failed to read (or not image): " << filename << std::endl;
        return 1;
    }

    gdcm::IconImageFilter iif;
    iif.SetFile( reader.GetFile() );
    bool b = iif.Extract();

    if( b )
    {
        const gdcm::IconImage &icon = iif.GetIconImage(0);
        icon.Print( std::cout );

        if( !icon.GetTransferSyntax().IsEncapsulated() )
        {
            // Let's write out this icon as PNM file
            WriteIconAsPNM("icon.ppm", icon);
        }
        else if( icon.GetTransferSyntax() ==
            gdcm::TransferSyntax::JPEGBaselineProcess1
            || icon.GetTransferSyntax() ==
            gdcm::TransferSyntax::JPEGExtendedProcess2_4
        )
        {
            const gdcm::DataElement& in = icon.GetDataElement();
            const gdcm::ByteValue *bv = in.GetByteValue();
            assert( bv );
            std::ofstream out( "icon.jpg" );
            out.write( bv->GetPointer(), bv->GetLength() );
            out.close();
        }
    }
    else
    {
        assert( iif.GetNumberOfIconImages() == 0 );
        std::cerr << "No Icon Found anywhere in file" << std::endl;

        const gdcm::Image &img = reader.GetImage();
        gdcm::IconImageGenerator iig;
        iig.AutoPixelMinMax(true);
        iig.SetPixmap( img );
        const unsigned int idims[2] = { 64, 64 };
        iig.SetOutputDimensions( idims );
        //iig.SetPixelMinMax(60, 868);
        if( !iig.Generate() ) return 1;
        const gdcm::IconImage &icon = iig.GetIconImage();
        WriteIconAsPNM("icon.ppm", icon);
    }

    return 0;
}

```

27.44 ExtractImageRegion.cs

```

/*=====

```

```

    Program: GDCM (Grassroots DICOM). A DICOM library

```

Copyright (c) 2006-2011 Mathieu Malaterre
 All rights reserved.
 See Copyright.txt or <http://gdcm.sourceforge.net/Copyright.html> for details.

This software is distributed WITHOUT ANY WARRANTY; without even
 the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
 PURPOSE. See the above copyright notice for more information.

```
=====*/

/*
 * This small code shows how to use the gdcm.ImageRegionReader API
 * In this example we are taking each frame by frame and dump them to
 * /tmp/frame.raw.
 *
 * Usage:
 * $ bin/ExtractImageRegion.exe input.dcm
 *
 * Example:
 * $ bin/ExtractImageRegion.exe gdcmData/012345.002.050.dcm
 * $ md5sum /tmp/frame.raw
 * d594a5e2fde12f32b6633ca859b4d4a6 /tmp/frame.raw
 * $ gdcminfo --md5sum gdcmData/012345.002.050.dcm
 * [...]
 * md5sum: d594a5e2fde12f32b6633ca859b4d4a6
 */
using System;
using gdcm;

public class ExtractImageRegion
{
    public static int Main(string[] args)
    {
        string filename = args[0];

        // instantiate the reader:
        gdcm.ImageRegionReader reader = new gdcm.ImageRegionReader();
        reader.SetFileName( filename );

        // pull DICOM info:
        if (!reader.ReadInformation()) return 1;
        // Get file infos
        gdcm.File f = reader.GetFile();

        // get some info about image
        UIntArrayType dims = ImageHelper.GetDimensionsValue(f);
        PixelFormat pf = ImageHelper.GetPixelFormatValue( f);
        int pixelsize = pf.GetPixelSize();

        // buffer to get the pixels
        byte[] buffer = new byte[ dims[0] * dims[1] * pixelsize ];

        // define a simple box region.
        BoxRegion box = new BoxRegion();
        for (uint z = 0; z < dims[2]; z++)
        {
            // Define that I want the image 0, full size (dimx x dimy pixels)
            // and do that for each z:
            box.SetDomain(0, dims[0] - 1, 0, dims[1] - 1, z, z);
            //System.Console.WriteLine( box.ToString() );
            reader.SetRegion( box );

            // reader will try to load the uncompressed image region into buffer.
            // the call returns an error when buffer.Length is too small. For instance
            // one can call:
            // uint buf_len = reader.ComputeBufferLength(); // take into account pixel size
            // to get the exact size of minimum buffer
            if (reader.ReadIntoBuffer(buffer, (uint)buffer.Length))
            {
                using (System.IO.Stream stream =
                    System.IO.File.Open(@"tmp/frame.raw",
                        System.IO.FileMode.Create))
                {
                    System.IO.BinaryWriter writer = new System.IO.BinaryWriter(stream);
                    writer.Write(buffer);
                }
            }
            else
            {
                throw new Exception("can't read pixels error");
            }
        }
    }
}
```



```

    }
    return 0;
}

```

27.45 ExtractImageRegionWithLUT.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

/*
 * This small code shows how to use the gdcm.ImageRegionReader API
 * In this example we are taking each frame by frame and dump them to
 * /tmp/frame.raw.
 * Furthermore we are applying the LUT on this image.
 * Special care should be taken in case the image is not PALETTE COLOR
 *
 * Usage:
 * $ bin/ExtractImageRegionWithLUT.exe input.dcm
 *
 * Example:
 * $ bin/ExtractImageRegionWithLUT.exe gdcmData/rle16l00.dcm
 * $ md5sum /tmp/frame_rgb.raw
 * 73bf61325fdb6e2830244a2b7b0c4ae2 /tmp/frame_rgb.raw
 * $ gdcimgm --depth 16 --spp 3 --size 600,430 /tmp/frame_rgb.raw rgb.dcm
 * $ gdcviewer rgb.dcm
 */
using System;
using gdcm;

public class ExtractImageRegion
{
    public static int Main(string[] args)
    {
        string filename = args[0];

        // instantiate the reader:
        gdcm.ImageRegionReader reader = new gdcm.ImageRegionReader();
        reader.SetFileName( filename );

        // pull DICOM info:
        if (!reader.ReadInformation()) return 1;
        // Get file infos
        gdcm.File f = reader.GetFile();

        gdcm.LookupTable lut = reader.GetImage().GetLUT();

        // get some info about image
        UIntArrayType dims = ImageHelper.GetDimensionsValue(f);
        PixelFormat pf = ImageHelper.GetPixelFormatValue (f);
        int pixelSize = pf.GetPixelSize();

        // buffer to get the pixels
        byte[] buffer = new byte[ dims[0] * dims[1] * pixelSize ];

        // output buffer for the RGB decoded image:
        byte[] buffer2 = new byte[ dims[0] * dims[1] * pixelSize * 3 ];

        // define a simple box region.
        BoxRegion box = new BoxRegion();
        for (uint z = 0; z < dims[2]; z++)
        {
            // Define that I want the image 0, full size (dimx x dimy pixels)
            // and do that for each z:
            box.SetDomain(0, dims[0] - 1, 0, dims[1] - 1, z, z);

```

```

//System.Console.WriteLine( box.toString() );
reader.SetRegion( box );

// reader will try to load the uncompressed image region into buffer.
// the call returns an error when buffer.Length is too small. For instance
// one can call:
// uint buf_len = reader.ComputeBufferLength(); // take into account pixel size
// to get the exact size of minimum buffer
if (reader.ReadIntoBuffer(buffer, (uint)buffer.Length))
{
    if( !lut.Decode( buffer2, (uint)buffer2.Length, buffer, (uint)buffer.Length ) )
    {
        throw new Exception("can't decode");
    }

    using (System.IO.Stream stream =
        System.IO.File.Open(@"tmp/frame_rgb.raw",
            System.IO.FileMode.Create))
    {
        System.IO.BinaryWriter writer = new System.IO.BinaryWriter(stream);
        writer.Write(buffer2);
    }
}
else
{
    throw new Exception("can't read pixels error");
}
}

return 0;
}
}

```

27.46 Extracting_All_Resolution.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
// This work was realised during the GSOC 2011 by Manoj Alwani

#include <fstream>
#include <openjpeg.h>
#include <stdint.h>
#include <string.h>
#include <assert.h>
#include <gdcm_j2k.h>
#include <gdcm_jp2.h>
#include <iostream>
#include <cstring>
#include <stdio.h>
#include <string.h>
#include <stdlib.h>
#include <math.h>
#include "gdcmImageReader.h"
#include "gdcmSequenceOfItems.h"
#include "gdcmSystem.h"
#include <fstream>

#include "gdcmMediaStorage.h"
#include "gdcmWriter.h"
#include "gdcmItem.h"
#include "gdcmImageReader.h"
#include "gdcmAttribute.h"
#include "gdcmFile.h"
#include "gdcmTag.h"

```

```

#include "gdcmTransferSyntax.h"
#include "gdcmUIDGenerator.h"
#include "gdcmAnonymizer.h"
#include "gdcmStreamImageWriter.h"
#include "gdcmImageHelper.h"
#include "gdcmTrace.h"

void error_callback(const char *msg, void *) {
    (void)msg;
}

void warning_callback(const char *msg, void *) {
    (void)msg;
}

void info_callback(const char *msg, void *) {
    (void)msg;
}

bool Write_Resolution(gdcm::StreamImageWriter & theStreamWriter, const char *
    filename, int res, std::ostream& of, int flag, gdcm::SequenceOfItems *sq, int
    No_Of_Resolutions)
{
    std::ifstream is;
    is.open( filename );
    opj_dparameters_t parameters; /* decompression parameters */
    opj_event_mgr_t event_mgr; /* event manager */
    opj_dinfo_t* dinfo; /* handle to a decompressor */
    opj_cio_t *cio;
    opj_image_t *image = NULL;
    // FIXME: Do some stupid work:
    is.seekg( 0, std::ios::end);
    std::streampos buf_size = is.tellg();
    char *dummy_buffer = new char[(unsigned int)buf_size];
    is.seekg(0, std::ios::beg);
    is.read( dummy_buffer, buf_size);
    unsigned char *src = (unsigned char*)dummy_buffer;
    uint32_t file_length = (uint32_t)buf_size; // 32bits truncation should be ok since DICOM cannot have
        larger than 2Gb image

    /* configure the event callbacks (not required) */
    memset(&event_mgr, 0, sizeof(opj_event_mgr_t));
    event_mgr.error_handler = error_callback;
    event_mgr.warning_handler = warning_callback;
    event_mgr.info_handler = info_callback;

    /* set decoding parameters to default values */
    opj_set_default_decoder_parameters(&parameters);

    // default blindly copied
    parameters.cp_layer=0;
    parameters.cp_reduce= res;
    // parameters.decode_format=-1;
    // parameters.cod_format=-1;

    const char jp2magic[] = "\x00\x00\x00\x0C\x6A\x50\x20\x20\x0D\x0A\x87\x0A";
    if( memcmp( src, jp2magic, sizeof(jp2magic) ) == 0 )
    {
        /* JPEG-2000 compressed image data ... sigh */
        // gdcmData/ELSCINT1_JP2vsJ2K.dcm
        // gdcmData/MAROTTECH_CT_JP2Lossy.dcm
        //gdcmWarningMacro( "J2K start like JPEG-2000 compressed image data instead of codestream" );
        parameters.decode_format = 1; //JP2_CFMT;
        //assert(parameters.decode_format == JP2_CFMT);
    }
    else
    {
        /* JPEG-2000 codestream */
        //parameters.decode_format = J2K_CFMT;
        //assert(parameters.decode_format == J2K_CFMT);
        assert( 0 );
    }
    parameters.cod_format = 11; // PGX_DFMT;
    //assert(parameters.cod_format == PGX_DFMT);

    /* get a decoder handle */
    dinfo = opj_create_decompress(CODEC_JP2);

    /* catch events using our callbacks and give a local context */
    opj_set_event_mgr((opj_common_ptr)dinfo, &event_mgr, NULL);
}

```

```

/* setup the decoder decoding parameters using user parameters */
opj_setup_decoder(dinfo, &parameters);

/* open a byte stream */
cio = opj_cio_open((opj_common_ptr)dinfo, src, file_length);

/* decode the stream and fill the image structure */
image = opj_decode(dinfo, cio);
if(!image) {
    opj_destroy_decompress(dinfo);
    opj_cio_close(cio);
    //gdcmErrorMacro( "opj_decode failed" );
    return 1;
}

    opj_cp_t * cp = ((opj_jp2_t*)dinfo->jp2_handle)->j2k->cp;
    opj_tcp_t *tcp = &cp->tcps[0];
    opj_tccp_t *tccp = &tcp->tccps[0];
/*     std::cout << "\n No of Cols In Image" << image->x1;
    std::cout << "\n No of Rows In Image" << image->y1;
    std::cout << "\n No of Components in Image" << image->numcomps;
    std::cout << "\n No of Resolutions"<< tccp->numresolutions << "\n";
*/

    opj_j2k_t* j2k = NULL;
    opj_jp2_t* jp2 = NULL;
    jp2 = (opj_jp2_t*)dinfo->jp2_handle;
    int reversible = jp2->j2k->cp->tcps->tccps->qmfbid;
    //std::cout << reversible;
    int compno = 0;
    opj_image_comp_t *comp = &image->comps[compno];
    int Dimensions[2];
    Dimensions[0]= comp->w;
    Dimensions[1] = comp->h;
    opj_cio_close(cio);
    unsigned long len = Dimensions[0]*Dimensions[1] * image->numcomps;
    //std::cout << "\nTest" <<image->comps[0].factor;
    char *raw = new char[len];
for (unsigned int compno = 0; compno < (unsigned int)image->numcomps; compno++)
{
    opj_image_comp_t *comp = &image->comps[compno];

    int w = image->comps[compno].w;
    int h = image->comps[compno].h;
    uint8_t *data8 = (uint8_t*)raw + compno;
    for (int i = 0; i < w * h ; i++)
    {
        int v = image->comps[compno].data[i];
        *data8 = (uint8_t)v;
        data8 += image->numcomps;
    }
}

gdcm::Writer w;
gdcm::File &file = w.GetFile();
gdcm::DataSet &ds = file.GetDataSet();

file.GetHeader().SetDataSetTransferSyntax(
    gdcm::TransferSyntax::ExplicitVRLittleEndian );

gdcm::UIDGenerator uid;
gdcm::DataElement de( gdcm::Tag(0x8,0x18) ); // SOP Instance UID
de.SetVR( gdcm::VR::UI );
const char *u = uid.Generate();
de.SetByteValue( u, strlen(u) );
ds.Insert( de );

gdcm::DataElement del( gdcm::Tag(0x8,0x16) );
del.SetVR( gdcm::VR::UI );
gdcm::MediaStorage ms( gdcm::MediaStorage::CTImageStorage
);
del.SetByteValue( ms.GetString(), strlen(ms.GetString()) );
ds.Insert( del );

const char mystr[] = "MONOCHROME2 ";
gdcm::DataElement de2( gdcm::Tag(0x28,0x04) );
//de.SetTag(gdcm::Tag(0x28,0x04));
de2.SetVR( gdcm::VR::CS );
de2.SetByteValue(mystr, strlen(mystr));
ds.Insert( de2 );

gdcm::Attribute<0x0028,0x0010> row = {image->comps[0].w};

```

```

    //row.SetValue(512);
    ds.Insert( row.GetAsDataElement() );
    // w.SetCheckFileMetaInformation( true );
    gdcm::Attribute<0x0028,0x0011> col = {image->comps[0].h};
    ds.Insert( col.GetAsDataElement() );
    gdcm::Attribute<0x0028,0x0008> Number_Of_Frames = {1};
    ds.Insert( Number_Of_Frames.GetAsDataElement() );

    gdcm::Attribute<0x0028,0x0100> at = {8};
    ds.Insert( at.GetAsDataElement() );

    gdcm::Attribute<0x0028,0x0002> at1 = {image->numcomps};
    ds.Insert( at1.GetAsDataElement() );

    gdcm::Attribute<0x0028,0x0101> at2 = {8};
    ds.Insert( at2.GetAsDataElement() );

    gdcm::Attribute<0x0028,0x0102> at3 = {7};
    ds.Insert( at3.GetAsDataElement() );

    if (flag == 1)
    {
        for (int i=0; i < No_Of_Resolutions; i++)
        {
            int a = 1;
            int b = 1;

            while(a!=(No_Of_Resolutions)-i))
            {
                b = b*2;
                a = a+1;
            }
            uint16_t row = (image->y1)/b;
            uint16_t col = (image->x1)/b;
            //std::cout << row;
            gdcm::Element<gdcm::VR::IS, gdcm::VM::VM1> el2;
            el2.SetValue(i+1);
            gdcm::DataElement rfn = el2.GetAsDataElement(); //ulr --> upper
                left row
            rfn.SetTag( gdcm::Tag(0x0008,0x1160) );

            gdcm::Element<gdcm::VR::US, gdcm::VM::VM2> el;
            el.SetValue(1,0);
            el.SetValue(1,1);
            gdcm::DataElement ulr = el.GetAsDataElement(); //ulr --> upper
                left col/row
            ulr.SetTag( gdcm::Tag(0x0048,0x0201) );

            gdcm::Element<gdcm::VR::US, gdcm::VM::VM2> el1;
            el1.SetValue(col,0);
            el1.SetValue(row,1);
            gdcm::DataElement brr = el1.GetAsDataElement();
            brr.SetTag( gdcm::Tag(0x0048,0x0202) ); //brr --> bottom right col/row
            gdcm::Item it;
            gdcm::DataSet &nds = it.GetNestedDataSet();
            nds.Insert( rfn );
            nds.Insert( ulr );
            nds.Insert( brr );

            sq->AddItem(it);
        }

        gdcm::Writer w1;
        gdcm::File &file1 = w1.GetFile();
        gdcm::DataSet &ds1 = file1.GetDataSet();
        file1.GetHeader().SetDataSetTransferSyntax(
            gdcm::TransferSyntax::ExplicitVRLittleEndian );

        gdcm::UIDGenerator uid1;
        gdcm::DataElement dea( gdcm::Tag(0x8,0x18) ); // SOP Instance UID
        dea.SetVR( gdcm::VR::UI );
        const char *ul = uid1.Generate();
        dea.SetByteValue( ul, strlen(ul) );
        ds1.Insert( dea );

        gdcm::DataElement deb( gdcm::Tag(0x8,0x16) );
        deb.SetVR( gdcm::VR::UI );

```

```

gdcmm::MediaStorage ms1(
    gdcmm::MediaStorage::VLWholeSlideMicroscopyImageStorage
);
deb.SetByteValue( ms1.GetString(), strlen(ms1.GetString()));
ds1.Insert( deb );

const char mystr1[] = "MONOCHROME2 ";
gdcmm::DataElement dec( gdcmm::Tag(0x28,0x04) );
//de.SetTag(gdcmm::Tag(0x28,0x04));
dec.SetVR( gdcmm::VR::CS );
dec.SetByteValue(mystr, strlen(mystr1));
ds1.Insert( dec );

gdcmm::Attribute<0x0028,0x0010> row1 = {image->y1};
//row.SetValue(512);
ds1.Insert( row1.GetAsDataElement() );
// w.SetCheckFileMetaInformation( true );
gdcmm::Attribute<0x0028,0x0011> coll = {image->x1};
ds1.Insert( coll.GetAsDataElement() );
gdcmm::Attribute<0x0028,0x0008> Number_Of_Frames1 = {tccp->numresolutions};
ds1.Insert( Number_Of_Frames1.GetAsDataElement() );

gdcmm::Attribute<0x0028,0x0100> ata = {8};
ds1.Insert( ata.GetAsDataElement() );

gdcmm::Attribute<0x0028,0x0002> atb = {image->numcomps};
ds1.Insert( atb.GetAsDataElement() );

gdcmm::Attribute<0x0028,0x0101> atc = {8};
ds1.Insert( atc.GetAsDataElement() );

gdcmm::Attribute<0x0028,0x0102> atd = {7};
ds1.Insert( atd.GetAsDataElement() );

theStreamWriter.SetFile(file1);

gdcmm::DataElement des( gdcmm::Tag(0x0048,0x0200) );
des.SetVR(gdcmm::VR::SQ);
//des.SetVR(gdcmm::VM::VM1);
des.SetValue(*sq);
des.SetVLToUndefined();

ds1.Insert( des );

if (!theStreamWriter.WriteImageInformation()){
    std::cerr << "unable to write image information" << std::endl;
    return 1; //the CanWrite function should prevent getting here, else,
    //that's a test failure
}

}

theStreamWriter.SetFile(file);

if (!theStreamWriter.CanWriteFile()){
    delete [] raw;
    std::cout << "Not able to write";
    return 0; //this means that the file was unwritable, period.
    //very similar to a ReadImageInformation failure
}
else
    std::cout<<"\nable to read";

// Important to write here
std::vector<unsigned int> extent = gdcmm::ImageHelper::GetDimensionsValue
    (file);

unsigned short xmax = extent[0];
unsigned short ymax = extent[1];
unsigned short theChunkSize = 4;
unsigned short ychunk = extent[1]/theChunkSize; //go in chunk sizes of theChunkSize
unsigned short zmax = extent[2];
std::cout << "\n" << xmax << "\n" << ymax << "\n" << zmax << "\n" << image->numcomps << "\n";

if (xmax == 0 || ymax == 0)
{
    std::cerr << "Image has no size, unable to write zero-sized image." << std::endl;
    return 0;
}

```

```

int z, y, nexty;
unsigned long prevLen = 0; //when going through the char buffer, make sure to grab
//the bytes sequentially. So, store how far you got in the buffer with each iteration.
for (z = 0; z < zmax; ++z){
    for (y = 0; y < ymax; y += ychunk){
        nexty = y + ychunk;
        if (nexty > ymax) nexty = ymax;
        theStreamWriter.DefinePixelExtent(0, xmax, y, nexty, z, z+1);
        unsigned long len = theStreamWriter.DefineProperBufferLength();
        std::cout << "\n" << len;
        char* finalBuffer = new char[len];
        memcpy(finalBuffer, &(raw[prevLen]), len);
        std::cout << "\nable to write";
        if (!theStreamWriter.Write(finalBuffer, len)){
            std::cerr << "writing failure:" << "output.dcm" << " at y = " << y << " and z= " << z <<
            std::endl;
            delete [] raw;
            delete [] finalBuffer;
            return 1;
        }
        delete [] finalBuffer;
        prevLen += len;
    }
}
delete raw;

delete[] src; //FIXME

if(dinfo) {
    opj_destroy_decompress(dinfo);
}

opj_image_destroy(image);

return true;
}

bool Different_Resolution( gdcm::StreamImageWriter & theStreamWriter, const char *
    filename, int res, std::ostream& of)
{
    //std::vector<std::string>::const_iterator it = filenames.begin();
    bool b = true;
    int flag = 1;

    gdcm::SmartPointer<gdcm::SequenceOfItems> sq = new
        gdcm::SequenceOfItems();
    sq->SetLengthToUndefined();

    for(int i = res-1 ; i>=0; --i)
    {
        b = b && Write_Resolution( theStreamWriter, filename, i, of ,flag,sq,res);
        // b = b && Get_Resolution( theStreamWriter, filename, i, of ,0);
        flag = 0;
    }
    //b = b && Get_Lowest_Resolution( writer, sq, filename, res-1 );
    //b = b && PopulateSingleFile( writer, sq, jpeg, filename2 );
    //image.SetDimension(2, res )
    return b;
}

int main(int argc, char *argv[])
{
    if( argc < 4 )
    {
        std::cerr << argv[0] << " input.jp2 output.dcm No. Of Resolutions " << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];
    char *resolutions = argv[3];
    int res = int((*resolutions)-48);
    //std::cout << "\nres"<< res;
    gdcm::StreamImageWriter theStreamWriter;

```

```

std::ofstream of;
of.open( outfile, std::ios::out | std::ios::binary );
theStreamWriter.SetStream(of);

if( !Different_Resolution( theStreamWriter, filename,res,of ) ) return 1;

uint16_t firstTag1 = 0xfffe;
uint16_t secondTag1 = 0xe0dd;
uint32_t thirdTag1 = 0x00000000;
//uint16_t fourthTag1 = 0xffff;
const int theBufferSize1 = 2*sizeof(uint16_t)+sizeof(uint32_t);
char* tmpBuffer2 = new char[theBufferSize1];
memcpy(&(tmpBuffer2[0]), &firstTag1, sizeof(uint16_t));
memcpy(&(tmpBuffer2[sizeof(uint16_t)]), &secondTag1, sizeof(uint16_t));
memcpy(&(tmpBuffer2[2*sizeof(uint16_t)]), &thirdTag1, sizeof(uint32_t));
//memcpy(&(tmpBuffer2[3*sizeof(uint16_t)]), &fourthTag1, sizeof(uint16_t));
assert( of && !of.eof() && of.good() );
of.write(tmpBuffer2, theBufferSize1);
of.flush();
assert( of );

return 0;
}

```

27.47 ExtractOneFrame.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * This small code shows how to use the gdcm.StreamImageReader API
 * to read a single (whole) frame at a time
 * The API allow extracting a smaller extent of the frame of course.
 * It will write out the extracted frame in /tmp/frame.raw
 *
 * Usage:
 * $ bin/ExtractOneFrame.exe input.dcm
 */
using System;
using gdcm;

public class ExtractOneFrame
{
    public static int Main(string[] args)
    {
        string filename = args[0];

        gdcm.StreamImageReader reader = new gdcm.StreamImageReader();

        reader.SetFileName( filename );

        if (!reader.ReadImageInformation()) return 1;
        // Get file infos
        gdcm.File f = reader.GetFile();

        // get some info about image
        UIntArrayType extent = ImageHelper.GetDimensionsValue(f);
        //System.Console.WriteLine( extent[0] );
        uint dimx = extent[0];
        //System.Console.WriteLine( extent[1] );
        uint dimy = extent[1];
        //System.Console.WriteLine( extent[2] );
        uint dimz = extent[2];
        PixelFormat pf = ImageHelper.GetPixelFormatValue (f);

```



```

int pixelSize = pf.GetPixelSize();
//System.Console.WriteLine( pixelSize );

// buffer to get the pixels
byte[] buffer = new byte[ dimx * dimy * pixelSize ];

for (int i = 0; i < dimz; i++)
{
    // Define that I want the image 0, full size (dimx x dimy pixels)
    reader.DefinePixelExtent(0, (ushort)dimx, 0, (ushort)dimy, (ushort)i, (ushort)(i+1));
    uint buf_len = reader.DefineProperBufferLength(); // take into account pixel size
    //System.Console.WriteLine( buf_len );
    if( buf_len > buffer.Length )
    {
        throw new Exception("buffer is too small for target");
    }

    if (reader.Read(buffer, (uint)buffer.Length))
    {
        using (System.IO.Stream stream =
            System.IO.File.Open(@"tmp/frame.raw",
                System.IO.FileMode.Create))
        {
            System.IO.BinaryWriter writer = new System.IO.BinaryWriter(stream);
            writer.Write(buffer);
        }
    }
    else
    {
        throw new Exception("can't read pixels error");
    }
}

return 0;
}

```

27.48 Fake_Image_Using_Stream_Image_Writer.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
// This work was realised during the GSOC 2011 by Manoj Alwani

#include "gdcmReader.h"
#include "gdcmMediaStorage.h"
#include "gdcmWriter.h"
#include "gdcmItem.h"
#include "gdcmImageReader.h"
#include "gdcmAttribute.h"
#include "gdcmFile.h"
#include "gdcmTag.h"
#include "gdcmTransferSyntax.h"
#include "gdcmUIDGenerator.h"
#include "gdcmAnonymizer.h"
#include "gdcmStreamImageWriter.h"
#include "gdcmImageHelper.h"
#include "gdcmTrace.h"

int main(int, char *[])
{
    char * buffer = new char[ 256 * 256 *3 ];
    // *p = (uint8_t*)buffer;
    char * p = buffer;

    gdcm::Trace::DebugOn();

```

```

gdcmm::Trace::WarningOn();

for(int row = 0; row < 256; ++row)
{
    for(int col = 0; col < 256; ++col)
        //for(int b = 0; b < 256; ++b)
        {
            *p++ = 255;
            *p++ = 0;
            *p++ = 0;
        }
}

gdcmm::Writer w;
gdcmm::File &file = w.GetFile();
gdcmm::DataSet &ds = file.GetDataSet();

file.GetHeader().SetDataSetTransferSyntax(
    gdcmm::TransferSyntax::ExplicitVRLittleEndian );

gdcmm::UIDGenerator uid;
gdcmm::DataElement de( gdcmm::Tag(0x8,0x18) ); // SOP Instance UID
de.SetVR( gdcmm::VR::UI );
const char *u = uid.Generate();
de.SetByteValue( u, strlen(u) );
ds.Insert( de );

gdcmm::DataElement del( gdcmm::Tag(0x8,0x16) );
del.SetVR( gdcmm::VR::UI );
gdcmm::MediaStorage ms(
    gdcmm::MediaStorage::VLWholeSlideMicroscopyImageStorage
);
del.SetByteValue( ms.GetString(), strlen(ms.GetString()) );
ds.Insert( del );

const char mystr[] = "RGB";
gdcmm::DataElement de2( gdcmm::Tag(0x28,0x04) );
//de.SetTag(gdcmm::Tag(0x28,0x04));
de2.SetVR( gdcmm::VR::CS );
de2.SetByteValue(mystr, strlen(mystr));
ds.Insert( de2 );

gdcmm::Attribute<0x0028,0x0010> row = {256};
//row.SetValue(512);
ds.Insert( row.GetAsDataElement() );
// w.SetCheckFileMetaInformation( true );
gdcmm::Attribute<0x0028,0x0011> col = {256};
ds.Insert( col.GetAsDataElement() );

gdcmm::Attribute<0x0028,0x0008> Number_Of_Frames = {1};
ds.Insert( Number_Of_Frames.GetAsDataElement() );

gdcmm::Attribute<0x0028,0x0100> at = {8};
ds.Insert( at.GetAsDataElement() );

gdcmm::Attribute<0x0028,0x0002> at1 = {3}; //bits per pixel
ds.Insert( at1.GetAsDataElement() );

gdcmm::Attribute<0x0028,0x0101> at2 = {8};
ds.Insert( at2.GetAsDataElement() );

gdcmm::Attribute<0x0028,0x0102> at3 = {7};
ds.Insert( at3.GetAsDataElement() );

gdcmm::Attribute<0x0028,0x0006> at4 = {0};
ds.Insert( at4.GetAsDataElement() );

gdcmm::Attribute<0x0028,0x0103> at5 = {0};
ds.Insert( at5.GetAsDataElement() );

//de.SetTag(gdcmm::Tag(0x7fe0,0x0010));
//ds.Insert(de);

gdcmm::StreamImageWriter theStreamWriter;
gdcmm::SmartPointer<gdcmm::SequenceOfItems> sq = new
    gdcmm::SequenceOfItems();
sq->SetLengthToUndefined();

uint16_t row1 = 256;
uint16_t col1 = 256;
//std::cout << row;

```

```

    gdcM::Element<gdcM::VR::IS,gdcM::VM::VM1> el2;
    el2.SetValue(1);
    gdcM::DataElement rfn = el2.GetAsDataElement();    //rfn --->
        reference frame number
    rfn.SetTag( gdcM::Tag(0x0008,0x1160) );

    gdcM::Element<gdcM::VR::US,gdcM::VM::VM2> el;
    el.SetValue(1,0);
    el.SetValue(1,1);
    gdcM::DataElement ulr = el.GetAsDataElement();    //ulr --> upper
        left col/row
    ulr.SetTag( gdcM::Tag(0x0048,0x0201) );

    gdcM::Element<gdcM::VR::US,gdcM::VM::VM2> ell;
    ell.SetValue(col1,0);
    ell.SetValue(row1,1);
    gdcM::DataElement brr = ell.GetAsDataElement();
    brr.SetTag( gdcM::Tag(0x0048,0x0202) );    //brr --> bottom right col/row

    gdcM::Item it;
    gdcM::DataSet &nds = it.GetNestedDataSet();
    nds.Insert( rfn );
    nds.Insert( ulr );
    nds.Insert( brr );

    sq->AddItem(it);

    gdcM::DataElement des( gdcM::Tag(0x0048,0x0200) );
    des.SetVR(gdcM::VR::SQ);
    des.SetValue(*sq);
    des.SetVLToUndefined();

    ds.Insert( des );

    theStreamWriter.SetFile(file);

    std::ofstream of;
    of.open( "output.dcm", std::ios::out | std::ios::binary );
    theStreamWriter.SetStream(of);

    if (!theStreamWriter.CanWriteFile()){
        delete [] buffer;
        std::cout << "Not able to write";
        return 0; //this means that the file was unwritable, period.
        //very similar to a ReadImageInformation failure
    }
    else
        std::cout<<"\nable to read";

    if (!theStreamWriter.WriteImageInformation()){
        std::cerr << "unable to write image information" << std::endl;
        delete [] buffer;
        return 1; //the CanWrite function should prevent getting here, else,
        //that's a test failure
    }

    std::vector<unsigned int> extent =
        gdcM::ImageHelper::GetDimensionsValue(file);

    unsigned short xmax = extent[0];
    unsigned short ymax = extent[1];
    unsigned short theChunkSize = 1;
    unsigned short ychunk = extent[1]/theChunkSize; //go in chunk sizes of theChunkSize
    unsigned short zmax = extent[2];

    std::cout << xmax << ymax << zmax;

    if (xmax == 0 || ymax == 0)
    {
        std::cerr << "Image has no size, unable to write zero-sized image." << std::endl;
        return 0;
    }

    int z, y, nexty;
    unsigned long prevLen = 0; //when going through the char buffer, make sure to grab
    //the bytes sequentially. So, store how far you got in the buffer with each iteration.
    for (z = 0; z < zmax; ++z){
        for (y = 0; y < ymax; y += ychunk){

```

```

        nexty = y + ychunk;
        if (nexty > ymax) nexty = ymax;
        theStreamWriter.DefinePixelExtent(0, xmax, y, nexty, z, z+1);
        unsigned long len = theStreamWriter.DefineProperBufferLength();
        std::cout << "\n" << len;
        char* finalBuffer = new char[len];
        memcpy(finalBuffer, &(buffer[prevLen]), len);
        std::cout << "\nable to write";
        if (!theStreamWriter.Write(finalBuffer, len)){
            std::cerr << "writing failure:" << "output.dcm" << " at y = " << y << " and z = " << z <<
std::endl;
            delete [] buffer;
            delete [] finalBuffer;
            return 1;
        }
        delete [] finalBuffer;
        prevLen += len;
    }
    delete buffer;

    uint16_t firstTag1 = 0xfffe;
    uint16_t secondTag1 = 0xe0dd;
    uint32_t thirdTag1 = 0x00000000;
    //uint16_t fourthTag1 = 0xffff;
    const int theBufferSize1 = 2*sizeof(uint16_t)+sizeof(uint32_t);
    char* tmpBuffer2 = new char[theBufferSize1];
    memcpy(&(tmpBuffer2[0]), &firstTag1, sizeof(uint16_t));
    memcpy(&(tmpBuffer2[sizeof(uint16_t)]), &secondTag1, sizeof(uint16_t));
    memcpy(&(tmpBuffer2[2*sizeof(uint16_t)]), &thirdTag1, sizeof(uint32_t));
    //memcpy(&(tmpBuffer2[3*sizeof(uint16_t)]), &fourthTag1, sizeof(uint16_t));
    assert( of && !of.eof() && of.good() );
    of.write(tmpBuffer2, theBufferSize1);
    of.flush();
    assert( of );

    return 0;
}

```

27.49 FileAnonymize.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * Simple C# example
 *
 * Usage:
 * $ mono bin/FileAnonymize.exe input.dcm output.dcm
 */
using System;
using gdcm;

public class FileAnonymize
{
    public static int Main(string[] args)
    {
        string filename = args[0];
        string outfilename = args[1];

        gdcm.FileAnonymizer fa = new gdcm.FileAnonymizer();
        fa.SetInputFileName( filename );
        fa.SetOutputFileName( outfilename );

        // Empty Operations
    }
}

```

```

// It will create elements, since those tags are non-registered public elements (2011):
fa.Empty( new Tag(0x0008,0x1313) );
fa.Empty( new Tag(0x0008,0x1317) );
// Remove Operations
// The following Tag are actually carefully chosen, since they refer to SQ:
fa.Remove( new Tag(0x0008,0x2112) );
fa.Remove( new Tag(0x0008,0x9215) );
// Replace Operations
// do not call replace operation on SQ attribute !
fa.Replace( new Tag(0x0018,0x5100), "MYVALUE " );
fa.Replace( new Tag(0x0008,0x1160), "MYOTHERVAL" );

if( !fa.Write() )
{
    System.Console.WriteLine( "Could not write" );
    return 1;
}

return 0;
}
}

```

27.50 FileAnonymize.java

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

import gdcm.*;

public class FileAnonymize
{
    public static class MyWatcher extends SimpleSubjectWatcher
    {
        public MyWatcher(Subject s) { super(s,"Override String"); }
        protected void ShowProgress(Subject caller, Event evt)
        {
            ProgressEvent pe = ProgressEvent.Cast(evt);
            System.out.println( "This is my progress: " + pe.GetProgress() );
        }
    }

    public static void main(String[] args) throws Exception
    {
        String input = args[0];
        String output = args[1];

        FileAnonymizer fa = new FileAnonymizer();
        fa.SetInputFileName( input );
        fa.SetOutputFileName( output );

        // Empty Operations
        // It will create elements, since those tags are non-registered public elements (2011):
        fa.Empty( new Tag(0x0008,0x1313) );
        fa.Empty( new Tag(0x0008,0x1317) );
        // Remove Operations
        // The following Tag are actually carefully chosen, since they refer to SQ:
        fa.Remove( new Tag(0x0008,0x2112) );
        fa.Remove( new Tag(0x0008,0x9215) );
        // Replace Operations
        // do not call replace operation on SQ attribute !
        fa.Replace( new Tag(0x0018,0x5100), "MYVALUE " );
        fa.Replace( new Tag(0x0008,0x1160), "MYOTHERVAL" );

        if( !fa.Write() )
        {
            System.out.println( "Could not write" );

```

```

        return;
    }

    System.out.println( "success" );
}

```

27.51 FindAllPatientName.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #       This software is distributed WITHOUT ANY WARRANTY; without even
10 #       the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #       PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14 """
15 This example shows how one can use the gdcm.CompositeNetworkFunctions class
16 for executing a C-FIND query
17 It will print the list of patient name found
18
19 Usage:
20
21   python FindAllPatientName.py
22
23 """
24
25 import gdcm
26
27 # Patient Name
28 tag = gdcm.Tag(0x10,0x10)
29 de = gdcm.DataElement(tag)
30
31 # Search all patient name where string match 'F*'
32 de.SetByteValue('F*',gdcm.VL(2))
33
34 ds = gdcm.DataSet()
35 ds.Insert(de)
36
37 cnf = gdcm.CompositeNetworkFunctions()
38 theQuery = cnf.ConstructQuery(gdcm.ePatientRootType,gdcm.ePatient,ds)
39
40 #print theQuery.ValidateQuery()
41
42 # prepare the variable for output
43 ret = gdcm.DataSetArrayType()
44
45 # Execute the C-FIND query
46 cnf.CFind('dicom.example.com',11112,theQuery,ret,'GDCM_PYTHON','ANY-SCP')
47
48 for i in range(0,ret.size()):
49     print "Patient #",i
50     print ret[i]

```

27.52 FixBrokenJ2K.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

```

```

=====*/
#include "gdcmReader.h"
#include "gdcmWriter.h"
#include "gdcmImageReader.h"
#include "gdcmSequenceOfFragments.h"
#include "gdcmFile.h"

// http://www.lost.in.ua/dicom/c.dcm
//
// -> BuggyJ2Kvuvua-fixed2-j2k.dcm

/*
 * This program attempts to fix a broken J2K/DICOM:
 * It contains 2 bugs:
 * 1. The first 8 bytes seems to be random bytes: remove them
 * 2. YCC is set to 1, while image is grayscale need to set it back to 0
 *
 * Ref:
 * It's a software from http://rentgenprom.ru/ , shipped with universal digital radiographic units
 * "ProScan-2000". The Ukrainian manufacturer developed own digital radiographic unit and it is
 * compatible with software from "ProScan-2000".
 */
int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];
    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        return 1;
    }

    gdcm::File &file = reader.GetFile();
    const gdcm::DataElement &pixeldata0 = file.GetDataSet().
        GetDataElement( gdcm::Tag(0x7fe0,0x0010) );
    const gdcm::SequenceOfFragments *sqf = pixeldata0.
        GetSequenceOfFragments();
    if( !sqf )
    {
        return 1;
    }
    const gdcm::Fragment &frag0 = sqf->GetFragment(0);

    const gdcm::ByteValue *bv = frag0.GetByteValue();
    const char *ptr = bv->GetPointer();
    size_t len = bv->GetLength();

    const char sig[] = "\x00\x00\x00\x00\x6A\x70\x32\x63";
    if( memcmp(ptr, sig, sizeof(sig)) != 0 )
    {
        std::cerr << "magic random signature not found" << std::endl;
        return 1;
    }

    // Apparently the flag to enable a color transform on 3 color components is set in
    // the COD marker. (YCC is byte[6] in the COD marker)
    // we need to disable this flag;
    const char *cod_marker = ptr + 0x35; /* 0x2d + 0x8 */ // FIXME
    if( cod_marker[0] == (char)0xff && cod_marker[1] == 0x52 )
    {
        // found start of COD
        if( cod_marker[6+2] == 1 )
        {
            // Change in place:
            *((char*)cod_marker + 6+2) = 0;
            // Prepare a new DataElement:
            gdcm::DataElement pixeldata( gdcm::Tag(0x7fe0,0x0010) );
            pixeldata.SetVR( gdcm::VR::OB );
            gdcm::SmartPointer<gdcm::SequenceOfFragments> sq = new
                gdcm::SequenceOfFragments;

            gdcm::Fragment frag;
            // remove 8 first bytes:
            frag.SetByteValue( ptr + 8, (uint32_t)(len - 8) );

```

```

        sq->AddFragment( frag );
        pixeldata.SetValue( *sq );
        file.GetDataSet().Replace( pixeldata );
    }
    else
    {
        return 1;
    }
}
else
{
    std::cerr << "COD not found" << (int)cod_marker[0] << std::endl;
    return 1;
}

gdcm::Writer writer;
writer.SetFile( reader.GetFile() );
writer.SetFileName( outfilename );
writer.CheckFileMetaInformationOff();
if( !writer.Write() )
{
    std::cerr << "Could not write" << std::endl;
}

// paranoid check:
gdcm::ImageReader ireader;
ireader.SetFileName( outfilename );
if( !ireader.Read() )
{
    std::cerr << "file written is still not valid, please report" << std::endl;
    return 1;
}

return 0;
}

```

27.53 FixCommaBug.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Using LC_NUMERIC set to something not compatible with "C" it is possible to write out "," instead of
17 "." as required by the DICOM standard
18 Issue is still current (IMHO) with gdcm 2.0.9
19 """
20
21 import gdcm
22 import sys
23
24 filename = sys.argv[1]
25 outname = sys.argv[2]
26
27 # read
28 r = gdcm.Reader()
29 r.SetFileName( filename )
30 if not r.Read():
31     print "not valid"
32     sys.exit(1)
33
34 file = r.GetFile()
35 dataset = file.GetDataSet()
36
37 ano = gdcm.Anonymizer()
38 ano.SetFile( file )

```



```

39
40 tags = [
41     gdcm.Tag(0x0018,0x1164),
42     gdcm.Tag(0x0018,0x0088),
43     gdcm.Tag(0x0018,0x0050),
44     gdcm.Tag(0x0028,0x0030),
45 ]
46
47 for tag in tags:
48     print tag
49     if dataset.FindElement( tag ):
50         pixelspacing = dataset.GetDataElement( tag )
51         #print pixelspacing
52         bv = pixelspacing.GetByteValue()
53         str = bv.GetBuffer()
54         #print bv.GetLength()
55         #print len(str)
56         new_str = str.replace(",",".")
57         # Need to explicitly pass bv.GetLength() to remove any trailing garbage
58         ano.Replace( tag, new_str, bv.GetLength() )
59
60 #print dataset
61
62 w = gdcm.Writer()
63 w.SetFile( file )
64 w.SetFileName( outname )
65 if not w.Write():
66     print "Cannot write"
67     sys.exit(1)
68
69 # paranoid:
70 image_reader = gdcm.ImageReader()
71 image_reader.SetFileName( outname )
72 if not image_reader.Read():
73     print "there is still a comma"
74     sys.exit(1)
75
76 print "Success!"
77 sys.exit(0) # success

```

27.54 FixJAIBugJPEGLS.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmReader.h"
#include "gdcmWriter.h"
#include "gdcmImageReader.h"

#include <fstream>

#include "gdcm_charls.h"

/*
 * This small example should show how one can handle the famous JAI-JPEGLS bug
 * It will take in as invalid DICOM/JAI-JPEG-LS and write out as Explicit Little
 * Endian. One can use 'gdcmconv --jpegls' to recompress properly
 *
 * References:
 * http://charls.codeplex.com/discussions/230307?ProjectName=charls
 * http://charls.codeplex.com/workitem/7297
 * http://www.dcm4che.org/jira/browse/DCM-442
 * http://www.dcm4che.org/jira/browse/DCMEE-1144
 * http://java.net/jira/browse/JAI_IMAGEIO_CORE-183
 *
 * Explanation of the issue:
 */

```

```

* Seems, the error is in the calculation of the default values for thresholds T1,
* T2, T3, in particular min(MAXVAL, 4095) is not applied in
*
* FACTOR = (min(MAXVAL, 4095) + 128)/256
*
* as specified in http://www.itu.int/rec/T-REC-T.87-199806-I/en .
*
*/
int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];
    gdcm::FileMetaInformation::SetSourceApplicationEntityTitle
        ( "FixJAIBugJPEGs" );

    gdcm::ImageReader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        return 1;
    }

    gdcm::Image &image = reader.GetImage();
    //unsigned long len = image.GetBufferLength();
    const gdcm::DataElement &in =
        reader.GetFile().GetDataSet().GetDataElement(
            gdcm::Tag(0x7fe0,0x0010) );
    const gdcm::SequenceOfFragments *sf = in.
        GetSequenceOfFragments();
    if( !sf )
    {
        std::cerr << "No pixel data (or not encapsulated)" << std::endl;
        return 1;
    }
    const unsigned int *dims = image.GetDimensions();
    if ( sf->GetNumberOfFragments() != dims[2] )
    {
        std::cerr << "Unsupported" << std::endl;
        return 1;
    }

    // unsigned long totalLen = sf->ComputeByteLength();
    std::vector<BYTE> rgbYTEOutall;
    for(unsigned int i = 0; i < sf->GetNumberOfFragments(); ++i)
    {
        const gdcm::Fragment &frag = sf->GetFragment(i);
        if( frag.IsEmpty() ) return 1;
        const gdcm::ByteValue *bv = frag.GetByteValue();
        if( !bv ) return 1;
        unsigned long totalLen = bv->GetLength();

        std::vector<char> vbuffer;
        vbuffer.resize( totalLen );
        char *buffer = &vbuffer[0];
        bv->GetBuffer(buffer, totalLen);
        const BYTE* pbyteCompressed0 = (const BYTE*)buffer;
        while( totalLen > 0 && pbyteCompressed0[totalLen-1] != 0xd9 )
        {
            totalLen--;
        }

        JlsParameters metadata;
        if (JpegLsReadHeader(buffer, totalLen, &metadata) != OK)
        {
            std::cerr << "Cant parse jpegls" << std::endl;
            return false;
        }

        std::cout << metadata.width << std::endl;
        std::cout << metadata.height << std::endl;
        std::cout << metadata.bitspersample << std::endl;

        gdcm::PixelFormat const &pf = image.GetPixelFormat();
        std::cout << pf << std::endl;

        // http://charls.codeplex.com/discussions/230307?ProjectName=charls

```

```

unsigned char marker_lse_13[] = {
    0xFF, 0xF8, 0x00, 0x0D,
    0x01,
    0x1F, 0xFF,
    0x00, 0x22, // T1 = 34
    0x00, 0x83, // T2 = 131
    0x02, 0x24, // T3 = 548
    0x00, 0x40
};

unsigned char marker_lse_14[] = {
    0xFF, 0xF8, 0x00, 0x0D,
    0x01,
    0x3F, 0xFF,
    0x00, 0x42, // T1 = 66
    0x01, 0x03, // T2 = 259
    0x04, 0x44, // T3 = 1092
    0x00, 0x40
};

unsigned char marker_lse_15[] = {
    0xFF, 0xF8, 0x00, 0x0D,
    0x01,
    0x7F, 0xFF,
    0x00, 0x82, // T1 = 130
    0x02, 0x03, // T2 = 515
    0x08, 0x84, // T3 = 2180
    0x00, 0x40
};

unsigned char marker_lse_16[] = {
    0xFF, 0xF8, 0x00, 0x0D,
    0x01,
    0xFF, 0xFF,
    0x01, 0x02, // T1 = 258
    0x04, 0x03, // T2 = 1027
    0x11, 0x04, // T3 = 4356
    0x00, 0x40
};

const unsigned char *marker_lse = NULL;
switch( metadata.bitspersample )
{
case 13:
    marker_lse = marker_lse_13;
    break;
case 14:
    marker_lse = marker_lse_14;
    break;
case 15:
    marker_lse = marker_lse_15;
    break;
case 16:
    marker_lse = marker_lse_16;
    break;
}
if( !marker_lse )
{
    std::cerr << "Cant handle: " << metadata.bitspersample << std::endl;
    return 1;
}

// FIXME: One should recompute the value for 0x0F
vbuffer.insert( vbuffer.begin() + 0x0F, marker_lse, marker_lse+15);

#if 0
std::ofstream of( "tmp/d.jls" );
of.write( &vbuffer[0], vbuffer.size() );
of.close();
#endif

const char *pbyteCompressed = &vbuffer[0];
size_t cbyteCompressed = vbuffer.size(); // updated legnth

JlsParameters params;
JpegLsReadHeader( pbyteCompressed, cbyteCompressed, &params);

std::vector<BYTE> rgbyteOut;
//rgbyteOut.resize( image.GetBufferLength() );
rgbyteOut.resize( params.height * params.width * ((params.bitspersample + 7)
    / 8) * params.components);

```

```

JLS_ERROR result =
    JpegLsDecode(&rgbyteOut[0], rgbyteOut.size(), pbyteCompressed, cbyteCompressed, &params );
if (result != OK)
{
    std::cerr << "Could not patch JAI-JPEGLS" << std::endl;
    return 1;
}
rgbyteOutall.insert( rgbyteOutall.end(), rgbyteOut.begin(), rgbyteOut.end() );
}

gdcm::DataElement pixeldata( gdcm::Tag(0x7fe0,0x0010) );
pixeldata.SetVR( gdcm::VR::OW );
pixeldata.SetByteValue( (char*)&rgbyteOutall[0], (uint32_t)rgbyteOutall.size() );

// Add the pixel data element
reader.GetFile().GetDataSet().Replace( pixeldata );
reader.GetFile().GetHeader().SetDataSetTransferSyntax(
    gdcm::TransferSyntax::ExplicitVRLittleEndian);

gdcm::Writer writer;
writer.SetFileName( outfilename );
writer.SetFile( reader.GetFile() );
writer.Write();

std::cout << "Success !" << std::endl;

return 0;
}

```

27.55 gdcmorthoplanes.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

#include "vtkActor.h"
#include "vtkCamera.h"
#include "vtkMatrix4x4.h"
#include "vtkTransform.h"
#include "vtkAssembly.h"
#include "vtkCellPicker.h"
#include "vtkCommand.h"
#include "vtkImageActor.h"
#include "vtkImageMapToColors.h"
#include "vtkImageOrthoPlanes.h"
#include "vtkImagePlaneWidget.h"
#include "vtkImageReader.h"
#include "vtkInteractorEventRecorder.h"
#include "vtkLookupTable.h"
#include "vtkOutlineFilter.h"
#include "vtkPolyDataMapper.h"
#include "vtkProperty.h"
#include "vtkRenderWindow.h"
#include "vtkRenderWindowInteractor.h"
#include "vtkRenderer.h"
#include "vtkVolume16Reader.h"
#include "vtkImageData.h"
#include "vtkImageChangeInformation.h"
#include "vtkOrientationMarkerWidget.h"
#include "vtkAnnotatedCubeActor.h"
#include "vtkAxesActor.h"
#include "vtkCaptionActor2D.h"
#include "vtkTextProperty.h"
#include "vtkPropAssembly.h"

```

```

#include "vtkGDCMImageReader.h"
#include "vtkGDCMImageWriter.h"
#include "vtkStringArray.h"

#include "gdcmSystem.h"
#include "gdcmDirectory.h"
#include "gdcmIPPSorter.h"

#ifdef vtkFloatingPointType
#define vtkFloatingPointType float
#endif

//-----
class vtkOrthoPlanesCallback : public vtkCommand
{
public:
    static vtkOrthoPlanesCallback *New()
    { return new vtkOrthoPlanesCallback; }

    void Execute( vtkObject *caller, unsigned long vtkNotUsed( event ),
                 void *callData )
    {
        vtkImagePlaneWidget* self =
            reinterpret_cast< vtkImagePlaneWidget* >( caller );
        if(!self) return;

        double* wl = static_cast<double*>( callData );

        if ( self == this->WidgetX )
        {
            this->WidgetY->SetWindowLevel(wl[0],wl[1],1);
            this->WidgetZ->SetWindowLevel(wl[0],wl[1],1);
        }
        else if( self == this->WidgetY )
        {
            this->WidgetX->SetWindowLevel(wl[0],wl[1],1);
            this->WidgetZ->SetWindowLevel(wl[0],wl[1],1);
        }
        else if (self == this->WidgetZ)
        {
            this->WidgetX->SetWindowLevel(wl[0],wl[1],1);
            this->WidgetY->SetWindowLevel(wl[0],wl[1],1);
        }
    }

    vtkOrthoPlanesCallback():WidgetX( 0 ), WidgetY( 0 ), WidgetZ ( 0 ) {}

    vtkImagePlaneWidget* WidgetX;
    vtkImagePlaneWidget* WidgetY;
    vtkImagePlaneWidget* WidgetZ;
};

int main( int argc, char *argv[] )
{
    //char* fname = vtkTestUtilities::ExpandDataFileName(argc, argv, "Data/headsq/quarter");

    //vtkVolume16Reader* v16 = vtkVolume16Reader::New();
    // v16->SetDataDimensions( 64, 64);
    // v16->SetDataByteOrderToLittleEndian();
    // v16->SetImageRange( 1, 93);
    // v16->SetDataSpacing( 3.2, 3.2, 1.5);
    // v16->SetFilePrefix( fname );
    // v16->SetDataMask( 0x7fff);
    // v16->Update();
    std::vector<std::string> filenames;
    if( argc < 2 )
    {
        std::cerr << argv[0] << " filename1.dcm [filename2.dcm ...]\n";
        return 1;
    }
    else
    {
        // Is it a single directory ? If so loop over all files contained in it:
        const char *filename = argv[1];
        if( argc == 2 && gdcm::System::FileIsDirectory( filename ) )
        {
            std::cout << "Loading directory: " << filename << std::endl;
            bool recursive = false;
            gdcm::Directory d;
            d.Load(filename, recursive);
            gdcm::Directory::FileNamesType const &files = d.

```

```

    GetFileNames();
    for( gdcmm::Directory::FileNamesType::const_iterator it = files.begin(); it != files.end(); ++it )
    {
        filenames.push_back( it->c_str() );
    }
}
else // list of files passed directly on the cmd line:
    // discard non-existing or directory
    {
        for(int i=1; i < argc; ++i)
        {
            filename = argv[i];
            if( gdcmm::System::FileExists( filename ) )
            {
                if( gdcmm::System::FileIsDirectory( filename ) )
                {
                    std::cerr << "Discarding directory: " << filename << std::endl;
                }
                else
                {
                    filenames.push_back( filename );
                }
            }
            else
            {
                std::cerr << "Discarding non existing file: " << filename << std::endl;
            }
        }
    }
//names->Print( std::cout );
}

vtkGDCMImageReader * reader = vtkGDCMImageReader::New();
double ippzspacing;
if( filenames.size() > 1 )
{
    //gdcmm::Trace::DebugOn();
    //gdcmm::Trace::WarningOn();
    gdcmm::IPPSorter s;
    s.SetComputeZSpacing( true );
    s.SetZSpacingTolerance( 1e-3 );
    bool b = s.Sort( filenames );
    if( !b )
    {
        std::cerr << "Failed to sort files" << std::endl;
        return 1;
    }
    std::cout << "Sorting succeeded:" << std::endl;
    s.Print( std::cout );

    std::cout << "Found z-spacing:" << std::endl;
    std::cout << s.GetZSpacing() << std::endl;
    ippzspacing = s.GetZSpacing();

    const std::vector<std::string> & sorted = s.GetFileNames();
    vtkStringArray *files = vtkStringArray::New();
    std::vector< std::string >::const_iterator it = sorted.begin();
    for( ; it != sorted.end(); ++it )
    {
        const std::string &f = *it;
        files->InsertNextValue( f.c_str() );
    }
    reader->SetFileNames( files );
    //reader->SetFileLowerLeft( 1 );
    reader->Update(); // important
    files->Delete();
}
else
{
    reader->SetFileName( argv[1] );
    reader->Update(); // important
    ippzspacing = reader->GetOutput()->GetSpacing()[2];
    ippzspacing = 4;
}

//reader->GetOutput()->Print( std::cout );
//vtkFloatingPointType range[2];
//reader->GetOutput()->GetScalarRange(range);
//std::cout << "Range: " << range[0] << " " << range[1] << std::endl;

const vtkFloatingPointType *spacing = reader->GetOutput()->GetSpacing();

```

```

vtkImageChangeInformation *v16 = vtkImageChangeInformation::New();
v16->SetInput( reader->GetOutput() );
v16->SetOutputSpacing( spacing[0], spacing[1], ippszspacing );
v16->Update();

#ifdef 0
    vtkGDCMImageWriter *writer = vtkGDCMImageWriter::New();
    writer->SetInput( v16->GetOutput() );
    writer->SetFileLowerLeft( reader->GetFileLowerLeft() );
    writer->SetDirectionCosines( reader->GetDirectionCosines() );
    writer->SetImageFormat( reader->GetImageFormat() );
    writer->SetFileDimensionality( 3); //reader->GetFileDimensionality() );
    writer->SetMedicalImageProperties( reader->GetMedicalImageProperties() );
    writer->SetShift( reader->GetShift() );
    writer->SetScale( reader->GetScale() );
    writer->SetFileName( "out.dcm" );
    writer->Write();
#endif

    vtkOutlineFilter* outline = vtkOutlineFilter::New();
    outline->SetInputConnection(v16->GetOutputPort());

    vtkPolyDataMapper* outlineMapper = vtkPolyDataMapper::New();
    outlineMapper->SetInputConnection(outline->GetOutputPort());

    vtkActor* outlineActor = vtkActor::New();
    outlineActor->SetMapper( outlineMapper);

    vtkRenderer* ren1 = vtkRenderer::New();
    vtkRenderer* ren2 = vtkRenderer::New();

    vtkRenderWindow* renWin = vtkRenderWindow::New();
    renWin->AddRenderer(ren2);
    renWin->AddRenderer(ren1);

    vtkRenderWindowInteractor* iren = vtkRenderWindowInteractor::New();
    iren->SetRenderWindow(renWin);

    vtkCellPicker* picker = vtkCellPicker::New();
    picker->SetTolerance(0.005);

    vtkProperty* ipwProp = vtkProperty::New();
    //assign default props to the ipw's texture plane actor

    vtkImagePlaneWidget* planeWidgetX = vtkImagePlaneWidget::New();
    planeWidgetX->SetInteractor( iren);
    planeWidgetX->SetKeyPressActivationValue('x');
    planeWidgetX->SetPicker(picker);
    planeWidgetX->RestrictPlaneToVolumeOn();
    planeWidgetX->GetPlaneProperty()->SetColor(1,0,0);
    planeWidgetX->SetTexturePlaneProperty(ipwProp);
    planeWidgetX->TextureInterpolateOff();
    planeWidgetX->SetResliceInterpolateToNearestNeighbour();
    planeWidgetX->SetInput(v16->GetOutput());
    planeWidgetX->SetPlaneOrientationToXAxes();
    //planeWidgetX->SetSliceIndex(32);
    planeWidgetX->DisplayTextOn();
    planeWidgetX->On();
    planeWidgetX->InteractionOff();
    planeWidgetX->InteractionOn();

    vtkImagePlaneWidget* planeWidgetY = vtkImagePlaneWidget::New();
    planeWidgetY->SetInteractor( iren);
    planeWidgetY->SetKeyPressActivationValue('y');
    planeWidgetY->SetPicker(picker);
    planeWidgetY->GetPlaneProperty()->SetColor(1,1,0);
    planeWidgetY->SetTexturePlaneProperty(ipwProp);
    planeWidgetY->TextureInterpolateOn();
    planeWidgetY->SetResliceInterpolateToLinear();
    planeWidgetY->SetInput(v16->GetOutput());
    planeWidgetY->SetPlaneOrientationToYAxes();
    //planeWidgetY->SetSlicePosition(102.4);
    planeWidgetY->SetLookupTable( planeWidgetX->GetLookupTable());
    planeWidgetY->DisplayTextOn();
    planeWidgetY->UpdatePlacement();
    planeWidgetY->On();

    vtkImagePlaneWidget* planeWidgetZ = vtkImagePlaneWidget::New();
    planeWidgetZ->SetInteractor( iren);

```

```

planeWidgetZ->SetKeyPressActivationValue('z');
planeWidgetZ->SetPicker(picker);
planeWidgetZ->GetPlaneProperty()->SetColor(0,0,1);
planeWidgetZ->SetTexturePlaneProperty(ipwProp);
planeWidgetZ->TextureInterpolateOn();
planeWidgetZ->SetResliceInterpolateToCubic();
planeWidgetZ->SetInput(vl6->GetOutput());
planeWidgetZ->SetPlaneOrientationToZAxes();
//planeWidgetZ->SetSliceIndex(25);
planeWidgetZ->SetLookupTable(planeWidgetX->GetLookupTable());
planeWidgetZ->DisplayTextOn();
planeWidgetZ->On();

vtkImageOrthoPlanes *orthoPlanes = vtkImageOrthoPlanes::New();
orthoPlanes->SetPlane(0, planeWidgetX);
orthoPlanes->SetPlane(1, planeWidgetY);
orthoPlanes->SetPlane(2, planeWidgetZ);
orthoPlanes->ResetPlanes();

vtkOrthoPlanesCallback* cbk = vtkOrthoPlanesCallback::New();
cbk->WidgetX = planeWidgetX;
cbk->WidgetY = planeWidgetY;
cbk->WidgetZ = planeWidgetZ;
planeWidgetX->AddObserver(vtkCommand::EndWindowLevelEvent, cbk);
planeWidgetY->AddObserver(vtkCommand::EndWindowLevelEvent, cbk);
planeWidgetZ->AddObserver(vtkCommand::EndWindowLevelEvent, cbk);
cbk->Delete();

double wl[2];
planeWidgetZ->GetWindowLevel(wl);

// Add a 2D image to test the GetReslice method
//
vtkImageMapToColors* colorMap = vtkImageMapToColors::New();
colorMap->PassAlphaToOutputOff();
colorMap->SetActiveComponent(0);
colorMap->SetOutputFormatToLuminance();
colorMap->SetInput(planeWidgetZ->GetResliceOutput());
colorMap->SetLookupTable(planeWidgetX->GetLookupTable());

vtkImageActor* imageActor = vtkImageActor::New();
imageActor->PickableOff();
imageActor->SetInput(colorMap->GetOutput());

// Add the actors
//
ren1->AddActor(outlineActor);
ren2->AddActor(imageActor);

ren1->SetBackground(0.1, 0.1, 0.2);
ren2->SetBackground(0.2, 0.1, 0.2);

renWin->SetSize(600, 350);

ren1->SetViewport(0,0,0.58333,1);
ren2->SetViewport(0.58333,0,1,1);

// Set the actors' postions
//
renWin->Render();
//iren->SetEventPosition(175,175);
//iren->SetKeyCode('r');
//iren->InvokeEvent(vtkCommand::CharEvent, NULL);
//iren->SetEventPosition(475,175);
//iren->SetKeyCode('r');
//iren->InvokeEvent(vtkCommand::CharEvent, NULL);
//renWin->Render();

//ren1->GetActiveCamera()->Elevation(110);
//ren1->GetActiveCamera()->SetViewUp(0, 0, -1);
//ren1->GetActiveCamera()->Azimuth(45);
//ren1->GetActiveCamera()->Dolly(1.15);
ren1->ResetCameraClippingRange();

vtkAnnotatedCubeActor* cube = vtkAnnotatedCubeActor::New();
cube->SetXPlusFaceText("R");
cube->SetXMinusFaceText("L");
cube->SetYPlusFaceText("A");
cube->SetYMinusFaceText("P");
cube->SetZPlusFaceText("H");
cube->SetZMinusFaceText("F");

```



```

cube->SetFaceTextScale( 0.666667 );

vtkAxesActor* axes2 = vtkAxesActor::New();

vtkMatrix4x4 *invert = vtkMatrix4x4::New();
invert->DeepCopy( reader->GetDirectionCosines() );
invert->Invert();

// simulate a left-handed coordinate system
//
vtkTransform *transform = vtkTransform::New();
transform->Identity();
//transform->RotateY(90);
transform->Concatenate(invert);
axes2->SetShaftTypeToCylinder();
axes2->SetUserTransform( transform );
cube->GetAssembly()->SetUserTransform( transform );

axes2->SetTotalLength( 1.5, 1.5, 1.5 );
axes2->SetCylinderRadius( 0.500 * axes2->GetCylinderRadius() );
axes2->SetConeRadius( 1.025 * axes2->GetConeRadius() );
axes2->SetSphereRadius( 1.500 * axes2->GetSphereRadius() );

vtkTextProperty* tprop = axes2->GetXAxisCaptionActor2D()->
    GetCaptionTextProperty();
tprop->ItalicOn();
tprop->ShadowOn();
tprop->SetFontFamilyToTimes();

axes2->GetYAxisCaptionActor2D()->GetCaptionTextProperty()->ShallowCopy( tprop );
axes2->GetZAxisCaptionActor2D()->GetCaptionTextProperty()->ShallowCopy( tprop );

vtkPropAssembly* assembly = vtkPropAssembly::New();
assembly->AddPart( axes2 );
assembly->AddPart( cube );

vtkOrientationMarkerWidget* widget = vtkOrientationMarkerWidget::New();
widget->SetOutlineColor( 0.9300, 0.5700, 0.1300 );
widget->SetOrientationMarker( assembly );
widget->SetInteractor( iren );
widget->SetViewport( 0.0, 0.0, 0.4, 0.4 );
widget->SetEnabled( 1 );
widget->InteractiveOff();
widget->InteractiveOn();

// Playback recorded events
//
//vtkInteractorEventRecorder *recorder = vtkInteractorEventRecorder::New();
//recorder->SetInteractor(iren);
//recorder->ReadFromInputStringOn();
//recorder->SetInputString( IOEventLog );

// Interact with data
// Render the image
//
iren->Initialize();
renWin->Render();

// Test SetKeyPressActivationValue for one of the widgets
//
//iren->SetKeyCode('z');
//iren->InvokeEvent(vtkCommand::CharEvent,NULL);
//iren->SetKeyCode('z');
//iren->InvokeEvent(vtkCommand::CharEvent,NULL);

//int retVal = vtkRegressionTestImage( renWin );
//
//if ( retVal == vtkRegressionTester::DO_INTERACTOR )
//{
//    iren->Start();
//}

// Clean up
//
//recorder->Off();
//recorder->Delete();

ipwProp->Delete();
orthoPlanes->Delete();
planeWidgetX->Delete();
planeWidgetY->Delete();

```

```

planeWidgetZ->Delete();
colorMap->Delete();
imageActor->Delete();
picker->Delete();
outlineActor->Delete();
outlineMapper->Delete();
outline->Delete();
iren->Delete();
renWin->Delete();
ren1->Delete();
ren2->Delete();
v16->Delete();
reader->Delete();

return 0;
}

```

27.56 gdcmmreslice.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkGDCMImageReader.h"

#include "vtkRenderer.h"
#include "vtkAssembly.h"
#include "vtkImageFlip.h"
#include "vtkImageReslice.h"
#include "vtkRenderWindow.h"
#include "vtkAnnotatedCubeActor.h"
#include "vtkTransform.h"
#include "vtkAxesActor.h"
#include "vtkTextProperty.h"
#include "vtkCaptionActor2D.h"
#include "vtkPropAssembly.h"
#include "vtkOrientationMarkerWidget.h"
#include "vtkRenderWindowInteractor.h"
#include "vtkPolyDataMapper.h"
#include "vtkActor.h"
#include "vtkImageData.h"
#include "vtkLookupTable.h"
#include "vtkTexture.h"
#include "vtkPlaneSource.h"

int main( int argc, char *argv[] )
{
    if( argc < 2 ) return 1;
    vtkGDCMImageReader *reader = vtkGDCMImageReader::New();
    reader->SetFileName( argv[1] );
    //reader->FileLowerLeftOn();
    reader->Update();

    vtkImageFlip *flip = vtkImageFlip::New();
    flip->SetInput( reader->GetOutput() );
    flip->SetFilteredAxis(0);
    flip->Update();

    vtkImageReslice *reslice = vtkImageReslice::New();
    //reslice->SetInput( reader->GetOutput() );
    reslice->SetInput( flip->GetOutput() );
    //reslice->SetResliceAxesDirectionCosines()
    reader->GetDirectionCosines()->Print( std::cout );
    vtkMatrix4x4 *invert = vtkMatrix4x4::New();
    invert->DeepCopy( reader->GetDirectionCosines() );
    invert->Invert();

    //reslice->SetResliceAxes( reader->GetDirectionCosines() );
}

```

```

reslice->SetResliceAxes( invert );
reslice->Update();
vtkImageData* ima = reslice->GetOutput();

vtkLookupTable* table = vtkLookupTable::New();
table->SetNumberOfColors(1000);
table->SetTableRange(0,1000);
table->SetSaturationRange(0,0);
table->SetHueRange(0,1);
table->SetValueRange(0,1);
table->SetAlphaRange(1,1);
table->Build();

// Texture
vtkTexture* texture = vtkTexture::New();
texture->SetInput(ima);
texture->InterpolateOn();
texture->SetLookupTable(table);

// PlaneSource
vtkPlaneSource* plane = vtkPlaneSource::New();

// PolyDataMapper
vtkPolyDataMapper *planeMapper = vtkPolyDataMapper::New();
planeMapper->SetInput(plane->GetOutput());

// Actor
vtkActor* planeActor = vtkActor::New();
planeActor->SetTexture(texture);
planeActor->SetMapper(planeMapper);
planeActor->PickableOn();

// Final rendering with simple interactor:
vtkRenderer *ren = vtkRenderer::New();
vtkRenderWindow *renwin = vtkRenderWindow::New();
renwin->AddRenderer(ren);
vtkRenderWindowInteractor *iren = vtkRenderWindowInteractor::New();
iren->SetRenderWindow(renwin);
ren->AddActor(planeActor);
ren->SetBackground(0,0,0.5);

// DICOM is RAH:
vtkAnnotatedCubeActor* cube = vtkAnnotatedCubeActor::New();
cube->SetXPlusFaceText ( "R" );
cube->SetXMinusFaceText ( "L" );
cube->SetYPlusFaceText ( "A" );
cube->SetYMinusFaceText ( "P" );
cube->SetZPlusFaceText ( "H" );
cube->SetZMinusFaceText ( "F" );

vtkAxesActor* axes2 = vtkAxesActor::New();

vtkTransform *transform = vtkTransform::New();
transform->Identity();
//reader->GetDirectionCosines()->Print(std::cout);
transform->Concatenate(invert);
//axes2->SetShaftTypeToCylinder();
axes2->SetUserTransform( transform );
cube->GetAssembly()->SetUserTransform( transform ); // cant get it to work

vtkPropAssembly* assembly = vtkPropAssembly::New();
assembly->AddPart( axes2 );
assembly->AddPart( cube );

vtkOrientationMarkerWidget* widget = vtkOrientationMarkerWidget::New();
widget->SetOrientationMarker( assembly );
widget->SetInteractor( iren );
widget->SetEnabled( 1 );
widget->InteractiveOff();
widget->InteractiveOn();

renwin->Render();
iren->Start();

// Clean up:
reader->Delete();
table->Delete();
texture->Delete();
plane->Delete();
planeMapper->Delete();
planeActor->Delete();

```

```

ren->Delete();
renwin->Delete();
iren->Delete();

return 0;
}

```

27.57 gdcmrtnplan.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcms.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkImageData.h"
#include "vtkPointData.h"
#include "vtkPolyData.h"
#include "vtkProperty.h"
#include "vtkPolyDataMapper.h"
#include "vtkActor.h"
#include "vtkRenderer.h"
#include "vtkCellArray.h"
#include "vtkPoints.h"
#include "vtkDoubleArray.h"
#include <vtkXMLImageDataWriter.h>
#include <vtkXMLPolyDataWriter.h>
#include <vtkRenderWindowInteractor.h>
#include <vtkImageColorViewer.h>

#include "gdcmReader.h"
#include "gdcmAttribute.h"

/*
This example is just for fun. We found a RT Ion Plan Storage and simply extracted the viz stuff for VTK

RTIonPlanStorage, // 1.2.840.10008.5.1.4.1.1.481.8
*/
int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " filename.dcm outfile.vti\n";
        return 1;
    }
    const char * filename = argv[1];
    const char * outfilename = argv[2];
    const char * outfilename2 = argv[3];

    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        return 1;
    }

    gdcm::MediaStorage ms;
    ms.SetFromFile( reader.GetFile() );
    if( ms != gdcm::MediaStorage::RTIonPlanStorage )
    {
        return 1;
    }

    /*
(300a,03a2) SQ # u/1,1 Ion Beam Sequence
(ffff,e000) na (Item with undefined length)
(0008,1040) LO [Test] # 4,1 Institutional Department Name
(300a,00b2) SH (no value) # 0,1 Treatment Machine Name
(300a,00b3) CS [MU] # 2,1 Primary Dosimeter Unit
(300a,00c0) IS [1 1] # 2,1 Beam Number
    */
}

```

```

(300a,00c2) LO [1 ] # 2,1 Beam Name
(300a,00c4) CS [STATIC] # 6,1 Beam Type
(300a,00c6) CS [PROTON] # 6,1 Radiation Type
(300a,00ce) CS [TREATMENT ] # 10,1 Treatment Delivery Type
(300a,00d0) IS [0 ] # 2,1 Number of Wedges
(300a,00e0) IS [1 ] # 2,1 Number of Compensators
(300a,00ed) IS [0 ] # 2,1 Number of Boli
(300a,00f0) IS [1 ] # 2,1 Number of Blocks
(300a,0110) IS [2 ] # 2,1 Number of Control Points
(300a,02ea) SQ # u/l,1 Ion Range Compensator Sequence
    (fffe,e000) na (Item with undefined length)
        (300a,00e1) SH [lucite] # 6,1 Material ID
        (300a,00e4) IS [1 ] # 2,1 Compensator Number
        (300a,00e5) SH [75hdhe5 ] # 8,1 Compensator ID
        (300a,00e7) IS [35] # 2,1 Compensator Rows
        (300a,00e8) IS [37] # 2,1 Compensator Columns
        (300a,00e9) DS [3.679991\4.249288 ] # 18,2 Compensator Pixel Spacing
        (300a,00ea) DS [-76.00\62.50] # 12,2 Compensator Position
        (300a,00ec) DS
[52.13\52.13\52.13\53.18\54.04\54.04\47.11\40.06\40.06\38.79\34.87\33.28\33.28\33.28\
33.28\35.43\35.43\34.54\34.54\34.71\36.10\38.62\44.88\44.88\44.88\45.00\45.00\45.00\45.66\45.66\46.42\39.77\39.77\39.77\39.77\3
Data
(300a,02e0) CS [ABSENT] # 6,1 Compensator Divergence
(300a,02e1) CS [SOURCE_SIDE ] # 12,1 Compensator Mounting Position
(300a,02e4) FL 39.2 # 4,1 Isocenter to Compensator Tray
Distance
(300a,02e5) FL 2.12 # 4,1 Compensator Column Offset
(300a,02e8) FL 4.76 # 4,1 Compensator Milling Tool Diameter
(fffe,e00d)
*/
const gdcmm::DataSet& ds = reader.GetFile().GetDataSet();
gdcmm::Tag tbeamsq(0x300a,0x03a2);
if( !ds.FindDataElement( tbeamsq ) )
{
return 1;
}
const gdcmm::DataElement &tbeamsq = ds.GetDataElement( tbeamsq );
//std::cout << beamsq << std::endl;
gdcmm::SmartPointer<gdcmm::SequenceOfItems> sqi = beamsq.
GetValueAsSQ();
if( !sqi || !sqi->GetNumberOfItems() )
{
return 1;
}

//for(unsigned int pd = 0; pd < sqi->GetNumberOfItems(); ++pd)
// {
//const gdcmm::Item &item = sqi->GetItem(1); // Item start at #1
const gdcmm::Item &item = sqi->GetItem(1); // Item start at #1
const gdcmm::DataSet& nestedds = item.GetNestedDataSet();
//std::cout << nestedds << std::endl;
gdcmm::Tag tcompensatorsq(0x300a,0x02ea);
if( !nestedds.FindDataElement( tcompensatorsq ) )
{
return 1;
}
const gdcmm::DataElement &compensatorsq = nestedds.
GetDataElement( tcompensatorsq );
//std::cout << compensatorsq << std::endl;
gdcmm::SmartPointer<gdcmm::SequenceOfItems> ssqi = compensatorsq
.GetValueAsSQ();
const gdcmm::Item &item2 = ssqi->GetItem(1); // Item start at #1
const gdcmm::DataSet& nestedds2 = item2.GetNestedDataSet();
//std::cout << nestedds2 << std::endl;
gdcmm::Tag tcompensatorthicknessdata(0x300a,0x00ec);
if( !nestedds2.FindDataElement( tcompensatorthicknessdata ) )
{
return 1;
}
const gdcmm::DataElement &compensatorthicknessdata = nestedds2.
GetDataElement( tcompensatorthicknessdata );
// std::cout << compensatorthicknessdata << std::endl;
gdcmm::Attribute<0x300a,0x00ec> at;
at.SetFromDataElement( compensatorthicknessdata );
const double* pts = at.GetValues();
// (300a,00e7) IS [35] # 2,1 Compensator Rows
gdcmm::Attribute<0x300a,0x00e7> atl;
const gdcmm::DataElement &compensatorrows = nestedds2.
GetDataElement( atl.GetTag() );
atl.SetFromDataElement( compensatorrows );
std::cout << atl.GetValue() << std::endl;

```

```

// (300a,00e8) IS [37] # 2,1 Compensator Columns
gdcm::Attribute<0x300a,0x00e8> at2;
const gdcm::DataElement &compensatorcols = nestedds2.
  GetDataElement( at2.GetTag() );
at2.SetFromDataElement( compensatorcols );
std::cout << at2.GetValue() << std::endl;

// (300a,00e9) DS [3.679991\4.249288 ] # 18,2 Compensator Pixel Spacing
gdcm::Attribute<0x300a,0x00e9> at3;
const gdcm::DataElement &compensatorpixelspacing = nestedds2.
  GetDataElement( at3.GetTag() );
at3.SetFromDataElement( compensatorpixelspacing );
std::cout << at3.GetValue(0) << std::endl;
// (300a,00ea) DS [-76.00\62.50] # 12,2 Compensator Position
gdcm::Attribute<0x300a,0x00ea> at4;
const gdcm::DataElement &compensatorposition = nestedds2.
  GetDataElement( at4.GetTag() );
at4.SetFromDataElement( compensatorposition );
std::cout << at4.GetValue(0) << std::endl;

vtkDoubleArray *d = vtkDoubleArray::New();
d->SetArray( (double*)pts , at1.GetValue() * at2.GetValue() , 0 );

vtkImageData *img = vtkImageData::New();
img->Initialize();
img->SetDimensions( at2.GetValue(), at1.GetValue(), 1 );
//imgb->SetExtent(1, xdim, 1, ydim, 1, zdim);
img->SetScalarTypeToDouble();
img->SetSpacing( at3.GetValue(1), at3.GetValue(0), 1); // FIXME image is upside down
img->SetOrigin( at4.GetValue(0), at4.GetValue(1), 1);
img->SetNumberOfScalarComponents(1);
img->GetPointData()->SetScalars(d);

img->Update();
img->Print(std::cout);

vtkXMLImageDataWriter *writeb= vtkXMLImageDataWriter::New();
writeb->SetInput( img );
writeb->SetFileName( outfilename );
writeb->Write( );

/*
(300a,03a6) SQ # u/l,1 Ion Block Sequence
  (fffe,e000) na (Item with undefined length)
    (300a,00e1) SH [brass ] # 6,1 Material ID
    (300a,00f7) FL 95.03 # 4,1 Isocenter to Block Tray Distance
    (300a,00f8) CS [APERTURE] # 8,1 Block Type
    (300a,00fa) CS [ABSENT] # 6,1 Block Divergence
    (300a,00fb) CS [SOURCE_SIDE ] # 12,1 Block Mounting Position
    (300a,00fc) IS [1 ] # 2,1 Block Number
    (300a,0100) DS [50.00 ] # 6,1 Block Thickness
    (300a,0104) IS [179 ] # 4,1 Block Number of Points
    (300a,0106) DS
      [1.7\50.0\14.3\50.0\16.7\49.4\18.7\48.2\19.4\47.7\20.1\47.1\21.0\47.0\22.3\47.0\23.7\
46.8\25.7\46.2\27.0\45.6\27.2\45.4\28.2\44.6\28.9\44.2\29.7\43.9\31.5\43.5\33.0\42.8\33.7\42.4\35.2\41.3\38.2\40.4\39.6\39.7\40.
2\37.4\43.0\37.1\44.7\36] # 1934,2-2n Block Data
    (fffe,e00d)
    (fffe,e0dd)

*/
gdcm::Tag tblocksq(0x300a,0x03a6);
if( !nestedds.FindDataElement( tblocksq ) )
{
  return 1;
}
const gdcm::DataElement &tblocksq = nestedds.GetDataElement( tblocksq );
//std::cout << tblocksq << std::endl;
gdcm::SmartPointer<gdcm::SequenceOfItems> sssqi = tblocksq.
  GetValueAsSQ();
const gdcm::Item &item3 = sssqi->GetItem(1); // Item start at #1
const gdcm::DataSet& nestedds3 = item3.GetNestedDataSet();

gdcm::Tag tblockdata(0x300a,0x0106);
if( !nestedds3.FindDataElement( tblockdata ) )
{
  return 1;
}
const gdcm::DataElement &tblockdata = nestedds3.
  GetDataElement( tblockdata );
// std::cout << tblockdata << std::endl;
gdcm::Attribute<0x300a,0x0106> at_;
at_.SetFromDataElement( tblockdata );

```

```

vtkDoubleArray *scalars = vtkDoubleArray::New();
scalars->SetNumberOfComponents(3);

gdcmm::Attribute<0x300a,0x0104> bnpts; // IS [179 ]
        # 4,1 Block Number of Points
if( !nestedds3.FindDataElement( bnpts.GetTag() ) )
{
    return 1;
}
const gdcmm::DataElement &blocknpts = nestedds3.
    GetDataElement( bnpts.GetTag() );
bnpts.SetFromDataElement( blocknpts );
//std::cout << bnpts.GetValue() << std::endl;

vtkPolyData *output = vtkPolyData::New();
vtkPoints *newPts = vtkPoints::New();
vtkCellArray *polys = vtkCellArray::New();
const double *ptr = at_.GetValues();
//unsigned int npts = bnpts.GetNumberOfValues() / 2;
unsigned int npts = bnpts.GetValue();
vtkIdType *ptIds = new vtkIdType[npts];
for(unsigned int i = 0; i < npts; ++i)
{
    float x[3] = {};
    x[0] = (float)ptr[2*i+0];
    x[1] = (float)ptr[2*i+1];
    //x[2] = ptr[i+2];
    vtkIdType ptId = newPts->InsertNextPoint( x );
    //std::cout << x[0] << " " << x[1] << " " << x[2] << std::endl;
    ptIds[i] = ptId;
}
vtkIdType cellId = polys->InsertNextCell(npts, ptIds);
(void)cellId;
delete[] ptIds;

output->SetPoints(newPts);
newPts->Delete();
output->SetPolys(polys);
polys->Delete();
//output->GetCellData()->SetScalars(scalars);
//scalars->Delete();
output->Update();
output->Print( std::cout );

// }

vtkRenderWindowInteractor *iren = vtkRenderWindowInteractor::New();

vtkImageColorViewer *viewer = vtkImageColorViewer::New();
viewer->SetInput(img);
viewer->SetupInteractor(iren);
viewer->SetSize(600, 600);
viewer->GetRenderer()->ResetCameraClippingRange();
viewer->Render();
viewer->GetRenderer()->ResetCameraClippingRange();

vtkPolyDataMapper *cubeMapper = vtkPolyDataMapper::New();
//vtkPolyDataMapper2D* cubeMapper = vtkPolyDataMapper2D::New();
cubeMapper->SetInput( output );
cubeMapper->SetScalarRange(0,7);
vtkActor *cubeActor = vtkActor::New();
//vtkActor2D* cubeActor = vtkActor2D::New();
cubeActor->SetMapper(cubeMapper);
vtkProperty *property = cubeActor->GetProperty();
property->SetRepresentationToWireframe();

viewer->GetRenderer()->AddActor( cubeActor );

vtkXMLPolyDataWriter *writec= vtkXMLPolyDataWriter::New();
writec->SetInput( output );
writec->SetFileName( outfilename2 );
writec->Write( );

iren->Initialize();
iren->Start();

```

```

    return 0;
}

```

27.58 gdcmrtplan.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkImageData.h"
#include "vtkPointData.h"
#include "vtkPolyData.h"
#include "vtkProperty.h"
#include "vtkPolyDataMapper.h"
#include "vtkActor.h"
#include "vtkRenderer.h"
#include "vtkCellArray.h"
#include "vtkPoints.h"
#include "vtkDoubleArray.h"
#include <vtkXMLImageDataWriter.h>
#include <vtkRenderWindowInteractor.h>
#include <vtkImageColorViewer.h>

#include "gdcmReader.h"
#include "gdcmAttribute.h"

/*
This example is just for fun. We found a fake RT Ion Plan Storage and simply extracted the viz stuff for
VTK
but this is rather a RT Plan storage
*/
int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " filename.dcm outfile.vti\n";
        return 1;
    }
    const char * filename = argv[1];
    const char * outfilename = argv[2];

    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        return 1;
    }

    gdcm::MediaStorage ms;
    ms.SetFromFile( reader.GetFile() );
    if( ms != gdcm::MediaStorage::RTIonPlanStorage )
    {
        return 1;
    }

    /*
(300a,00b0) SQ                                     # u/1,1 Beam Sequence
  (fffe,e000) na (Item with undefined length)
    (300a,00b2) SH (no value)                       # 0,1 Treatment Machine Name
    (300a,00c0) IS [1 ]                             # 2,1 Beam Number
    (300a,00c2) LO [1 ]                             # 2,1 Beam Name
    (300a,00c4) CS [STATIC]                         # 6,1 Beam Type
    (300a,00c6) CS [PROTON]                         # 6,1 Radiation Type
    (300a,00ce) CS [TREATMENT ]                    # 10,1 Treatment Delivery Type
    (300a,00e0) IS [1 ]                             # 2,1 Number of Compensators
    (300a,00e3) SQ                                   # u/1,1 Compensator Sequence
      (fffe,e000) na (Item with undefined length)
        (300a,00e1) SH [lucite]                     # 6,1 Material ID
    */

```



```

(300a,00e4) IS [1] # 2,1 Compensator Number
(300a,00e5) SH [75hdhe5] # 8,1 Compensator ID
(300a,00e7) IS [35] # 2,1 Compensator Rows
(300a,00e8) IS [37] # 2,1 Compensator Columns
(300a,00e9) DS [3.679991\4.249288] # 18,2 Compensator Pixel Spacing
(300a,00ea) DS [-76.00\62.50] # 12,2 Compensator Position
(300a,00ec) DS
[52.13\52.13\52.13\53.18\54.04\54.04\47.11\40.06\40.06\38.79\34.87\33.28\33.28\33.28\
33.28\35.43\35.43\34.54\34.54\34.71\36.10\38.62\44.88\44.88\44.88\45.00\45.00\45.00\45.66\45.66\46.42\39.77\39.77\39.77\39.77\3
Data
(300a,02e0) CS [ABSENT] # 6,1 Compensator Divergence
(300a,02e1) CS [SOURCE_SIDE] # 12,1 Compensator Mounting Position
(fffe,e00d)
(fffe,e000) na (Item with undefined length)
(fffe,e00d)
(fffe,e0dd)
*/
const gdcmm::DataSet& ds = reader.GetFile().GetDataSet();
gdcmm::Tag tbeamsq(0x300a,0x00b0);
if( !ds.FindDataElement( tbeamsq ) )
{
return 1;
}
const gdcmm::DataElement &tbeamsq = ds.GetDataElement( tbeamsq );
//std::cout << tbeamsq << std::endl;
gdcmm::SmartPointer<gdcmm::SequenceOfItems> sqi = tbeamsq.
GetValueAsSQ();
if( !sqi || !sqi->GetNumberOfItems() )
{
return 1;
}

//for(unsigned int pd = 0; pd < sqi->GetNumberOfItems(); ++pd)
// {
//const gdcmm::Item &item = sqi->GetItem(1); // Item start at #1
const gdcmm::Item &item = sqi->GetItem(2); // Item start at #1
const gdcmm::DataSet& nestedds = item.GetNestedDataSet();
//std::cout << nestedds << std::endl;
gdcmm::Tag tcompensatorsq(0x300a,0x00e3);
if( !nestedds.FindDataElement( tcompensatorsq ) )
{
return 1;
}
const gdcmm::DataElement &tcompensatorsq = nestedds.
GetDataElement( tcompensatorsq );
//std::cout << tcompensatorsq << std::endl;
gdcmm::SmartPointer<gdcmm::SequenceOfItems> ssqi = tcompensatorsq.
GetValueAsSQ();
const gdcmm::Item &item2 = ssqi->GetItem(1); // Item start at #1
const gdcmm::DataSet& nestedds2 = item2.GetNestedDataSet();
//std::cout << nestedds2 << std::endl;
gdcmm::Tag tcompensatorthicknessdata(0x300a,0x00ec);
if( !nestedds2.FindDataElement( tcompensatorthicknessdata ) )
{
return 1;
}
const gdcmm::DataElement &tcompensatorthicknessdata = nestedds2.
GetDataElement( tcompensatorthicknessdata );
// std::cout << tcompensatorthicknessdata << std::endl;
gdcmm::Attribute<0x300a,0x00ec> at;
at.SetFromDataElement( tcompensatorthicknessdata );
const double* pts = at.GetValues();
// (300a,00e7) IS [35] # 2,1 Compensator Rows
gdcmm::Attribute<0x300a,0x00e7> at1;
const gdcmm::DataElement &tcompensatorrows = nestedds2.
GetDataElement( at1.GetTag() );
at1.SetFromDataElement( tcompensatorrows );
std::cout << at1.GetValue() << std::endl;
// (300a,00e8) IS [37] # 2,1 Compensator Columns
gdcmm::Attribute<0x300a,0x00e8> at2;
const gdcmm::DataElement &tcompensatorcols = nestedds2.
GetDataElement( at2.GetTag() );
at2.SetFromDataElement( tcompensatorcols );
std::cout << at2.GetValue() << std::endl;

// (300a,00e9) DS [3.679991\4.249288] # 18,2 Compensator Pixel Spacing
gdcmm::Attribute<0x300a,0x00e9> at3;
const gdcmm::DataElement &tcompensatorpixelspacing = nestedds2.
GetDataElement( at3.GetTag() );
at3.SetFromDataElement( tcompensatorpixelspacing );
std::cout << at3.GetValue(0) << std::endl;

```

```

        // (300a,00ea) DS [-76.00\62.50] # 12,2 Compensator Position
gdcmm::Attribute<0x300a,0x00ea> at4;
const gdcmm::DataElement &compensatorposition = nesteddds2.
    GetDataElement( at4.GetTag() );
at4.SetFromDataElement( compensatorposition );
std::cout << at4.GetValue(0) << std::endl;

vtkDoubleArray *d = vtkDoubleArray::New();
d->SetArray( (double*)pts , at1.GetValue() * at2.GetValue() , 0 );

vtkImageData *img = vtkImageData::New();
img->Initialize();
img->SetDimensions( at2.GetValue(), at1.GetValue(), 1 );
//img->SetExtent(1, xdim, 1, ydim, 1, zdim);
img->SetScalarTypeToDouble();
img->SetSpacing( at3.GetValue(1), at3.GetValue(0), 1); // FIXME image is upside down
img->SetOrigin( at4.GetValue(0), at4.GetValue(1), 1);
img->SetNumberOfScalarComponents(1);
img->GetPointData()->SetScalars(d);

vtkXMLImageDataWriter *writeb= vtkXMLImageDataWriter::New();
writeb->SetInput( img );
writeb->SetFileName( outfilename );
writeb->Write();
*/
(300a,00f4) SQ # u/1,1 Block Sequence
    (fffe,e000) na (Item with undefined length)
    (300a,00e1) SH [brass ] # 6,1 Material ID
    (300a,00f8) CS [APERTURE] # 8,1 Block Type
    (300a,00fa) CS [ABSENT] # 6,1 Block Divergence
    (300a,00fb) CS [SOURCE_SIDE ] # 12,1 Block Mounting Position
    (300a,00fc) IS [1 ] # 2,1 Block Number
    (300a,0100) DS [50.00 ] # 6,1 Block Thickness
    (300a,0104) IS [179 ] # 4,1 Block Number of Points
    (300a,0106) DS
    [1.7\50.0\14.3\50.0\16.7\49.4\18.7\48.2\19.4\47.7\20.1\47.1\21.0\47.0\22.3\47.0\23.7\
    46.8\25.7\46.2\27.0\45.6\27.2\45.4\28.2\44.6\28.9\44.2\29.7\43.9\31.5\43.5\33.0\42.8\33.7\42.4\35.2\41.3\38.2\40.4\39.6\39.7\40.
    (fffe,e00d)
    (fffe,e000) na (Item with undefined length)
    (fffe,e00d)
(fffe,e0dd)
*/
gdcmm::Tag tblocksq(0x300a,0x00f4);
if( !nesteddds.FindDataElement( tblocksq ) )
{
    return 1;
}
const gdcmm::DataElement &blocksq = nesteddds.GetDataElement( tblocksq );
//std::cout << blocksq << std::endl;
gdcmm::SmartPointer<gdcmm::SequenceOfItems> sssqi = blocksq.
    GetValueAsSQ();
const gdcmm::Item & item3 = sssqi->GetItem(1); // Item start at #1
const gdcmm::DataSet& nesteddds3 = item3.GetNestedDataSet();

gdcmm::Tag tblockdata(0x300a,0x0106);
if( !nesteddds3.FindDataElement( tblockdata ) )
{
    return 1;
}
const gdcmm::DataElement &blockdata = nesteddds3.
    GetDataElement( tblockdata );
// std::cout << blockdata << std::endl;
gdcmm::Attribute<0x300a,0x0106> at_;
at_.SetFromDataElement( blockdata );

vtkDoubleArray *scalars = vtkDoubleArray::New();
scalars->SetNumberOfComponents(3);

gdcmm::Attribute<0x300a,0x0104> bnpts; // IS [179 ] # 4,1 Block Number of
    Points
if( !nesteddds3.FindDataElement( bnpts.GetTag() ) )
{
    return 1;
}
const gdcmm::DataElement &blocknpts = nesteddds3.
    GetDataElement( bnpts.GetTag() );
bnpts.SetFromDataElement( blocknpts );
std::cout << bnpts.GetValue() << std::endl;

vtkPolyData *output = vtkPolyData::New();
vtkPoints *newPts = vtkPoints::New();

```

```

vtkCellArray *polys = vtkCellArray::New();
const double *ptr = at_.GetValues();
//unsigned int npts = bnpts.GetNumberOfValues() / 2;
unsigned int npts = bnpts.GetValue();
vtkIdType *ptIds = new vtkIdType[npts];
for(unsigned int i = 0; i < npts; ++i)
{
    float x[3] = {};
    x[0] = (float)ptr[2*i+0];
    x[1] = (float)ptr[2*i+1];
    //x[2] = pts[i+2];
    vtkIdType ptId = newPts->InsertNextPoint( x );
    //std::cout << x[0] << ", " << x[1] << ", " << x[2] << std::endl;
    ptIds[i] = ptId;
}
vtkIdType cellId = polys->InsertNextCell(npts , ptIds);
(void)cellId;
delete[] ptIds;

output->SetPoints(newPts);
newPts->Delete();
output->SetPolys(polys);
polys->Delete();
//output->GetCellData()->SetScalars(scalars);
//scalars->Delete();
output->Update();
output->Print( std::cout );

// }

vtkRenderWindowInteractor *iren = vtkRenderWindowInteractor::New();

vtkImageColorViewer *viewer = vtkImageColorViewer::New();
viewer->SetInput(img);
viewer->SetupInteractor(iren);
viewer->SetSize(600, 600);
viewer->Render();

vtkPolyDataMapper *cubeMapper = vtkPolyDataMapper::New();
//vtkPolyDataMapper2D* cubeMapper = vtkPolyDataMapper2D::New();
cubeMapper->SetInput( output );
cubeMapper->SetScalarRange(0,7);
vtkActor *cubeActor = vtkActor::New();
//vtkActor2D* cubeActor = vtkActor2D::New();
cubeActor->SetMapper(cubeMapper);
vtkProperty *property = cubeActor->GetProperty();
property->SetRepresentationToWireframe();

viewer->GetRenderer()->AddActor( cubeActor );

iren->Initialize();
iren->Start();

return 0;
}

```

27.59 gdcmscene.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkGDCMPolyDataReader.h"
// #include "vtkGDCMPolyDataWriter.h"

```

```

#include "vtkAppendPolyData.h"
#include "vtkPolyDataWriter.h"
#include "vtkPolyDataMapper.h"
#include "vtkPolyDataMapper2D.h"
#include "vtkActor2D.h"
#include "vtkRenderWindowInteractor.h"
#include "vtkRenderWindow.h"
#include "vtkRenderer.h"
#include "vtkCamera.h"
#include "vtkProperty.h"
#include "vtkProperty2D.h"

// gdcmdataExtra/gdcmdNonImageData/exRT_Structure_Set_Storage.dcm
// gdcmdataExtra/gdcmdNonImageData/RTSTRUCT_1.3.6.1.4.1.22213.1.1396.2.dcm
// gdcmdataExtra/gdcmdNonImageData/RT/RTStruct.dcm

int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        std::cerr << argv[0] << " filename1.dcm\n";
        return 1;
    }
    const char * filename = argv[1];

    vtkGDCMPolyDataReader * reader =
        vtkGDCMPolyDataReader::New();
    reader->SetFileName( filename );
    reader->Update();

    // vtkGDCMPolyDataWriter * writer2 = vtkGDCMPolyDataWriter::New();
    // for(int num = 0; num < reader->GetNumberOfOutputPorts(); ++num )
    //     writer2->SetInput( num, reader->GetOutput( num ) );
    // writer2->SetFileName( "rtstruct.dcm" );
    // writer2->Write();

    // print reader output:
    reader->Print( std::cout );
    // print first output:
    reader->GetOutput()->Print( std::cout );

    vtkAppendPolyData *append = vtkAppendPolyData::New();
    int n = reader->GetNumberOfOutputPorts();
    for(int i = 0; i < n; ++i)
    {
        append->AddInput( reader->GetOutput(i) );
    }

    vtkPolyDataWriter * writer = vtkPolyDataWriter::New();
    writer->SetInput( reader->GetOutput() );
    writer->SetFileName( "rtstruct.vtk" );
    //writer->Write();

    // Now we'll look at it.
    vtkPolyDataMapper *cubeMapper = vtkPolyDataMapper::New();
    //vtkPolyDataMapper2D* cubeMapper = vtkPolyDataMapper2D::New();
    //cubeMapper->SetInput( reader->GetOutput() );
    cubeMapper->SetInput( append->GetOutput() );
    cubeMapper->SetScalarRange(0,7);
    vtkActor *cubeActor = vtkActor::New();
    //vtkActor2D* cubeActor = vtkActor2D::New();
    cubeActor->SetMapper(cubeMapper);
    vtkProperty * property = cubeActor->GetProperty();
    property->SetRepresentationToWireframe();
    //cubeActor->GetProperty()->SetColor(1, 0, 0);

    // The usual rendering stuff.
    // vtkCamera *camera = vtkCamera::New();
    //     camera->SetPosition(1,1,1);
    //     camera->SetFocalPoint(0,0,0);

    vtkRenderer *renderer = vtkRenderer::New();
    vtkRenderWindow *renWin = vtkRenderWindow::New();
    renWin->AddRenderer(renderer);

    vtkRenderWindowInteractor *iren = vtkRenderWindowInteractor::New();
    iren->SetRenderWindow(renWin);

```

```

renderer->AddActor(cubeActor);
//renderer->AddActor2D(cubeActor);
//renderer->SetActiveCamera(camera);
renderer->ResetCamera();
renderer->SetBackground(1,1,1);

renWin->SetSize(300,300);

// interact with data
renWin->Render();
iren->Start();

reader->Delete();
append->Delete();
cubeMapper->Delete();
cubeActor->Delete();
// camera->Delete();
renderer->Delete();
renWin->Delete();
iren->Delete();

writer->Delete();

return 0;
}

```

27.60 gdcmttexture.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkGDCMImageReader.h"

#include "vtkRenderer.h"
#include "vtkAssembly.h"
#include "vtkRenderWindow.h"
#include "vtkAnnotatedCubeActor.h"
#include "vtkTransform.h"
#include "vtkAxesActor.h"
#include "vtkTextProperty.h"
#include "vtkCaptionActor2D.h"
#include "vtkPropAssembly.h"
#include "vtkOrientationMarkerWidget.h"
#include "vtkRenderWindowInteractor.h"
#include "vtkPolyDataMapper.h"
#include "vtkActor.h"
#include "vtkImageData.h"
#include "vtkLookupTable.h"
#include "vtkTexture.h"
#include "vtkPlaneSource.h"

int main( int argc, char *argv[] )
{
    if( argc < 2 ) return 1;
    vtkGDCMImageReader *reader = vtkGDCMImageReader::New();
    reader->SetFileName( argv[1] );

    reader->Update();
    vtkImageData* ima = reader->GetOutput();

    vtkLookupTable* table = vtkLookupTable::New();
    table->SetNumberOfColors(1000);
    table->SetTableRange(0,1000);
    table->SetSaturationRange(0,0);
    table->SetHueRange(0,1);

```

```

table->SetValueRange(0,1);
table->SetAlphaRange(1,1);
table->Build();

// Texture
vtkTexture* texture = vtkTexture::New();
texture->SetInput(ima);
texture->InterpolateOn();
texture->SetLookupTable(table);

// PlaneSource
vtkPlaneSource* plane = vtkPlaneSource::New();
plane->SetOrigin( -0.5, -0.5, 0.0);
plane->SetPoint1( 0.5, -0.5, 0.0);
plane->SetPoint2( -0.5, 0.5, 0.0);

// PolyDataMapper
vtkPolyDataMapper *planeMapper = vtkPolyDataMapper::New();
planeMapper->SetInput(plane->GetOutput());

// Actor
vtkActor* planeActor = vtkActor::New();
planeActor->SetTexture(texture);
planeActor->SetMapper(planeMapper);
planeActor->PickableOn();

// Final rendering with simple interactor:
vtkRenderer *ren = vtkRenderer::New();
vtkRenderWindow *renwin = vtkRenderWindow::New();
renwin->AddRenderer(ren);
vtkRenderWindowInteractor *iren = vtkRenderWindowInteractor::New();
iren->SetRenderWindow(renwin);
ren->AddActor(planeActor);
ren->SetBackground(0,0,0.5);

vtkAnnotatedCubeActor* cube = vtkAnnotatedCubeActor::New();
cube->SetXPlusFaceText( "L" );
cube->SetXMinusFaceText( "R" );
cube->SetYPlusFaceText( "A" );
cube->SetYMinusFaceText( "P" );
cube->SetZPlusFaceText( "H" );
cube->SetZMinusFaceText( "F" );

vtkAxesActor* axes2 = vtkAxesActor::New();
// simulate a left-handed coordinate system
//
vtkTransform *transform = vtkTransform::New();
transform->Identity();
//transform->RotateY(180);
reader->GetDirectionCosines()->Print(std::cout);
transform->Concatenate(reader->GetDirectionCosines());
//axes2->SetShaftTypeToCylinder();
axes2->SetUserTransform( transform );
//cube->SetUserTransform( transform ); // cant get it to work
cube->GetAssembly()->SetUserTransform( transform ); // cant get it to work

vtkPropAssembly* assembly = vtkPropAssembly::New();
assembly->AddPart( axes2 );
assembly->AddPart( cube );

vtkOrientationMarkerWidget* widget = vtkOrientationMarkerWidget::New();
//widget->SetOutlineColor( 0.9300, 0.5700, 0.1300 );
widget->SetOrientationMarker( assembly );
widget->SetInteractor( iren );
//widget->SetViewport( 0.0, 0.0, 0.4, 0.4 );
widget->SetEnabled( 1 );
widget->InteractiveOff();
widget->InteractiveOn();

renwin->Render();
iren->Start();

// Clean up:
reader->Delete();
table->Delete();
texture->Delete();
plane->Delete();
planeMapper->Delete();
planeActor->Delete();
ren->Delete();
renwin->Delete();

```

```

    iren->Delete();

    return 0;
}

```

27.61 gdcmvolume.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkGDCMImageReader.h"
#include "vtkPiecewiseFunction.h"
#include "vtkColorTransferFunction.h"
#include "vtkVolume.h"
#include "vtkVolumeProperty.h"
#include "vtkVolumeTextureMapper3D.h"
#include "vtkFixedPointVolumeRayCastMapper.h"
#include "vtkInteractorStyleTrackballCamera.h"
#include "vtkRenderer.h"
#include "vtkRenderWindow.h"
#include "vtkImageClip.h"
#include "vtkRenderWindowInteractor.h"

// gdcmvolume gdcmData/GE_DLX-8-MONO2-Multiframe-Jpeg_Lossless.dcm
int main(int argc, char *argv[])
{
    if( argc < 2 ) return 1;
    vtkGDCMImageReader *reader = vtkGDCMImageReader::New();
    reader->SetFileName( argv[1] );
    reader->Update();

    // Create the renderers, render window, and interactor
    vtkRenderWindow *renWin = vtkRenderWindow::New();
    vtkRenderWindowInteractor *iren = vtkRenderWindowInteractor::New();
    iren->SetRenderWindow(renWin);
    vtkRenderer *ren = vtkRenderer::New();
    renWin->AddRenderer(ren);

    // Create a transfer function mapping scalar value to opacity
    vtkPiecewiseFunction *oTFun = vtkPiecewiseFunction::New();
    //oTFun->AddSegment(0, 1.0, 256, 0.1);
    oTFun->AddSegment(0, 1.0, 240, 0.1);

    vtkColorTransferFunction *cTFun = vtkColorTransferFunction::New();
    cTFun->AddRGBPoint( 0, 1.0, 1.0, 1.0 );
    //cTFun->AddRGBPoint( 255, 1.0, 1.0, 1.0 );
    cTFun->AddRGBPoint( 240, 1.0, 1.0, 1.0 );

    // Need to crop to actually see minimum intensity
    vtkImageClip *clip = vtkImageClip::New();
    clip->SetInputConnection( reader->GetOutputPort() );
    clip->SetOutputWholeExtent(0,66,0,66,30,37);
    clip->ClipDataOn();

    vtkVolumeProperty *property = vtkVolumeProperty::New();
    property->SetScalarOpacity(oTFun);
    property->SetColor(cTFun);
    property->SetInterpolationTypeToLinear();

    vtkFixedPointVolumeRayCastMapper *mapper = vtkFixedPointVolumeRayCastMapper::New();
    mapper->SetBlendModeToMinimumIntensity();
    mapper->SetInputConnection( reader->GetOutputPort() );

    vtkVolume *volume = vtkVolume::New();
    volume->SetMapper(mapper);
    volume->SetProperty(property);
}

```

```

ren->AddViewProp(volume);

renWin->Render();
{
    iren->Start();
}

volume->Delete();
mapper->Delete();
property->Delete();
clip->Delete();
cTFun->Delete();
oTFun->Delete();
reader->Delete();
renWin->Delete();
iren->Delete();
ren->Delete();

return 0;
}

```

27.62 GenAllVR.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmReader.h"
#include "gdcmGlobal.h"
#include "gdcmDummyValueGenerator.h"
#include "gdcmMediaStorage.h"
#include "gdcmWriter.h"
#include "gdcmItem.h"
#include "gdcmImageReader.h"
#include "gdcmSequenceOfItems.h"
#include "gdcmFile.h"
#include "gdcmTag.h"
#include "gdcmDict.h"
#include "gdcmDictEntry.h"
#include "gdcmDicts.h"
#include "gdcmTransferSyntax.h"
#include "gdcmUIDGenerator.h"
#include "gdcmFileExplicitFilter.h"

#include <cstdlib>
#include <cstring>

gdcm::Tag FindTagFromVR(gdcm::Dict const &dict, gdcm::VR const &vr)
{
    using gdcm::Dict;
    Dict::ConstIterator beg = dict.Begin();
    Dict::ConstIterator end = dict.End();
    Dict::ConstIterator it;
    for( it = beg; it != end; ++it)
    {
        const gdcm::Tag &t = it->first;
        const gdcm::DictEntry &de = it->second;
        const gdcm::VR &vr_de = de.GetVR();
        if( vr == vr_de && !de.GetRetired() && t.GetGroup() >= 0x8 )
        {
            return t;
        }
    }
    return gdcm::Tag(0xffff,0xffff);
}

```



```

}

struct rnd_gen {
    rnd_gen(char const* r = "abcdefghijklmnopqrstuvwxyz0123456789")
        : range(r), len(std::strlen(r)) { }

    char operator ()() const {
        return range[static_cast<std::size_t>(std::rand() * (1.0 / ((double)RAND_MAX + 1.0)) * (double)len)];
    }
private:
    char const* range;
    std::size_t len;
};

/*
*/
int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        std::cerr << argv[0] << " output.dcm" << std::endl;
        return 1;
    }
    const char *outfilename = argv[1];
    static const gdcm::Global &g = gdcm::Global::GetInstance();
    static const gdcm::Dicts &dicts = g.GetDicts();
    static const gdcm::Dict &pubdict = dicts.GetPublicDict();
    using gdcm::VR;
    using gdcm::Tag;

    gdcm::Writer w;

    gdcm::File &f = w.GetFile();
    gdcm::DataSet &ds = f.GetDataSet();

    gdcm::FileExplicitFilter fef;
    //fef.SetChangePrivateTags( true );
    fef.SetFile( w.GetFile() );
    if( !fef.Change() )
    {
        std::cerr << "Failed to change" << std::endl;
        return 1;
    }

    gdcm::SmartPointer<gdcm::SequenceOfItems> sq = new
        gdcm::SequenceOfItems();
    sq->SetLengthToUndefined();

    // gdcm::DummyValueGenerator dv;

    const std::size_t len = 10;
    char ss[len+1];
    ss[len] = '\0';

    const char owner_str[] = "GDCM CONFORMANCE TESTS";
    gdcm::DataElement owner( gdcm::Tag(0x4d4d, 0x10) );
    owner.SetByteValue(owner_str, (uint32_t)strlen(owner_str));
    owner.SetVR( gdcm::VR::LO );

    // Create an item
    gdcm::Item it;
    it.SetVLToUndefined();
    gdcm::DataSet &nds = it.GetNestedDataSet();
    // nds.Insert(owner);
    // nds.Insert(de);

    // Insert sequence into data set
    gdcm::DataElement des( gdcm::Tag(0x4d4d, 0x1001) );
    des.SetVR(gdcm::VR::SQ);
    des.SetValue(*sq);
    des.SetVLToUndefined();

    ds.Insert(owner);
    ds.Insert(des);

    // avoid INVALID = 0
    for(int i = 1; i < 27; ++i)
    {
        VR vr = (VR::VRType)(1 << i);
        Tag t = FindTagFromVR( pubdict, vr );
        if( vr != VR::UN && vr != VR::SQ )

```

```

    {
        assert( t != Tag(0xffff,0xffff) );
        gdcm::DataElement de( t );
        std::generate_n(ss, len, rnd_gen());
        de.SetVR( vr );
        de.SetByteValue( ss, (uint32_t)std::strlen( ss ) );
        nds.Insert( de );
    }
}
sq->AddItem(it);

// Make sure to override any UID stuff
gdcm::UIDGenerator uid;
gdcm::DataElement de( Tag(0x8,0x18) ); // SOP Instance UID
de.SetVR( VR:UI );
const char *u = uid.Generate();
de.SetByteValue( u, (uint32_t)strlen(u) );
ds.Insert( de );

de.SetTag( Tag(0x8,0x16) ); // SOP Class UID
de.SetVR( VR:UI );
gdcm::MediaStorage ms( gdcm::MediaStorage::RawDataStorage
    );
de.SetByteValue( ms.GetString(), (uint32_t)strlen(ms.GetString()) );
ds.Insert( de );

gdcm::FileMetaInformation &fmi = f.GetHeader();
//fmi.SetDataSetTransferSyntax( gdcm::TransferSyntax::ImplicitVRLittleEndian );
fmi.SetDataSetTransferSyntax(
    gdcm::TransferSyntax::ExplicitVRLittleEndian );

w.SetCheckFileMetaInformation( true );
w.SetFileName( outfilename );
if ( !w.Write() )
{
    return 1;
}

return 0;
}

```

27.63 GenerateDICOMDIR.cs

This is a C# example on how to use `gdcm::DICOMDIRGenerator`

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * Simple C# example to show how to use DICOMDIRGenerator
 *
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/GenerateDICOMDIR.exe path output_filename
 */
using System;
using gdcm;

public class GenerateDICOMDIR
{
    public static int Main(string[] args)
    {
        string directory = args[0];
        string outfilename = args[1];
    }
}

```

```

Directory d = new Directory();
uint nfiles = d.Load( directory, true );
if(nfiles == 0) return 1;
//System.Console.WriteLine( "Files:\n" + d.toString() );

// Implement fast path ?
// Scanner s = new Scanner();

string descriptor = "My_Descriptor";
FileNamesType filenames = d.GetFilesNames();

gdc.DICOMDIRGenerator gen = new DICOMDIRGenerator();
gen.SetFilenames( filenames );
gen.SetDescriptor( descriptor );
if( !gen.Generate() )
{
    return 1;
}

gdc.FileMetaInformation.SetSourceApplicationEntityTitle( "GenerateDICOMDIR" );
gdc.Writer writer = new Writer();
writer.SetFile( gen.GetFile() );
writer.SetFileName( outfilename );
if( !writer.Write() )
{
    return 1;
}

return 0;
}

```

27.64 GenerateRTSTRUCT.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdc.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkGDCMPolyDataWriter.h"
#include "vtkGDCMPolyDataReader.h"
#include "vtkPolyData.h"
#include "vtkPolyDataReader.h"
#include "vtkMedicalImageProperties.h"
#include "vtkRTStructSetProperties.h"
#include "vtkStringArray.h"
#include "vtkAppendPolyData.h"
#include "vtkPolyDataWriter.h"
#include "vtkPolyDataMapper.h"
#include "vtkPolyDataMapper2D.h"
#include "vtkActor2D.h"
#include "vtkRenderWindowInteractor.h"
#include "vtkMedicalImageProperties.h"
#include "vtkRenderWindow.h"
#include "vtkRenderer.h"
#include "vtkCamera.h"
#include "vtkProperty.h"
#include "vtkProperty2D.h"
#include "vtkImageData.h"

#include <algorithm> //for std::find

#include "gdcDirectoryHelper.h"

using namespace gdc;

//view each organ independently of the others, to make sure that
//organ names correspond to actual segmentations.
void ShowOrgan(vtkPolyData* inData)

```

```

{
    // Now we'll look at it.
    vtkPolyDataMapper *cubeMapper = vtkPolyDataMapper::New();
    cubeMapper->SetInput( inData );
    cubeMapper->SetScalarRange(0,7);
    vtkActor *cubeActor = vtkActor::New();
    cubeActor->SetMapper(cubeMapper);
    vtkProperty * property = cubeActor->GetProperty();
    property->SetRepresentationToWireframe();

    vtkRenderer *renderer = vtkRenderer::New();
    vtkRenderWindow *renWin = vtkRenderWindow::New();
    renWin->AddRenderer(renderer);

    vtkRenderWindowInteractor *iren = vtkRenderWindowInteractor::New();
    iren->SetRenderWindow(renWin);

    renderer->AddActor(cubeActor);
    renderer->ResetCamera();
    renderer->SetBackground(1,1,1);

    renWin->SetSize(300,300);

    renWin->Render();
    iren->Start();

    cubeMapper->Delete();
    cubeActor->Delete();
    renderer->Delete();
    renWin->Delete();
    iren->Delete();
}

/*
 * Full application which ... RTSTRUCT
 */
int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        std::cerr << argv[0] << " directory-with-rtstruct-and-ct-images\n";
        return 1;
    }
    std::string theDirName(argv[1]);
    Directory::FileNamesType theRTSeries =
        DirectoryHelper::GetRTStructSeriesUIDs(theDirName);

    gdcm::Directory theDir;
    theDir.Load(argv[1]);

    if (theRTSeries.empty())
    {
        std::cerr << "No RTStructs found for the test, ending." << std::endl;
        return 1;
    }

    for (size_t q = 0; q < theRTSeries.size(); q++)
    {
        Directory::FileNamesType theRTNames =
            DirectoryHelper::GetFileNamesFromSeriesUIDs(theDirName,
                theRTSeries[q]);

        if (theRTNames.empty()){
            std::cerr << "Unable to load RT Series " << theRTSeries[q] << ", continuing. " << std::endl;
            continue;
        }

        vtkGDCMPolyDataReader * reader =
            vtkGDCMPolyDataReader::New();
        reader->SetFileName( theRTNames[0].c_str() );
        reader->Update();

        //std::cout << reader->GetMedicalImageProperties()->GetStudyDate() << std::endl;

        vtkGDCMPolyDataWriter * writer =
            vtkGDCMPolyDataWriter::New();
        int numMasks = reader->GetNumberOfOutputPorts() + 1; //add a blank one in
        writer->SetNumberOfInputPorts( numMasks );
        std::string thePotentialName = theDirName + "/" + "GDCMTestRTStruct." + theRTSeries[q] + ".dcm";
        gdcm::Directory::FileNamesType theFileNames = theDir.
            GetFileNames();

```

```

//keep renaming the output until we get something that doesn't overwrite what was there already
int count = 0;
while (std::find(theFileNames.begin(), theFileNames.end(), thePotentialName) != theFileNames.end())
{
    char buff[255];
    sprintf(buff, "%d", count);
    thePotentialName = theDirName + "/" + "GDCMTestRTStruct." + buff + "." + theRTSeries[q] + ".dcm";
}
writer->SetFileName( thePotentialName.c_str());
writer->SetMedicalImageProperties( reader->GetMedicalImageProperties() );
//this line is cheating, we won't have the same stuff, and may not have a struct
//to start with.
//have to go back to the original data to reconstruct the RTStructureSetProperties
//writer->SetRTStructSetProperties( reader->GetRTStructSetProperties() );
//writer->Write();

//loop through the outputs in order to write them out as if they had been created and appended
vtkStringArray* roiNames = vtkStringArray::New();
vtkStringArray* roiAlgorithms = vtkStringArray::New();
vtkStringArray* roiTypes = vtkStringArray::New();
roiNames->SetNumberOfValues(numMasks);
roiAlgorithms->SetNumberOfValues(numMasks);
roiTypes->SetNumberOfValues(numMasks);
vtkAppendPolyData* append = vtkAppendPolyData::New();

//ok, now we'll add a blank organ
//the blank organ is to test to ensure that blank organs work; there have been crash reports
//this code is added at the beginning to ensure that the blank organs are read
//and preserved as individual organs.
vtkPolyData* blank = vtkPolyData::New();
writer->SetInput(0, blank);
roiNames->InsertValue(0, "blank");
roiAlgorithms->InsertValue(0, "blank");
roiTypes->InsertValue(0, "ORGAN");

//note the offsets used to place the blank rtstruct at the beginning of the newly generated RT.
//the idea is to run the program twice; first to generate an rtstruct with a blank mask (making
//sure that that functionality works), and then a second time to make sure that everything is
//being read properly. Multiple organs with the same name could cause some strangenesses.
for (int i = 1; i < numMasks; ++i)
{
    writer->SetInput(i, reader->GetOutput(i-1));
    append->AddInput(reader->GetOutput(i-1));
    std::string theString = reader->GetRTStructSetProperties()->GetStructureSetROIName(i-1);
    roiNames->InsertValue(i, theString);
    theString = reader->GetRTStructSetProperties()->GetStructureSetROIGenerationAlgorithm(i-1);
    roiAlgorithms->InsertValue(i, theString);
    theString = reader->GetRTStructSetProperties()->GetStructureSetROIInterpretedType(i-1);
    roiTypes->InsertValue(i, theString);

    ShowOrgan(reader->GetOutput(i-1));
}

vtkRTStructSetProperties* theProperties =
    vtkRTStructSetProperties::New();
writer->SetRTStructSetProperties(theProperties);
writer->InitializeRTStructSet(theDirName,
    reader->GetRTStructSetProperties()->GetStructureSetLabel(),
    reader->GetRTStructSetProperties()->GetStructureSetName(),
    roiNames, roiAlgorithms, roiTypes);

writer->SetRTStructSetProperties(theProperties);
writer->Write();

// print reader output:
reader->Print( std::cout );
// print first output:
reader->GetOutput()->Print( std::cout );

reader->Delete();
append->Delete();
roiNames->Delete();
roiTypes->Delete();
theProperties->Delete();
roiAlgorithms->Delete();
blank->Delete();

writer->Delete();
}
return 0;
}

```

27.65 GenerateStandardSOPClasses.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcml.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/
/*
*/

#include "gdcmlDefs.h"
#include "gdcmlUIDs.h"
#include "gdcmlGlobal.h"
#include "gdcmlMediaStorage.h"
#include "gdcmlSOPClassUIDToIOD.h"

int main(int , char *[])
{
    using gdcml::MediaStorage;
    gdcml::Global& g = gdcml::Global::GetInstance();
    if( !g.LoadResourcesFiles() )
    {
        std::cerr << "Could not LoadResourcesFiles" << std::endl;
        return 1;
    }

    const gdcml::Defs &defs = g.GetDefs();

    int ret = 0;

    //std::cout << "Table B.5-1 STANDARD SOP CLASSES" << std::endl;
    std::cout << "SOP Class Name,SOP Class UID,IOD Specification (defined in PS 3.3)" << std::endl;

    gdcml::MediaStorage::MSType mst;
    for ( mst = gdcml::MediaStorage::MediaStorageDirectoryStorage
          ; mst < gdcml::MediaStorage::MS_END;
          mst = (gdcml::MediaStorage::MSType)(mst + 1) )
    {
        const char *iod = defs.GetIODNameFromMediaStorage(mst);
        gdcml::UIDs uid;
        uid.SetFromUID( gdcml::MediaStorage::GetMSString(mst) /*
            mst.GetString()*/ );
        if( iod )
        {
            const char *iod_ref = gdcml::SOPClassUIDToIOD::GetIOD(uid);
            if( iod_ref )
            {
                std::string iod_ref_str = iod_ref;
                //iod_ref_str += " IOD Modules";
                //if( iod_ref_str != iod )
                {
                    //std::cout << "UID: " << uid << " ";
                    std::cout << "' ' << uid.GetName() << "' ' << ',' << "' ' <<uid.
                    GetString() << "' ' << ',' << "' ' <<iod << "' ' << std::endl;
                    //std::cout << "Incompatible IODs: [" << iod << "]" versus ref= [" << iod_ref_str << "]" <<
                    std::endl;
                    ++ret;
                }
            }
        }
    }

    return 0;
}

```

27.66 GenFakelIdentifyFile.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmReader.h"
#include "gdcmGlobal.h"
#include "gdcmDummyValueGenerator.h"
#include "gdcmMediaStorage.h"
#include "gdcmWriter.h"
#include "gdcmItem.h"
#include "gdcmImageReader.h"
#include "gdcmSequenceOfItems.h"
#include "gdcmAttribute.h"
#include "gdcmFile.h"
#include "gdcmTag.h"
#include "gdcmDict.h"
#include "gdcmDictEntry.h"
#include "gdcmDicts.h"
#include "gdcmTransferSyntax.h"
#include "gdcmUIDGenerator.h"
#include "gdcmAnonymizer.h"

#include <cstdlib>
#include <cstring>

gdcm::DataElement CreateFakeElement(gdcm::Tag const &tag, bool toremove)
{
    static const gdcm::Global &g = gdcm::Global::GetInstance();
    static const gdcm::Dicts &dicts = g.GetDicts();
    static const gdcm::Dict &pubdict = dicts.GetPublicDict();
    static size_t countglobal = 0;
    static std::vector<gdcm::Tag> balcptags =
        gdcm::Anonymizer::GetBasicApplicationLevelConfidentialityProfileAttributes
        ();
    size_t count = countglobal % balcptags.size();

    const gdcm::DictEntry &dictentry = pubdict.GetDictEntry(tag);

    gdcm::DataElement de;
    de.SetTag( tag );
    using gdcm::VR;
    const VR &vr = dictentry.GetVR();
    //if( vr != VR::INVALID )
    if( vr.IsDual() )
    {
        if( vr == VR::US_SS )
        {
            de.SetVR( VR::US );
        }
        else if( vr == VR::US_SS_OW )
        {
            de.SetVR( VR::OW );
        }
        else if( vr == VR::OB_OW )
        {
            de.SetVR( VR::OB );
        }
    }
    else
    {
        de.SetVR( vr );
    }
    const char str[] = "BasicApplicationLevelConfidentialityProfileAttributes";
    const char safe[] = "This is safe to keep";
    if( de.GetVR() != VR::SQ )
    {
        if( toremove )
            de.SetByteValue( str, (uint32_t)strlen(str) );
        else

```

```

        de.SetByteValue( safe, (uint32_t)strlen(safe) );
    }
    else
    {
        // Create an item
        gdcmm::Item it;
        it.SetVLToUndefined();
        gdcmm::DataSet &nds = it.GetNestedDataSet();
        // Insert sequence into data set
        assert(de.GetVR() == gdcmm::VR::SQ );
        gdcmm::SmartPointer<gdcmm::SequenceOfItems> sq = new
            gdcmm::SequenceOfItems();
        sq->SetLengthToUndefined();
        de.SetValue(*sq);
        de.SetVLToUndefined();
        //ds.Insert(de);

        if( !toremove )
        {
            nds.Insert( CreateFakeElement( balcptags[count], true ) );
            countglobal++;
        }
        else
        {
            gdcmm::Attribute<0x0008,0x0000> at1 = { 0 }; // This element has no
                reason to be 'anonymized'...
            nds.Insert( at1.GetAsDataElement() );
            gdcmm::Attribute<0x000a,0x0000> at2 = { 0 };
            nds.Insert( at2.GetAsDataElement() );
        }
        sq->AddItem(it);
    }
    return de;
}

/*
*/
int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        std::cerr << argv[0] << " output.dcm" << std::endl;
        return 1;
    }
    using gdcmm::Tag;
    using gdcmm::VR;
    const char *outfilename = argv[1];

    std::vector<gdcmm::Tag> balcptags =
        gdcmm::Anonymizer::GetBasicApplicationLevelConfidentialityProfileAttributes
            ();

    gdcmm::Writer w;
    gdcmm::File &f = w.GetFile();
    gdcmm::DataSet &ds = f.GetDataSet();

    // Add attribute that need to be anonymized:
    std::vector<gdcmm::Tag>::const_iterator it = balcptags.begin();
    for(; it != balcptags.end(); ++it)
    {
        ds.Insert( CreateFakeElement( *it, true ) );
    }

    // Add attribute that do NOT need to be anonymized:
    static const gdcmm::Global &g = gdcmm::Global::GetInstance();
    static const gdcmm::Dicts &dicts = g.GetDicts();
    static const gdcmm::Dict &pubdict = dicts.GetPublicDict();

    using gdcmm::Dict;
    Dict::ConstIterator dictit = pubdict.Begin();
    for(; dictit != pubdict.End(); ++dictit)
    {
        const gdcmm::Tag &dicttag = dictit->first;
        if( dicttag == Tag(0x6e65,0x6146) ) break;
        //const gdcmm::DictEntry &dictentry = dictit->second;
        ds.Insert( CreateFakeElement( dicttag, false ) );
    }
    ds.Remove( gdcmm::Tag(0x400,0x500) );
    ds.Remove( gdcmm::Tag(0x12,0x62) );
    ds.Remove( gdcmm::Tag(0x12,0x63) );

```



```

// Make sure to override any UID stuff
gdcm::UIDGenerator uid;
gdcm::DataElement de( Tag(0x8,0x18) ); // SOP Instance UID
de.SetVR( VR::UI );
const char *u = uid.Generate();
de.SetByteValue( u, (uint32_t)strlen(u) );
//ds.Insert( de );
ds.Replace( de );

de.SetTag( Tag(0x8,0x16) ); // SOP Class UID
de.SetVR( VR::UI );
gdcm::MediaStorage ms( gdcm::MediaStorage::RawDataStorage
);
de.SetByteValue( ms.GetString(), (uint32_t)strlen(ms.GetString()));
ds.Replace( de ); // replace !

gdcm::FileMetaInformation &fmi = f.GetHeader();
//fmi.SetDataSetTransferSyntax( gdcm::TransferSyntax::ImplicitVRLittleEndian );
fmi.SetDataSetTransferSyntax(
    gdcm::TransferSyntax::ExplicitVRLittleEndian );

w.SetCheckFileMetaInformation( true );
w.SetFileName( outfilename );
if (!w.Write() )
{
    return 1;
}

return 0;
}

```

27.67 GenFakelImage.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmImage.h"
#include "gdcmImageWriter.h"
#include "gdcmFileDerivation.h"
#include "gdcmUIDGenerator.h"
//#include "gdcmImageChangePhotometricInterpretation.h"

/*
 * This example shows two things:
 * 1. How to create an image ex-nihilo
 * 2. How to use the gdcm.FileDerivation filter. This filter is meant to create "DERIVED" image
 * object. FileDerivation has a simple API where you can reference *all* the input image that have been
 * used to generate the image. The API also allows user to specify the purpose of reference (see CID 7202,
 * PS 3.16 - 2008), and the image derivation type (CID 7203, PS 3.16 - 2008).
 */
int main(int, char *[])
{
    // Step 1: Fake Image
    gdcm::SmartPointer<gdcm::Image> im = new
        gdcm::Image;

    char * buffer = new char[ 256 * 256 * 3];
    char * p = buffer;
    int b = 128;
    int ybr[3];
    int ybr2[3];
    int rgb[3];

    for(int r = 0; r < 256; ++r)
        for(int g = 0; g < 256; ++g)
            //for(int b = 0; b < 256; ++b)
            {

```

```

    rgb[0] = r;
    rgb[1] = g;
    rgb[1] = 128;
    rgb[2] = b;
    ybr[0] = r;
    ybr[1] = g;
    ybr[1] = 128;
    ybr[2] = b;

    ybr2[0] = r;
    ybr2[1] = g;
    ybr2[1] = 128;
    ybr2[2] = b;
    //gdcm::ImageChangePhotometricInterpretation::YBR2RGB(rgb, ybr);
    //gdcm::ImageChangePhotometricInterpretation::RGB2YBR(ybr2, rgb);
    *p++ = (char)ybr2[0];
    *p++ = (char)ybr2[1];
    *p++ = (char)ybr2[2];
}

im->SetNumberOfDimensions( 2 );
im->SetDimension(0, 256 );
im->SetDimension(1, 256 );

im->GetPixelFormat().SetSamplesPerPixel(3);
//im->SetPhotometricInterpretation( gdcm::PhotometricInterpretation::RGB );
im->SetPhotometricInterpretation(
    gdcm::PhotometricInterpretation::YBR_FULL );

unsigned long l = im->GetBufferLength();
if( l != 256 * 256 * 3 )
{
    return 1;
}
gdcm::DataElement pixeldata( gdcm::Tag(0x7fe0,0x0010) );
pixeldata.SetByteValue( buffer, (uint32_t)l );
delete[] buffer;
im->SetDataElement( pixeldata );

gdcm::UIDGenerator uid; // helper for uid generation

gdcm::SmartPointer<gdcm::File> file = new
    gdcm::File; // empty file

// Step 2: DERIVED object
gdcm::FileDerivation fd;
// For the purpose of this exercise we will pretend that this image is referencing
// two source image (we need to generate fake UID for that).
const char ReferencedSOPClassUID[] = "1.2.840.10008.5.1.4.1.1.7"; // Secondary Capture
fd.AddReference( ReferencedSOPClassUID, uid.Generate() );
fd.AddReference( ReferencedSOPClassUID, uid.Generate() );

// Again for the purpose of the exercise we will pretend that the image is a
// multiplanar reformat (MPR):
// CID 7202 Source Image Purposes of Reference
// {"DCM",121322,"Source image for image processing operation"},
fd.SetPurposeOfReferenceCodeSequenceCodeValue( 121322 );
// CID 7203 Image Derivation
// { "DCM",113072,"Multiplanar reformatting" },
fd.SetDerivationCodeSequenceCodeValue( 113072 );
fd.SetFile( *file );
// If all Code Value are ok the filter will execute properly
if( !fd.Derive() )
{
    std::cerr << "Sorry could not derive using input info" << std::endl;
    return 1;
}

// We pass both :
// 1. the fake generated image
// 2. the 'DERIVED' dataset object
// to the writer.
gdcm::ImageWriter w;
w.SetImage( *im );
w.SetFile( fd.GetFile() );

// Set the filename:
w.SetFileName( "ybr2.dcm" );
if( !w.Write() )
{
    return 1;
}

```

```

    }
    return 0;
}

```

27.68 GenLongSeqs.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcml.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/
#include "gdcmlReader.h"
#include "gdcmlWriter.h"
#include "gdcmlItem.h"
#include "gdcmlImageReader.h"
#include "gdcmlSequenceOfItems.h"
#include "gdcmlFile.h"
#include "gdcmlTag.h"

/*
 * This example is used to generate the file:
 *
 *
 * There is a flaw in the DICOM design where it is assumed that Sequence can be
 * either represented as undefined length or defined length. This should work
 * in most case, but the undefined length is a little more general and can
 * store sequence of items that a defined length cannot.
 * We need to make sure that we can store numerous Item in a SQ
 *
 * Warning: do not try to compute the group length elements !
 * Warning: You may need a 64bits machine for this example to work.
 */
int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];
    gdcml::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        return 1;
    }

    gdcml::File &file = reader.GetFile();
    gdcml::DataSet &ds = file.GetDataSet();

    // Create a Sequence
    gdcml::SmartPointer<gdcml::SequenceOfItems> sq = new
        gdcml::SequenceOfItems();
    sq->SetLengthToUndefined();

    const char owner_str[] = "GDCM CONFORMANCE TESTS";
    gdcml::DataElement owner( gdcml::Tag(0x4d4d, 0x10) );
    owner.SetByteValue( owner_str, (uint32_t)strlen(owner_str));
    owner.SetVR( gdcml::VR::LO );

    size_t nitems = 1000;
    nitems += std::numeric_limits<uint32_t>::max();
    for( unsigned int idx = 0; idx < nitems; ++idx )
    {
        // Create a dataelement
        //gdcml::DataElement de( gdcml::Tag(0x4d4d, 0x1002) );
        //de.SetByteValue(ptr, ptr_len);

```

```

    //de.SetVR( gdcmm::VR::OB );

    // Create an item
    gdcmm::Item it;
    it.SetVLToUndefined();
    //gdcmm::DataSet &nds = it.GetNestedDataSet();
    //nds.Insert(owner);
    //nds.Insert(de);

    sq->AddItem(it);
}

// Insert sequence into data set
gdcmm::DataElement des( gdcmm::Tag(0x4d4d,0x1001) );
des.SetVR(gdcmm::VR::SQ);
des.SetValue(*sq);
des.SetVLToUndefined();

ds.Insert(owner);
ds.Insert(des);

gdcmm::Writer w;
w.SetFile( file );
//w.SetCheckFileMetaInformation( true );
w.SetFileName( outfilename );
if (!w.Write() )
{
    return 1;
}

return 0;
}

```

27.69 GenSeqs.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmmReader.h"
#include "gdcmmWriter.h"
#include "gdcmmItem.h"
#include "gdcmmImageReader.h"
#include "gdcmmSequenceOfItems.h"
#include "gdcmmFile.h"
#include "gdcmmTag.h"

/*
 * This example is used to generate the file:
 *
 * gdcmmConformanceTests/SequenceWithUndefinedLengthNotConvertibleToDefinedLength.dcm
 *
 * There is a flaw in the DICOM design where it is assumed that Sequence can be
 * either represented as undefined length or defined length. This should work
 * in most case, but the undefined length is a little more general and can
 * store sequence of items that a defined length cannot.
 * Deflated syntax was used in this case since this synthetic example can be
 * nicely compressed using this transfer syntax.
 *
 * Warning: do not try to compute the group length elements !
 * Warning: You may need a 64bits machine for this example to work.
 */
int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.dcm" << std::endl;
        return 1;
    }
}

```

```

    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];
    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        return 1;
    }

    gdcm::File &file = reader.GetFile();
    gdcm::DataSet &ds = file.GetDataSet();

    //const unsigned int nitems = 1000;
    const unsigned int ptr_len = 42; /*94967296 / nitems; */
    //assert( ptr_len == 42949672 );
    char *ptr = new char[ptr_len];
    memset(ptr,0,ptr_len);

    // Create a Sequence
    gdcm::SmartPointer<gdcm::SequenceOfItems> sq = new
        gdcm::SequenceOfItems();
    sq->SetLengthToUndefined();

    const char owner_str[] = "GDCM CONFORMANCE TESTS";
    gdcm::DataElement owner( gdcm::Tag(0x4d4d, 0x10) );
    owner.SetByteValue( owner_str, (uint32_t)strlen(owner_str));
    owner.SetVR( gdcm::VR::LO );

    for(unsigned int idx = 0; idx < 10/* nitems*/; ++idx)
    {
        // Create a dataelement
        gdcm::DataElement de( gdcm::Tag(0x4d4d, 0x1002) );
        de.SetByteValue(ptr, ptr_len);
        de.SetVR( gdcm::VR::OB );

        // Create an item
        gdcm::Item it;
        it.SetVLToUndefined();
        gdcm::DataSet &nds = it.GetNestedDataSet();
        nds.Insert( owner );
        nds.Insert( de );

        sq->AddItem(it);
    }

    // Insert sequence into data set
    gdcm::DataElement des( gdcm::Tag(0x4d4d,0x1001) );
    des.SetVR(gdcm::VR::SQ);
    des.SetValue(*sq);
    des.SetVLToUndefined();

    ds.Insert( owner );
    ds.Insert( des );

    gdcm::Writer w;
    w.SetFile( file );
    //w.SetCheckFileMetaInformation( true );
    w.SetFileName( outfile );
    if ( !w.Write() )
    {
        return 1;
    }

    return 0;
}

```

27.70 GetArray.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

```

This software is distributed WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the above copyright notice for more information.

```

=====*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/GetArray.exe gdcmData/012345.002.050.dcm
 */
using System;
using gdcm;

public class GetArray
{
    public static int Main(string[] args)
    {
        string file1 = args[0];
        ImageReader reader = new ImageReader();
        reader.SetFileName( file1 );
        bool ret = reader.Read();
        if( !ret )
        {
            return 1;
        }

        Image image = reader.GetImage();

        PixelFormat pixeltype = image.GetPixelFormat();

        if( image.GetNumberOfDimensions() != 2 )
        {
            // For the purpose of the test, exit early on
            return 1;
        }
        uint dimx = image.GetDimension(0);
        uint dimy = image.GetDimension(1);
        uint npixels = dimx * dimy;
        //LookupTable lut = image.GetLUT();
        //uint r1 = lut.GetLUTLength( LookupTable.LookupTableType.RED );
        //byte[] rbuf = new byte[ r1 ];
        //uint r12 = lut.GetLUT( LookupTable.LookupTableType.RED, rbuf );
        //assert r1 == r12;

        //byte[] str1 = new byte[ image.GetBufferLength()];
        //image.GetBuffer( str1 );
        if( pixeltype.GetScalarType() == PixelFormat.ScalarType.UINT8 )
        {
            System.Console.WriteLine( "Processing UINT8 image type" );
            byte[] str1 = new byte[ npixels ];
            image.GetArray( str1 );
        }
        else if( pixeltype.GetScalarType() == PixelFormat.ScalarType.INT16 )
        {
            System.Console.WriteLine( "Processing INT16 image type" );
            short[] str1 = new short[ npixels ];
            image.GetArray( str1 );
        }
        else if( pixeltype.GetScalarType() == PixelFormat.ScalarType.UINT16 )
        {
            System.Console.WriteLine( "Processing UINT16 image type" );
            ushort[] str1 = new ushort[ npixels ];
            image.GetArray( str1 );
        }
        else
        {
            //System.Console.WriteLine( "Default (unhandled pixel format): " + pixeltype.toString() );
            System.Console.WriteLine( "Default (unhandled pixel format): " + pixeltype.GetScalarTypeAsString() );
            // Get bytes
            byte[] str1 = new byte[ image.GetBufferLength()];
            image.GetBuffer( str1 );
        }

        return 0;
    }
}

```

27.71 GetJPEGSamplePrecision.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * This example is a little helper to detect the famous SIEMENS JPEG lossless compressed image
 * where DICOM is declared as:
 *
 * (0028,0100) US 16 # 2,1 Bits Allocated
 * (0028,0101) US 12 # 2,1 Bits Stored
 * (0028,0102) US 11 # 2,1 High Bit
 * (0028,0103) US 0 # 2,1 Pixel Representation
 *
 * But where JPEG is:
 *
 * JPEG_SOF_Parameters:
 * SamplePrecision = 16
 * nLines = 192
 * nSamplesPerLine = 192
 * nComponentsInFrame = 1
 * component 0
 * ComponentIdentifier = 1
 * HorizontalSamplingFactor = 1
 * VerticalSamplingFactor = 1
 * QuantizationTableDestinationSelector = 0
 *
 * This case is valid. One simply has to use the 16bits jpeg decoder to decode the 12bits stored image.
 * This used to be an issue in GDCM 1.2.x (fixed in GDCM 1.2.5)
 *
 * The main return 0 (no error) when the file read is actually a potential problem. At the end of the main
 * function, the jpeg stream is stored in the filename specified as second argument
 */

#include "gdcmImageReader.h"
#include "gdcmSequenceOfFragments.h"
#include "gdcmJPEGCodec.h"

#include <iostream>
#include <fstream>

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.jpg" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];

    gdcm::ImageReader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Could not read: " << filename << std::endl;
        return 1;
    }

    // The output of gdcm::Reader is a gdcm::File
    const gdcm::File &file = reader.GetFile();
    const gdcm::Image &image = reader.GetImage();

    const gdcm::TransferSyntax &ts = file.GetHeader().
        GetDataSetTransferSyntax();

    if( ts != gdcm::TransferSyntax::JPEGLosslessProcess14 && ts !=
        gdcm::TransferSyntax::JPEGLosslessProcess14_1 )
    {

```

```

    std::cerr << "Input is not a lossless JPEG" << std::endl;
    return 1;
}

// the dataset is the the set of element we are interested in:
const gdcm::DataSet &ds = file.GetDataSet();

const gdcm::Tag rawTag(0x7fe0, 0x0010); // Default to Pixel Data
const gdcm::DataElement& pdde = ds.GetDataElement( rawTag );
const gdcm::SequenceOfFragments *sf = pdde.
    GetSequenceOfFragments();
if( sf )
{
    std::ofstream output(outfilename, std::ios::binary);
    sf->WriteBuffer(output);
}
else
{
    std::cerr << "Error" << std::endl;
    return 1;
}

gdcm::JPEGCodec jpeg;
std::ifstream is(outfilename);
gdcm::PixelFormat pf ( gdcm::PixelFormat::UINT8 ); // let's
    pretend it's a 8bits jpeg
jpeg.SetPixelFormat( pf );
gdcm::TransferSyntax ts_jpg;
bool b = jpeg.GetHeaderInfo( is, ts_jpg );
if( !b )
{
    return 1;
}

//jpeg.Print( std::cout );
if( jpeg.GetPixelFormat().GetBitsAllocated() != image.
    GetPixelFormat().GetBitsAllocated()
|| jpeg.GetPixelFormat().GetBitsStored() != image.
    GetPixelFormat().GetBitsStored() )
{
    std::cerr << "There is a mismatch in between DICOM declared Pixel Format and Sample Precision used in
        the JPEG stream" << std::endl;
    return 0;
}

std::cout << jpeg.GetPixelFormat() << std::endl;
std::cout << image.GetPixelFormat() << std::endl;

return 1;
}

```

27.72 GetPortionCSAHeader.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:
17
18     python GetPortionCSAHeader.py input.dcm
19
20 Footnote:
21     SIEMENS is not publishing any information on the CSA header. So any info extracted
22     is at your own risk.
23 """
24

```



```

25 import sys
26 import gdcm
27
28 if __name__ == "__main__":
29
30     file = sys.argv[1]
31
32     r = gdcm.Reader()
33     r.SetFileName( file )
34     if not r.Read():
35         sys.exit(1)
36
37     ds = r.GetFile().GetDataSet()
38     csa_t1 = gdcm.CSAHeader()
39     csa_t2 = gdcm.CSAHeader()
40     #print csa
41     t1 = csa_t1.GetCSAImageHeaderInfoTag();
42     print t1
43     t2 = csa_t2.GetCSASeriesHeaderInfoTag();
44     print t2
45     # Let's do it for t1:
46     if ds.FindDataElement( t1 ):
47         csa_t1.LoadFromDataElement( ds.GetDataElement( t1 ) )
48         print csa_t1
49
50     # Now let's pretend we are only interested in B_value and DiffusionGradientDirection entries:
51     bvalues = csa_t1.GetCSAElementByName( "B_value" ) # WARNING: it is case sensitive !
52     print bvalues
53
54     diffgraddir = csa_t1.GetCSAElementByName( "DiffusionGradientDirection" ) # WARNING: it is case sensitive
55     !
56     print diffgraddir
57
58     # repeat for t2 if you like it:
59     if ds.FindDataElement( t2 ):
60         csa_t2.LoadFromDataElement( ds.GetDataElement( t2 ) )
61         # print csa_t2
62
63     gdt = csa_t2.GetCSAElementByName( "GradientDelayTime" )
64     print gdt
65
66     bv = gdt.GetByteValue();
67     #print bv
68     str = bv.GetPointer()
69     print str.split("\\")

```

27.73 GetSequenceUltrasound.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmReader.h"
#include "gdcmAttribute.h"

bool Region ( char* nomefile, unsigned int* X_min, unsigned int* Y_min, unsigned int* X_max, unsigned int*
Y_max );

int main(int argc, char* argv[] )
{
    // Controllo del numero di argomenti introdotti da riga di comando
    if( argc < 2 )
    {
        std::cerr << "Usage: " << std::endl;
        std::cerr << argv[0] << " inputImageFile " << std::endl;
        return EXIT_FAILURE;
    }
}

```

```

unsigned int x_min = 1;
unsigned int y_min = 1;
unsigned int x_max = 1;
unsigned int y_max = 1;

if( Region ( argv[1], &x_min, &y_min, &x_max, &y_max ) )
{
    std::cout << "x_min = " << x_min << std::endl;
    std::cout << "y_min = " << y_min << std::endl;
    std::cout << "x_max = " << x_max << std::endl;
    std::cout << "y_max = " << y_max << std::endl;
}

else
{
    std::cout << "no\n";
}

}

bool Region ( char* nomefile, unsigned int* X_min, unsigned int* Y_min, unsigned int* X_max, unsigned int*
    Y_max )
{
    gdcmm::Reader reader;
    reader.SetFileName( nomefile );
    if( !reader.Read() )
    {
        std::cerr << "Could not read: " << nomefile << std::endl;
        return false;
    }

    gdcmm::File &file = reader.GetFile();
    gdcmm::DataSet &ds = file.GetDataSet();

    gdcmm::Tag tsqr(0x0018,0x6011);
    if( !ds.FindDataElement( tsqr ) )
    {
        return false;
    }

    const gdcmm::DataElement &sqr= ds.GetDataElement( tsqr );
    //std::cout << sqr << std::endl;
    const gdcmm::SequenceOfItems *sqi = sqr.GetValueAssSQ();
    if( !sqi || !sqi->GetNumberOfItems() )
    {
        return false;
    }
    //std::cout << sqi << std::endl;

    const gdcmm::Item &item = sqi->GetItem(1);
    //std::cout << item << std::endl;
    const gdcmm::DataSet& nestedds = item.GetNestedDataSet();
    //std::cout << nestedds << std::endl;

    gdcmm::Tag tX0(0x0018,0x6018);
    gdcmm::Tag tY0(0x0018,0x601a);
    gdcmm::Tag tX1(0x0018,0x601c);
    gdcmm::Tag tY1(0x0018,0x601e);

    if( (!nestedds.FindDataElement( tX0 ))||(!nestedds.
        FindDataElement( tY0 ))||(!nestedds.FindDataElement( tX1 ))||(!nestedds.
        FindDataElement( tY1 )) )
    {
        return false;
    }

    const gdcmm::DataElement& deX0 = nestedds.GetDataElement( tX0 );
    const gdcmm::DataElement& deY0 = nestedds.GetDataElement( tY0 );
    const gdcmm::DataElement& deX1 = nestedds.GetDataElement( tX1 );
    const gdcmm::DataElement& deY1 = nestedds.GetDataElement( tY1 );
    //std::cout << deX0 << std::endl << deY0 << std::endl << deX1 << std::endl << deY1 << std::endl;

    //const gdcmm::ByteValue *bvX0 = deX0.GetByteValue();
    //const gdcmm::ByteValue *bvY0 = deY0.GetByteValue();
    //const gdcmm::ByteValue *bvX1 = deX1.GetByteValue();
    //const gdcmm::ByteValue *bvY1 = deY1.GetByteValue();
    //std::cout << bvX0 << std::endl << bvY0 << std::endl << bvX1 << std::endl << bvY1 << std::endl;

    gdcmm::Attribute<0x0018,0x6018> atX0;
    gdcmm::Attribute<0x0018,0x601a> atY0;

```

```

gdcmm::Attribute<0x0018,0x601c> atX1;
gdcmm::Attribute<0x0018,0x601e> atY1;
atX0.SetFromDataElement( deX0 );
atY0.SetFromDataElement( deY0 );
atX1.SetFromDataElement( deX1 );
atY1.SetFromDataElement( deY1 );
uint32_t X0 = atX0.GetValue();
uint32_t Y0 = atY0.GetValue();
uint32_t X1 = atX1.GetValue();
uint32_t Y1 = atY1.GetValue();
std::cout << X0 << std::endl << Y0 << std::endl << X1 << std::endl << Y1 << std::endl;

*X_min = static_cast<unsigned int>(X0);
*Y_min = static_cast<unsigned int>(Y0);
*X_max = static_cast<unsigned int>(X1);
*Y_max = static_cast<unsigned int>(Y1);

//std::cout << "X_min = " << *X_min << std::endl;
//std::cout << "Y_min = " << *Y_min << std::endl;
//std::cout << "X_max = " << *X_max << std::endl;
//std::cout << "Y_max = " << *Y_max << std::endl;

return true;
}

```

27.74 GetSubSequenceData.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmReader.h"
#include "gdcmImage.h"
#include "gdcmImageWriter.h"
#include "gdcmDataElement.h"
#include "gdcmPrivateTag.h"
#include "gdcmUIDGenerator.h"

#include <iostream>
#include <string>

#include <map>

/*
 * This example will extract the Movie from the private group of
 * GEMS_Ultrasound_MovieGroup_001 See Attribute
 * (7fel,60,GEMS_Ultrasound_MovieGroup_001)
 *
 * The output file will be stored in 'outvid.dcm' as
 * MultiframeGrayscaleByteSecondaryCaptureImageStorage
 */
int main(int argc, char *argv[])
{
    if( argc < 2 ) return 1;
    using namespace gdcm;
    const char *filename = argv[1];
    gdcm::Reader reader;
    reader.SetFileName( filename );
    reader.Read();

    gdcm::File &file = reader.GetFile();
    gdcm::DataSet &ds = file.GetDataSet();
    const PrivateTag tseq(0x7fel,0x1,"GEMS_Ultrasound_MovieGroup_001");

    if( !ds.FindDataElement( tseq ) ) return 1;
    const DataElement& seq = ds.GetDataElement( tseq );

    SmartPointer<SequenceOfItems> sqi = seq.GetValueAsSQ();

```

```

assert( sqi->GetNumberOfItems() == 1 );
Item &item = sqi->GetItem(1);
DataSet &subds = item.GetNestedDataSet();

const PrivateTag tseq1(0x7fel,0x10,"GEMS_Ultrasound_MovieGroup_001");

if( !subds.FindDataElement( tseq1 ) ) return 1;
const DataElement& seq1 = subds.GetDataElement( tseq1 );

SmartPointer<SequenceOfItems> sqi2 = seq1.GetValueAsSQ();
//int n = sqi2->GetNumberOfItems();
int index = 1;
Item &item2 = sqi2->GetItem(index);
DataSet &subds2 = item2.GetNestedDataSet();

const PrivateTag tseq2(0x7fel,0x20,"GEMS_Ultrasound_MovieGroup_001");

if( !subds2.FindDataElement( tseq2 ) ) return 1;
const DataElement& seq2 = subds2.GetDataElement( tseq2 );

//      std::cout << seq2 << std::endl;

SmartPointer<SequenceOfItems> sqi3 = seq2.GetValueAsSQ();
size_t ni3 = sqi3->GetNumberOfItems(); (void)ni3;
assert( sqi3->GetNumberOfItems() >= 1 );
Item &item3 = sqi3->GetItem(1);
DataSet &subds3 = item3.GetNestedDataSet();

const PrivateTag tseq6(0x7fel,0x26,"GEMS_Ultrasound_MovieGroup_001");
if( !subds3.FindDataElement( tseq6 ) ) return 1;
const DataElement& seq6 = subds3.GetDataElement( tseq6 );
SmartPointer<SequenceOfItems> sqi6 = seq6.GetValueAsSQ();
size_t ni6= sqi6->GetNumberOfItems();
assert( sqi6->GetNumberOfItems() >= 1 );
const PrivateTag tseq7(0x7fel,0x86,"GEMS_Ultrasound_MovieGroup_001");
int dimx = 0, dimy = 0;
for( size_t i6 = 1; i6 <= ni6; ++i6 )
{
    Item &item6 = sqi6->GetItem(i6);
    DataSet &subds6 = item6.GetNestedDataSet();

    if( subds6.FindDataElement( tseq7 ) )
    {
        Element<VR::SL, VM::VM4> el;
        el.SetFromDataElement( subds6.GetDataElement( tseq7 ) );
        std::cout << "El= " << el.GetValue() << std::endl;
        dimx = el.GetValue(0);
        dimy = el.GetValue(1);
    }
}

const PrivateTag tseq3(0x7fel,0x36,"GEMS_Ultrasound_MovieGroup_001");
if( !subds3.FindDataElement( tseq3 ) ) return 1;
const DataElement& seq3 = subds3.GetDataElement( tseq3 );

//      std::cout << seq3 << std::endl;

SmartPointer<SequenceOfItems> sqi4 = seq3.GetValueAsSQ();
size_t ni4= sqi4->GetNumberOfItems();
assert( sqi4->GetNumberOfItems() >= 1 );
const PrivateTag tseq8(0x7fel,0x37,"GEMS_Ultrasound_MovieGroup_001");
const PrivateTag tseq4(0x7fel,0x43,"GEMS_Ultrasound_MovieGroup_001");
const PrivateTag tseq5(0x7fel,0x60,"GEMS_Ultrasound_MovieGroup_001");

std::vector<char> imbuffer;
int dimz = 0;
for( size_t i4 = 1; i4 <= ni4; ++i4 )
{
    Item &item4 = sqi4->GetItem(i4);
    DataSet &subds4 = item4.GetNestedDataSet();

    if( !subds4.FindDataElement( tseq8 ) ) return 1;
    const DataElement& de8 = subds4.GetDataElement( tseq8 );
    Element<VR::UL, VM::VM1> ldimz;
    ldimz.SetFromDataElement( de8 );
    dimz += ldimz.GetValue();
    if( !subds4.FindDataElement( tseq4 ) ) return 1;
    const DataElement& seq4 = subds4.GetDataElement( tseq4 );
    if( !subds4.FindDataElement( tseq5 ) ) return 1;
    const DataElement& seq5 = subds4.GetDataElement( tseq5 );

```

```

//      std::cout << seq4 << std::endl;
//      std::cout << seq5 << std::endl;

const ByteValue *bv4 = seq4.GetByteValue();
(void)bv4;
#ifdef 0
{
    std::ofstream out( "/tmp/mo4" );
    out.write( bv4->GetPointer(), bv4->GetLength());
    out.close();
}
#endif
const ByteValue *bv5 = seq5.GetByteValue();
#ifdef 0
{
    std::ofstream out( "/tmp/mo5" );
    out.write( bv5->GetPointer(), bv5->GetLength());
    out.close();
}
#endif

std::cout << bv5->GetLength() << std::endl;
imbuffer.insert( imbuffer.begin(), bv5->GetPointer(), bv5->
    GetPointer() + bv5->GetLength() );
}
DataElement fakedata;
fakedata.SetByteValue( &imbuffer[0], (uint32_t)imbuffer.size() );

gdcm::SmartPointer<gdcm::Image> im = new
    gdcm::Image;
im->SetNumberOfDimensions( 3 );

im->SetDimension(0, dimx );
im->SetDimension(1, dimy );
im->SetDimension(2, dimz );
size_t l1 = imbuffer.size();
(void)l1;
size_t l2 = im->GetBufferLength();
(void)l2;
assert( im->GetBufferLength() == imbuffer.size() );
im->SetPhotometricInterpretation( gdcm::PhotometricInterpretation::MONOCHROME2
    );

im->SetDataElement( fakedata );

gdcm::ImageWriter w;
w.SetImage( *im );
DataSet &dataset = w.GetFile().GetDataSet();

gdcm::UIDGenerator uid;
gdcm::DataElement de( Tag(0x8,0x18) ); // SOP Instance UID
de.SetVR( VR::UI );
const char *u = uid.Generate();
de.SetByteValue( u, (uint32_t)strlen(u) );
//ds.Insert( de );
dataset.Replace( de );

de.SetTag( Tag(0x8,0x16) ); // SOP Class UID
de.SetVR( VR::UI );
gdcm::MediaStorage ms(
    gdcm::MediaStorage::MultiframeGrayscaleByteSecondaryCaptureImageStorage
    );
de.SetByteValue( ms.GetString(), (uint32_t)strlen(ms.
    GetString()));
dataset.Replace( de ); // replace !

w.SetFileName( "outvid.dcm" );
if( !w.Write() )
{
    return 1;
}

return 0;
}

```

27.75 headsq2dcm.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #       This software is distributed WITHOUT ANY WARRANTY; without even
10 #       the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #       PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:
17 python headsq2dcm.py -D /path/to/VTKData
18 """
19
20 import vtk
21 import vtkgdcm
22 from vtk.util.misc import vtkGetDataRoot
23 VTK_DATA_ROOT = vtkGetDataRoot()
24
25 reader = vtk.vtkVolume16Reader()
26 reader.SetDataDimensions(64, 64)
27 reader.SetDataByteOrderToLittleEndian()
28 reader.SetFilePrefix(VTK_DATA_ROOT + "/Data/headsq/quarter")
29 reader.SetImageRange(1, 93)
30 reader.SetDataSpacing(3.2, 3.2, 1.5)
31
32 cast = vtk.vtkImageCast()
33 cast.SetInput( reader.GetOutput() )
34 cast.SetOutputScalarTypeToUnsignedChar()
35
36 # By default this is creating a Multiframe Grayscale Word Secondary Capture Image Storage
37 writer = vtkgdcm.vtkGDCMImageWriter()
38 writer.SetFileName( "headsq.dcm" )
39 writer.SetInput( reader.GetOutput() )
40 # cast -> Multiframe Grayscale Byte Secondary Capture Image Storage
41 #writer.SetInput( cast.GetOutput() )
42 writer.SetFileDimensionality( 3 )
43 writer.Write()

```

27.76 HelloActiviz.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

    This software is distributed WITHOUT ANY WARRANTY; without even
    the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
    PURPOSE. See the above copyright notice for more information.

=====*/
using vtkgdcm;
using Kitware.VTK;
using System;
using System.Runtime.InteropServices;

/*
 * This example shows how vtkgdcm can be connected to Kitware.VTK Activiz product.
 * Three (3) arguments are required:
 * 1. Input DICOM file           (SWIG)
 * 2. Temporary PNG (intermediate) file (Activiz)
 * 3. Final DICOM file           (SWIG)
 *
 * $ export MONO_PATH=/usr/lib/cli/Activiz.NET:/usr/lib/cli/Kitware.mummy.Runtime-1.0
 * $ mono ./bin/HelloActiviz.exe ~/Creatis/gdcmData/test.acr out.png toto.dcm
 */

```

```

* Footnote:
* this test originally used vtkBMPWriter / vtkBMPReader combination to store intermediate
* image file, but BMP file are 24bits by default. Instead use PNG format which supports seems
* to be closer to what was expected in this simple test.
*/
public class HelloActiviz
{
    // Does not work with Activiz.NET-5.4.0.455-Linux-x86_64-Personal
    /*
    static void ConnectSWIGToActiviz(Kitware.VTK.vtkImageExport imgin, Kitware.VTK.vtkImageImport imgout)
    {
        imgout.SetUpdateInformationCallback(imgin.GetUpdateInformationCallback());
        imgout.SetPipelineModifiedCallback(imgin.GetPipelineModifiedCallback());
        imgout.SetWholeExtentCallback(imgin.GetWholeExtentCallback());
        imgout.SetSpacingCallback(imgin.GetSpacingCallback());
        imgout.SetOriginCallback(imgin.GetOriginCallback());
        imgout.SetScalarTypeCallback(imgin.GetScalarTypeCallback());
        imgout.SetNumberOfComponentsCallback(imgin.GetNumberOfComponentsCallback());
        imgout.SetPropagateUpdateExtentCallback(imgin.GetPropagateUpdateExtentCallback());
        imgout.SetUpdateDataCallback(imgin.GetUpdateDataCallback());
        imgout.SetDataExtentCallback(imgin.GetDataExtentCallback());
        imgout.SetBufferPointerCallback(imgin.GetBufferPointerCallback());
        imgout.SetCallbackUserData(imgin.GetCallbackUserData());
    }
    */

    static Kitware.VTK.vtkImageData ConnectSWIGToActiviz(vtkgdc.vtkImageData imgin)
    {
        HandleRef rawCppThis = imgin.GetCppThis();
        Kitware.VTK.vtkImageData imgout = new Kitware.VTK.vtkImageData( rawCppThis.Handle, false, false);
        return imgout;
    }

    static vtkgdc.vtkImageData ConnectActivizToSWIG(Kitware.VTK.vtkImageData imgin)
    {
        HandleRef rawCppThis = imgin.GetCppThis();
        vtkgdc.vtkImageData imgout = new vtkgdc.vtkImageData( rawCppThis );
        return imgout;
    }

    public static int Main(string[] args)
    {
        string filename = args[0];
        string outfilename = args[1];

        // Step 1. Test SWIG -> Activiz
        vtkGDCMImageReader reader = vtkGDCMImageReader.
            New();
        reader.SetFileName( filename );
        //reader.Update(); // DO NOT call Update to check pipeline execution

        Kitware.VTK.vtkImageData imgout = ConnectSWIGToActiviz(reader.GetOutput());

        System.Console.WriteLine( imgout.ToString() ); // not initialized as expected

        vtkPNGWriter writer = new vtkPNGWriter();
        writer.SetInput( imgout );
        writer.SetFileName( outfilename );
        writer.Write();

        // Step 2. Test Activiz -> SWIG
        vtkPNGReader bmpreader = new vtkPNGReader();
        bmpreader.SetFileName( outfilename );
        //bmpreader.Update(); // DO NOT update to check pipeline execution

        System.Console.WriteLine( bmpreader.GetOutput().ToString() ); // not initialized as expected

        vtkgdc.vtkImageData imgout2 = ConnectActivizToSWIG(bmpreader.GetOutput());

        System.Console.WriteLine( imgout2.ToString() ); // not initialized as expected

        Kitware.VTK.vtkMedicalImageProperties prop = new Kitware.VTK.vtkMedicalImageProperties();
        prop.SetModality( "MR" );

        string outfilename2 = args[2];
        vtkGDCMImageWriter writer2 = vtkGDCMImageWriter.
            New();
        writer2.SetMedicalImageProperties( prop.CastToActiviz() );
        writer2.SetFileName( outfilename2 );
    }
}

```

```

        writer2.SetInput( imgout2 );
        writer2.Write();

        return 0;
    }
}

```

27.77 HelloActiviz2.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/
using Kitware.VTK;
using Kitware.VTK.GDCM;

/*
 * Usage:
 * $ export MONO_PATH=/usr/lib/cli/Activiz.NET:/usr/lib/cli/Kitware.mummy.Runtime-1.0
 * $ mono ./bin/HelloActiviz2.exe gdcData/test.acr bla.png bla2.dcm
 */

/*
 * From the outside view, no-one can detect that object pass to/from
 * vtkGDCMImageWriter/vtkGDCMImageReader are not Activiz object.
 *
 * TODO: Test Command/Observer
 */
public class HelloActiviz2
{
    public static int Main(string[] args)
    {
        string filename = args[0];
        string outfilename = args[1];
        string outfilename2 = args[2];

        vtkGDCMImageReader reader = new Kitware.VTK.GDCM.
            vtkGDCMImageReader();
        reader.SetFileName( filename );

        // When calling multiple times creation of C# object from the same C++ object it triggers a:
        //error: potential refcounting error: Duplicate rawCppThis - weak reference that is still alive. Attempting
        //to add '0x00b2dc10' again.
        //    Allowing new wrapped object to take over table key...
        //    Original object should *not* have been destroyed while we still had it in our table without
        //    notifying us...
        //reader.GetOutput();
        //reader.GetOutput();

        System.Console.WriteLine( reader.ToString() ); // Test the ToString compat with Activiz

        vtkGDCMImageWriter writer = new vtkGDCMImageWriter();
        writer.SetInput( reader.GetOutput() );
        writer.SetFileName( outfilename2 );
        writer.Write();

        System.Console.WriteLine( reader.GetOutput().ToString() ); // Test the ToString compat with Activiz

        System.Console.WriteLine( writer.ToString() ); // Test the ToString compat with Activiz

        vtkPNGWriter pngwriter = new vtkPNGWriter();
        pngwriter.SetInput( reader.GetOutput() );
        pngwriter.SetFileName( outfilename );
        pngwriter.Write();

        // at that point the .Write() should have triggered an Update() on the reader:
        if( reader.GetImageFormat() == vtkgdcm.VTK_LUMINANCE ) // MONOCHROME2
        {

```



```

        System.Console.WriteLine( "Image is MONOCHROME2" ); //
    }

    vtkPNGReader bmpreader = new vtkPNGReader();
    bmpreader.SetFileName( outfilename );

    vtkMedicalImageProperties prop = new vtkMedicalImageProperties();
    prop.SetModality( "MR" );

    vtkMatrix4x4 dircos = reader.GetDirectionCosines();
    dircos.Invert();

    vtkGDCMImageWriter writer2 = new vtkGDCMImageWriter();
    writer2.SetFileName( outfilename2 );
    writer2.SetDirectionCosines( dircos );
    writer2.SetMedicalImageProperties( prop );
    writer2.SetInput( bmpreader.GetOutput() );
    writer2.Write();

    return 0;
}

```

27.78 HelloActiviz3.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/
using Kitware.VTK;
using Kitware.VTK.GDCM;

/*
 * $ export MONO_PATH=/usr/lib/cli/Activiz.NET:/usr/lib/cli/Kitware.mummy.Runtime-1.0
 * $ mono ./bin/HelloActiviz3.exe ~/Creatis/gdcmData/test.acr
 */
public class HelloActiviz3
{
    public static int Main(string[] args)
    {
        string filename = args[0];

        vtkGDCMImageReader reader = vtkGDCMImageReader.
            New();
        vtkStringArray array = vtkStringArray.New();
        array.InsertNextValue(filename);

        reader.SetFileNames(array);
        reader.Update();

        //System.Console.Write(reader.GetOutput());

        vtkRenderWindowInteractor iren = vtkRenderWindowInteractor.New();

        vtkImageViewer2 viewer = vtkImageViewer2.New();
        viewer.SetInput(reader.GetOutput());
        viewer.SetupInteractor(iren);
        viewer.SetSize(600, 600);
        viewer.Render();

        iren.Initialize();
        iren.Start();

        return 0;
    }
}

```

27.79 HelloActiviz4.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcms.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
using Kitware.VTK;
using Kitware.VTK.GDCM;

/*
 * $ export MONO_PATH=/usr/lib/cli/Activiz.NET:/usr/lib/cli/Kitware.mummy.Runtime-1.0
 * $ mono ./bin/HelloActiviz4.exe ~/Creatis/gdcmData/test.acr
 */
public class HelloActiviz4
{
    public static int Main(string[] args)
    {
        string filename = args[0];

        vtkGDCMImageReader reader = new vtkGDCMImageReader();
        vtkStringArray array = vtkStringArray.New();
        array.InsertNextValue(filename);

        reader.SetFileNames(array);
        reader.Update();

        //System.Console.WriteLine(reader.GetOutput());

        vtkRenderWindowInteractor iren = vtkRenderWindowInteractor.New();

        vtkImageViewer viewer = vtkImageViewer.New();
        viewer.SetInput(reader.GetOutput());
        viewer.SetupInteractor(iren);
        viewer.SetSize(600, 600);
        viewer.Render();

        iren.Initialize();
        iren.Start();

        return 0;
    }
}

```

27.80 HelloActiviz5.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcms.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
using Kitware.VTK;
using Kitware.VTK.GDCM;

// The command line arguments are:
// -I      => run in interactive mode; unless this is used, the program will
//          not allow interaction and exit
// -D <path> => path to the data; the data should be in <path>/Data/

/*

```

```

* $ export MONO_PATH=/usr/lib/cli/Activiz.NET:/usr/lib/cli/Kitware.mummy.Runtime-1.0
* $ mono ./bin/HelloActiviz5.exe -I
*/
public class HelloActiviz5
{
    public static int Main(string[] args)
    {
        vtkTesting testHelper = vtkTesting.New();
        for ( int cc = 0; cc < args.Length; cc++ )
        {
            //testHelper.AddArguments(argc, const_cast<const char **>(argv));
            //System.Console.Write( "args: " + args[cc] + "\n" );
            testHelper.AddArgument( args[cc] );
        }
        if ( testHelper.IsFlagSpecified("-D") != 0 )
        {
            string VTK_DATA_ROOT = vtkGDCMTesting.GetVTKDataRoot();
            if( VTK_DATA_ROOT != null )
            {
                //System.Console.Write( "VTK_DATA_ROOT: " + VTK_DATA_ROOT + "\n" );
                testHelper.SetDataRoot(VTK_DATA_ROOT);
                testHelper.AddArgument("-D");
                testHelper.AddArgument(VTK_DATA_ROOT);
            }
        }

        string dataRoot = testHelper.GetDataRoot();
        string filename = dataRoot;
        filename += "/Data/mr.001";

        vtkDirectory dir = vtkDirectory.New();
        if( dir.FileIsDirectory( dataRoot ) == 0 )
        {
            filename = vtkGDCMTesting.GetGDCMDataRoot() + "/test.acr";
        }
        //System.Console.Write( "dataRoot: " + dataRoot + "\n" );
        System.Console.Write( "filename being used is: " + filename + "\n" );

        vtkGDCMImageReader reader = vtkGDCMImageReader.
            New();
        vtkStringArray array = vtkStringArray.New();
        array.InsertNextValue(filename);
        reader.SetFileNames(array);
        reader.Update();

        System.Console.Write(reader.GetOutput());

        vtkRenderWindowInteractor iren = vtkRenderWindowInteractor.New();

        vtkRenderer renl = vtkRenderer.New();
        vtkRenderWindow renWin = vtkRenderWindow.New();
        renWin.AddRenderer(renl);

        vtkImageActor actor = vtkImageActor.New();

        vtkImageMapToWindowLevelColors coronalColors = vtkImageMapToWindowLevelColors.
            New();
        coronalColors.SetInput(reader.GetOutput());

        actor.SetInput(coronalColors.GetOutput());

        renl.AddActor(actor);
        iren.SetRenderWindow(renWin);

        iren.Initialize();

        renWin.Render();

        int retVal = testHelper.IsInteractiveModeSpecified();

        if( retVal != 0 )
        {
            iren.Start();
        }

        return 0;
    }
}

```

27.81 HelloSimple.java

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * Compilation:
 * $ CLASSPATH=gdcm.jar javac ../../gdcm/Examples/Java/HelloSimple.java -d .
 *
 * Usage:
 * $ LD_LIBRARY_PATH=. CLASSPATH=gdcm.jar:. java HelloSimple gdcmData/012345.002.050.dcm
 */
import gdcm.*;

public class HelloSimple
{
    public static void main(String[] args) throws Exception
    {
        String filename = args[0];
        Reader reader = new Reader();
        reader.SetFileName( filename );
        boolean ret = reader.Read();
        if( !ret )
        {
            throw new Exception("Could not read: " + filename );
        }
        File f = reader.GetFile();
        DataSet ds = f.GetDataSet();

        System.out.println( ds.toString() );

        System.out.println("Success reading: " + filename );
    }
}

```

27.82 HelloVizWorld.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * Basic example for dealing with a DICOM file that contains an Image
 * (read: Pixel Data element)
 */

#include "gdcmImageReader.h"
#include "gdcmImageWriter.h"
#include "gdcmImage.h"
#include "gdcmPhotometricInterpretation.h"

#include <iostream>

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {

```

```

    std::cerr << argv[0] << " input.dcm output.dcm" << std::endl;
    return 1;
}
const char *filename = argv[1];
const char *outfilename = argv[2];

// Instantiate the image reader:
gdcm::ImageReader reader;
reader.SetFileName( filename );
if( !reader.Read() )
{
    std::cerr << "Could not read: " << filename << std::endl;
    return 1;
}
// If we reach here, we know for sure 2 things:
// 1. It is a valid DICOM
// 2. And it contains an Image !

// The output of superclass gdcm::Reader is a gdcm::File
//gdcm::File &file = reader.GetFile();

// The other output of gdcm::ImageReader is a gdcm::Image
const gdcm::Image &image = reader.GetImage();

// Let's get some property from the image:
unsigned int ndim = image.GetNumberOfDimensions();
// Dimensions of the image:
const unsigned int *dims = image.GetDimensions();
// Origin
const double *origin = image.GetOrigin();
const gdcm::PhotometricInterpretation &pi = image.
    GetPhotometricInterpretation();
for(unsigned int i = 0; i < ndim; ++i)
{
    std::cout << "Dim(" << i << "): " << dims[i] << std::endl;
}
for(unsigned int i = 0; i < ndim; ++i)
{
    std::cout << "Origin(" << i << "): " << origin[i] << std::endl;
}
std::cout << "PhotometricInterpretation: " << pi << std::endl;

// Write the modified DataSet back to disk
gdcm::ImageWriter writer;
writer.SetImage( image );
writer.SetFileName( outfile );
//writer.SetFile( file ); // We purposely NOT copy the meta information from the input
// file, and instead only pass the image
if( !writer.Write() )
{
    std::cerr << "Could not write: " << outfile << std::endl;
    return 1;
}

return 0;
}

```

27.83 HelloVTKWorld.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/
using vtkgdcm;

/*
 * This test only test the SWIG/VTK part, you do not need Activiz
 */

```

```

public class HelloVTKWorld
{
    public static int Main(string[] args)
    {
        string filename = args[0];
        vtkGDCMImageReader reader = vtkGDCMImageReader.
            New();
        reader.SetFileName( filename );
        reader.Update();

        vtkMedicalImageProperties prop = reader.GetMedicalImageProperties();
        System.Console.WriteLine( prop.GetPatientName() ); //

        if( reader.GetImageFormat() == vtkgdcml.vtkgdcml.VTK_LUMINANCE ) // MONOCHROME2
        {
            System.Console.WriteLine( "Image is MONOCHROME2" ); //
        }

        // Just for fun, invert the direction cosines, output should reflect that:
        vtkMatrix4x4 dircos = reader.GetDirectionCosines();
        dircos.Invert();

        string outfilename = args[1];
        vtkGDCMImageWriter writer = vtkGDCMImageWriter.
            New();
        writer.SetMedicalImageProperties( reader.GetMedicalImageProperties() );
        writer.SetDirectionCosines( dircos );
        writer.SetShift( reader.GetShift() );
        writer.SetScale( reader.GetScale() );
        writer.SetImageFormat( reader.GetImageFormat() );
        writer.SetFileName( outfilename );
        //writer.SetInputConnection( reader.GetOutputPort() ); // new
        writer.SetInput( reader.GetOutput() ); // old
        writer.Write();

        return 0;
    }
}

```

27.84 HelloVTKWorld.java

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
// We are required to call the package 'vtk' eventhough I (MM) would have preferred
// an import statement along the line of:
// import vtkgdcml.*;
import vtk.*;

/*
 * Compilation:
 * CLASSPATH=vtkgdcml.jar:/usr/share/java/vtk.jar javac HelloVTKWorld.java
 *
 * Usage:
 * LD_LIBRARY_PATH=/usr/lib/jvm/java-6-openjdk/jre/lib/amd64/xawt:/usr/lib/jni:. CLASSPATH=/usr/share/java/
 *   vtk.jar:vtkgdcml.jar:gdcm.jar:. java HelloVTKWorld gdcmData/012345.002.050.dcm bla.dcm
 */
public class HelloVTKWorld
{
    static {
        System.loadLibrary("vtkCommonJava");
        System.loadLibrary("vtkFilteringJava");
        System.loadLibrary("vtkIOJava");
        System.loadLibrary("vtkImagingJava");
        System.loadLibrary("vtkGraphicsJava");
        System.loadLibrary("vtkgdcmlJava");
    }
}

```

```

    try {
        System.loadLibrary("vtkRenderingJava");
    } catch (Throwable e) {
        System.out.println("cannot load vtkHybrid, skipping...");
    }
    try {
        System.loadLibrary("vtkHybridJava");
    } catch (Throwable e) {
        System.out.println("cannot load vtkHybrid, skipping...");
    }
    try {
        System.loadLibrary("vtkVolumeRenderingJava");
    } catch (Throwable e) {
        System.out.println("cannot load vtkVolumeRendering, skipping...");
    }
}

public static void main(String[] args)
{
    String filename = args[0];
    vtkGDCMImageReader reader = new vtkGDCMImageReader();
    reader.SetFileName( filename );
    reader.Update();

    vtkMedicalImageProperties prop = reader.GetMedicalImageProperties();
    System.out.println( prop.GetPatientName() ); //

    // if( reader.GetImageFormat() == vtkgdc.vtkgdc.VTK_LUMINANCE ) // MONOCHROME2
    // {
    //     System.out.println( "Image is MONOCHROME2" ); //
    // }

    // Just for fun, invert the direction cosines, output should reflect that:
    vtkMatrix4x4 dircos = reader.GetDirectionCosines();
    dircos.Invert();

    // We need to maintain in sync information stored in vtkMedicalImageProperties:
    double[] cosines = new double[6];
    cosines[0] = dircos.GetElement(0,0);
    cosines[1] = dircos.GetElement(1,0);
    cosines[2] = dircos.GetElement(2,0);
    cosines[3] = dircos.GetElement(0,1);
    cosines[4] = dircos.GetElement(1,1);
    cosines[5] = dircos.GetElement(2,1);
    reader.GetMedicalImageProperties().SetDirectionCospine( cosines );

    String outfilename = args[1];
    vtkGDCMImageWriter writer = new vtkGDCMImageWriter();
    writer.SetMedicalImageProperties( reader.GetMedicalImageProperties() );
    writer.SetDirectionCosines( dircos );
    writer.SetShift( reader.GetShift() );
    writer.SetScale( reader.GetScale() );
    writer.SetImageFormat( reader.GetImageFormat() );
    writer.SetFileName( outfilename );
    //writer.SetInputConnection( reader.GetOutputPort() ); // new
    writer.SetInput( reader.GetOutput() ); // old
    writer.Write();

    System.out.println("Success reading: " + filename );
}
}

```

27.85 HelloVTKWorld2.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcml.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

```

```

using vtkgdcmm;

/*
 * This test only test the SWIG/VTK part, you do not need Activiz
 */
public class HelloVTKWorld2
{
    public static int Main(string[] args)
    {
        string VTK_DATA_ROOT = vtkGDCMTesting.GetVTKDataRoot();

        vtkVolume16Reader reader = vtkVolume16Reader.New();
        reader.SetDataDimensions(64, 64);
        reader.SetDataByteOrderToLittleEndian();
        reader.SetFilePrefix(VTK_DATA_ROOT + "/Data/headsq/quarter");
        reader.SetImageRange(1, 93);
        reader.SetDataSpacing(3.2, 3.2, 1.5);

        vtkImageCast cast = vtkImageCast.New();
        cast.SetInput( reader.GetOutput() );
        cast.SetOutputScalarTypeToUnsignedChar();

        // By default this is creating a Multiframe Grayscale Word Secondary Capture Image Storage
        vtkGDCMImageWriter writer = vtkGDCMImageWriter.
            New();
        writer.SetFileName( "headsq.dcm" );
        writer.SetInput( reader.GetOutput() );
        // cast -> Multiframe Grayscale Byte Secondary Capture Image Storage
        // writer.SetInput( cast.GetOutput() );
        writer.SetFileDimensionality( 3 );
        writer.Write();

        return 0;
    }
}

```

27.86 HelloWorld.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * This example is ... guess what this is for :)
 */

#include "gdcmReader.h"
#include "gdcmWriter.h"
#include "gdcmAttribute.h"

#include <iostream>

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];

    // Instantiate the reader:
    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Could not read: " << filename << std::endl;
    }
}

```



```

    return 1;
}

// If we reach here, we know for sure only 1 thing:
// It is a valid DICOM file (potentially an old ACR-NEMA 1.0/2.0 file)
// (Maybe, it's NOT a Dicom image -could be a DICOMDIR, a RTSTRUCT, etc-)

// The output of gdcm::Reader is a gdcm::File
gdcm::File &file = reader.GetFile();

// the dataset is the the set of element we are interested in:
gdcm::DataSet &ds = file.GetDataSet();

// Construct a static(*) type for Image Comments :
gdcm::Attribute<0x0020,0x4000> imagecomments;
imagecomments.SetValue( "Hello, World !" );

// Now replace the Image Comments from the dataset with our:
ds.Replace( imagecomments.GetAsDataElement() );

// Write the modified DataSet back to disk
gdcm::Writer writer;
writer.CheckFileMetaInformationOff(); // Do not attempt to reconstruct the
    file meta to preserve the file           // as close to the original as possible.
writer.SetFileName( outfilename );
writer.SetFile( file );
if( !writer.Write() )
{
    std::cerr << "Could not write: " << outfilename << std::endl;
    return 1;
}

return 0;
}

/*
 * (*) static type, means that extra DICOM information VR & VM are computed at compilation time.
 * The compiler is deducing those values from the template arguments of the class.
 */

```

27.87 HelloWorld.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Hello World !
17 """
18
19 import gdcm
20 import sys
21
22 if __name__ == "__main__":
23
24     # verbosity:
25     #gdcm.Trace.DebugOn()
26     #gdcm.Trace.WarningOn()
27     #gdcm.Trace.ErrorOn()
28
29     # Get the filename from the command line
30     filename = sys.argv[1]
31
32     # Instanciate a gdcm.Reader
33     # This is the main class to handle any type of DICOM object
34     # You should check for gdcm.ImageReader for reading specifically DICOM Image file

```

```

35  r = gdcm.Reader()
36  r.SetFileName( filename )
37  # If the reader fails to read the file, we should stop !
38  if not r.Read():
39      print "Not a valid DICOM file"
40      sys.exit(1)
41
42  # Get the DICOM File structure
43  file = r.GetFile()
44
45  # Get the DataSet part of the file
46  dataset = file.GetDataSet()
47
48  # Ok let's print it !
49  print dataset
50
51  # Use StringFilter to print a particular Tag:
52  sf = gdcm.StringFilter()
53  sf.SetFile(r.GetFile())
54
55  # Check if Attribute exist
56  print dataset.FindElement( gdcm.Tag(0x0028,0x0010))
57
58  # Let's print it as string pair:
59  print sf.ToStringPair(gdcm.Tag(0x0028,0x0010))

```

27.88 iU22tomultisc.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * iU22 Raw Data extractor
 */
#include "gdcmReader.h"
#include "gdcmImageWriter.h"
#include "gdcmAttribute.h"
#include "gdcmPrivateTag.h"

#include <math.h>

int main(int argc, char *argv [])
{
    if( argc < 2 ) return 1;
    // IM_001
    const char *filename = argv[1];

    gdcm::Reader reader; // Do not use ImageReader
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Failed to read: " << filename << std::endl;
        return 1;
    }

    // * The data is simply 8-bit unsigned in the obvious x/y/z order
    // * 200D,300B contains the data
    // * 200D,3001 contains the no. of voxels (416,412,256 in this case)
    // * 200D,3003 contains the voxel sizes (0.156184527398215 /
    // 0.1223749613981957 / 0.328479990704639 in this case)

    const gdcm::File &file = reader.GetFile();
    const gdcm::DataSet &ds = file.GetDataSet();
    const gdcm::PrivateTag trawdataus( 0x200d, 0x0b, "Philips US Imaging DD 033" );
    const gdcm::DataElement &rawdataus = ds.GetDataElement( trawdataus );

    const gdcm::PrivateTag tcolsrrowsframes( 0x200d, 0x01, "Philips US Imaging DD 036" );

```

```

const gdcm::DataElement &colsrowsframes = ds.GetDataElement(
    tcolsrowsframes );
// const gdcm::PrivateTag tcolsrowsframes( 0x200d, 0x02, "Philips US Imaging DD 036" );
// this is just a duplicate previous tag.
const gdcm::PrivateTag tvoxelspacing( 0x200d, 0x03, "Philips US Imaging DD 036" );
const gdcm::DataElement &voxelspacing = ds.GetDataElement( tvoxelspacing )
;

gdcm::Element<gdcm::VR::DS,gdcm::VM::VM3> dims; // Use DS to
    interpret value stored in LO
dims.SetFromDataElement( colsrowsframes );

gdcm::Element<gdcm::VR::DS,gdcm::VM::VM3> spacing;
spacing.SetFromDataElement( voxelspacing );

gdcm::ImageWriter writer;

gdcm::Image &image = writer.GetImage();
image.SetNumberOfDimensions( 3 ); // good default
image.SetDimension(0, (unsigned int)dims[0] );
image.SetDimension(1, (unsigned int)dims[1] );
image.SetDimension(2, (unsigned int)dims[2] );
image.SetSpacing(0, spacing[0] );
image.SetSpacing(1, spacing[1] );
image.SetSpacing(2, spacing[2] );
gdcm::PixelFormat pixeltype = gdcm::PixelFormat::UINT8;

gdcm::PhotometricInterpretation pi;
pi = gdcm::PhotometricInterpretation::MONOCHROME2;
image.SetPhotometricInterpretation( pi );
image.SetPixelFormat( pixeltype );

image.SetDataElement( rawdataus );

std::string outfilename = "outiu22.dcm";

gdcm::DataElement de( gdcm::Tag(0x8,0x16) ); // SOP Class UID
de.SetVR( gdcm::VR::UI );
gdcm::MediaStorage ms(
    gdcm::MediaStorage::UltrasoundMultiFrameImageStorage
);
// gdcm::MediaStorage::MultiframeGrayscaleByteSecondaryCaptureImageStorage );
de.SetByteValue( ms.GetString(), (uint32_t)strlen(ms.
    GetString()) );
writer.GetFile().GetDataSet().Replace( de );

writer.SetFileName( outfilename.c_str() );
if( !writer.Write() )
{
    std::cerr << "could not write: " << outfilename << std::endl;
    return 1;
}

return 0;
}

```

27.89 LargeVRDSExplicit.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmReader.h"
#include "gdcmWriter.h"
#include "gdcmAttribute.h"
#include "gdcmFileExplicitFilter.h"
#include "gdcmSequenceOfItems.h"

```

```

bool interpolate(const double * pts, size_t npts, std::vector<double> &out )
{
    out.clear();
    for(size_t i = 0; i < 2*npts; ++i )
    {
        const size_t j = i / 2;
        if( i % 2 )
        {
            if( j != npts - 1 )
            {
                assert( 3*j+5 < 3*npts );
                const double midpointx = (pts[3*j+0] + pts[3*j+3]) / 2;
                const double midpoiny = (pts[3*j+1] + pts[3*j+4]) / 2;
                const double midpointz = (pts[3*j+2] + pts[3*j+5]) / 2;
                out.push_back( midpointx );
                out.push_back( midpoiny );
                out.push_back( midpointz );
            }
        }
        else
        {
            assert( j < npts );
            out.push_back( pts[3*j+0] );
            out.push_back( pts[3*j+1] );
            out.push_back( pts[3*j+2] );
        }
    }
    assert( out.size() == 2 * npts * 3 - 3 );
    return true;
}

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    const char *outfilename = argv[2];
    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        return 1;
    }

    gdcm::File &file = reader.GetFile();
    gdcm::DataSet &ds = file.GetDataSet();

    gdcm::FileExplicitFilter fef;
    //fef.SetChangePrivateTags( changeprivatetags );
    fef.SetFile( reader.GetFile() );
    if( !fef.Change() )
    {
        std::cerr << "Failed to change: " << filename << std::endl;
        return 1;
    }

    // (3006,0039) SQ (Sequence with undefined length #=4)      # u/1, 1 ROIContourSequence
    gdcm::Tag tag(0x3006,0x0039);

    const gdcm::DataElement &roicsq = ds.GetDataElement( tag );
    gdcm::SmartPointer<gdcm::SequenceOfItems> sqi = roicsq.
        GetValueAsSQ();
    //sqi->SetNumberOfItems( 1 );
    const gdcm::Item &item = sqi->GetItem(1); // Item start at #1
    const gdcm::DataSet &nestedds = item.GetNestedDataSet();

    gdcm::Tag tcsq(0x3006,0x0040);
    if( !nestedds.FindDataElement( tcsq ) )
    {
        return 0;
    }
    const gdcm::DataElement &csq = nestedds.GetDataElement( tcsq );
    gdcm::SmartPointer<gdcm::SequenceOfItems> sqi2 = csq.
        GetValueAsSQ();
    if( !sqi2 || !sqi2->GetNumberOfItems() )
    {
        return 0;
    }
}

```

```

    }
    //unsigned int nitems = sqi2->GetNumberOfItems();
    gdcmm::Item & item2 = sqi2->GetItem(1); // Item start at #1

    gdcmm::DataSet& nesteddds2 = item2.GetNestedDataSet();
    //item2.SetVLToUndefined();
    //std::cout << nesteddds2 << std::endl;
    // (3006,0050) DS [43.57636\65.52504\ -10.0\46.043102\62.564945\ -10.0\49.126537\60.714... # 398,48
    ContourData
    gdcmm::Tag tcontourdata(0x3006,0x0050);
    const gdcmm::DataElement & contourdata = nesteddds2.
        GetDataElement( tcontourdata );
    //std::cout << contourdata << std::endl;

    //const gdcmm::ByteValue *bv = contourdata.GetByteValue();
    gdcmm::Attribute<0x3006,0x0046> ncontourpoints;
    ncontourpoints.Set( nesteddds2 );

    gdcmm::Attribute<0x3006,0x0050> at;
    at.SetFromDataElement( contourdata );
    const double* pts = at.GetValues();
    unsigned int npts = at.GetNumberOfValues() / 3;

    std::vector<double> out( pts, pts + npts * 3 );
    std::vector<double> out2;

    //const unsigned int niter = 7;
    const unsigned int niter = 8;
    for( unsigned int i = 0; i < niter; ++i)
    {
        //bool b =
        interpolate(&out[0], out.size() / 3, out2);
        //const double *pout = &out[0];
        out = out2;
        out2.clear();
    }
    assert( out.size() % 3 == 0 );

    gdcmm::Attribute<0x3006,0x0050> at_interpolate;
    at_interpolate.SetNumberOfValues( (unsigned int)(out.size() / 3) );
    at_interpolate.SetValues( &out[0], (uint32_t)out.size() );

    ncontourpoints.SetValue( at_interpolate.GetNumberOfValues() / 3 );
    nesteddds2.Replace( at_interpolate.GetAsDataElement() );
    nesteddds2.Replace( ncontourpoints.GetAsDataElement() );

    //assert(0);

    // Let's take item one and subdivide it

    gdcmm::TransferSyntax ts =
        gdcmm::TransferSyntax::ImplicitVRLittleEndian;
    ts = gdcmm::TransferSyntax::ExplicitVRLittleEndian;

    gdcmm::FileMetaInformation &fmi = file.GetHeader();
    const char *tsuid = gdcmm::TransferSyntax::GetTSString( ts );
    // const char * is ok since padding is \0 anyway...
    gdcmm::DataElement de( gdcmm::Tag(0x0002,0x0010) );
    de.SetByteValue( tsuid, (uint32_t)strlen(tsuid) );
    de.SetVR( gdcmm::Attribute<0x0002, 0x0010>::GetVR() );
    fmi.Replace( de );
    fmi.Remove( gdcmm::Tag(0x0002,0x0012) ); // will be regenerated
    fmi.Remove( gdcmm::Tag(0x0002,0x0013) ); // ' ' ' '
    fmi.SetDataSetTransferSyntax(ts);

    gdcmm::Writer w;
    w.SetFile( file );
    w.SetFileName( outfilename );
    if ( !w.Write() )
    {
        return 1;
    }

    return 0;
}

```

27.90 MagnifyFile.cxx

```

/*=====

Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkGDCMImageReader.h"
#include "vtkGDCMImageWriter.h"
#include "vtkImageData.h"
#include "vtkImageMagnify.h"
#include "vtkImageCast.h"

#include "gdcmTesting.h"
#include "gdcmSystem.h"

// This is a simple test to magnify an image that is known to give excellent
// compression ratio. This will be our test for those large image
int main(int, char *[])
{
    const char *directory = gdcm::Testing::GetDataRoot();
    if(!directory) return 1;
    std::string file = std::string(directory) + "/test.acr";
    std::cout << file << std::endl;
    if( !gdcm::System::FileExists( file.c_str() ) ) return 1;

    vtkGDCMImageReader *reader = vtkGDCMImageReader::New();
    reader->SetFileName( file.c_str() );
    reader->Update();
    //reader->GetOutput()->Print( std::cout );

    vtkImageCast *cast = vtkImageCast::New();
    cast->SetInput( reader->GetOutput() );
    cast->SetOutputScalarTypeToUnsignedShort();

    vtkImageMagnify *magnify = vtkImageMagnify::New();
    magnify->SetInput( cast->GetOutput() );
    magnify->SetInterpolate( 1 );
    magnify->SetInterpolate( 0 );
    int factor = 100;
    magnify->SetMagnificationFactors (factor, factor, 1);

    vtkGDCMImageWriter *writer = vtkGDCMImageWriter::New();
    writer->SetFileName( "/tmp/bla.dcm" );
    writer->SetInput( magnify->GetOutput() );
    writer->SetImageFormat( reader->GetImageFormat() );
    writer->SetMedicalImageProperties( reader->GetMedicalImageProperties() );
    writer->SetDirectionCosines( reader->GetDirectionCosines() );
    writer->SetShift( reader->GetShift() );
    writer->SetScale( reader->GetScale() );
    writer->Write();

    // TODO:
    //vtkImageAppendComponents.h

    reader->Delete();
    magnify->Delete();
    writer->Delete();

    return 0;
}

```

27.91 ManipulateFile.cs

```

/*=====

Program: GDCM (Grassroots DICOM). A DICOM library

```

```

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/ManipulateFile.exe gdcmData/012345.002.050.dcm out.dcm
 */
using System;
using gdcm;

public class ManipulateFile
{
    public static int Main(string[] args)
    {
        string file1 = args[0];
        string file2 = args[1];
        Reader reader = new Reader();
        reader.SetFileName( file1 );
        bool ret = reader.Read();
        if( !ret )
        {
            return 1;
        }

        Anonymizer ano = new Anonymizer();
        ano.SetFile( reader.GetFile() );
        ano.RemovePrivateTags();
        ano.RemoveGroupLength();
        Tag t = new Tag(0x10,0x10);
        ano.Replace( t, "GDCM^Csharp^Test^Hello^World" );

        UIDGenerator g = new UIDGenerator();
        ano.Replace( new Tag(0x0008,0x0018), g.Generate() );
        ano.Replace( new Tag(0x0020,0x000d), g.Generate() );
        ano.Replace( new Tag(0x0020,0x000e), g.Generate() );
        ano.Replace( new Tag(0x0020,0x0052), g.Generate() );

        Writer writer = new Writer();
        writer.SetFileName( file2 );
        writer.SetFile( ano.GetFile() );
        ret = writer.Write();
        if( !ret )
        {
            return 1;
        }

        return 0;
    }
}

```

27.92 ManipulateFile.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #       This software is distributed WITHOUT ANY WARRANTY; without even
10 #       the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #       PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:
17

```

```

18 python ManipulateFile.py input.dcm output.dcm
19
20 Footnote:
21   GDCM 1.2.x would create incorrect Multiframe MR Image Storage file. Try to recover from
22   the issues to recreate a MultiframeGrayscaleByteSecondaryCaptureImageStorage file.
23   e.g:
24
25   python ManipulateFile.py Insight/Testing/Temporary/itkGDCMImageIOTest5-j2k.dcm manipulated.dcm
26   """
27
28   import sys
29   import gdcm
30
31   if __name__ == "__main__":
32
33       file1 = sys.argv[1]
34       file2 = sys.argv[2]
35
36       r = gdcm.Reader()
37       r.SetFileName( file1 )
38       if not r.Read():
39           sys.exit(1)
40
41       ano = gdcm.Anonymizer()
42       ano.SetFile( r.GetFile() )
43       ano.RemovePrivateTags()
44       ano.Remove( gdcm.Tag(0x0032,0x1030) )
45       ano.Remove( gdcm.Tag(0x008,0x14) )
46       ano.Remove( gdcm.Tag(0x008,0x1111) )
47       ano.Remove( gdcm.Tag(0x008,0x1120) )
48       ano.Remove( gdcm.Tag(0x008,0x1140) )
49       ano.Remove( gdcm.Tag(0x10,0x21b0) )
50       ano.Empty( gdcm.Tag(0x10,0x10) )
51       ano.Empty( gdcm.Tag(0x10,0x20) )
52       ano.Empty( gdcm.Tag(0x10,0x30) )
53       ano.Empty( gdcm.Tag(0x20,0x10) )
54       ano.Empty( gdcm.Tag(0x32,0x1032) )
55       ano.Empty( gdcm.Tag(0x32,0x1033) )
56       ano.Empty( gdcm.Tag(0x40,0x241) )
57       ano.Empty( gdcm.Tag(0x40,0x254) )
58       ano.Empty( gdcm.Tag(0x40,0x253) )
59       ano.Empty( gdcm.Tag(0x40,0x1001) )
60       ano.Empty( gdcm.Tag(0x8,0x80) )
61       ano.Empty( gdcm.Tag(0x8,0x50) )
62       ano.Empty( gdcm.Tag(0x8,0x1030) )
63       ano.Empty( gdcm.Tag(0x8,0x103e) )
64       ano.Empty( gdcm.Tag(0x18,0x1030) )
65       ano.Empty( gdcm.Tag(0x38,0x300) )
66       g = gdcm.UIDGenerator()
67       ano.Replace( gdcm.Tag(0x0008,0x0018), g.Generate() )
68       ano.Replace( gdcm.Tag(0x0020,0x00d), g.Generate() )
69       ano.Replace( gdcm.Tag(0x0020,0x00e), g.Generate() )
70       ano.Replace( gdcm.Tag(0x0020,0x052), g.Generate() )
71       #ano.Replace( gdcm.Tag(0x0008,0x0016), "1.2.840.10008.5.1.4.1.1.7.2" )
72       """
73       ano.Remove( gdcm.Tag(0x0018,0x0020) ) # ScanningSequence
74       ano.Remove( gdcm.Tag(0x0018,0x0021) ) # SequenceVariant
75       ano.Remove( gdcm.Tag(0x0018,0x0022) ) # ScanOptions
76       ano.Remove( gdcm.Tag(0x0018,0x0023) ) # MRAcquisitionType
77       ano.Remove( gdcm.Tag(0x0018,0x0050) ) # SliceThickness
78       ano.Remove( gdcm.Tag(0x0018,0x0080) ) # RepetitionTime
79       ano.Remove( gdcm.Tag(0x0018,0x0081) ) # EchoTime
80       ano.Remove( gdcm.Tag(0x0018,0x0088) ) # SpacingBetweenSlices
81       ano.Remove( gdcm.Tag(0x0018,0x0091) ) # EchoTrainLength
82       ano.Remove( gdcm.Tag(0x0018,0x1164) ) # ImagerPixelSpacing
83
84       ano.Remove( gdcm.Tag(0x0020,0x0032) ) # Image Position (Patient)
85       ano.Remove( gdcm.Tag(0x0020,0x0037) ) # Image Orientation (Patient)
86       ano.Remove( gdcm.Tag(0x0020,0x0052) ) # Frame of Reference UID
87       ano.Remove( gdcm.Tag(0x0020,0x1040) ) # Position Reference Indicator
88
89       ano.Replace( gdcm.Tag(0x0028,0x0301), "NO" ) # Burned In Annotation
90
91       ano.Empty( gdcm.Tag(0x0020,0x0020) )
92
93       ano.Remove( gdcm.Tag(0x7fe0,0x0000) )
94
95       #ano.Empty( gdcm.Tag(0x0028,0x0009) ) # Frame Increment Pointer
96
97       #ano.Empty( gdcm.Tag(0x0028,0x1052) ) #<entry group="0028" element="1052" vr="DS" vm="1" name="Rescale
          Intercept"/>

```



```

98  #ano.Empty( gdc.Tag(0x0028,0x1053) )  #<entry group="0028" element="1053" vr="DS" vm="1" name="Rescale
    Slope"/>
99  #ano.Replace( gdc.Tag(0x0028,0x1054), "US" )  #<entry group="0028" element="1054" vr="LO" vm="1" name="
    Rescale Type"/>
100
101  ano.Replace( gdc.Tag(0x2050, 0x0020), "IDENTITY")
102  """
103
104  w = gdc.Writer()
105  w.SetFile( ano.GetFile() )
106  w.SetFileName( file2 )
107  if not w.Write():
108      sys.exit(1)

```

27.93 ManipulateSequence.py

```

1  #####
2  #
3  #  Program: GDCM (Grassroots DICOM). A DICOM library
4  #
5  #  Copyright (c) 2006-2011 Mathieu Malaterre
6  #  All rights reserved.
7  #  See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8  #
9  #  This software is distributed WITHOUT ANY WARRANTY; without even
10 #  the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #  PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:
17
18 python ManipulateSequence.py input.dcm output.dcm
19
20 This was tested using:
21
22 python ManipulateSequence.py gdcmData/D_CLUNIE_CT1_J2KI.dcm myoutput.dcm
23
24 This is a dummy example on how to modify a value set in a nested-nested dataset
25
26 WARNING:
27 Do not use as-is in production, this is just an example
28 This example works in an undefined length Item only (you need to explicitly recompute the length
    otherwise)
29 """
30
31 import sys
32 import gdcm
33
34 if __name__ == "__main__":
35
36     file1 = sys.argv[1]
37     file2 = sys.argv[2]
38
39     r = gdcm.Reader()
40     r.SetFileName( file1 )
41     if not r.Read():
42         sys.exit(1)
43
44     f = r.GetFile()
45     ds = f.GetDataSet()
46     tsis = gdcm.Tag(0x0008,0x2112) # SourceImageSequence
47     if ds.FindDataElement( tsis ):
48         sis = ds.GetDataElement( tsis )
49         #sqsis = sis.GetSequenceOfItems()
50         # GetValueAsSQ handle more cases
51         sqsis = sis.GetValueAsSQ()
52         if sqsis.GetNumberOfItems():
53             item1 = sqsis.GetItem(1)
54             nestedds = item1.GetNestedDataSet()
55             tprcs = gdcm.Tag(0x0040,0xa170) # PurposeOfReferenceCodeSequence
56             if nestedds.FindDataElement( tprcs ):
57                 prcs = nestedds.GetDataElement( tprcs )
58                 sqprcs = prcs.GetSequenceOfItems()
59                 if sqprcs.GetNumberOfItems():
60                     item2 = sqprcs.GetItem(1)

```

```

61         nestedds2 = item2.GetNestedDataSet()
62         # (0008,0104) LO [Uncompressed predecessor] # 24, 1 CodeMeaning
63         tcm = gdcm.Tag(0x0008,0x0104)
64         if nestedds2.FindDataElement( tcm ):
65             cm = nestedds2.GetDataElement( tcm )
66             mystr = "GDCM was here"
67             cm.SetByteValue( mystr, gdcm.VL( len(mystr) ) )
68
69     w = gdcm.Writer()
70     w.SetFile( f )
71     w.SetFileName( file2 )
72     if not w.Write():
73         sys.exit(1)

```

27.94 MergeFile.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:
17
18 python MergeFile.py input1.dcm input2.dcm
19
20 It will produce a 'merge.dcm' output file, which contains all meta information from input1.dcm
21 and copy the Stored Pixel values from input2.dcm
22 This script even works when input2.dcm is a Secondary Capture and does not contains information
23 such as IOP and IPP...
24 """
25
26 import sys
27 import gdcm
28
29 if __name__ == "__main__":
30     file1 = sys.argv[1]
31     file2 = sys.argv[2]
32
33     r1 = gdcm.ImageReader()
34     r1.SetFileName( file1 )
35     if not r1.Read():
36         sys.exit(1)
37
38     r2 = gdcm.ImageReader()
39     r2.SetFileName( file2 )
40     if not r2.Read():
41         sys.exit(1)
42
43     # Image from r2 could be Secondary Capture and thus would not contains neither IPP nor IOP
44     # Instead always prefer to only copy the Raw Data Element.
45     # Warning ! Image need to be identical ! Only the value of Stored Pixel can be different.
46     r1.GetImage().SetDataElement( r2.GetImage().GetDataElement() )
47
48     w = gdcm.ImageWriter()
49     w.SetFile( r1.GetFile() )
50     #w.SetImage( r2.GetImage() ) # See comment above
51     w.SetImage( r1.GetImage() )
52
53     w.SetFileName( "merge.dcm" )
54     if not w.Write():
55         sys.exit(1)
56
57     sys.exit(0)

```

27.95 MergeTwoFiles.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * This example will show how one can read in two DICOM files, use the dataset
 * from file1 and use image from file2 to save it in a 3rd file.
 *
 * Eg:
 * MergeTwoFiles gdcmData/012345.002.050.dcm gdcmData/test.acr merge.dcm
 */

#include "gdcmReader.h"
#include "gdcmImageReader.h"
#include "gdcmImageWriter.h"
#include "gdcmWriter.h"
#include "gdcmDataSet.h"
#include "gdcmAttribute.h"

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        return 1;
    }
    const char *file1 = argv[1];
    const char *file2 = argv[2];
    const char *file3 = argv[3];

    // Read file1
    gdcm::ImageReader reader1;
    reader1.SetFileName( file1 );
    if( !reader1.Read() )
    {
        return 1;
    }

    // Read file2
    gdcm::ImageReader reader2;
    reader2.SetFileName( file2 );
    if( !reader2.Read() )
    {
        return 1;
    }

    // Ok now let's take the DataSet from file1 and the Image from file2
    // Warning: if file2 is -for example- a Secondary Capture Storage, then it has no
    // Image Orientation (Patient) thus any Image Orientation (Patient) from file1
    // will be discarded...

    // let's be fancy. In case reader2 contains explicit, but reader1 is implicit
    // we would rather see an implicit output
    if( reader1.GetFile().GetHeader().GetDataSetTransferSyntax() ==
        gdcm::TransferSyntax::ImplicitVRLittleEndian )
    {
        reader2.GetImage().SetTransferSyntax(
            gdcm::TransferSyntax::ImplicitVRLittleEndian );
    }

    gdcm::ImageWriter writer;
    writer.SetFileName( file3 );
    writer.SetFile( reader1.GetFile() );
    // ImageWriter will always use all of gdcm::Image information an override anything wrong from
    // reader1.GetFile(), including the Transfer Syntax
    writer.SetImage( reader2.GetImage() );

    gdcm::DataSet &ds = reader1.GetFile().GetDataSet();

    // Make sure that SOPInstanceUID are different

```

```

// Simply removing it is sufficient as gdcm::ImageWriter will generate one by default
// if not found.
ds.Remove( gdcm::Tag(0x0008,0x0018) );
if( !writer.Write() )
{
    return 1;
}

return 0;
}

```

27.96 MetalmageMD5Activiz.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
using Kitware.VTK;
using Kitware.VTK.GDCM;
using gdcm;

/*
 * $ export MONO_PATH=/usr/lib/cli/Activiz.NET:/usr/lib/cli/Kitware.mummy.Runtime-1.0
 * $ mono ./bin/MetaImageMD5Activiz.exe gdcmData/012345.002.050.dcm
 */
public class MetaImageMD5Activiz
{
    public static int ProcessOneMHDMD5(string filename)
    {
        vtkGDCMImageReader reader = vtkGDCMImageReader.
            New();
        reader.FileLowerLeftOn();
        reader.DebugOff();
        int canread = reader.CanReadFile( filename );
        if( canread == 0 )
        {
            string refms = gdcm.Testing.GetMediaStorageFromFile(filename);
            if( gdcm.MediaStorage.IsImage( gdcm.MediaStorage.GetMSType(refms) ) )
            {
                System.Console.Write( "Problem with file: " + filename + "\n" );
                return 1;
            }
            // not an image
            return 0;
        }

        reader.SetFileName( filename );
        reader.Update();

        // System.Console.Write(reader.GetOutput());

        vtkMetaImageWriter writer = vtkMetaImageWriter.New();
        writer.SetCompression( false );
        writer.SetInput( reader.GetOutput() );
        string subdir = "MetaImageMD5Activiz";
        string tmpdir = gdcm.Testing.GetTempDirectory( subdir );
        if( !gdcm.PosixEmulation.FileIsDirectory( tmpdir ) )
        {
            gdcm.PosixEmulation.MakeDirectory( tmpdir );
        }
        string mhdfile = gdcm.Testing.GetTempFilename( filename, subdir );

        string rawfile = mhdfile;
        mhdfile += ".mhd";
        rawfile += ".raw";
        writer.SetFileName( mhdfile );
        writer.Write();
    }
}

```

```

string digestmhd = gdcm.Testing.ComputeFileMD5( mhdfile );
string digestraw = gdcm.Testing.ComputeFileMD5( rawfile );

string mhdref = vtkGDCMTesting.GetMHDMD5FromFile(filename);
string rawref = vtkGDCMTesting.GetRAWMD5FromFile(filename);

if( mhdref != digestmhd )
{
    System.Console.Write( "Problem with mhd file: " + filename + "\n" );
    System.Console.Write( digestmhd );
    System.Console.Write( "\n" );
    System.Console.Write( mhdref );
    System.Console.Write( "\n" );
    return 1;
}
if( rawref != digestraw )
{
    System.Console.Write( "Problem with raw file: " + filename + "\n" );
    System.Console.Write( digestraw );
    System.Console.Write( "\n" );
    System.Console.Write( rawref );
    System.Console.Write( "\n" );
    return 1;
}

return 0;
}
public static int Main(string[] args)
{
    if ( args.Length == 1 )
    {
        string filename = args[0];
        return ProcessOneMHDMD5( filename );
    }

    // Loop over all gdcmData
    gdcm.Trace.DebugOff();
    gdcm.Trace.WarningOff();
    gdcm.Trace.ErrorOff();

    uint n = gdcm.Testing.GetNumberOfFileNames();
    int ret = 0;
    for( uint i = 0; i < n; ++i )
    {
        string filename = gdcm.Testing.GetFileName( i );
        ret += ProcessOneMHDMD5( filename );
    }
    return ret;
}
}

```

27.97 MIPViewer.java

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
import vtk.*;
import gdcm.*;
import java.io.File;
import java.awt.Canvas;

/*
 * Compilation:
 * CLASSPATH=vtkgdcm.jar:/usr/share/java/vtk.jar javac MIPViewer.java
 *
 * Usage:
 * LD_LIBRARY_PATH=/usr/lib/jvm/java-6-openjdk/jre/lib/amd64/xawt:/usr/lib/jni:. CLASSPATH=/usr/share/java/
   vtk.jar:vtkgdcm.jar:gdcm.jar:. java MIPViewer BRAINX

```

```

*
*/
public class MIPViewer extends Canvas
{
    static {
        // VTK
        System.loadLibrary("vtkCommonJava");
        System.loadLibrary("vtkFilteringJava");
        System.loadLibrary("vtkIOJava");
        System.loadLibrary("vtkImagingJava");
        System.loadLibrary("vtkGraphicsJava");
        System.loadLibrary("vtkRenderingJava");
        System.loadLibrary("vtkVolumeRenderingJava"); // vtkSmartVolumeMapper
        System.loadLibrary("vtkWidgetsJava"); // vtkBoxWidget
        // VTK-GDCM
        System.loadLibrary("vtkgdcmJava");
    }

    static FilenamesType fns = new FilenamesType();

    protected native int Lock();

    protected native int UnLock();

    public static void process(String path)
    {
        fns.add( path );
    }

    // Process only files under dir
    public static void visitAllFiles(File dir)
    {
        if (dir.isDirectory())
        {
            String[] children = dir.list();
            for (int i=0; i<children.length; i++)
            {
                visitAllFiles(new File(dir, children[i]));
            }
        }
        else
        {
            process(dir.getPath());
        }
    }

    public static void main(String[] args) throws Exception
    {
        String dirname = args[0];
        if( !PosixEmulation.FileIsDirectory( dirname ) )
        {
            return;
        }

        File dir = new File(dirname);
        visitAllFiles(dir);

        IPPSorter ipp = new IPPSorter();
        ipp.SetComputeZSpacing( true );
        ipp.SetZSpacingTolerance( 1e-3 );
        boolean b = ipp.Sort( fns );
        if(!b)
        {
            throw new Exception("Could not scan");
        }
        double ippzspacing = ipp.GetZSpacing();

        FilenamesType sorted = ipp.GetFilenames();
        vtkStringArray files = new vtkStringArray();
        long nfiles = sorted.size();
        //for( String f : sorted )
        for (int i = 0; i < nfiles; i++) {
            String f = sorted.get(i);
            files.InsertNextValue( f );
        }
        vtkGDCMImageReader reader = new vtkGDCMImageReader();
        reader.SetFileNames( files );
        reader.Update(); // get spacing value

        double[] spacing = reader.GetOutput().GetSpacing();
    }
}

```

```

vtkImageChangeInformation change = new vtkImageChangeInformation();
change.SetInputConnection( reader.GetOutputPort() );
change.SetOutputSpacing( spacing[0], spacing[1], ippzspacing );

// Create our volume and mapper
vtkVolume volume = new vtkVolume();
vtkSmartVolumeMapper mapper = new vtkSmartVolumeMapper();

vtkRenderWindowInteractor iren = new vtkRenderWindowInteractor();

// Add a box widget if the clip option was selected
vtkBoxWidget box = new vtkBoxWidget();
box.SetInteractor(iren);
box.SetPlaceFactor(1.01);
box.SetInput(change.GetOutput());

//box.SetDefaultRenderer(renderer);
box.InsideOutOn();
box.PlaceWidget();
//vtkBoxWidgetCallback callback = vtkBoxWidgetCallback::New();
//callback.SetMapper(mapper);
//box.AddObserver(vtkCommand::InteractionEvent, callback);
//callback.Delete();
// Lock();
// box.EnabledOn();
// Unlock();
box.GetSelectedFaceProperty().SetOpacity(0.0);

mapper.SetInputConnection( change.GetOutputPort() );

// Create our transfer function
vtkColorTransferFunction colorFun = new vtkColorTransferFunction();
vtkPiecewiseFunction opacityFun = new vtkPiecewiseFunction();

// Create the property and attach the transfer functions
vtkVolumeProperty property = new vtkVolumeProperty();
property.IndependentComponentsOn();
property.SetColor( colorFun );
property.SetScalarOpacity( opacityFun );
property.SetInterpolationTypeToLinear();

// connect up the volume to the property and the mapper
volume.SetProperty( property );
volume.SetMapper( mapper );

vtkMedicalImageProperties medprop = reader.GetMedicalImageProperties();
int n = medprop.GetNumberOfWindowLevelPresets();
double opacityWindow = 4096;
double opacityLevel = 2048;

// Override default with value from DICOM files:
for( int i = 0; i < n; ++i )
{
    double wl[] = medprop.GetNthWindowLevelPreset(i);
    //System.out.println( "W/L: " + wl[0] + " " + wl[1] );
    opacityWindow = wl[0];
    opacityLevel = wl[1];
}

colorFun.AddRGBSegment(0.0, 1.0, 1.0, 1.0, 255.0, 1.0, 1.0, 1.0 );
opacityFun.AddSegment( opacityLevel - 0.5*opacityWindow, 0.0,
    opacityLevel + 0.5*opacityWindow, 1.0 );
mapper.SetBlendModeToMaximumIntensity();

// Create the RenderWindow, Renderer
vtkRenderer ren1 = new vtkRenderer();
vtkRenderWindow renWin = new vtkRenderWindow();
renWin.AddRenderer(ren1);

// Set the default window size
renWin.SetSize(600,600);

// Add the volume to the scene
ren1.AddVolume( volume );
ren1.ResetCamera();

iren.SetRenderWindow( renWin );

// interact with data
renWin.Render();

```

```

        iren.Start();
    }
}

```

27.98 MPRViewer.java

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

import vtk.*;
import gdcm.*;
import java.io.File;

/*
 * Compilation:
 * CLASSPATH=vtkgdcm.jar:/usr/share/java/vtk.jar javac MPRViewer.java
 *
 * Usage:
 * LD_LIBRARY_PATH=/usr/lib/jvm/java-6-openjdk/jre/lib/amd64/xawt:/usr/lib/jni:. CLASSPATH=/usr/share/java/
   vtk.jar:vtkgdcm.jar:gdcm.jar:. java MPRViewer BRAINX
 *
 */
public class MPRViewer
{
    static {
        // VTK
        System.loadLibrary("vtkCommonJava");
        System.loadLibrary("vtkFilteringJava");
        System.loadLibrary("vtkIOJava");
        System.loadLibrary("vtkImagingJava");
        System.loadLibrary("vtkGraphicsJava");
        System.loadLibrary("vtkRenderingJava");
        // VTK-GDCM
        System.loadLibrary("vtkgdcmJava");
    }

    static FilenamesType fns = new FilenamesType();

    public static void process(String path)
    {
        fns.add( path );
    }

    // Process only files under dir
    public static void visitAllFiles(File dir)
    {
        if (dir.isDirectory())
        {
            String[] children = dir.list();
            for (int i=0; i<children.length; i++)
            {
                visitAllFiles(new File(dir, children[i]));
            }
        }
        else
        {
            process(dir.getPath());
        }
    }

    public static void main(String[] args) throws Exception
    {
        String dirname = args[0];
        if( !PosixEmulation.FileIsDirectory( dirname ) )
        {
            return;
        }
    }
}

```



```

File dir = new File(dirname);
visitAllFiles(dir);

IPPSorter ipp = new IPPSorter();
ipp.SetComputeZSpacing( true );
ipp.SetZSpacingTolerance( 1e-3 );
boolean b = ipp.Sort( fns );
if(!b)
{
    throw new Exception("Could not scan");
}
double ippzspacing = ipp.GetZSpacing();

FileNamesType sorted = ipp.GetFileNames();
vtkStringArray files = new vtkStringArray();
long nfiles = sorted.size();
//for( String f : sorted )
for (int i = 0; i < nfiles; i++) {
    String f = sorted.get(i);
    files.InsertNextValue( f );
}
vtkGDCMImageReader reader = new vtkGDCMImageReader();
reader.SetFileNames( files );
reader.Update(); // get spacing value

double[] spacing = reader.GetOutput().GetSpacing();

vtkImageChangeInformation change = new vtkImageChangeInformation();
change.SetInputConnection( reader.GetOutputPort() );
change.SetOutputSpacing( spacing[0], spacing[1], ippzspacing );

// A simple vtkInteractorStyleImage example for
// 3D image viewing with the vtkImageResliceMapper.
//
// Drag Left mouse button to window/level
// Shift-Left drag to rotate (oblique slice)
// Shift-Middle drag to slice through image
// OR Ctrl-Right drag to slice through image

// Create the RenderWindow, Renderer
vtkRenderer ren1 = new vtkRenderer();
vtkRenderWindow renWin = new vtkRenderWindow();
renWin.AddRenderer(ren1);

vtkImageResliceMapper im = new vtkImageResliceMapper();
im.SetInputConnection(change.GetOutputPort());
im.SliceFacesCameraOn();
im.SliceAtFocalPointOn();
im.BorderOff();

vtkImageProperty ip = new vtkImageProperty();
ip.SetColorWindow(2000);
ip.SetColorLevel(1000);
ip.SetAmbient(0.0);
ip.SetDiffuse(1.0);
ip.SetOpacity(1.0);
ip.SetInterpolationTypeToLinear();

vtkImageSlice ia = new vtkImageSlice();
ia.SetMapper(im);
ia.SetProperty(ip);

ren1.AddViewProp(ia);
ren1.SetBackground(0.1,0.2,0.4);
renWin.SetSize(300,300);

vtkRenderWindowInteractor iren = new vtkRenderWindowInteractor();
vtkInteractorStyleImage style = new vtkInteractorStyleImage();
style.SetInteractionModeToImage3D();
iren.SetInteractorStyle(style);
renWin.SetInteractor(iren);

// render the image
renWin.Render();
vtkCamera cam1 = ren1.GetActiveCamera();
cam1.ParallelProjectionOn();
ren1.ResetCameraClippingRange();
renWin.Render();

iren.Start();

```

```

    }
}

```

27.99 MPRViewer2.java

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/
import vtk.*;
import gdcm.*;
import java.io.File;

/*
 * Compilation:
 * CLASSPATH=vtkgdcml.jar:/usr/share/java/vtk.jar javac MPRViewer2.java
 *
 * Usage:
 * LD_LIBRARY_PATH=/usr/lib/jvm/java-6-openjdk/jre/lib/amd64/xawt:/usr/lib/jni:. CLASSPATH=/usr/share/java/
 *   vtk.jar:vtkgdcml.jar:gdcm.jar:. java MPRViewer2 BRAINX
 */
public class MPRViewer2
{
    static {
        // VTK
        System.loadLibrary("vtkCommonJava");
        System.loadLibrary("vtkFilteringJava");
        System.loadLibrary("vtkIOJava");
        System.loadLibrary("vtkImagingJava");
        System.loadLibrary("vtkGraphicsJava");
        System.loadLibrary("vtkRenderingJava");
        System.loadLibrary("vtkHybridJava");
        System.loadLibrary("vtkWidgetsJava");
        // VTK-GDCM
        System.loadLibrary("vtkgdcmlJava");
    }

    static FilenamesType fns = new FilenamesType();

    public static void process(String path)
    {
        fns.add( path );
    }

    // Process only files under dir
    public static void visitAllFiles(File dir)
    {
        if (dir.isDirectory())
        {
            String[] children = dir.list();
            for (int i=0; i<children.length; i++)
            {
                visitAllFiles(new File(dir, children[i]));
            }
        }
        else
        {
            process(dir.getPath());
        }
    }

    public void dointer(vtkImagePlaneWidget current_widget)
    {
        int cstat = current_widget.GetCursorDataStatus();
        double[] v = current_widget.GetCurrentCursorPosition();
        //System.out.println( cstat );
        //System.out.println( v[0] );
    }
}

```

```

        //System.out.println( v[1] );
        //System.out.println( v[2] );
        planeWidgetX.SetSliceIndex( (int)v[0] );
        planeWidgetY.SetSliceIndex( (int)v[1] );
        planeWidgetZ.SetSliceIndex( (int)v[2] );
        planeWidgetX.GetCurrentRenderer().ResetCameraClippingRange();
        planeWidgetY.GetCurrentRenderer().ResetCameraClippingRange();
        planeWidgetZ.GetCurrentRenderer().ResetCameraClippingRange();
    }
    public void startinterX()
    {
        dointer( planeWidgetX );
    }
    public void interX()
    {
        dointer( planeWidgetX );
    }
    public void endinterX()
    {
    }
    public void startinterY()
    {
        dointer( planeWidgetY );
    }
    public void interY()
    {
        dointer( planeWidgetY );
    }
    public void endinterY()
    {
    }
    public void startinterZ()
    {
        dointer( planeWidgetZ );
    }
    public void interZ()
    {
        dointer( planeWidgetZ );
    }
    public void endinterZ()
    {
        //System.out.println( "endinter" );
    }

    public static void AlignCamera(int slice_number, vtkImagePlaneWidget current_widget)
    {
        vtkImageData image = (vtkImageData)current_widget.GetInput();
        vtkRenderer ren = current_widget.GetCurrentRenderer();
        double[] origin = image.GetOrigin();
        double ox = origin[0];
        double oy = origin[1];
        double oz = origin[2];

        int wextent[] = image.GetWholeExtent();
        int xmin = wextent[0];
        int xmax = wextent[1];
        int ymin = wextent[2];
        int ymax = wextent[3];
        int zmin = wextent[4];
        int zmax = wextent[5];

        double[] spacing = image.GetSpacing();
        double sx = spacing[0];
        double sy = spacing[1];
        double sz = spacing[2];

        double cx = ox + (0.5*(xmax-xmin))*sx;
        double cy = oy + (0.5*(ymax-ymin))*sy;
        double cz = oz + (0.5*(zmax-zmin))*sz;
        double vx = 0, vy = 0, vz = 0;
        double nx = 0, ny = 0, nz = 0;
        int iaxis = current_widget.GetPlaneOrientation();
        if ( iaxis == 0 ) {
            vz = -1;
            nx = ox + xmax*sx;
            cx = ox + slice_number*sx;
        }
        else if ( iaxis == 1 ) {
            vz = -1;
            ny = oy+ymax*sy;
            cy = oy+slice_number*sy;

```

```

    }
    else {
        vy = 1;
        nz = oz+zMax*sz;
        cz = oz+slice_number*sz;
    }
    double px = cx+nx*2;
    double py = cy+ny*2;
    double pz = cz+nz*3;

    vtkCamera camera = ren.GetActiveCamera();
    camera.SetViewUp(vx, vy, vz);
    camera.SetFocalPoint(cx, cy, cz);
    camera.SetPosition(px, py, pz);
    camera.OrthogonalizeViewUp();
    ren.ResetCameraClippingRange();
}

private vtkImagePlaneWidget planeWidgetX = new vtkImagePlaneWidget();
private vtkImagePlaneWidget planeWidgetY = new vtkImagePlaneWidget();
private vtkImagePlaneWidget planeWidgetZ = new vtkImagePlaneWidget();

public void config()
{
    //System.out.println( "config" );
    planeWidgetX.GetCurrentRenderer().ResetCamera();
    planeWidgetY.GetCurrentRenderer().ResetCamera();
    planeWidgetZ.GetCurrentRenderer().ResetCamera();
}

public void Run(String dirname)
{
    File dir = new File(dirname);
    visitAllFiles(dir);

    IPPSorter ipp = new IPPSorter();
    ipp.SetComputeZSpacing( true );
    ipp.SetZSpacingTolerance( 1e-3 );
    boolean b = ipp.Sort( fns );
    if(!b)
    {
        //throw new Exception("Could not scan");
    }
    double ippzspacing = ipp.GetZSpacing();

    FilenamesType sorted = ipp.GetFilenames();
    vtkStringArray files = new vtkStringArray();
    long nfiles = sorted.size();
    //for( String f : sorted )
    for (int i = 0; i < nfiles; i++) {
        String f = sorted.get(i);
        files.InsertNextValue( f );
    }
    vtkGDCMImageReader reader = new vtkGDCMImageReader();
    reader.SetFileNames( files );
    reader.Update(); // get spacing value

    double[] spacing = reader.GetOutput().GetSpacing();

    vtkImageChangeInformation change = new vtkImageChangeInformation();
    change.SetInputConnection( reader.GetOutputPort() );
    change.SetOutputSpacing( spacing[0], spacing[1], ippzspacing );
    change.Update();

    System.out.println( change.GetOutput().toString() );

    vtkRenderer ren1 = new vtkRenderer();
    ren1.SetViewport(0., 0., 0.333, 1);
    ren1.SetBackground(0.1,0.2,0.4);
    vtkRenderer ren2 = new vtkRenderer();
    ren2.SetViewport(0.333, 0., 0.667, 1);
    ren2.SetBackground(0.1,0.2,0.4);
    vtkRenderer ren3 = new vtkRenderer();
    ren3.SetViewport(0.667, 0., 1., 1.);
    ren3.SetBackground(0.1,0.2,0.4);

    vtkRenderWindow renWin = new vtkRenderWindow();
    renWin.AddRenderer(ren1);
    renWin.AddRenderer(ren2);
    renWin.AddRenderer(ren3);

```

```

vtkRenderWindowInteractor iren = new vtkRenderWindowInteractor();
iren.SetRenderWindow(renWin);

vtkInteractorStyleImage style = new vtkInteractorStyleImage();
iren.SetInteractorStyle( style );

vtkCellPicker picker = new vtkCellPicker();
picker.SetTolerance(0.005);

vtkProperty ipwProp = new vtkProperty();

//vtkImagePlaneWidget planeWidgetX = new vtkImagePlaneWidget();
planeWidgetX.SetInteractor(iren);
planeWidgetX.SetCurrentRenderer(ren1);
planeWidgetX.SetDefaultRenderer(ren1);
planeWidgetX.RestrictPlaneToVolumeOn();
planeWidgetX.SetTexturePlaneProperty(ipwProp);
//planeWidgetX.GetPlaneProperty().SetColor(1,0,0);
//planeWidgetX.TextureInterpolateOff();
//planeWidgetX.SetResliceInterpolateToNearestNeighbour();
planeWidgetX.SetInput(change.GetOutput());
planeWidgetX.SetPlaneOrientationToXAxes();
planeWidgetX.SetSliceIndex(62);
planeWidgetX.SetPicker(picker);
planeWidgetX.SetKeyPressActivationValue('x');
planeWidgetX.On();
planeWidgetX.InteractionOn();

//vtkImagePlaneWidget planeWidgetY = new vtkImagePlaneWidget();
planeWidgetY.SetInteractor(iren);
planeWidgetY.SetCurrentRenderer(ren2);
planeWidgetY.SetDefaultRenderer(ren2);
planeWidgetY.RestrictPlaneToVolumeOn();
planeWidgetY.SetTexturePlaneProperty(ipwProp);
//planeWidgetY.GetPlaneProperty().SetColor(1,0,0);
//planeWidgetY.TextureInterpolateOff();
//planeWidgetY.SetResliceInterpolateToNearestNeighbour();
planeWidgetY.SetInput(change.GetOutput());
planeWidgetY.SetLookupTable( planeWidgetX.GetLookupTable() );
planeWidgetY.SetPlaneOrientationToYAxes();
planeWidgetY.SetSliceIndex(32);
planeWidgetY.SetPicker(picker);
planeWidgetY.SetKeyPressActivationValue('y');
planeWidgetY.On();

//vtkImagePlaneWidget planeWidgetZ = new vtkImagePlaneWidget();
planeWidgetZ.SetInteractor(iren);
planeWidgetZ.SetCurrentRenderer(ren3);
planeWidgetZ.SetDefaultRenderer(ren3);
planeWidgetZ.RestrictPlaneToVolumeOn();
planeWidgetZ.SetTexturePlaneProperty(ipwProp);
//planeWidgetZ.GetPlaneProperty().SetColor(1,0,0);
//planeWidgetZ.TextureInterpolateOff();
//planeWidgetZ.SetResliceInterpolateToNearestNeighbour();
planeWidgetZ.SetInput(change.GetOutput());
planeWidgetZ.SetLookupTable( planeWidgetX.GetLookupTable() );
planeWidgetZ.SetPlaneOrientationToZAxes();
planeWidgetZ.SetSliceIndex(32);
planeWidgetZ.SetPicker(picker);
planeWidgetZ.SetKeyPressActivationValue('z');
planeWidgetZ.On();

iren.Initialize();

renWin.Render();
AlignCamera(52, planeWidgetX);
AlignCamera(32, planeWidgetY);
AlignCamera(32, planeWidgetZ);

planeWidgetX.GetCurrentRenderer().ResetCamera();
planeWidgetY.GetCurrentRenderer().ResetCamera();
planeWidgetZ.GetCurrentRenderer().ResetCamera();

renWin.Render();

planeWidgetX.AddObserver("StartInteractionEvent", this,"startinterX");
planeWidgetX.AddObserver("InteractionEvent", this,"interX");
planeWidgetX.AddObserver("EndInteractionEvent", this,"endinterX");
planeWidgetY.AddObserver("StartInteractionEvent", this,"startinterY");
planeWidgetY.AddObserver("InteractionEvent", this,"interY");

```

```

planeWidgetY.AddObserver("EndInteractionEvent", this,"endinterY");
planeWidgetZ.AddObserver("StartInteractionEvent", this,"startinterZ");
planeWidgetZ.AddObserver("InteractionEvent", this,"interZ");
planeWidgetZ.AddObserver("EndInteractionEvent", this,"endinterZ");

iren.AddObserver("ConfigureEvent", this,"config");

iren.Start();
}

public static void main(String[] args) throws Exception
{
    String dirname = args[0];
    if( !PosixEmulation.FileIsDirectory( dirname ) )
    {
        return;
    }

    MPRViewer2 me = new MPRViewer2();
    me.Run( dirname );
}
}

```

27.100 MrProtocol.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcml.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 *
 */

/*
28 - 'MrProtocol' VM 1, VR UN, SyngoDT 0, NoOfItems 6, Data '### ASCCONV BEGIN ###
ulVersion                               = 0xbee332
tSequenceFileName                       = "%SiemensSeq%\flfq_shphs"
tProtocolName                           = "flash+AF8-100+AF8-through-plane+AF8-V"
tReferenceImage0                         = "1.3.12.2.1107.5.2.9.16041.30000007062106100181200004658"
tReferenceImage1                         = "1.3.12.2.1107.5.2.9.16041.30000007062106100181200004635"
tReferenceImage2                         = "1.3.12.2.1107.5.2.9.16041.30000007062106100181200004683"
ucScanRegionPosValid                    = 0x1
sProtConsistencyInfo.tBaselineString    = "N4_VB11A_LATEST_20031004"
sProtConsistencyInfo.flNominalB0         = 1.494
sProtConsistencyInfo.flGMax              = 22
sProtConsistencyInfo.flRiseTime          = 10
sGRADSPEC.sEddyCompensationX.aflAmplitude[0] = 0.0141111
sGRADSPEC.sEddyCompensationX.aflAmplitude[1] = 0.057038
sGRADSPEC.sEddyCompensationX.aflAmplitude[2] = -0.00986504
sGRADSPEC.sEddyCompensationX.aflAmplitude[3] = 0.00247627
sGRADSPEC.sEddyCompensationX.aflAmplitude[4] = 0.0026377
sGRADSPEC.sEddyCompensationX.aflTimeConstant[0] = 1.53826
sGRADSPEC.sEddyCompensationX.aflTimeConstant[1] = 0.746617
sGRADSPEC.sEddyCompensationX.aflTimeConstant[2] = 0.339236
sGRADSPEC.sEddyCompensationX.aflTimeConstant[3] = 0.0309809
sGRADSPEC.sEddyCompensationX.aflTimeConstant[4] = 0.00067694
sGRADSPEC.sEddyCompensationY.aflAmplitude[0] = 0.0156411
sGRADSPEC.sEddyCompensationY.aflAmplitude[1] = 0.0440623
sGRADSPEC.sEddyCompensationY.aflAmplitude[2] = -0.00782663
sGRADSPEC.sEddyCompensationY.aflAmplitude[3] = 0.00186828
sGRADSPEC.sEddyCompensationY.aflAmplitude[4] = 0.00154504
sGRADSPEC.sEddyCompensationY.aflTimeConstant[0] = 1.47145
sGRADSPEC.sEddyCompensationY.aflTimeConstant[1] = 0.750538
sGRADSPEC.sEddyCompensationY.aflTimeConstant[2] = 0.339397
sGRADSPEC.sEddyCompensationY.aflTimeConstant[3] = 0.0312962
sGRADSPEC.sEddyCompensationY.aflTimeConstant[4] = 0.000895133
sGRADSPEC.sEddyCompensationZ.aflAmplitude[0] = 0.00618504
sGRADSPEC.sEddyCompensationZ.aflAmplitude[1] = 0.00313121

```

```
sGRADSPEC.sEddyCompensationZ.aflAmplitude[2] = 0.000289346
sGRADSPEC.sEddyCompensationZ.aflAmplitude[3] = -0.00019677
sGRADSPEC.sEddyCompensationZ.aflAmplitude[4] = 7.66445e-005
sGRADSPEC.sEddyCompensationZ.aflTimeConstant[0] = 3.37462
sGRADSPEC.sEddyCompensationZ.aflTimeConstant[1] = 0.999351
sGRADSPEC.sEddyCompensationZ.aflTimeConstant[2] = 0.0174646
sGRADSPEC.sEddyCompensationZ.aflTimeConstant[3] = 0.0110094
sGRADSPEC.sEddyCompensationZ.aflTimeConstant[4] = 0.00199922
sGRADSPEC.bEddyCompensationValid = 1
sGRADSPEC.sB0CompensationX.aflAmplitude[0] = 0.307474
sGRADSPEC.sB0CompensationX.aflAmplitude[1] = 0.029337
sGRADSPEC.sB0CompensationX.aflAmplitude[2] = -0.187118
sGRADSPEC.sB0CompensationX.aflTimeConstant[0] = 0.98583
sGRADSPEC.sB0CompensationX.aflTimeConstant[1] = 0.0308443
sGRADSPEC.sB0CompensationX.aflTimeConstant[2] = 0.000466792
sGRADSPEC.sB0CompensationY.aflAmplitude[0] = 0.365257
sGRADSPEC.sB0CompensationY.aflAmplitude[1] = -0.318647
sGRADSPEC.sB0CompensationY.aflAmplitude[2] = -0.0118978
sGRADSPEC.sB0CompensationY.aflTimeConstant[0] = 0.61535
sGRADSPEC.sB0CompensationY.aflTimeConstant[1] = 0.488831
sGRADSPEC.sB0CompensationY.aflTimeConstant[2] = 0.00199991
sGRADSPEC.sB0CompensationZ.aflAmplitude[0] = -0.44647
sGRADSPEC.sB0CompensationZ.aflAmplitude[1] = -0.0455154
sGRADSPEC.sB0CompensationZ.aflAmplitude[2] = -0.0304901
sGRADSPEC.sB0CompensationZ.aflTimeConstant[0] = 0.959231
sGRADSPEC.sB0CompensationZ.aflTimeConstant[1] = 0.0720189
sGRADSPEC.sB0CompensationZ.aflTimeConstant[2] = 0.00190141
sGRADSPEC.bB0CompensationValid = 1
sGRADSPEC.sCrossTermCompensationXY.aflAmplitude[0] = 0.00105046
sGRADSPEC.sCrossTermCompensationXY.aflTimeConstant[0] = 0.842014
sGRADSPEC.sCrossTermCompensationXZ.aflAmplitude[0] = -0.00150189
sGRADSPEC.sCrossTermCompensationXZ.aflTimeConstant[0] = 0.736169
sGRADSPEC.sCrossTermCompensationYX.aflAmplitude[0] = -5.5278e-005
sGRADSPEC.sCrossTermCompensationYX.aflTimeConstant[0] = 0.228697
sGRADSPEC.sCrossTermCompensationYZ.aflAmplitude[0] = 0.000307999
sGRADSPEC.sCrossTermCompensationYZ.aflTimeConstant[0] = 1.19431
sGRADSPEC.sCrossTermCompensationZX.aflAmplitude[0] = -0.000286868
sGRADSPEC.sCrossTermCompensationZX.aflTimeConstant[0] = 0.665979
sGRADSPEC.sCrossTermCompensationZY.aflAmplitude[0] = 0.000355175
sGRADSPEC.sCrossTermCompensationZY.aflTimeConstant[0] = 0.844189
sGRADSPEC.bCrossTermCompensationValid = 1
sGRADSPEC.lOffsetX = 25
sGRADSPEC.lOffsetY = 84
sGRADSPEC.lOffsetZ = 47
sGRADSPEC.bOffsetValid = 1
sGRADSPEC.lDelayX = 12
sGRADSPEC.lDelayY = 11
sGRADSPEC.lDelayZ = 9
sGRADSPEC.bDelayValid = 1
sGRADSPEC.flSensitivityX = 0.000264087
sGRADSPEC.flSensitivityY = 0.000272009
sGRADSPEC.flSensitivityZ = 0.000272677
sGRADSPEC.bSensitivityValid = 1
sGRADSPEC.alShimCurrent[0] = 183
sGRADSPEC.alShimCurrent[1] = -25
sGRADSPEC.alShimCurrent[2] = -85
sGRADSPEC.alShimCurrent[3] = 378
sGRADSPEC.alShimCurrent[4] = 82
sGRADSPEC.bShimCurrentValid = 1
sGRADSPEC.ucMode = 0x2
sTXSPEC.asNucleusInfo[0].tNucleus = "1H"
sTXSPEC.asNucleusInfo[0].lFrequency = 63684693
sTXSPEC.asNucleusInfo[0].bFrequencyValid = 1
sTXSPEC.asNucleusInfo[0].flReferenceAmplitude = 359.734
sTXSPEC.asNucleusInfo[0].bReferenceAmplitudeValid = 1
sTXSPEC.asNucleusInfo[0].flAmplitudeCorrection = 1
sTXSPEC.asNucleusInfo[0].bAmplitudeCorrectionValid = 1
sTXSPEC.asNucleusInfo[1].bFrequencyValid = 1
sTXSPEC.asNucleusInfo[1].bReferenceAmplitudeValid = 1
sTXSPEC.asNucleusInfo[1].bAmplitudeCorrectionValid = 1
sTXSPEC.arFPULSE[0].tName = "03GreFCE"
sTXSPEC.arFPULSE[0].bAmplitudeValid = 0x1
sTXSPEC.arFPULSE[0].flAmplitude = 147.095
sTXSPEC.arFPULSE[1].tName = "02GreFCE"
sTXSPEC.arFPULSE[1].bAmplitudeValid = 0x1
sTXSPEC.arFPULSE[1].flAmplitude = 147.095
sTXSPEC.arFPULSE[2].tName = "01GreFCE"
sTXSPEC.arFPULSE[2].bAmplitudeValid = 0x1
sTXSPEC.arFPULSE[2].flAmplitude = 147.095
sTXSPEC.lNoOfTraPulses = 3
sTXSPEC.lBTB1ParallelCapacity = 2
```

```

sTXSPEC.lBTB1SerialCapacity      = 24
sTXSPEC.lBTB2ParallelCapacity    = 2
sTXSPEC.lBTB2SerialCapacity      = 26
sTXSPEC.bBTBValid                = 1
sTXSPEC.flKDynMagnitudeMin       = 0.5
sTXSPEC.flKDynMagnitudeMax       = 1.5
sTXSPEC.flKDynMagnitudeClipLow   = 0.96
sTXSPEC.flKDynMagnitudeClipHigh  = 1.04
sTXSPEC.flKDynPhaseMax           = 0.698132
sTXSPEC.flKDynPhaseClip          = 0.174533
sTXSPEC.bKDynValid               = 1
sTXSPEC.ucRFPulseType            = 0x1
sTXSPEC.ucExcitMode               = 0x1
sTXSPEC.ucSimultaneousExcitation = 0x1
sRXSPEC.lGain                    = 1
sRXSPEC.bGainValid               = 1
sRXSPEC.aFFT_SCALE[0].lRxChannel = 1
sRXSPEC.aFFT_SCALE[0].flFactor   = 1.06857
sRXSPEC.aFFT_SCALE[0].bValid     = 1
sRXSPEC.aFFT_SCALE[1].lRxChannel = 2
sRXSPEC.aFFT_SCALE[1].flFactor   = 1.07454
sRXSPEC.aFFT_SCALE[1].bValid     = 1
sRXSPEC.aFFT_SCALE[2].lRxChannel = 3
sRXSPEC.aFFT_SCALE[2].flFactor   = 1.06622
sRXSPEC.aFFT_SCALE[2].bValid     = 1
sRXSPEC.aFFT_SCALE[3].lRxChannel = 4
sRXSPEC.aFFT_SCALE[3].flFactor   = 1.06524
sRXSPEC.aFFT_SCALE[3].bValid     = 1
sRXSPEC.aFFT_SCALE[4].lRxChannel = 5
sRXSPEC.aFFT_SCALE[4].flFactor   = 0.982692
sRXSPEC.aFFT_SCALE[4].bValid     = 1
sRXSPEC.aFFT_SCALE[5].lRxChannel = 6
sRXSPEC.aFFT_SCALE[5].flFactor   = 0.988603
sRXSPEC.aFFT_SCALE[5].bValid     = 1
sRXSPEC.aFFT_SCALE[6].lRxChannel = 7
sRXSPEC.aFFT_SCALE[6].flFactor   = 0.981538
sRXSPEC.aFFT_SCALE[6].bValid     = 1
sRXSPEC.aFFT_SCALE[7].lRxChannel = 8
sRXSPEC.aFFT_SCALE[7].flFactor   = 1.00856
sRXSPEC.aFFT_SCALE[7].bValid     = 1
sRXSPEC.bVariCapVoltagesValid    = 1
sRXSPEC.alDwellTime[0]           = 8500
sAdjFreSpec.ulMode                = 0x1
sAdjFreSpec.ucAdjWithBC           = 0x1
sAdjTraSpec.ucAdjWithBC           = 0x1
sAdjShimSpec.ulMode               = 0x1
sAdjShimSpec.ucAdjWithBC          = 0x1
sAdjWatSupSpec.ulMode             = 0x1
sAdjWatSupSpec.ucAdjWithBC        = 0x1
alTR[0]                           = 37000
lContrasts                        = 1
alTE[0]                           = 4000
acFlowComp[0]                    = 1
lCombinedEchoes                   = 1
sSliceArray.asSlice[0].sPosition.dSag = 35.31199581
sSliceArray.asSlice[0].sPosition.dCor = -8.387765754
sSliceArray.asSlice[0].sPosition.dTra = -23.13178296
sSliceArray.asSlice[0].sNormal.dSag  = 0.771051253
sSliceArray.asSlice[0].sNormal.dCor  = 0.5863890019
sSliceArray.asSlice[0].sNormal.dTra  = -0.2482496801
sSliceArray.asSlice[0].dThickness    = 6
sSliceArray.asSlice[0].dPhaseFOV     = 187.5
sSliceArray.asSlice[0].dReadoutFOV   = 250
sSliceArray.lSize                    = 1
sSliceArray.lSag                     = 1
sSliceArray.lConc                    = 1
sSliceArray.ucMode                    = 0x1
sSliceArray.sTSat.dThickness          = 40
sSliceArray.sTSat.dGap                = 10
sGroupArray.asGroup[0].nSize          = 1
sGroupArray.asGroup[0].dDistFact      = 0.2
sGroupArray.anMember[1]               = -1
sGroupArray.lSize                     = 1
sGroupArray.sPSat.dThickness          = 50
sGroupArray.sPSat.dGap                = 10
sAutoAlign.dAAMatrix[0]              = 1
sAutoAlign.dAAMatrix[5]              = 1
sAutoAlign.dAAMatrix[10]             = 1
sAutoAlign.dAAMatrix[15]             = 1
sNavigatorPara.ucRespComp             = 0x4
sPrepPulses.ucFatSat                 = 0x4

```



```

sPrepPulses.ucWaterSat           = 0x4
sPrepPulses.ucInversion          = 0x4
sPrepPulses.ucSatRecovery        = 0x1
sPrepPulses.ucFatSatMode         = 0x2
sKSpace.lBaseResolution          = 256
sKSpace.lPhaseEncodingLines      = 192
sKSpace.dPhaseResolution         = 1
sKSpace.lPartitions              = 32
sKSpace.lImagesPerSlab           = 32
sKSpace.dSliceResolution         = 1
sKSpace.ucPhasePartialFourier    = 0x10
sKSpace.ucSlicePartialFourier    = 0x10
sKSpace.ucAveragingMode          = 0x2
sKSpace.ucMultiSliceMode         = 0x1
sKSpace.ucDimension              = 0x2
sKSpace.ucAsymmetricEchoAllowed = 0x1
sKSpace.unReordering             = 0x1
sFastImaging.lEPIFactor          = 1
sFastImaging.lTurboFactor        = 1
sFastImaging.lSegments           = 3
sFastImaging.ulEnableRFSpoiling  = 0x1
sPhysioImaging.lSignal1          = 2
sPhysioImaging.lMethod1          = 2
sPhysioImaging.lSignal2          = 1
sPhysioImaging.lMethod2          = 1
sPhysioImaging.lPhases           = 21
sPhysioImaging.lRetroGatedImages = 16
sPhysioImaging.sPhysioECG.lScanWindow = 805
sPhysioImaging.sPhysioECG.lTriggerPulses = 1
sPhysioImaging.sPhysioECG.lTriggerWindow = 5
sPhysioImaging.sPhysioECG.lArrhythmiaDetection = 1
sPhysioImaging.sPhysioECG.lCardiacGateOnThreshold = 100000
sPhysioImaging.sPhysioECG.lCardiacGateOffThreshold = 700000
sPhysioImaging.sPhysioPulse.lTriggerPulses = 1
sPhysioImaging.sPhysioPulse.lTriggerWindow = 5
sPhysioImaging.sPhysioPulse.lCardiacGateOnThreshold = 100000
sPhysioImaging.sPhysioPulse.lCardiacGateOffThreshold = 700000
sPhysioImaging.sPhysioExt.lTriggerPulses = 1
sPhysioImaging.sPhysioExt.lTriggerWindow = 5
sPhysioImaging.sPhysioExt.lCardiacGateOnThreshold = 100000
sPhysioImaging.sPhysioExt.lCardiacGateOffThreshold = 700000
sPhysioImaging.sPhysioResp.lRespGateThreshold = 20
sPhysioImaging.sPhysioResp.lRespGatePhase = 2
sPhysioImaging.sPhysioResp.dGatingRatio = 0.3
sSpecPara.lPhaseCyclingType      = 1
sSpecPara.lPhaseEncodingType     = 1
sSpecPara.lRFExcitationBandwidth = 1
sSpecPara.ucRemoveOversampling   = 0x1
sSpecPara.lDecouplingType        = 1
sSpecPara.lNOEType               = 1
sSpecPara.lExcitationType        = 1
sSpecPara.lSpectralSuppression   = 1
sDiffusion.ulMode                 = 0x1
sAngio.sFlowArray.asElm[0].nVelocity = 100
sAngio.sFlowArray.asElm[0].nDir   = 0x4
sAngio.sFlowArray.lSize           = 1
sAngio.ucPCFlowMode               = 0x2
sAngio.ucTOFInflow                = 0x4
sAngio.ucRephasedImage            = 0x1
sAngio.ucPhaseImage               = 0x1
sEllipticalFilter.ucMode          = 0x1
sPat.lAccelFactPE                 = 1
sPat.lAccelFact3D                 = 1
sPat.ucPATMode                    = 0x1
sPat.ucRefScanMode                = 0x1
ucAutoMovie                       = 0x1
ucDisableChangeStoreImages        = 0x1
ucReconstructionMode              = 0x1
ucPHAPSMode                       = 0x1
ucDixon                           = 0x1
lAverages                         = 2
adFlipAngleDegree[0]              = 30
lScanTimeSec                      = 103
lTotalScanTimeSec                 = 112
dRefSNR                           = 165404.1473
dRefSNR_VOI                       = 165404.1473
tdefaultEVAProt                   = "%SiemensEvaDefProt%\Inline\Inline.evp"
tcurrentEVAProt                   = "%CURRENTEVAPROT%\EVA2A5.tmp"
sCOIL_SELECT_MEAS.asList[0].sCoilElementID.tCoilID = "6_Ch_Body_P"
sCOIL_SELECT_MEAS.asList[0].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[0].sCoilElementID.tElement = "PP6"

```

```

sCOIL_SELECT_MEAS.asList[0].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[0].lRxChannelConnected = 1
sCOIL_SELECT_MEAS.asList[1].sCoilElementID.tCoilID = "6_Ch_Body_P"
sCOIL_SELECT_MEAS.asList[1].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[1].sCoilElementID.tElement = "PP5"
sCOIL_SELECT_MEAS.asList[1].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[1].lRxChannelConnected = 1
sCOIL_SELECT_MEAS.asList[2].sCoilElementID.tCoilID = "6_Ch_Body_P"
sCOIL_SELECT_MEAS.asList[2].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[2].sCoilElementID.tElement = "PP3"
sCOIL_SELECT_MEAS.asList[2].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[2].lRxChannelConnected = 2
sCOIL_SELECT_MEAS.asList[3].sCoilElementID.tCoilID = "6_Ch_Body_P"
sCOIL_SELECT_MEAS.asList[3].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[3].sCoilElementID.tElement = "PP4"
sCOIL_SELECT_MEAS.asList[3].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[3].lRxChannelConnected = 3
sCOIL_SELECT_MEAS.asList[4].sCoilElementID.tCoilID = "6_Ch_Body_P"
sCOIL_SELECT_MEAS.asList[4].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[4].sCoilElementID.tElement = "PP2"
sCOIL_SELECT_MEAS.asList[4].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[4].lRxChannelConnected = 4
sCOIL_SELECT_MEAS.asList[5].sCoilElementID.tCoilID = "6_Ch_Body_P"
sCOIL_SELECT_MEAS.asList[5].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[5].sCoilElementID.tElement = "PP1"
sCOIL_SELECT_MEAS.asList[5].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[5].lRxChannelConnected = 4
sCOIL_SELECT_MEAS.asList[6].sCoilElementID.tCoilID = "6_Ch_Body_A"
sCOIL_SELECT_MEAS.asList[6].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[6].sCoilElementID.tElement = "PA6"
sCOIL_SELECT_MEAS.asList[6].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[6].lRxChannelConnected = 5
sCOIL_SELECT_MEAS.asList[7].sCoilElementID.tCoilID = "6_Ch_Body_A"
sCOIL_SELECT_MEAS.asList[7].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[7].sCoilElementID.tElement = "PA5"
sCOIL_SELECT_MEAS.asList[7].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[7].lRxChannelConnected = 5
sCOIL_SELECT_MEAS.asList[8].sCoilElementID.tCoilID = "6_Ch_Body_A"
sCOIL_SELECT_MEAS.asList[8].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[8].sCoilElementID.tElement = "PA3"
sCOIL_SELECT_MEAS.asList[8].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[8].lRxChannelConnected = 6
sCOIL_SELECT_MEAS.asList[9].sCoilElementID.tCoilID = "6_Ch_Body_A"
sCOIL_SELECT_MEAS.asList[9].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[9].sCoilElementID.tElement = "PA4"
sCOIL_SELECT_MEAS.asList[9].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[9].lRxChannelConnected = 7
sCOIL_SELECT_MEAS.asList[10].sCoilElementID.tCoilID = "6_Ch_Body_A"
sCOIL_SELECT_MEAS.asList[10].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[10].sCoilElementID.tElement = "PA2"
sCOIL_SELECT_MEAS.asList[10].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[10].lRxChannelConnected = 8
sCOIL_SELECT_MEAS.asList[11].sCoilElementID.tCoilID = "6_Ch_Body_A"
sCOIL_SELECT_MEAS.asList[11].sCoilElementID.lCoilCopy = 1
sCOIL_SELECT_MEAS.asList[11].sCoilElementID.tElement = "PA1"
sCOIL_SELECT_MEAS.asList[11].lElementSelected = 1
sCOIL_SELECT_MEAS.asList[11].lRxChannelConnected = 8
sCOIL_SELECT_MEAS.sCOILPLUGS.aulPlugId[0] = 0xff
sCOIL_SELECT_MEAS.sCOILPLUGS.aulPlugId[1] = 0x76
sCOIL_SELECT_MEAS.sCOILPLUGS.aulPlugId[2] = 0x78
sCOIL_SELECT_MEAS.sCOILPLUGS.aulPlugId[3] = 0x87
sCOIL_SELECT_MEAS.sCOILPLUGS.aulPlugId[4] = 0x67
sCOIL_SELECT_MEAS.sCOILPLUGS.auiNmbrOfNibbles[0] = 0x2
sCOIL_SELECT_MEAS.sCOILPLUGS.auiNmbrOfNibbles[1] = 0x2
sCOIL_SELECT_MEAS.sCOILPLUGS.auiNmbrOfNibbles[2] = 0x2
sCOIL_SELECT_MEAS.sCOILPLUGS.auiNmbrOfNibbles[3] = 0x2
sCOIL_SELECT_MEAS.sCOILPLUGS.auiNmbrOfNibbles[4] = 0x2
sEFISPEC.bEFIDataValid = 1
### ASCCONV END ###
'
*/

/*
 * Table of equivalence:
 *
ulVersion = 0xbee332
<=>
27 - 'MrProtocolVersion' VM 1, VR IS, SyngoDT 6, NoOfItems 6, Data '12510002'
*/

#include "gdcMReader.h"

```

```

#include "gdcmImageReader.h"
#include "gdcmImageWriter.h"
#include "gdcmCSAHeader.h"
#include "gdcmAttribute.h"
#include "gdcmGlobal.h"
#include "gdcmDicts.h"

#include <map>

#include <math.h>

int main(int argc, char *argv [])
{
    if( argc < 2 ) return 1;
    const char *filename = argv[1];
    gdcm::ImageReader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Failed to read: " << filename << std::endl;
        return 1;
    }

    gdcm::CSAHeader csa;
    const gdcm::DataSet& ds = reader.GetFile().GetDataSet();

    //const gdcm::PrivateTag &t1 = csa.GetCSAImageHeaderInfoTag();
    const gdcm::PrivateTag &t2 = csa.GetCSASeriesHeaderInfoTag();

    if( ds.FindDataElement( t2 ) )
    {
        csa.LoadFromDataElement( ds.GetDataElement( t2 ) );
        //csa.Print( std::cout );
    }

    if( !csa.FindCSAElementByName( "MrProtocol" ) )
    {
        return 1;
    }
    const gdcm::CSAElement &csael = csa.GetCSAElementByName( "MrProtocol" );
    //std::cout << csael << std::endl;

    const gdcm::ByteValue *bv = csael.GetByteValue();
    if( !bv )
    {
        return 1;
    }
    std::string str(bv->GetPointer(), bv->GetLength());
    std::istringstream is(str);
    std::string s;
    typedef std::map< std::string, std::string > MyMapType;
    MyMapType mymap;
    while( std::getline(is, s) )
    {
        std::string::size_type pos = s.find( '=' );
        if( pos != std::string::npos )
        {
            std::string sub1 = s.substr(0, pos);
            sub1.erase( sub1.find_last_not_of(' ') + 1 );
            std::string sub2 = s.substr(pos+1); // skip the '=' char
            sub2.erase( 0, sub2.find_first_not_of(' ') );
            //std::cout << sub1 << std::endl;
            mymap.insert( MyMapType::value_type(sub1, sub2) );
        }
        else
        {
            // ### ASCCONV BEGIN ###
            // ### ASCCONV END ###
        }
    }

    const char fourierstr[] = "sKSpace.ucSlicePartialFourier";
    const gdcm::CSAHeaderDict &csadict =
        gdcm::Global::GetInstance().GetDicts().
        GetCSAHeaderDict();
    const gdcm::CSAHeaderDictEntry &fourier = csadict.
        GetCSAHeaderDictEntry( fourierstr );
    std::cout << fourier << std::endl;
    MyMapType::const_iterator it = mymap.find( fourierstr );
    if( it == mymap.end() ) return 1;
    //std::cout << it->second << std::endl;

```

```

const std::string &partial_fourier = it->second;
if( partial_fourier == "0x1" )
{
    std::cout << "partial fourier is 4/8" << std::endl;
}
else if( partial_fourier == "0x2" )
{
    std::cout << "partial fourier is 5/8" << std::endl;
}
else if( partial_fourier == "0x4" )
{
    std::cout << "partial fourier is 6/8" << std::endl;
}
else if( partial_fourier == "0x8" )
{
    std::cout << "partial fourier is 7/8" << std::endl;
}
else if( partial_fourier == "0x10" )
{
    std::cout << "partial fourier is 8/8" << std::endl;
}
else
{
    std::cerr << "Impossible: " << partial_fourier << std::endl;
    return 1;
}

/*
This is the Flip Angle:
adFlipAngleDegree[0]                                = 30

One can find it also in the protocol:

...
    <ParamFunctor."<TlmapFunctor">">
    {
        <Class> "<TlmapFunctor@IceImagePostProcFunctors">

        <ParamBool."<EXECUTE">"> { }
        <ParamDouble."<Flipl_deg">"> { <Precision> 16 14.7378520000000000 }
    }
...

*/
// Below is an attemp to play with the CSAHeader dict:
#ifdef 0
const char gspec[] = "sGRADSPEC.flSensitivityX";
it = mymap.find( gspec );
if( it == mymap.end() ) return 1;
const std::string &dummy = it->second;
std::cout << dummy << std::endl;

const gdcm::CSAHeaderDictEntry &csaentry = csadict.
    GetCSAHeaderDictEntry( gspec );
std::cout << csaentry << std::endl;
#endif

/*
sSliceArray.ucMode -- should be in (1, 2, 4)
enum SeriesMode
{
    ASCENDING    = 0x01,
    DESCENDING   = 0x02,
    INTERLEAVED  = 0x04
};

*/
const char sliceorderstr[] = "sSliceArray.ucMode";
const gdcm::CSAHeaderDictEntry &sliceorder = csadict.
    GetCSAHeaderDictEntry( sliceorderstr );
std::cout << sliceorder << std::endl;

it = mymap.find ( sliceorderstr );
if( it == mymap.end() ) return 1;
const std::string &slice_order = it->second;
if( slice_order == "0x1" )
{
    std::cout << "slice_order: ASCENDING" << std::endl;
}
else if( slice_order == "0x2" )
{
    std::cout << "slice_order: DESCENDING" << std::endl;
}

```

```

else if( slice_order == "0x4" )
{
    std::cout << "slice_order: INTERLEAVED" << std::endl;
}
else
{
    std::cerr << "Impossible: " << slice_order << std::endl;
    return 1;
}

return 0;
}

```

27.101 NewSequence.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/NewSequence.exe gdcmData/012345.002.050.dcm out.dcm
 */
using System;
//using gdcm;

public class NewSequence
{
    public static byte[] StrToByteArray(string str)
    {
        System.Text.ASCIIEncoding encoding=new System.Text.ASCIIEncoding();
        return encoding.GetBytes(str);
    }

    public static int Main(string[] argv)
    {
        string file1 = argv[0];
        string file2 = argv[1];

        gdcm.Reader r = new gdcm.Reader();
        r.SetFileName( file1 );
        if ( ! r.Read() )
        {
            return 1;
        }

        gdcm.File f = r.GetFile();
        gdcm.DataSet ds = f.GetDataSet();
        // tsis = gdcm.Tag(0x0008,0x2112) # SourceImageSequence

        // Create a dataelement
        gdcm.DataElement de = new gdcm.DataElement(new gdcm.Tag(0x0010, 0x2180));
        string occ = "Occupation";
        de.SetByteValue( StrToByteArray(occ), new gdcm.VL((uint)occ.Length));
        de.SetVR(new gdcm.VR(gdcm.VR.VRType.SH));

        // Create an item
        gdcm.Item it = new gdcm.Item();
        it.SetVLToUndefined(); // Needed to not popup error message
        //it.InsertDataElement(de)
        gdcm.DataSet nds = it.GetNestedDataSet();
        nds.Insert(de);

        // Create a Sequence
        gdcm.SmartPtrSQ sq = gdcm.SequenceOfItems.New();
        sq.SetLengthToUndefined();
    }
}

```

```

sq.AddItem(it);

// Insert sequence into data set
gdcM.DataElement des = new gdcM.DataElement(new gdcM.Tag(0x0400,0x0550));
des.SetVR(new gdcM.VR(gdcM.VR.VRType.SQ));
des.SetValue(sq.__ref__());
des.SetVLToUndefined();

ds.Insert(des);

gdcM.Writer w = new gdcM.Writer();
w.SetFile( f );
w.SetFileName( file2 );
if ( !w.Write() )
    return 1;

return 0;
}

```

27.102 NewSequence.py

```

1 #####
2 #
3 # Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 # Copyright (c) 2006-2011 Mathieu Malaterre
6 # All rights reserved.
7 # See Copyright.txt or http://gdcM.sourceforge.net/Copyright.html for details.
8 #
9 # This software is distributed WITHOUT ANY WARRANTY; without even
10 # the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 # PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:
17
18 python NewSequence.py input.dcm output.dcm
19
20
21 Thanks to Robert Irie for code
22 """
23
24 import sys
25 import gdcM
26
27 if __name__ == "__main__":
28
29     file1 = sys.argv[1]
30     file2 = sys.argv[2]
31
32     r = gdcM.Reader()
33     r.SetFileName( file1 )
34     if not r.Read():
35         sys.exit(1)
36
37     f = r.GetFile()
38     ds = f.GetDataSet()
39     #tisis = gdcM.Tag(0x0008,0x2112) # SourceImageSequence
40
41     # Create a dataelement
42     de = gdcM.DataElement(gdcM.Tag(0x0010, 0x2180))
43     de.SetByteValue("Occupation", gdcM.VL(len("Occupation")))
44     de.SetVR(gdcM.VR(gdcM.VR.SH))
45
46     # Create an item
47     it=gdcM.Item()
48     it.SetVLToUndefined() # Needed to not popup error message
49     #it.InsertDataElement(de)
50     nds=it.GetNestedDataSet()
51     nds.Insert(de)
52
53     # Create a Sequence
54     sq=gdcM.SequenceOfItems().New()
55     sq.SetLengthToUndefined()

```

```

56  sq.AddItem(it)
57
58  # Insert sequence into data set
59  des=gdcml.DataElement(gdcml.Tag(0x0400,0x0550))
60  des.SetVR(gdcml.VR(gdcml.VR.SQ))
61  des.SetValue(sq.__ref__())
62  des.SetVLToUndefined()
63
64  ds.Insert(des)
65
66  w = gdcml.Writer()
67  w.SetFile( f )
68  w.SetFileName( file2 )
69  if not w.Write():
70      sys.exit(1)

```

27.103 offscreenimage.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

#include "vtkGDCMImageReader.h"
#include "vtkRenderWindow.h"
#include "vtkRenderer.h"
#include "vtkImageMapToWindowLevelColors.h"
#include "vtkImageActor.h"
#include "vtkPNGWriter.h"
#include "vtkWindowToImageFilter.h"
#include "vtkMedicalImageProperties.h"

int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        return 1;
    }
    const char *filename = argv[1];

    vtkGDCMImageReader *reader = vtkGDCMImageReader::New();
    reader->SetFileName( filename );
    reader->Update(); // important to read the window/level info

    vtkMedicalImageProperties *prop = reader->GetMedicalImageProperties();

    vtkRenderWindow *renWin = vtkRenderWindow::New();
    renWin->OffScreenRenderingOn();

    vtkRenderer *renderer = vtkRenderer::New();
    renWin->AddRenderer(renderer);

    vtkImageMapToWindowLevelColors *windowlevel = vtkImageMapToWindowLevelColors::New();
    windowlevel->SetInput( reader->GetOutput() );
    unsigned int n = prop->GetNumberOfWindowLevelPresets();
    if( n )
    {
        // Take the first one by default:
        const double *wl = prop->GetNthWindowLevelPreset(0);
        windowlevel->SetWindow( wl[0] );
        windowlevel->SetLevel( wl[1] );
    }

    vtkImageActor *actor = vtkImageActor::New();
    actor->SetInput( windowlevel->GetOutput() );

    renderer->AddActor( actor );

    renWin->Render();
}

```

```

vtkWindowToImageFilter *w2if = vtkWindowToImageFilter::New();
w2if->SetInput ( renWin );

vtkPNGWriter *wr = vtkPNGWriter::New();
wr->SetInput( w2if->GetOutput() );
wr->SetFileName ( "offscreenimage.png" );
wr->Write();

reader->Delete();
renWin->Delete();
renderer->Delete();
windowlevel->Delete();
actor->Delete();
w2if->Delete();
wr->Delete();

return 0;
}

```

27.104 PatchFile.cxx

This is a C++ example on how to use `gdcm::Attribute`

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * The image was a broken file where the Pixel Data element was 8 times too big
 * Apparently multiplying the BitsAllocated to 4 and multiplying the number of
 * frames by 2 would solve the problem
 *
 * This C++ code can be used to patch the header.
 */

#include "gdcmReader.h"
#include "gdcmImageReader.h"
#include "gdcmWriter.h"
#include "gdcmDataSet.h"
#include "gdcmAttribute.h"

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        return 1;
    }
    const char *f = argv[1];
    const char *out = argv[2];
    gdcm::Reader r;
    r.SetFileName( f );
    if( !r.Read() )
    {
        return 1;
    }

    gdcm::File &file = r.GetFile();
    gdcm::DataSet& ds = file.GetDataSet();
    // (0028,0100) US 16 # 2, 1 BitsAllocated
    // (0028,0101) US 16 # 2, 1 BitsStored
    // (0028,0102) US 15 # 2, 1 HighBit
    //
    {
        gdcm::Attribute<0x28,0x100> at;
        at.SetFromDataElement( ds.GetDataElement( at.
            GetTag() ) );
    }
}

```



```

    if( at.GetValue() != 8 )
    {
        return 1;
    }
    at.SetValue( 32 );
    ds.Replace( at.GetAsDataElement() );
}
{
    gdcm::Attribute<0x28,0x101> at;
    at.SetFromDataElement( ds.GetDataElement( at.
        GetTag() ) );
    if( at.GetValue() != 8 )
    {
        return 1;
    }
    at.SetValue( 32 );
    ds.Replace( at.GetAsDataElement() );
}
{
    gdcm::Attribute<0x28,0x102> at;
    at.SetFromDataElement( ds.GetDataElement( at.
        GetTag() ) );
    if( at.GetValue() != 7 )
    {
        return 1;
    }
    at.SetValue( 31 );
    ds.Replace( at.GetAsDataElement() );
}
// (0028,0008) IS [56] # 2, 1 NumberOfFrames

{
    gdcm::Attribute<0x28,0x8> at;
    at.SetFromDataElement( ds.GetDataElement( at.
        GetTag() ) );
    at.SetValue( at.GetValue() * 2 );
    ds.Replace( at.GetAsDataElement() );
}

gdcm::Writer w;
w.SetFile( file );
w.SetCheckFileMetaInformation( false );
w.SetFileName( out );
if( !w.Write() )
{
    return 1;
}

// Now let's see if we can read it as an image:
gdcm::ImageReader ir;
ir.SetFileName( out );
if(!ir.Read())
{
    return 1;
}
gdcm::Image &image = ir.GetImage();
unsigned long len = image.GetBufferLength();
const gdcm::ByteValue *bv = ir.GetFile().GetDataSet().
    GetDataElement( gdcm::Tag(0x7fe0,0x0010) ).GetByteValue();
if( !bv || len != bv->GetLength() )
{
    return 1;
}
std::cout << bv->GetLength() << " " << len << std::endl;

std::cout << "Success to rewrite image !" << std::endl;
image.Print( std::cout );
return 0;
}

```

27.105 PhilipsPrivateRescaleInterceptSlope.py

```

1 #####
2 #
3 # Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 # Copyright (c) 2006-2011 Mathieu Malaterre

```

```

6 # All rights reserved.
7 # See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 # This software is distributed WITHOUT ANY WARRANTY; without even
10 # the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 # PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:
17
18 python
19 """
20
21 import gdcm
22 import sys
23
24 filename = sys.argv[1]
25 tmpfile = "/tmp/philips_rescaled.dcm"
26
27
28 # Need to access some private tags, read the file :
29 reader = gdcm.Reader()
30 reader.SetFileName( filename )
31 if not reader.Read():
32     sys.exit(1)
33
34 ds = reader.GetFile().GetDataSet()
35
36 #print ds
37 # (2005,1409) DS 4 0.0
38 # (2005,140a) DS 16 1.52283272283272
39
40 # (2005,0014) LO 26 Philips MR Imaging DD 005
41 tag1 = gdcm.PrivateTag(0x2005,0x09,"Philips MR Imaging DD 005")
42 tag2 = gdcm.PrivateTag(0x2005,0x0a,"Philips MR Imaging DD 005")
43 print tag1
44 print tag2
45
46 # make sure to do a copy, we want the private tag to remain
47 # otherwise gdcm gives us a reference
48 e11 = gdcm.DataElement( ds.GetDataElement( tag1 ) )
49 print e11
50 e12 = gdcm.DataElement( ds.GetDataElement( tag2 ) )
51 print e12
52
53 # (0028,1052) DS [-1000] # 6, 1 RescaleIntercept
54 # (0028,1053) DS [1] # 2, 1 RescaleSlope
55
56 e11.SetTag( gdcm.Tag(0x0028,0x1052) )
57 e12.SetTag( gdcm.Tag(0x0028,0x1053) )
58
59 ds.Insert( e11 )
60 ds.Insert( e12 )
61
62 w = gdcm.Writer()
63 w.SetCheckFileMetaInformation( False )
64 w.SetFileName( tmpfile )
65 w.SetFile( reader.GetFile() )
66 if not w.Write():
67     sys.exit(1)
68
69 print "success"

```

27.106 PlaySound.py

```

1 #####
2 #
3 # Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 # Copyright (c) 2006-2011 Mathieu Malaterre
6 # All rights reserved.
7 # See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 # This software is distributed WITHOUT ANY WARRANTY; without even
10 # the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR

```

```

11 #     PURPOSE.  See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:
17
18 python PlaySound.py input.dcm
19 """
20
21 import gdcmm
22 import sys
23
24 #filename = "/home/mmalaterre/Creatis/gdcmDataExtra/gdcmNonImageData/audio_from_rafael_sanguinetti.dcm"
25 filename = sys.argv[1]
26 print filename
27
28 r = gdcmm.Reader()
29 r.SetFileName( filename )
30 if not r.Read():
31     sys.exit(1)
32
33 ds = r.GetFile().GetDataSet()
34
35 waveformtag = gdcmm.Tag(0x5400,0x0100)
36 waveformsq = ds.GetDataElement( waveformtag )
37 #print waveformsq
38
39 #print dir(waveformsq)
40
41 items = waveformsq.GetSequenceOfItems()
42
43 if not items.GetNumberOfItems():
44     sys.exit(1)
45
46 item = items.GetItem(1)
47 #print item
48
49 waveformds = item.GetNestedDataSet()
50 #print waveformds
51
52 waveformdatatag = gdcmm.Tag(0x5400,0x0101)
53 waveformdata = waveformds.GetDataElement( waveformdatatag )
54
55 #print waveformdata.GetPointer()
56 bv = waveformdata.GetByteValue()
57 print dir(bv)
58
59 #print bv.GetPointer()
60 print bv.GetLength()
61 l = 116838
62
63 file='test.wav'
64 myfile = open(file, "wb")
65 s = bv.GetPointer()
66 for i in range(0, l):
67     myfile.write(s[i])
68 myfile.close()
69
70 # http://mail.python.org/pipermail/python-list/2004-October/288905.html
71 if sys.platform.startswith('win'):
72     from winsound import PlaySound, SND_FILENAME, SND_ASYNC
73     PlaySound(file, SND_FILENAME|SND_ASYNC)
74 elif sys.platform.find('linux')>-1:
75     from wave import open as waveOpen
76     from ossaudiodev import open as ossOpen
77     s = waveOpen(file,'rb')
78     (nc,sw,fr,nf,comptype, compname) = s.getparams()
79     dsp = ossOpen('/dev/dsp','w')
80     try:
81         from ossaudiodev import AFMT_S16_NE
82     except ImportError:
83         if byteorder == "little":
84             AFMT_S16_NE = ossaudiodev.AFMT_S16_LE
85         else:
86             AFMT_S16_NE = ossaudiodev.AFMT_S16_BE
87     dsp.setparameters(AFMT_S16_NE, nc, fr)
88     data = s.readframes(nf)
89     s.close()
90     dsp.write(data)
91     dsp.close()

```

27.107 pmsct_rgb1.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * This example shows how to rewrite a ELSCINT1/PMSCT_RGB1 compressed
 * image so that it is readable by most 3rd party software (DICOM does
 * not specify this particular encoding).
 * This is required for the sake of interoperability with any standard
 * conforming DICOM system.
 *
 * Everything done in this code is for the sole purpose of writing interoperable
 * software under Sect. 1201 (f) Reverse Engineering exception of the DMCA.
 * If you believe anything in this code violates any law or any of your rights,
 * please contact us (gdcm-developers@lists.sourceforge.net) so that we can
 * find a solution.
 *
 * Everything you do with this code is at your own risk, since decompression
 * algorithm was not written from specification documents.
 *
 * Special thanks to:
 * Jean-Pierre Roux for providing the sample datasets
 */
#include "gdcmReader.h"
#include "gdcmPrivateTag.h"
#include "gdcmAttribute.h"
#include "gdcmImageWriter.h"

void delta_decode(const unsigned char *data_in, size_t data_size,
std::vector<unsigned char> &new_stream, unsigned short pc, size_t w, size_t h)
{
    const size_t plane_size = h * w;
    const size_t outputlen = 3 * plane_size;
    new_stream.resize( outputlen );

    assert( data_size != outputlen );
    if( data_size == outputlen )
    {
        return;
    }
    typedef unsigned char byte;
    enum {
        COLORMODE = 0x81,
        ESCMODE = 0x82,
        REPEATMODE = 0x83
    };

    byte* src = (byte*)data_in;
    byte* dest = (byte*)&new_stream[0];
    union { byte gray; byte rgb[3]; } pixel;
    pixel.rgb[0] = pixel.rgb[1] = pixel.rgb[2] = 0;
    // always start in grayscale mode
    bool graymode = true;
    size_t dx = 1;
    size_t dy = 3;
    // algorithm works with both planar configuration
    // It does produce surprising greenish background color for planar
    // configuration is 0, while the nested Icon SQ display a nice black
    // background
    if (pc)
    {
        dx = plane_size;
        dy = 1;
    }
    size_t ps = plane_size;

    // The following is highly unoptimized as we have nested if statement in a while loop
    // we need to switch from one algorithm to ther other (RGB <-> GRAY)
    while (ps)

```

```

{
// next byte:
byte b = *src++;
assert( src < data_in + data_size );
// mode selection:
switch ( b )
{
case ESCMODE:
// Used to treat a byte 81/82/83 as a normal byte
if (graymode)
{
pixel.gray += *src++;
dest[0*dx] = pixel.gray;
dest[1*dx] = pixel.gray;
dest[2*dx] = pixel.gray;
}
else
{
pixel.rgb[0] += *src++;
pixel.rgb[1] += *src++;
pixel.rgb[2] += *src++;
dest[0*dx] = pixel.rgb[0];
dest[1*dx] = pixel.rgb[1];
dest[2*dx] = pixel.rgb[2];
}
dest += dy;
ps--;
break;
case REPEATMODE:
// repeat mode (RLE)
b = *src++;
ps -= b;
if (graymode)
{
while (b-- > 0)
{
dest[0*dx] = pixel.gray;
dest[1*dx] = pixel.gray;
dest[2*dx] = pixel.gray;
dest += dy;
}
}
else
{
while (b-- > 0)
{
dest[0*dx] = pixel.rgb[0];
dest[1*dx] = pixel.rgb[1];
dest[2*dx] = pixel.rgb[2];
dest += dy;
}
}
break;
case COLORMODE:
// We are swithing from one mode to the other. The stream contains an intermixed
// compression of RGB codec and GRAY codec. Each one not knowing of the other
// reset old value to 0.
if (graymode)
{
graymode = false;
pixel.rgb[0] = pixel.rgb[1] = pixel.rgb[2] = 0;
}
else
{
graymode = true;
pixel.gray = 0;
}
break;
default:
// This is identical to ESCMODE, it would be nicer to use fall-through
if (graymode)
{
pixel.gray += b;
dest[0*dx] = pixel.gray;
dest[1*dx] = pixel.gray;
dest[2*dx] = pixel.gray;
}
else
{
pixel.rgb[0] += b;
pixel.rgb[1] += *src++;
}
}
}

```

```

        pixel.rgb[2] += *src++;
        dest[0*dx] = pixel.rgb[0];
        dest[1*dx] = pixel.rgb[1];
        dest[2*dx] = pixel.rgb[2];
    }
    dest += dy;
    ps--;
    break;
} // end switch
} // end while
}

int main(int argc, char *argv [])
{
    if( argc < 2 ) return 1;
    const char *filename = argv[1];
    gdc::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Failed to read: " << filename << std::endl;
        return 1;
    }
    const gdc::DataSet& ds = reader.GetFile().GetDataSet();

    // (07a1,1011) CS [PMSCT_RGB1] # 10,1 Tamar Compression Type
    const gdc::PrivateTag tcompressiontype(0x07a1,0x0011,"ELSCINT1");
    if( !ds.FindDataElement( tcompressiontype ) ) return 1;
    const gdc::DataElement& compressiontype = ds.GetDataElement(
        tcompressiontype );
    if ( compressiontype.IsEmpty() ) return 1;
    const gdc::ByteValue *bv = compressiontype.GetByteValue();
    std::string comprle = "PMSCT_RLE1";
    std::string comprgb = "PMSCT_RGB1";
    bool isrle = false;
    bool isrgb = false;
    if( strcmp( bv->GetPointer(), comprle.c_str(), comprle.size() ) == 0 )
    {
        isrle = true;
        return 1;
    }
    if( strcmp( bv->GetPointer(), comprgb.c_str(), comprgb.size() ) == 0 )
    {
        isrgb = true;
    }
    if( !isrgb && !isrle ) return 1;

    const gdc::PrivateTag tcompressedpixeldata(0x07a1,0x000a,"ELSCINT1");
    if( !ds.FindDataElement( tcompressedpixeldata ) ) return 1;
    const gdc::DataElement& compressionpixeldata = ds.
        GetDataElement( tcompressedpixeldata );
    if ( compressionpixeldata.IsEmpty() ) return 1;
    const gdc::ByteValue *bv2 = compressionpixeldata.GetByteValue();

    gdc::Attribute<0x0028,0x0006> at0;
    at0.SetFromDataSet( ds );
    gdc::Attribute<0x0028,0x0010> at1;
    at1.SetFromDataSet( ds );
    gdc::Attribute<0x0028,0x0011> at2;
    at2.SetFromDataSet( ds );

    std::vector<unsigned char> buffer;
    delta_decode((const unsigned char*)bv2->GetPointer(), bv2->GetLength(), buffer,
        at0.GetValue(), at1.GetValue(), at2.GetValue() );

    gdc::DataElement pixeldata( gdc::Tag(0x7fe0,0x0010) );
    pixeldata.SetVR( gdc::VR::OW );
    pixeldata.SetByteValue( (char*)&buffer[0], (uint32_t)buffer.size() );
    // TODO we should check that decompress byte buffer match the expected size (row*col*...)

    // Add the pixel data element
    reader.GetFile().GetDataSet().Replace( pixeldata );

    reader.GetFile().GetHeader().SetDataSetTransferSyntax(
        gdc::TransferSyntax::ExplicitVRLittleEndian);
    gdc::Writer writer;
    writer.SetFile( reader.GetFile() );

    // Cleanup stuff:
    // remove the compressed pixel data:
    // FIXME: should I remove more private tags ? all of them ?

```

```

// oh well this is just an example
// use gdcm::Anonymizer::RemovePrivateTags if needed...
writer.GetFile().GetDataSet().Remove( compressionpixeldata.
    GetTag() );
std::string outfilename;
if (argc > 2)
    outfilename = argv[2];
else
    outfilename = "outrgb.dcm";
writer.SetFileName( outfilename.c_str() );
if( !writer.Write() )
{
    std::cerr << "Failed to write" << std::endl;
    return 1;
}

std::cout << "success !" << std::endl;

return 0;
}

```

27.108 PrivateDict.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #       This software is distributed WITHOUT ANY WARRANTY; without even
10 #       the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #       PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 """
17
18 import gdcm
19 import sys,os
20
21 if __name__ == "__main__":
22     #gdcm.Trace.DebugOn()
23     globInst = gdcm.Global.GetInstance()
24     # Try to load Part3.xml file
25     # This file is too big for being accessible directly at runtime.
26     globInst.LoadResourcesFiles()
27
28
29     # Get a private tag from the runtime dicts. LoadResourcesFiles could
30     # have failed but this has no impact on the private dict
31
32     d = globInst.GetDicts()
33     print d.GetDictEntry( gdcm.Tag(0x0029,0x0010) ,"SIEMENS CSA HEADER" )
34     pd = d.GetPrivateDict()
35     print pd.GetDictEntry( gdcm.PrivateTag(0x0029,0x0010,"SIEMENS CSA HEADER") )

```

27.109 PublicDict.cxx

```

/*=====

Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

```

```

=====*/
/*
 * Dummy example to show GDCM Dict(s) API (Part 6) + Collected Private Attributes:
 */

#include "gdcmGlobal.h"
#include "gdcmDicts.h"
#include "gdcmDict.h"
#include "gdcmCSAHeader.h"
#include "gdcmPrivateTag.h"

int main(int , char *[])
{
    const gdcm::Global& g = gdcm::Global::GetInstance(); // sum of all
        knowledge !
    const gdcm::Dicts &dicts = g.GetDicts();
    const gdcm::Dict &pub = dicts.GetPublicDict(); // Part 6

    //std::cout << pub << std::endl;

    // 3 differents way to access the same information

    // 1. From the public dict only:
    gdcm::Tag patient_name(0x10,0x10);
    const gdcm::DictEntry &entry1 = pub.GetDictEntry(patient_name);
    std::cout << entry1 << std::endl;

    // 2. From all dicts:
    const gdcm::DictEntry &entry2 = dicts.GetDictEntry(patient_name);
    std::cout << entry2 << std::endl;

    // 3. This solution is the most flexible solution as you can request using the same
    // API either a public tag or a private tag
    const char *strowner = 0;
    const gdcm::DictEntry &entry3 = dicts.GetDictEntry(patient_name,strowner);
    std::cout << entry3 << std::endl;

    // Private attributes:

    // try with a private tag now:
    const gdcm::PrivateTag &private_tag =
        gdcm::CSAHeader::GetCSAImageHeaderInfoTag();
    //std::cout << private_tag << std::endl;
    const gdcm::DictEntry &entry4 = dicts.GetDictEntry(private_tag,private_tag.
        GetOwner());
    std::cout << entry4 << std::endl;

    // Let's pretend that private lookup is on 0x10xx elements:
    gdcm::PrivateTag dummy = private_tag;
    dummy.SetElement( (uint16_t)(0x1000 + dummy.GetElement()) );
    const gdcm::DictEntry &entry5 = dicts.GetDictEntry(dummy,dummy.
        GetOwner());
    std::cout << entry5 << std::endl;

    return 0;
}

```

27.110 ReadAndDumpDICOMDIR.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * This example shows how to read and dump a DICOMDIR File
 *
 * Thanks:

```



```

*   Tom Marynowski (lordglub gmail) for contributing this example
*/
#include "gdcmReader.h"
#include "gdcmMediaStorage.h"

typedef std::set<gdcm::DataElement> DataElementSet;
typedef DataElementSet::const_iterator ConstIterator;

int main(int argc, char *argv [])
{
    if( argc < 2 ) return 1;
    const char *filename = argv[1];

    gdcm::Reader reader;
    reader.SetFileName( filename);
    if( !reader.Read() )
    {
        std::cerr << "Could not read: " << filename << std::endl;
        return 1;
    }
    std::stringstream strm;

    gdcm::File &file = reader.GetFile();
    gdcm::DataSet &ds = file.GetDataSet();
    gdcm::FileMetaInformation &fmi = file.GetHeader();

    gdcm::MediaStorage ms;
    ms.SetFromFile(file);
    if( ms != gdcm::MediaStorage::MediaStorageDirectoryStorage
        )
    {
        std::cout << "This file is not a DICOMDIR" << std::endl;
        return 1;
    }

    if (fmi.FindDataElement( gdcm::Tag (0x0002, 0x0002)))
    {
        strm.str("");
        fmi.GetDataElement( gdcm::Tag (0x0002, 0x0002) ).
            GetValue().Print(strm);
    }
    else
    {
        std::cerr << " Media Storage Sop Class UID not present" << std::cout;
    }

    //TODO il faut trimer strm.str() avant la comparaison au cas ou...
    if ("1.2.840.10008.1.3.10"!=strm.str())
    {
        std::cout << "This file is not a DICOMDIR" << std::endl;
        return 1;
    }

    ConstIterator it = ds.GetDES().begin();
    for( ; it != ds.GetDES().end(); ++it)
    {
        if (it->GetTag()==gdcm::Tag (0x0004, 0x1220))
        {
            const gdcm::DataElement &de = (*it);
            // ne pas utiliser GetSequenceOfItems pour extraire les items
            gdcm::SmartPointer<gdcm::SequenceOfItems> sqi =de.
                GetValueAsSQ();
            unsigned int itemused = 1;
            while (itemused<=sqi->GetNumberOfItems())
            {
                strm.str("");

                if (sqi->GetItem(itemused).FindDataElement(
                    gdcm::Tag (0x0004, 0x1430)))
                    sqi->GetItem(itemused).GetDataElement(gdcm::Tag (0x0004, 0x1430)).
                        GetValue().Print(strm);

                //TODO il faut trimer strm.str() avant la comparaison
                while((strm.str()=="PATIENT")||((strm.str()=="PATIENT ")))
                {
                    std::cout << strm.str() << std::endl;
                    strm.str("");
                    if (sqi->GetItem(itemused).FindDataElement(

```

```

gdcM::Tag (0x0010, 0x0010)))
    sqi->GetItem(itemused).GetDataElement(gdcM::Tag (0x0010, 0x0010))
.GetValue().Print(strm);
std::cout << "PATIENT NAME : " << strm.str() << std::endl;

//PATIENT ID
strm.str("");
if (sqi->GetItem(itemused).FindDataElement(
gdcM::Tag (0x0010, 0x0020)))
    sqi->GetItem(itemused).GetDataElement(gdcM::Tag (0x0010, 0x0020))
.GetValue().Print(strm);
std::cout << "PATIENT ID : " << strm.str() << std::endl;

/*ADD TAG TO READ HERE*/
std::cout << "===== " << std::endl;
itemused++;
strm.str("");
if (sqi->GetItem(itemused).FindDataElement(
gdcM::Tag (0x0004, 0x1430)))
    sqi->GetItem(itemused).GetDataElement(gdcM::Tag (0x0004, 0x1430))
.GetValue().Print(strm);

//TODO il faut trimer strm.str() avant la comparaison
while((strm.str()=="STUDY")||((strm.str()=="STUDY ")))
{
    std::cout << " " << strm.str() << std::endl;
    //UID
    strm.str("");
    if (sqi->GetItem(itemused).FindDataElement(
gdcM::Tag (0x0020, 0x000d)))
        sqi->GetItem(itemused).GetDataElement(
gdcM::Tag (0x0020, 0x000d)).GetValue().Print(strm);
    std::cout << "          STUDY UID : " << strm.str() << std::endl;

    //STUDY DATE
    strm.str("");
    if (sqi->GetItem(itemused).FindDataElement(
gdcM::Tag (0x0008, 0x0020)))
        sqi->GetItem(itemused).GetDataElement(
gdcM::Tag (0x0008, 0x0020)).GetValue().Print(strm);
    std::cout << "          STUDY DATE : " << strm.str() << std::endl;

    //STUDY DESCRIPTION
    strm.str("");
    if (sqi->GetItem(itemused).FindDataElement(
gdcM::Tag (0x0008, 0x1030)))
        sqi->GetItem(itemused).GetDataElement(
gdcM::Tag (0x0008, 0x1030)).GetValue().Print(strm);
    std::cout << "          STUDY DESCRIPTION : " << strm.str() << std::endl;

    /*ADD TAG TO READ HERE*/
    std::cout << "          " << "===== " << std::endl;

    itemused++;
    strm.str("");
    if (sqi->GetItem(itemused).FindDataElement(
gdcM::Tag (0x0004, 0x1430)))
        sqi->GetItem(itemused).GetDataElement(
gdcM::Tag (0x0004, 0x1430)).GetValue().Print(strm);

    //TODO il faut trimer strm.str() avant la comparaison
    while((strm.str()=="SERIES")||((strm.str()=="SERIES ")))
    {
        std::cout << "          " << strm.str() << std::endl;
        strm.str("");
        if (sqi->GetItem(itemused).FindDataElement(
gdcM::Tag (0x0020, 0x000e)))
            sqi->GetItem(itemused).GetDataElement(
gdcM::Tag (0x0020, 0x000e)).GetValue().Print(strm);
        std::cout << "          SERIE UID" << strm.str() << std::endl;

        //SERIE MODALITY
        strm.str("");
        if (sqi->GetItem(itemused).FindDataElement(
gdcM::Tag (0x0008, 0x0060)))
            sqi->GetItem(itemused).GetDataElement(
gdcM::Tag (0x0008, 0x0060)).GetValue().Print(strm);
        std::cout << "          SERIE MODALITY" << strm.str() << std::endl;

        //SERIE DESCRIPTION

```

```

        strm.str("");
        if (sqi->GetItem(itemused).FindDataElement(
gdcmm::Tag (0x0008, 0x103e)))
            sqi->GetItem(itemused).GetDataElement(
gdcmm::Tag (0x0008, 0x103e)).GetValue().Print(strm);
        std::cout << "                SERIE DESCRIPTION" << strm.str() << std::endl;

        /*ADD TAG TO READ HERE*/

        std::cout << "                " << "===== " << std::endl;
        itemused++;
        strm.str("");
        if (sqi->GetItem(itemused).FindDataElement(
gdcmm::Tag (0x0004, 0x1430)))
            sqi->GetItem(itemused).GetDataElement(
gdcmm::Tag (0x0004, 0x1430)).GetValue().Print(strm);

        //TODO il faut trimer strm.str() avant la comparaison
        while ((strm.str()=="IMAGE") || ((strm.str()=="IMAGE ")))
            // if(tmp=="IMAGE")
            {
                std::cout << "                " << strm.str() << std::endl;

                //UID
                strm.str("");
                if (sqi->GetItem(itemused).FindDataElement(
gdcmm::Tag (0x0004, 0x1511)))
                    sqi->GetItem(itemused).GetDataElement(
gdcmm::Tag (0x0004, 0x1511)).GetValue().Print(strm);
                std::cout << "                IMAGE UID : " << strm.str() << std::endl;

                //PATH de l'image
                strm.str("");
                if (sqi->GetItem(itemused).FindDataElement(
gdcmm::Tag (0x0004, 0x1500)))
                    sqi->GetItem(itemused).GetDataElement(
gdcmm::Tag (0x0004, 0x1500)).GetValue().Print(strm);
                std::cout << "                IMAGE PATH : " << strm.str() << std::endl;
                /*ADD TAG TO READ HERE*/

                if(itemused < sqi->GetNumberOfItems())
                    {itemused++;}
                    else{break;}

                strm.str("");

                if (sqi->GetItem(itemused).FindDataElement(
gdcmm::Tag (0x0004, 0x1430)))
                    sqi->GetItem(itemused).GetDataElement(
gdcmm::Tag (0x0004, 0x1430)).GetValue().Print(strm);

            }
        }
    }
    itemused++;
}
}
return 0;
}

```

27.111 ReadAndDumpDICOMDIR.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.
8 #

```

```

9 # This software is distributed WITHOUT ANY WARRANTY; without even
10 # the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 # PURPOSE. See the above copyright notice for more information.
12 #
13 # File: ReadAndDumpDICOMDIR.py
14 #
15 # Author: Lukas Batteau (lbatteau gmail)
16 #
17 # This example shows how to read and dump a DICOMDIR File.
18 # Based on Tom Marynowski's (lordglub gmail) example.
19 #
20 # Usage:
21 # python ReadAndDumpDICOMDIR.py [DICOMDIR file]
22 #####
23
24
25
26 import sys
27 import gdcm
28
29 if __name__ == "__main__":
30     # Check arguments
31     if (len(sys.argv) < 2):
32         # No filename passed
33         print "No input filename found"
34         quit()
35
36     filename = sys.argv[1]
37
38
39     # Read file
40     reader = gdcm.Reader()
41     reader.SetFileName(filename)
42     if (not reader.Read()):
43         print "Unable to read %s" % (filename)
44         quit()
45
46     file = reader.GetFile()
47
48     # Retrieve header information
49     fileMetaInformation = file.GetHeader()
50     print fileMetaInformation
51
52     # Retrieve data set
53     dataSet = file.GetDataSet()
54     #print dataSet
55
56     # Check media storage
57     mediaStorage = gdcm.MediaStorage()
58     mediaStorage.SetFromFile(file)
59     if (gdcm.MediaStorage.GetMSType(str(mediaStorage)) !=
gdcm.MediaStorage.MediaStorageDirectoryStorage):
60         # File is not a DICOMDIR
61         print "This file is not a DICOMDIR (Media storage type: %s)" % (str(mediaStorage))
62         quit()
63
64     # Check Media Storage SOP Class
65     if (fileMetaInformation.FindDataElement(gdcm.Tag(0x0002, 0x0002))):
66         sopClassUid = str(fileMetaInformation.GetDataElement(gdcm.Tag(0x0002, 0x0002)).GetValue())
67         # Check SOP UID
68         if (sopClassUid != "1.2.840.10008.1.3.10"):
69             # File is not a DICOMDIR
70             print "This file is not a DICOMDIR"
71     else:
72         # Not present
73         print "Media Storage SOP Class not present"
74         quit()
75
76     # Iterate through the DICOMDIR data set
77     iterator = dataSet.GetDES().begin()
78     while (not iterator.equal(dataSet.GetDES().end())):
79         dataElement = iterator.next()
80
81         # Check the element tag
82         if (dataElement.GetTag() == gdcm.Tag(0x004, 0x1220)):
83             # The 'Directory Record Sequence' element
84             sequence = dataElement.GetValueAsSQ()
85
86             # Loop through the sequence items
87             itemNr = 1
88             while (itemNr < sequence.GetNumberOfItems()):

```

```

89         item = sequence.GetItem(itemNr)
90
91         # Check the element tag
92         if (item.FindDataElement(gdcm.Tag(0x0004, 0x1430))):
93             # The 'Directory Record Type' element
94             value = str(item.GetDataElement(gdcm.Tag(0x0004, 0x1430)).GetValue())
95
96             # PATIENT
97             while (value.strip() == "PATIENT"):
98                 print value.strip()
99                 # Print patient name
100                 if (item.FindDataElement(gdcm.Tag(0x0010, 0x0010))):
101                     value = str(item.GetDataElement(gdcm.Tag(0x0010, 0x0010)).GetValue())
102                     print value
103
104                 # Print patient ID
105                 if (item.FindDataElement(gdcm.Tag(0x0010, 0x0020))):
106                     value = str(item.GetDataElement(gdcm.Tag(0x0010, 0x0020)).GetValue())
107                     print value
108
109                 # Next
110                 itemNr = itemNr + 1
111                 item = sequence.GetItem(itemNr)
112                 if (item.FindDataElement(gdcm.Tag(0x0004, 0x1430))):
113                     value = str(item.GetDataElement(gdcm.Tag(0x0004, 0x1430)).GetValue())
114
115                 # STUDY
116                 while (value.strip() == "STUDY"):
117                     print value.strip()
118
119                     # Print study UID
120                     if (item.FindDataElement(gdcm.Tag(0x0020, 0x000d))):
121                         value = str(item.GetDataElement(gdcm.Tag(0x0020, 0x000d)).GetValue())
122
123                         print value
124
125                     # Print study date
126                     if (item.FindDataElement(gdcm.Tag(0x0008, 0x0020))):
127                         value = str(item.GetDataElement(gdcm.Tag(0x0008, 0x0020)).GetValue())
128
129                         print value
130
131                     # Print study description
132                     if (item.FindDataElement(gdcm.Tag(0x0008, 0x1030))):
133                         value = str(item.GetDataElement(gdcm.Tag(0x0008, 0x1030)).GetValue())
134
135                         print value
136
137                     # Next
138                     itemNr = itemNr + 1
139                     item = sequence.GetItem(itemNr)
140                     if (item.FindDataElement(gdcm.Tag(0x0004, 0x1430))):
141                         value = str(item.GetDataElement(gdcm.Tag(0x0004, 0x1430)).GetValue())
142
143                         # SERIES
144                         while (value.strip() == "SERIES"):
145                             print value.strip()
146
147                             # Print series UID
148                             if (item.FindDataElement(gdcm.Tag(0x0020, 0x000e))):
149                                 value = str(item.GetDataElement(gdcm.Tag(0x0020, 0x000e)).GetValue())
150
151                                 print value
152
153                             # Print series modality
154                             if (item.FindDataElement(gdcm.Tag(0x0008, 0x0060))):
155                                 value = str(item.GetDataElement(gdcm.Tag(0x0008, 0x0060)).GetValue())
156
157                                 print "Modality"
158                                 print value
159
160                             # Print series description
161                             if (item.FindDataElement(gdcm.Tag(0x0008, 0x103e))):
162                                 value = str(item.GetDataElement(gdcm.Tag(0x0008, 0x103e)).GetValue())
163
164                                 print "Description"
165                                 print value
166
167                             # Next
168                             itemNr = itemNr + 1

```

```

163             item = sequence.GetItem(itemNr)
164             if (item.FindDataElement(gdcm.Tag(0x0004, 0x1430))):
165                 value = str(item.GetDataElement(gdcm.Tag(0x0004, 0x1430))).
        GetValue()
166
167         # IMAGE
168         while (value.strip() == "IMAGE"):
169             print value.strip()
170
171         # Print image UID
172         if (item.FindDataElement(gdcm.Tag(0x0004, 0x1511))):
173             value = str(item.GetDataElement(gdcm.Tag(0x0004, 0x1511))).
        GetValue()
174
175             print value
176
177         # Next
178         if (itemNr < sequence.GetNumberOfItems()):
179             itemNr = itemNr + 1
180         else:
181             break
182
183         item = sequence.GetItem(itemNr)
184         if (item.FindDataElement(gdcm.Tag(0x0004, 0x1430))):
185             value = str(item.GetDataElement(
        gdcm.Tag(0x0004, 0x1430)).GetValue())
186
187         # Next
188         itemNr = itemNr + 1

```

27.112 ReadAndPrintAttributes.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * This small example will show how one can read and print
 * a DICOM Attribute using different technique (by tag or by name)
 */

#include "gdcmReader.h"
#include "gdcmGlobal.h"
#include "gdcmDicts.h"
#include "gdcmDict.h"
#include "gdcmAttribute.h"
#include "gdcmStringFilter.h"

#include <iostream>

int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        std::cerr << argv[0] << " input.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];

    // Instantiate the reader:
    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Could not read: " << filename << std::endl;
        return 1;
    }

    // The output of gdcm::Reader is a gdcm::File

```

```

gdcM::File &file = reader.GetFile();

// the dataset is the the set of element we are interested in:
gdcM::DataSet &ds = file.GetDataSet();

const gdcM::Global& g = gdcM::Global::GetInstance();
const gdcM::Dicts &dicts = g.GetDicts();
const gdcM::Dict &pubdict = dicts.GetPublicDict();

using namespace gdcM;

// In this example we will show why using name to lookup attribute can be
// dangerous.
Tag tPatientName(0x0,0x0);
//const DictEntry &de1 =
pubdict.GetDictEntryByName("Patient Name", tPatientName);

std::cout << "Found: " << tPatientName << std::endl;

// Indeed the attribute could not be found. Since DICOM 2003, Patient Name
// has become Patient's Name.

Tag tPatientsName;
//const DictEntry &de2 =
pubdict.GetDictEntryByName("Patient's Name", tPatientsName);

std::cout << "Found: " << tPatientsName << std::endl;

// Let's try to read an arbitrary DICOM Attribute:
Tag tDoseGridScaling;
//const DictEntry &de3 =
pubdict.GetDictEntryByName("Dose Grid Scaling", tDoseGridScaling);

std::cout << "Found: " << tDoseGridScaling << std::endl;

if( ds.FindDataElement( tDoseGridScaling ) )
{
    gdcM::StringFilter sf;
    sf.SetFile(file);
    std::cout << "Attribute Value as String: " << sf.ToString( tDoseGridScaling ) << std::endl;

    // Let's check the name again:
    std::pair<std::string, std::string> pss
        = sf.ToStringPair( tDoseGridScaling );
    std::cout << "Attribute Name Checked: " << pss.first << std::endl;
    std::cout << "Attribute Value (string): " << pss.second << std::endl;

    //const DataElement &dgs = ds.GetDataElement( tDoseGridScaling );

    // Let's assume for a moment we knew the tag number:
    Attribute<0x3004,0x000e> at;
    assert( at.GetTag() == tDoseGridScaling );
    at.SetFromDataSet( ds );
    // For the sake of long term maintenance, we will not write
    // that this particular attribute is stored as a double. What if
    // a user made a mistake. It is much safer to rely on GDCM internal
    // mechanism to deduce the VR::DS type (represented as a ieee double)
    Attribute<0x3004,0x000e>::ArrayType v = at.
        GetValue();
    std::cout << "DoseGridScaling=" << v << std::endl;
}

return 0;
}

```

27.113 ReadExplicitLengthSQIVR.cxx

```

/*=====

Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcM.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR

```

```

    PURPOSE.  See the above copyright notice for more information.

=====*/
#include "gdcmReader.h"
#include "gdcmImplicitDataElement.h"
#include "gdcmDataSet.h"
#include "gdcmPrivateTag.h"
#include "gdcmPrivateTag.h"
#include "gdcmByteValue.h"
#include "gdcmSequenceOfItems.h"

using namespace gdcm;

int main(int argc, char *argv[])
{
    if ( argc < 2 ) return 1;
    const char *filename = argv[1];
    gdcm::Reader r;
    r.SetFileName( filename );
    r.Read();

    //gdcm::PrivateTag pt(0x01,0x42,"ELSCINT1");
    //gdcm::Tag pt(0x88,0x200);
    gdcm::Tag pt(0x8,0x1140);
    DataSet &ds = r.GetFile().GetDataSet();
    const DataElement &de = ds.GetDataElement( pt );

    std::cout << de << std::endl;
    const ByteValue *bv = de.GetByteValue();
    SmartPointer<SequenceOfItems> sqi = new
        SequenceOfItems;
    sqi->SetLength( bv->GetLength() );
    std::stringstream ss;
    ss.str( std::string( bv->GetPointer(), bv->GetLength() ) );
    sqi->Read<ImplicitDataElement,SwapperNoOp>( ss );

    std::cout << *sqi << std::endl;

    return 0;
}

```

27.114 ReadFiles.java

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE.  See the above copyright notice for more information.

=====*/
import gdcm.*;
import java.io.File;

public class ReadFiles
{
    static int i = 0;
    public static void process(String path)
    {
        //String path = file.getPath();
        assert PosixEmulation.FileExists(path) : "Problem converting to 8bits";

        System.out.println("Reading: " + path );
        System.out.println("File: " + i++);
        Reader r = new Reader();
        try
        {
            r.SetFileName( path );
            TagSetType skip = new TagSetType();
            skip.insert( new Tag(0x7fe0,0x10) );
            boolean b = r.ReadUpToTag( new Tag(0x88,0x200), skip );

```



```

        //System.out.println("DS:\n" + r.GetFile().GetDataSet().toString() );
    }
    finally
    {
        r.delete(); // will properly call C++ destructor and close file descriptor
    }
}

// Process only files under dir
public static void visitAllFiles(File dir)
{
    if (dir.isDirectory())
    {
        String[] children = dir.list();
        for (int i=0; i<children.length; i++)
        {
            visitAllFiles(new File(dir, children[i]));
        }
    }
    else
    {
        process(dir.getPath());
    }
}

public static void waiting (int n)
{
    long t0, t1;
    t0 = System.currentTimeMillis();
    do
    {
        t1 = System.currentTimeMillis();
    }
    while ((t1 - t0) < (n * 1000));
}

public static void main(String[] args) throws Exception
{
    String directory = args[0];

    Directory gdir = new Directory();
    long n = gdir.Load( directory, true );
    System.out.println( gdir.toString() );
    FilenamesType files = gdir.GetFilenames();
    for( long i = 0; i < n; ++i )
    {
        String path = files.get( (int)i );
        process( path );
    }

    System.out.println( "Java API" );

    //waiting( 10 );
    for( int i = 0; i < 2; ++i )
    {
        File dir = new File(directory);
        visitAllFiles(dir);
    }
}
}

```

27.115 ReadGEMSSDO.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmReader.h"

```

```

#include "gdcmDataElement.h"
#include "gdcmPrivateTag.h"

#include <iostream>
#include <string>

using namespace gdcm;

struct SDOElement
{
    typedef std::vector<std::string>::size_type SizeType;
    const char *GetData(SizeType index) const {
        return Data[index].c_str();
    }
    SizeType GetNumberOfData() const {
        return Data.size();
    }
    void SetData(SizeType index, const char *data) {
        Data[index] = data;
    }
    const char *GetDataFormat() const {
        return DataFormat.c_str();
    }
    void SetDataFormat(const char *dataformat, SizeType num) {
        DataFormat = dataformat;
        Data.resize( num );
    }
    void Print( std::ostream &os ) const {
        os << DataFormat << ":" << std::endl;
        std::vector<std::string>::const_iterator it = Data.begin();
        size_t s = 0;
        for( ; it != Data.end(); ++it )
        {
            os << "  (" << s++ << ") " << *it << std::endl;
        }
    }
private:
    std::string DataFormat;
    std::vector<std::string> Data;
};

class SDOHeader
{
public:
    typedef std::vector<SDOElement> SDOElements;
    typedef SDOElements::size_type SizeType;
    SizeType GetNumberOfSDOElements() const {
        return InternalSDODataset.size();
    }
    void AddSDOElement(SDOElement const &sdoelement) {
        InternalSDODataset.push_back( sdoelement );
    }
    const SDOElement &GetSDOElement(SizeType index) const {
        return InternalSDODataset[index];
    }
    const SDOElement &GetSDOElementByName(const char *) const {
        return InternalSDODataset[0];
    }
    void LoadFromAttributes(std::string const &s1, std::string const &s2)
    {
        std::string tok;
        std::string tok2;
        std::stringstream strstr(s1);
        std::stringstream strstr2(s2);

        SDOElement element;
        // Do format
        size_t count = 0;
        while ( std::getline ( strstr2, tok, '\\') )
        {
            //std::cout << tok << " ";
            std::getline ( strstr2, tok2, '\\');
            //std::cout << tok2 << std::endl;
            count += atoi( tok2.c_str() );
            element.SetDataFormat( tok.c_str(), atoi( tok2.c_str() ) );
            for( size_t t = 0; t < element.GetNumberOfData(); ++t )
            {
                std::getline ( strstr, tok, '\\');
                element.SetData(t, tok.c_str() );
            }
            AddSDOElement( element );
        }
    }
};

```

```

    }
    //while ( std::getline ( strstr, tok, '^' ) )
    // while ( std::getline ( strstr, tok, '\\') )
    // {
    //     std::cout << tok << std::endl;
    //     count++;
    // }
    // std::cout << "Count: " << count << std::endl;
    // count = 0;

// std::cout << "Count: " << count << std::endl;

    }
    void Print( std::ostream &os ) const {
        SDOElements::const_iterator it = InternalSDODataset.begin();
        for( ; it != InternalSDODataset.end(); ++it )
        {
            it->Print ( os );
        }
    }
private:
    SDOElements InternalSDODataset;
};

bool sdo_decode( DataElement const &stringdata, DataElement const &stringdataformat )
{
    const char *sd = stringdata.GetByteValue()->GetPointer();
    const size_t len_sd = stringdata.GetByteValue()->GetLength();

    std::string s1 = std::string( sd, len_sd );

    const char *sdf = stringdataformat.GetByteValue()->GetPointer();
    const size_t len_sdf = stringdataformat.GetByteValue()->GetLength();

    std::string s2 = std::string( sdf, len_sdf );

    // std::cout << s1 << std::endl;
    // std::cout << s2 << std::endl;

    SDOHeader header;
    header.LoadFromAttributes( s1, s2 );

    header.Print( std::cout );

    return true;
}

int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        std::cerr << argv[0] << " input.dcm" << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        return 1;
    }

    File &file = reader.GetFile();
    DataSet &ds = file.GetDataSet();

    // StringData (0033,xx1F) 3 "GEMS_GENIE_1" List of SDO parameters stored as
    // list of strings
    const PrivateTag tstringdata(0x33,0x1f,"GEMS_GENIE_1");
    // StringDataFormat (0033,xx23) 3 "GEMS_GENIE_1" Format of string parameters;
    // contains information about name and number of strings in list
    const PrivateTag tstringdataformat(0x33,0x23,"GEMS_GENIE_1");

    if( !ds.FindDataElement( tstringdata ) ) return 1;
    const DataElement& stringdata = ds.GetDataElement( tstringdata );
    if( !ds.FindDataElement( tstringdataformat ) ) return 1;
    const DataElement& stringdataformat = ds.GetDataElement( tstringdataformat );

    sdo_decode( stringdata, stringdataformat );

    return 0;
}

```

27.116 ReadMultiTimesException.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
// The intention of this sample program is to provoke bad_alloc exceptions in gdcm code

#include "gdcmImageReader.h"

int main(int argc, char* argv[])
{
    // We pre-allocate some memory (about 1Gb) to help the issue to show up earlier
    char *dummyBuffer = new char[1024*1024*1100]; (void)dummyBuffer;
    // Check the number of parameters given
    if (argc < 3)
    {
        std::cerr << "Usage: " << argv[0] << " Filename numberOfTries" << std::endl;
        return 1;
    }

    std::cout << "We are going to read the file: " << argv[1] << " " << argv[2] << " times" << std::endl;
    // We hold the pointers in an array to avoid the memory to be released
    // We read the input file n-times
    for (int i = 0; i < atoi(argv[2]); ++i)
    {
        gdcm::ImageReader reader;
        std::cout << "Reading try: " << i << std::endl;
        // Read files
        reader.SetFileName(argv[1]);
        try
        {
            reader.Read();
            gdcm::Image & img = reader.GetImage();
            unsigned long len = img.GetBufferLength();
            char *buffer = new char[ len ];
            img.GetBuffer( buffer ); // do NOT de-allocate buffer !
        }
        catch (std::bad_alloc)
        {
            std::cerr << "BAD ALLOC Exception caught!" << std::endl;
        }
        catch (...)
        {
            std::cerr << "Exception caught!" << std::endl;
        }
    }

    return 0;
}

```

27.117 ReadSeriesIntoVTK.java

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
// We are required to call the package 'vtk' eventhough I (MM) would have preferred

```

```

// an import statement along the line of:
// import vtkgdc.*;
import vtk.*;

/*
 * Usage:
 * export LD_LIBRARY_PATH=/usr/lib/jvm/java-6-openjdk/jre/lib/amd64/xawt:.
 * java -classpath `pwd`/vtkgdc.jar:/usr/share/java/vtk.jar:. ReadSeriesIntoVTK
 */
public class ReadSeriesIntoVTK
{
    static {
        System.loadLibrary("vtkCommonJava");
        System.loadLibrary("vtkFilteringJava");
        System.loadLibrary("vtkIOJava");
        System.loadLibrary("vtkImagingJava");
        System.loadLibrary("vtkGraphicsJava");
        System.loadLibrary("vtkgdcJava");
        try {
            System.loadLibrary("vtkRenderingJava");
        } catch (Throwable e) {
            System.out.println("cannot load vtkHybrid, skipping...");
        }
        try {
            System.loadLibrary("vtkHybridJava");
        } catch (Throwable e) {
            System.out.println("cannot load vtkHybrid, skipping...");
        }
        try {
            System.loadLibrary("vtkVolumeRenderingJava");
        } catch (Throwable e) {
            System.out.println("cannot load vtkVolumeRendering, skipping...");
        }
    }

    public static void main(String[] args)
    {
        vtkFileOutputWindow outWin = new vtkFileOutputWindow();
        outWin.SetInstance(outWin);
        outWin.SetFileName("MVSvtkViewer.log");

        // See: http://review.source.kitware.com/#change,888
        // vtkWrapJava does not handle static keyword
        // String directory = vtkGDCMTesting.GetGDCMDataRoot();
        vtkGDCMTesting t = new vtkGDCMTesting();
        String directory = t.GetGDCMDataRoot();
        String file0 = directory + "/SIEMENS_MAGNETOM-12-MONO2-FileSeq0.dcm";
        String file1 = directory + "/SIEMENS_MAGNETOM-12-MONO2-FileSeq1.dcm";
        String file2 = directory + "/SIEMENS_MAGNETOM-12-MONO2-FileSeq2.dcm";
        String file3 = directory + "/SIEMENS_MAGNETOM-12-MONO2-FileSeq3.dcm";

        vtkStringArray s = new vtkStringArray();
        System.out.println("adding : " + file0 );
        s.InsertNextValue( file0 );
        s.InsertNextValue( file1 );
        s.InsertNextValue( file2 );
        s.InsertNextValue( file3 );

        vtkGDCMImageReader reader = new vtkGDCMImageReader();
        reader.SetFileNames( s );
        reader.Update();

        System.out.println("Success reading: " + file0 );

        vtkMetaImageWriter writer = new vtkMetaImageWriter();
        writer.DebugOn();
        writer.SetCompression( false );
        writer.SetInput( reader.GetOutput() );
        writer.SetFileName( "ReadSeriesIntoVTK.mhd" );
        writer.Write();

        System.out.println("Success writing: " + writer.GetFileName() );
    }
}

```

27.118 ReadUTF8QtDir.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

/*
 * GDCM API expect a const char * as input for SetFileName
 * In order to use this API from Qt, here is a simple test that
 * shows how to do it in a portable manner:
 *
 * http://doc.qt.nokia.com/latest/qdir.html#navigation-and-directory-operations
 */

#include "gdcmReader.h"
#include "gdcmDirectory.h"

#include <QDir>
#include <QString>
#include <QCoreApplication>

#include <string>
#include <fstream>

#include <stdio.h> // fopen

static int TestBothFuncs(const char *info , const char *ba_str)
{
    int res = 0;
    FILE *f = fopen( ba_str, "r" );
    if( f )
    {
        std::cout << info << " fopen: " << ba_str << std::endl;
        fclose(f);
        ++res;
    }
    gdcm::Reader reader;
    std::ifstream is( ba_str );
    if( is.is_open() )
    {
        std::cout << info << " is_open: " << ba_str << std::endl;
        ++res;
    }
    reader.SetStream( is );
    if( reader.CanRead() == true )
    {
        std::cout << info << " SetStream/CanRead:" << ba_str << std::endl;
        ++res;
    }
    is.close();
    reader.SetFileName( ba_str );
    if( reader.CanRead() == true )
    {
        std::cout << info << " SetFileName/CanRead:" << ba_str << std::endl;
        ++res;
    }
    return 4 - res;
}

static int scanFolder(const char dirname[])
{
    int res = 0;
    gdcm::Directory dir;
    unsigned int nfiles = dir.Load( dirname, true );
    const gdcm::Directory::FileNamesType &filenames = dir.
        GetFileNames();

    for( unsigned int i = 0; i < nfiles; ++i )
    {
        const char *ba_str = filenames[i].c_str();
        res += TestBothFuncs("GDCM",ba_str);
    }
}

```

```

    }
    return res;
}

static int scanFolderQt(QDir const &dir, QStringList& files)
{
    int res = 0;
    QFileInfoList children = dir.entryInfoList(QDir::AllEntries|QDir::NoDotAndDotDot);
    for ( int i=0; i<children.count(); i++ ) {
        QFileInfo file = children.at(i);
        if ( file.isDir() == true ) {
            res += scanFolderQt(QDir(file.absoluteFilePath()), files);
            continue;
        }
        // Convert back from the internal representation to 8bits
        // toLocal8Bit() returns by copy. Need to store explicetely the QByteArray
        QByteArray str = file.absoluteFilePath().toLocal8Bit();
        const char *ba_str1 = str.constData();
        res += TestBothFuncs("QString", ba_str1);
    }
    return res;
}

int main(int argc, char *argv[])
{
    // very important:
    QApplication qCoreApp( argc , argv );
    if( argc < 2 )
    {
        std::cerr << argv[0] << " dir " << std::endl;
        return 1;
    }

    int res = 0;
    const char *dirname = argv[1];
    res += scanFolder( dirname );

    QDir dir( QString::fromLocal8Bit(dirname) );
    QStringList files;
    res += scanFolderQt( dir, files);

    if( res )
        std::cerr << "Problem with UTF-8" << std::endl;
    else
        std::cerr << "Success with UTF-8" << std::endl;

    return res;
}

```

27.119 RefCounting.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
using Kitware.VTK;
using Kitware.VTK.GDCM;

/*
 * this is not so much an example but simply a test to make sure cstor / dstor work as expected
 * and call the ::New and ->Delete() of VTK style.
 */
public class RefCounting
{
    public static int Main(string[] args)
    {
        vtkGDCMTesting testing1 = vtkGDCMTesting.New();
        vtkGDCMTesting testing2 = new vtkGDCMTesting(); // just in case people do
    }
}

```

```

        not read STYLE documentation

    vtkGDCMImageReader reader1 = vtkGDCMImageReader.
        New();
    vtkGDCMImageReader reader2 = new vtkGDCMImageReader();

    vtkGDCMImageWriter writer1 = vtkGDCMImageWriter.
        New();
    vtkGDCMImageWriter writer2 = new vtkGDCMImageWriter();

    using (vtkGDCMTesting testing3 = new vtkGDCMTesting())
    {
        System.Console.Write( "GetReferenceCount: " + testing1.GetReferenceCount() + "\n");
        System.Console.Write( "GetReferenceCount: " + testing2.GetReferenceCount() + "\n");
        System.Console.Write( "GetReferenceCount: " + testing3.GetReferenceCount() + "\n");
    }

    using (vtkGDCMImageReader reader3 = new vtkGDCMImageReader())
    {
        System.Console.Write( "GetReferenceCount: " + reader3.GetReferenceCount() + "\n");
    }

    using (vtkGDCMImageWriter writer3 = vtkGDCMImageWriter.
        New())
    {
        System.Console.Write( "GetReferenceCount: " + writer3.GetReferenceCount() + "\n");
    }

    // C# destructor will call ->Delete on all C++ object as expected.
    return 0;
}

```

27.120 ReformatFile.cs

This is a C++ example on how to use [gdcm::FileDerivation](#)

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * Simple C# example
 *
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/ReformatFile.exe input.dcm output.dcm
 */
using System;
using gdcm;

public class ReformatFile
{
    public static int Main(string[] args)
    {
        gdcm.FileMetaInformation.SetSourceApplicationEntityTitle( "My Reformat App" );

        // http://www.oid-info.com/get/1.3.6.1.4.17434
        string THERALYS_ORG_ROOT = "1.3.6.1.4.17434";
        gdcm.UIDGenerator.SetRoot( THERALYS_ORG_ROOT );
        System.Console.WriteLine( "Root dir is now: " + gdcm.UIDGenerator.GetRoot() );

        string filename = args[0];
        string outfilename = args[1];

        Reader reader = new Reader();
    }
}

```



```

reader.SetFileName( filename );
if( !reader.Read() )
{
    System.Console.WriteLine( "Could not read: " + filename );
    return 1;
}

UIDGenerator uid = new UIDGenerator(); // helper for uid generation
FileDerivation fd = new FileDerivation();
// For the pupose of this excise we will pretend that this image is referencing
// two source image (we need to generate fake UID for that).
string ReferencedSOPClassUID = "1.2.840.10008.5.1.4.1.1.7"; // Secondary Capture
fd.AddReference( ReferencedSOPClassUID, uid.Generate() );
fd.AddReference( ReferencedSOPClassUID, uid.Generate() );

// Again for the purpose of the exercise we will pretend that the image is a
// multiplanar reformat (MPR):
// CID 7202 Source Image Purposes of Reference
// {"DCM",121322,"Source image for image processing operation"},
fd.SetPurposeOfReferenceCodeSequenceCodeValue( 121322 );
// CID 7203 Image Derivation
// { "DCM",113072,"Multiplanar reformatting" },
fd.SetDerivationCodeSequenceCodeValue( 113072 );
fd.SetFile( reader.GetFile() );
// If all Code Value are ok the filter will execute properly
if( !fd.Derive() )
{
    return 1;
}

gdcm.FileMetaInformation fmi = reader.GetFile().GetHeader();
// The following three lines make sure to regenerate any value:
fmi.Remove( new gdcm.Tag(0x0002,0x0012) );
fmi.Remove( new gdcm.Tag(0x0002,0x0013) );
fmi.Remove( new gdcm.Tag(0x0002,0x0016) );

Writer writer = new Writer();
writer.SetFileName( outfilename );
writer.SetFile( fd.GetFile() );
if( !writer.Write() )
{
    System.Console.WriteLine( "Could not write: " + outfilename );
    return 1;
}

return 0;
}

```

27.121 RemovePrivateTags.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:
17
18 python RemovePrivateTags.py input.dcm output.dcm
19 """
20
21 import sys
22 import gdcm
23
24
25 if __name__ == "__main__":

```

```

26
27 file1 = sys.argv[1]
28 file2 = sys.argv[2]
29
30 # Instantiate the reader.
31 r = gdcm.Reader()
32 r.SetFileName( file1 )
33 if not r.Read():
34     sys.exit(1)
35
36 # Remove private tags
37 ano = gdcm.Anonymizer()
38 ano.SetFile( r.GetFile() )
39 if not ano.RemovePrivateTags():
40     sys.exit(1)
41
42 # Write DICOM file
43 w = gdcm.Writer()
44 w.SetFile( ano.GetFile() )
45 #w.CheckFileMetaInformationOff() # Do not attempt to check meta header
46 w.SetFileName( file2 )
47 if not w.Write():
48     sys.exit(1)
49
50 # It is usually a good idea to exit the script with an error, as gdcm does not remove partial (incorrect)
    DICOM file
51 # (application level)

```

27.122 RescaleImage.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/DecompressImage.exe gdcmData/012345.002.050.dcm rescaled.dcm
 */
using System;
using gdcm;

public class DecompressImage
{
    public static int Main(string[] args)
    {
        string file1 = args[0];
        ImageReader reader = new ImageReader();
        reader.SetFileName( file1 );
        bool ret = reader.Read();
        if( !ret )
        {
            return 1;
        }

        Image image = reader.GetImage();
        PixelFormat pixeltype = image.GetPixelFormat();

        Rescaler r = new Rescaler();
        r.SetIntercept( 0 );
        r.SetSlope( 1.2 );
        r.SetPixelFormat( pixeltype );
        PixelFormat outputpt = new PixelFormat( r.ComputeInterceptSlopePixelFormat() );

        System.Console.WriteLine( "pixeltype" );
        System.Console.WriteLine( pixeltype.ToString() );
        System.Console.WriteLine( "outputpt" );
    }
}

```

```

System.Console.WriteLine( outputpt.toString() );

uint len = image.GetBufferLength();
short[] input = new short[ len / 2 ]; // sizeof(short) == 2
image.GetArray( input );

double[] output = new double[ len / 2 ];
r.Rescale( output, input, len );

// First Pixel is:
System.Console.WriteLine( "Input:" );
System.Console.WriteLine( input[0] );

System.Console.WriteLine( "Output:" );
System.Console.WriteLine( output[0] );

return 0;
}

```

27.123 reslicesphere.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcml.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
//
// Load a DICOM series.
// Position a sphere within the volume.
// Allow the user to change between Axial, Sagittal, Coronal, and
// Oblique view of the images and move through the slices.
// The display should show the resliced image and the cross section
// of the sphere intersecting that plane.
//

/*
from Scott Johnson /Scott Johnson neuwave com/
to VTK /vtkusers vtk.org/
date Tue, May 11, 2010 at 7:01 PM
*/
#include <sstream>
#include <string>

#include <vtkDICOMImageReader.h>
#include <vtkStringArray.h>
#include <vtkDirectory.h>
#include <vtkImageThreshold.h>
#include <vtkImageShiftScale.h>
#include <vtkImageReslice.h>
#include <vtkRenderWindowInteractor.h>
#include <vtkImageViewer2.h>
#include <vtkSphereSource.h>
#include <vtkPolyDataMapper.h>
#include <vtkPlane.h>
#include <vtkCutter.h>
#include <vtkActor.h>
#include <vtkCommand.h>
#include <vtkSmartPointer.h>
#include <vtkMatrix4x4.h>
#include <vtkInteractorObserver.h>
#include <vtkProperty.h>
#include <vtkRenderer.h>
#include <vtkImageData.h>
#include <vtkImageActor.h>
#include "vtkTransformPolyDataFilter.h"
#include <vtkCamera.h>
#include <vtkMath.h>

```

```

#include <vtkTransform.h>
#include <vtkTextActor.h>
#include <vtkActor2D.h>
#include <vtkPolyDataMapper2D.h>
#include <vtkProperty2D.h>
#include <vtkGDCMImageReader.h>
#include <vtkImageChangeInformation.h>

#include "gdcmDirectory.h"
#include "gdcmTesting.h"
#include "gdcmIPPSorter.h"

// Change to match the path to find Raw_0.vti or provide
// the parameter when starting ResliceSphere.

const double sphereCenter[3]={74, 219, 70};

// Angles (0, 0, 0)
const double AxialMatrix[] = { 1.0,  0.0,  0.0,  0.0,
                               0.0,  1.0,  0.0,  0.0,
                               0.0,  0.0,  1.0,  0.0,
                               0.0,  0.0,  0.0,  1.0 };

// Angles (0, 90, 0)
const double SagittalMatrix[] = { 0.0,  0.0,  1.0,  0.0,
                                   0.0,  1.0,  0.0,  0.0,
                                   -1.0,  0.0,  0.0,  0.0,
                                   0.0,  0.0,  0.0,  1.0 };

// Angles (-90, 0, 0)
const double CoronalMatrix[] = { 1.0,  0.0,  0.0,  0.0,
                                  0.0,  0.0,  1.0,  0.0,
                                  0.0, -1.0,  0.0,  0.0,
                                  0.0,  0.0,  0.0,  1.0 };

// Angles (0, 90, 31)
const double ObliqueMatrix[] = { 0.0, -0.515038, 0.857167, 0.0,
                                   0.0,  0.857167, 0.515038, 0.0,
                                   -1.0,  0.0,  0.0,  0.0,
                                   0.0,  0.0,  0.0,  1.0 };

class ResliceRender;

// Class to handle key press events.
class KeyCallback : public vtkCommand
{
public:
    static KeyCallback* New()
    {
        return new KeyCallback();
    }

    void Execute(vtkObject* caller, unsigned long eventId, void *calldata);
    void SetCallbackData(ResliceRender* reslice);

protected:
    ResliceRender* _reslice;
};

class ResliceRender
{
public:
    typedef enum _ORIENTATION
    {
        AXIAL = 0,
        SAGITTAL = 1,
        CORONAL = 2,
        OBLIQUE = 3
    } ORIENTATION;

    ResliceRender()
    {
        _orientation=AXIAL;
    }

    ~ResliceRender()
    {
        _transform->Delete();
        _reader->Delete();
        _reslice->Delete();
        _interactor->Delete();
        _imageView->Delete();

        _sphere->Delete();
    }
};

```

```

        _sphereMapper->Delete();
        _sphereActor->Delete();

        _plane->Delete();
        _cutter->Delete();
        _polyTransform->Delete();
        _ROIMapper->Delete();
        _ROIActor->Delete();

        _annotation->Delete();
    }

    void CreatePipeline(const char* fileName)
    {
        vtkProperty2D* props;

        //_reader=vtkXMLImageDataReader::New();
        //_reader->SetFileName(fileName);
        //_reader->Update();

        //_reader=qzDICOMImageReader::New();
        _reader=vtkGDCMImageReader::New();

        //vtkDirectory *d = vtkDirectory::New();
        //d->Open(fileName);
        //d->Print( std::cout );
        gdcm::Directory d;
        d.Load(fileName);
        gdcm::Directory::FileNamesType const &files = d.
        GetFileNames();

        gdcm::IPPSorter s;
        s.SetComputeZSpacing( true );
        s.SetZSpacingTolerance( 1e-3 );
        bool b = s.Sort( files );
        if( !b )
        {
            std::cerr << "Failed to sort:" << fileName << std::endl;
            //return ;
        }
        //std::cout << "Sorting succeeded:" << std::endl;
        //s.Print( std::cout );

        //std::cout << "Found z-spacing:" << std::endl;
        //std::cout << s.GetZSpacing() << std::endl;
        double ippzspacing = s.GetZSpacing();

        const std::vector<std::string> & sorted = s.GetFileNames();
        vtkStringArray *vtkfiles = vtkStringArray::New();
        std::vector< std::string >::const_iterator it = sorted.begin();
        for( ; it != sorted.end(); ++it)
        {
            const std::string &f = *it;
            vtkfiles->InsertNextValue( f.c_str() );
        }

        //_reader->SetDirectoryName(fileName);
        //_reader->SetFileNames( d->GetFiles() );
        _reader->SetFileNames( vtkfiles );
        _reader->Update();

        const vtkFloatingPointType *spacing = _reader->GetOutput()->GetSpacing();

        vtkImageChangeInformation *v16 = vtkImageChangeInformation::New();
        v16->SetInput( _reader->GetOutput() );
        v16->SetOutputSpacing( spacing[0], spacing[1], ippzspacing );
        v16->Update();

        _threshold=vtkImageThreshold::New();
        _threshold->ThresholdByUpper(-3024.0);
        _threshold->ReplaceOutOn();
        _threshold->SetOutValue(0.0);
        _threshold->SetInputConnection(v16->GetOutputPort());

        _shift=vtkImageShiftScale::New();
        _shift->SetShift(0);
        _shift->SetScale(1);
        _shift->SetInputConnection(_threshold->GetOutputPort());

        // Initialize the reslice with an axial orientation.

```

```

vtkSmartPointer<vtkMatrix4x4> matrix =
    vtkSmartPointer<vtkMatrix4x4>::New();
matrix->Identity();

_transform = vtkTransform::New();
_transform->SetMatrix(matrix);

_reslice = vtkImageReslice::New();
_reslice->SetOutputDimensionality(3);

// PROBLEM:
// The original intent was to connect the same transform
// to the vtkImageReslice and vtkTransformPolyDataFilter,
// but the resulting reslices appear different using the
// vtkTransform as opposed to explicitly setting the
// reslice axes via SetResliceAxes. Also, if the vtkTransform
// is connected and orientated other than axial, the extents
// don't seem to update resulting in VTK believing the slice
// is out of range.

_reslice->SetResliceTransform(_transform);
_reslice->SetResliceAxes(matrix);
_reslice->SetInputConnection(_reader->GetOutputPort());
_reslice->SetInputConnection(_shift->GetOutputPort());

// Create the sphere target shape.
_sphere=vtkSphereSource::New();
_sphere->SetRadius(7.0);
_sphere->SetThetaResolution(16);
_sphere->SetPhiResolution(16);
_sphere->SetCenter(sphereCenter[0], sphereCenter[1], sphereCenter[2]);

_sphereMapper=vtkPolyDataMapper::New();
_sphereMapper->SetInputConnection(_sphere->GetOutputPort());

_sphereActor=vtkActor::New();
_sphereActor->SetMapper(_sphereMapper);
_sphereActor->PickableOff();
_sphereActor->GetProperty()->SetColor(1.0, 0.0, 0.0);
_sphereActor->GetProperty()->SetEdgeColor(1.0, 0.0, 0.0);
_sphereActor->GetProperty()->SetDiffuseColor(1.0, 0.0, 0.0);
_sphereActor->SetVisibility(true);

// Create the cutting pipeline.
// This plane will be positioned in the original image coordinate system.
_plane = vtkPlane::New();
_plane->SetNormal(0.0, 0.0, 1.0);

_cutter = vtkCutter::New();
_cutter->SetInputConnection(_sphere->GetOutputPort());
_cutter->SetCutFunction(_plane);
_cutter->GenerateCutScalarsOn();
_cutter->SetValue(0, 0.5);

// The transform attached to _polyTransform should move the cut
// ROI into the resliced coordinate system, which should be the
// same as the coordinate system of the resliced images.
// PROBLEM: It doesn't.
_polyTransform = vtkTransformPolyDataFilter::New();
_polyTransform->SetTransform(_transform);
_polyTransform->SetInputConnection(_cutter->GetOutputPort());

_ROIMapper = vtkPolyDataMapper2D::New();
_ROIMapper->SetInputConnection(_polyTransform->GetOutputPort());

vtkCoordinate* coordinate = vtkCoordinate::New();
coordinate->SetCoordinateSystemToWorld();
_ROIMapper->SetTransformCoordinate(coordinate);

_ROIActor = vtkActor2D::New();
_ROIActor->SetMapper(_ROIMapper);

// Make sure the cut can be seen, especially the edges.
props=_ROIActor->GetProperty();
props->SetLineWidth(2);
props->SetOpacity(1.0);
// props->EdgeVisibilityOn();
// props->SetDiffuse(0.8);
// props->SetSpecular(0.3);
// props->SetSpecularPower(20);
// props->SetRepresentationToSurface();

```

```

//      props->SetDiffuseColor(1.0, 0.0, 0.0);
//      props->SetEdgeColor(1.0, 0.0, 0.0);
props->SetColor(1.0, 0.0, 0.0);

_interactor = vtkRenderWindowInteractor::New();

// Create the image viewer and add the actor with the cut ROI.
_imageViewer = vtkImageViewer2::New();
_imageViewer->SetupInteractor(_interactor);
_imageViewer->SetSize(400, 400);
_imageViewer->SetColorWindow(1024);
_imageViewer->SetColorLevel(800);
_imageViewer->SetInputConnection(_reslice->GetOutputPort());
_imageViewer->GetImageActor()->SetOpacity(0.5);

_annotation = vtkTextActor::New();
_annotation->SetTextScaleModeToViewport();
_imageViewer->GetRenderer()->AddActor(_annotation);

// Add the cut shape actor to the renderer.
_imageViewer->GetRenderer()->AddActor(_ROIActor);

// Set up the key handler.
vtkSmartPointer<KeyCallback> callback = vtkSmartPointer<KeyCallback>::New();
callback->SetCallbackData(this);
_interactor->AddObserver(vtkCommand::KeyPressEvent, callback);

_interactor->Initialize();
}

void Start()
{
    _interactor->Start();
}

void ResetOrientation()
{
    vtkSmartPointer<vtkMatrix4x4> matrix =
        vtkSmartPointer<vtkMatrix4x4>::New();
    matrix->Identity();

    SetOrientation(matrix);
}

// Make sure the orientation of the vtkImageReslice and
// vtkTransform are in sync.
void SetOrientation(vtkMatrix4x4* matrix)
{
    _reslice->SetResliceAxes(matrix);
    _reslice->Update();

    vtkMatrix4x4* inverse = vtkMatrix4x4::New();
    vtkMatrix4x4::Invert(matrix, inverse);

    _transform->SetMatrix(inverse);
    _transform->Update();
}

// Set the current slice of the current view.
void SetSlice(int slice)
{
    std::stringstream posString;

    double    center[3];
    double    spacing[3];
    double    origin[3];
    double    point[4];
    double    newPoint[4];

    vtkImageData* imageData;
    int newSlice;

    // Try to make sure the extents of the reslice are updated.
    // PROBLEM: It doesn't seem to work when changing the orientation.
    imageData=vtkImageData::SafeDownCast(_reslice->GetOutput());
    imageData->UpdateInformation();

    // Let vtkImageViewer2 handle the slice limits.
    _imageViewer->SetSlice(slice);
    newSlice=GetSlice();

```

```

    imageData->GetCenter(center);
    imageData->GetSpacing(spacing);
    imageData->GetOrigin(origin);

    // Compute the position of the center of the slice based on the
    // spacing of the slices. The resliced axis will always
    // be the "Z" axis.
    point[0]=center[0];
    point[1]=center[1];
    point[2]=(newSlice * spacing[2]) + origin[2];
    point[3]=1.0;

    // Convert the coordinate from the reslice coordinate system to the
    // original image coordinate system.
    // PROBLEM: Logically this seems like it should have been multiplied
    // by the inverse to translate from the resliced coordinate system to
    // the original coordinate system. However, multiplying by the inverse
    // sticks the plane in the wrong place completely. Using the original
    // matrix at least gets the Z coordinate right.
    vtkMatrix4x4* matrix=_reslice->GetResliceAxes();
    vtkSmartPointer<vtkMatrix4x4> inverse =
        vtkSmartPointer<vtkMatrix4x4>::New();
    vtkMatrix4x4::Invert(matrix, inverse);

    matrix->MultiplyPoint(point, newPoint);
    _plane->SetOrigin(newPoint[0], newPoint[1], newPoint[2]);

    // Annotate the image.
    posString << "Position: (" << newPoint[0] << ", " << newPoint[1]
        << ", " << newPoint[2] << ") Slice: " << newSlice;
    _annotation->SetInput(posString.str());

    _imageView->Render();
}

int GetSlice()
{
    return _imageView->GetSlice();
}

// Set the orientation of the view.
void SetOrientation(ResliceRender::ORIENTATION orientation)
{
    vtkCamera* camera=_imageView->GetRenderer()->GetActiveCamera();

    double spacing[3];
    double origin[3];
    double point[4];
    double newPoint[4];
    double initialPosition;
    double xDirCosine[3];
    double yDirCosine[3];
    double zDirCosine[3];
    double normal[3];

    vtkImageData* imageData;

    vtkSmartPointer<vtkMatrix4x4> matrix =
        vtkSmartPointer<vtkMatrix4x4>::New();

    _orientation=orientation;

    // Reset ViewUp
    camera->SetViewUp(0.0, 1.0, 0.0);

    // Compute the cut plane position to the input coordinate system.
    imageData=vtkImageData::SafeDownCast(_reslice->GetInput());
    imageData->UpdateInformation();
    imageData->GetSpacing(spacing);
    imageData->GetOrigin(origin);

    point[0]=origin[0];
    point[1]=origin[1];
    point[2]=origin[2];
    point[3]=1.0;

    switch (_orientation)
    {
    case AXIAL:
        matrix->DeepCopy(AxialMatrix);
        initialPosition=sphereCenter[2];

```



```

        break;

    case CORONAL:
        matrix->DeepCopy(CoronalMatrix);
        initialPosition=sphereCenter[1];
        break;

    case SAGITTAL:
        matrix->DeepCopy(SagittalMatrix);
        initialPosition=sphereCenter[0];
        break;

    case OBLIQUE:
        matrix->DeepCopy(ObliqueMatrix);
        initialPosition=sphereCenter[2];
        break;
}

// Move the origin from the original image coordinate system to the
// resliced image coordinate system.
matrix->MultiplyPoint(point, newPoint);
matrix->SetElement(0, 3, newPoint[0]);
matrix->SetElement(1, 3, newPoint[1]);
matrix->SetElement(2, 3, newPoint[2]);

ResetOrientation();
SetOrientation(matrix);

// Compute the cutting plane normal and set it.
// PROBLEM: If the transformation is connected rather than
// using SetResliceAxes, the Direction Cosines do not reflect
// the orientation of the vtkImageReslice.
_reslice->GetResliceAxesDirectionCosines(xDirCosine, yDirCosine,
                                          zDirCosine);
vtkMath::Cross(xDirCosine, yDirCosine, normal);
_plane->SetNormal(normal);

// Set the extents and spacing of the reslice to account for
// all of the data.
_reslice->SetOutputExtentToDefault();
_reslice->SetOutputSpacing(spacing[0], spacing[0], spacing[0]);

// Force the vtkImageViewer2 to update.
// PROBLEM: The whole extent does not seem to be set in time
// for the first render. This results in an error because the
// slice is positioned outside the old bounds.
_imageViewer->SetInput(NULL);
_imageViewer->SetInputConnection(_reslice->GetOutputPort());

_imageViewer->GetRenderer()->ResetCameraClippingRange();
_imageViewer->GetRenderer()->ResetCamera();

// Set the initial slice to be at the center of the sphere.
// Divide by the spacing because this will be undone in SetSlice.
SetSlice( (int)(initialPosition / spacing[0]));
}

vtkRenderWindowInteractor* GetInteractor()
{
    return _interactor;
}

protected:
    ORIENTATION                _orientation;

    //qzDICOMImageReader*      _reader;
    vtkGDCMImageReader*        _reader;
    vtkImageThreshold*          _threshold;
    vtkImageShiftScale*         _shift;
    vtkImageReslice*            _reslice;
    vtkRenderWindowInteractor*  _interactor;
    vtkImageViewer2*            _imageViewer;

    vtkSphereSource*            _sphere;
    vtkPolyDataMapper*          _sphereMapper;
    vtkActor*                   _sphereActor;

    vtkPlane*                   _plane;
    vtkCutter*                  _cutter;
    vtkTransform*               _transform;
    vtkTransformPolyDataFilter* _polyTransform;

```

```

    vtkPolyDataMapper2D*      _ROIMapper;
    vtkActor2D*               _ROIActor;

    vtkTextActor*             _annotation;
};

// Catch KeyPress events.
// Up Arrow   - increases the slice
// Down Arrow - decreases the slice
// 'A'        - sets the view to Axial
// 'S'        - sets the view to Sagittal
// 'C'        - sets the view to Coronal
// 'O'        - set the view to Oblique

void KeyCallback::Execute(vtkObject* caller, unsigned long eventId, void *calldata)
{
    (void)caller;
    (void)eventId;
    (void)calldata;
    std::string sym=_reslice->GetInteractor()->GetKeySym();

    if (!sym.compare("Up"))
    {
        _reslice->SetSlice(_reslice->GetSlice() + 1);
    }
    else if (!sym.compare("Down"))
    {
        _reslice->SetSlice(_reslice->GetSlice() - 1);
    }
    else if ((!sym.compare("A")) || (!sym.compare("a")))
    {
        _reslice->SetOrientation(ResliceRender::AXIAL);
    }
    else if ((!sym.compare("C")) || (!sym.compare("c")))
    {
        _reslice->SetOrientation(ResliceRender::CORONAL);
    }
    else if ((!sym.compare("S")) || (!sym.compare("s")))
    {
        _reslice->SetOrientation(ResliceRender::SAGITTAL);
    }
    else if ((!sym.compare("O")) || (!sym.compare("o")))
    {
        _reslice->SetOrientation(ResliceRender::OBLIQUE);
    }
}

void KeyCallback::SetCallbackData(ResliceRender* reslice)
{
    _reslice=reslice;
}

// Usage: ResliceSphere [fileName]
int main(int argc, char *argv[])
{
    ResliceRender render;

    if (argc == 1)
    {
        const char *root = gdcm::Testing::GetDataExtraRoot();
        std::string dir3 = root;
        dir3 += "/gdcmSampleData/ForSeriesTesting/Dentist/images/";
        render.CreatePipeline(dir3.c_str());
    }
    else
    {
        render.CreatePipeline(argv[1]);
    }

    render.SetOrientation(ResliceRender::AXIAL);
    render.Start();

    return EXIT_SUCCESS;
}

```

27.124 ReWriteSCAsMR.py

```

1 #####
2 #
3 # Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 # Copyright (c) 2006-2011 Mathieu Malaterre
6 # All rights reserved.
7 # See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 # This software is distributed WITHOUT ANY WARRANTY; without even
10 # the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 # PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 GDCM 1.x would write out MR Image Storage as Secondary Capture Object while still setting Rescale
17 Slope/Intercept
18 and saving the Pixel Spacing in (0028,0030)
19 """
20 import gdcm
21 import sys,os
22
23 def CheckSecondaryCaptureObjectIsMRImageStorage(r):
24     ds = r.GetFile().GetDataSet()
25     # Check Source Image Sequence
26     if ds.FindDataElement( gdcm.Tag(0x0008,0x2112) ):
27         sis = ds.GetDataElement( gdcm.Tag(0x0008,0x2112) )
28         sqsis = sis.GetSequenceOfItems()
29         if sqsis.GetNumberOfItems():
30             item1 = sqsis.GetItem(1)
31             nestedds = item1.GetNestedDataSet()
32             if nestedds.FindDataElement( gdcm.Tag(0x0008,0x1150) ):
33                 ReferencedSOPClassUID = nestedds.GetDataElement( gdcm.Tag(0x0008,0x1150) )
34                 raw = ReferencedSOPClassUID.GetByteValue().GetPointer()
35                 uids = gdcm.UIDs()
36                 # what is the actual object we are looking at ?
37                 ms = gdcm.MediaStorage()
38                 ms.SetFromDataSet(ds)
39                 msuid = ms.GetString()
40                 uids.SetFromUID( msuid )
41                 msuidname = uids.GetName() # real Media Storage Name
42                 uids.SetFromUID( raw )
43                 sqmsuidname = uids.GetName() # Source Image Sequence Media Storage Name
44                 # If object is SC and Source derivation is MRImageStorage then we can assume 'Pixel Spacing' is
45                 correct
46                 if( sqmsuidname == 'MR Image Storage' and msuidname == 'Secondary Capture Image Storage' ):
47                     return True
48             # in all other case simply return the currentspacing:
49             return False
50
51 if __name__ == "__main__":
52     r = gdcm.ImageReader()
53     filename = sys.argv[1]
54     r.SetFileName( filename )
55     if not r.Read():
56         sys.exit(1)
57     f = r.GetFile()
58
59     if( CheckSecondaryCaptureObjectIsMRImageStorage(r) ):
60         # Special handling of the spacing:
61         # GDCM 1.2.0 would not rewrite correctly DICOM Object and would always set them as 'Secondary Capture
62         Image Storage'
63         # while we would rather have 'MR Image Storage'
64         gdcm.ImageHelper.SetForcePixelSpacing( True )
65         mrspacing = gdcm.ImageHelper.GetSpacingValue( r.GetFile() )
66         # TODO: I cannot do simply the following:
67         #image.SetSpacing( mrspacing )
68         image.SetSpacing(0, mrspacing[0] )
69         image.SetSpacing(1, mrspacing[1] )
70         image.SetSpacing(2, mrspacing[2] )
71         gdcm.ImageHelper.SetForceRescaleInterceptSlope( True )
72         ris = gdcm.ImageHelper.GetRescaleInterceptSlopeValue(
73             r.GetFile() )
74         image.SetIntercept( ris[0] )
75         image.SetSlope( ris[1] )
76
77     outfilename = sys.argv[2]

```

```

75  w = gdcm.ImageWriter()
76  w.SetFileName( outfilename )
77  w.SetFile( r.GetFile() )
78  w.SetImage( image )
79  if not w.Write():
80      sys.exit(1)
81
82  sys.exit(0)

```

27.125 rle2img.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * This example shows how to rewrite a ELSCINT1/PMSCT_RLE1 compressed
 * image so that it is readable by most 3rd party software (DICOM does
 * not specify this particular encoding).
 * This is required for the sake of interoperability with any standard
 * conforming DICOM system.
 *
 * Everything done in this code is for the sole purpose of writing interoperable
 * software under Sect. 1201 (f) Reverse Engineering exception of the DMCA.
 * If you believe anything in this code violates any law or any of your rights,
 * please contact us (gdcm-developers@lists.sourceforge.net) so that we can
 * find a solution.
 *
 * Everything you do with this code is at your own risk, since decompression
 * algorithm was not written from specification documents.
 *
 * Special thanks to:
 * Mauro Maiorca for bringing to our attention on this new ELSCINT1
 * compression algorithm : PMSCT_RLE1 (different from the 'LOSSLESS RICE')
 * See post at:
 * http://groups.google.com/group/comp.protocols.dicom/msg/f2b99bf706a7f8ca
 *
 * Thanks to Jesus Spinola, for more datasets,
 * http://www.itk.org/pipermail/insight-users/2008-April/025571.html
 *
 * And last but not least, a very big thank to Ivo van Poorten, without
 * whom we would still be looking at this compressed byte stream as if
 * it was RLE compressed.
 */
#include "gdcmReader.h"
#include "gdcmPrivateTag.h"
#include "gdcmAttribute.h"
#include "gdcmImageWriter.h"

/* FIXME: Why is PhilipsLosslessRice.dcm a 512x512 image ... */
void delta_decode(const char *inbuffer, size_t length, std::vector<unsigned short> &output)
{
    // RLE pass
    std::vector<char> temp;
    for(size_t i = 0; i < length; ++i)
    {
        if( inbuffer[i] == (char)0xa5 )
        {
            //unsigned char repeat = (unsigned char)inbuffer[i+1] + 1;
            //assert( (unsigned char)inbuffer[i+1] != 255 );
            int repeat = (unsigned char)inbuffer[i+1] + 1;
            char value = inbuffer[i+2];
            while(repeat)
            {
                temp.push_back( value );
                --repeat;
            }
            i+=2;
        }
    }
}

```

```

    }
    else
    {
        temp.push_back( inbuffer[i] );
    }
}

// Delta encoding pass
unsigned short delta = 0;
for(size_t i = 0; i < temp.size(); ++i)
{
    if( temp[i] == 0x5a )
    {
        unsigned char v1 = (unsigned char)temp[i+1];
        unsigned char v2 = (unsigned char)temp[i+2];
        unsigned short value = (unsigned short)(v2 * 256 + v1);
        output.push_back( value );
        delta = value;
        i+=2;
    }
    else
    {
        unsigned short value = (unsigned short)(temp[i] + delta);
        output.push_back( value );
        delta = value;
    }
    //assert( output[output.size()-1] == ref[output.size()-1] );
}

if ( output.size() % 2 )
{
    output.resize( output.size() - 1 );
}
std::cout << length << " -> " << output.size() * 2 << std::endl;
}

int main(int argc, char *argv [])
{
    if( argc < 2 )
    {
        std::cerr << argv[0] << "input.dcm [output.dcm]" << std::endl;
        std::cerr << "will default to 'out.rle.dcm' unless output.dcm is specified."
        << std::endl;
        return 1;
    }
    const char *filename = argv[1];
    gdcm::Reader reader;
    reader.SetFileName( filename );
    if( !reader.Read() )
    {
        std::cerr << "Failed to read: " << filename << std::endl;
        return 1;
    }
    const gdcm::DataSet& ds = reader.GetFile().GetDataSet();

    // (07a1,1011) CS [PMSCT_RLE1] # 10,1 Tamar Compression Type
    const gdcm::PrivateTag tcompressiontype(0x07a1,0x0011,"ELSCINT1");
    if( !ds.FindDataElement( tcompressiontype ) ) return 1;
    const gdcm::DataElement& compressiontype = ds.GetDataElement(
        tcompressiontype );
    if ( compressiontype.IsEmpty() ) return 1;
    const gdcm::ByteValue *bv = compressiontype.GetByteValue();
    std::string comprle = "PMSCT_RLE1";
    std::string comprgb = "PMSCT_RGB1";
    bool isrle = false;
    bool isrgb = false;
    if( strncmp( bv->GetPointer(), comprle.c_str(), comprle.size() ) == 0 )
    {
        isrle = true;
    }
    if( strncmp( bv->GetPointer(), comprgb.c_str(), comprgb.size() ) == 0 )
    {
        isrgb = true;
        std::cerr << "See: pmsct_rgb1.cxx instead" << std::endl;
        return 1;
    }
    if( !isrgb && !isrle ) return 1;

    const gdcm::PrivateTag tcompressedpixeldata(0x07a1,0x000a,"ELSCINT1");
    if( !ds.FindDataElement( tcompressedpixeldata ) ) return 1;
    const gdcm::DataElement& compressionpixeldata = ds.

```

```

        GetDataElement( tcompressedpixeldata);
    if ( compressionpixeldata.IsEmpty() ) return 1;
    const gdcm::ByteValue * bv2 = compressionpixeldata.GetByteValue();

    gdcm::Attribute<0x0028,0x0010> at1;
    at1.SetFromDataSet( ds );
    gdcm::Attribute<0x0028,0x0011> at2;
    at2.SetFromDataSet( ds );

    gdcm::DataElement pixeldata( gdcm::Tag(0x7fe0,0x0010) );
    pixeldata.SetVR( gdcm::VR::OW );
    gdcm::VL bv2l = bv2->GetLength();
    gdcm::VL at1l = at1.GetValue() * at2.GetValue() * 2; /* sizeof(unsigned short) ==
        2 */
    // Handle special case that is not compressed:
    if( bv2l == at1l )
    {
        pixeldata.SetByteValue( bv2->GetPointer(), bv2->GetLength() );
    }
    else
    {
        std::vector<unsigned short> buffer;
        delta_decode(bv2->GetPointer(), bv2->GetLength(), buffer);
        pixeldata.SetByteValue( (char*)&buffer[0], (uint32_t)(buffer.size() * sizeof( unsigned short )) );
    }
    // TODO we should check that decompress byte buffer match the expected size (row*col*...)

    // Add the pixel data element
    reader.GetFile().GetDataSet().Replace( pixeldata );

    reader.GetFile().GetHeader().SetDataSetTransferSyntax(
        gdcm::TransferSyntax::ExplicitVRLittleEndian);
    gdcm::Writer writer;
    writer.SetFile( reader.GetFile() );

    // Cleanup stuff:
    // remove the compressed pixel data:
    // FIXME: should I remove more private tags ? all of them ?
    // oh well this is just an example
    // use gdcm::Anonymizer::RemovePrivateTags if needed...
    writer.GetFile().GetDataSet().Remove( compressionpixeldata.
        GetTag() );
    std::string outfilename;
    if (argc > 2)
        outfilename = argv[2];
    else
        outfilename = "out.rle.dcm";
    writer.SetFileName( outfilename.c_str() );
    if( !writer.Write() )
    {
        std::cerr << "Failed to write" << std::endl;
        return 1;
    }

    std::cout << "success !" << std::endl;

    return 0;
}

```

27.126 rtstructapp.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "vtkgDCMPolyDataReader.h"
#include "vtkgDCMPolyDataWriter.h"

```

```

#include "vtkPolyDataWriter.h"
#include "vtkPolyDataMapper.h"
#include "vtkPolyDataMapper2D.h"
#include "vtkActor2D.h"
#include "vtkRenderWindowInteractor.h"
#include "vtkMedicalImageProperties.h"
#include "vtkRenderWindow.h"
#include "vtkRenderer.h"
#include "vtkCamera.h"
#include "vtkProperty.h"
#include "vtkProperty2D.h"
#include "vtkAppendPolyData.h"
#include "vtkImageData.h"

/*
 * Small example to read in a RTSTRUCT and write it out (displays it too).
 */

// gdcmDataExtra/gdcmNonImageData/exRT_Structure_Set_Storage.dcm
// gdcmDataExtra/gdcmNonImageData/RTSTRUCT_1.3.6.1.4.1.22213.1.1396.2.dcm
// gdcmDataExtra/gdcmNonImageData/RT/RTStruct.dcm

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.dcm\n";
        return 1;
    }
    const char * filename = argv[1];
    const char * outfilename = argv[2];
    vtkGDCMPolyDataReader * reader =
        vtkGDCMPolyDataReader::New();
    reader->SetFileName( filename );
    reader->Update();

    //std::cout << reader->GetMedicalImageProperties()->GetStudyDate() << std::endl;

    vtkGDCMPolyDataWriter * writer =
        vtkGDCMPolyDataWriter::New();
    writer->SetNumberOfInputPorts( reader->GetNumberOfOutputPorts() );
    writer->SetFileName( outfilename );
    for(int num = 0; num < reader->GetNumberOfOutputPorts(); ++num )
        writer->SetInput( num, reader->GetOutput(num) );
    //doesn't look like the medical properties are actually written out
    writer->SetMedicalImageProperties( reader->GetMedicalImageProperties() );
    writer->SetRTStructSetProperties( reader->GetRTStructSetProperties() );
    writer->Write();

    // print reader output:
    reader->Print( std::cout );
    // print first output:
    reader->GetOutput()->Print( std::cout );

    vtkAppendPolyData *append = vtkAppendPolyData::New();

    int n = reader->GetNumberOfOutputPorts();
    for(int i = 0; i < n; ++i)
    {
        append->AddInput( reader->GetOutput(i) );
    }

    // Now we'll look at it.
    vtkPolyDataMapper *cubeMapper = vtkPolyDataMapper::New();
    cubeMapper->SetInput( append->GetOutput() );
    cubeMapper->SetScalarRange(0,7);
    vtkActor *cubeActor = vtkActor::New();
    cubeActor->SetMapper(cubeMapper);
    vtkProperty * property = cubeActor->GetProperty();
    property->SetRepresentationToWireframe();

    vtkRenderer *renderer = vtkRenderer::New();
    vtkRenderWindow *renWin = vtkRenderWindow::New();
    renWin->AddRenderer(renderer);

    vtkRenderWindowInteractor *iren = vtkRenderWindowInteractor::New();
    iren->SetRenderWindow(renWin);

    renderer->AddActor(cubeActor);
    renderer->ResetCamera();
    renderer->SetBackground(1,1,1);

```

```

renWin->SetSize(300,300);

renWin->Render();
iren->Start();

reader->Delete();
append->Delete();
cubeMapper->Delete();
cubeActor->Delete();
renderer->Delete();
renWin->Delete();
iren->Delete();
writer->Delete();

return 0;
}

```

27.127 ScanDirectory.cs

This is a C# example on how to use [gdcm::Scanner](#)

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/ScanDirectory.exe /path/to/gdcmData/
 */
using System;
using gdcm;

public class ScanDirectory
{
    public static int Main(string[] args)
    {
        string directory = args[0];
        Tag t = new Tag(0x8,0x8);

        Directory d = new Directory();
        uint nfiles = d.Load( directory );
        if(nfiles == 0) return 1;
        //System.Console.WriteLine( "Files:\n" + d.toString() );

        //Scanner s = new Scanner();
        SmartPtrScan sscan = Scanner.New();
        Scanner s = sscan.__ref__();
        SimpleSubjectWatcher watcher = new SimpleSubjectWatcher(s, "MySimple");
        s.AddTag( t );
        bool b = s.Scan( d.GetFileNames() );
        if(!b) return 1;

        System.Console.WriteLine( "Scan:\n" + s.toString() );

        System.Console.WriteLine( "success" );
        return 0;
    }
}

```


27.128 ScanDirectory.java

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

import gdcm.*;
import gdcm.Reader;
import gdcm.LookupTable;
import java.io.File;
import java.io.*;
import java.awt.image.*;
import javax.imageio.ImageIO;

public class ScanDirectory
{
    public static class MyWatcher extends SimpleSubjectWatcher
    {
        public MyWatcher(Subject s) { super(s,"Override String"); }
        protected void ShowProgress(Subject caller, Event evt)
        {
            ProgressEvent pe = ProgressEvent.Cast(evt);
            System.out.println( "This is my progress: " + pe.GetProgress() );
        }
    }

    public static byte[] GetAsByte(Bitmap input)
    {
        long len = input.GetBufferLength();
        byte[] buffer = new byte[ (int)len ];
        PhotometricInterpretation pi = input.GetPhotometricInterpretation();
        if( pi.GetType() == PhotometricInterpretation.PITYPE.MONOCHROME1 )
        {
            ImageChangePhotometricInterpretation icpi = new ImageChangePhotometricInterpretation();
            icpi.SetInput( input );
            icpi.SetPhotometricInterpretation(
                new PhotometricInterpretation(
                    PhotometricInterpretation.PITYPE.MONOCHROME2 ) );
            if( icpi.Change() )
            {
                Bitmap output = icpi.GetOutput();
                output.GetArray( buffer );
            }
            return buffer;
        }
        else
        {
            input.GetArray( buffer );
            return buffer;
        }
    }

    public static short[] GetAsShort(Bitmap input)
    {
        long len = input.GetBufferLength(); // length in bytes
        short[] buffer = new short[ (int)len / 2 ];
        PhotometricInterpretation pi = input.GetPhotometricInterpretation();
        if( pi.GetType() == PhotometricInterpretation.PITYPE.MONOCHROME1 )
        {
            ImageChangePhotometricInterpretation icpi = new ImageChangePhotometricInterpretation();
            icpi.SetInput( input );
            icpi.SetPhotometricInterpretation(
                new PhotometricInterpretation(
                    PhotometricInterpretation.PITYPE.MONOCHROME2 ) );
            if( icpi.Change() )
            {
                Bitmap output = icpi.GetOutput();
                output.GetArray( buffer );
            }
            return buffer;
        }
    }
}

```

```

else
{
    input.GetArray( buffer );
    return buffer;
}
}

public static boolean WritePNG(Bitmap input, String outfilename )
{
    int imageType = BufferedImage.TYPE_CUSTOM;
    PixelFormat pf = input.GetPixelFormat();
    PhotometricInterpretation pi = input.GetPhotometricInterpretation();
    // We need to handle both public and private icon
    // It could well be that we are getting an RGB Icon or 16 bits Icon:
    ColorModel colorModel = null;
    if( pf.GetSamplesPerPixel() == 1 )
    {
        if( pi.GetType() == PhotometricInterpretation.PIType.MONOCHROME1
            || pi.GetType() == PhotometricInterpretation.PIType.MONOCHROME2 )
        {
            if( pf.GetScalarType() == PixelFormat.ScalarType.UINT8 )
            {
                imageType = BufferedImage.TYPE_BYTE_GRAY;
            }
            else if( pf.GetScalarType() == PixelFormat.ScalarType.UINT12 )
            {
                imageType = BufferedImage.TYPE_USHORT_GRAY;
            }
            else if( pf.GetScalarType() == PixelFormat.ScalarType.UINT16 )
            {
                imageType = BufferedImage.TYPE_USHORT_GRAY;
            }
        }
        else if( pi.GetType() == PhotometricInterpretation.PIType.PALETTE_COLOR )
        {
            LookupTable lut = input.GetLUT();
            long r1 = lut.GetLUTLength( LookupTable.LookupTableType.RED );
            byte[] rbuf = new byte[ (int)r1 ];
            long r12 = lut.GetLUT( LookupTable.LookupTableType.RED, rbuf );
            assert r1 == r12;
            long g1 = lut.GetLUTLength( LookupTable.LookupTableType.GREEN );
            byte[] gbuf = new byte[ (int)g1 ];
            long g12 = lut.GetLUT( LookupTable.LookupTableType.GREEN, gbuf );
            assert g1 == g12;
            long b1 = lut.GetLUTLength( LookupTable.LookupTableType.BLUE );
            byte[] bbuf = new byte[ (int)b1 ];
            long b12 = lut.GetLUT( LookupTable.LookupTableType.BLUE, bbuf );
            assert b1 == b12;
            colorModel = new IndexColorModel(8, (int)r1, rbuf, gbuf, bbuf);
            // For code below
            imageType = BufferedImage.TYPE_BYTE_GRAY;
        }
    }
    else if( pf.GetSamplesPerPixel() == 3 )
    {
        if( pf.GetScalarType() == PixelFormat.ScalarType.UINT8 )
        {
            // FIXME should be TYPE_3BYTE_RGB
            imageType = BufferedImage.TYPE_3BYTE_BGR;
        }
    }
    //System.out.println( "pf: " + pf.toString() );
    //System.out.println( "pi: " + pi.toString() );
    long width = input.GetDimension(0);
    long height = input.GetDimension(0);
    BufferedImage bi;
    if( pi.GetType() == PhotometricInterpretation.PIType.PALETTE_COLOR )
    {
        bi = new BufferedImage(colorModel,
            colorModel.createCompatibleWritableRaster((int)width, (int)height),
            false, null);
    }
    else
    {
        bi = new BufferedImage((int)width, (int)height, imageType);
    }
    WritableRaster wr = bi.getRaster();
    //System.out.println( "imagetype: " + imageType );
    if( imageType == BufferedImage.TYPE_BYTE_GRAY
        || imageType == BufferedImage.TYPE_3BYTE_BGR )
    {
        byte[] buffer = GetAsByte( input );

```

```

        wr.setDataElements (0, 0, (int)width, (int)height, buffer);
    }
    else if( imageType == BufferedImage.TYPE_USHORT_GRAY )
    {
        short[] buffer = GetAsShort( input );
        wr.setDataElements (0, 0, (int)width, (int)height, buffer);
    }

    File outputfile = new File( outfilename );
    try {
        ImageIO.write(bi, "png", outputfile);
    } catch (IOException e) {
        return false;
    }
    return true;
}

public static void main(String[] args) throws Exception
{
    String directory = args[0];

    Directory d = new Directory();
    long nfiles = d.Load( directory, true );
    if(nfiles == 0)
    {
        throw new Exception("No files found");
    }
    // System.out.println( "Files:\n" + d.toString() );
    FilenamesType fns = d.GetFilenames();

    //Scanner s = new Scanner();
    SmartPtrScan sscan = Scanner.New();
    Scanner s = sscan.__ref__();
    //SimpleSubjectWatcher watcher = new SimpleSubjectWatcher(s, "MySimple");
    MyWatcher watcher = new MyWatcher(s);
    Tag[] tagarray = {
        new Tag(0x0010, 0x0010),    // PatientName
        new Tag(0x0010, 0x0020),    // PatientID
        new Tag(0x0010, 0x0030),    // PatientBirthDate
        new Tag(0x0010, 0x0040),    // PatientSex
        new Tag(0x0010, 0x1010),    // PatientAge
        new Tag(0x0020, 0x000d),    // StudyInstanceUID
        new Tag(0x0020, 0x0010),    // StudyID
        new Tag(0x0008, 0x0020),    // StudyDate
        new Tag(0x0008, 0x1030),    // StudyDescription
        new Tag(0x0020, 0x000e),    // SeriesInstanceUID
        new Tag(0x0020, 0x0011),    // SeriesNumber
        new Tag(0x0008, 0x0021),    // SeriesDate
        new Tag(0x0008, 0x103e),    // SeriesDescription
        new Tag(0x0008, 0x0090),    // ReferringPhysicianName
        new Tag(0x0008, 0x0060),    // Modality
        new Tag(0x0054, 0x0400),    // ImageID ?? Should be Instance number ??
        new Tag(0x0008, 0x0018),    // SOPInstanceUID
        new Tag(0x0008, 0x0032),    // AcquisitionTime
        new Tag(0x0008, 0x0033),    // ContentTime
        new Tag(0x0020, 0x0013),    // InstanceNumber
        new Tag(0x0020, 0x1041),    // SliceLocation
        new Tag(0x0018, 0x0050),    // SliceThickness ?? Eg. Enhanced MR Image Storage
        new Tag(0x0008, 0x0080),    // InstitutionName
        new Tag(0x0028, 0x1050),    // WindowCenter
        new Tag(0x0028, 0x1051),    // WindowWidth
    };
    for( Tag t : tagarray ) {
        //System.out.println( "Tag: " + t.toString() );
        s.AddTag( t );
    }
    boolean b = s.Scan( fns );
    if(!b)
    {
        throw new Exception("Could not scan");
    }

    for( long idx = 0; idx < fns.size(); ++idx )
    {
        Reader r = new Reader();
        String fn = fns.get( (int)idx );
        String outfn = fn + ".png";
        r.SetFileName( fn );
        TagSetType tst = new TagSetType();
        tst.insert( new Tag(0x7fe0,0x10) );
        b = r.ReadUpToTag( new Tag(0x88,0x200), tst );
    }
}

```

```

UIntArrayType dims = ImageHelper.GetDimensionsValue( r.GetFile() );
if( b )
{
    IconImageFilter iif = new IconImageFilter();
    System.out.println( "Processing: " + fn );

    iif.SetFile( r.GetFile() );
    b = iif.Extract();
    if( b )
    {
        Bitmap icon = iif.GetIconImage(0);
        WritePNG(icon, outfn);
    }
    else
    {
        ImageReader ir = new ImageReader();
        ir.SetFileName( fn );
        if( ir.Read() )
        {
            Image img = ir.GetImage();
            StringFilter sf = new StringFilter();
            sf.SetFile( r.GetFile() );
            String strval = sf.ToString( new Tag(0x0028,0x0120) );
            IconImageGenerator iig = new IconImageGenerator();
            iig.SetPixmap( img );
            iig.AutoPixelMinMax( true );
            try {
                double val = Double.parseDouble( strval );
                iig.SetOutsideValuePixel( val );
            }
            catch ( NumberFormatException e ) {
            }
            iig.ConvertRGBToPaletteColor( false );
            long idims[] = { 128, 128 };
            iig.SetOutputDimensions( idims );
            iig.Generate();
            Bitmap icon = iig.GetIconImage();
            WritePNG(icon, outfn);
        }
    }
}

System.out.println( "Scan:\n" + s.toString() );

System.out.println( "success" );
}
}

```

27.129 ScanDirectory.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 import gdcm
16 import sys,os
17
18 class ProgressWatcher(gdcm.SimpleSubjectWatcher):
19     def ShowProgress(self, sender, event):
20         pe = gdcm.ProgressEvent.Cast(event)
21         print pe.GetProgress()
22     def EndFilter(self):
23         print "Yay ! I am done"
24
25 if __name__ == "__main__":
26     directory = sys.argv[1]

```

```

27
28 # Define the set of tags we are interested in
29 t1 = gdcm.Tag(0x8,0x8);
30 t2 = gdcm.Tag(0x10,0x10);
31
32 # Iterate over directory
33 d = gdcm.Directory();
34 nfiles = d.Load( directory );
35 if(nfiles == 0): sys.exit(1);
36 # System.Console.WriteLine( "Files:\n" + d.toString() );
37
38 filenames = d.GetFilenames()
39
40 # Get rid of any Warning while parsing the DICOM files
41 gdcm.Trace.WarningOff()
42
43 # instanciate Scanner:
44 sp = gdcm.Scanner.New();
45 s = sp.__ref__()
46 w = ProgressWatcher(s, 'Watcher')
47
48 s.AddTag( t1 );
49 s.AddTag( t2 );
50 b = s.Scan( filenames );
51 if(not b): sys.exit(1);
52
53 print "success" ;
54 #print s
55
56 pttv = gdcm.PythonTagToValue( s.GetMapping( filenames[1] ) )
57 pttv.Start()
58 # iterate until the end:
59 while( not pttv.IsAtEnd() ):
60     # get current value for tag and associated value:
61     # if tag was not found, then it was simply not added to the internal std::map
62     # Warning value can be None
63     tag = pttv.GetCurrentTag()
64     value = pttv.GetCurrentValue()
65     print tag,"->",value
66     # increment iterator
67     pttv.Next()
68
69 sys.exit(0)

```

27.130 SendFileSCU.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Perso/gdcm-gcc/bin
 * $ mono bin/SendFileSCU.exe server port input.dcm
 */
using System;
using gdcm;

public class SendFileSCU
{
    public static int Main(string[] args)
    {
        string server = args[0];
        ushort port = ushort.Parse(args[1]);
        string filename = args[2];

        bool b = CompositeNetworkFunctions.CEcho( server, port );
    }
}

```

```

        if( !b ) return 1;

        FilenamesType files = new FilenamesType();
        files.Add( filename );
        b = CompositeNetworkFunctions.CStore( server, port, files );
        if( !b ) return 1;

        return 0;
    }
}

```

27.131 SimplePrint.cs

This is a C# example on how to use `gdcmm::SWIGDataSet`

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

/*
  Convertor convertor = new Convertor();
  int a = convertor.Convert<int>( some_int_blob );
  double b = convertor.Convert<double>( some_double_blob );
*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcmm/debug-gcc/bin
 * $ mono bin/SimplePrint.exe gdcmmData/012345.002.050.dcm
*/
using System;
using gdcmm;

public class SimplePrint
{
    public static void RecurseDataSet( File f, DataSet ds, string indent )
    {
        CSharpDataSet cds = new CSharpDataSet( ds );
        while( !cds.IsAtEnd() )
        {
            DataElement de = cds.GetCurrent();
            // Compute VR from the toplevel file, and the currently processed dataset:
            VR vr = DataSetHelper.ComputeVR( f, ds, de.GetTag() );

            if( vr.Compatible( new VR( VR.VRType.SQ ) ) )
            {
                uint uvl = (uint)de.GetVL(); // Test cast is ok
                System.Console.WriteLine( indent + de.GetTag().ToString() + ":" + uvl ); // why not ?
                //SequenceOfItems sq = de.GetSequenceOfItems();
                // GetValueAsSQ handle more cases than GetSequenceOfItems
                SmartPtrSQ sq = de.GetValueAsSQ();
                uint n = sq.GetNumberOfItems();
                for( uint i = 1; i <= n; i++ ) // item starts at 1, not 0
                {
                    Item item = sq.GetItem( i );
                    DataSet nested = item.GetNestedDataSet();
                    RecurseDataSet( f, nested, indent + "  " );
                }
            }
            else
            {
                System.Console.WriteLine( indent + de.ToString() );
            }
            cds.Next();
        }
    }
}

```

```

public static int Main(string[] args)
{
    string filename = args[0];
    Reader reader = new Reader();
    reader.SetFileName( filename );
    bool ret = reader.Read();
    if( !ret )
    {
        return 1;
    }
    File f = reader.GetFile();
    DataSet ds = f.GetDataSet();

    RecurseDataSet( f, ds, "" );

    return 0;
}

```

27.132 SimplePrintPatientName.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Perso/gdcm/debug-gcc/bin
 * $ mono bin/SimplePrintPatientName.exe gdcmData/012345.002.050.dcm
 */
/*
This example was provided by Jonathan Morra /jonmorra gmail com/
on the gdcm mailing list (Fri, 28 May 2010)
*/
using System;
using gdcm;

namespace GDCMTest
{
    class SimplePrintPatientName
    {
        static int Main(string[] args)
        {
            if (args.Length != 1)
            {
                Console.WriteLine("This program prints the patient name of a dicom file with gdcm");
                Console.WriteLine("Usage: [input.dcm]");
                return 1;
            }

            gdcm.Reader reader = new gdcm.Reader();
            reader.SetFileName(args[0]);
            bool ret = reader.Read();
            //TagSetType tst = new TagSetType();
            //tst.Add( new Tag(0x7fe0,0x10) );
            //bool ret = reader.ReadUpToTag( new Tag(0x88,0x200), tst );
            if( !ret )
            {
                return 1;
            }

            gdcm.File file = reader.GetFile();

            gdcm.StringFilter filter = new gdcm.StringFilter();
            filter.SetFile(file);
            string value = filter.ToString(new gdcm.Tag(0x0010, 0x0010));

            Console.WriteLine("Patient Name: " + value);
        }
    }
}

```

```

        return 0;
    }
}

```

27.133 SimpleScanner.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcml.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/

/*
 * Simple example to show how to use Scanner API.
 * It exposes the three different cases:
 * - DICOM Attribute is present and has a value
 * - DICOM Attribute is present and has no value
 * - DICOM Attribute is not present at all
 * It also shows the purpose of the function 'IsKey' to detect whether or
 * not the file has been read by the gdcml::Scanner. Technically most of the time
 * if a file is not a 'Key' this is because it is not a DICOM file. You need to use
 * gdcml::System::FileExists to decide whether or not the file actually exist on the disk.
 *
 * It was tested on this particular image:
 * ./SimpleScanner gdcmlData/012345.002.050.dcm
 */

#include "gdcmlScanner.h"

int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        return 1;
    }
    const char *filename = argv[1];
    const char filename_invalid[] = "this is a file that may not exist on this disk.dcm";

    gdcml::Scanner s;

    const gdcml::Tag tag_array[] = {
        gdcml::Tag(0x8,0x50),
        gdcml::Tag(0x8,0x51),
        gdcml::Tag(0x8,0x60),
    };
    s.AddTag( tag_array[0] );
    s.AddTag( tag_array[1] );
    s.AddTag( tag_array[2] );

    gdcml::Directory::FileNamesType filenames;
    filenames.push_back( filename );
    filenames.push_back( filename_invalid );

    if( !s.Scan( filenames ) )
    {
        return 1;
    }

    //s.Print( std::cout );

    if( s.IsKey( filename ) )
    {
        std::cout << "INFO:" << filename << " is a proper Key for the Scanner (this is a DICOM file)" <<
            std::endl;
    }

    if( !s.IsKey( filename_invalid ) )
    {

```



```

        std::cout << "INFO:" << filename_invalid << " is not a proper Key for the Scanner (this is either not a
        DICOM file or file does not exist)" << std::endl;
    }

    gdcm::Scanner::TagToValue const &ttv = s.GetMapping(filename);

    const gdcm::Tag *ptag = tag_array;
    for( ; ptag != tag_array + 3; ++ptag )
    {
        gdcm::Scanner::TagToValue::const_iterator it = ttv.find( *ptag );
        if( it != ttv.end() )
        {
            std::cout << *ptag << " was properly found in this file" << std::endl;
            // it contains a pair of value. the first one is the actual tag, so the following is always true:
            // *ptag == it->first
            // The second part is the actual value (stored as RAW strings). You will have to reinterpret this
            string
            // if VR for *ptag is not VR:VRASCII !
            const char *value = it->second;
            if( *value )
            {
                std::cout << " It has the value: " << value << std::endl;
            }
            else
            {
                std::cout << " It has no value (empty)" << std::endl;
            }
        }
        else
        {
            std::cout << "Sorry " << *ptag << " could not be found in this file" << std::endl;
        }
    }

    return 0;
}

```

27.134 SortImage.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
/*
*/
#include "gdcmSorter.h"
#include "gdcmScanner.h"
#include "gdcmDataSet.h"
#include "gdcmAttribute.h"

bool mysort(gdcm::DataSet const & ds1, gdcm::DataSet const & ds2 )
{
    //gdcm::Attribute<0x0020,0x0013> at1; // Instance Number
    gdcm::Attribute<0x0018,0x1060> at1; // Trigger Time
    gdcm::Attribute<0x0020,0x0032> at11; // Image Position (Patient)
    at1.Set( ds1 );
    at11.Set( ds1 );
    //gdcm::Attribute<0x0020,0x0013> at2;
    gdcm::Attribute<0x0018,0x1060> at2;
    gdcm::Attribute<0x0020,0x0032> at22;
    at2.Set( ds2 );
    at22.Set( ds2 );
    if( at11 == at22 )
    {
        return at1 < at2;
    }
    return at11 < at22;
}

```

```

}

bool mysort_part1(gdcm::DataSet const & ds1, gdcm::DataSet const & ds2 )
{
    gdcm::Attribute<0x0018,0x1060> at1;
    at1.Set( ds1 );
    gdcm::Attribute<0x0018,0x1060> at2;
    at2.Set( ds2 );
    return at1 < at2;
}

bool mysort_part2(gdcm::DataSet const & ds1, gdcm::DataSet const & ds2 )
{
    gdcm::Attribute<0x0020,0x0032> at1;
    at1.Set( ds1 );
    gdcm::Attribute<0x0020,0x0032> at2;
    at2.Set( ds2 );
    return at1 < at2;
}

// technically all files are in the same Frame of Reference, so this function
// should be a no-op
bool mysort_dummy(gdcm::DataSet const & ds1, gdcm::DataSet const & ds2 )
{
    gdcm::Attribute<0x0020,0x0052> at1; // FrameOfReferenceUID
    at1.Set( ds1 );
    gdcm::Attribute<0x0020,0x0052> at2;
    at2.Set( ds2 );
    return at1 < at2;
}

int main(int argc, char *argv[])
{
    if (argc < 2 ) return 1;
    const char *dirname = argv[1];
    gdcm::Directory dir;
    unsigned int nfiles = dir.Load( dirname );

    dir.Print( std::cout );

    gdcm::Sorter sorter;
    sorter.SetSortFunction( mysort );
    sorter.Sort( dir.GetFilesNames() );

    std::cout << "Sorter:" << std::endl;
    sorter.Print( std::cout );

    gdcm::Sorter sorter2;
    sorter2.SetSortFunction( mysort_part1 );
    sorter2.StableSort( dir.GetFilesNames() );
    sorter2.SetSortFunction( mysort_part2 );
    sorter2.StableSort( sorter2.GetFilesNames() ); // IMPORTANT
    sorter2.SetSortFunction( mysort_dummy );
    sorter2.StableSort( sorter2.GetFilesNames() ); // IMPORTANT

    std::cout << "Sorter2:" << std::endl;
    sorter2.Print( std::cout );

    gdcm::Scanner s;
    s.AddTag( gdcm::Tag(0x20,0x32) ); // Image Position (Patient)
    //s.AddTag( gdcm::Tag(0x20,0x37) ); // Image Orientation (Patient)
    s.Scan( dir.GetFilesNames() );

    //s.Print( std::cout );

    // Count how many different IPP there are:
    const gdcm::Scanner::ValueType &values = s.GetValues();
    size_t nvalues = values.size();
    std::cout << "There are " << nvalues << " different type of values" << std::endl;

    //std::cout << "nfiles=" << nfiles << std::endl;
    if( nfiles % nvalues != 0 )
    {
        std::cerr << "Impossible: this is a not a proper series" << std::endl;
        return 1;
    }
    std::cout << "Series is composed of " << (nfiles/nvalues) << " different 3D volumes" << std::endl;

    return 0;
}

```

27.135 SortImage.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.
8 #
9 #       This software is distributed WITHOUT ANY WARRANTY; without even
10 #       the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #       PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:
17
18   python SortImage.py dirname
19 """
20
21 import gdcm
22 import sys
23
24 def PrintProgress(object, event):
25     assert event == "ProgressEvent"
26     print "Progress:", object.GetProgress()
27
28 def MySort(ds1, ds2):
29     # compare ds1
30     return False
31
32 if __name__ == "__main__":
33
34     dirname = sys.argv[1]
35     d = gdcm.Directory()
36     d.Load( dirname )
37
38     print d
39
40     sorter = gdcm.Sorter()
41     sorter.SetSortFunction( MySort )
42     #sorter.AddObserver( "ProgressEvent", PrintProgress )
43     sorter.Sort( d.GetFileNames() )
44
45     print "Sorter:"
46     print sorter

```

27.136 SortImage2.cs

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

    This software is distributed WITHOUT ANY WARRANTY; without even
    the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
    PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/SortImage.exe gdcmData/012345.002.050.dcm out.dcm
 */
using System;
using gdcm;

public class SortImage2
{
    bool mysort(DataSet ds1, DataSet ds2)

```

```

    {
        return false;
    }

    public static int Main(string[] args)
    {
        Sorter sorter = new Sorter();
        sorter.SetSortFunction( mysort );

        return 0;
    }
}

```

27.137 StandardizeFiles.cs

This is a C++ example on how to use [gdcm::ImageChangeTransferSyntax](#)

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

    This software is distributed WITHOUT ANY WARRANTY; without even
    the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
    PURPOSE. See the above copyright notice for more information.

=====*/

/*
 * Simple C# example to show how one would 'Standardize' a DICOM File-Set
 *
 * Usage:
 * $ export LD_LIBRARY_PATH=$HOME/Projects/gdcm/debug-gcc/bin
 * $ mono bin/StandardizeFiles.exe input_path output_path
 */
using System;
using gdcm;

public class StandardizeFiles
{
    public static bool ProcessOneFile( string filename, string outfilename )
    {
        PixmapReader reader = new PixmapReader();
        reader.SetFileName( filename );
        if( !reader.Read() )
        {
            System.Console.WriteLine( "Could not read: " + filename );
            return false;
        }

        ImageChangeTransferSyntax change = new ImageChangeTransferSyntax();
        change.SetForce( false ); // do we really want to recompress when input is already compressed in same
        //    alg ?
        change.SetCompressIconImage( false ); // Keep it simple
        change.SetTransferSyntax( new TransferSyntax( TransferSyntax.TSType.JPEG2000Lossless ) );
        change.SetInput( reader.GetPixmap() );
        if( !change.Change() )
        {
            System.Console.WriteLine( "Could not change: " + filename );
            return false;
        }

        gdcm.FileMetaInformation fmi = reader.GetFile().GetHeader();
        // The following three lines make sure to regenerate any value:
        fmi.Remove( new gdcm.Tag(0x0002,0x0012) );
        fmi.Remove( new gdcm.Tag(0x0002,0x0013) );
        fmi.Remove( new gdcm.Tag(0x0002,0x0016) );

        PixmapWriter writer = new PixmapWriter();
        writer.SetFileName( outfilename );
        writer.SetFile( reader.GetFile() );
        gdcm.Pixmap pixout = ((PixmapToPixmapFilter)change).GetOutput();
    }
}

```

```

writer.SetPixmap( pixout );
if( !writer.Write() )
{
    System.Console.WriteLine( "Could not write: " + outfilename );
    return false;
}

return true;
}

public static int Main(string[] args)
{
    gdcm.FileMetaInformation.SetSourceApplicationEntityTitle( "My Standardize App" );

    // http://www.oid-info.com/get/1.3.6.1.4.17434
    string THERALYS_ORG_ROOT = "1.3.6.1.4.17434";
    gdcm.UIDGenerator.SetRoot( THERALYS_ORG_ROOT );
    System.Console.WriteLine( "Root dir is now: " + gdcm.UIDGenerator.GetRoot() );

    string dir1 = args[0];
    string dir2 = args[1];

    // Check input is valid:
    if( !gdcm.PosixEmulation.FileIsDirectory(dir1) )
    {
        System.Console.WriteLine( "Input directory: " + dir1 + " does not exist. Sorry" );
        return 1;
    }
    if( !gdcm.PosixEmulation.FileIsDirectory(dir2) )
    {
        System.Console.WriteLine( "Output directory: " + dir2 + " does not exist. Sorry" );
        return 1;
    }

    Directory d = new Directory();
    uint nfiles = d.Load( dir1, true );
    if(nfiles == 0) return 1;

    // Process all filenames:
    FilenamesType filenames = d.GetFilenames();
    for( uint i = 0; i < nfiles; ++i )
    {
        string filename = filenames[ (int)i ];
        string outfilename = filename.Replace( dir1, dir2 );
        System.Console.WriteLine( "Filename: " + filename );
        System.Console.WriteLine( "Out Filename: " + outfilename );
        if( !ProcessOneFile( filename, outfilename ) )
        {
            System.Console.WriteLine( "Could not process filename: " + filename );
            //return 1;
        }
    }

    return 0;
}
}

```

27.138 StreamImageReaderTest.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
// This work was realised during the GSOC 2011 by Manoj Alwani

#include "gdcmStreamImageReader.h"
#include "gdcmFileMetaInformation.h"

```

```

#include "gdcmSystem.h"
#include "gdcmFilename.h"
#include "gdcmByteSwap.h"
#include "gdcmTrace.h"
#include "gdcmTesting.h"
#include "gdcmImageHelper.h"
#include "gdcmImageReader.h"
#include "gdcmImage.h"
#include "gdcmMediaStorage.h"
#include "gdcmRAWCodec.h"
#include "gdcmJPEGLSCodec.h"
#include "gdcmUIDGenerator.h"
#include "gdcmStreamImageWriter.h"
#include "gdcmAttribute.h"
#include "gdcmFile.h"
#include "gdcmTag.h"

bool StreamImageRead(gdcm::StreamImageWriter & theStreamWriter,
    const char* filename, const char* outfilename, int resolution)
{
    gdcm::StreamImageReader reader;

    reader.SetFileName( filename );

    if (!reader.ReadImageInformation())
    {
        std::cerr << "unable to read image information" << std::endl;
        return 1; //unable to read tags as expected.
    }
    //let's be tricky; each image will be read in portions, first the top half, then the bottom
    //that way, we can test how the stream handles fragmentation of the data
    //we could also loop this to get various different size combinations, but I'm not sure
    //that's useful, yet.
    std::vector<unsigned int> extent =
        gdcm::ImageHelper::GetDimensionsValue(reader.
            GetFile());
    // std::cout << extent[0];
    //at this point, these values aren't used, but may be in the future
    //unsigned short xmin = 0;
    //unsigned short xmax = extent[0];
    //unsigned short ymin = 0;
    //unsigned short ymax = extent[1];
    //unsigned short zmin = 0;
    //unsigned short zmax = extent[2];

    std::cout<< "\n Row: "<<extent[0] <<"\n Col :"<< extent[1]<< "\n Resolution :"<< extent[2] << std::endl;

    int a =1;
    for (int i=1; i<=(extent[2]-resolution);++i)
        a = a*2;

    reader.DefinePixelExtent(0, extent[0]/a, 0, extent[1]/a, resolution-1, resolution);

    unsigned long len = reader.DefineProperBufferLength();
    char* finalBuffer = new char[len];
    memset(finalBuffer, 0, sizeof(char)*len);

    if (reader.CanReadImage())
    {
        bool result = reader.Read(finalBuffer, len);
        if( !result )
        {
            std::cout << "res2 failure:" << filename << std::endl;
            delete [] finalBuffer;
            return 1;
        }
        else
        {
            std::cout<< "Able to read";
        }
    }
    else
    {
        std::cerr<< "Not able to put in buffer"<< std::endl;
    }
}

/*
    //now, read in smaller buffer extents
    reader.DefinePixelExtent(xmin, xmax, ymin, ymax);
    len = reader.DefineProperBufferLength();

    char* buffer = new char[len];

```

```

    bool res2 = reader.Read(buffer, len);
    if( !res2 ){
        std::cerr << "res2 failure:" << filename << std::endl;
        return 1;
    }
    //copy the result into finalBuffer
    memcpy(finalBuffer, buffer, len);

    //now read the next half of the image
    ymin = ymax;
    ymax = extent[1];

    reader.DefinePixelExtent(xmin, xmax, ymin, ymax);

    //std::cerr << "Success to read image from file: " << filename << std::endl;
    unsigned long len2 = reader.DefineProperBufferLength();

    char* buffer2 = new char[len2];
    bool res3 = reader.Read(buffer2, len2);
    if( !res3 ){
        std::cerr << "res3 failure:" << filename << std::endl;
        return 1;
    }
    //copy the result into finalBuffer
    memcpy(&(finalBuffer[len]), buffer2, len2);

    delete [] buffer;
    delete [] buffer2;
*/

gdcm::Writer w;
gdcm::File &file = w.GetFile();
gdcm::DataSet &ds = file.GetDataSet();

file.GetHeader().SetDataSetTransferSyntax(
    gdcm::TransferSyntax::ExplicitVRLittleEndian );

gdcm::UIDGenerator uid;
gdcm::DataElement de( gdcm::Tag(0x8,0x18) ); // SOP Instance UID
de.SetVR( gdcm::VR::UI );
const char *u = uid.Generate();
de.SetByteValue( u, strlen(u) );
ds.Insert( de );

gdcm::DataElement del( gdcm::Tag(0x8,0x16) );
del.SetVR( gdcm::VR::UI );
gdcm::MediaStorage ms(
    gdcm::MediaStorage::VLWholeSlideMicroscopyImageStorage
);
del.SetByteValue( ms.GetString(), strlen(ms.GetString()) );
ds.Insert( del );

const char mystr[] = "MONOCHROME2 ";
gdcm::DataElement de2( gdcm::Tag(0x28,0x04) );
//de.SetTag(gdcm::Tag(0x28,0x04));
de2.SetVR( gdcm::VR::CS );
de2.SetByteValue(mystr, strlen(mystr));
ds.Insert( de2 );

gdcm::Attribute<0x0028,0x0008> Number_Of_Frames = {1};
ds.Insert( Number_Of_Frames.GetAsDataElement() );

gdcm::Attribute<0x0028,0x0010> row = {extent[0]/a}; //
ds.Insert( row.GetAsDataElement() );

gdcm::Attribute<0x0028,0x0011> col = {extent[1]/a}; //
ds.Insert( col.GetAsDataElement() );

gdcm::Attribute<0x0028,0x0100> at = {8};
ds.Insert( at.GetAsDataElement() );

gdcm::Attribute<0x0028,0x0002> at1 = {1}; //
ds.Insert( at1.GetAsDataElement() );

gdcm::Attribute<0x0028,0x0101> at2 = {8};
ds.Insert( at2.GetAsDataElement() );

gdcm::Attribute<0x0028,0x0102> at3 = {7};
ds.Insert( at3.GetAsDataElement() );
/*
ds1.Remove( gdcm::Tag(0x0028,0x0008) );

```

```

gdcmm::Attribute<0x0028,0x0008> Number_Of_Frames = {1};
ds1.Insert( Number_Of_Frames.GetAsDataElement() );
*/
theStreamWriter.SetFile(file);

if (!theStreamWriter.WriteImageInformation())
{
    std::cerr << "unable to write image information" << std::endl;
    return 1; //the CanWrite function should prevent getting here, else,
    //that's a test failure
}
std::vector<unsigned int> extent1 = gdcmm::ImageHelper::GetDimensionsValue
(file);

unsigned short xmax = extent1[0];
unsigned short ymax = extent1[1];
unsigned short theChunkSize = 1;
unsigned short ychunk = extent1[1]/theChunkSize; //go in chunk sizes of theChunkSize
unsigned short zmax = 1;

std::cout<< "\n Row: "<<extent1[0] <<"\n Col :"<< extent1[1]<< "\n Resolution :"<< extent1[2] <<
std::endl;

if (xmax == 0 || ymax == 0)
{
    std::cerr << "Image has no size, unable to write zero-sized image." << std::endl;
    return 0;
}

int z, y, nexty;
unsigned long prevLen = 0; //when going through the char buffer, make sure to grab
//the bytes sequentially. So, store how far you got in the buffer with each iteration.

for (z = 0; z < zmax; ++z){
    for (y = 0; y < ymax; y += ychunk){
        nexty = y + ychunk;
        if (nexty > ymax) nexty = ymax;
        theStreamWriter.DefinePixelExtent(0, xmax, y, nexty, z, z+1);
        unsigned long len = theStreamWriter.DefineProperBufferLength();
        std::cout << "\n" <<len;
        char* finalBuffer1 = new char[len];
        memcpy(finalBuffer1, &(finalBuffer[prevLen]), len);
        std::cout << "\nable to write";

        if (!theStreamWriter.Write(finalBuffer1, len)){
            std::cerr << "writing failure:" << "output.dcm" << " at y = " << y << " and z= " << z <<
std::endl;
            delete [] finalBuffer1;
            delete [] finalBuffer;
            return 1;
        }
        delete [] finalBuffer1;
        prevLen += len;
    }
}
delete [] finalBuffer;
std::cout << "all is set";

return true;
}

int main(int argc, char *argv[])
{
    if( argc < 3 )
    {
        std::cerr << argv[0] << " input.dcm output.dcm Resolution" << std::endl;
        return 1;
    }

    const char *filename = argv[1];
    const char *outfilename = argv[2];
    char *res = argv[3];

    int resolution = atoi(res);

    gdcmm::StreamImageWriter theStreamWriter;

    std::ofstream of;
    of.open( outfile, std::ios::out | std::ios::binary );

```



```

theStreamWriter.SetStream(of);

// else
// First of get rid of warning/debug message
gdcmm::Trace::DebugOn();
gdcmm::Trace::WarningOn();

if(!StreamImageRead( theStreamWriter, filename, outfilename, resolution))
    return 1;

uint16_t firstTag1 = 0xffff;
uint16_t secondTag1 = 0xe0dd;
uint32_t thirdTag1 = 0x00000000;
//uint16_t fourthTag1 = 0xffff;
const int theBufferSize1 = 2*sizeof(uint16_t)+sizeof(uint32_t);
char* tmpBuffer2 = new char[theBufferSize1];
memcpy(&(tmpBuffer2[0]), &firstTag1, sizeof(uint16_t));
memcpy(&(tmpBuffer2[sizeof(uint16_t)]), &secondTag1, sizeof(uint16_t));
memcpy(&(tmpBuffer2[2*sizeof(uint16_t)]), &thirdTag1, sizeof(uint32_t));
//memcpy(&(tmpBuffer2[3*sizeof(uint16_t)]), &fourthTag1, sizeof(uint16_t));
assert( of && !of.eof() && of.good() );
of.write(tmpBuffer2, theBufferSize1);
of.flush();
assert( of );

return 0;
}

```

27.139 TestByteSwap.cxx

This is a C++ example on how to use `gdcmm::ByteSwap`

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmmTypes.h"
#include "gdcmmSwapCode.h"
#include "gdcmmByteSwap.h"

#include <string.h> // memcpy

int myfunc()
{
    char vl_str[4];
    const char raw[] = "\000\000\000\004";
    memcpy(vl_str, raw, 4);
    uint32_t vl;
    gdcmm::ByteSwap<uint32_t>::SwapRangeFromSwapCodeIntoSystem(
        ((uint32_t*)(&vl_str)), gdcmm::SwapCode::BigEndian, 1);
    memcpy(&vl, vl_str, 4);
    if( vl != 0x00000004 )
    {
        std::cerr << std::hex << "vl: " << vl << std::endl;
        return 1;
    }

    gdcmm::ByteSwap<uint32_t>::SwapFromSwapCodeIntoSystem(
        vl, gdcmm::SwapCode::LittleEndian);
    if( vl != 0x00000004 )
    {
        std::cerr << std::hex << "vl: " << vl << std::endl;
        return 1;
    }

    gdcmm::ByteSwap<uint32_t>::SwapFromSwapCodeIntoSystem(
        vl, gdcmm::SwapCode::BigEndian);
}

```

```

std::cout << std::hex << "v1: " << v1 << std::endl;
if( v1 != 0x4000000 )
{
    return 1;
}

return 0;
}

int TestByteSwap(int , char *[])
{
    gdcm::SwapCode sc = gdcm::SwapCode::Unknown;
    if ( gdcm::ByteSwap<uint16_t>::SystemIsBigEndian() )
    {
        sc = gdcm::SwapCode::BigEndian;
    }
    else if ( gdcm::ByteSwap<uint16_t>::SystemIsLittleEndian() )
    {
        sc = gdcm::SwapCode::LittleEndian;
    }
    if( sc == gdcm::SwapCode::Unknown )
    {
        return 1;
    }

    std::cout << "sc: " << sc << std::endl;

    uint16_t t = 0x1234;
    gdcm::ByteSwap<uint16_t>::SwapFromSwapCodeIntoSystem(
        t, sc);
    if( sc == gdcm::SwapCode::BigEndian )
    {
        if( t != 0x3412 )
        {
            std::cerr << std::hex << "t: " << t << std::endl;
            return 1;
        }
        // ok test pass rest value to old one
        t = 0x1234;
    }
    else if ( sc == gdcm::SwapCode::LittleEndian )
    {
        if( t != 0x1234 )
        {
            std::cerr << std::hex << "t: " << t << std::endl;
            return 1;
        }
    }
}

union { char n[2]; uint16_t tn; } ul6;
memcpy(ul6.n, &t, 2 );
gdcm::ByteSwap<uint16_t>::SwapRangeFromSwapCodeIntoSystem
    (&ul6.tn, sc, 1);
uint16_t tn = ul6.tn;
if( sc == gdcm::SwapCode::BigEndian )
{
    if( tn != 0x3412 )
    {
        std::cerr << std::hex << "tn: " << tn << std::endl;
        return 1;
    }
    // ok test pass rest value to old one
    t = 0x1234;
}
else if ( sc == gdcm::SwapCode::LittleEndian )
{
    if( tn != 0x1234 )
    {
        std::cerr << std::hex << "tn: " << tn << std::endl;
        return 1;
    }
}
gdcm::ByteSwap<uint16_t>::SwapRangeFromSwapCodeIntoSystem
    (&ul6.tn, gdcm::SwapCode::BigEndian, 1);
tn = ul6.tn;
if( sc == gdcm::SwapCode::LittleEndian )
{
    if( tn != 0x3412 )
    {
        std::cerr << std::hex << "tn: " << tn << std::endl;
    }
}

```

```

        return 1;
    }
}
else if ( sc == gdcm::SwapCode::BigEndian )
{
    if( tn != 0x1234 )
    {
        std::cerr << std::hex << "tn: " << tn << std::endl;
        return 1;
    }
}

if( myfunc() )
{
    return 1;
}

uint16_t array[] = { 0x1234 };
gdcm::ByteSwap<uint16_t>::SwapRangeFromSwapCodeIntoSystem
    (array,
     gdcm::SwapCode::BigEndian,2);
if ( array[0] != 0x3412 )
{
    return 1;
}

return 0;
}

```

27.140 TestReader.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmReader.h"
#include "gdcmFileMetaInformation.h"
#include "gdcmFile.h"
#include "gdcmTesting.h"
#include "gdcmMediaStorage.h"

int TestRead(const char* filename, bool verbose = false)
{
    if( verbose )
        std::cout << "TestRead: " << filename << std::endl;

    gdcm::Reader reader;
    reader.SetFileName( filename );
    if ( !reader.Read() )
    {
        std::cerr << "TestReadError: Failed to read: " << filename << std::endl;
        return 1;
    }

    //commenting out the fmi and ds to avoid warnings
    //const gdcm::FileMetaInformation &h = reader.GetFile().GetHeader();
    //std::cout << h << std::endl;

    //const gdcm::DataSet &ds = reader.GetFile().GetDataSet();
    //std::cout << ds << std::endl;

    const char *ref = gdcm::Testing::GetMediaStorageFromFile(filename);
    gdcm::MediaStorage ms;
    ms.SetFromFile( reader.GetFile() );
    if( !ref )
    {
        std::cerr << "TestReadError: Missing MediaStorage: " << filename << std::endl;
        std::cerr << "It should be: " << ms << std::endl;
    }
}

```

```

    return 1;
}

if( ms.IsUndefined() && ref && *ref != 0 )
{
    std::cerr << "TestReadError: MediaStorage: " << filename << std::endl;
    std::cerr << "It should be instead: " << ref << std::endl;
    return 1;
}

// Make sure it is the right one:

if( ref && *ref != 0 && ms != gdcmm::MediaStorage::GetMSType(ref) )
{
    std::cerr << "Error: Found MediaStorage: " << ms << " for " << filename << std::endl;
    std::cerr << "It should be instead: " << ref << std::endl;
    return 1;
}

return 0;
}

int TestReader(int argc, char *argv[])
{
    if( argc == 2 )
    {
        const char *filename = argv[1];
        return TestRead(filename, true);
    }

    // else
    gdcmm::Trace::DebugOff();
    gdcmm::Trace::WarningOff();
    int r = 0, i = 0;
    const char *filename;
    const char * const *filenames = gdcmm::Testing::GetFileNames();
    while( (filename = filenames[i]) )
    {
        r += TestRead( filename );
        ++i;
    }

    return r;
}

```

27.141 TestReader.py

This is a C++ example on how to use `gdcmm::Reader`

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 import gdcmm
16 import os,sys
17
18 def TestRead(filename, verbose = False):
19     r = gdcmm.Reader()
20     r.SetFileName( filename )
21     success = r.Read()
22     #if verbose: print r.GetFile()
23     if verbose: print(r.GetFile().GetDataSet())
24     return success
25
26 if __name__ == "__main__":
27     success = 0

```

```

28     try:
29         filename = os.sys.argv[1]
30         success += TestRead( filename, True )
31     except:
32         # loop over all files:
33         gdcmm.Trace.DebugOff()
34         gdcmm.Trace.WarningOff()
35         t = gdcmm.Testing()
36         nfiles = t.GetNumberOfFileNames()
37         for i in range(0,nfiles):
38             filename = t.GetFileName(i)
39             success += TestRead( filename )
40
41
42     # Test succeed ?
43     sys.exit(success == 0)

```

27.142 threadgdcmm.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmmReader.h"
#include "gdcmmImageReader.h"
#include "gdcmmDirectory.h"
#include "gdcmmSystem.h"

#include "vtkImageData.h"
#include "vtkStructuredPointsWriter.h"

#include <pthread.h>

struct threadparams
{
    const char **filenames;
    size_t nfiles;
    char *scalarpointer;
// TODO I should also pass in the dim of the reference image just in case
};

void *ReadFilesThread(void *voidparams)
{
    const threadparams *params = static_cast<const threadparams *> (voidparams);

    const size_t nfiles = params->nfiles;
    for(unsigned int file = 0; file < nfiles; ++file)
    {
        /*
        // TODO: update progress
        pthread_mutex_lock(&params->lock);
        //section critique
        ReadingProgress+=params->stepProgress;
        pthread_mutex_unlock(&params->lock);
        */
        const char *filename = params->filenames[file];
        //std::cerr << filename << std::endl;

        gdcmm::ImageReader reader;
        reader.SetFileName( filename );
        try
        {
            {
                if( !reader.Read() )
                {
                    std::cerr << "Failed to read: " << filename << std::endl;
                    break;
                }
            }
        }
    }
}

```

```

    catch( ... )
    {
        std::cerr << "Failed to read: " << filename << std::endl;
        break;
    }

    const gdcm::Image &image = reader.GetImage();
    unsigned long len = image.GetBufferLength();
    char * pointer = params->scalarpointer;

#ifdef 0
    char *tempimage = new char[len];
    image.GetBuffer(tempimage);

    memcpy(pointer + file*len, tempimage, len);
    delete[] tempimage;
#else
    char *tempimage = pointer + file * len;
    image.GetBuffer(tempimage);
#endif
}

return voidparams;
}

void ShowFileNames(const threadparams &params)
{
    std::cout << "start" << std::endl;
    for(unsigned int i = 0; i < params.nfiles; ++i)
    {
        const char *filename = params.fileNames[i];
        std::cout << filename << std::endl;
    }
    std::cout << "end" << std::endl;
}

void ReadFiles(size_t nfiles, const char *fileNames[])
{
    // \precondition: nfiles > 0
    assert( nfiles > 0 );
    const char *reference= fileNames[0]; // take the first image as reference

    gdcm::ImageReader reader;
    reader.SetFileName( reference );
    if( !reader.Read() )
    {
        // That would be very bad...
        assert(0);
    }

    const gdcm::Image &image = reader.GetImage();
    gdcm::PixelFormat pixeltype = image.GetPixelFormat();
    unsigned long len = image.GetBufferLength();
    const unsigned int *dims = image.GetDimensions();
    unsigned short pixelSize = pixeltype.GetPixelSize();
    (void)pixelSize;
    assert( image.GetNumberOfDimensions() == 2 );

    vtkImageData *output = vtkImageData::New();
    output->SetDimensions(dims[0], dims[1], (int)nfiles);

    switch( pixeltype )
    {
        {
            case gdcm::PixelFormat::INT8:
#ifdef (VTK_MAJOR_VERSION >= 5) || ( VTK_MAJOR_VERSION == 4 && VTK_MINOR_VERSION > 5 )
                output->SetScalarType ( VTK_SIGNED_CHAR );
            #else
                output->SetScalarType ( VTK_CHAR );
            #endif
            break;
            case gdcm::PixelFormat::UINT8:
                output->SetScalarType ( VTK_UNSIGNED_CHAR );
            break;
            case gdcm::PixelFormat::INT16:
                output->SetScalarType ( VTK_SHORT );
            break;
            case gdcm::PixelFormat::UINT16:
                output->SetScalarType ( VTK_UNSIGNED_SHORT );
            break;
            case gdcm::PixelFormat::INT32:
                output->SetScalarType ( VTK_INT );
            break;

```

```

case gdcm::PixelFormat::UINT32:
    output->SetScalarType ( VTK_UNSIGNED_INT );
    break;
default:
    assert(0);
}

output->SetNumberOfScalarComponents ( pixeltype.GetSamplesPerPixel() );

output->AllocateScalars();
char * scalarpointer = static_cast<char*>(output->GetScalarPointer());

const unsigned int nthreads = 4;
threadparams params[nthreads];

//pthread_mutex_t lock;
//pthread_mutex_init(&lock, NULL);

pthread_t *pthread = new pthread_t[nthreads];

// There is nfiles, and nThreads
assert( nfiles > nthreads );
const size_t partition = nfiles / nthreads;
for (unsigned int thread=0; thread < nthreads; ++thread)
{
    params[thread].filenames = filenames + thread * partition;
    params[thread].nfiles = partition;
    if( thread == nthreads - 1 )
    {
        // There is slightly more files to process in this thread:
        params[thread].nfiles += nfiles % nthreads;
    }
    assert( thread * partition < nfiles );
    params[thread].scalarpointer = scalarpointer + thread * partition * len;
    //assert( params[thread].scalarpointer < scalarpointer + 2 * dims[0] * dims[1] * dims[2] );
    // start thread:
    int res = pthread_create( &pthread[thread], NULL, ReadFilesThread, &params[thread]);
    if( res )
    {
        std::cerr << "Unable to start a new thread, pthread returned: " << res << std::endl;
        assert(0);
    }
    //ShowFilenames(params[thread]);
}
// DEBUG
size_t total = 0;
for (unsigned int thread=0; thread < nthreads; ++thread)
{
    total += params[thread].nfiles;
}
assert( total == nfiles );
// END DEBUG

for (unsigned int thread=0;thread<nthreads;thread++)
{
    pthread_join( pthread[thread], NULL);
}
delete[] pthread;

//pthread_mutex_destroy(&lock);

// For some reason writing down the file is painfully slow...
vtkStructuredPointsWriter *writer = vtkStructuredPointsWriter::New();
writer->SetInput( output );
writer->SetFileName( "/tmp/threadgdcmm.vtk" );
writer->SetFileTypeToBinary();
//writer->Write();
writer->Delete();

//output->Print( std::cout );
output->Delete();
}

int main(int argc, char *argv[])
{
    if( argc < 2 )
    {
        std::cerr << argv[0] << " [directory|list of filenames]\n";
        return 1;
    }
}

```

```

// Check if user pass in a single directory
if( argc == 2 && gdcm::System::FileIsDirectory( argv[1] ) )
{
    gdcm::Directory d;
    d.Load( argv[1] );
    gdcm::Directory::FileNamesType l = d.
        GetFileNames();
    const size_t nfiles = l.size();
    const char **filenames = new const char* [ nfiles ];
    for(unsigned int i = 0; i < nfiles; ++i)
    {
        filenames[i] = l[i].c_str();
    }
    ReadFiles(nfiles, filenames);
    delete[] filenames;
}
else
{
    // Simply copy all filenames into the vector:
    const char **filenames = const_cast<const char**>(argv+1);
    const size_t nfiles = argc - 1;
    ReadFiles(nfiles, filenames);
}

return 0;
}

```

27.143 TraverseModules.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/
/*
*/

#include "gdcmDefs.h"
#include "gdcmGlobal.h"
#include "gdcmIODs.h"
#include "gdcmIOD.h"
#include "gdcmMacros.h"
#include "gdcmIODEntry.h"
#include "gdcmModules.h"
#include "gdcmModule.h"
#include "gdcmAnonymizer.h"
#include "gdcmDicts.h"

int main(int , char *[])
{
    using namespace gdcm;
    static Global &g = Global::GetInstance();

    if( !g.LoadResourcesFiles() )
    {
        return 1;
    }

    static const Defs &defs = g.GetDefs();
    static const Modules &modules = defs.GetModules();
    static const IODs &iods = defs.GetIODs();
    static const Macros &macros = defs.GetMacros();
    static const Dicts &dicts = g.GetDicts();

    std::vector<Tag> tags =
        gdcm::Anonymizer::GetBasicApplicationLevelConfidentialityProfileAttributes
        ();
    for( std::vector<Tag>::const_iterator tit = tags.begin(); tit != tags.end(); ++tit )

```



```

{
    const Tag &tag = *tit;
    const DictEntry &dictentry = dicts.GetDictEntry(tag);
    std::cout << "Processing Attribute: " << tag << " " << dictentry << std::endl;

    IODs::IODMapTypeConstIterator it = iods.Begin();
    for( ; it != iods.End(); ++it )
    {
        const IODs::IODName &name = it->first;
        const IOD &iod = it->second;

        const size_t niods = iod.GetNumberOfIODs();
        // Iterate over each iod entry in order:
        for(unsigned int idx = 0; idx < niods; ++idx)
        {
            const IODEntry &iodentry = iod.GetIODEntry(idx);
            const char *ref = iodentry.GetRef();
            //Usage::UsageType ut = iodentry.GetUsageType();

            const Module &module = modules.GetModule( ref );
            if( module.FindModuleEntryInMacros(macros, tag) )
            {
                const ModuleEntry &module_entry = module.
                GetModuleEntryInMacros(macros,tag);
                Type type = module_entry.GetType();
                std::cout << "IOD Name: " << name << std::endl;
                std::cout << "Type: " << type << std::endl;
            }
        }
    }
}

return 0;
}

```

27.144 uid_unique.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.

=====*/
#include "gdcmUIDGenerator.h"

#include <iostream>
#include <string>
#include <set>

int main()
{
    gdcm::UIDGenerator uid;
    //const char myroot[] = "9876543210.9876543210.9876543210.9876543210.9876543210"; // fails in ~40000
    tries
    const char myroot[] = "9876543210.9876543210.9876543210";
    uid.SetRoot( myroot );
    std::set<std::string> uids;
    uint64_t wrap = 0;
    uint64_t c = 0;
    while(1)
    {
        const char *unique = uid.Generate();
        //std::cout << unique << std::endl;
        if( c % 10000 == 0 )
        {
            std::cout << "wrap=" << wrap << ",c=" << c << std::endl;
        }
        ++c;
        if( c == 0 )
    }
}

```

```

        {
            wrap++;
        }
        if ( uids.count(unique) == 1 )
        {
            std::cerr << "Failed with: " << unique << std::endl;
            return 1;
        }
        uids.insert( unique );
    }
    return 0;
}

```

27.145 VolumeSorter.cxx

```

/*=====
Program: GDCM (Grassroots DICOM). A DICOM library

Copyright (c) 2006-2011 Mathieu Malaterre
All rights reserved.
See Copyright.txt or http://gdcm.sourceforge.net/Copyright.html for details.

This software is distributed WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the above copyright notice for more information.
=====*/
/*
*/
#include "gdcmSorter.h"
#include "gdcmIPPSorter.h"
#include "gdcmScanner.h"
#include "gdcmDataSet.h"
#include "gdcmAttribute.h"
#include "gdcmTesting.h"

bool mysort1(gdcm::DataSet const & ds1, gdcm::DataSet const & ds2 )
{
    gdcm::Attribute<0x0020,0x000d> at1;
    at1.Set( ds1 );
    gdcm::Attribute<0x0020,0x000d> at2;
    at2.Set( ds2 );
    return at1 < at2;
}

bool mysort2(gdcm::DataSet const & ds1, gdcm::DataSet const & ds2 )
{
    gdcm::Attribute<0x0020,0x000e> at1;
    at1.Set( ds1 );
    gdcm::Attribute<0x0020,0x000e> at2;
    at2.Set( ds2 );
    return at1 < at2;
}

bool mysort3(gdcm::DataSet const & ds1, gdcm::DataSet const & ds2 )
{
    // This is a floating point number is the comparison ok ?
    gdcm::Attribute<0x0020,0x0037> at1;
    at1.Set( ds1 );
    gdcm::Attribute<0x0020,0x0037> at2;
    at2.Set( ds2 );
    return at1 < at2;
}

bool mysort4(gdcm::DataSet const & ds1, gdcm::DataSet const & ds2 )
{
    // Do the IPP sorting here
    gdcm::Attribute<0x0020,0x0032> ipp1;
    gdcm::Attribute<0x0020,0x0037> iop1;
    ipp1.Set( ds1 );
    iop1.Set( ds1 );
    gdcm::Attribute<0x0020,0x0032> ipp2;
    gdcm::Attribute<0x0020,0x0037> iop2;
    ipp2.Set( ds2 );
    iop2.Set( ds2 );
}

```

```

    if( iop1 != iop2 )
    {
        return false;
    }

    // else
    double normal[3];
    normal[0] = iop1[1]*iop1[5] - iop1[2]*iop1[4];
    normal[1] = iop1[2]*iop1[3] - iop1[0]*iop1[5];
    normal[2] = iop1[0]*iop1[4] - iop1[1]*iop1[3];
    double dist1 = 0;
    for (int i = 0; i < 3; ++i) dist1 += normal[i]*ipp1[i];
    double dist2 = 0;
    for (int i = 0; i < 3; ++i) dist2 += normal[i]*ipp2[i];

    std::cout << dist1 << ", " << dist2 << std::endl;
    return dist1 < dist2;
}

int main(int argc, char *argv[])
{
    const char *extradataroot = gdcm::Testing::GetDataExtraRoot();
    std::string dir1;
    if( argc < 2 )
    {
        if( !extradataroot )
        {
            return 1;
        }
        dir1 = extradataroot;
        dir1 += "/gdcmSampleData/ForSeriesTesting/VariousIncidences/ST1";
    }
    else
    {
        dir1 = argv[1];
    }

    gdcm::Directory d;
    d.Load( dir1.c_str(), true ); // recursive !
    const gdcm::Directory::FileNamesType &l1 = d.
        GetFileNames();
    const size_t nfiles = l1.size();
    std::cout << nfiles << std::endl;

    //if( nfiles != 280 )
    // {
    //     return 1;
    // }

    //d.Print( std::cout );

    gdcm::Scanner s0;
    const gdcm::Tag t1(0x0020,0x000d); // Study Instance UID
    const gdcm::Tag t2(0x0020,0x000e); // Series Instance UID
    //const gdcm::Tag t3(0x0010,0x0010); // Patient's Name
    s0.AddTag( t1 );
    s0.AddTag( t2 );
    //s0.AddTag( t3 );
    //s0.AddTag( t4 );
    //s0.AddTag( t5 );
    //s0.AddTag( t6 );
    bool b = s0.Scan( d.GetFileNames() );
    if( !b )
    {
        std::cerr << "Scanner failed" << std::endl;
        return 1;
    }

    //s0.Print( std::cout );

    // Only get the DICOM files:
    gdcm::Directory::FileNamesType l2 = s0.GetKeys();
    const size_t nfiles2 = l2.size();
    std::cout << nfiles2 << std::endl;

    if ( nfiles2 > nfiles )
    {
        return 1;
    }
}

```

```

gdcmm::Sorter sorter;
sorter.SetSortFunction( mysort1 );
sorter.StableSort( 12 );

sorter.SetSortFunction( mysort2 );
sorter.StableSort( sorter.GetFileNames() );

sorter.SetSortFunction( mysort3 );
sorter.StableSort( sorter.GetFileNames() );

sorter.SetSortFunction( mysort4 );
sorter.StableSort( sorter.GetFileNames() );

//sorter.Print( std::cout );

// Let's try to check our result:
// assume that IPP is precise enough so that we can test floating point equality:
size_t nvalues = 0;
{
    gdcmm::Scanner s;
    s.AddTag( gdcmm::Tag(0x20,0x32) ); // Image Position (Patient)
    //s.AddTag( gdcmm::Tag(0x20,0x37) ); // Image Orientation (Patient)
    s.Scan( d.GetFileNames() );

    //s.Print( std::cout );

    const gdcmm::Scanner::ValueType &values = s.GetValues();
    nvalues = values.size();
    std::cout << "There are " << nvalues << " different type of values" << std::endl;
    assert( nfiles2 % nvalues == 0 );
    std::cout << "Series is composed of " << (nfiles/nvalues) << " different 3D volumes" << std::endl;
}

gdcmm::Directory::FileNamesType sorted_files = sorter.
    GetFileNames();

// Which means we can take nvalues files at a time and execute gdcmm::IPPSorter on it:
gdcmm::IPPSorter ippsorter;
gdcmm::Directory::FileNamesType sub( sorted_files.begin(), sorted_files.
    begin() + nvalues);
std::cout << sub.size() << std::endl;
std::cout << sub[0] << std::endl;
std::cout << sub[nvalues-1] << std::endl;
ippsorter.SetComputeZSpacing( false );
if( !ippsorter.Sort( sub ) )
{
    std::cerr << "Could not sort" << std::endl;
    return 1;
}

std::cout << "IPPSorter:" << std::endl;
ippsorter.Print( std::cout );

return 0;
}

```

27.146 WriteBuffer.py

```

1 #####
2 #
3 #   Program: GDCM (Grassroots DICOM). A DICOM library
4 #
5 #   Copyright (c) 2006-2011 Mathieu Malaterre
6 #   All rights reserved.
7 #   See Copyright.txt or http://gdcmm.sourceforge.net/Copyright.html for details.
8 #
9 #   This software is distributed WITHOUT ANY WARRANTY; without even
10 #   the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
11 #   PURPOSE. See the above copyright notice for more information.
12 #
13 #####
14
15 """
16 Usage:

```

```

17
18 http://chuckhahm.com/Ischem/Zurich/XX_0134
19
20 (2005,1132) SQ (Sequence with undefined length #=8) # u/l, 1 Unknown Tag & Data
21 (fffe,e000) na (Item with undefined length #=9) # u/l, 1 Item
22 (2005,0011) LO [Philips MR Imaging DD 002] # 26, 1 PrivateCreator
23 (2005,1137) PN [PDF_CONTROL_GEN_PARS] # 20, 1 Unknown Tag & Data
24 (2005,1138) PN (no value available) # 0, 0 Unknown Tag & Data
25 (2005,1139) PN [IEEE_PDF] # 8, 1 Unknown Tag & Data
26 (2005,1140) PN (no value available) # 0, 0 Unknown Tag & Data
27 (2005,1141) PN (no value available) # 0, 0 Unknown Tag & Data
28 (2005,1143) SL 3103 # 4, 1 Unknown Tag & Data
29 (2005,1144) OW 0566\0000\013b\0000\0a4a\0000\000e\0000\0a7a\0000\0195\0000\0008... # 3104, 1 Unknown
    Tag & Data
30 (2005,1147) CS [Y] # 2, 1 Unknown Tag & Data
31 (fffe,e00d) na (ItemDelimitationItem) # 0, 0 ItemDelimitationItem
32 (fffe,e000) na (Item with undefined length #=9) # u/l, 1 Item
33 (2005,0011) LO [Philips MR Imaging DD 002] # 26, 1 PrivateCreator
34 (2005,1137) PN [PDF_CONTROL_PREP_PARS] # 22, 1 Unknown Tag & Data
35 (2005,1138) PN (no value available) # 0, 0 Unknown Tag & Data
36 (2005,1139) PN [IEEE_PDF] # 8, 1 Unknown Tag & Data
37 (2005,1140) PN (no value available) # 0, 0 Unknown Tag & Data
38 (2005,1141) PN (no value available) # 0, 0 Unknown Tag & Data
39 (2005,1143) SL 7934 # 4, 1 Unknown Tag & Data
40 (2005,1144) OW 19b6\0000\005f\0000\1b2a\0000\00f3\0000\1eee\0000\0000\0000\0008... # 7934, 1 Unknown
    Tag & Data
41 (2005,1147) CS [Y] # 2, 1 Unknown Tag & Data
42 (fffe,e00d) na (ItemDelimitationItem) # 0, 0 ItemDelimitationItem
43 ...
44 ""
45
46 import sys
47 import gdcm
48
49 if __name__ == "__main__":
50
51     file1 = sys.argv[1]
52     file2 = sys.argv[2]
53
54     r = gdcm.Reader()
55     r.SetFileName( file1 )
56     if not r.Read():
57         sys.exit(1)
58
59     fg = gdcm.FileNameGenerator()
60     f = r.GetFile()
61     ds = f.GetDataSet()
62     tsis = gdcm.Tag(0x2005,0x1132) #
63     if ds.FindDataElement( tsis ):
64         sis = ds.GetDataElement( tsis )
65         #sqsis = sis.GetSequenceOfItems()
66         # GetValueAsSQ handle more cases
67         sqsis = sis.GetValueAsSQ()
68         if sqsis.GetNumberOfItems():
69             nitems = sqsis.GetNumberOfItems();
70             fg.SetNumberOfFileNames( nitems )
71             fg.SetPrefix( file2 )
72             if not fg.Generate():
73                 print "problem"
74                 sys.exit(1)
75             for i in range(0,nitems):
76                 item1 = sqsis.GetItem(i+1) # Item start at 1
77                 nestedds = item1.GetNestedDataSet()
78                 tprcs = gdcm.Tag(0x2005,0x1144) #
79                 if nestedds.FindDataElement( tprcs ):
80                     prcs = nestedds.GetDataElement( tprcs )
81                     bv = prcs.GetByteValue()
82                     print bv
83                     f = open( fg.GetFilename(i) , "w" )
84                     f.write( bv.WriteBuffer() )

```

Index

- ~ASN1
 - gdcmm::ASN1, [161](#)
- ~AnonymizeEvent
 - gdcmm::AnonymizeEvent, [147](#)
- ~Anonymizer
 - gdcmm::Anonymizer, [150](#)
- ~Attribute
 - gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >, [178](#)
- ~AudioCodec
 - gdcmm::AudioCodec, [189](#)
- ~Base64
 - gdcmm::Base64, [190](#)
- ~BasePDU
 - gdcmm::network::BasePDU, [194](#)
- ~BaseRootQuery
 - gdcmm::BaseRootQuery, [196](#)
- ~Bitmap
 - gdcmm::Bitmap, [206](#)
- ~BitmapToBitmapFilter
 - gdcmm::BitmapToBitmapFilter, [212](#)
- ~BoxRegion
 - gdcmm::BoxRegion, [214](#)
- ~ByteSwapFilter
 - gdcmm::ByteSwapFilter, [218](#)
- ~ByteValue
 - gdcmm::ByteValue, [221](#)
- ~CSAHeader
 - gdcmm::CSAHeader, [258](#)
- ~Coder
 - gdcmm::Coder, [236](#)
- ~Command
 - gdcmm::Command, [241](#)
- ~CommandDataSet
 - gdcmm::CommandDataSet, [243](#)
- ~CryptographicMessageSyntax
 - gdcmm::CryptographicMessageSyntax, [251](#)
- ~Curve
 - gdcmm::Curve, [269](#)
- ~DICOMDIRGenerator
 - gdcmm::DICOMDIRGenerator, [300](#)
- ~DataEvent
 - gdcmm::DataEvent, [282](#)
- ~DataSetEvent
 - gdcmm::DataSetEvent, [291](#)
- ~Decoder
 - gdcmm::Decoder, [292](#)
- ~Defs
 - gdcmm::Defs, [295](#)
- ~DeltaEncodingCodec
 - gdcmm::DeltaEncodingCodec, [297](#)
- ~DictConverter
 - gdcmm::DictConverter, [304](#)
- ~DictPrinter
 - gdcmm::DictPrinter, [309](#)
- ~Dicts
 - gdcmm::Dicts, [311](#)
- ~DirectionCosines
 - gdcmm::DirectionCosines, [315](#)
- ~Directory
 - gdcmm::Directory, [317](#)
- ~Dumper
 - gdcmm::Dumper, [322](#)
- ~Element
 - gdcmm::Element< TVR, VM::VM1_n >, [328](#)
- ~Event
 - gdcmm::Event, [346](#)
- ~Exception
 - gdcmm::Exception, [348](#)
- ~File
 - gdcmm::File, [356](#)
- ~FileAnonymizer
 - gdcmm::FileAnonymizer, [359](#)
- ~FileDerivation
 - gdcmm::FileDerivation, [361](#)
- ~FileExplicitFilter
 - gdcmm::FileExplicitFilter, [363](#)
- ~FileMetaInformation
 - gdcmm::FileMetaInformation, [367](#)
- ~FilenameGenerator
 - gdcmm::FilenameGenerator, [373](#)
- ~Global
 - gdcmm::Global, [385](#)
- ~GroupDict
 - gdcmm::GroupDict, [387](#)
- ~IPPSorter
 - gdcmm::IPPSorter, [444](#)
- ~IconImageFilter
 - gdcmm::IconImageFilter, [389](#)
- ~IconImageGenerator

- gdcmm::IconImageGenerator, 391
- ~Image
 - gdcmm::Image, 395
- ~ImageApplyLookupTable
 - gdcmm::ImageApplyLookupTable, 399
- ~ImageChangePhotometricInterpretation
 - gdcmm::ImageChangePhotometricInterpretation, 402
- ~ImageChangePlanarConfiguration
 - gdcmm::ImageChangePlanarConfiguration, 405
- ~ImageChangeTransferSyntax
 - gdcmm::ImageChangeTransferSyntax, 408
- ~ImageCodec
 - gdcmm::ImageCodec, 412
- ~ImageConverter
 - gdcmm::ImageConverter, 416
- ~ImageFragmentSplitter
 - gdcmm::ImageFragmentSplitter, 418
- ~ImageReader
 - gdcmm::ImageReader, 424
- ~ImageRegionReader
 - gdcmm::ImageRegionReader, 427
- ~ImageToImageFilter
 - gdcmm::ImageToImageFilter, 430
- ~ImageWriter
 - gdcmm::ImageWriter, 432
- ~JPEG12Codec
 - gdcmm::JPEG12Codec, 452
- ~JPEG16Codec
 - gdcmm::JPEG16Codec, 454
- ~JPEG2000Codec
 - gdcmm::JPEG2000Codec, 456
- ~JPEG8Codec
 - gdcmm::JPEG8Codec, 459
- ~JPEGCodec
 - gdcmm::JPEGCodec, 462
- ~JPEGLSCodec
 - gdcmm::JPEGLSCodec, 466
- ~KAKADUCodec
 - gdcmm::KAKADUCodec, 468
- ~LookupTable
 - gdcmm::LookupTable, 474
- ~MD5
 - gdcmm::MD5, 481
- ~MemberCommand
 - gdcmm::MemberCommand, 491
- ~MeshPrimitive
 - gdcmm::MeshPrimitive, 495
- ~ModuleEntry
 - gdcmm::ModuleEntry, 500
- ~Object
 - gdcmm::Object, 512
- ~Orientation
 - gdcmm::Orientation, 514
- ~Overlay
 - gdcmm::Overlay, 518
- ~PDBHeader
 - gdcmm::PDBHeader, 531
- ~PDFCodec
 - gdcmm::PDFCodec, 533
- ~PGXCodec
 - gdcmm::PGXCodec, 537
- ~PNMCodec
 - gdcmm::PNMCodec, 559
- ~PVRGCodec
 - gdcmm::PVRGCodec, 580
- ~ParseException
 - gdcmm::ParseException, 522
- ~Parser
 - gdcmm::Parser, 524
- ~PixelFormat
 - gdcmm::PixelFormat, 542
- ~Pixmap
 - gdcmm::Pixmap, 547
- ~PixmapReader
 - gdcmm::PixmapReader, 551
- ~PixmapToPixmapFilter
 - gdcmm::PixmapToPixmapFilter, 553
- ~PixmapWriter
 - gdcmm::PixmapWriter, 556
- ~Preamble
 - gdcmm::Preamble, 560
- ~Printer
 - gdcmm::Printer, 572
- ~PrivateDict
 - gdcmm::PrivateDict, 574
- ~ProgressEvent
 - gdcmm::ProgressEvent, 578
- ~PythonFilter
 - gdcmm::PythonFilter, 581
- ~QueryBase
 - gdcmm::QueryBase, 583
- ~RAWCodec
 - gdcmm::RAWCodec, 594
- ~RLECodec
 - gdcmm::RLECodec, 607
- ~Reader
 - gdcmm::Reader, 598
- ~Region
 - gdcmm::Region, 601
- ~Rescaler
 - gdcmm::Rescaler, 604
- ~SHA1
 - gdcmm::SHA1, 647
- ~Scanner
 - gdcmm::Scanner, 614
- ~Segment
 - gdcmm::Segment, 619
- ~SegmentReader

- gdcmm::SegmentReader, 624
- ~SegmentWriter
 - gdcmm::SegmentWriter, 627
- ~SegmentedPaletteColorLookupTable
 - gdcmm::SegmentedPaletteColorLookupTable, 622
- ~SerieHelper
 - gdcmm::SerieHelper, 639
- ~ServiceClassUser
 - gdcmm::ServiceClassUser, 644
- ~SimpleMemberCommand
 - gdcmm::SimpleMemberCommand, 650
- ~SimpleSubjectWatcher
 - gdcmm::SimpleSubjectWatcher, 651
- ~SmartPointer
 - gdcmm::SmartPointer, 654
- ~Sorter
 - gdcmm::Sorter, 660
- ~Spacing
 - gdcmm::Spacing, 662
- ~SplitMosaicFilter
 - gdcmm::SplitMosaicFilter, 664
- ~StreamImageReader
 - gdcmm::StreamImageReader, 667
- ~StreamImageWriter
 - gdcmm::StreamImageWriter, 671
- ~StringFilter
 - gdcmm::StringFilter, 678
- ~Subject
 - gdcmm::Subject, 682
- ~Surface
 - gdcmm::Surface, 686
- ~SurfaceReader
 - gdcmm::SurfaceReader, 694
- ~SurfaceWriter
 - gdcmm::SurfaceWriter, 696
- ~Table
 - gdcmm::Table, 704
- ~TableEntry
 - gdcmm::TableEntry, 705
- ~TableReader
 - gdcmm::TableReader, 706
- ~TableRow
 - gdcmm::network::TableRow, 708
- ~TagPath
 - gdcmm::TagPath, 715
- ~Testing
 - gdcmm::Testing, 717
- ~Trace
 - gdcmm::Trace, 721
- ~Transition
 - gdcmm::network::Transition, 728
- ~ULAction
 - gdcmm::network::ULAction, 754
- ~ULBasicCallback
 - gdcmm::network::ULBasicCallback, 788
- ~ULConnection
 - gdcmm::network::ULConnection, 790
- ~ULConnectionCallback
 - gdcmm::network::ULConnectionCallback, 792
- ~ULConnectionManager
 - gdcmm::network::ULConnectionManager, 796
- ~ULEvent
 - gdcmm::network::ULEvent, 797
- ~ULWritingCallback
 - gdcmm::network::ULWritingCallback, 800
- ~UserInformation
 - gdcmm::network::UserInformation, 808
- ~Validate
 - gdcmm::Validate, 810
- ~Value
 - gdcmm::Value, 811
- ~Version
 - gdcmm::Version, 813
- ~Writer
 - gdcmm::Writer, 884
- ~XMLDictReader
 - gdcmm::XMLDictReader, 887
- ~XMLPrivateDictReader
 - gdcmm::XMLPrivateDictReader, 889
- ~vtkGDCMImageReader
 - vtkGDCMImageReader, 831
- ~vtkGDCMImageWriter
 - vtkGDCMImageWriter, 837
- ~vtkGDCMMedicalImageProperties
 - vtkGDCMMedicalImageProperties, 841
- ~vtkGDCMPolyDataReader
 - vtkGDCMPolyDataReader, 843
- ~vtkGDCMPolyDataWriter
 - vtkGDCMPolyDataWriter, 846
- ~vtkGDCMTesting
 - vtkGDCMTesting, 849
- ~vtkGDCMThreadedImageReader
 - vtkGDCMThreadedImageReader, 852
- ~vtkGDCMThreadedImageReader2
 - vtkGDCMThreadedImageReader2, 854
- ~vtkImageColorViewer
 - vtkImageColorViewer, 859
- ~vtkImageMapToColors16
 - vtkImageMapToColors16, 864
- ~vtkImageMapToWindowLevelColors2
 - vtkImageMapToWindowLevelColors2, 867
- ~vtkImagePlanarComponentsToComponents
 - vtkImagePlanarComponentsToComponents, 869
- ~vtkImageRGBToYBR
 - vtkImageRGBToYBR, 871
- ~vtkImageYBRToRGB
 - vtkImageYBRToRGB, 873
- ~vtkLookupTable16

- vtkLookupTable16, [874](#)
- ~vtkRTStructSetProperties
 - vtkRTStructSetProperties, [877](#)
- AE
 - gdcm::VR, [822](#)
- AES128_CIPHER
 - gdcm::CryptographicMessageSyntax, [251](#)
- AES192_CIPHER
 - gdcm::CryptographicMessageSyntax, [251](#)
- AES256_CIPHER
 - gdcm::CryptographicMessageSyntax, [251](#)
- ALGOType_END
 - gdcm::Segment, [619](#)
- ARGB
 - gdcm::PhotometricInterpretation, [539](#)
- AS
 - gdcm::VR, [822](#)
- AT
 - gdcm::VR, [822](#)
- AUTOMATIC
 - gdcm::Segment, [619](#)
- AXIAL
 - gdcm::Orientation, [514](#)
- AAAbortPDU
 - gdcm::network::AAAbortPDU, [134](#)
- AAAssociateACPDU
 - gdcm::network::AAAssociateACPDU, [137](#)
 - gdcm::network::AAAssociateRQPDU, [143](#)
- AAAssociateRJPDU
 - gdcm::network::AAAssociateRJPDU, [139](#)
- AAAssociateRQPDU
 - gdcm::network::AAAssociateACPDU, [137](#)
 - gdcm::network::AAAssociateRQPDU, [141](#)
- AECComp
 - gdcm, [117](#)
- ALGOType
 - gdcm::Segment, [619](#)
- ARTIMTimer
 - gdcm::network::ARTIMTimer, [160](#)
- AReleaseRPPDU
 - gdcm::network::AReleaseRPPDU, [157](#)
- AReleaseRQPDU
 - gdcm::network::AReleaseRQPDU, [159](#)
- ASComp
 - gdcm, [117](#)
- ASN1
 - gdcm::ASN1, [161](#)
- AbstractSyntax
 - gdcm::network::AbstractSyntax, [145](#)
- ActiveComponent
 - vtkImageMapToColors16, [865](#)
- Add
 - gdcm::GroupDict, [387](#)
 - AddAcceptedPresentationContext
 - gdcm::network::ULConnection, [790](#)
 - AddCSAHeaderDictEntry
 - gdcm::CSAHeaderDict, [261](#)
 - AddContourReferencedFrameOfReference
 - vtkRTStructSetProperties, [877](#)
 - AddDerivationDescription
 - gdcm::FileDerivation, [361](#)
 - AddDictEntry
 - gdcm::Dict, [302](#)
 - gdcm::PrivateDict, [574](#)
 - AddFile
 - gdcm::FileSet, [375](#)
 - gdcm::SerieHelper, [639](#)
 - AddFileName
 - gdcm::SerieHelper, [639](#)
 - AddFragment
 - gdcm::SequenceOfFragments, [630](#)
 - AddGroupLength
 - gdcm::DictConverter, [304](#)
 - AddIOD
 - gdcm::IODs, [442](#)
 - AddIODEntry
 - gdcm::IOD, [439](#)
 - AddImageDirectoryRecord
 - gdcm::DICOMDIRGenerator, [300](#)
 - AddInput
 - vtkImageColorViewer, [859](#)
 - AddInputConnection
 - vtkImageColorViewer, [859](#)
 - AddItem
 - gdcm::SequenceOfItems, [635](#)
 - AddMacro
 - gdcm::Macros, [479](#)
 - gdcm::Module, [498](#)
 - AddMacroEntry
 - gdcm::Macro, [477](#)
 - AddModule
 - gdcm::Modules, [502](#)
 - AddModuleEntry
 - gdcm::Module, [498](#)
 - gdcm::NestedModuleEntries, [509](#)
 - AddObserver
 - gdcm::Subject, [682](#)
 - AddPatientDirectoryRecord
 - gdcm::DICOMDIRGenerator, [300](#)
 - AddPresentationContext
 - gdcm::network::AAAssociateRQPDU, [142](#)
 - gdcm::PresentationContextGenerator, [565](#)
 - AddPresentationContextAC
 - gdcm::network::AAAssociateACPDU, [137](#)
 - AddPresentationDataValue
 - gdcm::network::PDataTFPDU, [527](#)
 - AddPrimitiveData

- gdcmm::MeshPrimitive, 495
- AddPrivateTag
 - gdcmm::Scanner, 614
- AddPurposeOfReferenceCodeSequence
 - gdcmm::FileDerivation, 361
- AddQueryDataSet
 - gdcmm::BaseRootQuery, 196
- AddReference
 - gdcmm::FileDerivation, 361
- AddReferencedFrameOfReference
 - vtkRTStructSetProperties, 878
- AddRestriction
 - gdcmm::SerieHelper, 640
- AddRoleSelectionSub
 - gdcmm::network::UserInformation, 808
- AddSOPClassExtendedNegociationSub
 - gdcmm::network::UserInformation, 808
- AddSegment
 - gdcmm::SegmentWriter, 627
- AddSelect
 - gdcmm::Sorter, 660
- AddSeriesDirectoryRecord
 - gdcmm::DICOMDIRGenerator, 300
- AddSkipTag
 - gdcmm::Scanner, 614
- AddSourceImageSequence
 - gdcmm::FileDerivation, 361
- AddStructureSetROI
 - vtkRTStructSetProperties, 878
- AddStructureSetROIObservation
 - vtkRTStructSetProperties, 878
- AddStudyDirectoryRecord
 - gdcmm::DICOMDIRGenerator, 300
- AddSurface
 - gdcmm::Segment, 619
- AddTag
 - gdcmm::Scanner, 614
- AddTransferSyntax
 - gdcmm::network::PresentationContextRQ, 567
 - gdcmm::PresentationContext, 562
- AffectedSOPClassUID
 - gdcmm::network::CEchoRQ, 224
- Allocate
 - gdcmm::LookupTable, 474
- AmbulatoryECGWaveformStorage
 - gdcmm::MediaStorage, 485
 - gdcmm::UIDs, 741
- AnatomicRegion
 - gdcmm::Segment, 620
- AnonymizeEvent
 - gdcmm::Anonymizer, 147
- Anonymizer
 - gdcmm::Anonymizer, 150
- Append
 - gdcmm::Global, 385
- AppendImplementationClassUID
 - gdcmm::FileMetaInformation, 367
- ApplicationContext
 - gdcmm::network::ApplicationContext, 154
- Apply
 - gdcmm::ImageApplyLookupTable, 399
- ApplyInverseVideo
 - vtkGDCMImageReader, 834
- ApplyLookupTable
 - vtkGDCMImageReader, 834
- ApplyPlanarConfiguration
 - vtkGDCMImageReader, 834
- ApplyShiftScale
 - vtkGDCMImageReader, 834
- ApplyYBRToRGB
 - vtkGDCMImageReader, 834
- AreOverlaysInPixelData
 - gdcmm::Bitmap, 206
 - gdcmm::Pixmap, 547
- Area
 - gdcmm::BoxRegion, 214
 - gdcmm::Region, 601
- ArrayIncludeMacrosType
 - gdcmm::Macro, 477
 - gdcmm::Module, 498
- ArrayType
 - gdcmm::Attribute, 164
 - gdcmm::Attribute< Group, Element, TVR, VM::VM1 >, 171
 - gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >, 178
- AsynchronousOperationsWindowSub
 - gdcmm::network::AsynchronousOperationsWindow-Sub, 162
- Attribute
 - gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >, 178
 - gdcmm::terminal, 131
- Audio
 - gdcmm::MediaStorage, 486
- AudioSRStorageTrialRetired
 - gdcmm::UIDs, 742
- AudioCodec
 - gdcmm::AudioCodec, 189
- AutoPixelMinMax
 - gdcmm::IconImageGenerator, 391
- BLUE
 - gdcmm::LookupTable, 474
- BALCPPProtect
 - gdcmm::Anonymizer, 150
- backslash
 - gdcmm, 119

- BadBigEndian
 - gdcm::SwapCode, [697](#)
- BadLittleEndian
 - gdcm::SwapCode, [697](#)
- Base64
 - gdcm::Base64, [190](#)
- BaseRootQuery
 - gdcm::BaseRootQuery, [196](#)
- BasicAnnotationBoxSOPClass
 - gdcm::UIDs, [740](#)
- BasicColorImageBoxSOPClass
 - gdcm::UIDs, [740](#)
- BasicColorPrintManagementMetaSOPClass
 - gdcm::UIDs, [740](#)
- BasicFilmBoxSOPClass
 - gdcm::UIDs, [740](#)
- BasicFilmSessionSOPClass
 - gdcm::UIDs, [740](#)
- BasicGrayscaleImageBoxSOPClass
 - gdcm::UIDs, [740](#)
- BasicGrayscalePrintManagementMetaSOPClass
 - gdcm::UIDs, [740](#)
- BasicPrintImageOverlayBoxSOPClassRetired
 - gdcm::UIDs, [741](#)
- BasicStudyContentNotificationSOPClassRetired
 - gdcm::UIDs, [740](#)
- BasicTextSR
 - gdcm::MediaStorage, [485](#)
- BasicTextSRStorage
 - gdcm::UIDs, [742](#)
- BasicVoiceAudioWaveformStorage
 - gdcm::MediaStorage, [485](#)
 - gdcm::UIDs, [741](#)
- BasicApplicationLevelConfidentialityProfile
 - gdcm::Anonymizer, [150](#)
- BasicCodedEntry
 - gdcm::SegmentHelper::BasicCodedEntry, [200](#)
- BasicOffsetTable
 - gdcm::BasicOffsetTable, [202](#)
- Begin
 - gdcm::CSAHeaderDict, [261](#)
 - gdcm::DataSet, [285](#)
 - gdcm::Dict, [302](#)
 - gdcm::IODs, [442](#)
 - gdcm::Scanner, [614](#)
 - gdcm::SequenceOfFragments, [630](#)
 - gdcm::SequenceOfItems, [635](#)
- BigEndian
 - gdcm::SwapCode, [697](#)
- BitSample
 - gdcm::JPEGCodec, [463](#)
 - gdcm::LookupTable, [476](#)
- Bitmap
 - gdcm::Bitmap, [206](#)
 - gdcm::JPEG2000Codec, [457](#)
 - gdcm::PixelFormat, [545](#)
- BitmapToBitmapFilter
 - gdcm::BitmapToBitmapFilter, [212](#)
- black
 - gdcm::terminal, [131](#)
- BlendingSoftcopyPresentationStateStorageSOPClass
 - gdcm::UIDs, [742](#)
- blink
 - gdcm::terminal, [131](#)
- blue
 - gdcm::terminal, [131](#)
- BoundingBox
 - gdcm::BoxRegion, [214](#)
- BoxRegion
 - gdcm::BoxRegion, [214](#)
- BreakConnection
 - gdcm::network::ULConnectionManager, [796](#)
- BreakConnectionNow
 - gdcm::network::ULConnectionManager, [796](#)
- BreastImagingRelevantPatientInformationQuery
 - gdcm::UIDs, [743](#)
- BreastTomosynthesisImageStorage
 - gdcm::MediaStorage, [486](#)
 - gdcm::UIDs, [745](#)
- bright
 - gdcm::terminal, [131](#)
- Build
 - vtkLookupTable16, [874](#)
- ByteBuffer
 - gdcm::ByteBuffer, [216](#)
- ByteSwap
 - gdcm::ByteSwapFilter, [218](#)
- ByteSwapFilter
 - gdcm::ByteSwapFilter, [218](#)
- ByteValue
 - gdcm::ByteValue, [220](#)
- bytes
 - gdcm::Tag, [714](#)
- C_CANCEL_RQ
 - gdcm::network::DIMSE, [314](#)
- C_ECHO_RQ
 - gdcm::network::DIMSE, [313](#)
- C_ECHO_RSP
 - gdcm::network::DIMSE, [313](#)
- C_FIND_RQ
 - gdcm::network::DIMSE, [313](#)
- C_FIND_RSP
 - gdcm::network::DIMSE, [313](#)
- C_GET_RQ
 - gdcm::network::DIMSE, [313](#)
- C_GET_RSP
 - gdcm::network::DIMSE, [313](#)

- C_MOVE_RQ
 - gdcm::network::DIMSE, [313](#)
- C_MOVE_RSP
 - gdcm::network::DIMSE, [313](#)
- C_STORE_RQ
 - gdcm::network::DIMSE, [313](#)
- C_STORE_RSP
 - gdcm::network::DIMSE, [313](#)
- CALIBRATED
 - gdcm::Spacing, [662](#)
- CMYK
 - gdcm::PhotometricInterpretation, [539](#)
- CONDENSED_STYLE
 - gdcm::Printer, [572](#)
- CONSOLE
 - gdcm::terminal, [131](#)
- CORONAL
 - gdcm::Orientation, [514](#)
- CS
 - gdcm::VR, [822](#)
- CSANonImageStorage
 - gdcm::MediaStorage, [485](#)
- CT_private_ELE
 - gdcm::TransferSyntax, [725](#)
- CTImageStorage
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- CEcho
 - gdcm::CompositeNetworkFunctions, [246](#)
- CFind
 - gdcm::CompositeNetworkFunctions, [246](#)
- CM
 - gdcm::SegmentHelper::BasicCodedEntry, [200](#)
- cMaxEventID
 - gdcm::network, [129](#)
- cMaxStateID
 - gdcm::network, [129](#)
- CMove
 - gdcm::CompositeNetworkFunctions, [246](#)
- CSAElement
 - gdcm::CSAElement, [253](#)
- CSAHeader
 - gdcm::CSAHeader, [258](#)
 - gdcm::DataSet, [289](#)
- CSAHeaderDict
 - gdcm::CSAHeaderDict, [261](#)
- CSAHeaderDictEntry
 - gdcm::CSAHeaderDictEntry, [263](#)
- CSAHeaderType
 - gdcm::CSAHeader, [258](#)
- CSComp
 - gdcm, [117](#)
- CSD
 - gdcm::SegmentHelper::BasicCodedEntry, [200](#)
- CSV
 - gdcm::SegmentHelper::BasicCodedEntry, [200](#)
- CStore
 - gdcm::CompositeNetworkFunctions, [247](#)
- CV
 - gdcm::SegmentHelper::BasicCodedEntry, [200](#)
- CanCode
 - gdcm::AudioCodec, [189](#)
 - gdcm::Coder, [236](#)
 - gdcm::ImageCodec, [412](#)
 - gdcm::JPEG2000Codec, [456](#)
 - gdcm::JPEGCodec, [462](#)
 - gdcm::JPEGLSCodec, [466](#)
 - gdcm::KAKADUCodec, [468](#)
 - gdcm::PDFCodec, [533](#)
 - gdcm::PGXCodec, [537](#)
 - gdcm::PNMCodec, [559](#)
 - gdcm::PVRGCodec, [580](#)
 - gdcm::RAWCodec, [594](#)
 - gdcm::RLECodec, [607](#)
- CanDecode
 - gdcm::AudioCodec, [189](#)
 - gdcm::Decoder, [293](#)
 - gdcm::DeltaEncodingCodec, [297](#)
 - gdcm::ImageCodec, [412](#)
 - gdcm::JPEG2000Codec, [456](#)
 - gdcm::JPEGCodec, [462](#)
 - gdcm::JPEGLSCodec, [466](#)
 - gdcm::KAKADUCodec, [468](#)
 - gdcm::PDFCodec, [533](#)
 - gdcm::PGXCodec, [537](#)
 - gdcm::PNMCodec, [559](#)
 - gdcm::PVRGCodec, [580](#)
 - gdcm::RAWCodec, [595](#)
 - gdcm::RLECodec, [607](#)
- CanDisplay
 - gdcm::VR, [823](#)
- CanEmptyTag
 - gdcm::Anonymizer, [151](#)
- CanRead
 - gdcm::Reader, [598](#)
- CanReadFile
 - vtkGDCMImageReader, [832](#)
- CanReadImage
 - gdcm::StreamImageReader, [667](#)
- CanStoreLossy
 - gdcm::TransferSyntax, [725](#)
- CanWriteFile
 - gdcm::StreamImageWriter, [671](#)
- CardiacElectrophysiologyWaveformStorage
 - gdcm::MediaStorage, [485](#)
 - gdcm::UIDs, [741](#)
- CardiacRelevantPatientInformationQuery
 - gdcm::UIDs, [744](#)

- Change
 - gdcm::FileExplicitFilter, [363](#)
 - gdcm::ImageChangePhotometricInterpretation, [402](#)
 - gdcm::ImageChangePlanarConfiguration, [405](#)
 - gdcm::ImageChangeTransferSyntax, [408](#)
- ChangeFMI
 - gdcm::FileExplicitFilter, [364](#)
- ChangeMonochrome
 - gdcm::ImageChangePhotometricInterpretation, [402](#)
- CharacterDataHandler
 - gdcm::TableReader, [706](#)
 - gdcm::XMLDictReader, [887](#)
 - gdcm::XMLPrivateDictReader, [889](#)
- CheckEvent
 - gdcm::AnonymizeEvent, [147](#)
 - gdcm::DataEvent, [282](#)
 - gdcm::DataSetEvent, [291](#)
 - gdcm::Event, [346](#)
 - gdcm::ProgressEvent, [578](#)
- CheckFileMetaInformationOff
 - gdcm::Writer, [884](#)
- CheckFileMetaInformationOn
 - gdcm::Writer, [884](#)
- ChestCADSRStorage
 - gdcm::UIDs, [743](#)
- CipherTypes
 - gdcm::CryptographicMessageSyntax, [251](#)
- Clear
 - gdcm::Bitmap, [206](#)
 - gdcm::ByteValue, [221](#)
 - gdcm::DataElement, [274](#)
 - gdcm::DataSet, [285](#)
 - gdcm::IOD, [439](#)
 - gdcm::IODs, [442](#)
 - gdcm::Item, [448](#)
 - gdcm::LookupTable, [474](#)
 - gdcm::Macro, [477](#)
 - gdcm::Macros, [479](#)
 - gdcm::Module, [498](#)
 - gdcm::Modules, [502](#)
 - gdcm::Preamble, [560](#)
 - gdcm::SequenceOfFragments, [630](#)
 - gdcm::SequenceOfItems, [635](#)
 - gdcm::SerieHelper, [640](#)
 - gdcm::Value, [811](#)
 - vtkGDCMMedicalImageProperties, [841](#)
 - vtkRTStructSetProperties, [878](#)
- ClearSkipTags
 - gdcm::Scanner, [614](#)
- ClearTags
 - gdcm::Scanner, [614](#)
- Clone
 - gdcm::BoxRegion, [215](#)
 - gdcm::Region, [601](#)
- Code
 - gdcm::Coder, [236](#)
 - gdcm::JPEG2000Codec, [457](#)
 - gdcm::JPEGCodec, [462](#)
 - gdcm::JPEGLSCodec, [466](#)
 - gdcm::KAKADUCodec, [468](#)
 - gdcm::PVRGCodec, [580](#)
 - gdcm::RAWCodec, [595](#)
 - gdcm::RLECodec, [607](#)
- CodeString
 - gdcm::CodeString, [238](#)
- Color
 - gdcm::terminal, [131](#)
- ColorSoftcopyPresentationStateStorageSOPClass
 - gdcm::UIDs, [742](#)
- ColorArray
 - gdcm::SurfaceHelper, [690](#)
- Command
 - gdcm::Command, [241](#)
- CommandDataSet
 - gdcm::CommandDataSet, [243](#)
- CommandTypes
 - gdcm::network::DIMSE, [313](#)
- CompOperators
 - gdcm, [118](#)
- Compatible
 - gdcm::VM, [819](#)
 - gdcm::VR, [823](#)
- Component
 - gdcm::PersonName, [535](#)
- ComprehensiveSR
 - gdcm::MediaStorage, [485](#)
- ComprehensiveSRStorage
 - gdcm::UIDs, [742](#)
- ComprehensiveSRStorageTrialRetired
 - gdcm::UIDs, [742](#)
- CompressionTypes
 - vtkGDCMImageWriter, [837](#)
- Compute
 - gdcm::MD5, [481](#)
 - gdcm::SHA1, [647](#)
- ComputeBoundingBox
 - gdcm::BoxRegion, [215](#)
 - gdcm::Region, [602](#)
- ComputeBufferLength
 - gdcm::ImageRegionReader, [427](#)
- ComputeByteLength
 - gdcm::SequenceOfFragments, [630](#)
- ComputeDataElement
 - gdcm::DataSet, [285](#)
- ComputeDataSetMediaStorageSOPClass
 - gdcm::FileMetaInformation, [367](#)
- ComputeDataSetTransferSyntax
 - gdcm::FileMetaInformation, [367](#)

- ComputeDistAlongNormal
 - gdcm::DirectionCosines, [315](#)
- ComputeFile
 - gdcm::MD5, [481](#)
 - gdcm::SHA1, [647](#)
- ComputeFileMD5
 - gdcm::Testing, [717](#)
- ComputeGroupLength
 - gdcm::DataSet, [285](#)
- ComputeInterceptSlopePixelType
 - gdcm::Rescaler, [604](#)
- ComputeLength
 - gdcm::SequenceOfFragments, [630](#)
 - gdcm::SequenceOfItems, [635](#)
- ComputeLossyFlag
 - gdcm::Bitmap, [206](#)
- ComputeMD5
 - gdcm::Testing, [717](#)
- ComputeMOSAICDimensions
 - gdcm::SplitMosaicFilter, [664](#)
- ComputeNumberOfSurfaces
 - gdcm::SurfaceWriter, [696](#)
- ComputeOffsetTable
 - gdcm::JPEGCodec, [462](#)
- ComputePixelAspectRatioFromPixelSpacing
 - gdcm::Spacing, [662](#)
- ComputePixelTypeFromMinMax
 - gdcm::Rescaler, [604](#)
- ComputeSpacingFromImagePositionPatient
 - gdcm::ImageHelper, [419](#)
- ComputeVR
 - gdcm::DataSetHelper, [291](#)
- ComputeZSpacing
 - gdcm::IPPSorter, [446](#)
- ComputedRadiographyImageStorage
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- ConcatenatePDVBlobs
 - gdcm::network::PresentationDataValue, [569](#)
- Conditional
 - gdcm::Usage, [806](#)
- const
 - gdcm::SOPClassUIDToIOD, [657](#)
- const_iterator
 - gdcm::CodeString, [238](#)
 - gdcm::LO, [471](#)
 - gdcm::String, [676](#)
- const_reference
 - gdcm::CodeString, [238](#)
 - gdcm::LO, [471](#)
 - gdcm::String, [676](#)
- const_reverse_iterator
 - gdcm::CodeString, [238](#)
 - gdcm::LO, [471](#)
- gdcm::String, [676](#)
- ConstCharWrapper
 - gdcm::ConstCharWrapper, [248](#)
- ConstIterator
 - gdcm::CSAHeaderDict, [261](#)
 - gdcm::DataSet, [285](#)
 - gdcm::Dict, [302](#)
 - gdcm::Scanner, [613](#)
 - gdcm::SequenceOfFragments, [630](#)
 - gdcm::SequenceOfItems, [635](#)
- Construct
 - gdcm::BaseRootQuery, [197](#)
- ConstructAbortPDU
 - gdcm::network::PDUFactory, [534](#)
- ConstructCEchoRQ
 - gdcm::network::CompositeMessageFactory, [244](#)
- ConstructCFindRQ
 - gdcm::network::CompositeMessageFactory, [244](#)
- ConstructCMoveRQ
 - gdcm::network::CompositeMessageFactory, [244](#)
- ConstructCStoreRQ
 - gdcm::network::CompositeMessageFactory, [244](#)
- ConstructCStoreRSP
 - gdcm::network::CompositeMessageFactory, [244](#)
- ConstructFromString
 - gdcm::TagPath, [715](#)
- ConstructFromTagList
 - gdcm::TagPath, [715](#)
- ConstructPDU
 - gdcm::network::PDUFactory, [534](#)
- ConstructPDV
 - gdcm::network::BaseCompositeMessage, [192](#)
 - gdcm::network::CEchoRQ, [224](#)
 - gdcm::network::CFindRQ, [228](#)
 - gdcm::network::CMoveRQ, [232](#)
 - gdcm::network::CStoreRQ, [265](#)
 - gdcm::network::CStoreRSP, [267](#)
- ConstructPDVByDataSet
 - gdcm::network::CEchoRSP, [225](#)
 - gdcm::network::CFindCancelRQ, [227](#)
 - gdcm::network::CFindRSP, [230](#)
 - gdcm::network::CMoveCancelRq, [231](#)
 - gdcm::network::CMoveRSP, [234](#)
- ConstructQuery
 - gdcm::CompositeNetworkFunctions, [247](#)
- ConstructReleasePDU
 - gdcm::network::PDUFactory, [534](#)
- ConstructorType
 - gdcm::Dicts, [311](#)
- Convert
 - gdcm::DictConverter, [304](#)
 - gdcm::ImageConverter, [416](#)
- ConvertRGBToPaletteColor
 - gdcm::IconImageGenerator, [391](#)

- ConvertToCXX
 - gdcm::DictConverter, [304](#)
- ConvertToXML
 - gdcm::DictConverter, [304](#)
- Create
 - gdcm::Preamble, [561](#)
- CreateCEchoPDU
 - gdcm::network::PDUFactory, [534](#)
- CreateCFindPDU
 - gdcm::network::PDUFactory, [534](#)
- CreateCMovePDU
 - gdcm::network::PDUFactory, [534](#)
- CreateCStoreRQPDU
 - gdcm::network::PDUFactory, [534](#)
- CreateCStoreRSPPDU
 - gdcm::network::PDUFactory, [534](#)
- CreateDefaultUniqueSeriesIdentifier
 - gdcm::SerieHelper, [640](#)
- CreateUniqueSeriesIdentifier
 - gdcm::SerieHelper, [640](#)
- Cross
 - gdcm::DirectionCosines, [315](#)
- CrossDot
 - gdcm::DirectionCosines, [315](#)
- CryptographicMessageSyntax
 - gdcm::CryptographicMessageSyntax, [251](#)
- Curve
 - gdcm::Curve, [269](#)
 - vtkGDCMImageReader, [834](#)
- Curves
 - gdcm::Pixmap, [548](#)
- cyan
 - gdcm::terminal, [131](#)
- DA
 - gdcm::VR, [822](#)
- DATASET_FORMAT
 - gdcm::CSAHeader, [258](#)
- DES3_CIPHER
 - gdcm::CryptographicMessageSyntax, [251](#)
- DES_CIPHER
 - gdcm::CryptographicMessageSyntax, [251](#)
- DETECTOR
 - gdcm::Spacing, [662](#)
- DICOMApplicationContextName
 - gdcm::UIDs, [740](#)
- DICOMControlledTerminology
 - gdcm::UIDs, [740](#)
- DICOMUIDRegistry
 - gdcm::UIDs, [740](#)
- DICT_DEBUG
 - gdcm::DictConverter, [304](#)
- DICT_DEFAULT
 - gdcm::DictConverter, [304](#)
- DICT_XML
 - gdcm::DictConverter, [304](#)
- DS
 - gdcm::VR, [822](#)
- DT
 - gdcm::VR, [823](#)
- DAComp
 - gdcm, [117](#)
- DICOMDIR
 - gdcm::DICOMDIR, [298](#)
- DICOMDIRGenerator
 - gdcm::DICOMDIRGenerator, [300](#)
- DTComp
 - gdcm, [117](#)
- DataElement
 - gdcm::DataElement, [273](#)
- DataElementSet
 - gdcm::DataSet, [285](#)
- DataElementType
 - gdcm::ModuleEntry, [501](#)
- DataEvent
 - gdcm::DataEvent, [282](#)
- DataField
 - gdcm::CSAElement, [255](#)
- DataPtr
 - gdcm::CSAElement, [253](#)
- DataSetEvent
 - gdcm::DataSetEvent, [291](#)
- DataSetHandled
 - gdcm::network::ULConnectionCallback, [792](#)
- DataSetHandles
 - gdcm::network::ULConnectionCallback, [792](#)
- DataSetMS
 - gdcm::FileMetaInformation, [369](#)
- DataSetTS
 - gdcm::FileMetaInformation, [369](#)
- DataWasPassed
 - vtkImageMapToColors16, [865](#)
- DebugOff
 - gdcm::Trace, [721](#)
- DebugOn
 - gdcm::Trace, [721](#)
- Decode
 - gdcm::AudioCodec, [189](#)
 - gdcm::Base64, [190](#)
 - gdcm::Curve, [269](#)
 - gdcm::Decoder, [293](#)
 - gdcm::DeltaEncodingCodec, [297](#)
 - gdcm::ImageCodec, [412](#)
 - gdcm::JPEG2000Codec, [457](#)
 - gdcm::JPEGCodec, [462](#)
 - gdcm::JPEGLSCodec, [466](#)
 - gdcm::KAKADUCodec, [469](#)
 - gdcm::LookupTable, [474](#)

- gdcmm::Overlay, 518
- gdcmm::PDFCodec, 533
- gdcmm::PVRGCodec, 580
- gdcmm::RAWCodec, 595
- gdcmm::RLECodec, 608
- DecodeByStreams
 - gdcmm::Decoder, 293
 - gdcmm::ImageCodec, 412
 - gdcmm::JPEG12Codec, 452
 - gdcmm::JPEG16Codec, 454
 - gdcmm::JPEG2000Codec, 457
 - gdcmm::JPEG8Codec, 459
 - gdcmm::JPEGCodec, 462
 - gdcmm::RAWCodec, 595
 - gdcmm::RLECodec, 608
- DecodeBytes
 - gdcmm::RAWCodec, 595
- DecodeExtent
 - gdcmm::JPEG2000Codec, 457
 - gdcmm::JPEGCodec, 462
 - gdcmm::JPEGLSCodec, 466
 - gdcmm::RLECodec, 608
- Decompress
 - gdcmm::Overlay, 518
- Decrypt
 - gdcmm::CryptographicMessageSyntax, 251
- DeepCopy
 - vtkRTStructSetProperties, 878
- Default
 - gdcmm::FileMetaInformation, 367
- DefinePixelExtent
 - gdcmm::StreamImageReader, 667
 - gdcmm::StreamImageWriter, 672
- DefineProperBufferLength
 - gdcmm::StreamImageReader, 668
 - gdcmm::StreamImageWriter, 672
- DefinedTerms
 - gdcmm::DefinedTerms, 294
- DeflatedExplicitVRLittleEndian
 - gdcmm::TransferSyntax, 724
 - gdcmm::UIDs, 738
- DeformableSpatialRegistrationStorage
 - gdcmm::UIDs, 742
- Defs
 - gdcmm::Defs, 295
- DeleteDirectory
 - gdcmm::System, 700
- DeltaEncodingCodec
 - gdcmm::DeltaEncodingCodec, 297
- Derive
 - gdcmm::FileDerivation, 361
- Description
 - gdcmm::ModuleEntry, 500
- DescriptionField
 - gdcmm::ModuleEntry, 501
- DetachedInterpretationManagementSOPClassRetired
 - gdcmm::UIDs, 740
- DetachedPatientManagementMetaSOPClassRetired
 - gdcmm::UIDs, 740
- DetachedPatientManagementSOPClass
 - gdcmm::MediaStorage, 485
- DetachedPatientManagementSOPClassRetired
 - gdcmm::UIDs, 740
- DetachedResultsManagementMetaSOPClassRetired
 - gdcmm::UIDs, 740
- DetachedResultsManagementSOPClassRetired
 - gdcmm::UIDs, 740
- DetachedStudyManagementMetaSOPClassRetired
 - gdcmm::UIDs, 740
- DetachedStudyManagementSOPClass
 - gdcmm::MediaStorage, 485
- DetachedStudyManagementSOPClassRetired
 - gdcmm::UIDs, 740
- DetachedVisitManagementSOPClass
 - gdcmm::MediaStorage, 485
- DetachedVisitManagementSOPClassRetired
 - gdcmm::UIDs, 740
- DetailSRStorageTrialRetired
 - gdcmm::UIDs, 742
- DetermineEventByPDU
 - gdcmm::network::PDUFactory, 534
- dicomAETitle
 - gdcmm::UIDs, 744
- dicomApplicationCluster
 - gdcmm::UIDs, 744
- dicomAssociationAcceptor
 - gdcmm::UIDs, 744
- dicomAssociationInitiator
 - gdcmm::UIDs, 744
- dicomAuthorizedNodeCertificateReference
 - gdcmm::UIDs, 744
- dicomConfigurationRoot
 - gdcmm::UIDs, 744
- dicomDescription
 - gdcmm::UIDs, 744
- dicomDevice
 - gdcmm::UIDs, 744
- dicomDeviceName
 - gdcmm::UIDs, 744
- dicomDeviceSerialNumber
 - gdcmm::UIDs, 744
- dicomDevicesRoot
 - gdcmm::UIDs, 744
- dicomHostname
 - gdcmm::UIDs, 744
- dicomInstalled
 - gdcmm::UIDs, 744
- dicomInstitutionAddress

- gdcm::UIDs, [744](#)
- dicomInstitutionDepartmentName
 - gdcm::UIDs, [744](#)
- dicomInstitutionName
 - gdcm::UIDs, [744](#)
- dicomIssuerOfPatientID
 - gdcm::UIDs, [744](#)
- dicomManufacturer
 - gdcm::UIDs, [744](#)
- dicomManufacturerModelName
 - gdcm::UIDs, [744](#)
- dicomNetworkAE
 - gdcm::UIDs, [744](#)
- dicomNetworkConnection
 - gdcm::UIDs, [745](#)
- dicomNetworkConnectionReference
 - gdcm::UIDs, [744](#)
- dicomPort
 - gdcm::UIDs, [744](#)
- dicomPreferredCalledAETitle
 - gdcm::UIDs, [744](#)
- dicomPreferredCallingAETitle
 - gdcm::UIDs, [744](#)
- dicomPrimaryDeviceType
 - gdcm::UIDs, [744](#)
- dicomRelatedDeviceReference
 - gdcm::UIDs, [744](#)
- dicomSOPClass
 - gdcm::UIDs, [744](#)
- dicomSoftwareVersion
 - gdcm::UIDs, [744](#)
- dicomStationName
 - gdcm::UIDs, [744](#)
- dicomSupportedCharacterSet
 - gdcm::UIDs, [744](#)
- dicomTLSCyphersuite
 - gdcm::UIDs, [744](#)
- dicomThisNodeCertificateReference
 - gdcm::UIDs, [744](#)
- dicomTransferCapability
 - gdcm::UIDs, [745](#)
- dicomTransferRole
 - gdcm::UIDs, [744](#)
- dicomTransferSyntax
 - gdcm::UIDs, [744](#)
- dicomUniqueAETitle
 - gdcm::UIDs, [745](#)
- dicomUniqueAETitlesRegistryRoot
 - gdcm::UIDs, [744](#)
- dicomVendorData
 - gdcm::UIDs, [744](#)
- Dict
 - gdcm::Dict, [302](#)
- DictConverter
 - gdcm::DictConverter, [304](#)
- DictEntry
 - gdcm::DictEntry, [306](#)
- DictPrinter
 - gdcm::DictPrinter, [309](#)
- Dicts
 - gdcm::CSAHeaderDict, [261](#)
 - gdcm::Dict, [303](#)
 - gdcm::Dicts, [311](#)
 - gdcm::PrivateDict, [574](#)
- difference_type
 - gdcm::CodeString, [238](#)
 - gdcm::LO, [471](#)
 - gdcm::String, [676](#)
- DigitalIntraoralXRayImageStorageForPresentation
 - gdcm::UIDs, [741](#)
- DigitalIntraoralXRayImageStorageForProcessing
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- DigitalIntraoralXrayImageStorageForPresentation
 - gdcm::MediaStorage, [484](#)
- DigitalMammographyImageStorageForPresentation
 - gdcm::MediaStorage, [484](#)
- DigitalMammographyImageStorageForProcessing
 - gdcm::MediaStorage, [484](#)
- DigitalMammographyXRayImageStorageForPresentation
 - gdcm::UIDs, [741](#)
- DigitalMammographyXRayImageStorageForProcessing
 - gdcm::UIDs, [741](#)
- DigitalXRayImageStorageForPresentation
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- DigitalXRayImageStorageForProcessing
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- dim
 - gdcm::terminal, [131](#)
- Dimensions
 - gdcm::Bitmap, [210](#)
 - gdcm::ImageCodec, [414](#)
- DirCosTolerance
 - gdcm::IPPSorter, [446](#)
- DirectionCosines
 - gdcm::DirectionCosines, [315](#)
 - vtkGDCMImageReader, [834](#)
- Directory
 - gdcm::Directory, [317](#)
- DoByteSwap
 - gdcm::ImageCodec, [413](#)
- DolconImage
 - gdcm::PixmapWriter, [556](#)
- DolInvertMonochrome
 - gdcm::ImageCodec, [413](#)
- DoOverlayCleanup

- gdcmm::ImageCodec, 413
- DoPaddedCompositePixelCode
 - gdcmm::ImageCodec, 413
- DoPlanarConfiguration
 - gdcmm::ImageCodec, 413
- DoSimpleCopy
 - gdcmm::ImageCodec, 413
- DoYBR
 - gdcmm::ImageCodec, 413
- Dot
 - gdcmm::DirectionCosines, 315
- DropDuplicatePositions
 - gdcmm::IPPSorter, 446
- Dumper
 - gdcmm::Dumper, 322
- DuplicateAttributeError
 - gdcmm::Parser, 524
- eAABORTPDURceivedOpen
 - gdcmm::network, 128
- eAABORTRequest
 - gdcmm::network, 128
- eAASSOCIATE_RQPDURceived
 - gdcmm::network, 128
- eAASSOCIATERequestLocalUser
 - gdcmm::network, 128
- eAASSOCIATEResponseAccept
 - gdcmm::network, 128
- eAASSOCIATEResponseReject
 - gdcmm::network, 128
- eARELEASE_RPPDURceived
 - gdcmm::network, 128
- eARELEASE_RQPDURceivedOpen
 - gdcmm::network, 128
- eARELEASERequest
 - gdcmm::network, 128
- eARELEASEResponse
 - gdcmm::network, 128
- eARTIMTimerExpired
 - gdcmm::network, 129
- eASSOCIATE_ACPDURceived
 - gdcmm::network, 128
- eASSOCIATE_RJPDURceived
 - gdcmm::network, 128
- eArabic
 - gdcmm, 118
- eCyrillic
 - gdcmm, 118
- EDGE
 - gdcmm::MeshPrimitive, 494
- eEventDoesNotExist
 - gdcmm::network, 129
- eFind
 - gdcmm, 119
- eGB18030
 - gdcmm, 119
- eGreek
 - gdcmm, 118
- eHebrew
 - gdcmm, 118
- eImage
 - gdcmm, 119
- eJapanese
 - gdcmm, 119
- eJapaneseKanjiMultibyte
 - gdcmm, 119
- eJapaneseSupplementaryKanjiMultibyte
 - gdcmm, 119
- eKoreanHangulHanjaMultibyte
 - gdcmm, 119
- eLatin1
 - gdcmm, 118
- eLatin2
 - gdcmm, 118
- eLatin3
 - gdcmm, 118
- eLatin4
 - gdcmm, 118
- eLatin5
 - gdcmm, 119
- eMove
 - gdcmm, 119
- ePDATATFPDU
 - gdcmm::network, 128
- ePDATArequest
 - gdcmm::network, 128
- ePatient
 - gdcmm, 119
- ePatientRootType
 - gdcmm, 119
- eSeries
 - gdcmm, 119
- eSta10ReleaseCollisionAc
 - gdcmm::network, 129
- eSta11ReleaseCollisionRq
 - gdcmm::network, 129
- eSta12ReleaseCollisionAcLocal
 - gdcmm::network, 129
- eSta13AwaitingClose
 - gdcmm::network, 129
- eSta1Idle
 - gdcmm::network, 129
- eSta2Open
 - gdcmm::network, 129
- eSta3WaitLocalAssoc
 - gdcmm::network, 129
- eSta4LocalAssocDone
 - gdcmm::network, 129

- eSta5WaitRemoteAssoc
 - gdcm::network, [129](#)
- eSta6TransferReady
 - gdcm::network, [129](#)
- eSta7WaitRelease
 - gdcm::network, [129](#)
- eSta8WaitLocalRelease
 - gdcm::network, [129](#)
- eSta9ReleaseCollisionRqLocal
 - gdcm::network, [129](#)
- eStaDoesNotExist
 - gdcm::network, [129](#)
- eStudy
 - gdcm, [119](#)
- eStudyRootType
 - gdcm, [119](#)
- eThai
 - gdcm, [119](#)
- eTransportConnConfirmLocal
 - gdcm::network, [128](#)
- eTransportConnIndicLocal
 - gdcm::network, [128](#)
- eTransportConnectionClosed
 - gdcm::network, [128](#)
- eUTF8
 - gdcm, [119](#)
- eUnrecognizedPDURceived
 - gdcm::network, [129](#)
- ECharSet
 - gdcm, [118](#)
- EEventID
 - gdcm::network, [128](#)
- EQueryLevel
 - gdcm, [119](#)
- EQueryType
 - gdcm, [119](#)
- ERootType
 - gdcm, [119](#)
- EStateID
 - gdcm::network, [129](#)
- elem
 - gdcm::SerieHelper::Rule, [610](#)
- Element
 - gdcm::Element< TVR, VM::VM1_n >, [328](#)
- Empty
 - gdcm::Anonymizer, [151](#)
 - gdcm::BoxRegion, [215](#)
 - gdcm::DataElement, [274](#)
 - gdcm::FileAnonymizer, [359](#)
 - gdcm::Region, [602](#)
- EncapsulatedCDASStorage
 - gdcm::MediaStorage, [485](#)
 - gdcm::UIDs, [743](#)
- EncapsulatedPDFStorage
 - gdcm::MediaStorage, [485](#)
 - gdcm::UIDs, [743](#)
- EncapsulatedDocument
 - gdcm::EncapsulatedDocument, [340](#)
- Encode
 - gdcm::Base64, [190](#)
- EncodeBytes
 - gdcm::System, [700](#)
- Encrypt
 - gdcm::CryptographicMessageSyntax, [251](#)
- End
 - gdcm::CSAHeaderDict, [261](#)
 - gdcm::DataSet, [286](#)
 - gdcm::Dict, [302](#)
 - gdcm::IODs, [442](#)
 - gdcm::Scanner, [614](#)
 - gdcm::SequenceOfFragments, [630](#)
 - gdcm::SequenceOfItems, [635](#)
- EndElement
 - gdcm::TableReader, [706](#)
 - gdcm::XMLDictReader, [887](#)
 - gdcm::XMLPrivateDictReader, [889](#)
- EndElementHandler
 - gdcm::Parser, [524](#)
- EndFilter
 - gdcm::SimpleSubjectWatcher, [651](#)
- EndWith
 - gdcm::Filename, [371](#)
- EnhancedCTImageStorage
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- EnhancedMRImageStorage
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- EnhancedSR
 - gdcm::MediaStorage, [485](#)
- EnhancedSRStorage
 - gdcm::UIDs, [742](#)
- EnhancedUSVolumeStorage
 - gdcm::MediaStorage, [486](#)
 - gdcm::UIDs, [745](#)
- EnhancedXAImageStorage
 - gdcm::MediaStorage, [486](#)
 - gdcm::UIDs, [742](#)
- EnhancedXRImageStorage
 - gdcm::UIDs, [742](#)
- EnumeratedValues
 - gdcm::EnumeratedValues, [345](#)
- ErrorOff
 - gdcm::Trace, [721](#)
- ErrorOn
 - gdcm::Trace, [721](#)
- ErrorType
 - gdcm::Parser, [524](#)

- EstablishConnection
 - gdcm::network::ULConnectionManager, [796](#)
- EstablishConnectionMove
 - gdcm::network::ULConnectionManager, [796](#)
- Event
 - gdcm::Event, [346](#)
- Exception
 - gdcm::Exception, [348](#)
- Execute
 - gdcm::Command, [241](#)
 - gdcm::MemberCommand, [491](#)
 - gdcm::SimpleMemberCommand, [650](#)
- ExecuteData
 - vtkGDCMImageReader, [832](#)
 - vtkGDCMThreadedImageReader, [852](#)
- ExecuteInformation
 - vtkGDCMImageReader, [832](#)
 - vtkGDCMThreadedImageReader, [852](#)
- ExecuteQuery
 - gdcm::StringFilter, [678](#), [679](#)
- Explicit
 - gdcm::TransferSyntax, [724](#)
- ExplicitVRBigEndian
 - gdcm::TransferSyntax, [724](#)
 - gdcm::UIDs, [738](#)
- ExplicitVRLittleEndian
 - gdcm::TransferSyntax, [724](#)
 - gdcm::UIDs, [738](#)
- Explore
 - gdcm::Directory, [317](#)
- Extract
 - gdcm::IconImageFilter, [389](#)
- ExtractIconImages
 - gdcm::IconImageFilter, [389](#)
- ExtractVeprolIconImages
 - gdcm::IconImageFilter, [389](#)
- F
 - gdcm::Printer, [573](#)
 - gdcm::Reader, [600](#)
 - gdcm::Validate, [810](#)
- FACET
 - gdcm::MeshPrimitive, [494](#)
- FD
 - gdcm::VR, [823](#)
- FL
 - gdcm::VR, [823](#)
- FLOAT16
 - gdcm::PixelFormat, [542](#)
- FLOAT32
 - gdcm::PixelFormat, [542](#)
- FLOAT64
 - gdcm::PixelFormat, [542](#)
- Fiducials
 - gdcm::Fiducials, [354](#)
- File
 - gdcm::File, [356](#)
- FileAnonymizer
 - gdcm::FileAnonymizer, [359](#)
- FileDerivation
 - gdcm::FileDerivation, [361](#)
- FileExists
 - gdcm::System, [700](#)
- FileExplicitFilter
 - gdcm::FileExplicitFilter, [363](#)
- FilesDirectory
 - gdcm::System, [701](#)
- FilesSymlink
 - gdcm::System, [701](#)
- FileList
 - gdcm, [117](#)
- FileMetaInformation
 - gdcm::FileMetaInformation, [367](#)
- FileName
 - vtkGDCMPolyDataReader, [844](#)
- FileNameOrdering
 - gdcm::SerieHelper, [640](#)
- FileNames
 - vtkGDCMImageReader, [834](#)
- FileSet
 - gdcm::FileSet, [375](#)
- FileSize
 - gdcm::System, [701](#)
- FileTime
 - gdcm::System, [701](#)
- FileType
 - gdcm::FileSet, [375](#)
- FileWithName
 - gdcm::FileWithName, [377](#)
- Filename
 - gdcm::Filename, [371](#)
- filename
 - gdcm::FileWithName, [377](#)
- FilenameGenerator
 - gdcm::FilenameGenerator, [373](#)
- FilenameType
 - gdcm::DICOMDIRGenerator, [300](#)
 - gdcm::Directory, [317](#)
 - gdcm::FilenameGenerator, [373](#)
- Filenames
 - gdcm::Sorter, [661](#)
- FilenamesType
 - gdcm::DICOMDIRGenerator, [300](#)
 - gdcm::Directory, [317](#)
 - gdcm::FilenameGenerator, [373](#)
- FileType
 - gdcm::FileSet, [375](#)
- Fill

- gdcm::ByteValue, 221
- FillFromDataSet
 - gdcm::FileMetaInformation, 367
- FillMedicalImageInformation
 - vtkGDCMImageReader, 832
 - vtkGDCMPolyDataReader, 843
- FindCSAElementByName
 - gdcm::CSAHeader, 258
- FindContext
 - gdcm::network::ULConnection, 790
- FindDataElement
 - gdcm::DataSet, 286
 - gdcm::Item, 448
 - gdcm::SequenceOfItems, 636
- FindDictEntry
 - gdcm::PrivateDict, 574
- FindMacroEntry
 - gdcm::Macro, 477
- FindModuleEntryInMacros
 - gdcm::Module, 498
- FindNextDataElement
 - gdcm::DataSet, 286
- FindPDBelementByName
 - gdcm::PDBHeader, 531
- FindPatientRootQuery
 - gdcm::FindPatientRootQuery, 378
- FindStudyRootQuery
 - gdcm::FindStudyRootQuery, 381
- FirstRender
 - vtkImageColorViewer, 862
- ForceRescale
 - vtkGDCMImageReader, 834
- FormatDateTime
 - gdcm::System, 701
- Fragment
 - gdcm::Fragment, 383
- FragmentVector
 - gdcm::SequenceOfFragments, 630
- FromString
 - gdcm::StringFilter, 679
- FujiPrivateCRImageStorage
 - gdcm::MediaStorage, 486
- GDCM_DIFFERENT
 - gdcm, 118
- GDCM_EQUAL
 - gdcm, 118
- GDCM_GREATER
 - gdcm, 118
- GDCM_GREATEROREQUAL
 - gdcm, 118
- GDCM_LESS
 - gdcm, 118
- GDCM_LESSOREQUAL
 - gdcm, 118
- GEMS
 - gdcm::Dicts, 311
- GEPrivate3DModelStorage
 - gdcm::MediaStorage, 485
- GRAY
 - gdcm::LookupTable, 474
- GREEN
 - gdcm::LookupTable, 474
- GDCM_DO_JOIN
 - gdcmStaticAssert.h, 1108
- GDCM_DO_JOIN2
 - gdcmStaticAssert.h, 1108
- GDCM_EXPORT
 - gdcmWin32.h, 1168
- GDCM_FUNCTION
 - gdcmTrace.h, 1131
- GDCM_JOIN
 - gdcmStaticAssert.h, 1108
- GDCM_LEGACY
 - gdcmLegacyMacro.h, 1017
- GDCM_LEGACY_BODY
 - gdcmLegacyMacro.h, 1017
- GDCM_STATIC_ASSERT
 - gdcm::Attribute, 165
 - gdcmStaticAssert.h, 1108
- GDCMMACROENTRY_H
 - gdcmMacroEntry.h, 1023
- gdcm, 103
 - AEComp, 117
 - ASComp, 117
 - backslash, 119
 - CSComp, 117
 - CompOperators, 118
 - DAComp, 117
 - DTComp, 117
 - eArabic, 118
 - eCyrillic, 118
 - eFind, 119
 - eGB18030, 119
 - eGreek, 118
 - eHebrew, 118
 - eImage, 119
 - eJapanese, 119
 - eJapaneseKanjiMultibyte, 119
 - eJapaneseSupplementaryKanjiMultibyte, 119
 - eKoreanHangulHanjaMultibyte, 119
 - eLatin1, 118
 - eLatin2, 118
 - eLatin3, 118
 - eLatin4, 118
 - eLatin5, 119
 - eMove, 119
 - ePatient, 119

- ePatientRootType, 119
- eSeries, 119
- eStudy, 119
- eStudyRootType, 119
- eThai, 119
- eUTF8, 119
- ECharSet, 118
- EQueryLevel, 119
- EQueryType, 119
- ERootType, 119
- FileList, 117
- GDCM_DIFFERENT, 118
- GDCM_EQUAL, 118
- GDCM_GREATER, 118
- GDCM_GREATEROREQUAL, 118
- GDCM_LESS, 118
- GDCM_LESOREQUAL, 118
- GetVRFromTag, 119
- GlobalInstance, 124
- IconImage, 117
- LD_ALL, 119
- LD_NOSEQ, 119
- LD_NOSHADOW, 119
- LD_NOSHADOWSEQ, 119
- LOComp, 118
- LTComp, 118
- LodModeType, 119
- MacroEntry, 118
- NestedMacroEntries, 118
- operator<<, 120–123
- operator>>, 124
- operator==, 123
- PNComp, 118
- SHComp, 118
- STComp, 118
- TMComp, 118
- TYPETOENCODING, 124
- to_string, 124
- UIComp, 118
- UTComp, 118
- VRBINARY, 124
- gdcm2pnm.man, 891
- gdcm2vtk.man, 891
- gdcm::Attribute
 - VMType, 165
- gdcm::Attribute< Group, Element, TVR, VM::VM1 >
 - VMType, 171
- gdcm::CSAHeader
 - DATASET_FORMAT, 258
 - INTERFILE, 258
 - NOMAGIC, 258
 - SV10, 258
 - UNKNOWN, 258
 - ZEROED_OUT, 258
- gdcm::CryptographicMessageSyntax
 - AES128_CIPHER, 251
 - AES192_CIPHER, 251
 - AES256_CIPHER, 251
 - DES3_CIPHER, 251
 - DES_CIPHER, 251
- gdcm::DictConverter
 - DICT_DEBUG, 304
 - DICT_DEFAULT, 304
 - DICT_XML, 304
- gdcm::Dicts
 - GEMS, 311
 - PHILIPS, 311
 - SIEMENS, 311
- gdcm::LookupTable
 - BLUE, 474
 - GRAY, 474
 - GREEN, 474
 - RED, 474
 - UNKNOWN, 474
- gdcm::MediaStorage
 - AmbulatoryECGWaveformStorage, 485
 - Audio, 486
 - BasicTextSR, 485
 - BasicVoiceAudioWaveformStorage, 485
 - BreastTomosynthesisImageStorage, 486
 - CSANonImageStorage, 485
 - CTImageStorage, 484
 - CardiacElectrophysiologyWaveformStorage, 485
 - ComprehensiveSR, 485
 - ComputedRadiographyImageStorage, 484
 - DetachedPatientManagementSOPClass, 485
 - DetachedStudyManagementSOPClass, 485
 - DetachedVisitManagementSOPClass, 485
 - DigitalIntraoralXRayImageStorageForProcessing, 484
 - DigitalIntraoralXrayImageStorageForPresentation, 484
 - DigitalMammographyImageStorageForPresentation, 484
 - DigitalMammographyImageStorageForProcessing, 484
 - DigitalXRayImageStorageForPresentation, 484
 - DigitalXRayImageStorageForProcessing, 484
 - EncapsulatedCDASStorage, 485
 - EncapsulatedPDFStorage, 485
 - EnhancedCTImageStorage, 484
 - EnhancedMRIImageStorage, 484
 - EnhancedSR, 485
 - EnhancedUSVolumeStorage, 486
 - EnhancedXAImageStorage, 486
 - FujiPrivateCRLImageStorage, 486
 - GEPrivate3DModelStorage, 485
 - GeneralECGWaveformStorage, 485

- GeneralElectricMagneticResonanceImageStorage, 485
- GrayscaleSoftcopyPresentationStateStorageSOP-Class, 485
- HangingProtocolStorage, 486
- HardcopyGrayscaleImageStorage, 485
- HemodynamicWaveformStorage, 485
- KeyObjectSelectionDocument, 485
- LeadECGWaveformStorage, 485
- MRImageStorage, 484
- MRSpectroscopyStorage, 484
- MS_END, 486
- MammographyCADSR, 485
- MediaStorageDirectoryStorage, 484
- ModalityPerformedProcedureStepSOPClass, 486
- MultiframeGrayscaleByteSecondaryCaptureImageStorage, 484
- MultiframeGrayscaleWordSecondaryCaptureImageStorage, 484
- MultiframeSingleBitSecondaryCaptureImageStorage, 484
- MultiframeTrueColorSecondaryCaptureImageStorage, 485
- NoObject, 486
- NuclearMedicineImageStorage, 485
- NuclearMedicineImageStorageRetired, 484
- ObjectEnd, 486
- OphthalmicPhotography8BitImageStorage, 486
- OphthalmicTomographyImageStorage, 486
- PDF, 486
- PETImageStorage, 485
- Philips3D, 485
- PhilipsPrivateMRSyntheticImageStorage, 486
- RTDoseStorage, 485
- RTImageStorage, 485
- RTIonBeamsTreatmentRecordStorage, 486
- RTIonPlanStorage, 486
- RTPlanStorage, 485
- RTStructureSetStorage, 485
- RTTreatmentSummaryRecordStorage, 486
- RawDataStorage, 485
- SecondaryCaptureImageStorage, 484
- Segmentation, 486
- SegmentationStorage, 486
- SpacialFiducialsStorage, 485
- SpacialRegistrationStorage, 485
- StandaloneCurveStorage, 485
- StandaloneModalityLUTStorage, 485
- StandaloneOverlayStorage, 485
- StandaloneVOILUTStorage, 485
- StudyComponentManagementSOPClass, 485
- SurfaceSegmentationStorage, 486
- ToshibaPrivateDataStorage, 485
- URI, 486
- UltrasoundImageStorage, 484
- UltrasoundImageStorageRetired, 484
- UltrasoundMultiFrameImageStorage, 484
- UltrasoundMultiFrameImageStorageRetired, 484
- VLEndoscopicImageStorage, 486
- VLPhotographicImageStorage, 486
- VLWholeSlideMicroscopyImageStorage, 486
- Video, 486
- VideoEndoscopicImageStorage, 485
- Waveform, 486
- XRay3DAngiographicImageStorage, 486
- XRayAngiographicBiPlaneImageStorageRetired, 485
- XRayAngiographicImageStorage, 485
- XRayRadiationDoseSR, 486
- XRayRadiofluoroscopicImageStorage, 485
- gdcmmesh::MeshPrimitive
 - EDGE, 494
 - FACET, 494
 - LINE, 494
 - MPTYPE_END, 494
 - TRIANGLE, 494
 - TRIANGLE_FAN, 494
 - TRIANGLE_STRIP, 494
 - VERTEX, 494
- gdcmmath::Orientation
 - AXIAL, 514
 - CORONAL, 514
 - OBLIQUE, 514
 - SAGITTAL, 514
 - UNKNOWN, 514
- gdcmmath::Overlay
 - Graphics, 517
 - Invalid, 517
 - ROI, 517
- gdcmmath::Parser
 - DuplicateAttributeError, 524
 - JunkAfterDocElementError, 524
 - NoElementsError, 524
 - NoError, 524
 - NoMemoryError, 524
 - SyntaxError, 524
 - TagMismatchError, 524
 - UndefinedEntityError, 524
 - UnexpectedStateError, 524
- gdcmmath::PhotometricInterpretation
 - ARGB, 539
 - CMYK, 539
 - HSV, 539
 - MONOCHROME1, 539
 - MONOCHROME2, 539
 - PALETTE_COLOR, 539
 - PI_END, 539
 - RGB, 539
 - UNKNOWN, 539

- YBR_FULL, 539
- YBR_FULL_422, 539
- YBR_ICT, 539
- YBR_PARTIAL_420, 539
- YBR_PARTIAL_422, 539
- YBR_RCT, 539
- gdcmm::PixelFormat
 - FLOAT16, 542
 - FLOAT32, 542
 - FLOAT64, 542
 - INT12, 542
 - INT16, 542
 - INT32, 542
 - INT8, 542
 - SINGLEBIT, 542
 - UINT12, 542
 - UINT16, 542
 - UINT32, 542
 - UINT8, 542
 - UNKNOWN, 542
- gdcmm::Printer
 - CONDENSED_STYLE, 572
 - VERBOSE_STYLE, 572
 - XML, 572
- gdcmm::STATIC_ASSERTION_FAILURE< true >
 - value, 666
- gdcmm::Segment
 - ALGOType_END, 619
 - AUTOMATIC, 619
 - MANUAL, 619
- gdcmm::Spacing
 - CALIBRATED, 662
 - DETECTOR, 662
 - MAGNIFIED, 662
 - UNKNOWN, 662
- gdcmm::Surface
 - NO, 686
 - POINTS, 686
 - STATES_END, 686
 - SURFACE, 686
 - UNKNOWN, 686
 - VIEWType_END, 686
 - WIREFRAME, 686
 - YES, 686
- gdcmm::SwapCode
 - BadBigEndian, 697
 - BadLittleEndian, 697
 - BigEndian, 697
 - LittleEndian, 697
 - Unknown, 697
- gdcmm::TransferSyntax
 - CT_private_ELE, 725
 - DeflatedExplicitVRLittleEndian, 724
 - Explicit, 724
 - ExplicitVRBigEndian, 724
 - ExplicitVRLittleEndian, 724
 - Implicit, 724
 - ImplicitVRBigEndianACRNEMA, 725
 - ImplicitVRBigEndianPrivateGE, 724
 - ImplicitVRLittleEndian, 724
 - JPEG2000, 725
 - JPEG2000Lossless, 725
 - JPEG2000Part2, 725
 - JPEG2000Part2Lossless, 725
 - JPEGBaselineProcess1, 725
 - JPEGExtendedProcess2_4, 725
 - JPEGExtendedProcess3_5, 725
 - JPEGFullProgressionProcess10_12, 725
 - JPEGLSLossless, 725
 - JPEGLSNearLossless, 725
 - JPEGLosslessProcess14, 725
 - JPEGLosslessProcess14_1, 725
 - JPEGSpectralSelectionProcess6_8, 725
 - JPIPRendered, 725
 - MPEG2MainProfile, 725
 - RLELossless, 725
 - TS_END, 725
 - Unknown, 724
- gdcmm::Type
 - T1, 730
 - T1C, 730
 - T2, 730
 - T2C, 730
 - T3, 730
 - UNKNOWN, 730
- gdcmm::UIDs
 - AmbulatoryECGWaveformStorage, 741
 - AudioSRStorageTrialRetired, 742
 - BasicAnnotationBoxSOPClass, 740
 - BasicColorImageBoxSOPClass, 740
 - BasicColorPrintManagementMetaSOPClass, 740
 - BasicFilmBoxSOPClass, 740
 - BasicFilmSessionSOPClass, 740
 - BasicGrayscaleImageBoxSOPClass, 740
 - BasicGrayscalePrintManagementMetaSOPClass, 740
 - BasicPrintImageOverlayBoxSOPClassRetired, 741
 - BasicStudyContentNotificationSOPClassRetired, 740
 - BasicTextSRStorage, 742
 - BasicVoiceAudioWaveformStorage, 741
 - BlendingSoftcopyPresentationStateStorageSOPClass, 742
 - BreastImagingRelevantPatientInformationQuery, 743
 - BreastTomosynthesisImageStorage, 745
 - CTImageStorage, 741
 - CardiacElectrophysiologyWaveformStorage, 741
 - CardiacRelevantPatientInformationQuery, 744

- ChestCADSRStorage, [743](#)
- ColorSoftcopyPresentationStateStorageSOPClass, [742](#)
- ComprehensiveSRStorage, [742](#)
- ComprehensiveSRStorageTrialRetired, [742](#)
- ComputedRadiographyImageStorage, [741](#)
- DICOMApplicationContextName, [740](#)
- DICOMControlledTerminology, [740](#)
- DICOMUIDRegistry, [740](#)
- DeflatedExplicitVRLittleEndian, [738](#)
- DeformableSpatialRegistrationStorage, [742](#)
- DetachedInterpretationManagementSOPClass-Retired, [740](#)
- DetachedPatientManagementMetaSOPClass-Retired, [740](#)
- DetachedPatientManagementSOPClassRetired, [740](#)
- DetachedResultsManagementMetaSOPClass-Retired, [740](#)
- DetachedResultsManagementSOPClassRetired, [740](#)
- DetachedStudyManagementMetaSOPClassRetired, [740](#)
- DetachedStudyManagementSOPClassRetired, [740](#)
- DetachedVisitManagementSOPClassRetired, [740](#)
- DetailSRStorageTrialRetired, [742](#)
- dicomAETitle, [744](#)
- dicomApplicationCluster, [744](#)
- dicomAssociationAcceptor, [744](#)
- dicomAssociationInitiator, [744](#)
- dicomAuthorizedNodeCertificateReference, [744](#)
- dicomConfigurationRoot, [744](#)
- dicomDescription, [744](#)
- dicomDevice, [744](#)
- dicomDeviceName, [744](#)
- dicomDeviceSerialNumber, [744](#)
- dicomDevicesRoot, [744](#)
- dicomHostname, [744](#)
- dicomInstalled, [744](#)
- dicomInstitutionAddress, [744](#)
- dicomInstitutionDepartmentName, [744](#)
- dicomInstitutionName, [744](#)
- dicomIssuerOfPatientID, [744](#)
- dicomManufacturer, [744](#)
- dicomManufacturerModelName, [744](#)
- dicomNetworkAE, [744](#)
- dicomNetworkConnection, [745](#)
- dicomNetworkConnectionReference, [744](#)
- dicomPort, [744](#)
- dicomPreferredCalledAETitle, [744](#)
- dicomPreferredCallingAETitle, [744](#)
- dicomPrimaryDeviceType, [744](#)
- dicomRelatedDeviceReference, [744](#)
- dicomSOPClass, [744](#)
- dicomSoftwareVersion, [744](#)
- dicomStationName, [744](#)
- dicomSupportedCharacterSet, [744](#)
- dicomTLSCyphersuite, [744](#)
- dicomThisNodeCertificateReference, [744](#)
- dicomTransferCapability, [745](#)
- dicomTransferRole, [744](#)
- dicomTransferSyntax, [744](#)
- dicomUniqueAETitle, [745](#)
- dicomUniqueAETitlesRegistryRoot, [744](#)
- dicomVendorData, [744](#)
- DigitalIntraoralXRayImageStorageForPresentation, [741](#)
- DigitalIntraoralXRayImageStorageForProcessing, [741](#)
- DigitalMammographyXRayImageStorageForPresentation, [741](#)
- DigitalMammographyXRayImageStorageForProcessing, [741](#)
- DigitalXRayImageStorageForPresentation, [741](#)
- DigitalXRayImageStorageForProcessing, [741](#)
- EncapsulatedCDASStorage, [743](#)
- EncapsulatedPDFStorage, [743](#)
- EnhancedCTImageStorage, [741](#)
- EnhancedMRIImageStorage, [741](#)
- EnhancedSRStorage, [742](#)
- EnhancedUSVolumeStorage, [745](#)
- EnhancedXAImageStorage, [742](#)
- EnhancedXRFImageStorage, [742](#)
- ExplicitVRBigEndian, [738](#)
- ExplicitVRLittleEndian, [738](#)
- GeneralECGWaveformStorage, [741](#)
- GeneralPurposePerformedProcedureStepSOP-Class, [743](#)
- GeneralPurposeScheduledProcedureStepSOP-Class, [743](#)
- GeneralPurposeWorklistInformationModelFIND, [743](#)
- GeneralPurposeWorklistManagementMetaSOP-Class, [743](#)
- GeneralRelevantPatientInformationQuery, [743](#)
- GrayscaleSoftcopyPresentationStateStorageSOP-Class, [742](#)
- HangingProtocolInformationModelFIND, [744](#)
- HangingProtocolInformationModelMOVE, [744](#)
- HangingProtocolStorage, [744](#)
- HardcopyColorImageStorageSOPClassRetired, [741](#)
- HardcopyGrayscaleImageStorageSOPClassRetired, [741](#)
- HemodynamicWaveformStorage, [741](#)
- ICBM452T1FrameofReference, [740](#)
- ICBMSingleSubjectMRIFrameofReference, [740](#)
- ImageOverlayBoxSOPClassRetired, [741](#)
- ImplicitVRLittleEndianDefaultTransferSyntaxforDICOM, [738](#)
- InstanceAvailabilityNotificationSOPClass, [743](#)

- JPEG2000ImageCompression, [739](#)
- JPEG2000ImageCompressionLosslessOnly, [739](#)
- JPEG2000Part2MulticomponentImageCompression, [739](#)
- JPEG2000Part2MulticomponentImageCompression-LosslessOnly, [739](#)
- JPEGBaselineProcess1DefaultTransferSyntaxfor-LossyJPEG8BitImageCompression, [738](#)
- JPEGExtendedHierarchicalProcess1618Retired, [739](#)
- JPEGExtendedHierarchicalProcess1719Retired, [739](#)
- JPEGExtendedProcess24DefaultTransferSyntaxfor-LossyJPEG12BitImageCompressionProcess4only, [738](#)
- JPEGExtendedProcess35Retired, [738](#)
- JPEGFullProgressionHierarchicalProcess2426-Retired, [739](#)
- JPEGFullProgressionHierarchicalProcess2527-Retired, [739](#)
- JPEGFullProgressionNonHierarchicalProcess1012-Retired, [738](#)
- JPEGFullProgressionNonHierarchicalProcess1113-Retired, [738](#)
- JPEGLSLosslessImageCompression, [739](#)
- JPEGLSLossyNearLosslessImageCompression, [739](#)
- JPEGLosslessHierarchicalProcess28Retired, [739](#)
- JPEGLosslessHierarchicalProcess29Retired, [739](#)
- JPEGLosslessNonHierarchicalFirstOrderPrediction-Process14SelectionValue1DefaultTransfer-SyntaxforLosslessJPEGImageCompression, [739](#)
- JPEGLosslessNonHierarchicalProcess14, [738](#)
- JPEGLosslessNonHierarchicalProcess15Retired, [739](#)
- JPEGSpectralSelectionHierarchicalProcess2022-Retired, [739](#)
- JPEGSpectralSelectionHierarchicalProcess2123-Retired, [739](#)
- JPEGSpectralSelectionNonHierarchicalProcess68-Retired, [738](#)
- JPEGSpectralSelectionNonHierarchicalProcess79-Retired, [738](#)
- JPIPReferenced, [739](#)
- JPIPReferencedDeflate, [739](#)
- KeyObjectSelectionDocumentStorage, [743](#)
- MPEG2MainProfileMainLevel, [739](#)
- MRImageStorage, [741](#)
- MRSpectroscopyStorage, [741](#)
- MammographyCADSRStorage, [742](#)
- MediaCreationManagementSOPClassUID, [741](#)
- MediaStorageDirectoryStorage, [739](#)
- ModalityPerformedProcedureStepNotificationSOP-Class, [740](#)
- ModalityPerformedProcedureStepRetrieveSOP-Class, [740](#)
- ModalityPerformedProcedureStepSOPClass, [740](#)
- ModalityWorklistInformationModelFIND, [743](#)
- MultiframeGrayscaleByteSecondaryCaptureImage-Storage, [741](#)
- MultiframeGrayscaleWordSecondaryCaptureImage-Storage, [741](#)
- MultiframeSingleBitSecondaryCaptureImageStorage, [741](#)
- MultiframeTrueColorSecondaryCaptureImage-Storage, [741](#)
- NuclearMedicineImageStorage, [742](#)
- NuclearMedicineImageStorageRetired, [741](#)
- OphthalmicPhotography16BitImageStorage, [742](#)
- OphthalmicPhotography8BitImageStorage, [742](#)
- OphthalmicTomographyImageStorage, [742](#)
- PatientRootQueryRetrieveInformationModelFIND, [743](#)
- PatientRootQueryRetrieveInformationModelGET, [743](#)
- PatientRootQueryRetrieveInformationModelMOVE, [743](#)
- PatientStudyOnlyQueryRetrieveInformationModelFI-NDRetired, [743](#)
- PatientStudyOnlyQueryRetrieveInformationModelG-ETRetired, [743](#)
- PatientStudyOnlyQueryRetrieveInformationModelM-OVERetired, [743](#)
- PositronEmissionTomographyImageStorage, [743](#)
- PresentationLUTSOPClass, [741](#)
- PrintJobSOPClass, [740](#)
- PrintQueueManagementSOPClassRetired, [741](#)
- PrintQueueSOPInstanceRetired, [741](#)
- PrinterConfigurationRetrieveSOPClass, [740](#)
- PrinterConfigurationRetrieveSOPInstance, [740](#)
- PrinterSOPClass, [740](#)
- PrinterSOPInstance, [740](#)
- ProceduralEventLoggingSOPClass, [740](#)
- ProceduralEventLoggingSOPInstance, [740](#)
- ProcedureLogStorage, [742](#)
- ProductCharacteristicsQuerySOPClass, [744](#)
- PseudoColorSoftcopyPresentationStateStorageSO-PClass, [742](#)
- PullPrintRequestSOPClassRetired, [741](#)
- PullStoredPrintManagementMetaSOPClassRetired, [741](#)
- RFC2557MIMEencapsulation, [739](#)
- RLELossless, [739](#)
- RTBeamsDeliveryInstructionStorageSupplement74-FrozenDraft, [743](#)
- RTBeamsTreatmentRecordStorage, [743](#)
- RTBrachyTreatmentRecordStorage, [743](#)
- RTConventionalMachineVerificationSupplement74-FrozenDraft, [743](#)
- RTDoseStorage, [743](#)

- RTImageStorage, [743](#)
- RTIonBeamsTreatmentRecordStorage, [743](#)
- RTIonMachineVerificationSupplement74FrozenDraft, [743](#)
- RTIonPlanStorage, [743](#)
- RTPlanStorage, [743](#)
- RTStructureSetStorage, [743](#)
- RTTreatmentSummaryRecordStorage, [743](#)
- RawDataStorage, [742](#)
- RealWorldValueMappingStorage, [742](#)
- ReferencedColorPrintManagementMetaSOPClass-Retired, [740](#)
- ReferencedGrayscalePrintManagementMetaSOP-ClassRetired, [740](#)
- ReferencedImageBoxSOPClassRetired, [740](#)
- SPM2AVG152PDFFrameofReference, [739](#)
- SPM2AVG152T1FrameofReference, [739](#)
- SPM2AVG152T2FrameofReference, [739](#)
- SPM2AVG305T1FrameofReference, [739](#)
- SPM2BRAINMASKFrameofReference, [739](#)
- SPM2CSFFFrameofReference, [739](#)
- SPM2EPIFrameofReference, [739](#)
- SPM2FILT1FrameofReference, [739](#)
- SPM2GRAYFrameofReference, [739](#)
- SPM2PDFFrameofReference, [739](#)
- SPM2PETFrameofReference, [739](#)
- SPM2SINGLESUBJT1FrameofReference, [739](#)
- SPM2SPECTFrameofReference, [739](#)
- SPM2T1FrameofReference, [739](#)
- SPM2T2FrameofReference, [739](#)
- SPM2TRANSMFrameofReference, [739](#)
- SPM2WHITEFrameofReference, [739](#)
- SecondaryCaptureImageStorage, [741](#)
- SegmentationStorage, [742](#)
- SpatialFiducialsStorage, [742](#)
- SpatialRegistrationStorage, [742](#)
- StandaloneCurveStorageRetired, [741](#)
- StandaloneModalityLUTStorageRetired, [742](#)
- StandaloneOverlayStorageRetired, [741](#)
- StandalonePETCurveStorageRetired, [743](#)
- StandaloneVOILUTStorageRetired, [742](#)
- StereometricRelationshipStorage, [742](#)
- StorageCommitmentPullModelSOPClassRetired, [740](#)
- StorageCommitmentPullModelSOPInstanceRetired, [740](#)
- StorageCommitmentPushModelSOPClass, [740](#)
- StorageCommitmentPushModelSOPInstance, [740](#)
- StorageServiceClass, [740](#)
- StoredPrintStorageSOPClassRetired, [741](#)
- StudyComponentManagementSOPClassRetired, [740](#)
- StudyRootQueryRetrieveInformationModelIFIND, [743](#)
- StudyRootQueryRetrieveInformationModelGET, [743](#)
- StudyRootQueryRetrieveInformationModelMOVE, [743](#)
- SubstanceAdministrationLoggingSOPClass, [740](#)
- SubstanceAdministrationLoggingSOPInstance, [740](#)
- SubstanceApprovalQuerySOPClass, [744](#)
- SurfaceSegmentationStorage, [745](#)
- TalairachBrainAtlasFrameofReference, [739](#)
- TextSRStorageTrialRetired, [742](#)
- uid_1_2_840_10008_15_0_3_1, [750](#)
- uid_1_2_840_10008_15_0_3_10, [750](#)
- uid_1_2_840_10008_15_0_3_11, [750](#)
- uid_1_2_840_10008_15_0_3_12, [751](#)
- uid_1_2_840_10008_15_0_3_13, [751](#)
- uid_1_2_840_10008_15_0_3_14, [751](#)
- uid_1_2_840_10008_15_0_3_15, [751](#)
- uid_1_2_840_10008_15_0_3_16, [751](#)
- uid_1_2_840_10008_15_0_3_17, [751](#)
- uid_1_2_840_10008_15_0_3_18, [751](#)
- uid_1_2_840_10008_15_0_3_19, [751](#)
- uid_1_2_840_10008_15_0_3_2, [750](#)
- uid_1_2_840_10008_15_0_3_20, [751](#)
- uid_1_2_840_10008_15_0_3_21, [751](#)
- uid_1_2_840_10008_15_0_3_22, [751](#)
- uid_1_2_840_10008_15_0_3_23, [751](#)
- uid_1_2_840_10008_15_0_3_24, [751](#)
- uid_1_2_840_10008_15_0_3_25, [751](#)
- uid_1_2_840_10008_15_0_3_26, [751](#)
- uid_1_2_840_10008_15_0_3_27, [751](#)
- uid_1_2_840_10008_15_0_3_28, [751](#)
- uid_1_2_840_10008_15_0_3_29, [751](#)
- uid_1_2_840_10008_15_0_3_3, [750](#)
- uid_1_2_840_10008_15_0_3_30, [751](#)
- uid_1_2_840_10008_15_0_3_31, [751](#)
- uid_1_2_840_10008_15_0_3_4, [750](#)
- uid_1_2_840_10008_15_0_3_5, [750](#)
- uid_1_2_840_10008_15_0_3_6, [750](#)
- uid_1_2_840_10008_15_0_3_7, [750](#)
- uid_1_2_840_10008_15_0_3_8, [750](#)
- uid_1_2_840_10008_15_0_3_9, [750](#)
- uid_1_2_840_10008_15_0_4_1, [751](#)
- uid_1_2_840_10008_15_0_4_2, [751](#)
- uid_1_2_840_10008_15_0_4_3, [751](#)
- uid_1_2_840_10008_15_0_4_4, [751](#)
- uid_1_2_840_10008_15_0_4_5, [751](#)
- uid_1_2_840_10008_15_0_4_6, [751](#)
- uid_1_2_840_10008_15_0_4_7, [751](#)
- uid_1_2_840_10008_15_0_4_8, [751](#)
- uid_1_2_840_10008_1_1, [745](#)
- uid_1_2_840_10008_1_2, [745](#)
- uid_1_2_840_10008_1_20_1, [746](#)
- uid_1_2_840_10008_1_20_1_1, [746](#)
- uid_1_2_840_10008_1_20_2, [746](#)
- uid_1_2_840_10008_1_20_2_1, [746](#)
- uid_1_2_840_10008_1_2_1, [745](#)

uid_1_2_840_10008_1_2_1_99, 745
uid_1_2_840_10008_1_2_2, 745
uid_1_2_840_10008_1_2_4_100, 746
uid_1_2_840_10008_1_2_4_50, 745
uid_1_2_840_10008_1_2_4_51, 745
uid_1_2_840_10008_1_2_4_52, 745
uid_1_2_840_10008_1_2_4_53, 745
uid_1_2_840_10008_1_2_4_54, 745
uid_1_2_840_10008_1_2_4_55, 745
uid_1_2_840_10008_1_2_4_56, 745
uid_1_2_840_10008_1_2_4_57, 745
uid_1_2_840_10008_1_2_4_58, 745
uid_1_2_840_10008_1_2_4_59, 745
uid_1_2_840_10008_1_2_4_60, 745
uid_1_2_840_10008_1_2_4_61, 745
uid_1_2_840_10008_1_2_4_62, 745
uid_1_2_840_10008_1_2_4_63, 745
uid_1_2_840_10008_1_2_4_64, 745
uid_1_2_840_10008_1_2_4_65, 745
uid_1_2_840_10008_1_2_4_66, 745
uid_1_2_840_10008_1_2_4_70, 745
uid_1_2_840_10008_1_2_4_80, 745
uid_1_2_840_10008_1_2_4_81, 745
uid_1_2_840_10008_1_2_4_90, 745
uid_1_2_840_10008_1_2_4_91, 745
uid_1_2_840_10008_1_2_4_92, 745
uid_1_2_840_10008_1_2_4_93, 745
uid_1_2_840_10008_1_2_4_94, 745
uid_1_2_840_10008_1_2_4_95, 746
uid_1_2_840_10008_1_2_5, 746
uid_1_2_840_10008_1_2_6_1, 746
uid_1_2_840_10008_1_2_6_2, 746
uid_1_2_840_10008_1_3_10, 746
uid_1_2_840_10008_1_40, 746
uid_1_2_840_10008_1_40_1, 746
uid_1_2_840_10008_1_42, 746
uid_1_2_840_10008_1_42_1, 746
uid_1_2_840_10008_1_4_1_1, 746
uid_1_2_840_10008_1_4_1_10, 746
uid_1_2_840_10008_1_4_1_11, 746
uid_1_2_840_10008_1_4_1_12, 746
uid_1_2_840_10008_1_4_1_13, 746
uid_1_2_840_10008_1_4_1_14, 746
uid_1_2_840_10008_1_4_1_15, 746
uid_1_2_840_10008_1_4_1_16, 746
uid_1_2_840_10008_1_4_1_17, 746
uid_1_2_840_10008_1_4_1_18, 746
uid_1_2_840_10008_1_4_1_2, 746
uid_1_2_840_10008_1_4_1_3, 746
uid_1_2_840_10008_1_4_1_4, 746
uid_1_2_840_10008_1_4_1_5, 746
uid_1_2_840_10008_1_4_1_6, 746
uid_1_2_840_10008_1_4_1_7, 746
uid_1_2_840_10008_1_4_1_8, 746
uid_1_2_840_10008_1_4_1_9, 746
uid_1_2_840_10008_1_4_2_1, 746
uid_1_2_840_10008_1_4_2_2, 746
uid_1_2_840_10008_1_9, 746
uid_1_2_840_10008_2_16_4, 746
uid_1_2_840_10008_2_6_1, 746
uid_1_2_840_10008_3_1_1_1, 746
uid_1_2_840_10008_3_1_2_1_1, 746
uid_1_2_840_10008_3_1_2_1_4, 746
uid_1_2_840_10008_3_1_2_2_1, 746
uid_1_2_840_10008_3_1_2_3_1, 746
uid_1_2_840_10008_3_1_2_3_2, 747
uid_1_2_840_10008_3_1_2_3_3, 747
uid_1_2_840_10008_3_1_2_3_4, 747
uid_1_2_840_10008_3_1_2_3_5, 747
uid_1_2_840_10008_3_1_2_5_1, 747
uid_1_2_840_10008_3_1_2_5_4, 747
uid_1_2_840_10008_3_1_2_5_5, 747
uid_1_2_840_10008_3_1_2_6_1, 747
uid_1_2_840_10008_4_2, 747
uid_1_2_840_10008_5_1_1_1, 747
uid_1_2_840_10008_5_1_1_14, 747
uid_1_2_840_10008_5_1_1_15, 747
uid_1_2_840_10008_5_1_1_16, 747
uid_1_2_840_10008_5_1_1_16_376, 747
uid_1_2_840_10008_5_1_1_17, 747
uid_1_2_840_10008_5_1_1_17_376, 747
uid_1_2_840_10008_5_1_1_18, 747
uid_1_2_840_10008_5_1_1_18_1, 747
uid_1_2_840_10008_5_1_1_2, 747
uid_1_2_840_10008_5_1_1_22, 747
uid_1_2_840_10008_5_1_1_23, 747
uid_1_2_840_10008_5_1_1_24, 747
uid_1_2_840_10008_5_1_1_24_1, 747
uid_1_2_840_10008_5_1_1_25, 747
uid_1_2_840_10008_5_1_1_26, 747
uid_1_2_840_10008_5_1_1_27, 747
uid_1_2_840_10008_5_1_1_29, 747
uid_1_2_840_10008_5_1_1_30, 747
uid_1_2_840_10008_5_1_1_31, 747
uid_1_2_840_10008_5_1_1_32, 747
uid_1_2_840_10008_5_1_1_33, 747
uid_1_2_840_10008_5_1_1_4, 747
uid_1_2_840_10008_5_1_1_4_1, 747
uid_1_2_840_10008_5_1_1_4_2, 747
uid_1_2_840_10008_5_1_1_9, 747
uid_1_2_840_10008_5_1_1_9_1, 747
uid_1_2_840_10008_5_1_4_1_1_1, 747
uid_1_2_840_10008_5_1_4_1_1_10, 748
uid_1_2_840_10008_5_1_4_1_1_104_1, 749
uid_1_2_840_10008_5_1_4_1_1_104_2, 749
uid_1_2_840_10008_5_1_4_1_1_11, 748
uid_1_2_840_10008_5_1_4_1_1_11_1, 748
uid_1_2_840_10008_5_1_4_1_1_11_2, 748

uid_1_2_840_10008_5_1_4_1_1_11_3, 748
uid_1_2_840_10008_5_1_4_1_1_11_4, 748
uid_1_2_840_10008_5_1_4_1_1_128, 749
uid_1_2_840_10008_5_1_4_1_1_129, 749
uid_1_2_840_10008_5_1_4_1_1_12_1, 748
uid_1_2_840_10008_5_1_4_1_1_12_1_1, 748
uid_1_2_840_10008_5_1_4_1_1_12_2, 748
uid_1_2_840_10008_5_1_4_1_1_12_2_1, 748
uid_1_2_840_10008_5_1_4_1_1_12_3, 748
uid_1_2_840_10008_5_1_4_1_1_13_1_1, 748
uid_1_2_840_10008_5_1_4_1_1_13_1_2, 748
uid_1_2_840_10008_5_1_4_1_1_13_1_3, 751
uid_1_2_840_10008_5_1_4_1_1_1_1, 747
uid_1_2_840_10008_5_1_4_1_1_1_1_1, 747
uid_1_2_840_10008_5_1_4_1_1_1_2, 747
uid_1_2_840_10008_5_1_4_1_1_1_2_1, 747
uid_1_2_840_10008_5_1_4_1_1_1_3, 747
uid_1_2_840_10008_5_1_4_1_1_1_3_1, 748
uid_1_2_840_10008_5_1_4_1_1_2, 748
uid_1_2_840_10008_5_1_4_1_1_20, 748
uid_1_2_840_10008_5_1_4_1_1_2_1, 748
uid_1_2_840_10008_5_1_4_1_1_3, 748
uid_1_2_840_10008_5_1_4_1_1_3_1, 748
uid_1_2_840_10008_5_1_4_1_1_4, 748
uid_1_2_840_10008_5_1_4_1_1_481_1, 749
uid_1_2_840_10008_5_1_4_1_1_481_2, 749
uid_1_2_840_10008_5_1_4_1_1_481_3, 749
uid_1_2_840_10008_5_1_4_1_1_481_4, 749
uid_1_2_840_10008_5_1_4_1_1_481_5, 749
uid_1_2_840_10008_5_1_4_1_1_481_6, 749
uid_1_2_840_10008_5_1_4_1_1_481_7, 749
uid_1_2_840_10008_5_1_4_1_1_481_8, 749
uid_1_2_840_10008_5_1_4_1_1_481_9, 749
uid_1_2_840_10008_5_1_4_1_1_4_1, 748
uid_1_2_840_10008_5_1_4_1_1_4_2, 748
uid_1_2_840_10008_5_1_4_1_1_5, 748
uid_1_2_840_10008_5_1_4_1_1_6, 748
uid_1_2_840_10008_5_1_4_1_1_66, 748
uid_1_2_840_10008_5_1_4_1_1_66_1, 748
uid_1_2_840_10008_5_1_4_1_1_66_2, 748
uid_1_2_840_10008_5_1_4_1_1_66_3, 749
uid_1_2_840_10008_5_1_4_1_1_66_4, 749
uid_1_2_840_10008_5_1_4_1_1_66_5, 751
uid_1_2_840_10008_5_1_4_1_1_67, 749
uid_1_2_840_10008_5_1_4_1_1_6_1, 748
uid_1_2_840_10008_5_1_4_1_1_6_2, 751
uid_1_2_840_10008_5_1_4_1_1_7, 748
uid_1_2_840_10008_5_1_4_1_1_77_1, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_1, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_1_1, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_2, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_2_1, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_3, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_4, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_4_1, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_5_1, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_5_2, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_5_3, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_5_4, 749
uid_1_2_840_10008_5_1_4_1_1_77_1_6, 751
uid_1_2_840_10008_5_1_4_1_1_77_2, 749
uid_1_2_840_10008_5_1_4_1_1_7_1, 748
uid_1_2_840_10008_5_1_4_1_1_7_2, 748
uid_1_2_840_10008_5_1_4_1_1_7_3, 748
uid_1_2_840_10008_5_1_4_1_1_7_4, 748
uid_1_2_840_10008_5_1_4_1_1_8, 748
uid_1_2_840_10008_5_1_4_1_1_88_1, 749
uid_1_2_840_10008_5_1_4_1_1_88_11, 749
uid_1_2_840_10008_5_1_4_1_1_88_2, 749
uid_1_2_840_10008_5_1_4_1_1_88_22, 749
uid_1_2_840_10008_5_1_4_1_1_88_3, 749
uid_1_2_840_10008_5_1_4_1_1_88_33, 749
uid_1_2_840_10008_5_1_4_1_1_88_4, 749
uid_1_2_840_10008_5_1_4_1_1_88_40, 749
uid_1_2_840_10008_5_1_4_1_1_88_50, 749
uid_1_2_840_10008_5_1_4_1_1_88_59, 749
uid_1_2_840_10008_5_1_4_1_1_88_65, 749
uid_1_2_840_10008_5_1_4_1_1_88_67, 749
uid_1_2_840_10008_5_1_4_1_1_9, 748
uid_1_2_840_10008_5_1_4_1_1_9_1, 748
uid_1_2_840_10008_5_1_4_1_1_9_1_1, 748
uid_1_2_840_10008_5_1_4_1_1_9_1_2, 748
uid_1_2_840_10008_5_1_4_1_1_9_1_3, 748
uid_1_2_840_10008_5_1_4_1_1_9_2_1, 748
uid_1_2_840_10008_5_1_4_1_1_9_3_1, 748
uid_1_2_840_10008_5_1_4_1_1_9_4_1, 748
uid_1_2_840_10008_5_1_4_1_2_1_1, 749
uid_1_2_840_10008_5_1_4_1_2_1_2, 750
uid_1_2_840_10008_5_1_4_1_2_1_3, 750
uid_1_2_840_10008_5_1_4_1_2_2_1, 750
uid_1_2_840_10008_5_1_4_1_2_2_2, 750
uid_1_2_840_10008_5_1_4_1_2_2_3, 750
uid_1_2_840_10008_5_1_4_1_2_3_1, 750
uid_1_2_840_10008_5_1_4_1_2_3_2, 750
uid_1_2_840_10008_5_1_4_1_2_3_3, 750
uid_1_2_840_10008_5_1_4_31, 750
uid_1_2_840_10008_5_1_4_32, 750
uid_1_2_840_10008_5_1_4_32_1, 750
uid_1_2_840_10008_5_1_4_32_2, 750
uid_1_2_840_10008_5_1_4_32_3, 750
uid_1_2_840_10008_5_1_4_33, 750
uid_1_2_840_10008_5_1_4_34_1, 750
uid_1_2_840_10008_5_1_4_34_2, 750
uid_1_2_840_10008_5_1_4_34_3, 750
uid_1_2_840_10008_5_1_4_34_4, 750
uid_1_2_840_10008_5_1_4_34_4_1, 750
uid_1_2_840_10008_5_1_4_34_4_2, 750
uid_1_2_840_10008_5_1_4_34_4_3, 750

- uid_1_2_840_10008_5_1_4_34_4_4, [750](#)
- uid_1_2_840_10008_5_1_4_34_5, [750](#)
- uid_1_2_840_10008_5_1_4_37_1, [750](#)
- uid_1_2_840_10008_5_1_4_37_2, [750](#)
- uid_1_2_840_10008_5_1_4_37_3, [750](#)
- uid_1_2_840_10008_5_1_4_38_1, [750](#)
- uid_1_2_840_10008_5_1_4_38_2, [750](#)
- uid_1_2_840_10008_5_1_4_38_3, [750](#)
- uid_1_2_840_10008_5_1_4_41, [750](#)
- uid_1_2_840_10008_5_1_4_42, [750](#)
- UltrasoundImageStorage, [741](#)
- UltrasoundImageStorageRetired, [741](#)
- UltrasoundMultiframeImageStorage, [741](#)
- UltrasoundMultiframeImageStorageRetired, [741](#)
- UnifiedProcedureStepEventSOPClass, [743](#)
- UnifiedProcedureStepPullSOPClass, [743](#)
- UnifiedProcedureStepPushSOPClass, [743](#)
- UnifiedProcedureStepWatchSOPClass, [743](#)
- UnifiedWorklistandProcedureStepSOPInstance, [743](#)
- UnifiedWorklistandProcedureStepServiceClass, [743](#)
- VLEndoscopicImageStorage, [742](#)
- VImageStorageTrialRetired, [742](#)
- VLMicroscopicImageStorage, [742](#)
- VMultiframeImageStorageTrialRetired, [742](#)
- VLPhotographicImageStorage, [742](#)
- VLSlideCoordinatesMicroscopicImageStorage, [742](#)
- VLWholeSlideMicroscopyImageStorage, [745](#)
- VOILUTBoxSOPClass, [741](#)
- VerificationSOPClass, [738](#)
- VideoEndoscopicImageStorage, [742](#)
- VideoMicroscopicImageStorage, [742](#)
- VideoPhotographicImageStorage, [742](#)
- WaveformStorageTrialRetired, [741](#)
- XMLEncoding, [739](#)
- XRay3DAngiographicImageStorage, [742](#)
- XRay3DCraniofacialImageStorage, [742](#)
- XRayAngiographicBiPlaneImageStorageRetired, [742](#)
- XRayAngiographicImageStorage, [742](#)
- XRayRadiationDoseSRStorage, [743](#)
- XRayRadiofluoroscopicImageStorage, [742](#)
- gdcmm::Usage
 - Conditional, [806](#)
 - Invalid, [806](#)
 - Mandatory, [806](#)
 - UserOption, [806](#)
- gdcmm::VM
 - VM0, [818](#)
 - VM1, [818](#)
 - VM10, [818](#)
 - VM12, [818](#)
 - VM16, [818](#)
 - VM18, [818](#)
 - VM1_2, [819](#)
 - VM1_3, [819](#)
 - VM1_32, [819](#)
 - VM1_4, [819](#)
 - VM1_5, [819](#)
 - VM1_8, [819](#)
 - VM1_99, [819](#)
 - VM1_n, [819](#)
 - VM2, [818](#)
 - VM24, [818](#)
 - VM256, [819](#)
 - VM28, [818](#)
 - VM2_2n, [819](#)
 - VM2_n, [819](#)
 - VM3, [818](#)
 - VM30_30n, [819](#)
 - VM32, [818](#)
 - VM35, [818](#)
 - VM3_3n, [819](#)
 - VM3_4, [819](#)
 - VM3_n, [819](#)
 - VM4, [818](#)
 - VM47_47n, [819](#)
 - VM4_4n, [819](#)
 - VM5, [818](#)
 - VM6, [818](#)
 - VM6_6n, [819](#)
 - VM7_7n, [819](#)
 - VM8, [818](#)
 - VM9, [818](#)
 - VM99, [819](#)
 - VM_END, [819](#)
- gdcmm::VR
 - AE, [822](#)
 - AS, [822](#)
 - AT, [822](#)
 - CS, [822](#)
 - DA, [822](#)
 - DS, [822](#)
 - DT, [823](#)
 - FD, [823](#)
 - FL, [823](#)
 - INVALID, [822](#)
 - IS, [823](#)
 - LO, [823](#)
 - LT, [823](#)
 - OB, [823](#)
 - OB_OW, [823](#)
 - OF, [823](#)
 - OW, [823](#)
 - PN, [823](#)
 - SH, [823](#)
 - SL, [823](#)
 - SQ, [823](#)
 - SS, [823](#)
 - ST, [823](#)

- TM, [823](#)
- UI, [823](#)
- UL, [823](#)
- UN, [823](#)
- US, [823](#)
- US_SS, [823](#)
- US_SS_OW, [823](#)
- UT, [823](#)
- VL16, [823](#)
- VL32, [823](#)
- VR_END, [823](#)
- VR_VM1, [823](#)
- VRALL, [823](#)
- VRASCII, [823](#)
- VRBINARY, [823](#)
- gdcmm::network
 - eAABORTPDUReceivedOpen, [128](#)
 - eAABORTRequest, [128](#)
 - eAASSOCIATE_RQPDUreceived, [128](#)
 - eAASSOCIATERequestLocalUser, [128](#)
 - eAASSOCIATEResponseAccept, [128](#)
 - eAASSOCIATEResponseReject, [128](#)
 - eARELEASE_RPPDUReceived, [128](#)
 - eARELEASE_RQPDUReceivedOpen, [128](#)
 - eARELEASERequest, [128](#)
 - eARELEASEResponse, [128](#)
 - eARTIMTimerExpired, [129](#)
 - eASSOCIATE_ACPDUreceived, [128](#)
 - eASSOCIATE_RJPDUreceived, [128](#)
 - eEventDoesNotExist, [129](#)
 - ePDATATFPDU, [128](#)
 - ePDATArequest, [128](#)
 - eSta10ReleaseCollisionAc, [129](#)
 - eSta11ReleaseCollisionRq, [129](#)
 - eSta12ReleaseCollisionAcLocal, [129](#)
 - eSta13AwaitingClose, [129](#)
 - eSta1Idle, [129](#)
 - eSta2Open, [129](#)
 - eSta3WaitLocalAssoc, [129](#)
 - eSta4LocalAssocDone, [129](#)
 - eSta5WaitRemoteAssoc, [129](#)
 - eSta6TransferReady, [129](#)
 - eSta7WaitRelease, [129](#)
 - eSta8WaitLocalRelease, [129](#)
 - eSta9ReleaseCollisionRqLocal, [129](#)
 - eStaDoesNotExist, [129](#)
 - eTransportConnConfirmLocal, [128](#)
 - eTransportConnIndicLocal, [128](#)
 - eTransportConnectionClosed, [128](#)
 - eUnrecognizedPDUReceived, [129](#)
- gdcmm::network::DIMSE
 - C_CANCEL_RQ, [314](#)
 - C_ECHO_RQ, [313](#)
 - C_ECHO_RSP, [313](#)
 - C_FIND_RQ, [313](#)
 - C_FIND_RSP, [313](#)
 - C_GET_RQ, [313](#)
 - C_GET_RSP, [313](#)
 - C_MOVE_RQ, [313](#)
 - C_MOVE_RSP, [313](#)
 - C_STORE_RQ, [313](#)
 - C_STORE_RSP, [313](#)
 - N_ACTION_RQ, [314](#)
 - N_ACTION_RSP, [314](#)
 - N_CREATE_RQ, [314](#)
 - N_CREATE_RSP, [314](#)
 - N_DELETE_RQ, [314](#)
 - N_DELETE_RSP, [314](#)
 - N_EVENT_REPORT_RQ, [313](#)
 - N_EVENT_REPORT_RSP, [313](#)
 - N_GET_RQ, [313](#)
 - N_GET_RSP, [314](#)
 - N_SET_RQ, [314](#)
 - N_SET_RSP, [314](#)
- gdcmm::terminal
 - black, [131](#)
 - blink, [131](#)
 - blue, [131](#)
 - bright, [131](#)
 - CONSOLE, [131](#)
 - cyan, [131](#)
 - dim, [131](#)
 - green, [131](#)
 - hidden, [131](#)
 - magenta, [131](#)
 - red, [131](#)
 - reset, [131](#)
 - reverse, [131](#)
 - underline, [131](#)
 - VT100, [131](#)
 - white, [131](#)
 - yellow, [131](#)
- gdcmm::ASN1, [161](#)
 - ~ASN1, [161](#)
 - ASN1, [161](#)
 - ParseDump, [161](#)
 - ParseDumpFile, [161](#)
 - TestPBKDF2, [161](#)
- gdcmm::AbortEvent, [143](#)
- gdcmm::AnonymizeEvent, [145](#)
 - ~AnonymizeEvent, [147](#)
 - AnonymizeEvent, [147](#)
 - CheckEvent, [147](#)
 - GetEventName, [147](#)
 - GetTag, [147](#)
 - MakeObject, [147](#)
 - Self, [147](#)
 - SetTag, [147](#)

- Superclass, [147](#)
- gdcmm::Anonymizer, [148](#)
 - ~Anonymizer, [150](#)
 - Anonymizer, [150](#)
 - BALCPPProtect, [150](#)
 - BasicApplicationLevelConfidentialityProfile, [150](#)
 - CanEmptyTag, [151](#)
 - Empty, [151](#)
 - GetBasicApplicationLevelConfidentialityProfile-Attributes, [151](#)
 - GetCryptographicMessageSyntax, [151](#)
 - GetFile, [151](#)
 - New, [151](#)
 - RecurseDataSet, [151](#)
 - Remove, [151](#)
 - RemoveGroupLength, [151](#)
 - RemovePrivateTags, [151](#)
 - RemoveRetired, [152](#)
 - Replace, [152](#)
 - SetCryptographicMessageSyntax, [152](#)
 - SetFile, [152](#)
- gdcmm::AnyEvent, [152](#)
- gdcmm::ApplicationEntity, [155](#)
 - Internal, [156](#)
 - IsValid, [156](#)
 - MaxLength, [156](#)
 - MaxNumberOfComponents, [156](#)
 - Padding, [156](#)
 - Print, [156](#)
 - Separator, [156](#)
 - SetBlob, [156](#)
 - Squeeze, [156](#)
- gdcmm::Attribute
 - ArrayType, [164](#)
 - GDCM_STATIC_ASSERT, [165](#)
 - GetAsDataElement, [165](#)
 - GetDictVM, [165](#)
 - GetDictVR, [165](#)
 - GetNumberOfValues, [165](#)
 - GetTag, [166](#)
 - GetVM, [166](#)
 - GetVR, [167](#)
 - GetValue, [166](#)
 - GetValues, [166](#)
 - Internal, [169](#)
 - operator<, [167](#)
 - operator==, [167](#)
 - Print, [167](#)
 - Set, [168](#)
 - SetByteValue, [168](#)
 - SetByteValueNoSwap, [168](#)
 - SetFromDataElement, [168](#)
 - SetFromDataSet, [168](#)
 - SetValue, [169](#)
 - SetValues, [169](#)
- gdcmm::Attribute< Group, Element, TVR, TVM >, [162](#)
- gdcmm::Attribute< Group, Element, TVR, VM::VM1 >, [170](#)
 - ArrayType, [171](#)
 - GetAsDataElement, [172](#)
 - GetDictVM, [172](#)
 - GetDictVR, [172](#)
 - GetNumberOfValues, [172](#)
 - GetTag, [172](#)
 - GetVM, [172](#)
 - GetVR, [172](#)
 - GetValue, [172](#)
 - GetValues, [172](#)
 - Internal, [174](#)
 - operator<, [173](#)
 - operator==, [173](#)
 - Print, [173](#)
 - Set, [173](#)
 - SetByteValue, [173](#)
 - SetByteValueNoSwap, [173](#)
 - SetFromDataElement, [173](#)
 - SetFromDataSet, [174](#)
 - SetValue, [174](#)
- gdcmm::Attribute< Group, Element, TVR, VM::VM1_3 >, [174](#)
 - GetVM, [175](#)
- gdcmm::Attribute< Group, Element, TVR, VM::VM1_8 >, [176](#)
 - GetVM, [177](#)
- gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >, [177](#)
 - ~Attribute, [178](#)
 - ArrayType, [178](#)
 - Attribute, [178](#)
 - GetAsDataElement, [179](#)
 - GetDictVM, [179](#)
 - GetDictVR, [179](#)
 - GetNumberOfValues, [179](#)
 - GetTag, [179](#)
 - GetVM, [179](#)
 - GetVR, [179](#)
 - GetValue, [179](#)
 - GetValues, [179](#)
 - Print, [180](#)
 - Set, [180](#)
 - SetByteValue, [180](#)
 - SetFromDataElement, [180](#)
 - SetFromDataSet, [180](#)
 - SetNumberOfValues, [180](#)
 - SetValue, [181](#)
 - SetValues, [181](#)
- gdcmm::Attribute< Group, Element, TVR, VM::VM2_2n >, [181](#)
 - GetVM, [183](#)

gdcmm::Attribute< Group, Element, TVR, VM::VM2_n >, 183
 GetVM, 184
gdcmm::Attribute< Group, Element, TVR, VM::VM3_3n >, 184
 GetVM, 186
gdcmm::Attribute< Group, Element, TVR, VM::VM3_n >, 186
 GetVM, 187
gdcmm::AudioCodec, 187
 ~AudioCodec, 189
 AudioCodec, 189
 CanCode, 189
 CanDecode, 189
 Decode, 189
gdcmm::Base64, 189
 ~Base64, 190
 Base64, 190
 Decode, 190
 Encode, 190
 GetDecodeLength, 190
 GetEncodeLength, 191
gdcmm::BaseRootQuery, 194
 ~BaseRootQuery, 196
 AddQueryDataSet, 196
 BaseRootQuery, 196
 Construct, 197
 GetAbstractSyntaxUID, 197
 GetQueryDataSet, 197
 GetQueryLevelFromQueryRoot, 197
 GetQueryLevelFromString, 197
 GetQueryLevelString, 197
 GetTagListByLevel, 197
 InitializeDataSet, 197
 mDataSet, 198
 mHelpDescription, 198
 mImage, 198
 mPatient, 198
 mRootType, 198
 mSeries, 198
 mStudy, 198
 Print, 197
 QueryFactory, 198
 SetSearchParameter, 197
 ValidateQuery, 197
 WriteHelpFile, 198
 WriteQuery, 198
gdcmm::BasicOffsetTable, 201
 BasicOffsetTable, 202
 operator<<, 203
 Read, 202
gdcmm::Bitmap, 203
 ~Bitmap, 206
 AreOverlaysInPixelData, 206
 Bitmap, 206
 Clear, 206
 ComputeLossyFlag, 206
 Dimensions, 210
 GetBuffer, 206
 GetBuffer2, 206
 GetBufferLength, 206
 GetColumns, 207
 GetDataElement, 207
 GetDimension, 207
 GetDimensions, 207
 GetLUT, 207
 GetNeedByteSwap, 207
 GetNumberOfDimensions, 207
 GetPhotometricInterpretation, 207
 GetPixelFormat, 207, 208
 GetPlanarConfiguration, 208
 GetRows, 208
 GetTransferSyntax, 208
 ImageChangeTransferSyntax, 210
 IsEmpty, 208
 IsLossy, 208
 IsTransferSyntaxCompatible, 208
 LUT, 210
 LUTPtr, 206
 LossyFlag, 210
 NeedByteSwap, 210
 NumberOfDimensions, 210
 PF, 210
 PI, 210
 PixelData, 210
 PixmapReader, 210
 PlanarConfiguration, 210
 Print, 208
 SetColumns, 208
 SetDataElement, 208
 SetDimension, 208
 SetDimensions, 209
 SetLUT, 209
 SetLossyFlag, 209
 SetNeedByteSwap, 209
 SetNumberOfDimensions, 209
 SetPhotometricInterpretation, 209
 SetPixelFormat, 209
 SetPlanarConfiguration, 209
 SetRows, 209
 SetTransferSyntax, 210
 TS, 211
 TryJPEG2000Codec, 210
 TryJPEG2000Codec2, 210
 TryJPEGCodec, 210
 TryJPEGCodec2, 210
 TryJPEGLSCodec, 210
 TryKAKADUCodec, 210

- TryPVRGCodec, [210](#)
- TryRAWCodec, [210](#)
- TryRLECodec, [210](#)
- gdcmm::BitmapToBitmapFilter, [211](#)
- ~BitmapToBitmapFilter, [212](#)
- BitmapToBitmapFilter, [212](#)
- GetOutput, [212](#)
- GetOutputAsBitmap, [212](#)
- Input, [212](#)
- Output, [212](#)
- SetInput, [212](#)
- gdcmm::BoxRegion, [213](#)
- ~BoxRegion, [214](#)
- Area, [214](#)
- BoundingBox, [214](#)
- BoxRegion, [214](#)
- Clone, [215](#)
- ComputeBoundingBox, [215](#)
- Empty, [215](#)
- GetXMax, [215](#)
- GetXMin, [215](#)
- GetYMax, [215](#)
- GetYMin, [215](#)
- GetZMax, [215](#)
- GetZMin, [215](#)
- IsValid, [215](#)
- operator=, [215](#)
- Print, [215](#)
- SetDomain, [215](#)
- gdcmm::ByteBuffer, [216](#)
- ByteBuffer, [216](#)
- Get, [216](#)
- GetStart, [216](#)
- ShiftEnd, [216](#)
- UpdatePosition, [216](#)
- gdcmm::ByteSwap
- Swap, [217](#)
- SwapFromSwapCodeIntoSystem, [217](#)
- SwapRange, [217](#)
- SwapRangeFromSwapCodeIntoSystem, [217](#)
- SystemIsBigEndian, [217](#)
- SystemIsLittleEndian, [217](#)
- gdcmm::ByteSwap< T >, [217](#)
- gdcmm::ByteSwapFilter, [218](#)
- ~ByteSwapFilter, [218](#)
- ByteSwap, [218](#)
- ByteSwapFilter, [218](#)
- SetByteSwapTag, [218](#)
- gdcmm::ByteValue, [218](#)
- ~ByteValue, [221](#)
- ByteValue, [220](#)
- Clear, [221](#)
- Fill, [221](#)
- GetBuffer, [221](#)
- GetLength, [221](#)
- GetPointer, [221](#)
- IsEmpty, [222](#)
- IsPrintable, [222](#)
- operator const std::vector< char > &, [222](#)
- operator=, [222](#)
- operator==, [222](#)
- Print, [222](#)
- PrintASCII, [222](#)
- PrintGroupLength, [222](#)
- PrintHex, [222](#)
- Read, [222](#)
- SetLength, [222](#)
- Write, [222](#)
- WriteBuffer, [223](#)
- gdcmm::CP246ExplicitDataElement, [248](#)
- GetLength, [249](#)
- Read, [249](#)
- ReadPreValue, [250](#)
- ReadValue, [250](#)
- ReadWithLength, [250](#)
- gdcmm::CSAElement, [251](#)
- CSAElement, [253](#)
- DataField, [255](#)
- DataPtr, [253](#)
- GetByteValue, [253](#)
- GetKey, [254](#)
- GetName, [254](#)
- GetNoOfItems, [254](#)
- GetSyngoDT, [254](#)
- GetVM, [254](#)
- GetVR, [254](#)
- GetValue, [254](#)
- IsEmpty, [254](#)
- KeyField, [255](#)
- NameField, [255](#)
- NoOfItemsField, [256](#)
- operator<, [255](#)
- operator<<, [255](#)
- operator=, [255](#)
- operator==, [255](#)
- SetByteValue, [255](#)
- SetKey, [255](#)
- SetName, [255](#)
- SetNoOfItems, [255](#)
- SetSyngoDT, [255](#)
- SetVM, [255](#)
- SetVR, [255](#)
- SetValue, [255](#)
- SyngoDTField, [256](#)
- VRField, [256](#)
- ValueMultiplicityField, [256](#)
- gdcmm::CSAHeader, [256](#)
- ~CSAHeader, [258](#)

- CSAHeader, [258](#)
- CSAHeaderType, [258](#)
- FindCSAElementByName, [258](#)
- GetCSADataInfo, [258](#)
- GetCSAEEnd, [258](#)
- GetCSAElementByName, [259](#)
- GetCSAImageHeaderInfoTag, [259](#)
- GetCSASeriesHeaderInfoTag, [259](#)
- GetDataSet, [259](#)
- GetFormat, [259](#)
- GetInterfile, [259](#)
- LoadFromDataElement, [259](#)
- operator<<, [260](#)
- Print, [259](#)
- Read, [260](#)
- Write, [260](#)
- gdcmm::CSAHeaderDict, [260](#)
 - AddCSAHeaderDictEntry, [261](#)
 - Begin, [261](#)
 - CSAHeaderDict, [261](#)
 - ConstIterator, [261](#)
 - Dicts, [261](#)
 - End, [261](#)
 - GetCSAHeaderDictEntry, [261](#)
 - IsEmpty, [261](#)
 - Iterator, [261](#)
 - LoadDefault, [261](#)
 - MapCSAHeaderDictEntry, [261](#)
 - operator<<, [261](#)
- gdcmm::CSAHeaderDictEntry, [262](#)
 - CSAHeaderDictEntry, [263](#)
 - GetDescription, [263](#)
 - GetName, [263](#)
 - GetVM, [263](#)
 - GetVR, [263](#)
 - operator<, [263](#)
 - operator<<, [263](#)
 - SetDescription, [263](#)
 - SetName, [263](#)
 - SetVM, [263](#)
 - SetVR, [263](#)
- gdcmm::CSAHeaderDictException, [263](#)
- gdcmm::CodeString, [237](#)
 - CodeString, [238](#)
 - const_iterator, [238](#)
 - const_reference, [238](#)
 - const_reverse_iterator, [238](#)
 - difference_type, [238](#)
 - GetAsString, [239](#)
 - IsValid, [239](#)
 - iterator, [238](#)
 - operator<<, [239](#)
 - operator==, [239](#)
 - pointer, [238](#)
 - reference, [238](#)
 - reverse_iterator, [238](#)
 - Size, [239](#)
 - size_type, [238](#)
 - TrimInternal, [239](#)
 - value_type, [238](#)
- gdcmm::Codec, [234](#)
- gdcmm::Coder, [235](#)
 - ~Coder, [236](#)
 - CanCode, [236](#)
 - Code, [236](#)
 - InternalCode, [236](#)
- gdcmm::Command, [239](#)
 - ~Command, [241](#)
 - Command, [241](#)
 - Execute, [241](#)
- gdcmm::CommandDataSet, [241](#)
 - ~CommandDataSet, [243](#)
 - CommandDataSet, [243](#)
 - Insert, [243](#)
 - operator<<, [243](#)
 - Read, [243](#)
 - Replace, [243](#)
 - Write, [243](#)
- gdcmm::CompositeNetworkFunctions, [244](#)
 - CEcho, [246](#)
 - CFind, [246](#)
 - CMove, [246](#)
 - CStore, [247](#)
 - ConstructQuery, [247](#)
 - KeyValuePairArrayType, [245](#)
 - KeyValuePairType, [245](#)
- gdcmm::ConstCharWrapper, [247](#)
 - ConstCharWrapper, [248](#)
 - operator const char *, [248](#)
- gdcmm::CryptographicMessageSyntax, [250](#)
 - ~CryptographicMessageSyntax, [251](#)
 - CipherTypes, [251](#)
 - CryptographicMessageSyntax, [251](#)
 - Decrypt, [251](#)
 - Encrypt, [251](#)
 - GetCipherType, [251](#)
 - ParseCertificateFile, [251](#)
 - ParseKeyFile, [251](#)
 - SetCipherType, [251](#)
- gdcmm::Curve, [267](#)
 - ~Curve, [269](#)
 - Curve, [269](#)
 - Decode, [269](#)
 - GetAsPoints, [269](#)
 - GetCurveDataDescriptor, [269](#)
 - GetDataValueRepresentation, [269](#)
 - GetDimensions, [269](#)
 - GetGroup, [269](#)

- GetNumberOfCurves, 269
- GetNumberOfPoints, 269
- GetTypeOfData, 269
- GetTypeOfDataDescription, 269
- IsEmpty, 269
- Print, 269
- SetCoordinateStartValue, 269
- SetCoordinateStepValue, 270
- SetCurve, 270
- SetCurveDataDescriptor, 270
- SetCurveDescription, 270
- SetDataValueRepresentation, 270
- SetDimensions, 270
- SetGroup, 270
- SetNumberOfPoints, 270
- SetTypeOfData, 270
- Update, 270
- gdcmm::DICOMDIR, 298
 - DICOMDIR, 298
- gdcmm::DICOMDIRGenerator, 298
 - ~DICOMDIRGenerator, 300
 - AddImageDirectoryRecord, 300
 - AddPatientDirectoryRecord, 300
 - AddSeriesDirectoryRecord, 300
 - AddStudyDirectoryRecord, 300
 - DICOMDIRGenerator, 300
 - FilenameType, 300
 - FileNamesType, 300
 - Generate, 300
 - GetFile, 300
 - GetScanner, 300
 - SetDescriptor, 300
 - SetFile, 300
 - SetFileNames, 300
 - SetRootDirectory, 300
- gdcmm::DataElement, 270
 - Clear, 274
 - DataElement, 273
 - Empty, 274
 - GetByteValue, 274
 - GetLength, 274
 - GetSequenceOfFragments, 274
 - GetSequenceOfItems, 274, 275
 - GetTag, 275
 - GetVL, 276
 - GetVR, 276
 - GetValue, 275
 - GetValueAsSQ, 275
 - IsEmpty, 276
 - IsUndefinedLength, 276
 - operator<, 276
 - operator<<, 279
 - operator=, 276
 - operator==, 277
 - Read, 277
 - ReadOrSkip, 277
 - ReadPreValue, 277
 - ReadValue, 277
 - ReadWithLength, 277
 - SetByteValue, 277
 - SetTag, 277
 - SetVL, 278
 - SetVLToUndefined, 278
 - SetVR, 278
 - SetValue, 277
 - TagField, 279
 - VRField, 279
 - ValueField, 279
 - ValueLengthField, 279
 - ValuePtr, 273
 - Write, 278
- gdcmm::DataElementException, 279
- gdcmm::DataEvent, 280
 - ~DataEvent, 282
 - CheckEvent, 282
 - DataEvent, 282
 - GetData, 282
 - GetDataLength, 282
 - GetEventName, 282
 - MakeObject, 282
 - Self, 281
 - SetData, 282
 - Superclass, 281
- gdcmm::DataSet, 282
 - Begin, 285
 - CSAHeader, 289
 - Clear, 285
 - ComputeDataElement, 285
 - ComputeGroupLength, 285
 - ConstIterator, 285
 - DataElementSet, 285
 - End, 286
 - FindDataElement, 286
 - FindNextDataElement, 286
 - GetDEEnd, 287
 - GetDES, 287
 - GetDataElement, 286, 287
 - GetLength, 287
 - GetMediaStorage, 287
 - GetPrivateCreator, 287
 - Insert, 287
 - InsertDataElement, 287
 - IsEmpty, 287
 - Iterator, 285
 - operator<<, 289
 - operator(), 288
 - operator=, 288
 - Print, 288

- Read, [288](#)
- ReadNested, [288](#)
- ReadSelectedTags, [288](#)
- ReadSelectedTagsWithLength, [288](#)
- ReadUpToTag, [288](#)
- ReadUpToTagWithLength, [288](#)
- ReadWithLength, [288](#)
- Remove, [288](#)
- Replace, [288](#)
- ReplaceEmpty, [288](#)
- Size, [289](#)
- SizeType, [285](#)
- Write, [289](#)
- gdcmm::DataSetEvent, [289](#)
 - ~DataSetEvent, [291](#)
 - CheckEvent, [291](#)
 - DataSetEvent, [291](#)
 - GetDataSet, [291](#)
 - GetEventName, [291](#)
 - MakeObject, [291](#)
 - Self, [290](#)
 - Superclass, [290](#)
- gdcmm::DataSetHelper, [291](#)
 - ComputeVR, [291](#)
- gdcmm::Decoder, [292](#)
 - ~Decoder, [292](#)
 - CanDecode, [293](#)
 - Decode, [293](#)
 - DecodeByStreams, [293](#)
- gdcmm::DefinedTerms, [293](#)
 - DefinedTerms, [294](#)
- gdcmm::Defs, [294](#)
 - ~Defs, [295](#)
 - Defs, [295](#)
 - GetIODFromFile, [295](#)
 - GetIODNameFromMediaStorage, [295](#)
 - GetIODs, [295](#)
 - GetMacros, [295](#)
 - GetModules, [295](#)
 - GetTypeFromTag, [295](#)
 - Global, [296](#)
 - IsEmpty, [295](#)
 - LoadDefaults, [295](#)
 - LoadFromFile, [295](#)
 - Verify, [295](#), [296](#)
- gdcmm::DeltaEncodingCodec, [296](#)
 - ~DeltaEncodingCodec, [297](#)
 - CanDecode, [297](#)
 - Decode, [297](#)
 - DeltaEncodingCodec, [297](#)
- gdcmm::Dict, [301](#)
 - AddDictEntry, [302](#)
 - Begin, [302](#)
 - ConstIterator, [302](#)
 - Dict, [302](#)
 - Dicts, [303](#)
 - End, [302](#)
 - GetDictEntry, [302](#)
 - GetDictEntryByKeyword, [302](#)
 - GetDictEntryByName, [302](#)
 - GetKeywordFromTag, [302](#)
 - IsEmpty, [303](#)
 - Iterator, [302](#)
 - LoadDefault, [303](#)
 - MapDictEntry, [302](#)
 - operator<<, [303](#)
- gdcmm::DictConverter, [303](#)
 - ~DictConverter, [304](#)
 - AddGroupLength, [304](#)
 - Convert, [304](#)
 - ConvertToCXX, [304](#)
 - ConvertToXML, [304](#)
 - DictConverter, [304](#)
 - GetDictName, [305](#)
 - GetInputFilename, [305](#)
 - GetOutputFilename, [305](#)
 - GetOutputType, [305](#)
 - OutputTypes, [304](#)
 - ReadVM, [305](#)
 - ReadVR, [305](#)
 - Readuint16, [305](#)
 - SetDictName, [305](#)
 - SetInputFileName, [305](#)
 - SetOutputFileName, [305](#)
 - SetOutputType, [305](#)
 - WriteFooter, [305](#)
 - WriteHeader, [305](#)
- gdcmm::DictEntry, [305](#)
 - DictEntry, [306](#)
 - GetKeyword, [306](#)
 - GetName, [306](#)
 - GetRetired, [306](#)
 - GetVM, [307](#)
 - GetVR, [307](#)
 - IsUnique, [307](#)
 - operator<<, [308](#)
 - SetElementXX, [307](#)
 - SetGroupXX, [307](#)
 - SetKeyword, [307](#)
 - SetName, [307](#)
 - SetRetired, [307](#)
 - SetVM, [307](#)
 - SetVR, [307](#)
- gdcmm::DictPrinter, [308](#)
 - ~DictPrinter, [309](#)
 - DictPrinter, [309](#)
 - Print, [310](#)
 - PrintDataElement2, [310](#)

- PrintDataSet2, 310
- gdcm::Dicts, 310
 - ~Dicts, 311
 - ConstructorType, 311
 - Dicts, 311
 - GetCSAHeaderDict, 311
 - GetConstructorString, 311
 - GetDictEntry, 311, 312
 - GetPrivateDict, 312
 - GetPublicDict, 312
 - Global, 312
 - IsEmpty, 312
 - LoadDefaults, 312
 - operator<<, 312
- gdcm::DirectionCosines, 314
 - ~DirectionCosines, 315
 - ComputeDistAlongNormal, 315
 - Cross, 315
 - CrossDot, 315
 - DirectionCosines, 315
 - Dot, 315
 - IsValid, 315
 - Normalize, 315
 - operator const double *, 315
 - Print, 315
 - SetFromString, 316
- gdcm::Directory, 316
 - ~Directory, 317
 - Directory, 317
 - Explore, 317
 - FilenameType, 317
 - FileNamesType, 317
 - GetDirectories, 317
 - GetFileNames, 317
 - GetToplevel, 318
 - Load, 318
 - operator<<, 318
 - Print, 318
- gdcm::DirectoryHelper, 318
 - GetCTImageSeriesUIDs, 319
 - GetFileNamesFromSeriesUIDs, 319
 - GetFrameOfReference, 319
 - GetMRImageSeriesUIDs, 319
 - GetRTStructSeriesUIDs, 319
 - GetSOPClassUID, 320
 - GetSeriesUIDsBySOPClassUID, 320
 - GetStringValueFromTag, 320
 - LoadImageFromFiles, 320
 - RetrieveSOPInstanceUIDFromIndex, 320
 - RetrieveSOPInstanceUIDFromZPosition, 320
- gdcm::DummyValueGenerator, 320
 - Generate, 320
- gdcm::Dumper, 321
 - ~Dumper, 322
- Dumper, 322
- gdcm::Element
 - GetAsDataElement, 325
 - GetLength, 325
 - GetVM, 325
 - GetVR, 325
 - GetValue, 325
 - GetValues, 325
 - Internal, 325
 - Print, 325
 - Read, 325
 - Set, 325
 - SetFromDataElement, 325
 - SetNoSwap, 325
 - SetValue, 325
 - Type, 325
 - Write, 325
- gdcm::Element< TVR, TVM >, 323
- gdcm::Element< TVR, VM::VM1_2 >, 326
 - Parent, 327
 - SetLength, 327
- gdcm::Element< TVR, VM::VM1_n >, 327
 - ~Element, 328
 - Element, 328
 - GetAsDataElement, 328
 - GetLength, 328
 - GetVM, 328
 - GetVR, 328
 - GetValue, 328
 - operator=, 329
 - Print, 329
 - Read, 329
 - Set, 329
 - SetArray, 329
 - SetFromDataElement, 329
 - SetLength, 329
 - SetNoSwap, 329
 - SetValue, 329
 - Type, 328
 - Write, 329
 - WriteASCII, 329
- gdcm::Element< TVR, VM::VM2_2n >, 329
 - Parent, 331
 - SetLength, 331
- gdcm::Element< TVR, VM::VM2_n >, 331
 - Parent, 332
 - SetLength, 332
- gdcm::Element< TVR, VM::VM3_3n >, 332
 - Parent, 334
 - SetLength, 334
- gdcm::Element< TVR, VM::VM3_n >, 334
 - Parent, 335
 - SetLength, 335
- gdcm::Element< VR::AS, VM::VM5 >, 335

- GetLength, 336
- Internal, 336
- Print, 336
- gdcmm::Element< VR::OB, VM::VM1 >, 336
- gdcmm::Element< VR::OW, VM::VM1 >, 337
- gdcmm::ElementDisableCombinations< TVR, TVM >, 339
- gdcmm::ElementDisableCombinations< VR::OB, VM::VM1-
_n >, 340
- gdcmm::ElementDisableCombinations< VR::OW, VM::V-
M1_n >, 340
- gdcmm::EncapsulatedDocument, 340
 - EncapsulatedDocument, 340
- gdcmm::EncodingImplementation< T >, 341
- gdcmm::EncodingImplementation< VR::VRASCII >, 341
 - Read, 341
 - ReadComputeLength, 341
 - ReadNoSwap, 342
 - Write, 342
- gdcmm::EncodingImplementation< VR::VRBINARY >, 342
 - Read, 342
 - ReadComputeLength, 342
 - ReadNoSwap, 343
 - Write, 343
- gdcmm::EndEvent, 343
- gdcmm::EnumeratedValues, 344
 - EnumeratedValues, 345
- gdcmm::Event, 345
 - ~Event, 346
 - CheckEvent, 346
 - Event, 346
 - GetEventName, 346
 - MakeObject, 346
 - Print, 346
- gdcmm::Exception, 347
 - ~Exception, 348
 - Exception, 348
 - GetDescription, 348
 - what, 348
- gdcmm::ExitEvent, 348
- gdcmm::ExplicitDataElement, 350
 - GetLength, 351
 - Read, 351
 - ReadPreValue, 351
 - ReadValue, 351
 - ReadWithLength, 351
 - Write, 351
- gdcmm::ExplicitImplicitDataElement, 351
 - GetLength, 353
 - Read, 353
 - ReadPreValue, 353
 - ReadValue, 353
 - ReadWithLength, 353
- gdcmm::Fiducials, 353
 - Fiducials, 354
- gdcmm::File, 354
 - ~File, 356
 - File, 356
 - GetDataSet, 356
 - GetHeader, 356
 - operator<<, 357
 - Read, 357
 - SetDataSet, 357
 - SetHeader, 357
 - Write, 357
- gdcmm::FileAnonymizer, 357
 - ~FileAnonymizer, 359
 - Empty, 359
 - FileAnonymizer, 359
 - Remove, 359
 - Replace, 359
 - SetInputFileName, 359
 - SetOutputFileName, 360
 - Write, 360
- gdcmm::FileDerivation, 360
 - ~FileDerivation, 361
 - AddDerivationDescription, 361
 - AddPurposeOfReferenceCodeSequence, 361
 - AddReference, 361
 - AddSourceImageSequence, 361
 - Derive, 361
 - FileDerivation, 361
 - GetFile, 361, 362
 - SetDerivationCodeSequenceCodeValue, 362
 - SetDerivationDescription, 362
 - SetFile, 362
 - SetPurposeOfReferenceCodeSequenceCodeValue,
362
- gdcmm::FileExplicitFilter, 362
 - ~FileExplicitFilter, 363
 - Change, 363
 - ChangeFMI, 364
 - FileExplicitFilter, 363
 - GetFile, 364
 - ProcessDataSet, 364
 - SetChangePrivateTags, 364
 - SetFile, 364
 - SetRecomputeItemLength, 364
 - SetRecomputeSequenceLength, 364
 - SetUseVRUN, 364
- gdcmm::FileMetaInformation, 364
 - ~FileMetaInformation, 367
 - AppendImplementationClassUID, 367
 - ComputeDataSetMediaStorageSOPClass, 367
 - ComputeDataSetTransferSyntax, 367
 - DataSetMS, 369
 - DataSetTS, 369
 - Default, 367
 - FileMetaInformation, 367

- FillFromDataSet, 367
- GetDataSetTransferSyntax, 367
- GetFileMetaInformationVersion, 367
- GetFullLength, 368
- GetGDCMImplementationClassUID, 368
- GetGDCMImplementationVersionName, 368
- GetGDCMSourceApplicationEntityTitle, 368
- GetImplementationClassUID, 368
- GetImplementationVersionName, 368
- GetMediaStorage, 368
- GetMetaInformationTS, 368
- GetPreamble, 368
- GetSourceApplicationEntityTitle, 368
- Insert, 368
- IsValid, 368
- MetaInformationTS, 369
- operator<<, 369
- Read, 368
- ReadCompat, 368
- ReadCompatInternal, 368
- Replace, 368
- SetDataSetTransferSyntax, 369
- SetImplementationClassUID, 369
- SetImplementationVersionName, 369
- SetPreamble, 369
- SetSourceApplicationEntityTitle, 369
- Write, 369
- gdcmm::FileSet, 374
 - AddFile, 375
 - FileSet, 375
 - FileType, 375
 - FilesType, 375
 - GetFiles, 375
 - operator<<, 375
 - SetFiles, 375
- gdcmm::FileWithName, 375
 - FileWithName, 377
 - filename, 377
- gdcmm::Filename, 370
 - EndWith, 371
 - Filename, 371
 - GetExtension, 371
 - GetFileName, 371
 - GetName, 371
 - GetPath, 371
 - IsEmpty, 371
 - IsIdentical, 371
 - Join, 371
 - operator const char *, 371
 - ToUnixSlashes, 371
 - ToWindowsSlashes, 371
- gdcmm::FilenameGenerator, 372
 - ~FilenameGenerator, 373
 - FilenameGenerator, 373
- FilenameType, 373
- FileNamesType, 373
- Generate, 373
- GetFilename, 373
- GetFileNames, 373
- GetNumberOfFileNames, 373
- GetPattern, 373
- GetPrefix, 374
- SetNumberOfFileNames, 374
- SetPattern, 374
- SetPrefix, 374
- SizeType, 373
- gdcmm::FindPatientRootQuery, 377
 - FindPatientRootQuery, 378
 - GetAbstractSyntaxUID, 378
 - GetTagListByLevel, 378
 - InitializeDataSet, 379
 - QueryFactory, 379
 - ValidateQuery, 379
- gdcmm::FindStudyRootQuery, 379
 - FindStudyRootQuery, 381
 - GetAbstractSyntaxUID, 381
 - GetTagListByLevel, 381
 - InitializeDataSet, 381
 - QueryFactory, 381
 - ValidateQuery, 381
- gdcmm::Fragment, 381
 - Fragment, 383
 - GetLength, 383
 - operator<<, 384
 - Read, 383
 - ReadBacktrack, 383
 - ReadPreValue, 383
 - ReadValue, 383
 - Write, 383
- gdcmm::Global, 384
 - ~Global, 385
 - Append, 385
 - GetDefs, 385
 - GetDicts, 385
 - GetInstance, 385
 - Global, 385
 - LoadResourcesFiles, 386
 - Locate, 386
 - operator<<, 386
 - Prepend, 386
- gdcmm::GroupDict, 386
 - ~GroupDict, 387
 - Add, 387
 - GetAbbreviation, 387
 - GetName, 387
 - GroupDict, 387
 - GroupStringVector, 387
 - Insert, 387

- operator<<, 388
- Size, 388
- gdcmm::IOD, 438
 - AddIODEntry, 439
 - Clear, 439
 - GetIODEntry, 439
 - GetNumberOfIODs, 439
 - GetTypeFromTag, 439
 - IOD, 438
 - MapIODEntry, 438
 - operator<<, 439
 - SizeType, 438
- gdcmm::IODEntry, 439
 - GetIE, 440
 - GetName, 440
 - GetRef, 440
 - GetUsage, 440
 - GetUsageType, 441
 - IODEntry, 440
 - operator<<, 441
 - SetIE, 441
 - SetName, 441
 - SetRef, 441
 - SetUsage, 441
- gdcmm::IODs, 441
 - AddIOD, 442
 - Begin, 442
 - Clear, 442
 - End, 442
 - GetIOD, 442
 - IODMapType, 442
 - IODMapTypeConstIterator, 442
 - IODName, 442
 - IODs, 442
 - operator<<, 442
- gdcmm::IPPSorter, 442
 - ~IPPSorter, 444
 - ComputeZSpacing, 446
 - DirCosTolerance, 446
 - DropDuplicatePositions, 446
 - GetDirectionCosinesTolerance, 444
 - GetZSpacing, 444
 - GetZSpacingTolerance, 445
 - IPPSorter, 444
 - SetComputeZSpacing, 445
 - SetDirectionCosinesTolerance, 445
 - SetDropDuplicatePositions, 445
 - SetZSpacingTolerance, 445
 - Sort, 445
 - ZSpacing, 446
 - ZTolerance, 446
- gdcmm::IconImageFilter, 388
 - ~IconImageFilter, 389
 - Extract, 389
 - ExtractIconImages, 389
 - ExtractVeprolIconImages, 389
 - GetFile, 389
 - GetIconImage, 389
 - GetNumberOfIconImages, 390
 - IconImageFilter, 389
 - SetFile, 390
- gdcmm::IconImageGenerator, 390
 - ~IconImageGenerator, 391
 - AutoPixelMinMax, 391
 - ConvertRGBToPaletteColor, 391
 - Generate, 391
 - GetIconImage, 391
 - GetPixmap, 392
 - IconImageGenerator, 391
 - SetOutputDimensions, 392
 - SetOutsideValuePixel, 392
 - SetPixelMinMax, 392
 - SetPixmap, 392
- gdcmm::Image, 393
 - ~Image, 395
 - GetDirectionCosines, 395
 - GetIntercept, 395
 - GetOrigin, 395
 - GetSlope, 396
 - GetSpacing, 396
 - Image, 395
 - Print, 396
 - SetDirectionCosines, 396
 - SetIntercept, 396
 - SetOrigin, 396
 - SetSlope, 396
 - SetSpacing, 396
- gdcmm::ImageApplyLookupTable, 397
 - ~ImageApplyLookupTable, 399
 - Apply, 399
 - ImageApplyLookupTable, 399
- gdcmm::ImageChangePhotometricInterpretation, 399
 - ~ImageChangePhotometricInterpretation, 402
 - Change, 402
 - ChangeMonochrome, 402
 - GetPhotometricInterpretation, 402
 - ImageChangePhotometricInterpretation, 402
 - RGB2YBR, 402
 - SetPhotometricInterpretation, 402
 - YBR2RGB, 403
- gdcmm::ImageChangePlanarConfiguration, 403
 - ~ImageChangePlanarConfiguration, 405
 - Change, 405
 - GetPlanarConfiguration, 405
 - ImageChangePlanarConfiguration, 405
 - RGBPixelsToRGBPlanes, 405
 - RGBPlanesToRGBPixels, 405
 - SetPlanarConfiguration, 406

- gdcm::ImageChangeTransferSyntax, 406
 - ~ImageChangeTransferSyntax, 408
 - Change, 408
 - GetTransferSyntax, 408
 - ImageChangeTransferSyntax, 408
 - SetCompressIconImage, 408
 - SetForce, 409
 - SetTransferSyntax, 409
 - SetUserCodec, 409
 - TryJPEG2000Codec, 409
 - TryJPEGCodec, 409
 - TryJPEGLSCodec, 409
 - TryRAWCodec, 409
 - TryRLECodec, 409
- gdcm::ImageCodec, 410
 - ~ImageCodec, 412
 - CanCode, 412
 - CanDecode, 412
 - Decode, 412
 - DecodeByStreams, 412
 - Dimensions, 414
 - DoByteSwap, 413
 - DoInvertMonochrome, 413
 - DoOverlayCleanup, 413
 - DoPaddedCompositePixelCode, 413
 - DoPlanarConfiguration, 413
 - DoSimpleCopy, 413
 - DoYBR, 413
 - GetDimensions, 413
 - GetHeaderInfo, 413
 - GetLUT, 413
 - GetLossyFlag, 413
 - GetNeedByteSwap, 413
 - GetNumberOfDimensions, 413
 - GetPhotometricInterpretation, 413
 - GetPixelFormat, 413
 - GetPlanarConfiguration, 413
 - ImageChangePhotometricInterpretation, 414
 - ImageCodec, 412
 - IsLossy, 413
 - IsValid, 413
 - LUT, 415
 - LUTPtr, 412
 - LossyFlag, 415
 - NeedByteSwap, 415
 - NeedOverlayCleanup, 415
 - NumberOfDimensions, 415
 - PF, 415
 - PI, 415
 - PlanarConfiguration, 415
 - RequestPaddedCompositePixelCode, 415
 - RequestPlanarConfiguration, 415
 - SetDimensions, 414
 - SetLUT, 414
 - SetLossyFlag, 414
 - SetNeedByteSwap, 414
 - SetNeedOverlayCleanup, 414
 - SetNumberOfDimensions, 414
 - SetPhotometricInterpretation, 414
 - SetPixelFormat, 414
 - SetPlanarConfiguration, 414
- gdcm::ImageConverter, 415
 - ~ImageConverter, 416
 - Convert, 416
 - GetOutput, 416
 - ImageConverter, 416
 - SetInput, 416
- gdcm::ImageFragmentSplitter, 416
 - ~ImageFragmentSplitter, 418
 - GetFragmentSizeMax, 418
 - ImageFragmentSplitter, 418
 - SetForce, 418
 - SetFragmentSizeMax, 418
 - Split, 418
- gdcm::ImageHelper, 418
 - ComputeSpacingFromImagePositionPatient, 419
 - GetDimensionsValue, 419
 - GetDirectionCosinesFromDataSet, 420
 - GetDirectionCosinesValue, 420
 - GetForcePixelSpacing, 420
 - GetForceRescaleInterceptSlope, 420
 - GetLUT, 420
 - GetOriginValue, 420
 - GetPhotometricInterpretationValue, 420
 - GetPixelFormatValue, 420
 - GetPlanarConfigurationValue, 420
 - GetPointerFromElement, 420
 - GetRescaleInterceptSlopeValue, 420
 - GetSpacingTagFromMediaStorage, 420
 - GetSpacingValue, 421
 - GetZSpacingTagFromMediaStorage, 421
 - SetDimensionsValue, 421
 - SetDirectionCosinesValue, 421
 - SetForcePixelSpacing, 421
 - SetForceRescaleInterceptSlope, 421
 - SetOriginValue, 421
 - SetRescaleInterceptSlopeValue, 421
 - SetSpacingValue, 421
- gdcm::ImageReader, 421
 - ~ImageReader, 424
 - GetImage, 424
 - ImageReader, 424
 - Read, 424
 - ReadACRNEMAIImage, 425
 - ReadImage, 425
- gdcm::ImageRegionReader, 425
 - ~ImageRegionReader, 427
 - ComputeBufferLength, 427

- GetRegion, [427](#)
- ImageRegionReader, [427](#)
- Read, [427](#)
- ReadInformation, [427](#)
- ReadIntoBuffer, [427](#)
- SetRegion, [428](#)
- gdcmm::ImageToImageFilter, [428](#)
- ~ImageToImageFilter, [430](#)
- GetInput, [430](#)
- GetOutput, [430](#)
- ImageToImageFilter, [430](#)
- gdcmm::ImageWriter, [430](#)
- ~ImageWriter, [432](#)
- GetImage, [432](#)
- ImageWriter, [432](#)
- Write, [432](#)
- gdcmm::ImplicitDataElement, [435](#)
- GetLength, [436](#)
- Read, [436](#)
- ReadPreValue, [436](#)
- ReadValue, [436](#)
- ReadWithLength, [436](#)
- Write, [436](#)
- gdcmm::InitializeEvent, [436](#)
- gdcmm::Item, [446](#)
- Clear, [448](#)
- FindDataElement, [448](#)
- GetDataElement, [448](#)
- GetLength, [448](#)
- GetNestedDataSet, [448](#), [449](#)
- InsertDataElement, [449](#)
- Item, [448](#)
- operator<<, [449](#)
- Read, [449](#)
- SetNestedDataSet, [449](#)
- Write, [449](#)
- gdcmm::IterationEvent, [449](#)
- gdcmm::JPEG12Codec, [451](#)
- ~JPEG12Codec, [452](#)
- DecodeByStreams, [452](#)
- GetHeaderInfo, [452](#)
- InternalCode, [452](#)
- IsStateSuspension, [452](#)
- JPEG12Codec, [452](#)
- gdcmm::JPEG16Codec, [453](#)
- ~JPEG16Codec, [454](#)
- DecodeByStreams, [454](#)
- GetHeaderInfo, [454](#)
- InternalCode, [454](#)
- IsStateSuspension, [454](#)
- JPEG16Codec, [454](#)
- gdcmm::JPEG2000Codec, [455](#)
- ~JPEG2000Codec, [456](#)
- Bitmap, [457](#)
- CanCode, [456](#)
- CanDecode, [456](#)
- Code, [457](#)
- Decode, [457](#)
- DecodeByStreams, [457](#)
- DecodeExtent, [457](#)
- GetHeaderInfo, [457](#)
- GetQuality, [457](#)
- GetRate, [457](#)
- ImageRegionReader, [457](#)
- JPEG2000Codec, [456](#)
- SetNumberOfResolutions, [457](#)
- SetQuality, [457](#)
- SetRate, [457](#)
- SetReversible, [457](#)
- SetTileSize, [457](#)
- gdcmm::JPEG8Codec, [458](#)
- ~JPEG8Codec, [459](#)
- DecodeByStreams, [459](#)
- GetHeaderInfo, [459](#)
- InternalCode, [459](#)
- IsStateSuspension, [459](#)
- JPEG8Codec, [459](#)
- gdcmm::JPEGCodec, [460](#)
- ~JPEGCodec, [462](#)
- BitSample, [463](#)
- CanCode, [462](#)
- CanDecode, [462](#)
- Code, [462](#)
- ComputeOffsetTable, [462](#)
- Decode, [462](#)
- DecodeByStreams, [462](#)
- DecodeExtent, [462](#)
- GetHeaderInfo, [463](#)
- GetLossless, [463](#)
- GetQuality, [463](#)
- ImageRegionReader, [463](#)
- IsStateSuspension, [463](#)
- IsValid, [463](#)
- JPEGCodec, [462](#)
- Lossless, [463](#)
- Quality, [463](#)
- SetBitSample, [463](#)
- SetLossless, [463](#)
- SetPixelFormat, [463](#)
- SetQuality, [463](#)
- gdcmm::JPEGLSCodec, [464](#)
- ~JPEGLSCodec, [466](#)
- CanCode, [466](#)
- CanDecode, [466](#)
- Code, [466](#)
- Decode, [466](#)
- DecodeExtent, [466](#)
- GetBufferLength, [466](#)

- GetHeaderInfo, 466
- GetLossless, 466
- ImageRegionReader, 467
- JPEGLSCodec, 466
- SetBufferLength, 466
- SetLossless, 466
- SetLossyError, 466
- gdcmm::KAKADUCodec, 467
 - ~KAKADUCodec, 468
 - CanCode, 468
 - CanDecode, 468
 - Code, 468
 - Decode, 469
 - KAKADUCodec, 468
- gdcmm::LO, 469
 - const_iterator, 471
 - const_reference, 471
 - const_reverse_iterator, 471
 - difference_type, 471
 - IsValid, 471
 - iterator, 471
 - LO, 471
 - pointer, 471
 - reference, 471
 - reverse_iterator, 471
 - size_type, 471
 - Superclass, 471
 - value_type, 471
- gdcmm::LookupTable, 474
 - ~LookupTable, 474
 - Allocate, 474
 - BitSample, 476
 - Clear, 474
 - Decode, 474
 - GetBitSample, 474
 - GetBufferAsRGBA, 474
 - GetLUT, 474
 - GetLUTDescriptor, 475
 - GetLUTLength, 475
 - GetPointer, 475
 - IncompleteLUT, 476
 - InitializeBlueLUT, 475
 - InitializeGreenLUT, 475
 - InitializeLUT, 475
 - InitializeRedLUT, 475
 - Initialized, 475
 - Internal, 476
 - LookupTable, 474
 - LookupTableType, 474
 - Print, 475
 - SetBlueLUT, 475
 - SetGreenLUT, 475
 - SetLUT, 475
 - SetRedLUT, 475
 - WriteBufferAsRGBA, 475
- gdcmm::MD5, 480
 - ~MD5, 481
 - Compute, 481
 - ComputeFile, 481
 - MD5, 481
- gdcmm::Macro, 476
 - AddMacroEntry, 477
 - ArrayIncludeMacrosType, 477
 - Clear, 477
 - FindMacroEntry, 477
 - GetMacroEntry, 477
 - GetName, 477
 - Macro, 477
 - MapModuleEntry, 477
 - operator<<, 478
 - SetName, 477
 - Verify, 477
- gdcmm::Macros, 478
 - AddMacro, 479
 - Clear, 479
 - GetMacro, 479
 - IsEmpty, 479
 - Macros, 479
 - ModuleMapType, 479
 - operator<<, 479
- gdcmm::MediaStorage, 481
 - GetMSString, 487
 - GetMSType, 487
 - GetModality, 487
 - GetModalityDimension, 487
 - GetNumberOfMSString, 487
 - GetNumberOfMSType, 487
 - GetNumberOfModality, 487
 - GetString, 487
 - GuessFromModality, 487
 - IsImage, 487
 - IsUndefined, 487
 - MSType, 484
 - MediaStorage, 487
 - ObjectType, 486
 - operator MSType, 488
 - operator<<, 488
 - SetFromDataSet, 488
 - SetFromFile, 488
 - SetFromHeader, 488
 - SetFromModality, 488
 - SetFromSourceImageSequence, 488
- gdcmm::MemberCommand
 - ~MemberCommand, 491
 - Execute, 491
 - m_ConstMemberFunction, 492
 - m_MemberFunction, 492
 - m_This, 492

- MemberCommand, 491
- New, 491
- Self, 490
- SetCallbackFunction, 491
- TConstMemberFunctionPointer, 490
- TMemberFunctionPointer, 491
- gdcmmemberCommand< T >, 488
- gdcmmeshPrimitive, 492
 - ~MeshPrimitive, 495
 - AddPrimitiveData, 495
 - GetMPTType, 495
 - GetMPTTypeString, 495
 - GetNumberOfPrimitivesData, 495
 - GetPrimitiveData, 495
 - GetPrimitiveType, 495
 - GetPrimitivesData, 495
 - MPTType, 494
 - MeshPrimitive, 495
 - PrimitiveData, 495
 - PrimitiveType, 495
 - PrimitivesData, 494
 - SetPrimitiveData, 495
 - SetPrimitiveType, 495
 - SetPrimitivesData, 495
- gdcmmodifiedEvent, 495
- gdcmmodule, 497
 - AddMacro, 498
 - AddModuleEntry, 498
 - ArrayIncludeMacrosType, 498
 - Clear, 498
 - FindModuleEntryInMacros, 498
 - GetModuleEntryInMacros, 498
 - GetName, 498
 - MapModuleEntry, 498
 - Module, 498
 - operator<<, 498
 - SetName, 498
 - Verify, 498
- gdcmmoduleEntry, 499
 - ~ModuleEntry, 500
 - DataElementType, 501
 - Description, 500
 - DescriptionField, 501
 - GetDescription, 501
 - GetName, 501
 - GetType, 501
 - ModuleEntry, 500
 - Name, 501
 - operator<<, 501
 - SetDescription, 501
 - SetName, 501
 - SetType, 501
- gdcmmodules, 501
 - AddModule, 502
 - Clear, 502
 - GetModule, 502
 - IsEmpty, 502
 - ModuleMapType, 502
 - Modules, 502
 - operator<<, 503
- gdcmmovePatientRootQuery, 503
 - GetAbstractSyntaxUID, 504
 - GetTagListByLevel, 504
 - InitializeDataSet, 504
 - MovePatientRootQuery, 504
 - QueryFactory, 505
 - ValidateQuery, 504
- gdcmmoveStudyRootQuery, 505
 - GetAbstractSyntaxUID, 506
 - GetTagListByLevel, 506
 - InitializeDataSet, 507
 - MoveStudyRootQuery, 506
 - QueryFactory, 507
 - ValidateQuery, 507
- gdcmnestedModuleEntries, 507
 - AddModuleEntry, 509
 - GetModuleEntry, 509
 - GetNumberOfModuleEntries, 509
 - NestedModuleEntries, 509
 - operator<<, 509
 - SizeType, 509
- gdcmnotionEvent, 509
- gdcmobject, 510
 - ~Object, 512
 - Object, 512
 - operator<<, 512
 - operator=, 512
 - Print, 512
 - Register, 512
 - SmartPointer, 512
 - UnRegister, 512
- gdcmorientation, 513
 - ~Orientation, 514
 - GetLabel, 514
 - GetMajorAxisFromPatientRelativeDirectionCosine, 514
 - GetObliquityThresholdCosineValue, 514
 - GetType, 514
 - operator<<, 514
 - Orientation, 514
 - OrientationType, 514
 - Print, 514
 - SetObliquityThresholdCosineValue, 514
- gdcmoverlay, 515
 - ~Overlay, 518
 - Decode, 518
 - Decompress, 518
 - GetBitPosition, 518

- GetBitsAllocated, 518
- GetBuffer, 518
- GetColumns, 518
- GetDescription, 518
- GetGroup, 518
- GetOrigin, 518
- GetOverlayData, 518
- GetOverlayTypeAsString, 519
- GetOverlayTypeFromString, 519
- GetRows, 519
- GetType, 519
- GetTypeAsEnum, 519
- GetUnpackBuffer, 519
- GetUnpackBufferLength, 519
- GrabOverlayFromPixelData, 519
- IsEmpty, 519
- IsInPixelData, 519
- IsZero, 519
- Overlay, 518
- OverlayType, 517
- Print, 519
- SetBitPosition, 520
- SetBitsAllocated, 520
- SetColumns, 520
- SetDescription, 520
- SetFrameOrigin, 520
- SetGroup, 520
- SetNumberOfFrames, 520
- SetOrigin, 520
- SetOverlay, 520
- SetRows, 520
- SetType, 520
- Update, 521
- gdcmm::PDBelement, 528
 - GetName, 529
 - GetValue, 529
 - NameField, 529
 - operator<<, 529
 - operator==, 529
 - PDBelement, 529
 - SetName, 529
 - SetValue, 529
 - ValueField, 529
- gdcmm::PDBHeader, 530
 - ~PDBHeader, 531
 - FindPDBelementByName, 531
 - GetPDBelement, 531
 - GetPDBelementByName, 531
 - GetPDBInfoTag, 531
 - LoadFromDataElement, 531
 - operator<<, 531
 - PDBHeader, 531
 - Print, 531
- gdcmm::PDFCodec, 532
 - ~PDFCodec, 533
 - CanCode, 533
 - CanDecode, 533
 - Decode, 533
 - PDFCodec, 533
- gdcmm::PGXCodec, 536
 - ~PGXCodec, 537
 - CanCode, 537
 - CanDecode, 537
 - GetHeaderInfo, 537
 - PGXCodec, 537
 - Read, 538
 - Write, 538
- gdcmm::PNMCodec, 557
 - ~PNMCodec, 559
 - CanCode, 559
 - CanDecode, 559
 - GetBufferLength, 559
 - GetHeaderInfo, 559
 - PNMCodec, 559
 - Read, 559
 - SetBufferLength, 559
 - Write, 559
- gdcmm::PVRGCodec, 579
 - ~PVRGCodec, 580
 - CanCode, 580
 - CanDecode, 580
 - Code, 580
 - Decode, 580
 - PVRGCodec, 580
- gdcmm::ParseException, 521
 - ~ParseException, 522
 - GetLastElement, 522
 - operator=, 522
 - ParseException, 522
 - SetLastElement, 522
- gdcmm::Parser, 523
 - ~Parser, 524
 - EndElementHandler, 524
 - ErrorType, 524
 - GetBuffer, 524
 - GetCurrentByteIndex, 524
 - GetErrorCode, 524
 - GetErrorString, 524
 - GetUserData, 524
 - Parse, 524
 - ParseBuffer, 525
 - Parser, 524
 - Process, 525
 - SetElementHandler, 525
 - SetUserData, 525
 - StartElementHandler, 524
- gdcmm::Patient, 525
 - Patient, 525

- gdcmm::PersonName, 535
 - Component, 535
 - GetMaxLength, 535
 - GetNumberOfComponents, 535
 - MaxLength, 536
 - MaxNumberOfComponents, 536
 - Padding, 536
 - Print, 535
 - Separator, 536
 - SetBlob, 535
 - SetComponents, 535
- gdcmm::PhotometricInterpretation, 538
 - GetPIString, 539
 - GetPIType, 539
 - GetSamplesPerPixel, 540
 - GetString, 540
 - GetType, 540
 - IsLossless, 540
 - IsLossy, 540
 - IsRetired, 540
 - IsSameColorSpace, 540
 - operator PIType, 540
 - operator<=, 540
 - PIType, 539
 - PhotometricInterpretation, 539
- gdcmm::PixelFormat, 540
 - ~PixelFormat, 542
 - Bitmap, 545
 - GetBitsAllocated, 542
 - GetBitsStored, 543
 - GetHighBit, 543
 - GetMax, 543
 - GetMin, 543
 - GetPixelRepresentation, 543
 - GetPixelSize, 543
 - GetSamplesPerPixel, 543
 - GetScalarType, 544
 - GetScalarTypeAsString, 544
 - IsValid, 544
 - operator ScalarType, 544
 - operator<=, 545
 - operator==, 544
 - PixelFormat, 542
 - Print, 544
 - ScalarType, 542
 - SetBitsAllocated, 544
 - SetBitsStored, 544
 - SetHighBit, 544
 - SetPixelRepresentation, 544
 - SetSamplesPerPixel, 544
 - SetScalarType, 544
 - Validate, 545
- gdcmm::Pixmap, 545
 - ~Pixmap, 547
 - AreOverlaysInPixelData, 547
 - Curves, 548
 - GetCurve, 547
 - GetIconImage, 548
 - GetNumberOfCurves, 548
 - GetNumberOfOverlays, 548
 - GetOverlay, 548
 - Icon, 548
 - Overlays, 548
 - Pixmap, 547
 - Print, 548
 - RemoveOverlay, 548
 - SetIconImage, 548
 - SetNumberOfCurves, 548
 - SetNumberOfOverlays, 548
- gdcmm::PixmapReader, 548
 - ~PixmapReader, 551
 - GetPixmap, 551
 - PixelData, 552
 - PixmapReader, 551
 - Read, 551
 - ReadACRNEMAImage, 551
 - ReadImage, 551
 - ReadImageInternal, 551
- gdcmm::PixmapToPixmapFilter, 552
 - ~PixmapToPixmapFilter, 553
 - GetInput, 554
 - GetOutput, 554
 - GetOutputAsPixmap, 554
 - PixmapToPixmapFilter, 553
- gdcmm::PixmapWriter, 554
 - ~PixmapWriter, 556
 - DoIconImage, 556
 - GetImage, 556
 - GetPixmap, 556
 - PixelData, 557
 - PixmapWriter, 556
 - PrepareWrite, 556
 - SetImage, 556
 - SetPixmap, 557
 - Write, 557
- gdcmm::Preamble, 560
 - ~Preamble, 560
 - Clear, 560
 - Create, 561
 - GetInternal, 561
 - GetLength, 561
 - IsEmpty, 561
 - IsValid, 561
 - operator<=, 561
 - operator=, 561
 - Preamble, 560
 - Print, 561
 - Read, 561

- Remove, [561](#)
- Valid, [561](#)
- Write, [561](#)
- gdcmm::PresentationContext, [561](#)
 - AddTransferSyntax, [562](#)
 - GetAbstractSyntax, [562](#)
 - GetNumberOfTransferSyntaxes, [562](#)
 - GetPresentationContextID, [562](#)
 - GetTransferSyntax, [562](#)
 - operator==, [562](#)
 - PresentationContext, [562](#)
 - Print, [562](#)
 - SetAbstractSyntax, [562](#)
 - SetPresentationContextID, [562](#)
 - SizeType, [562](#)
 - TransferSyntaxArrayType, [562](#)
- gdcmm::PresentationContextGenerator, [564](#)
 - AddPresentationContext, [565](#)
 - GenerateFromFilenames, [565](#)
 - GenerateFromUID, [565](#)
 - GetDefaultTransferSyntax, [565](#)
 - GetPresentationContexts, [566](#)
 - PresentationContextArrayType, [565](#)
 - PresentationContextGenerator, [565](#)
 - SetDefaultTransferSyntax, [566](#)
 - SetMergeModeToAbstractSyntax, [566](#)
 - SetMergeModeToTransferSyntax, [566](#)
 - SizeType, [565](#)
- gdcmm::Printer, [570](#)
 - ~Printer, [572](#)
 - F, [573](#)
 - GetPrintStyle, [572](#)
 - MaxPrintLength, [573](#)
 - Print, [572](#)
 - PrintDataElement, [572](#)
 - PrintDataSet, [572](#)
 - PrintSQ, [572](#)
 - PrintStyle, [573](#)
 - PrintStyles, [572](#)
 - Printer, [572](#)
 - SetColor, [573](#)
 - SetFile, [573](#)
 - SetStyle, [573](#)
- gdcmm::PrivateDict, [573](#)
 - ~PrivateDict, [574](#)
 - AddDictEntry, [574](#)
 - Dicts, [574](#)
 - FindDictEntry, [574](#)
 - GetDictEntry, [574](#)
 - IsEmpty, [574](#)
 - LoadDefault, [574](#)
 - operator<<, [574](#)
 - PrintXML, [574](#)
 - PrivateDict, [574](#)
 - RemoveDictEntry, [574](#)
- gdcmm::PrivateTag, [575](#)
 - GetOwner, [576](#)
 - operator<, [576](#)
 - operator<<, [576](#)
 - PrivateTag, [576](#)
 - ReadFromCommaSeparatedString, [576](#)
 - SetOwner, [576](#)
- gdcmm::ProgressEvent, [576](#)
 - ~ProgressEvent, [578](#)
 - CheckEvent, [578](#)
 - GetEventName, [578](#)
 - GetProgress, [578](#)
 - MakeObject, [578](#)
 - ProgressEvent, [578](#)
 - Self, [578](#)
 - SetProgress, [578](#)
 - Superclass, [578](#)
- gdcmm::PythonFilter, [581](#)
 - ~PythonFilter, [581](#)
 - GetFile, [581](#)
 - PythonFilter, [581](#)
 - SetDicts, [581](#)
 - SetFile, [581](#)
 - ToPyObject, [581](#)
 - UseDictAlways, [581](#)
- gdcmm::QueryBase, [582](#)
 - ~QueryBase, [583](#)
 - GetAllRequiredTags, [583](#)
 - GetAllTags, [583](#)
 - GetHierarchicalSearchTags, [583](#)
 - GetName, [583](#)
 - GetOptionalTags, [583](#)
 - GetQueryLevel, [583](#)
 - GetRequiredTags, [583](#)
 - GetUniqueTags, [583](#)
- gdcmm::QueryFactory, [584](#)
 - GetCharacterFromCurrentLocale, [584](#)
 - ListCharSets, [584](#)
 - ProduceCharacterSetDataElement, [584](#)
 - ProduceQuery, [585](#)
- gdcmm::QueryImage, [585](#)
 - GetHierarchicalSearchTags, [586](#)
 - GetName, [586](#)
 - GetOptionalTags, [586](#)
 - GetQueryLevel, [586](#)
 - GetRequiredTags, [587](#)
 - GetUniqueTags, [587](#)
- gdcmm::QueryPatient, [587](#)
 - GetHierarchicalSearchTags, [588](#)
 - GetName, [588](#)
 - GetOptionalTags, [588](#)
 - GetQueryLevel, [588](#)
 - GetRequiredTags, [589](#)

- GetUniqueTags, [589](#)
- gdcm::QuerySeries, [589](#)
 - GetHierarchicalSearchTags, [590](#)
 - GetName, [590](#)
 - GetOptionalTags, [590](#)
 - GetQueryLevel, [590](#)
 - GetRequiredTags, [591](#)
 - GetUniqueTags, [591](#)
- gdcm::QueryStudy, [591](#)
 - GetHierarchicalSearchTags, [592](#)
 - GetName, [592](#)
 - GetOptionalTags, [592](#)
 - GetQueryLevel, [592](#)
 - GetRequiredTags, [593](#)
 - GetUniqueTags, [593](#)
- gdcm::RAWCodec, [593](#)
 - ~RAWCodec, [594](#)
 - CanCode, [594](#)
 - CanDecode, [595](#)
 - Code, [595](#)
 - Decode, [595](#)
 - DecodeByStreams, [595](#)
 - DecodeBytes, [595](#)
 - GetHeaderInfo, [595](#)
 - RAWCodec, [594](#)
- gdcm::RLECodec, [605](#)
 - ~RLECodec, [607](#)
 - CanCode, [607](#)
 - CanDecode, [607](#)
 - Code, [607](#)
 - Decode, [608](#)
 - DecodeByStreams, [608](#)
 - DecodeExtent, [608](#)
 - GetBufferLength, [608](#)
 - GetHeaderInfo, [608](#)
 - ImageRegionReader, [608](#)
 - RLECodec, [607](#)
 - SetBufferLength, [608](#)
 - SetLength, [608](#)
- gdcm::Reader, [595](#)
 - ~Reader, [598](#)
 - CanRead, [598](#)
 - F, [600](#)
 - GetFile, [598](#)
 - GetStreamPtr, [599](#)
 - Read, [599](#)
 - ReadDataSet, [599](#)
 - ReadMetaInformation, [599](#)
 - ReadPreamble, [599](#)
 - ReadSelectedTags, [599](#)
 - ReadUpToTag, [599](#)
 - Reader, [598](#)
 - SetFile, [599](#)
 - SetFileName, [599](#)
 - SetStream, [600](#)
 - StreamImageReader, [600](#)
- gdcm::Region, [600](#)
 - ~Region, [601](#)
 - Area, [601](#)
 - Clone, [601](#)
 - ComputeBoundingBox, [602](#)
 - Empty, [602](#)
 - IsValid, [602](#)
 - Print, [602](#)
 - Region, [601](#)
- gdcm::Rescaler, [602](#)
 - ~Rescaler, [604](#)
 - ComputeInterceptSlopePixelType, [604](#)
 - ComputePixelTypeFromMinMax, [604](#)
 - GetIntercept, [604](#)
 - GetSlope, [604](#)
 - InverseRescale, [604](#)
 - InverseRescaleFunctionIntoBestFit, [604](#)
 - Rescale, [604](#)
 - RescaleFunctionIntoBestFit, [604](#)
 - Rescaler, [604](#)
 - SetIntercept, [604](#)
 - SetMinMaxForPixelType, [604](#)
 - SetPixelFormat, [604](#)
 - SetSlope, [605](#)
 - SetTargetPixelType, [605](#)
 - SetUseTargetPixelType, [605](#)
- gdcm::SHA1, [646](#)
 - ~SHA1, [647](#)
 - Compute, [647](#)
 - ComputeFile, [647](#)
 - SHA1, [647](#)
- gdcm::SOPClassUIDToIOD, [656](#)
 - const, [657](#)
 - GetIOD, [657](#)
- gdcm::Scanner, [610](#)
 - ~Scanner, [614](#)
 - AddPrivateTag, [614](#)
 - AddSkipTag, [614](#)
 - AddTag, [614](#)
 - Begin, [614](#)
 - ClearSkipTags, [614](#)
 - ClearTags, [614](#)
 - ConstIterator, [613](#)
 - End, [614](#)
 - GetAllFilenamesFromTagToValue, [614](#)
 - GetFilenameFromTagToValue, [614](#)
 - GetFilenames, [614](#)
 - GetKeys, [614](#)
 - GetMapping, [615](#)
 - GetMappingFromTagToValue, [615](#)
 - GetMappings, [615](#)
 - GetOrderedValues, [615](#)

- GetValue, 615
- GetValues, 615
- IsKey, 615
- MappingType, 613
- New, 616
- operator<<, 616
- Print, 616
- ProcessPublicTag, 616
- Scan, 616
- Scanner, 614
- TagToValue, 613
- TagToValueValueType, 613
- ValueType, 614
- gdcm::Scanner::ltstr, 476
 - operator(), 476
- gdcm::Segment, 616
 - ~Segment, 619
 - ALGOType, 619
 - AddSurface, 619
 - AnatomicRegion, 620
 - GetALGOType, 619
 - GetALGOTypeString, 619
 - GetAnatomicRegion, 619
 - GetPropertyCategory, 619
 - GetPropertyType, 619
 - GetSegmentAlgorithmName, 619
 - GetSegmentAlgorithmType, 619
 - GetSegmentDescription, 619
 - GetSegmentLabel, 619
 - GetSegmentNumber, 619
 - GetSurface, 619
 - GetSurfaceCount, 619
 - GetSurfaces, 620
 - PropertyCategory, 620
 - PropertyType, 620
 - Segment, 619
 - SegmentAlgorithmName, 620
 - SegmentAlgorithmType, 620
 - SegmentDescription, 620
 - SegmentLabel, 620
 - SegmentNumber, 620
 - SetAnatomicRegion, 620
 - SetPropertyCategory, 620
 - SetPropertyType, 620
 - SetSegmentAlgorithmName, 620
 - SetSegmentAlgorithmType, 620
 - SetSegmentDescription, 620
 - SetSegmentLabel, 620
 - SetSegmentNumber, 620
 - SetSurfaceCount, 620
 - SurfaceCount, 620
 - SurfaceVector, 619
 - Surfaces, 620
- gdcm::SegmentHelper, 130
 - gdcm::SegmentHelper::BasicCodedEntry, 198
 - BasicCodedEntry, 200
 - CM, 200
 - CSD, 200
 - CSV, 200
 - CV, 200
 - IsEmpty, 200
 - gdcm::SegmentReader, 622
 - ~SegmentReader, 624
 - GetSegments, 624
 - Read, 625
 - ReadSegment, 625
 - ReadSegments, 625
 - SegmentMap, 624
 - SegmentReader, 624
 - SegmentVector, 624
 - Segments, 625
 - gdcm::SegmentWriter, 625
 - ~SegmentWriter, 627
 - AddSegment, 627
 - GetNumberOfSegments, 627
 - GetSegment, 627
 - GetSegments, 627
 - PrepareWrite, 627
 - SegmentVector, 627
 - SegmentWriter, 627
 - Segments, 627
 - SetNumberOfSegments, 627
 - SetSegments, 627
 - Write, 627
 - gdcm::SegmentedPaletteColorLookupTable, 621
 - ~SegmentedPaletteColorLookupTable, 622
 - Print, 622
 - SegmentedPaletteColorLookupTable, 622
 - SetLUT, 622
 - gdcm::SequenceOfFragments, 627
 - AddFragment, 630
 - Begin, 630
 - Clear, 630
 - ComputeByteLength, 630
 - ComputeLength, 630
 - ConstIterator, 630
 - End, 630
 - FragmentVector, 630
 - GetBuffer, 630
 - GetFragBuffer, 630
 - GetFragment, 630
 - GetLength, 631
 - GetNumberOfFragments, 631
 - GetTable, 631
 - Iterator, 630
 - New, 631
 - operator==, 631
 - Print, 631

- Read, [631](#)
- ReadPreValue, [631](#)
- ReadValue, [631](#)
- SequenceOfFragments, [630](#)
- SetLength, [631](#)
- SizeType, [630](#)
- Write, [632](#)
- WriteBuffer, [632](#)
- gdcmm::SequenceOfItems, [632](#)
 - AddItem, [635](#)
 - Begin, [635](#)
 - Clear, [635](#)
 - ComputeLength, [635](#)
 - ConstIterator, [635](#)
 - End, [635](#)
 - FindDataElement, [636](#)
 - GetItem, [636](#)
 - GetLength, [636](#)
 - GetNumberOfItems, [636](#)
 - IsUndefinedLength, [636](#)
 - ItemVector, [635](#)
 - Items, [637](#)
 - Iterator, [635](#)
 - New, [636](#)
 - operator=, [636](#)
 - operator==, [636](#)
 - Print, [636](#)
 - Read, [636](#)
 - SequenceLengthField, [637](#)
 - SequenceOfItems, [635](#)
 - SetLength, [637](#)
 - SetLengthToUndefined, [637](#)
 - SetNumberOfItems, [637](#)
 - SizeType, [635](#)
 - Write, [637](#)
- gdcmm::SerieHelper, [638](#)
 - ~SerieHelper, [639](#)
 - AddFile, [639](#)
 - AddFileName, [639](#)
 - AddRestriction, [640](#)
 - Clear, [640](#)
 - CreateDefaultUniqueSeriesIdentifier, [640](#)
 - CreateUniqueSeriesIdentifier, [640](#)
 - FileNameOrdering, [640](#)
 - GetFirstSingleSerieUIDFileSet, [640](#)
 - GetNextSingleSerieUIDFileSet, [640](#)
 - ImagePositionPatientOrdering, [640](#)
 - ItFileSetHt, [640](#)
 - OrderFileList, [640](#)
 - SerieHelper, [639](#)
 - SerieRestrictions, [639](#)
 - SetDirectory, [640](#)
 - SetLoadMode, [640](#)
 - SetUseSeriesDetails, [640](#)
 - SingleSerieUIDFileSetHT, [640](#)
 - SingleSerieUIDFileSetmap, [639](#)
 - UserOrdering, [640](#)
- gdcmm::SerieHelper::Rule, [609](#)
 - elem, [610](#)
 - group, [610](#)
 - op, [610](#)
 - value, [610](#)
- gdcmm::Series, [640](#)
 - Series, [641](#)
- gdcmm::ServiceClassUser, [642](#)
 - ~ServiceClassUser, [644](#)
 - GetAETitle, [644](#)
 - GetCalledAETitle, [644](#)
 - GetTimeout, [644](#)
 - InitializeConnection, [644](#)
 - IsPresentationContextAccepted, [644](#)
 - SendEcho, [644](#)
 - SendFind, [644](#)
 - SendMove, [644](#)
 - SendStore, [645](#)
 - ServiceClassUser, [644](#)
 - SetAETitle, [645](#)
 - SetCalledAETitle, [645](#)
 - SetHostname, [645](#)
 - SetPort, [645](#)
 - SetPortSCP, [645](#)
 - SetPresentationContexts, [646](#)
 - SetTimeout, [646](#)
 - StartAssociation, [646](#)
 - StopAssociation, [646](#)
- gdcmm::SimpleMemberCommand
 - ~SimpleMemberCommand, [650](#)
 - Execute, [650](#)
 - m_MemberFunction, [650](#)
 - m_This, [650](#)
 - New, [650](#)
 - Self, [649](#)
 - SetCallbackFunction, [650](#)
 - SimpleMemberCommand, [650](#)
 - TMemberFunctionPointer, [649](#)
- gdcmm::SimpleMemberCommand< T >, [647](#)
- gdcmm::SimpleSubjectWatcher, [651](#)
 - ~SimpleSubjectWatcher, [651](#)
 - EndFilter, [651](#)
 - ShowAbort, [651](#)
 - ShowAnonymization, [651](#)
 - ShowData, [652](#)
 - ShowDataSet, [652](#)
 - ShowIteration, [652](#)
 - ShowProgress, [652](#)
 - SimpleSubjectWatcher, [651](#)
 - StartFilter, [652](#)
 - TestAbortOff, [652](#)

- TestAbortOn, [652](#)
- gdcmm::SmartPointer
 - ~SmartPointer, [654](#)
 - GetPointer, [654](#)
 - operator ObjectType *, [654](#)
 - operator*, [655](#)
 - operator->, [655](#)
 - operator=, [655](#)
 - SmartPointer, [654](#)
- gdcmm::SmartPointer< ObjectType >, [652](#)
- gdcmm::Sorter, [657](#)
 - ~Sorter, [660](#)
 - AddSelect, [660](#)
 - FileNames, [661](#)
 - GetFileNames, [660](#)
 - operator<<, [661](#)
 - Print, [660](#)
 - Selection, [661](#)
 - SelectionMap, [659](#)
 - SetSortFunction, [660](#)
 - Sort, [660](#)
 - SortFunc, [661](#)
 - SortFunction, [659](#)
 - Sorter, [660](#)
 - StableSort, [660](#)
- gdcmm::Spacing, [661](#)
 - ~Spacing, [662](#)
 - ComputePixelAspectRatioFromPixelSpacing, [662](#)
 - Spacing, [662](#)
 - SpacingType, [662](#)
- gdcmm::Spectroscopy, [663](#)
 - Spectroscopy, [663](#)
- gdcmm::SplitMosaicFilter, [663](#)
 - ~SplitMosaicFilter, [664](#)
 - ComputeMOSAICDimensions, [664](#)
 - GetFile, [664](#)
 - GetImage, [664](#)
 - SetFile, [664](#)
 - SetImage, [664](#)
 - Split, [664](#)
 - SplitMosaicFilter, [664](#)
- gdcmm::StartEvent, [664](#)
- gdcmm::StreamImageReader, [666](#)
 - ~StreamImageReader, [667](#)
 - CanReadImage, [667](#)
 - DefinePixelExtent, [667](#)
 - DefineProperBufferLength, [668](#)
 - GetDimensionsValueForResolution, [668](#)
 - GetFile, [668](#)
 - Read, [668](#)
 - ReadImageInformation, [668](#)
 - SetFileName, [668](#)
 - SetStream, [669](#)
 - StreamImageReader, [667](#)
- gdcmm::StreamImageWriter, [669](#)
 - ~StreamImageWriter, [671](#)
 - CanWriteFile, [671](#)
 - DefinePixelExtent, [672](#)
 - DefineProperBufferLength, [672](#)
 - mElementOffsets, [673](#)
 - mElementOffsets1, [673](#)
 - mWriter, [674](#)
 - mXMax, [674](#)
 - mXMin, [674](#)
 - mYMax, [674](#)
 - mYMin, [674](#)
 - mZMax, [674](#)
 - mZMin, [674](#)
 - mspFile, [674](#)
 - SetFile, [672](#)
 - SetFileName, [672](#)
 - SetStream, [672](#)
 - StreamImageWriter, [671](#)
 - Write, [672](#)
 - WriteImageInformation, [673](#)
 - WriteImageSubregionRAW, [673](#)
 - WriteRawHeader, [673](#)
- gdcmm::String
 - const_iterator, [676](#)
 - const_reference, [676](#)
 - const_reverse_iterator, [676](#)
 - difference_type, [676](#)
 - IsValid, [677](#)
 - iterator, [676](#)
 - operator const char *, [677](#)
 - pointer, [676](#)
 - reference, [676](#)
 - reverse_iterator, [676](#)
 - size_type, [676](#)
 - String, [677](#)
 - Trim, [677](#)
 - Truncate, [677](#)
 - value_type, [676](#)
- gdcmm::String< TDelimiter, TMaxLength, TPadChar >, [674](#)
- gdcmm::StringFilter, [678](#)
 - ~StringFilter, [678](#)
 - ExecuteQuery, [678](#), [679](#)
 - FromString, [679](#)
 - GetFile, [679](#)
 - SetDicts, [679](#)
 - SetFile, [679](#)
 - StringFilter, [678](#)
 - ToString, [679](#)
 - ToStringPair, [679](#)
 - UseDictAlways, [680](#)
- gdcmm::Study, [680](#)
 - Study, [680](#)
- gdcmm::Subject, [680](#)

- ~Subject, [682](#)
- AddObserver, [682](#)
- GetCommand, [682](#)
- HasObserver, [682](#)
- InvokeEvent, [682](#)
- RemoveAllObservers, [682](#)
- RemoveObserver, [682](#)
- Subject, [682](#)
- gdcmm::Surface, [683](#)
 - ~Surface, [686](#)
 - GetAlgorithmFamily, [686](#)
 - GetAlgorithmName, [686](#)
 - GetAlgorithmVersion, [686](#)
 - GetAxisOfRotation, [686](#)
 - GetCenterOfRotation, [686](#)
 - GetFiniteVolume, [687](#)
 - GetManifold, [687](#)
 - GetMaximumPointDistance, [687](#)
 - GetMeanPointDistance, [687](#)
 - GetMeshPrimitive, [687](#)
 - GetNumberOfSurfacePoints, [687](#)
 - GetNumberOfVectors, [687](#)
 - GetPointCoordinatesData, [687](#)
 - GetPointPositionAccuracy, [687](#)
 - GetPointsBoundingBoxCoordinates, [687](#)
 - GetProcessingAlgorithm, [687](#)
 - GetRecommendedDisplayCIELabValue, [687](#)
 - GetRecommendedDisplayGrayscaleValue, [687](#)
 - GetRecommendedPresentationOpacity, [687](#)
 - GetRecommendedPresentationType, [687](#)
 - GetSTATES, [688](#)
 - GetSTATESString, [688](#)
 - GetSurfaceComments, [688](#)
 - GetSurfaceNumber, [688](#)
 - GetSurfaceProcessing, [688](#)
 - GetSurfaceProcessingDescription, [688](#)
 - GetSurfaceProcessingRatio, [688](#)
 - GetVIEWType, [688](#)
 - GetVIEWTypeString, [688](#)
 - GetVectorAccuracy, [688](#)
 - GetVectorCoordinateData, [688](#)
 - GetVectorDimensionality, [688](#)
 - STATES, [686](#)
 - SetAlgorithmFamily, [688](#)
 - SetAlgorithmName, [688](#)
 - SetAlgorithmVersion, [688](#)
 - SetAxisOfRotation, [688](#)
 - SetCenterOfRotation, [688](#)
 - SetFiniteVolume, [688](#)
 - SetManifold, [688](#)
 - SetMaximumPointDistance, [688](#)
 - SetMeanPointDistance, [688](#)
 - SetMeshPrimitive, [688](#)
 - SetNumberOfSurfacePoints, [688](#)
 - SetNumberOfVectors, [688](#)
 - SetPointCoordinatesData, [688](#)
 - SetPointPositionAccuracy, [689](#)
 - SetPointsBoundingBoxCoordinates, [689](#)
 - SetProcessingAlgorithm, [689](#)
 - SetRecommendedDisplayCIELabValue, [689](#)
 - SetRecommendedDisplayGrayscaleValue, [689](#)
 - SetRecommendedPresentationOpacity, [689](#)
 - SetRecommendedPresentationType, [689](#)
 - SetSurfaceComments, [689](#)
 - SetSurfaceNumber, [689](#)
 - SetSurfaceProcessing, [689](#)
 - SetSurfaceProcessingDescription, [689](#)
 - SetSurfaceProcessingRatio, [689](#)
 - SetVectorAccuracy, [689](#)
 - SetVectorCoordinateData, [689](#)
 - SetVectorDimensionality, [689](#)
 - Surface, [686](#)
 - VIEWType, [686](#)
- gdcmm::SurfaceHelper, [689](#)
 - ColorArray, [690](#)
 - RGBToRecommendedDisplayCIELab, [691](#), [692](#)
 - RGBToRecommendedDisplayGrayscale, [692](#)
 - RecommendedDisplayCIELabToRGB, [690](#), [691](#)
- gdcmm::SurfaceReader, [692](#)
 - ~SurfaceReader, [694](#)
 - GetNumberOfSurfaces, [694](#)
 - Read, [694](#)
 - ReadPointMacro, [694](#)
 - ReadSurface, [694](#)
 - ReadSurfaces, [694](#)
 - SurfaceReader, [694](#)
- gdcmm::SurfaceWriter, [695](#)
 - ~SurfaceWriter, [696](#)
 - ComputeNumberOfSurfaces, [696](#)
 - GetNumberOfSurfaces, [696](#)
 - NumberOfSurfaces, [696](#)
 - PrepareWrite, [696](#)
 - PrepareWritePointMacro, [696](#)
 - SetNumberOfSurfaces, [696](#)
 - SurfaceWriter, [696](#)
 - Write, [696](#)
- gdcmm::SwapCode, [696](#)
 - GetIndex, [698](#)
 - GetSwapCodeString, [698](#)
 - operator SwapCode::SwapCodeType, [698](#)
 - operator<<, [698](#)
 - SwapCode, [698](#)
 - SwapCodeType, [697](#)
- gdcmm::SwapperDoOp, [698](#)
 - Swap, [698](#)
 - SwapArray, [698](#)
- gdcmm::SwapperNoOp, [699](#)
 - Swap, [699](#)

- SwapArray, 699
- gdcmm::System, 699
 - DeleteDirectory, 700
 - EncodeBytes, 700
 - FileExists, 700
 - FileIsDirectory, 701
 - FileIsSymlink, 701
 - FileSize, 701
 - FileTime, 701
 - FormatDateTime, 701
 - GetCWD, 702
 - GetCurrentDateTime, 701
 - GetCurrentModuleFileName, 701
 - GetCurrentProcessFileName, 702
 - GetCurrentResourcesDirectory, 702
 - GetHostName, 702
 - GetLastSystemError, 702
 - GetLocaleCharSet, 702
 - GetPermissions, 702
 - GetTimezoneOffsetFromUTC, 702
 - MakeDirectory, 702
 - ParseDateTime, 702, 703
 - RemoveFile, 703
 - SetPermissions, 703
 - StrCaseCmp, 703
 - StrNCaseCmp, 703
 - StrTokR, 703
- gdcmm::Table, 703
 - ~Table, 704
 - GetTableEntry, 704
 - InsertEntry, 704
 - MapTableEntry, 704
 - operator<<, 704
 - Table, 704
- gdcmm::TableEntry, 704
 - ~TableEntry, 705
 - TableEntry, 705
- gdcmm::TableReader, 705
 - ~TableReader, 706
 - CharacterDataHandler, 706
 - EndElement, 706
 - GetDefs, 706
 - GetFilename, 706
 - HandleIOD, 706
 - HandleIODEntry, 706
 - HandleMacro, 706
 - HandleMacroEntry, 706
 - HandleMacroEntryDescription, 706
 - HandleModule, 706
 - HandleModuleEntry, 706
 - HandleModuleEntryDescription, 706
 - HandleModuleInclude, 707
 - Read, 707
 - SetFilename, 707
 - StartElement, 707
 - TableReader, 706
- gdcmm::Tag, 708
 - bytes, 714
 - GetElement, 710
 - GetElementTag, 711
 - GetGroup, 711
 - GetLength, 711
 - GetPrivateCreator, 711
 - IsGroupLength, 711
 - IsGroupXX, 711
 - IsIllegal, 711
 - IsPrivate, 711
 - IsPrivateCreator, 712
 - IsPublic, 712
 - operator<, 712
 - operator<<, 714
 - operator<=, 712
 - operator>>, 714
 - operator=, 712
 - operator==, 712
 - PrintAsPipeSeparatedString, 712
 - Read, 713
 - ReadFromCommaSeparatedString, 713
 - ReadFromPipeSeparatedString, 713
 - SetElement, 713
 - SetElementTag, 713
 - SetGroup, 713
 - SetPrivateCreator, 713
 - Tag, 710
 - tag, 714
 - tags, 714
 - Write, 714
- gdcmm::TagPath, 714
 - ~TagPath, 715
 - ConstructFromString, 715
 - ConstructFromTagList, 715
 - IsValid, 715
 - Print, 715
 - Push, 715
 - TagPath, 715
- gdcmm::Testing, 716
 - ~Testing, 717
 - ComputeFileMD5, 717
 - ComputeMD5, 717
 - GetDataExtraRoot, 717
 - GetDataRoot, 717
 - GetFilename, 718
 - GetFileNames, 718
 - GetLossyFlagFromFile, 718
 - GetMD5DataImage, 718
 - GetMD5DataImages, 718
 - GetMD5FromBrokenFile, 718
 - GetMD5FromFile, 718

- GetMediaStorageDataFile, [718](#)
- GetMediaStorageDataFiles, [718](#)
- GetMediaStorageFromFile, [718](#)
- GetNumberOfFileNames, [718](#)
- GetNumberOfMD5DataImages, [718](#)
- GetNumberOfMediaStorageDataFiles, [718](#)
- GetPixelSpacingDataRoot, [719](#)
- GetSelectedTagsOffsetFromFile, [719](#)
- GetSourceDirectory, [719](#)
- GetStreamOffsetFromFile, [719](#)
- GetTempDirectory, [719](#)
- GetTempDirectoryW, [719](#)
- GetTempFilename, [719](#)
- GetTempFilenameW, [719](#)
- MD5DataImagesType, [717](#)
- MediaStorageDataFilesType, [717](#)
- Print, [719](#)
- Testing, [717](#)
- gdcm::Trace, [719](#)
 - ~Trace, [721](#)
 - DebugOff, [721](#)
 - DebugOn, [721](#)
 - ErrorOff, [721](#)
 - ErrorOn, [721](#)
 - GetDebugFlag, [721](#)
 - GetDebugStream, [721](#)
 - GetErrorFlag, [721](#)
 - GetErrorStream, [721](#)
 - GetStream, [721](#)
 - GetWarningFlag, [721](#)
 - GetWarningStream, [721](#)
 - SetDebug, [721](#)
 - SetDebugStream, [721](#)
 - SetError, [721](#)
 - SetErrorStream, [722](#)
 - SetStream, [722](#)
 - SetStreamToFile, [722](#)
 - SetWarning, [722](#)
 - SetWarningStream, [722](#)
 - Trace, [721](#)
 - WarningOff, [722](#)
 - WarningOn, [722](#)
- gdcm::TransferSyntax, [723](#)
 - CanStoreLossy, [725](#)
 - GetNegociatedType, [725](#)
 - GetString, [725](#)
 - GetSwapCode, [725](#)
 - GetTSString, [725](#)
 - GetTSType, [726](#)
 - IsEncapsulated, [726](#)
 - IsEncoded, [726](#)
 - IsExplicit, [726](#)
 - IsImplicit, [726](#)
 - IsLossless, [726](#)
 - IsLossy, [726](#)
 - IsValid, [726](#)
 - NegociatedType, [724](#)
 - operator TSType, [726](#)
 - operator<<, [726](#)
 - TSType, [724](#)
 - TransferSyntax, [725](#)
- gdcm::Type, [729](#)
 - GetTypeString, [730](#)
 - GetTypeType, [730](#)
 - operator TypeType, [730](#)
 - operator<<, [731](#)
 - Type, [730](#)
 - TypeType, [730](#)
- gdcm::UI, [731](#)
 - Internal, [731](#)
 - operator<<, [731](#)
- gdcm::UIDGenerator, [731](#)
 - Generate, [732](#)
 - GenerateUUID, [732](#)
 - GetGDCMUID, [732](#)
 - GetRoot, [732](#)
 - IsValid, [733](#)
 - SetRoot, [733](#)
 - UIDGenerator, [732](#)
- gdcm::UIDs, [733](#)
 - GetName, [751](#)
 - GetNumberOfTransferSyntaxStrings, [751](#)
 - GetString, [752](#)
 - GetTransferSyntaxString, [752](#)
 - GetTransferSyntaxStrings, [752](#)
 - GetUIDName, [752](#)
 - GetUIDString, [752](#)
 - operator TSType, [752](#)
 - SetFromUID, [752](#)
 - TSName, [738](#)
 - TSType, [745](#)
 - TransferSyntaxStringsType, [738](#)
- gdcm::UNExplicitDataElement, [800](#)
 - GetLength, [801](#)
 - Read, [801](#)
 - ReadPreValue, [802](#)
 - ReadValue, [802](#)
 - ReadWithLength, [802](#)
- gdcm::UNExplicitImplicitDataElement, [802](#)
 - GetLength, [803](#)
 - Read, [803](#)
 - ReadPreValue, [804](#)
 - ReadValue, [804](#)
- gdcm::Unpacker12Bits, [804](#)
 - Pack, [804](#)
 - Unpack, [804](#)
- gdcm::Usage, [805](#)
 - GetUsageString, [806](#)

- GetUsageType, 806
 - operator UsageType, 806
 - operator<<, 806
 - Usage, 806
 - UsageType, 806
- gdcmm::UserEvent, 806
- gdcmm::VL, 814
 - GetLength, 815
 - GetVL16Max, 815
 - GetVL32Max, 815
 - IsOdd, 815
 - IsUndefined, 815
 - operator uint32_t, 815
 - operator<<, 816
 - operator++, 815
 - operator+==, 815
 - Read, 815
 - Read16, 816
 - SetToUndefined, 816
 - Type, 815
 - VL, 815
 - Write, 816
 - Write16, 816
- gdcmm::VM, 816
 - Compatible, 819
 - GetIndex, 819
 - GetLength, 819
 - GetNumberOfElementsFromArray, 819
 - GetVMString, 819
 - GetVMType, 819
 - GetVMTypeFromLength, 820
 - IsValid, 820
 - operator VMType, 820
 - operator<<, 820
 - VM, 819
 - VMType, 818
- gdcmm::VMToLength< T >, 820
- gdcmm::VR, 820
 - CanDisplay, 823
 - Compatible, 823
 - GetLength, 823, 824
 - GetSize, 824
 - GetSizeof, 824
 - GetVRString, 824
 - GetVRStringFromFile, 824
 - GetVRType, 824
 - GetVRTypeFromFile, 824
 - IsASCII, 824
 - IsASCII2, 824
 - IsBinary, 824
 - IsBinary2, 824
 - IsDual, 824
 - IsSwap, 824
 - IsVRFile, 824
 - IsValid, 824
 - operator VRTYPE, 824
 - operator<<, 825
 - Read, 824
 - VR, 823
 - VRTYPE, 822
 - Write, 824
- gdcmm::VR16ExplicitDataElement, 825
 - GetLength, 826
 - Read, 826
 - ReadPreValue, 827
 - ReadValue, 827
 - ReadWithLength, 827
- gdcmm::VRToEncoding< T >, 827
- gdcmm::VRToType< T >, 827
- gdcmm::VRVLSIZE< 0 >, 828
 - Read, 828
 - Write, 828
- gdcmm::VRVLSIZE< 1 >, 828
 - Read, 828
 - Write, 828
- gdcmm::VRVLSIZE< T >, 828
- gdcmm::Validate, 809
 - ~Validate, 810
 - F, 810
 - GetValidatedFile, 810
 - SetFile, 810
 - V, 810
 - Validate, 810
 - Validation, 810
- gdcmm::Value, 810
 - ~Value, 811
 - Clear, 811
 - GetLength, 811
 - operator==, 812
 - SetLength, 812
 - Value, 811
- gdcmm::ValueIO
 - Read, 812
 - Write, 812
- gdcmm::ValueIO< TDE, TSwap, TType >, 812
- gdcmm::Version, 813
 - ~Version, 813
 - GetBuildVersion, 813
 - GetMajorVersion, 813
 - GetMinorVersion, 813
 - GetVersion, 813
 - operator<<, 814
 - Print, 813
 - Version, 813
- gdcmm::Waveform, 880
 - Waveform, 880
- gdcmm::Writer, 880
 - ~Writer, 884

- CheckFileMetaInformationOff, 884
- CheckFileMetaInformationOn, 884
- GetFile, 884
- GetStreamPtr, 884
- Ofstream, 885
- SetCheckFileMetaInformation, 884
- SetFile, 884
- SetFileName, 885
- SetStream, 885
- SetWriteDataSetOnly, 885
- Stream, 885
- StreamImageWriter, 885
- Write, 885
- Writer, 884
- gdcmm::XMLDictReader, 886
 - ~XMLDictReader, 887
 - CharacterDataHandler, 887
 - EndElement, 887
 - GetDict, 887
 - HandleDescription, 887
 - HandleEntry, 887
 - StartElement, 887
 - XMLDictReader, 887
- gdcmm::XMLPrivateDictReader, 887
 - ~XMLPrivateDictReader, 889
 - CharacterDataHandler, 889
 - EndElement, 889
 - GetPrivateDict, 889
 - HandleDescription, 889
 - HandleEntry, 889
 - StartElement, 889
 - XMLPrivateDictReader, 889
- gdcmm::ignore_char, 392
 - ignore_char, 393
 - m_char, 393
- gdcmm::network, 124
 - cMaxEventID, 129
 - cMaxStateID, 129
 - EEventID, 128
 - EStateID, 129
 - GetStateIndex, 129
- gdcmm::network::AAbortPDU, 133
 - AAbortPDU, 134
 - IsLastFragment, 134
 - Print, 134
 - Read, 134
 - SetReason, 134
 - SetSource, 135
 - Size, 135
 - Write, 135
- gdcmm::network::AAssociateACPDU, 135
 - AAssociateACPDU, 137
 - AAssociateRQPDU, 137
 - AddPresentationContextAC, 137
 - GetNumberOfPresentationContextAC, 137
 - GetPresentationContextAC, 137
 - GetUserInformation, 137
 - InitFromRQ, 137
 - IsLastFragment, 137
 - Print, 137
 - Read, 137
 - SetCalledAETitle, 137
 - SetCallingAETitle, 137
 - Size, 137
 - SizeType, 137
 - Write, 137
- gdcmm::network::AAssociateRJPDU, 138
 - AAssociateRJPDU, 139
 - IsLastFragment, 139
 - Print, 139
 - Read, 139
 - Size, 139
 - Write, 139
- gdcmm::network::AAssociateRQPDU, 139
 - AAssociateACPDU, 143
 - AAssociateRQPDU, 141
 - AddPresentationContext, 142
 - GetCalledAETitle, 142
 - GetCallingAETitle, 142
 - GetNumberOfPresentationContext, 142
 - GetPresentationContext, 142
 - GetPresentationContextByAbstractSyntax, 142
 - GetPresentationContextByID, 142
 - GetPresentationContexts, 142
 - GetReserved43_74, 142
 - GetUserInformation, 142
 - IsAETitleValid, 142
 - IsLastFragment, 142
 - PresentationContextArrayType, 141
 - Print, 142
 - Read, 142
 - SetCalledAETitle, 142
 - SetCallingAETitle, 142
 - SetUserInformation, 142
 - Size, 143
 - SizeType, 141
 - Write, 143
- gdcmm::network::ARTIMTimer, 160
 - ARTIMTimer, 160
 - GetElapsedTime, 160
 - GetHasExpired, 160
 - GetTimeout, 160
 - SetTimeout, 161
 - Start, 161
 - Stop, 161
- gdcmm::network::AReleaseRPPDU, 156
 - AReleaseRPPDU, 157
 - IsLastFragment, 158

- Print, 158
- Read, 158
- Size, 158
- Write, 158
- gdcmm::network::AReleaseRQPDU, 158
 - AReleaseRQPDU, 159
 - IsLastFragment, 159
 - Print, 159
 - Read, 159
 - Size, 159
 - Write, 160
- gdcmm::network::AbstractSyntax, 144
 - AbstractSyntax, 145
 - GetAsDataElement, 145
 - GetName, 145
 - operator==, 145
 - Print, 145
 - Read, 145
 - SetName, 145
 - SetNameFromUID, 145
 - Size, 145
 - Write, 145
- gdcmm::network::ApplicationContext, 154
 - ApplicationContext, 154
 - GetName, 154
 - Print, 154
 - Read, 154
 - SetName, 154
 - Size, 154
 - Write, 154
- gdcmm::network::AsynchronousOperationsWindowSub, 162
 - AsynchronousOperationsWindowSub, 162
 - Print, 162
 - Read, 162
 - Size, 162
 - Write, 162
- gdcmm::network::BaseCompositeMessage, 191
 - ConstructPDV, 192
- gdcmm::network::BasePDU, 192
 - ~BasePDU, 194
 - IsLastFragment, 194
 - Print, 194
 - Read, 194
 - Size, 194
 - Write, 194
- gdcmm::network::CEchoRQ, 223
 - AffectedSOPClassUID, 224
 - ConstructPDV, 224
 - MessageID, 224
- gdcmm::network::CEchoRSP, 224
 - ConstructPDVByDataSet, 225
- gdcmm::network::CFind, 226
- gdcmm::network::CFindCancelRQ, 226
 - ConstructPDVByDataSet, 227
- gdcmm::network::CFindRQ, 227
 - ConstructPDV, 228
- gdcmm::network::CFindRSP, 229
 - ConstructPDVByDataSet, 230
- gdcmm::network::CMoveCancelRq, 230
 - ConstructPDVByDataSet, 231
- gdcmm::network::CMoveRQ, 231
 - ConstructPDV, 232
- gdcmm::network::CMoveRSP, 233
 - ConstructPDVByDataSet, 234
- gdcmm::network::CStoreRQ, 264
 - ConstructPDV, 265
- gdcmm::network::CStoreRSP, 266
 - ConstructPDV, 267
- gdcmm::network::CompositeMessageFactory, 243
 - ConstructCEchoRQ, 244
 - ConstructCFindRQ, 244
 - ConstructCMoveRQ, 244
 - ConstructCStoreRQ, 244
 - ConstructCStoreRSP, 244
- gdcmm::network::DIMSE, 312
 - CommandTypes, 313
- gdcmm::network::ImplementationClassUIDSub, 433
 - ImplementationClassUIDSub, 433
 - Print, 433
 - Read, 433
 - Size, 433
 - Write, 433
- gdcmm::network::ImplementationUIDSub, 433
 - ImplementationUIDSub, 434
 - Write, 434
- gdcmm::network::ImplementationVersionNameSub, 434
 - ImplementationVersionNameSub, 434
 - Print, 434
 - Read, 434
 - Size, 434
 - Write, 434
- gdcmm::network::MaximumLengthSub, 479
 - GetMaximumLength, 480
 - MaximumLengthSub, 480
 - Print, 480
 - Read, 480
 - SetMaximumLength, 480
 - Size, 480
 - Write, 480
- gdcmm::network::PDUFactory, 533
 - ConstructAbortPDU, 534
 - ConstructPDU, 534
 - ConstructReleasePDU, 534
 - CreateCEchoPDU, 534
 - CreateCFindPDU, 534
 - CreateCMovePDU, 534
 - CreateCStoreRQPDU, 534

- CreateCStoreRSPDU, 534
- DetermineEventByPDU, 534
- GetPDVs, 534
- gdcmm::network::PDataTFPDU, 525
 - AddPresentationDataValue, 527
 - GetNumberOfPresentationDataValues, 527
 - GetPresentationDataValue, 527
 - IsLastFragment, 527
 - PDataTFPDU, 527
 - Print, 527
 - Read, 527
 - ReadInto, 527
 - Size, 527
 - SizeType, 527
 - Write, 527
- gdcmm::network::PresentationContextAC, 563
 - GetPresentationContextID, 563
 - GetReason, 563
 - GetTransferSyntax, 563
 - PresentationContextAC, 563
 - Print, 563
 - Read, 563
 - SetPresentationContextID, 563
 - SetReason, 564
 - SetTransferSyntax, 564
 - Size, 564
 - Write, 564
- gdcmm::network::PresentationContextRQ, 566
 - AddTransferSyntax, 567
 - GetAbstractSyntax, 567
 - GetNumberOfTransferSyntaxes, 567
 - GetPresentationContextID, 567
 - GetTransferSyntax, 567
 - GetTransferSyntaxes, 567
 - operator==, 567
 - PresentationContextRQ, 567
 - Print, 568
 - Read, 568
 - SetAbstractSyntax, 568
 - SetPresentationContextID, 568
 - Size, 568
 - SizeType, 567
 - Write, 568
- gdcmm::network::PresentationDataValue, 568
 - ConcatenatePDVBlobs, 569
 - GetBlob, 569
 - GetIsCommand, 569
 - GetIsLastFragment, 569
 - GetMessageHeader, 569
 - GetPresentationContextID, 569
 - PresentationDataValue, 569
 - Print, 569
 - Read, 569
 - ReadInto, 569
 - SetBlob, 569
 - SetCommand, 569
 - DataSet, 569
 - SetLastFragment, 569
 - SetMessageHeader, 569
 - SetPresentationContextID, 569
 - Size, 570
 - Write, 570
- gdcmm::network::RoleSelectionSub, 608
 - Print, 609
 - Read, 609
 - RoleSelectionSub, 609
 - SetTuple, 609
 - Size, 609
 - Write, 609
- gdcmm::network::SOPClassExtendedNegotiationSub, 655
 - Print, 656
 - Read, 656
 - SOPClassExtendedNegotiationSub, 656
 - SetTuple, 656
 - Size, 656
 - Write, 656
- gdcmm::network::ServiceClassApplicationInformation, 641
 - Print, 641
 - Read, 641
 - ServiceClassApplicationInformation, 641
 - SetTuple, 641
 - Size, 641
 - Write, 641
- gdcmm::network::TableRow, 707
 - ~TableRow, 708
 - TableRow, 708
 - transitions, 708
- gdcmm::network::TransferSyntaxSub, 726
 - GetName, 727
 - operator==, 727
 - Print, 727
 - Read, 727
 - SetName, 727
 - SetNameFromUID, 727
 - Size, 727
 - TransferSyntaxSub, 727
 - Write, 727
- gdcmm::network::Transition, 727
 - ~Transition, 728
 - mAction, 729
 - mEnd, 729
 - MakeNew, 729
 - Transition, 728
- gdcmm::network::ULAction, 752
 - ~ULAction, 754
 - PerformAction, 754
 - ULAction, 754
- gdcmm::network::ULActionAA1, 755

PerformAction, 755
 gdcmm::network::ULActionAA2, 756
 PerformAction, 756
 gdcmm::network::ULActionAA3, 757
 PerformAction, 758
 gdcmm::network::ULActionAA4, 758
 PerformAction, 759
 gdcmm::network::ULActionAA5, 759
 PerformAction, 760
 gdcmm::network::ULActionAA6, 760
 PerformAction, 761
 gdcmm::network::ULActionAA7, 762
 PerformAction, 762
 gdcmm::network::ULActionAA8, 763
 PerformAction, 763
 gdcmm::network::ULActionAE1, 764
 PerformAction, 765
 gdcmm::network::ULActionAE2, 765
 PerformAction, 766
 gdcmm::network::ULActionAE3, 766
 PerformAction, 767
 gdcmm::network::ULActionAE4, 767
 PerformAction, 768
 gdcmm::network::ULActionAE5, 769
 PerformAction, 769
 gdcmm::network::ULActionAE6, 770
 PerformAction, 770
 gdcmm::network::ULActionAE7, 771
 PerformAction, 772
 gdcmm::network::ULActionAE8, 772
 PerformAction, 773
 gdcmm::network::ULActionAR1, 773
 PerformAction, 774
 gdcmm::network::ULActionAR10, 774
 PerformAction, 775
 gdcmm::network::ULActionAR2, 776
 PerformAction, 776
 gdcmm::network::ULActionAR3, 777
 PerformAction, 777
 gdcmm::network::ULActionAR4, 778
 PerformAction, 779
 gdcmm::network::ULActionAR5, 779
 PerformAction, 780
 gdcmm::network::ULActionAR6, 780
 PerformAction, 781
 gdcmm::network::ULActionAR7, 781
 PerformAction, 782
 gdcmm::network::ULActionAR8, 783
 PerformAction, 783
 gdcmm::network::ULActionAR9, 784
 PerformAction, 784
 gdcmm::network::ULActionDT1, 785
 PerformAction, 786
 gdcmm::network::ULActionDT2, 786

PerformAction, 787
 gdcmm::network::ULBasicCallback, 787
 ~ULBasicCallback, 788
 GetDataSets, 788
 GetResponses, 788
 HandleDataSet, 788
 HandleResponse, 788
 ULBasicCallback, 788
 gdcmm::network::ULConnection, 789
 ~ULConnection, 790
 AddAcceptedPresentationContext, 790
 FindContext, 790
 GetAcceptedPresentationContexts, 790
 GetConnectionInfo, 790
 GetMaxPDUSize, 790
 GetPresentationContextACByID, 790
 GetPresentationContextIDFromPresentationContext, 790
 GetPresentationContextRQByID, 790
 GetPresentationContexts, 790
 GetProtocol, 790
 GetState, 790
 GetTimer, 790
 InitializeConnection, 791
 InitializeIncomingConnection, 791
 SetMaxPDUSize, 791
 SetPresentationContexts, 791
 SetState, 791
 StopProtocol, 791
 ULConnection, 790
 gdcmm::network::ULConnectionCallback, 791
 ~ULConnectionCallback, 792
 DataSetHandled, 792
 DataSetHandles, 792
 HandleDataSet, 792
 HandleResponse, 792
 ResetHandledDataSet, 792
 ULConnectionCallback, 792
 gdcmm::network::ULConnectionInfo, 793
 GetCalledAETitle, 793
 GetCalledComputerName, 793
 GetCalledIPAddress, 793
 GetCalledIPPort, 793
 GetCallingAETitle, 793
 GetMaxPDULength, 793
 Initialize, 793
 SetMaxPDULength, 793
 ULConnectionInfo, 793
 gdcmm::network::ULConnectionManager, 794
 ~ULConnectionManager, 796
 BreakConnection, 796
 BreakConnectionNow, 796
 EstablishConnection, 796
 EstablishConnectionMove, 796

- SendEcho, [796](#)
- SendFind, [796](#)
- SendMove, [796](#)
- SendStore, [796](#)
- ULConnectionManager, [796](#)
- gdcmm::network::ULEvent, [797](#)
 - ~ULEvent, [797](#)
 - GetEvent, [797](#)
 - GetPDUs, [797](#)
 - SetEvent, [797](#)
 - SetPDU, [797](#)
 - ULEvent, [797](#)
- gdcmm::network::ULTransitionTable, [798](#)
 - HandleEvent, [798](#)
 - PrintTable, [798](#)
 - ULTransitionTable, [798](#)
- gdcmm::network::ULWritingCallback, [798](#)
 - ~ULWritingCallback, [800](#)
 - HandleDataSet, [800](#)
 - HandleResponse, [800](#)
 - SetDirectory, [800](#)
 - ULWritingCallback, [799](#)
- gdcmm::network::UserInformation, [808](#)
 - ~UserInformation, [808](#)
 - AddRoleSelectionSub, [808](#)
 - AddSOPClassExtendedNegociationSub, [808](#)
 - GetMaximumLengthSub, [808](#)
 - operator=, [808](#)
 - Print, [808](#)
 - Read, [808](#)
 - Size, [808](#)
 - UserInformation, [808](#)
 - Write, [809](#)
- gdcmm::static_assert_test< x >, [666](#)
- gdcmm::terminal, [130](#)
 - Attribute, [131](#)
 - Color, [131](#)
 - Mode, [131](#)
 - setattribute, [131](#)
 - setbgcolor, [131](#)
 - setfgcolor, [131](#)
 - setmode, [131](#)
- gdcmAAbortPDU.h, [891](#)
- gdcmAAssociateACPDU.h, [892](#)
- gdcmAAssociateRJPDU.h, [893](#)
- gdcmAAssociateRQPDU.h, [894](#)
- gdcmARTIMTimer.h, [902](#)
- gdcmAReleaseRPPDU.h, [899](#)
- gdcmAReleaseRQPDU.h, [900](#)
- gdcmASN1.h, [903](#)
- gdcmAbstractSyntax.h, [894](#)
- gdcmAnonymizeEvent.h, [896](#)
- gdcmAnonymizer.h, [897](#)
- gdcmApplicationContext.h, [898](#)
- gdcmApplicationEntity.h, [899](#)
- gdcmAssertAlwaysMacro
 - gdcmTrace.h, [1131](#)
- gdcmAssertMacro
 - gdcmTrace.h, [1131](#)
- gdcmAsynchronousOperationsWindowSub.h, [904](#)
- gdcmAttribute.h, [905](#)
- gdcmAudioCodec.h, [906](#)
- gdcmBase64.h, [907](#)
- gdcmBaseCompositeMessage.h, [907](#)
- gdcmBasePDU.h, [909](#)
- gdcmBaseRootQuery.h, [910](#)
- gdcmBasicOffsetTable.h, [911](#)
- gdcmBitmap.h, [912](#)
- gdcmBitmapToBitmapFilter.h, [913](#)
- gdcmBoxRegion.h, [914](#)
- gdcmByteBuffer.h, [915](#)
- gdcmByteSwap.h, [917](#)
- gdcmByteSwapFilter.h, [917](#)
- gdcmByteValue.h, [918](#)
- gdcmCEchoMessages.h, [919](#)
- gdcmCFindMessages.h, [920](#)
- gdcmCMoveMessages.h, [921](#)
- gdcmCP246ExplicitDataElement.h, [930](#)
- gdcmCSAElement.h, [931](#)
- gdcmCSAHeader.h, [933](#)
- gdcmCSAHeaderDict.h, [934](#)
- gdcmCSAHeaderDictEntry.h, [935](#)
- gdcmCStoreMessages.h, [936](#)
- gdcmCodeString.h, [925](#)
- gdcmCodec.h, [922](#)
- gdcmCoder.h, [923](#)
- gdcmCommand.h, [925](#)
- gdcmCommandDataSet.h, [927](#)
- gdcmCompositeMessageFactory.h, [928](#)
- gdcmCompositeNetworkFunctions.h, [928](#)
- gdcmConstCharWrapper.h, [929](#)
- gdcmCryptographicMessageSyntax.h, [930](#)
- gdcmCurve.h, [937](#)
- gdcmDICOMDIR.h, [948](#)
- gdcmDICOMDIRGenerator.h, [949](#)
- gdcmDIMSE.h, [956](#)
- gdcmDataElement.h, [939](#)
- gdcmDataEvent.h, [940](#)
- gdcmDataSet.h, [941](#)
- gdcmDataSetEvent.h, [942](#)
- gdcmDataSetHelper.h, [942](#)
- gdcmDebugMacro
 - gdcmTrace.h, [1132](#)
- gdcmDecoder.h, [943](#)
- gdcmDefinedTerms.h, [945](#)
- gdcmDeflateStream.h, [945](#)
- gdcmDefs.h, [946](#)
- gdcmDeltaEncodingCodec.h, [947](#)

gdcmDict.h, 950
gdcmDictConverter.h, 952
gdcmDictEntry.h, 952
gdcmDictPrinter.h, 954
gdcmDicts.h, 954
gdcmDirectionCosines.h, 957
gdcmDirectory.h, 957
gdcmDirectoryHelper.h, 958
gdcmDummyValueGenerator.h, 959
gdcmDumper.h, 960
gdcmElement.h, 961
gdcmEncapsulatedDocument.h, 963
gdcmEnumeratedValues.h, 964
gdcmErrorMacro
 gdcmTrace.h, 1132
gdcmEvent.h, 964
 gdcmEventMacro, 966
gdcmEventMacro
 gdcmEvent.h, 966
gdcmException.h, 966
gdcmExplicitDataElement.h, 967
gdcmExplicitImplicitDataElement.h, 968
gdcmFiducials.h, 969
gdcmFile.h, 970
gdcmFileAnonymizer.h, 971
gdcmFileDerivation.h, 972
gdcmFileExplicitFilter.h, 972
gdcmFileMetaInformation.h, 973
gdcmFileSet.h, 976
gdcmFilename.h, 974
gdcmFilenameGenerator.h, 975
gdcmFindPatientRootQuery.h, 978
gdcmFindStudyRootQuery.h, 979
gdcmFragment.h, 979
gdcmGlobal.h, 981
gdcmGroupDict.h, 982
gdcmIOD.h, 1003
gdcmIODEntry.h, 1005
gdcmIODs.h, 1007
gdcmIPPSorter.h, 1008
gdcmIconImage.h, 983
gdcmIconImageFilter.h, 984
gdcmIconImageGenerator.h, 984
gdcmImage.h, 985
gdcmImageApplyLookupTable.h, 987
gdcmImageChangePhotometricInterpretation.h, 987
gdcmImageChangePlanarConfiguration.h, 988
gdcmImageChangeTransferSyntax.h, 989
gdcmImageCodec.h, 990
gdcmImageConverter.h, 991
gdcmImageFragmentSplitter.h, 992
gdcmImageHelper.h, 993
gdcmImageReader.h, 994
gdcmImageRegionReader.h, 996
gdcmImageToImageFilter.h, 996
gdcmImageWriter.h, 997
gdcmImplementationClassUIDSub.h, 998
gdcmImplementationUIDSub.h, 1000
gdcmImplementationVersionNameSub.h, 1000
gdcmImplicitDataElement.h, 1002
gdcmItem.h, 1009
gdcmJPEG12Codec.h, 1010
gdcmJPEG16Codec.h, 1011
gdcmJPEG2000Codec.h, 1012
gdcmJPEG8Codec.h, 1012
gdcmJPEGCodec.h, 1013
gdcmJPEGLSCodec.h, 1015
gdcmKAKADUCodec.h, 1015
gdcmLO.h, 1017
gdcmLegacyMacro.h, 1016
 GDCM_LEGACY, 1017
 GDCM_LEGACY_BODY, 1017
gdcmLookupTable.h, 1018
gdcmMD5.h, 1026
gdcmMacro.h, 1019
gdcmMacroEntry.h, 1022
 GDCMMACROENTRY_H, 1023
gdcmMacros.h, 1023
gdcmMaximumLengthSub.h, 1025
gdcmMediaStorage.h, 1027
gdcmMeshPrimitive.h, 1029
gdcmModule.h, 1030
gdcmModuleEntry.h, 1032
gdcmModules.h, 1034
gdcmMovePatientRootQuery.h, 1035
gdcmMoveStudyRootQuery.h, 1036
gdcmNestedModuleEntries.h, 1037
gdcmNetworkEvents.h, 1039
gdcmNetworkStateID.h, 1040
gdcmObject.h, 1041
gdcmOrientation.h, 1042
gdcmOverlay.h, 1043
gdcmPDBelement.h, 1047
gdcmPDBHeader.h, 1049
gdcmPDFCodec.h, 1050
gdcmPDUFactory.h, 1050
gdcmPDataTFPDU.h, 1046
gdcmPGXCodec.h, 1052
gdcmPNMCodec.h, 1060
gdcmPVRGCodec.h, 1070
gdcmParseException.h, 1044
gdcmParser.h, 1045
gdcmPatient.h, 1046
gdcmPersonName.h, 1051
gdcmPhotometricInterpretation.h, 1053
gdcmPixelFormat.h, 1054
gdcmPixmap.h, 1056
gdcmPixmapReader.h, 1057

- gdcmPixmapToPixmapFilter.h, 1058
- gdcmPixmapWriter.h, 1059
- gdcmPreamble.h, 1061
- gdcmPresentationContext.h, 1062
- gdcmPresentationContextAC.h, 1063
- gdcmPresentationContextGenerator.h, 1064
- gdcmPresentationContextRQ.h, 1065
- gdcmPresentationDataValue.h, 1066
- gdcmPrinter.h, 1067
- gdcmPrivateTag.h, 1068
- gdcmProgressEvent.h, 1069
- gdcmPythonFilter.h, 1071
- gdcmQueryBase.h, 1072
- gdcmQueryFactory.h, 1074
- gdcmQueryImage.h, 1075
- gdcmQueryPatient.h, 1076
- gdcmQuerySeries.h, 1077
- gdcmQueryStudy.h, 1078
- gdcmRAWCodec.h, 1079
- gdcmRLECodec.h, 1083
- gdcmReader.h, 1080
- gdcmRegion.h, 1081
- gdcmRescaler.h, 1082
- gdcmRoleSelectionSub.h, 1084
- gdcmSHA1.h, 1098
- gdcmSOPClassExtendedNegociationSub.h, 1101
- gdcmSOPClassUIDToIOD.h, 1102
- gdcmScanner.h, 1084
- gdcmSegment.h, 1086
- gdcmSegmentHelper.h, 1088
- gdcmSegmentReader.h, 1089
- gdcmSegmentWriter.h, 1090
- gdcmSegmentedPaletteColorLookupTable.h, 1087
- gdcmSequenceOfFragments.h, 1092
- gdcmSequenceOfItems.h, 1092
- gdcmSerieHelper.h, 1093
- gdcmSeries.h, 1095
- gdcmServiceClassApplicationInformation.h, 1096
- gdcmServiceClassUser.h, 1098
- gdcmSimpleSubjectWatcher.h, 1099
- gdcmSmartPointer.h, 1100
- gdcmSorter.h, 1103
- gdcmSpacing.h, 1105
- gdcmSpectroscopy.h, 1105
- gdcmSplitMosaicFilter.h, 1106
- gdcmStaticAssert.h, 1107
 - GDCM_DO_JOIN, 1108
 - GDCM_DO_JOIN2, 1108
 - GDCM_JOIN, 1108
- gdcmStreamImageReader.h, 1109
- gdcmStreamImageWriter.h, 1109
- gdcmString.h, 1110
- gdcmStringFilter.h, 1111
- gdcmStudy.h, 1112
- gdcmSubject.h, 1114
- gdcmSurface.h, 1115
- gdcmSurfaceHelper.h, 1116
- gdcmSurfaceReader.h, 1117
- gdcmSurfaceWriter.h, 1117
- gdcmSwapCode.h, 1118
- gdcmSwapper.h, 1119
- gdcmSystem.h, 1120
- gdcmTable.h, 1121
- gdcmTableEntry.h, 1122
- gdcmTableReader.h, 1124
- gdcmTag.h, 1125
- gdcmTagPath.h, 1126
- gdcmTagToVR.h, 1127
- gdcmTerminal.h, 1127
- gdcmTestDriver.h, 1128
- gdcmTesting.h, 1129
- gdcmTrace.h, 1130
 - GDCM_FUNCTION, 1131
 - gdcmAssertAlwaysMacro, 1131
 - gdcmAssertMacro, 1131
 - gdcmDebugMacro, 1132
 - gdcmErrorMacro, 1132
 - gdcmWarningMacro, 1132
- gdcmTransferSyntax.h, 1133
- gdcmTransferSyntaxSub.h, 1134
- gdcmType.h, 1135
- gdcmTypes.h, 1137
- gdcmUIDGenerator.h, 1137
- gdcmUIDs.h, 1138
- gdcmULAction.h, 1140
- gdcmULActionAA.h, 1141
- gdcmULActionAE.h, 1141
- gdcmULActionAR.h, 1142
- gdcmULActionDT.h, 1143
- gdcmULBasicCallback.h, 1144
- gdcmULConnection.h, 1145
- gdcmULConnectionCallback.h, 1146
- gdcmULConnectionInfo.h, 1147
- gdcmULConnectionManager.h, 1149
- gdcmULEvent.h, 1150
- gdcmULTransitionTable.h, 1151
- gdcmULWritingCallback.h, 1152
- gdcmUNExplicitDataElement.h, 1153
- gdcmUNExplicitImplicitDataElement.h, 1153
- gdcmUnpacker12Bits.h, 1154
- gdcmUsage.h, 1155
- gdcmUserInformation.h, 1157
- gdcmVL.h, 1161
- gdcmVM.h, 1162
 - TYPETOLENGTH, 1164
- gdcmVR.h, 1164
 - TYPETOENCODING, 1166
 - VRTypeTemplateCase, 1166

- gdcmVR16ExplicitDataElement.h, [1166](#)
- gdcmValidate.h, [1158](#)
- gdcmValue.h, [1159](#)
- gdcmValueIO.h, [1159](#)
- gdcmVersion.h, [1160](#)
- gdcmWarningMacro
 - gdcmTrace.h, [1132](#)
- gdcmWaveform.h, [1167](#)
- gdcmWin32.h, [1167](#)
 - GDCM_EXPORT, [1168](#)
- gdcmWriter.h, [1168](#)
- gdcmXMLDictReader.h, [1169](#)
- gdcmXMLPrivateDictReader.h, [1169](#)
- gdcmanon.man, [896](#)
- gdcmconv.man, [930](#)
- gdcmdiff.man, [956](#)
- gdcmdump.man, [960](#)
- gdcmgendir.man, [981](#)
- gdcmimg.man, [998](#)
- gdcminfo.man, [1002](#)
- gdcmpdf.man, [1049](#)
- gdcmraw.man, [1079](#)
- gdcmscanner.man, [1085](#)
- gdcmscu.man, [1086](#)
- gdcmtar.man, [1127](#)
- gdcmviewer.man, [1161](#)
- GeneralECGWaveformStorage
 - gdcm::MediaStorage, [485](#)
 - gdcm::UIDs, [741](#)
- GeneralElectricMagneticResonanceImageStorage
 - gdcm::MediaStorage, [485](#)
- GeneralPurposePerformedProcedureStepSOPClass
 - gdcm::UIDs, [743](#)
- GeneralPurposeScheduledProcedureStepSOPClass
 - gdcm::UIDs, [743](#)
- GeneralPurposeWorklistInformationModelFIND
 - gdcm::UIDs, [743](#)
- GeneralPurposeWorklistManagementMetaSOPClass
 - gdcm::UIDs, [743](#)
- GeneralRelevantPatientInformationQuery
 - gdcm::UIDs, [743](#)
- Generate
 - gdcm::DICOMDIRGenerator, [300](#)
 - gdcm::DummyValueGenerator, [320](#)
 - gdcm::FilenameGenerator, [373](#)
 - gdcm::IconImageGenerator, [391](#)
 - gdcm::UIDGenerator, [732](#)
- GenerateFromFileNames
 - gdcm::PresentationContextGenerator, [565](#)
- GenerateFromUID
 - gdcm::PresentationContextGenerator, [565](#)
- GenerateUUID
 - gdcm::UIDGenerator, [732](#)
- Get
 - gdcm::ByteBuffer, [216](#)
- GetAETitle
 - gdcm::ServiceClassUser, [644](#)
- GetALGOType
 - gdcm::Segment, [619](#)
- GetALGOTypeString
 - gdcm::Segment, [619](#)
- GetAbbreviation
 - gdcm::GroupDict, [387](#)
- GetAbstractSyntax
 - gdcm::network::PresentationContextRQ, [567](#)
 - gdcm::PresentationContext, [562](#)
- GetAbstractSyntaxUID
 - gdcm::BaseRootQuery, [197](#)
 - gdcm::FindPatientRootQuery, [378](#)
 - gdcm::FindStudyRootQuery, [381](#)
 - gdcm::MovePatientRootQuery, [504](#)
 - gdcm::MoveStudyRootQuery, [506](#)
- GetAcceptedPresentationContexts
 - gdcm::network::ULConnection, [790](#)
- GetAlgorithmFamily
 - gdcm::Surface, [686](#)
- GetAlgorithmName
 - gdcm::Surface, [686](#)
- GetAlgorithmVersion
 - gdcm::Surface, [686](#)
- GetAllFileNamesFromTagToValue
 - gdcm::Scanner, [614](#)
- GetAllRequiredTags
 - gdcm::QueryBase, [583](#)
- GetAllTags
 - gdcm::QueryBase, [583](#)
- GetAnatomicRegion
 - gdcm::Segment, [619](#)
- GetAsDataElement
 - gdcm::Attribute, [165](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, [172](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [179](#)
 - gdcm::Element, [325](#)
 - gdcm::Element< TVR, VM::VM1_n >, [328](#)
 - gdcm::network::AbstractSyntax, [145](#)
- GetAsPoints
 - gdcm::Curve, [269](#)
- GetAsString
 - gdcm::CodeString, [239](#)
- GetAxisOfRotation
 - gdcm::Surface, [686](#)
- GetBasicApplicationLevelConfidentialityProfileAttributes
 - gdcm::Anonymizer, [151](#)
- GetBitPosition
 - gdcm::Overlay, [518](#)
- GetBitSample

- gdcm::LookupTable, [474](#)
- GetBitsAllocated
 - gdcm::Overlay, [518](#)
 - gdcm::PixelFormat, [542](#)
- GetBitsStored
 - gdcm::PixelFormat, [543](#)
- GetBlob
 - gdcm::network::PresentationDataValue, [569](#)
- GetBuffer
 - gdcm::Bitmap, [206](#)
 - gdcm::ByteValue, [221](#)
 - gdcm::Overlay, [518](#)
 - gdcm::Parser, [524](#)
 - gdcm::SequenceOfFragments, [630](#)
- GetBuffer2
 - gdcm::Bitmap, [206](#)
- GetBufferAsRGBA
 - gdcm::LookupTable, [474](#)
- GetBufferLength
 - gdcm::Bitmap, [206](#)
 - gdcm::JPEGLSCodec, [466](#)
 - gdcm::PNMCodec, [559](#)
 - gdcm::RLECodec, [608](#)
- GetBuildVersion
 - gdcm::Version, [813](#)
- GetByteValue
 - gdcm::CSAElement, [253](#)
 - gdcm::DataElement, [274](#)
- GetCSADataInfo
 - gdcm::CSAHeader, [258](#)
- GetCSAEEnd
 - gdcm::CSAHeader, [258](#)
- GetCSAElementByName
 - gdcm::CSAHeader, [259](#)
- GetCSAHeaderDict
 - gdcm::Dicts, [311](#)
- GetCSAHeaderDictEntry
 - gdcm::CSAHeaderDict, [261](#)
- GetCSAImageHeaderInfoTag
 - gdcm::CSAHeader, [259](#)
- GetCSASeriesHeaderInfoTag
 - gdcm::CSAHeader, [259](#)
- GetCTImageSeriesUIDs
 - gdcm::DirectoryHelper, [319](#)
- GetCWD
 - gdcm::System, [702](#)
- GetCalledAETitle
 - gdcm::network::AAssociateRQPDU, [142](#)
 - gdcm::network::ULConnectionInfo, [793](#)
 - gdcm::ServiceClassUser, [644](#)
- GetCalledComputerName
 - gdcm::network::ULConnectionInfo, [793](#)
- GetCalledIPAddress
 - gdcm::network::ULConnectionInfo, [793](#)
- GetCalledIPPort
 - gdcm::network::ULConnectionInfo, [793](#)
- GetCallingAETitle
 - gdcm::network::AAssociateRQPDU, [142](#)
 - gdcm::network::ULConnectionInfo, [793](#)
- GetCenterOfRotation
 - gdcm::Surface, [686](#)
- GetCharacterFromCurrentLocale
 - gdcm::QueryFactory, [584](#)
- GetCipherType
 - gdcm::CryptographicMessageSyntax, [251](#)
- GetColorLevel
 - vtkImageColorViewer, [859](#)
- GetColorWindow
 - vtkImageColorViewer, [859](#)
- GetColumns
 - gdcm::Bitmap, [207](#)
 - gdcm::Overlay, [518](#)
- GetCommand
 - gdcm::Subject, [682](#)
- GetConnectionInfo
 - gdcm::network::ULConnection, [790](#)
- GetConstructorString
 - gdcm::Dicts, [311](#)
- GetContourReferencedFrameOfReferenceClassUID
 - vtkRTStructSetProperties, [878](#)
- GetContourReferencedFrameOfReferenceInstanceUID
 - vtkRTStructSetProperties, [878](#)
- GetCryptographicMessageSyntax
 - gdcm::Anonymizer, [151](#)
- GetCurrentByteIndex
 - gdcm::Parser, [524](#)
- GetCurrentDateTime
 - gdcm::System, [701](#)
- GetCurrentModuleFileName
 - gdcm::System, [701](#)
- GetCurrentProcessFileName
 - gdcm::System, [702](#)
- GetCurrentResourcesDirectory
 - gdcm::System, [702](#)
- GetCurve
 - gdcm::Pixmap, [547](#)
- GetCurveDataDescriptor
 - gdcm::Curve, [269](#)
- GetDEEnd
 - gdcm::DataSet, [287](#)
- GetDES
 - gdcm::DataSet, [287](#)
- GetData
 - gdcm::DataEvent, [282](#)
- GetDataElement
 - gdcm::Bitmap, [207](#)
 - gdcm::DataSet, [286](#), [287](#)
 - gdcm::Item, [448](#)

- GetDataExtraRoot
 - gdcm::Testing, [717](#)
- GetDataLength
 - gdcm::DataEvent, [282](#)
- GetDataRoot
 - gdcm::Testing, [717](#)
- GetDataSet
 - gdcm::CSAHeader, [259](#)
 - gdcm::DataSetEvent, [291](#)
 - gdcm::File, [356](#)
- GetDataSetTransferSyntax
 - gdcm::FileMetaInformation, [367](#)
- GetDataSets
 - gdcm::network::ULBasicCallback, [788](#)
- GetDataValueRepresentation
 - gdcm::Curve, [269](#)
- GetDebugFlag
 - gdcm::Trace, [721](#)
- GetDebugStream
 - gdcm::Trace, [721](#)
- GetDecodeLength
 - gdcm::Base64, [190](#)
- GetDefaultTransferSyntax
 - gdcm::PresentationContextGenerator, [565](#)
- GetDefs
 - gdcm::Global, [385](#)
 - gdcm::TableReader, [706](#)
- GetDescription
 - gdcm::CSAHeaderDictEntry, [263](#)
 - gdcm::Exception, [348](#)
 - gdcm::ModuleEntry, [501](#)
 - gdcm::Overlay, [518](#)
- GetDescriptiveName
 - vtkGDCMImageReader, [832](#)
 - vtkGDCMImageWriter, [837](#)
- GetDict
 - gdcm::XMLDictReader, [887](#)
- GetDictEntry
 - gdcm::Dict, [302](#)
 - gdcm::Dicts, [311](#), [312](#)
 - gdcm::PrivateDict, [574](#)
- GetDictEntryByKeyword
 - gdcm::Dict, [302](#)
- GetDictEntryByName
 - gdcm::Dict, [302](#)
- GetDictName
 - gdcm::DictConverter, [305](#)
- GetDictVM
 - gdcm::Attribute, [165](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, [172](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [179](#)
- GetDictVR
 - gdcm::Attribute, [165](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, [172](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [179](#)
- GetDicts
 - gdcm::Global, [385](#)
- GetDimension
 - gdcm::Bitmap, [207](#)
- GetDimensions
 - gdcm::Bitmap, [207](#)
 - gdcm::Curve, [269](#)
 - gdcm::ImageCodec, [413](#)
- GetDimensionsValue
 - gdcm::ImageHelper, [419](#)
- GetDimensionsValueForResolution
 - gdcm::StreamImageReader, [668](#)
- GetDirectionCosines
 - gdcm::Image, [395](#)
- GetDirectionCosinesFromDataSet
 - gdcm::ImageHelper, [420](#)
- GetDirectionCosinesTolerance
 - gdcm::IPPSorter, [444](#)
- GetDirectionCosinesValue
 - gdcm::ImageHelper, [420](#)
- GetDirectories
 - gdcm::Directory, [317](#)
- GetElapsedTime
 - gdcm::network::ARTIMTimer, [160](#)
- GetElement
 - gdcm::Tag, [710](#)
- GetElementTag
 - gdcm::Tag, [711](#)
- GetEncodeLength
 - gdcm::Base64, [191](#)
- GetErrorCode
 - gdcm::Parser, [524](#)
- GetErrorFlag
 - gdcm::Trace, [721](#)
- GetErrorStream
 - gdcm::Trace, [721](#)
- GetErrorString
 - gdcm::Parser, [524](#)
- GetEvent
 - gdcm::network::ULEvent, [797](#)
- GetEventName
 - gdcm::AnonymizeEvent, [147](#)
 - gdcm::DataEvent, [282](#)
 - gdcm::DataSetEvent, [291](#)
 - gdcm::Event, [346](#)
 - gdcm::ProgressEvent, [578](#)
- GetExtension
 - gdcm::Filename, [371](#)
- GetFile

- gdcm::Anonymizer, [151](#)
- gdcm::DICOMDIRGenerator, [300](#)
- gdcm::FileDerivation, [361](#), [362](#)
- gdcm::FileExplicitFilter, [364](#)
- gdcm::IconImageFilter, [389](#)
- gdcm::PythonFilter, [581](#)
- gdcm::Reader, [598](#)
- gdcm::SplitMosaicFilter, [664](#)
- gdcm::StreamImageReader, [668](#)
- gdcm::StringFilter, [679](#)
- gdcm::Writer, [884](#)
- vtkGDCMMedicalImageProperties, [841](#)
- GetFileExtensions
 - vtkGDCMImageReader, [832](#)
 - vtkGDCMImageWriter, [838](#)
- GetFileMetaInformationVersion
 - gdcm::FileMetaInformation, [367](#)
- GetFileName
 - gdcm::Filename, [371](#)
 - gdcm::Testing, [718](#)
 - vtkGDCMImageWriter, [838](#)
 - vtkGDCMThreadedImageReader2, [854](#)
- GetFileNames
 - gdcm::Testing, [718](#)
- GetFilename
 - gdcm::FilenameGenerator, [373](#)
 - gdcm::TableReader, [706](#)
- GetFilenameFromTagToValue
 - gdcm::Scanner, [614](#)
- GetFilenames
 - gdcm::Directory, [317](#)
 - gdcm::FilenameGenerator, [373](#)
 - gdcm::Scanner, [614](#)
 - gdcm::Sorter, [660](#)
- GetFilenamesFromSeriesUIDs
 - gdcm::DirectoryHelper, [319](#)
- GetFiles
 - gdcm::FileSet, [375](#)
- GetFiniteVolume
 - gdcm::Surface, [687](#)
- GetFirstSingleSerieUIDFileSet
 - gdcm::SerieHelper, [640](#)
- GetForcePixelSpacing
 - gdcm::ImageHelper, [420](#)
- GetForceRescaleInterceptSlope
 - gdcm::ImageHelper, [420](#)
- GetFormat
 - gdcm::CSAHeader, [259](#)
- GetFragBuffer
 - gdcm::SequenceOfFragments, [630](#)
- GetFragment
 - gdcm::SequenceOfFragments, [630](#)
- GetFragmentSizeMax
 - gdcm::ImageFragmentSplitter, [418](#)
- GetFrameOfReference
 - gdcm::DirectoryHelper, [319](#)
- GetFullLength
 - gdcm::FileMetaInformation, [368](#)
- GetGDCMDataRoot
 - vtkGDCMTesting, [849](#)
- GetGDCMImplementationClassUID
 - gdcm::FileMetaInformation, [368](#)
- GetGDCMImplementationVersionName
 - gdcm::FileMetaInformation, [368](#)
- GetGDCMSourceApplicationEntityTitle
 - gdcm::FileMetaInformation, [368](#)
- GetGDCMUID
 - gdcm::UIDGenerator, [732](#)
- GetGroup
 - gdcm::Curve, [269](#)
 - gdcm::Overlay, [518](#)
 - gdcm::Tag, [711](#)
- GetHasExpired
 - gdcm::network::ARTIMTimer, [160](#)
- GetHeader
 - gdcm::File, [356](#)
- GetHeaderInfo
 - gdcm::ImageCodec, [413](#)
 - gdcm::JPEG12Codec, [452](#)
 - gdcm::JPEG16Codec, [454](#)
 - gdcm::JPEG2000Codec, [457](#)
 - gdcm::JPEG8Codec, [459](#)
 - gdcm::JPEGCodec, [463](#)
 - gdcm::JPEGLSCodec, [466](#)
 - gdcm::PGXCodec, [537](#)
 - gdcm::PNMCodec, [559](#)
 - gdcm::RAWCodec, [595](#)
 - gdcm::RLECodec, [608](#)
- GetHierarchicalSearchTags
 - gdcm::QueryBase, [583](#)
 - gdcm::QueryImage, [586](#)
 - gdcm::QueryPatient, [588](#)
 - gdcm::QuerySeries, [590](#)
 - gdcm::QueryStudy, [592](#)
- GetHighBit
 - gdcm::PixelFormat, [543](#)
- GetHostName
 - gdcm::System, [702](#)
- GetIE
 - gdcm::IODEntry, [440](#)
- GetIOD
 - gdcm::IODs, [442](#)
 - gdcm::SOPClassUIDToIOD, [657](#)
- GetIODEntry
 - gdcm::IOD, [439](#)
- GetIODFromFile
 - gdcm::Defs, [295](#)
- GetIODFromSOPClassUID

- gdcm::SOPClassUIDToIOD, 657
- GetIODNameFromMediaStorage
 - gdcm::Defs, 295
- GetIODs
 - gdcm::Defs, 295
- GetIconImage
 - gdcm::IconImageFilter, 389
 - gdcm::IconImageGenerator, 391
 - gdcm::Pixmap, 548
 - vtkGDCMImageReader, 832
- GetImage
 - gdcm::ImageReader, 424
 - gdcm::ImageWriter, 432
 - gdcm::PixmapWriter, 556
 - gdcm::SplitMosaicFilter, 664
- GetImplementationClassUID
 - gdcm::FileMetaInformation, 368
- GetImplementationVersionName
 - gdcm::FileMetaInformation, 368
- GetIndex
 - gdcm::SwapCode, 698
 - gdcm::VM, 819
- GetInput
 - gdcm::ImageToImageFilter, 430
 - gdcm::PixmapToPixmapFilter, 554
 - vtkImageColorViewer, 859
- GetInputFilename
 - gdcm::DictConverter, 305
- GetInstance
 - gdcm::Global, 385
- GetIntercept
 - gdcm::Image, 395
 - gdcm::Rescaler, 604
- GetInterfile
 - gdcm::CSAHeader, 259
- GetInternal
 - gdcm::Preamble, 561
- GetIsCommand
 - gdcm::network::PresentationDataValue, 569
- GetIsLastFragment
 - gdcm::network::PresentationDataValue, 569
- GetItem
 - gdcm::SequenceOfItems, 636
- GetKey
 - gdcm::CSAElement, 254
- GetKeys
 - gdcm::Scanner, 614
- GetKeyword
 - gdcm::DictEntry, 306
- GetKeywordFromTag
 - gdcm::Dict, 302
- GetLUT
 - gdcm::Bitmap, 207
 - gdcm::ImageCodec, 413
 - gdcm::ImageHelper, 420
 - gdcm::LookupTable, 474
- GetLUTDescriptor
 - gdcm::LookupTable, 475
- GetLUTLength
 - gdcm::LookupTable, 475
- GetLabel
 - gdcm::Orientation, 514
- GetLastElement
 - gdcm::ParseException, 522
- GetLastSystemError
 - gdcm::System, 702
- GetLength
 - gdcm::ByteValue, 221
 - gdcm::CP246ExplicitDataElement, 249
 - gdcm::DataElement, 274
 - gdcm::DataSet, 287
 - gdcm::Element, 325
 - gdcm::Element< TVR, VM::VM1_n >, 328
 - gdcm::Element< VR::AS, VM::VM5 >, 336
 - gdcm::ExplicitDataElement, 351
 - gdcm::ExplicitImplicitDataElement, 353
 - gdcm::Fragment, 383
 - gdcm::ImplicitDataElement, 436
 - gdcm::Item, 448
 - gdcm::Preamble, 561
 - gdcm::SequenceOfFragments, 631
 - gdcm::SequenceOfItems, 636
 - gdcm::Tag, 711
 - gdcm::UNExplicitDataElement, 801
 - gdcm::UNExplicitImplicitDataElement, 803
 - gdcm::Value, 811
 - gdcm::VL, 815
 - gdcm::VM, 819
 - gdcm::VR, 823, 824
 - gdcm::VR16ExplicitDataElement, 826
- GetLocaleCharset
 - gdcm::System, 702
- GetLossless
 - gdcm::JPEGCodec, 463
 - gdcm::JPEGLSCodec, 466
- GetLossyFlag
 - gdcm::ImageCodec, 413
- GetLossyFlagFromFile
 - gdcm::Testing, 718
- GetMD5DataImage
 - gdcm::Testing, 718
- GetMD5DataImages
 - gdcm::Testing, 718
- GetMD5FromBrokenFile
 - gdcm::Testing, 718
- GetMD5FromFile
 - gdcm::Testing, 718
- GetMD5MetaImage

- vtkGDCMTesting, [849](#)
- GetMHDMD5FromFile
 - vtkGDCMTesting, [849](#)
- GetMPTType
 - gdcm::MeshPrimitive, [495](#)
- GetMPTTypeString
 - gdcm::MeshPrimitive, [495](#)
- GetMRIImageSeriesUIDs
 - gdcm::DirectoryHelper, [319](#)
- GetMSString
 - gdcm::MediaStorage, [487](#)
- GetMSType
 - gdcm::MediaStorage, [487](#)
- GetMTime
 - vtkImageMapToColors16, [864](#)
- GetMacro
 - gdcm::Macros, [479](#)
- GetMacroEntry
 - gdcm::Macro, [477](#)
- GetMacros
 - gdcm::Defs, [295](#)
- GetMajorAxisFromPatientRelativeDirectionCosine
 - gdcm::Orientation, [514](#)
- GetMajorVersion
 - gdcm::Version, [813](#)
- GetManifold
 - gdcm::Surface, [687](#)
- GetMapping
 - gdcm::Scanner, [615](#)
- GetMappingFromTagToValue
 - gdcm::Scanner, [615](#)
- GetMappings
 - gdcm::Scanner, [615](#)
- GetMax
 - gdcm::PixelFormat, [543](#)
- GetMaxLength
 - gdcm::PersonName, [535](#)
- GetMaxPDULength
 - gdcm::network::ULConnectionInfo, [793](#)
- GetMaxPDUSize
 - gdcm::network::ULConnection, [790](#)
- GetMaximumLength
 - gdcm::network::MaximumLengthSub, [480](#)
- GetMaximumLengthSub
 - gdcm::network::UserInformation, [808](#)
- GetMaximumPointDistance
 - gdcm::Surface, [687](#)
- GetMeanPointDistance
 - gdcm::Surface, [687](#)
- GetMediaStorage
 - gdcm::DataSet, [287](#)
 - gdcm::FileMetaInformation, [368](#)
- GetMediaStorageDataFile
 - gdcm::Testing, [718](#)
- GetMediaStorageDataFiles
 - gdcm::Testing, [718](#)
- GetMediaStorageFromFile
 - gdcm::Testing, [718](#)
- GetMeshPrimitive
 - gdcm::Surface, [687](#)
- GetMessageHeader
 - gdcm::network::PresentationDataValue, [569](#)
- GetMetaInformationTS
 - gdcm::FileMetaInformation, [368](#)
- GetMin
 - gdcm::PixelFormat, [543](#)
- GetMinorVersion
 - gdcm::Version, [813](#)
- GetModality
 - gdcm::MediaStorage, [487](#)
- GetModalityDimension
 - gdcm::MediaStorage, [487](#)
- GetModule
 - gdcm::Modules, [502](#)
- GetModuleEntry
 - gdcm::NestedModuleEntries, [509](#)
- GetModuleEntryInMacros
 - gdcm::Module, [498](#)
- GetModules
 - gdcm::Defs, [295](#)
- GetName
 - gdcm::CSAElement, [254](#)
 - gdcm::CSAHeaderDictEntry, [263](#)
 - gdcm::DictEntry, [306](#)
 - gdcm::Filename, [371](#)
 - gdcm::GroupDict, [387](#)
 - gdcm::IODEntry, [440](#)
 - gdcm::Macro, [477](#)
 - gdcm::Module, [498](#)
 - gdcm::ModuleEntry, [501](#)
 - gdcm::network::AbstractSyntax, [145](#)
 - gdcm::network::ApplicationContext, [154](#)
 - gdcm::network::TransferSyntaxSub, [727](#)
 - gdcm::PDBElement, [529](#)
 - gdcm::QueryBase, [583](#)
 - gdcm::QueryImage, [586](#)
 - gdcm::QueryPatient, [588](#)
 - gdcm::QuerySeries, [590](#)
 - gdcm::QueryStudy, [592](#)
 - gdcm::UIDs, [751](#)
- GetNeedByteSwap
 - gdcm::Bitmap, [207](#)
 - gdcm::ImageCodec, [413](#)
- GetNegotiatedType
 - gdcm::TransferSyntax, [725](#)
- GetNestedDataSet
 - gdcm::Item, [448](#), [449](#)
- GetNextSingleSerieUIDFileSet

- gdcm::SerieHelper, [640](#)
- GetNoOfItems
 - gdcm::CSAElement, [254](#)
- GetNumberOfComponents
 - gdcm::PersonName, [535](#)
- GetNumberOfContourReferencedFrameOfReferences
 - vtkRTStructSetProperties, [878](#)
- GetNumberOfCurves
 - gdcm::Curve, [269](#)
 - gdcm::Pixmap, [548](#)
- GetNumberOfDimensions
 - gdcm::Bitmap, [207](#)
 - gdcm::ImageCodec, [413](#)
- GetNumberOfElementsFromArray
 - gdcm::VM, [819](#)
- GetNumberOfFileNames
 - gdcm::Testing, [718](#)
- GetNumberOfFilenames
 - gdcm::FilenameGenerator, [373](#)
- GetNumberOfFragments
 - gdcm::SequenceOfFragments, [631](#)
- GetNumberOfIODs
 - gdcm::IOD, [439](#)
- GetNumberOfIconImages
 - gdcm::IconImageFilter, [390](#)
- GetNumberOfItems
 - gdcm::SequenceOfItems, [636](#)
- GetNumberOfMD5DataImages
 - gdcm::Testing, [718](#)
- GetNumberOfMD5MetaImages
 - vtkGDCMTesting, [849](#)
- GetNumberOfMSString
 - gdcm::MediaStorage, [487](#)
- GetNumberOfMSType
 - gdcm::MediaStorage, [487](#)
- GetNumberOfMediaStorageDataFiles
 - gdcm::Testing, [718](#)
- GetNumberOfModality
 - gdcm::MediaStorage, [487](#)
- GetNumberOfModuleEntries
 - gdcm::NestedModuleEntries, [509](#)
- GetNumberOfOverlays
 - gdcm::Pixmap, [548](#)
- GetNumberOfPoints
 - gdcm::Curve, [269](#)
- GetNumberOfPresentationContext
 - gdcm::network::AAssociateRQPDU, [142](#)
- GetNumberOfPresentationContextAC
 - gdcm::network::AAssociateACPDU, [137](#)
- GetNumberOfPresentationDataValues
 - gdcm::network::PDataTFPDU, [527](#)
- GetNumberOfPrimitivesData
 - gdcm::MeshPrimitive, [495](#)
- GetNumberOfReferencedFrameOfReferences
 - vtkRTStructSetProperties, [878](#)
- GetNumberOfSOPClassToIOD
 - gdcm::SOPClassUIDToIOD, [657](#)
- GetNumberOfSegments
 - gdcm::SegmentWriter, [627](#)
- GetNumberOfStructureSetROIs
 - vtkRTStructSetProperties, [878](#)
- GetNumberOfSurfacePoints
 - gdcm::Surface, [687](#)
- GetNumberOfSurfaces
 - gdcm::SurfaceReader, [694](#)
 - gdcm::SurfaceWriter, [696](#)
- GetNumberOfTransferSyntaxStrings
 - gdcm::UIDs, [751](#)
- GetNumberOfTransferSyntaxes
 - gdcm::network::PresentationContextRQ, [567](#)
 - gdcm::PresentationContext, [562](#)
- GetNumberOfValues
 - gdcm::Attribute, [165](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, [172](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [179](#)
- GetNumberOfVectors
 - gdcm::Surface, [687](#)
- GetObliquityThresholdCosineValue
 - gdcm::Orientation, [514](#)
- GetOffScreenRendering
 - vtkImageColorViewer, [859](#)
- GetOptionalTags
 - gdcm::QueryBase, [583](#)
 - gdcm::QueryImage, [586](#)
 - gdcm::QueryPatient, [588](#)
 - gdcm::QuerySeries, [590](#)
 - gdcm::QueryStudy, [592](#)
- GetOrderedValues
 - gdcm::Scanner, [615](#)
- GetOrigin
 - gdcm::Image, [395](#)
 - gdcm::Overlay, [518](#)
- GetOriginValue
 - gdcm::ImageHelper, [420](#)
- GetOutput
 - gdcm::ImageConverter, [416](#)
- GetOutput
 - gdcm::BitmapToBitmapFilter, [212](#)
 - gdcm::ImageToImageFilter, [430](#)
 - gdcm::PixmapToPixmapFilter, [554](#)
- GetOutputAsBitmap
 - gdcm::BitmapToBitmapFilter, [212](#)
- GetOutputAsPixmap
 - gdcm::PixmapToPixmapFilter, [554](#)
- GetOutputFilename
 - gdcm::DictConverter, [305](#)

GetOutputType
 gdcm::DictConverter, 305

GetOverlay
 gdcm::Pixmap, 548
 vtkGDCMImageReader, 832

GetOverlayData
 gdcm::Overlay, 518

GetOverlayTypeAsString
 gdcm::Overlay, 519

GetOverlayTypeFromString
 gdcm::Overlay, 519

GetOverlayVisibility
 vtkImageColorViewer, 859

GetOwner
 gdcm::PrivateTag, 576

GetPDBEEnd
 gdcm::PDBHeader, 531

GetPDBElementByName
 gdcm::PDBHeader, 531

GetPDBInfoTag
 gdcm::PDBHeader, 531

GetPDUs
 gdcm::network::ULEvent, 797

GetPDVs
 gdcm::network::PDUFactory, 534

GetPIString
 gdcm::PhotometricInterpretation, 539

GetPIType
 gdcm::PhotometricInterpretation, 539

GetPath
 gdcm::Filename, 371

GetPattern
 gdcm::FilenameGenerator, 373

GetPermissions
 gdcm::System, 702

GetPhotometricInterpretation
 gdcm::Bitmap, 207
 gdcm::ImageChangePhotometricInterpretation, 402
 gdcm::ImageCodec, 413

GetPhotometricInterpretationValue
 gdcm::ImageHelper, 420

GetPixelFormat
 gdcm::Bitmap, 207, 208
 gdcm::ImageCodec, 413

GetPixelFormatValue
 gdcm::ImageHelper, 420

GetPixelRepresentation
 gdcm::PixelFormat, 543

GetPixelSize
 gdcm::PixelFormat, 543

GetPixelSpacingDataRoot
 gdcm::Testing, 719

GetPixmap
 gdcm::IconImageGenerator, 392
 gdcm::PixmapReader, 551
 gdcm::PixmapWriter, 556

GetPlanarConfiguration
 gdcm::Bitmap, 208
 gdcm::ImageChangePlanarConfiguration, 405
 gdcm::ImageCodec, 413

GetPlanarConfigurationValue
 gdcm::ImageHelper, 420

GetPointCoordinatesData
 gdcm::Surface, 687

GetPointPositionAccuracy
 gdcm::Surface, 687

GetPointer
 gdcm::ByteValue, 221
 gdcm::LookupTable, 475
 gdcm::SmartPointer, 654
 vtkLookupTable16, 875

GetPointerFromElement
 gdcm::ImageHelper, 420

GetPointsBoundingBoxCoordinates
 gdcm::Surface, 687

GetPosition
 vtkImageColorViewer, 859

GetPreamble
 gdcm::FileMetaInformation, 368

GetPrefix
 gdcm::FilenameGenerator, 374

GetPresentationContext
 gdcm::network::AAssociateRQPDU, 142

GetPresentationContextAC
 gdcm::network::AAssociateACPDU, 137

GetPresentationContextACByID
 gdcm::network::ULConnection, 790

GetPresentationContextByAbstractSyntax
 gdcm::network::AAssociateRQPDU, 142

GetPresentationContextByID
 gdcm::network::AAssociateRQPDU, 142

GetPresentationContextID
 gdcm::network::PresentationContextAC, 563
 gdcm::network::PresentationContextRQ, 567
 gdcm::network::PresentationDataValue, 569
 gdcm::PresentationContext, 562

GetPresentationContextIDFromPresentationContext
 gdcm::network::ULConnection, 790

GetPresentationContextRQByID
 gdcm::network::ULConnection, 790

GetPresentationContexts
 gdcm::network::AAssociateRQPDU, 142
 gdcm::network::ULConnection, 790
 gdcm::PresentationContextGenerator, 566

GetPresentationDataValue
 gdcm::network::PDataTFPDU, 527

GetPrimitiveData
 gdcm::MeshPrimitive, 495

- GetPrimitiveType
 - gdcm::MeshPrimitive, [495](#)
- GetPrimitivesData
 - gdcm::MeshPrimitive, [495](#)
- GetPrintStyle
 - gdcm::Printer, [572](#)
- GetPrivateCreator
 - gdcm::DataSet, [287](#)
 - gdcm::Tag, [711](#)
- GetPrivateDict
 - gdcm::Dicts, [312](#)
 - gdcm::XMLPrivateDictReader, [889](#)
- GetProcessingAlgorithm
 - gdcm::Surface, [687](#)
- GetProgress
 - gdcm::ProgressEvent, [578](#)
- GetPropertyCategory
 - gdcm::Segment, [619](#)
- GetPropertyType
 - gdcm::Segment, [619](#)
- GetProtocol
 - gdcm::network::ULConnection, [790](#)
- GetPublicDict
 - gdcm::Dicts, [312](#)
- GetQuality
 - gdcm::JPEG2000Codec, [457](#)
 - gdcm::JPEGCodec, [463](#)
- GetQueryDataSet
 - gdcm::BaseRootQuery, [197](#)
- GetQueryLevel
 - gdcm::QueryBase, [583](#)
 - gdcm::QueryImage, [586](#)
 - gdcm::QueryPatient, [588](#)
 - gdcm::QuerySeries, [590](#)
 - gdcm::QueryStudy, [592](#)
- GetQueryLevelFromQueryRoot
 - gdcm::BaseRootQuery, [197](#)
- GetQueryLevelFromString
 - gdcm::BaseRootQuery, [197](#)
- GetQueryLevelString
 - gdcm::BaseRootQuery, [197](#)
- GetRAWMD5FromFile
 - vtkGDCMTesting, [849](#)
- GetRTStructSeriesUIDs
 - gdcm::DirectoryHelper, [319](#)
- GetRate
 - gdcm::JPEG2000Codec, [457](#)
- GetReason
 - gdcm::network::PresentationContextAC, [563](#)
- GetRecommendedDisplayCIELabValue
 - gdcm::Surface, [687](#)
- GetRecommendedDisplayGrayscaleValue
 - gdcm::Surface, [687](#)
- GetRecommendedPresentationOpacity
 - gdcm::Surface, [687](#)
- GetRecommendedPresentationType
 - gdcm::Surface, [687](#)
- GetRef
 - gdcm::IODEntry, [440](#)
- GetReferencedFrameOfReferenceClassUID
 - vtkRTStructSetProperties, [878](#)
- GetReferencedFrameOfReferenceInstanceUID
 - vtkRTStructSetProperties, [878](#)
- GetRegion
 - gdcm::ImageRegionReader, [427](#)
- GetRequiredTags
 - gdcm::QueryBase, [583](#)
 - gdcm::QueryImage, [587](#)
 - gdcm::QueryPatient, [589](#)
 - gdcm::QuerySeries, [591](#)
 - gdcm::QueryStudy, [593](#)
- GetRescaleInterceptSlopeValue
 - gdcm::ImageHelper, [420](#)
- GetReserved43_74
 - gdcm::network::AAssociateRQPDU, [142](#)
- GetResponses
 - gdcm::network::ULBasicCallback, [788](#)
- GetRetired
 - gdcm::DictEntry, [306](#)
- GetRoot
 - gdcm::UIDGenerator, [732](#)
- GetRows
 - gdcm::Bitmap, [208](#)
 - gdcm::Overlay, [519](#)
- GetSOPClassUID
 - gdcm::DirectoryHelper, [320](#)
- GetSOPClassUIDFromIOD
 - gdcm::SOPClassUIDToIOD, [657](#)
- GetSOPClassUIDToIOD
 - gdcm::SOPClassUIDToIOD, [657](#)
- GetSOPClassUIDToIODs
 - gdcm::SOPClassUIDToIOD, [657](#)
- GetSTATES
 - gdcm::Surface, [688](#)
- GetSTATESString
 - gdcm::Surface, [688](#)
- GetSamplesPerPixel
 - gdcm::PhotometricInterpretation, [540](#)
 - gdcm::PixelFormat, [543](#)
- GetScalarType
 - gdcm::PixelFormat, [544](#)
- GetScalarTypeAsString
 - gdcm::PixelFormat, [544](#)
- GetScanner
 - gdcm::DICOMDIRGenerator, [300](#)
- GetSegment
 - gdcm::SegmentWriter, [627](#)
- GetSegmentAlgorithmName

- gdcm::Segment, [619](#)
- GetSegmentAlgorithmType
 - gdcm::Segment, [619](#)
- GetSegmentDescription
 - gdcm::Segment, [619](#)
- GetSegmentLabel
 - gdcm::Segment, [619](#)
- GetSegmentNumber
 - gdcm::Segment, [619](#)
- GetSegments
 - gdcm::SegmentReader, [624](#)
 - gdcm::SegmentWriter, [627](#)
- GetSelectedTagsOffsetFromFile
 - gdcm::Testing, [719](#)
- GetSequenceOfFragments
 - gdcm::DataElement, [274](#)
- GetSequenceOfItems
 - gdcm::DataElement, [274](#), [275](#)
- GetSeriesUIDsBySOPClassUID
 - gdcm::DirectoryHelper, [320](#)
- GetSize
 - gdcm::VR, [824](#)
 - vtkImageColorViewer, [860](#)
- GetSizeof
 - gdcm::VR, [824](#)
- GetSliceMax
 - vtkImageColorViewer, [860](#)
- GetSliceMin
 - vtkImageColorViewer, [860](#)
- GetSliceRange
 - vtkImageColorViewer, [860](#)
- GetSlope
 - gdcm::Image, [396](#)
 - gdcm::Rescaler, [604](#)
- GetSourceApplicationEntityTitle
 - gdcm::FileMetaInformation, [368](#)
- GetSourceDirectory
 - gdcm::Testing, [719](#)
- GetSpacing
 - gdcm::Image, [396](#)
- GetSpacingTagFromMediaStorage
 - gdcm::ImageHelper, [420](#)
- GetSpacingValue
 - gdcm::ImageHelper, [421](#)
- GetStart
 - gdcm::ByteBuffer, [216](#)
- GetState
 - gdcm::network::ULConnection, [790](#)
- GetStateIndex
 - gdcm::network, [129](#)
- GetStream
 - gdcm::Trace, [721](#)
- GetStreamOffsetFromFile
 - gdcm::Testing, [719](#)
- GetStreamPtr
 - gdcm::Reader, [599](#)
 - gdcm::Writer, [884](#)
- GetString
 - gdcm::MediaStorage, [487](#)
 - gdcm::PhotometricInterpretation, [540](#)
 - gdcm::TransferSyntax, [725](#)
 - gdcm::UIDs, [752](#)
- GetStringValueFromTag
 - gdcm::DirectoryHelper, [320](#)
- GetStructureSetObservationNumber
 - vtkRTStructSetProperties, [878](#)
- GetStructureSetROIDescription
 - vtkRTStructSetProperties, [878](#)
- GetStructureSetROIGenerationAlgorithm
 - vtkRTStructSetProperties, [878](#)
- GetStructureSetROIName
 - vtkRTStructSetProperties, [878](#)
- GetStructureSetROINumber
 - vtkRTStructSetProperties, [878](#)
- GetStructureSetROIObservationLabel
 - vtkRTStructSetProperties, [878](#)
- GetStructureSetROIRefFrameRefUID
 - vtkRTStructSetProperties, [878](#)
- GetStructureSetRTROIInterpretedType
 - vtkRTStructSetProperties, [878](#)
- GetSurface
 - gdcm::Segment, [619](#)
- GetSurfaceComments
 - gdcm::Surface, [688](#)
- GetSurfaceCount
 - gdcm::Segment, [619](#)
- GetSurfaceNumber
 - gdcm::Surface, [688](#)
- GetSurfaceProcessing
 - gdcm::Surface, [688](#)
- GetSurfaceProcessingDescription
 - gdcm::Surface, [688](#)
- GetSurfaceProcessingRatio
 - gdcm::Surface, [688](#)
- GetSurfaces
 - gdcm::Segment, [620](#)
- GetSwapCode
 - gdcm::TransferSyntax, [725](#)
- GetSwapCodeString
 - gdcm::SwapCode, [698](#)
- GetSyngoDT
 - gdcm::CSAElement, [254](#)
- GetTSString
 - gdcm::TransferSyntax, [725](#)
- GetTSType
 - gdcm::TransferSyntax, [726](#)
- GetTable
 - gdcm::SequenceOfFragments, [631](#)

- GetTableEntry
 - gdcm::Table, 704
- GetTag
 - gdcm::AnonymizeEvent, 147
 - gdcm::Attribute, 166
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, 172
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, 179
 - gdcm::DataElement, 275
- GetTagListByLevel
 - gdcm::BaseRootQuery, 197
 - gdcm::FindPatientRootQuery, 378
 - gdcm::FindStudyRootQuery, 381
 - gdcm::MovePatientRootQuery, 504
 - gdcm::MoveStudyRootQuery, 506
- GetTempDirectory
 - gdcm::Testing, 719
- GetTempDirectoryW
 - gdcm::Testing, 719
- GetTempFilename
 - gdcm::Testing, 719
- GetTempFilenameW
 - gdcm::Testing, 719
- GetTimeout
 - gdcm::network::ARTIMTimer, 160
 - gdcm::ServiceClassUser, 644
- GetTimer
 - gdcm::network::ULConnection, 790
- GetTimezoneOffsetFromUTC
 - gdcm::System, 702
- GetToplevel
 - gdcm::Directory, 318
- GetTransferSyntax
 - gdcm::Bitmap, 208
 - gdcm::ImageChangeTransferSyntax, 408
 - gdcm::network::PresentationContextAC, 563
 - gdcm::network::PresentationContextRQ, 567
 - gdcm::PresentationContext, 562
- GetTransferSyntaxString
 - gdcm::UIDs, 752
- GetTransferSyntaxStrings
 - gdcm::UIDs, 752
- GetTransferSyntaxes
 - gdcm::network::PresentationContextRQ, 567
- GetType
 - gdcm::ModuleEntry, 501
 - gdcm::Orientation, 514
 - gdcm::Overlay, 519
 - gdcm::PhotometricInterpretation, 540
- GetTypeAsEnum
 - gdcm::Overlay, 519
- GetTypeFromTag
 - gdcm::Defs, 295
 - gdcm::IOD, 439
- GetTypeOfData
 - gdcm::Curve, 269
- GetTypeOfDataDescription
 - gdcm::Curve, 269
- GetTypeString
 - gdcm::Type, 730
- GetTypeType
 - gdcm::Type, 730
- GetUIDName
 - gdcm::UIDs, 752
- GetUIDString
 - gdcm::UIDs, 752
- GetUniqueTags
 - gdcm::QueryBase, 583
 - gdcm::QueryImage, 587
 - gdcm::QueryPatient, 589
 - gdcm::QuerySeries, 591
 - gdcm::QueryStudy, 593
- GetUnpackBuffer
 - gdcm::Overlay, 519
- GetUnpackBufferLength
 - gdcm::Overlay, 519
- GetUsage
 - gdcm::IODEntry, 440
- GetUsageString
 - gdcm::Usage, 806
- GetUsageType
 - gdcm::IODEntry, 441
 - gdcm::Usage, 806
- GetUserData
 - gdcm::Parser, 524
- GetUserInformation
 - gdcm::network::AAssociateACPDU, 137
 - gdcm::network::AAssociateRQPDU, 142
- GetVIEWType
 - gdcm::Surface, 688
- GetVIEWTypeString
 - gdcm::Surface, 688
- GetVL
 - gdcm::DataElement, 276
- GetVL16Max
 - gdcm::VL, 815
- GetVL32Max
 - gdcm::VL, 815
- GetVM
 - gdcm::Attribute, 166
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, 172
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_3 >, 175
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_8 >, 177

- gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [179](#)
- gdcm::Attribute< Group, Element, TVR, VM::VM2_-2n >, [183](#)
- gdcm::Attribute< Group, Element, TVR, VM::VM2_n >, [184](#)
- gdcm::Attribute< Group, Element, TVR, VM::VM3_-3n >, [186](#)
- gdcm::Attribute< Group, Element, TVR, VM::VM3_n >, [187](#)
- gdcm::CSAElement, [254](#)
- gdcm::CSAHeaderDictEntry, [263](#)
- gdcm::DictEntry, [307](#)
- gdcm::Element, [325](#)
- gdcm::Element< TVR, VM::VM1_n >, [328](#)
- GetVMString
 - gdcm::VM, [819](#)
- GetVMType
 - gdcm::VM, [819](#)
- GetVMTypeFromLength
 - gdcm::VM, [820](#)
- GetVR
 - gdcm::Attribute, [167](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, [172](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [179](#)
 - gdcm::CSAElement, [254](#)
 - gdcm::CSAHeaderDictEntry, [263](#)
 - gdcm::DataElement, [276](#)
 - gdcm::DictEntry, [307](#)
 - gdcm::Element, [325](#)
 - gdcm::Element< TVR, VM::VM1_n >, [328](#)
- GetVRFromTag
 - gdcm, [119](#)
- GetVRString
 - gdcm::VR, [824](#)
- GetVRStringFromFile
 - gdcm::VR, [824](#)
- GetVRType
 - gdcm::VR, [824](#)
- GetVRTypeFromFile
 - gdcm::VR, [824](#)
- GetVTKDataRoot
 - vtkGDCMTesting, [849](#)
- GetValidatedFile
 - gdcm::Validate, [810](#)
- GetValue
 - gdcm::Attribute, [166](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, [172](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [179](#)
 - gdcm::CSAElement, [254](#)
 - gdcm::DataElement, [275](#)
 - gdcm::Element, [325](#)
 - gdcm::Element< TVR, VM::VM1_n >, [328](#)
 - gdcm::PDBelement, [529](#)
 - gdcm::Scanner, [615](#)
- GetValueAsSQ
 - gdcm::DataElement, [275](#)
- GetValues
 - gdcm::Attribute, [166](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, [172](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [179](#)
 - gdcm::Element, [325](#)
 - gdcm::Scanner, [615](#)
- GetVectorAccuracy
 - gdcm::Surface, [688](#)
- GetVectorCoordinateData
 - gdcm::Surface, [688](#)
- GetVectorDimensionality
 - gdcm::Surface, [688](#)
- GetVersion
 - gdcm::Version, [813](#)
- GetWarningFlag
 - gdcm::Trace, [721](#)
- GetWarningStream
 - gdcm::Trace, [721](#)
- GetWindowName
 - vtkImageColorViewer, [860](#)
- GetXMax
 - gdcm::BoxRegion, [215](#)
- GetXMin
 - gdcm::BoxRegion, [215](#)
- GetYMax
 - gdcm::BoxRegion, [215](#)
- GetYMin
 - gdcm::BoxRegion, [215](#)
- GetZMax
 - gdcm::BoxRegion, [215](#)
- GetZMin
 - gdcm::BoxRegion, [215](#)
- GetZSpacing
 - gdcm::IPPSorter, [444](#)
- GetZSpacingTagFromMediaStorage
 - gdcm::ImageHelper, [421](#)
- GetZSpacingTolerance
 - gdcm::IPPSorter, [445](#)
- Global
 - gdcm::Defs, [296](#)
 - gdcm::Dicts, [312](#)
 - gdcm::Global, [385](#)
- GlobalInstance
 - gdcm, [124](#)
- GrabOverlayFromPixelData

- gdcmm::Overlay, 519
- Graphics
 - gdcmm::Overlay, 517
- GrayscaleSoftcopyPresentationStateStorageSOPClass
 - gdcmm::MediaStorage, 485
 - gdcmm::UIDs, 742
- green
 - gdcmm::terminal, 131
- group
 - gdcmm::SerieHelper::Rule, 610
- GroupDict
 - gdcmm::GroupDict, 387
- GroupStringVector
 - gdcmm::GroupDict, 387
- GuessFromModality
 - gdcmm::MediaStorage, 487
- HSV
 - gdcmm::PhotometricInterpretation, 539
- HandleDataSet
 - gdcmm::network::ULBasicCallback, 788
 - gdcmm::network::ULConnectionCallback, 792
 - gdcmm::network::ULWritingCallback, 800
- HandleDescription
 - gdcmm::XMLDictReader, 887
 - gdcmm::XMLPrivateDictReader, 889
- HandleEntry
 - gdcmm::XMLDictReader, 887
 - gdcmm::XMLPrivateDictReader, 889
- HandleEvent
 - gdcmm::network::ULTransitionTable, 798
- HandleIOD
 - gdcmm::TableReader, 706
- HandleIODEntry
 - gdcmm::TableReader, 706
- HandleMacro
 - gdcmm::TableReader, 706
- HandleMacroEntry
 - gdcmm::TableReader, 706
- HandleMacroEntryDescription
 - gdcmm::TableReader, 706
- HandleModule
 - gdcmm::TableReader, 706
- HandleModuleEntry
 - gdcmm::TableReader, 706
- HandleModuleEntryDescription
 - gdcmm::TableReader, 706
- HandleModuleInclude
 - gdcmm::TableReader, 707
- HandleResponse
 - gdcmm::network::ULBasicCallback, 788
 - gdcmm::network::ULConnectionCallback, 792
 - gdcmm::network::ULWritingCallback, 800
- HangingProtocolInformationModelFIND
 - gdcmm::UIDs, 744
- HangingProtocolInformationModelMOVE
 - gdcmm::UIDs, 744
- HangingProtocolStorage
 - gdcmm::MediaStorage, 486
 - gdcmm::UIDs, 744
- HardcopyColorImageStorageSOPClassRetired
 - gdcmm::UIDs, 741
- HardcopyGrayscaleImageStorage
 - gdcmm::MediaStorage, 485
- HardcopyGrayscaleImageStorageSOPClassRetired
 - gdcmm::UIDs, 741
- HasObserver
 - gdcmm::Subject, 682
- HemodynamicWaveformStorage
 - gdcmm::MediaStorage, 485
 - gdcmm::UIDs, 741
- hidden
 - gdcmm::terminal, 131
- ICBM452T1FrameofReference
 - gdcmm::UIDs, 740
- ICBMSingleSubjectMRIFrameofReference
 - gdcmm::UIDs, 740
- INT12
 - gdcmm::PixelFormat, 542
- INT16
 - gdcmm::PixelFormat, 542
- INT32
 - gdcmm::PixelFormat, 542
- INT8
 - gdcmm::PixelFormat, 542
- INTERFILE
 - gdcmm::CSAHeader, 258
- INVALID
 - gdcmm::VR, 822
- IS
 - gdcmm::VR, 823
- IOD
 - gdcmm::IOD, 438
- IODEntry
 - gdcmm::IODEntry, 440
- IODMapType
 - gdcmm::IODs, 442
- IODMapTypeConstIterator
 - gdcmm::IODs, 442
- IODName
 - gdcmm::IODs, 442
- IODs
 - gdcmm::IODs, 442
- IPPSorter
 - gdcmm::IPPSorter, 444
- Icon
 - gdcmm::Pixmap, 548

- IconDataScalarType
 - vtkGDCMImageReader, [834](#)
- IconImage
 - gdcm, [117](#)
- IconImageDataExtent
 - vtkGDCMImageReader, [834](#)
- IconImageFilter
 - gdcm::IconImageFilter, [389](#)
- IconImageGenerator
 - gdcm::IconImageGenerator, [391](#)
- IconNumberOfScalarComponents
 - vtkGDCMImageReader, [834](#)
- ignore_char
 - gdcm::ignore_char, [393](#)
- Image
 - gdcm::Image, [395](#)
- ImageOverlayBoxSOPClassRetired
 - gdcm::UIDs, [741](#)
- ImageActor
 - vtkImageColorViewer, [862](#)
- ImageApplyLookupTable
 - gdcm::ImageApplyLookupTable, [399](#)
- ImageChangePhotometricInterpretation
 - gdcm::ImageChangePhotometricInterpretation, [402](#)
 - gdcm::ImageCodec, [414](#)
- ImageChangePlanarConfiguration
 - gdcm::ImageChangePlanarConfiguration, [405](#)
- ImageChangeTransferSyntax
 - gdcm::Bitmap, [210](#)
 - gdcm::ImageChangeTransferSyntax, [408](#)
- ImageCodec
 - gdcm::ImageCodec, [412](#)
- ImageConverter
 - gdcm::ImageConverter, [416](#)
- ImageFormat
 - vtkGDCMImageReader, [834](#)
- ImageFragmentSplitter
 - gdcm::ImageFragmentSplitter, [418](#)
- ImageOrientationPatient
 - vtkGDCMImageReader, [834](#)
- ImagePositionPatient
 - vtkGDCMImageReader, [834](#)
- ImagePositionPatientOrdering
 - gdcm::SerieHelper, [640](#)
- ImageReader
 - gdcm::ImageReader, [424](#)
- ImageRegionReader
 - gdcm::ImageRegionReader, [427](#)
 - gdcm::JPEG2000Codec, [457](#)
 - gdcm::JPEGCodec, [463](#)
 - gdcm::JPEGLSCCodec, [467](#)
 - gdcm::RLECodec, [608](#)
- ImageToImageFilter
 - gdcm::ImageToImageFilter, [430](#)
- ImageWriter
 - gdcm::ImageWriter, [432](#)
- ImplementationClassUIDSub
 - gdcm::network::ImplementationClassUIDSub, [433](#)
- ImplementationUIDSub
 - gdcm::network::ImplementationUIDSub, [434](#)
- ImplementationVersionNameSub
 - gdcm::network::ImplementationVersionNameSub, [434](#)
- Implicit
 - gdcm::TransferSyntax, [724](#)
- ImplicitVRBigEndianACRNEMA
 - gdcm::TransferSyntax, [725](#)
- ImplicitVRBigEndianPrivateGE
 - gdcm::TransferSyntax, [724](#)
- ImplicitVRLittleEndian
 - gdcm::TransferSyntax, [724](#)
- ImplicitVRLittleEndianDefaultTransferSyntaxforDICOM
 - gdcm::UIDs, [738](#)
- IncompleteLUT
 - gdcm::LookupTable, [476](#)
- InitFromRQ
 - gdcm::network::AAssociateACPDU, [137](#)
- Initialize
 - gdcm::network::ULConnectionInfo, [793](#)
- InitializeBlueLUT
 - gdcm::LookupTable, [475](#)
- InitializeConnection
 - gdcm::network::ULConnection, [791](#)
 - gdcm::ServiceClassUser, [644](#)
- InitializeDataSet
 - gdcm::BaseRootQuery, [197](#)
 - gdcm::FindPatientRootQuery, [379](#)
 - gdcm::FindStudyRootQuery, [381](#)
 - gdcm::MovePatientRootQuery, [504](#)
 - gdcm::MoveStudyRootQuery, [507](#)
- InitializeGreenLUT
 - gdcm::LookupTable, [475](#)
- InitializeIncomingConnection
 - gdcm::network::ULConnection, [791](#)
- InitializeLUT
 - gdcm::LookupTable, [475](#)
- InitializeRTStructSet
 - vtkGDCMPolyDataWriter, [846](#)
- InitializeRedLUT
 - gdcm::LookupTable, [475](#)
- Initialized
 - gdcm::LookupTable, [475](#)
- Input
 - gdcm::BitmapToBitmapFilter, [212](#)
- Insert
 - gdcm::CommandDataSet, [243](#)
 - gdcm::DataSet, [287](#)
 - gdcm::FileMetaInformation, [368](#)

- gdcmm::GroupDict, [387](#)
- InsertDataElement
 - gdcmm::DataSet, [287](#)
 - gdcmm::Item, [449](#)
- InsertEntry
 - gdcmm::Table, [704](#)
- InstallPipeline
 - vtkImageColorViewer, [860](#)
- InstanceAvailabilityNotificationSOPClass
 - gdcmm::UIDs, [743](#)
- Interactor
 - vtkImageColorViewer, [862](#)
- InteractorStyle
 - vtkImageColorViewer, [862](#)
- Internal
 - gdcmm::ApplicationEntity, [156](#)
 - gdcmm::Attribute, [169](#)
 - gdcmm::Attribute< Group, Element, TVR, VM::VM1 >, [174](#)
 - gdcmm::Element, [325](#)
 - gdcmm::Element< VR::AS, VM::VM5 >, [336](#)
 - gdcmm::LookupTable, [476](#)
 - gdcmm::UI, [731](#)
- InternalCode
 - gdcmm::Coder, [236](#)
 - gdcmm::JPEG12Codec, [452](#)
 - gdcmm::JPEG16Codec, [454](#)
 - gdcmm::JPEG8Codec, [459](#)
- Internals
 - vtkRTStructSetProperties, [879](#)
- Invalid
 - gdcmm::Overlay, [517](#)
 - gdcmm::Usage, [806](#)
- InverseRescale
 - gdcmm::Rescaler, [604](#)
- InverseRescaleFunctionIntoBestFit
 - gdcmm::Rescaler, [604](#)
- InvokeEvent
 - gdcmm::Subject, [682](#)
- IsAETitleValid
 - gdcmm::network::AAAssociateRQPDU, [142](#)
- IsASCII
 - gdcmm::VR, [824](#)
- IsASCII2
 - gdcmm::VR, [824](#)
- IsBinary
 - gdcmm::VR, [824](#)
- IsBinary2
 - gdcmm::VR, [824](#)
- IsDual
 - gdcmm::VR, [824](#)
- IsEmpty
 - gdcmm::Bitmap, [208](#)
 - gdcmm::ByteValue, [222](#)
- gdcmm::CSAElement, [254](#)
- gdcmm::CSAHeaderDict, [261](#)
- gdcmm::Curve, [269](#)
- gdcmm::DataElement, [276](#)
- gdcmm::DataSet, [287](#)
- gdcmm::Defs, [295](#)
- gdcmm::Dict, [303](#)
- gdcmm::Dicts, [312](#)
- gdcmm::Filename, [371](#)
- gdcmm::Macros, [479](#)
- gdcmm::Modules, [502](#)
- gdcmm::Overlay, [519](#)
- gdcmm::Preamble, [561](#)
- gdcmm::PrivateDict, [574](#)
- gdcmm::SegmentHelper::BasicCodedEntry, [200](#)
- IsEncapsulated
 - gdcmm::TransferSyntax, [726](#)
- IsEncoded
 - gdcmm::TransferSyntax, [726](#)
- IsExplicit
 - gdcmm::TransferSyntax, [726](#)
- IsGroupLength
 - gdcmm::Tag, [711](#)
- IsGroupXX
 - gdcmm::Tag, [711](#)
- IsIdentical
 - gdcmm::Filename, [371](#)
- IsIllegal
 - gdcmm::Tag, [711](#)
- IsImage
 - gdcmm::MediaStorage, [487](#)
- IsImplicit
 - gdcmm::TransferSyntax, [726](#)
- IsInPixelData
 - gdcmm::Overlay, [519](#)
- IsKey
 - gdcmm::Scanner, [615](#)
- IsLastFragment
 - gdcmm::network::AAAbortPDU, [134](#)
 - gdcmm::network::AAAssociateACPDU, [137](#)
 - gdcmm::network::AAAssociateRJPDU, [139](#)
 - gdcmm::network::AAAssociateRQPDU, [142](#)
 - gdcmm::network::AResponseRPPDU, [158](#)
 - gdcmm::network::AResponseRQPDU, [159](#)
 - gdcmm::network::BasePDU, [194](#)
 - gdcmm::network::PDataTFPDU, [527](#)
- IsLossless
 - gdcmm::PhotometricInterpretation, [540](#)
 - gdcmm::TransferSyntax, [726](#)
- IsLossy
 - gdcmm::Bitmap, [208](#)
 - gdcmm::ImageCodec, [413](#)
 - gdcmm::PhotometricInterpretation, [540](#)
 - gdcmm::TransferSyntax, [726](#)

- IsOdd
 - gdcm::VL, [815](#)
- IsPresentationContextAccepted
 - gdcm::ServiceClassUser, [644](#)
- IsPrintable
 - gdcm::ByteValue, [222](#)
- IsPrivate
 - gdcm::Tag, [711](#)
- IsPrivateCreator
 - gdcm::Tag, [712](#)
- IsPublic
 - gdcm::Tag, [712](#)
- IsRetired
 - gdcm::PhotometricInterpretation, [540](#)
- IsSameColorSpace
 - gdcm::PhotometricInterpretation, [540](#)
- IsStateSuspension
 - gdcm::JPEG12Codec, [452](#)
 - gdcm::JPEG16Codec, [454](#)
 - gdcm::JPEG8Codec, [459](#)
 - gdcm::JPEGCodec, [463](#)
- IsSwap
 - gdcm::VR, [824](#)
- IsTransferSyntaxCompatible
 - gdcm::Bitmap, [208](#)
- IsUndefined
 - gdcm::MediaStorage, [487](#)
 - gdcm::VL, [815](#)
- IsUndefinedLength
 - gdcm::DataElement, [276](#)
 - gdcm::SequenceOfItems, [636](#)
- IsUnique
 - gdcm::DictEntry, [307](#)
- IsVRFile
 - gdcm::VR, [824](#)
- IsValid
 - gdcm::ApplicationEntity, [156](#)
 - gdcm::BoxRegion, [215](#)
 - gdcm::CodeString, [239](#)
 - gdcm::DirectionCosines, [315](#)
 - gdcm::FileMetaInformation, [368](#)
 - gdcm::ImageCodec, [413](#)
 - gdcm::JPEGCodec, [463](#)
 - gdcm::LO, [471](#)
 - gdcm::PixelFormat, [544](#)
 - gdcm::Preamble, [561](#)
 - gdcm::Region, [602](#)
 - gdcm::String, [677](#)
 - gdcm::TagPath, [715](#)
 - gdcm::TransferSyntax, [726](#)
 - gdcm::UIDGenerator, [733](#)
 - gdcm::VM, [820](#)
 - gdcm::VR, [824](#)
- IsZero
 - gdcm::Overlay, [519](#)
- ItFileSetHt
 - gdcm::SerieHelper, [640](#)
- Item
 - gdcm::Item, [448](#)
- ItemVector
 - gdcm::SequenceOfItems, [635](#)
- Items
 - gdcm::SequenceOfItems, [637](#)
- Iterator
 - gdcm::CSAHeaderDict, [261](#)
 - gdcm::DataSet, [285](#)
 - gdcm::Dict, [302](#)
 - gdcm::SequenceOfFragments, [630](#)
 - gdcm::SequenceOfItems, [635](#)
- iterator
 - gdcm::CodeString, [238](#)
 - gdcm::LO, [471](#)
 - gdcm::String, [676](#)
- JPEG2000
 - gdcm::TransferSyntax, [725](#)
- JPEG2000_COMPRESSION
 - vtkGDCMImageWriter, [837](#)
- JPEG2000ImageCompression
 - gdcm::UIDs, [739](#)
- JPEG2000ImageCompressionLosslessOnly
 - gdcm::UIDs, [739](#)
- JPEG2000Lossless
 - gdcm::TransferSyntax, [725](#)
- JPEG2000Part2
 - gdcm::TransferSyntax, [725](#)
- JPEG2000Part2Lossless
 - gdcm::TransferSyntax, [725](#)
- JPEG2000Part2MulticomponentImageCompression
 - gdcm::UIDs, [739](#)
- JPEG2000Part2MulticomponentImageCompression-LosslessOnly
 - gdcm::UIDs, [739](#)
- JPEG_COMPRESSION
 - vtkGDCMImageWriter, [837](#)
- JPEGBaselineProcess1
 - gdcm::TransferSyntax, [725](#)
- JPEGBaselineProcess1DefaultTransferSyntaxforLossyJPEGBitImageCompression
 - gdcm::UIDs, [738](#)
- JPEGExtendedHierarchicalProcess1618Retired
 - gdcm::UIDs, [739](#)
- JPEGExtendedHierarchicalProcess1719Retired
 - gdcm::UIDs, [739](#)
- JPEGExtendedProcess24DefaultTransferSyntaxforLossyJPEGBitImageCompressionProcess4only
 - gdcm::UIDs, [738](#)
- JPEGExtendedProcess2_4

- gdcm::TransferSyntax, [725](#)
- JPEGExtendedProcess35Retired
 - gdcm::UIDs, [738](#)
- JPEGExtendedProcess3_5
 - gdcm::TransferSyntax, [725](#)
- JPEGFullProgressionHierarchicalProcess2426Retired
 - gdcm::UIDs, [739](#)
- JPEGFullProgressionHierarchicalProcess2527Retired
 - gdcm::UIDs, [739](#)
- JPEGFullProgressionNonHierarchicalProcess1012-Retired
 - gdcm::UIDs, [738](#)
- JPEGFullProgressionNonHierarchicalProcess1113-Retired
 - gdcm::UIDs, [738](#)
- JPEGFullProgressionProcess10_12
 - gdcm::TransferSyntax, [725](#)
- JPEGLS_COMPRESSION
 - vtkGDCMImageWriter, [837](#)
- JPEGLSLossless
 - gdcm::TransferSyntax, [725](#)
- JPEGLSLosslessImageCompression
 - gdcm::UIDs, [739](#)
- JPEGLSLossyNearLosslessImageCompression
 - gdcm::UIDs, [739](#)
- JPEGLSNearLossless
 - gdcm::TransferSyntax, [725](#)
- JPEGLosslessHierarchicalProcess28Retired
 - gdcm::UIDs, [739](#)
- JPEGLosslessHierarchicalProcess29Retired
 - gdcm::UIDs, [739](#)
- JPEGLosslessNonHierarchicalFirstOrderPrediction-Process14SelectionValue1DefaultTransfer-SyntaxforLosslessJPEGImageCompression
 - gdcm::UIDs, [739](#)
- JPEGLosslessNonHierarchicalProcess14
 - gdcm::UIDs, [738](#)
- JPEGLosslessNonHierarchicalProcess15Retired
 - gdcm::UIDs, [739](#)
- JPEGLosslessProcess14
 - gdcm::TransferSyntax, [725](#)
- JPEGLosslessProcess14_1
 - gdcm::TransferSyntax, [725](#)
- JPEGSpectralSelectionHierarchicalProcess2022Retired
 - gdcm::UIDs, [739](#)
- JPEGSpectralSelectionHierarchicalProcess2123Retired
 - gdcm::UIDs, [739](#)
- JPEGSpectralSelectionNonHierarchicalProcess68Retired
 - gdcm::UIDs, [738](#)
- JPEGSpectralSelectionNonHierarchicalProcess79Retired
 - gdcm::UIDs, [738](#)
- JPEGSpectralSelectionProcess6_8
 - gdcm::TransferSyntax, [725](#)
- JPIPReferenced
 - gdcm::TransferSyntax, [725](#)
 - gdcm::UIDs, [739](#)
- JPIPReferencedDeflate
 - gdcm::UIDs, [739](#)
- JPEG12Codec
 - gdcm::JPEG12Codec, [452](#)
- JPEG16Codec
 - gdcm::JPEG16Codec, [454](#)
- JPEG2000Codec
 - gdcm::JPEG2000Codec, [456](#)
- JPEG8Codec
 - gdcm::JPEG8Codec, [459](#)
- JPEGCodec
 - gdcm::JPEGCodec, [462](#)
- JPEGLSCodec
 - gdcm::JPEGLSCodec, [466](#)
- Join
 - gdcm::Filename, [371](#)
- JunkAfterDocElementError
 - gdcm::Parser, [524](#)
- KAKADUCodec
 - gdcm::KAKADUCodec, [468](#)
- KeyObjectSelectionDocument
 - gdcm::MediaStorage, [485](#)
- KeyObjectSelectionDocumentStorage
 - gdcm::UIDs, [743](#)
- KeyField
 - gdcm::CSAElement, [255](#)
- KeyValuePairArrayType
 - gdcm::CompositeNetworkFunctions, [245](#)
- KeyValuePairType
 - gdcm::CompositeNetworkFunctions, [245](#)
- LD_ALL
 - gdcm, [119](#)
- LD_NOSEQ
 - gdcm, [119](#)
- LD_NOSHADOW
 - gdcm, [119](#)
- LD_NOSHADOWSEQ
 - gdcm, [119](#)
- LINE
 - gdcm::MeshPrimitive, [494](#)
- LO
 - gdcm::VR, [823](#)
- LT
 - gdcm::VR, [823](#)
- LO
 - gdcm::LO, [471](#)
- LOComp
 - gdcm, [118](#)
- LTComp
 - gdcm, [118](#)
- LUT

- gdcm::Bitmap, [210](#)
- gdcm::ImageCodec, [415](#)
- LUTPtr
 - gdcm::Bitmap, [206](#)
 - gdcm::ImageCodec, [412](#)
- LeadECGWaveformStorage
 - gdcm::MediaStorage, [485](#)
- Level
 - vtkImageMapToWindowLevelColors2, [868](#)
- ListCharSets
 - gdcm::QueryFactory, [584](#)
- LittleEndian
 - gdcm::SwapCode, [697](#)
- Load
 - gdcm::Directory, [318](#)
- LoadDefault
 - gdcm::CSAHeaderDict, [261](#)
 - gdcm::Dict, [303](#)
 - gdcm::PrivateDict, [574](#)
- LoadDefaults
 - gdcm::Defs, [295](#)
 - gdcm::Dicts, [312](#)
- LoadFromDataElement
 - gdcm::CSAHeader, [259](#)
 - gdcm::PDBHeader, [531](#)
- LoadFromFile
 - gdcm::Defs, [295](#)
- LoadIconImage
 - vtkGDCMImageReader, [835](#)
- LoadImageFromFiles
 - gdcm::DirectoryHelper, [320](#)
- LoadOverlays
 - vtkGDCMImageReader, [835](#)
- LoadResourcesFiles
 - gdcm::Global, [386](#)
- LoadSingleFile
 - vtkGDCMImageReader, [832](#)
- Locate
 - gdcm::Global, [386](#)
- LodModeType
 - gdcm, [119](#)
- LookupTable
 - gdcm::LookupTable, [474](#)
 - vtkImageMapToColors16, [865](#)
- LookupTableType
 - gdcm::LookupTable, [474](#)
- Lossless
 - gdcm::JPEGCodec, [463](#)
- LossyFlag
 - gdcm::Bitmap, [210](#)
 - gdcm::ImageCodec, [415](#)
 - vtkGDCMImageReader, [835](#)
- MAGNIFIED
 - gdcm::Spacing, [662](#)
- MANUAL
 - gdcm::Segment, [619](#)
- MONOCHROME1
 - gdcm::PhotometricInterpretation, [539](#)
- MONOCHROME2
 - gdcm::PhotometricInterpretation, [539](#)
- MPEG2MainProfile
 - gdcm::TransferSyntax, [725](#)
- MPEG2MainProfileMainLevel
 - gdcm::UIDs, [739](#)
- MPTType_END
 - gdcm::MeshPrimitive, [494](#)
- MRImageStorage
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- MRSpectroscopyStorage
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- MS_END
 - gdcm::MediaStorage, [486](#)
- m_ConstMemberFunction
 - gdcm::MemberCommand, [492](#)
- m_MemberFunction
 - gdcm::MemberCommand, [492](#)
 - gdcm::SimpleMemberCommand, [650](#)
- m_This
 - gdcm::MemberCommand, [492](#)
 - gdcm::SimpleMemberCommand, [650](#)
- m_char
 - gdcm::ignore_char, [393](#)
- mAction
 - gdcm::network::Transition, [729](#)
- MD5
 - gdcm::MD5, [481](#)
- MD5DataImagesType
 - gdcm::Testing, [717](#)
- MD5MetalImagesType
 - vtkGDCMTesting, [849](#)
- mDataSet
 - gdcm::BaseRootQuery, [198](#)
- mElementOffsets
 - gdcm::StreamImageWriter, [673](#)
- mElementOffsets1
 - gdcm::StreamImageWriter, [673](#)
- mEnd
 - gdcm::network::Transition, [729](#)
- mHelpDescription
 - gdcm::BaseRootQuery, [198](#)
- mImage
 - gdcm::BaseRootQuery, [198](#)
- MPTType
 - gdcm::MeshPrimitive, [494](#)
- mPatient

- gdcmm::BaseRootQuery, 198
- mRootType
 - gdcmm::BaseRootQuery, 198
- MSType
 - gdcmm::MediaStorage, 484
- mSeries
 - gdcmm::BaseRootQuery, 198
- mStudy
 - gdcmm::BaseRootQuery, 198
- mWriter
 - gdcmm::StreamImageWriter, 674
- mXMax
 - gdcmm::StreamImageWriter, 674
- mXMin
 - gdcmm::StreamImageWriter, 674
- mYMax
 - gdcmm::StreamImageWriter, 674
- mYMin
 - gdcmm::StreamImageWriter, 674
- mZMax
 - gdcmm::StreamImageWriter, 674
- mZMin
 - gdcmm::StreamImageWriter, 674
- Macro
 - gdcmm::Macro, 477
- MacroEntry
 - gdcmm, 118
- Macros
 - gdcmm::Macros, 479
- magenta
 - gdcmm::terminal, 131
- MakeDirectory
 - gdcmm::System, 702
- MakeNew
 - gdcmm::network::Transition, 729
- MakeObject
 - gdcmm::AnonymizeEvent, 147
 - gdcmm::DataEvent, 282
 - gdcmm::DataSetEvent, 291
 - gdcmm::Event, 346
 - gdcmm::ProgressEvent, 578
- MammographyCADSR
 - gdcmm::MediaStorage, 485
- MammographyCADSRStorage
 - gdcmm::UIDs, 742
- Mandatory
 - gdcmm::Usage, 806
- MapCSAHeaderDictEntry
 - gdcmm::CSAHeaderDict, 261
- MapDictEntry
 - gdcmm::Dict, 302
- MapIODEntry
 - gdcmm::IOD, 438
- MapModuleEntry
 - gdcmm::Macro, 477
 - gdcmm::Module, 498
- MapScalarsThroughTable2
 - vtkLookupTable16, 875
- MapTableEntry
 - gdcmm::Table, 704
- MappingType
 - gdcmm::Scanner, 613
- MaxLength
 - gdcmm::ApplicationEntity, 156
 - gdcmm::PersonName, 536
- MaxNumberOfComponents
 - gdcmm::ApplicationEntity, 156
 - gdcmm::PersonName, 536
- MaxPrintLength
 - gdcmm::Printer, 573
- MaximumLengthSub
 - gdcmm::network::MaximumLengthSub, 480
- MediaCreationManagementSOPClassUID
 - gdcmm::UIDs, 741
- MediaStorageDirectoryStorage
 - gdcmm::MediaStorage, 484
 - gdcmm::UIDs, 739
- MediaStorage
 - gdcmm::MediaStorage, 487
- MediaStorageDataFilesType
 - gdcmm::Testing, 717
- MedicalImageProperties
 - vtkGDCMImageReader, 835
 - vtkGDCMPolyDataReader, 844
 - vtkGDCMPolyDataWriter, 847
- MemberCommand
 - gdcmm::MemberCommand, 491
- MeshPrimitive
 - gdcmm::MeshPrimitive, 495
- MessageID
 - gdcmm::network::CEchoRQ, 224
- MetaInformationTS
 - gdcmm::FileMetaInformation, 369
- ModalityPerformedProcedureStepNotificationSOPClass
 - gdcmm::UIDs, 740
- ModalityPerformedProcedureStepRetrieveSOPClass
 - gdcmm::UIDs, 740
- ModalityPerformedProcedureStepSOPClass
 - gdcmm::MediaStorage, 486
 - gdcmm::UIDs, 740
- ModalityWorklistInformationModelIFIND
 - gdcmm::UIDs, 743
- Mode
 - gdcmm::terminal, 131
- Module
 - gdcmm::Module, 498
- ModuleEntry
 - gdcmm::ModuleEntry, 500

- ModuleMapType
 - gdcm::Macros, [479](#)
 - gdcm::Modules, [502](#)
- Modules
 - gdcm::Modules, [502](#)
- MovePatientRootQuery
 - gdcm::MovePatientRootQuery, [504](#)
- MoveStudyRootQuery
 - gdcm::MoveStudyRootQuery, [506](#)
- mSPFile
 - gdcm::StreamImageWriter, [674](#)
- MultiframeGrayscaleByteSecondaryCaptureImageStorage
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- MultiframeGrayscaleWordSecondaryCaptureImageStorage
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- MultiframeSingleBitSecondaryCaptureImageStorage
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- MultiframeTrueColorSecondaryCaptureImageStorage
 - gdcm::MediaStorage, [485](#)
 - gdcm::UIDs, [741](#)
- N_ACTION_RQ
 - gdcm::network::DIMSE, [314](#)
- N_ACTION_RSP
 - gdcm::network::DIMSE, [314](#)
- N_CREATE_RQ
 - gdcm::network::DIMSE, [314](#)
- N_CREATE_RSP
 - gdcm::network::DIMSE, [314](#)
- N_DELETE_RQ
 - gdcm::network::DIMSE, [314](#)
- N_DELETE_RSP
 - gdcm::network::DIMSE, [314](#)
- N_EVENT_REPORT_RQ
 - gdcm::network::DIMSE, [313](#)
- N_EVENT_REPORT_RSP
 - gdcm::network::DIMSE, [313](#)
- N_GET_RQ
 - gdcm::network::DIMSE, [313](#)
- N_GET_RSP
 - gdcm::network::DIMSE, [314](#)
- N_SET_RQ
 - gdcm::network::DIMSE, [314](#)
- N_SET_RSP
 - gdcm::network::DIMSE, [314](#)
- NO
 - gdcm::Surface, [686](#)
- NO_COMPRESSION
 - vtkGDCMImageWriter, [837](#)
- NOMAGIC
 - gdcm::CSAHeader, [258](#)
- Name
 - gdcm::ModuleEntry, [501](#)
- NameField
 - gdcm::CSAElement, [255](#)
 - gdcm::PDBelement, [529](#)
- NeedByteSwap
 - gdcm::Bitmap, [210](#)
 - gdcm::ImageCodec, [415](#)
- NeedOverlayCleanup
 - gdcm::ImageCodec, [415](#)
- NegotiatedType
 - gdcm::TransferSyntax, [724](#)
- NestedMacroEntries
 - gdcm, [118](#)
- NestedModuleEntries
 - gdcm::NestedModuleEntries, [509](#)
- New
 - gdcm::Anonymizer, [151](#)
 - gdcm::MemberCommand, [491](#)
 - gdcm::Scanner, [616](#)
 - gdcm::SequenceOfFragments, [631](#)
 - gdcm::SequenceOfItems, [636](#)
 - gdcm::SimpleMemberCommand, [650](#)
 - vtkGDCMImageReader, [832](#)
 - vtkGDCMImageWriter, [838](#)
 - vtkGDCMMedicalImageProperties, [841](#)
 - vtkGDCMPolyDataReader, [843](#)
 - vtkGDCMPolyDataWriter, [846](#)
 - vtkGDCMTesting, [849](#)
 - vtkGDCMThreadedImageReader, [852](#)
 - vtkGDCMThreadedImageReader2, [854](#)
 - vtkImageColorViewer, [860](#)
 - vtkImageMapToColors16, [864](#)
 - vtkImageMapToWindowLevelColors2, [867](#)
 - vtkImagePlanarComponentsToComponents, [869](#)
 - vtkImageRGBToYBR, [871](#)
 - vtkImageYBRToRGB, [873](#)
 - vtkLookupTable16, [875](#)
 - vtkRTStructSetProperties, [878](#)
- NoElementsError
 - gdcm::Parser, [524](#)
- NoError
 - gdcm::Parser, [524](#)
- NoMemoryError
 - gdcm::Parser, [524](#)
- NoObject
 - gdcm::MediaStorage, [486](#)
- NoOfItemsField
 - gdcm::CSAElement, [256](#)
- Normalize
 - gdcm::DirectionCosines, [315](#)
- NuclearMedicineImageStorage

- gdcmm::MediaStorage, 485
- gdcmm::UIDs, 742
- NuclearMedicineImageStorageRetired
 - gdcmm::MediaStorage, 484
 - gdcmm::UIDs, 741
- NumberOfDimensions
 - gdcmm::Bitmap, 210
 - gdcmm::ImageCodec, 415
- NumberOfIconImages
 - vtkGDCMImageReader, 835
- NumberOfOverlays
 - vtkGDCMImageReader, 835
- NumberOfSurfaces
 - gdcmm::SurfaceWriter, 696
- OB
 - gdcmm::VR, 823
- OB_OW
 - gdcmm::VR, 823
- OBLIQUE
 - gdcmm::Orientation, 514
- OF
 - gdcmm::VR, 823
- OW
 - gdcmm::VR, 823
- Object
 - gdcmm::Object, 512
- ObjectEnd
 - gdcmm::MediaStorage, 486
- ObjectType
 - gdcmm::MediaStorage, 486
- Ofstream
 - gdcmm::Writer, 885
- op
 - gdcmm::SerieHelper::Rule, 610
- operator const char *
 - gdcmm::ConstCharWrapper, 248
 - gdcmm::Filename, 371
 - gdcmm::String, 677
- operator const double *
 - gdcmm::DirectionCosines, 315
- operator const std::vector< char > &
 - gdcmm::ByteValue, 222
- operator MStype
 - gdcmm::MediaStorage, 488
- operator ObjectType *
 - gdcmm::SmartPointer, 654
- operator PType
 - gdcmm::PhotometricInterpretation, 540
- operator ScalarType
 - gdcmm::PixelFormat, 544
- operator SwapCode::SwapCodeType
 - gdcmm::SwapCode, 698
- operator TStype
 - gdcmm::TransferSyntax, 726
 - gdcmm::UIDs, 752
- operator TypeType
 - gdcmm::Type, 730
- operator uint32_t
 - gdcmm::VL, 815
- operator UsageType
 - gdcmm::Usage, 806
- operator VMType
 - gdcmm::VM, 820
- operator VRType
 - gdcmm::VR, 824
- operator<
 - gdcmm::Attribute, 167
 - gdcmm::Attribute< Group, Element, TVR, VM::VM1 >, 173
 - gdcmm::CSAElement, 255
 - gdcmm::CSAHeaderDictEntry, 263
 - gdcmm::DataElement, 276
 - gdcmm::PrivateTag, 576
 - gdcmm::Tag, 712
- operator<<
 - gdcmm, 120–123
 - gdcmm::BasicOffsetTable, 203
 - gdcmm::CodeString, 239
 - gdcmm::CommandDataSet, 243
 - gdcmm::CSAElement, 255
 - gdcmm::CSAHeader, 260
 - gdcmm::CSAHeaderDict, 261
 - gdcmm::CSAHeaderDictEntry, 263
 - gdcmm::DataElement, 279
 - gdcmm::DataSet, 289
 - gdcmm::Dict, 303
 - gdcmm::DictEntry, 308
 - gdcmm::Dicts, 312
 - gdcmm::Directory, 318
 - gdcmm::File, 357
 - gdcmm::FileMetaInformation, 369
 - gdcmm::FileSet, 375
 - gdcmm::Fragment, 384
 - gdcmm::Global, 386
 - gdcmm::GroupDict, 388
 - gdcmm::IOD, 439
 - gdcmm::IODEntry, 441
 - gdcmm::IODs, 442
 - gdcmm::Item, 449
 - gdcmm::Macro, 478
 - gdcmm::Macros, 479
 - gdcmm::MediaStorage, 488
 - gdcmm::Module, 498
 - gdcmm::ModuleEntry, 501
 - gdcmm::Modules, 503
 - gdcmm::NestedModuleEntries, 509
 - gdcmm::Object, 512

- gdcmm::Orientation, 514
- gdcmm::PDBelement, 529
- gdcmm::PDHeader, 531
- gdcmm::PhotometricInterpretation, 540
- gdcmm::PixelFormat, 545
- gdcmm::Preamble, 561
- gdcmm::PrivateDict, 574
- gdcmm::PrivateTag, 576
- gdcmm::Scanner, 616
- gdcmm::Sorter, 661
- gdcmm::SwapCode, 698
- gdcmm::Table, 704
- gdcmm::Tag, 714
- gdcmm::TransferSyntax, 726
- gdcmm::Type, 731
- gdcmm::UI, 731
- gdcmm::Usage, 806
- gdcmm::Version, 814
- gdcmm::VL, 816
- gdcmm::VM, 820
- gdcmm::VR, 825
- operator<=
 - gdcmm::Tag, 712
- operator>>
 - gdcmm, 124
 - gdcmm::Tag, 714
- operator*
 - gdcmm::SmartPointer, 655
- operator()
 - gdcmm::DataSet, 288
 - gdcmm::Scanner::Itstr, 476
- operator++
 - gdcmm::VL, 815
- operator+=
 - gdcmm::VL, 815
- operator->
 - gdcmm::SmartPointer, 655
- operator=
 - gdcmm::BoxRegion, 215
 - gdcmm::ByteValue, 222
 - gdcmm::CSAElement, 255
 - gdcmm::DataElement, 276
 - gdcmm::DataSet, 288
 - gdcmm::Element< TVR, VM::VM1_n >, 329
 - gdcmm::network::UserInformation, 808
 - gdcmm::Object, 512
 - gdcmm::ParseException, 522
 - gdcmm::Preamble, 561
 - gdcmm::SequenceOfItems, 636
 - gdcmm::SmartPointer, 655
 - gdcmm::Tag, 712
- operator==
 - gdcmm, 123
 - gdcmm::Attribute, 167
 - gdcmm::Attribute< Group, Element, TVR, VM::VM1 >, 173
 - gdcmm::ByteValue, 222
 - gdcmm::CodeString, 239
 - gdcmm::CSAElement, 255
 - gdcmm::DataElement, 277
 - gdcmm::network::AbstractSyntax, 145
 - gdcmm::network::PresentationContextRQ, 567
 - gdcmm::network::TransferSyntaxSub, 727
 - gdcmm::PDBelement, 529
 - gdcmm::PixelFormat, 544
 - gdcmm::PresentationContext, 562
 - gdcmm::SequenceOfFragments, 631
 - gdcmm::SequenceOfItems, 636
 - gdcmm::Tag, 712
 - gdcmm::Value, 812
- OphthalmicPhotography16BitImageStorage
 - gdcmm::UIDs, 742
- OphthalmicPhotography8BitImageStorage
 - gdcmm::MediaStorage, 486
 - gdcmm::UIDs, 742
- OphthalmicTomographyImageStorage
 - gdcmm::MediaStorage, 486
 - gdcmm::UIDs, 742
- OrderFileList
 - gdcmm::SerieHelper, 640
- Orientation
 - gdcmm::Orientation, 514
- OrientationType
 - gdcmm::Orientation, 514
- Output
 - gdcmm::BitmapToBitmapFilter, 212
- OutputFormat
 - vtkImageMapToColors16, 865
- OutputTypes
 - gdcmm::DictConverter, 304
- Overlay
 - gdcmm::Overlay, 518
- OverlayImageActor
 - vtkImageColorViewer, 862
- OverlayType
 - gdcmm::Overlay, 517
- Overlays
 - gdcmm::Pixmap, 548
- PALETTE_COLOR
 - gdcmm::PhotometricInterpretation, 539
- PDF
 - gdcmm::MediaStorage, 486
- PETImageStorage
 - gdcmm::MediaStorage, 485
- PHILIPS
 - gdcmm::Dicts, 311
- PI_END

- gdcmm::PhotometricInterpretation, 539
- PN
 - gdcmm::VR, 823
- POINTS
 - gdcmm::Surface, 686
- PDBElement
 - gdcmm::PDBElement, 529
- PDBHeader
 - gdcmm::PDBHeader, 531
- PDFCodec
 - gdcmm::PDFCodec, 533
- PDataTFPDU
 - gdcmm::network::PDataTFPDU, 527
- PF
 - gdcmm::Bitmap, 210
 - gdcmm::ImageCodec, 415
- PGXCodec
 - gdcmm::PGXCodec, 537
- PI
 - gdcmm::Bitmap, 210
 - gdcmm::ImageCodec, 415
- PType
 - gdcmm::PhotometricInterpretation, 539
- PNComp
 - gdcmm, 118
- PNMCodec
 - gdcmm::PNMCodec, 559
- PVRGCodec
 - gdcmm::PVRGCodec, 580
- Pack
 - gdcmm::Unpacker12Bits, 804
- Padding
 - gdcmm::ApplicationEntity, 156
 - gdcmm::PersonName, 536
- Parent
 - gdcmm::Element< TVR, VM::VM1_2 >, 327
 - gdcmm::Element< TVR, VM::VM2_2n >, 331
 - gdcmm::Element< TVR, VM::VM2_n >, 332
 - gdcmm::Element< TVR, VM::VM3_3n >, 334
 - gdcmm::Element< TVR, VM::VM3_n >, 335
- Parse
 - gdcmm::Parser, 524
- ParseBuffer
 - gdcmm::Parser, 525
- ParseCertificateFile
 - gdcmm::CryptographicMessageSyntax, 251
- ParseDateTime
 - gdcmm::System, 702, 703
- ParseDump
 - gdcmm::ASN1, 161
- ParseDumpFile
 - gdcmm::ASN1, 161
- ParseException
 - gdcmm::ParseException, 522
- ParseKeyFile
 - gdcmm::CryptographicMessageSyntax, 251
- Parser
 - gdcmm::Parser, 524
- PassAlphaToOutput
 - vtkImageMapToColors16, 865
- Patient
 - gdcmm::Patient, 525
- PatientRootQueryRetrieveInformationModelFIND
 - gdcmm::UIDs, 743
- PatientRootQueryRetrieveInformationModelGET
 - gdcmm::UIDs, 743
- PatientRootQueryRetrieveInformationModelMOVE
 - gdcmm::UIDs, 743
- PatientStudyOnlyQueryRetrieveInformationModelFIND-Retired
 - gdcmm::UIDs, 743
- PatientStudyOnlyQueryRetrieveInformationModelGET-Retired
 - gdcmm::UIDs, 743
- PatientStudyOnlyQueryRetrieveInformationModelMOVE-Retired
 - gdcmm::UIDs, 743
- PerformAction
 - gdcmm::network::ULAction, 754
 - gdcmm::network::ULActionAA1, 755
 - gdcmm::network::ULActionAA2, 756
 - gdcmm::network::ULActionAA3, 758
 - gdcmm::network::ULActionAA4, 759
 - gdcmm::network::ULActionAA5, 760
 - gdcmm::network::ULActionAA6, 761
 - gdcmm::network::ULActionAA7, 762
 - gdcmm::network::ULActionAA8, 763
 - gdcmm::network::ULActionAE1, 765
 - gdcmm::network::ULActionAE2, 766
 - gdcmm::network::ULActionAE3, 767
 - gdcmm::network::ULActionAE4, 768
 - gdcmm::network::ULActionAE5, 769
 - gdcmm::network::ULActionAE6, 770
 - gdcmm::network::ULActionAE7, 772
 - gdcmm::network::ULActionAE8, 773
 - gdcmm::network::ULActionAR1, 774
 - gdcmm::network::ULActionAR10, 775
 - gdcmm::network::ULActionAR2, 776
 - gdcmm::network::ULActionAR3, 777
 - gdcmm::network::ULActionAR4, 779
 - gdcmm::network::ULActionAR5, 780
 - gdcmm::network::ULActionAR6, 781
 - gdcmm::network::ULActionAR7, 782
 - gdcmm::network::ULActionAR8, 783
 - gdcmm::network::ULActionAR9, 784
 - gdcmm::network::ULActionDT1, 786
 - gdcmm::network::ULActionDT2, 787
- Philips3D

- gdcm::MediaStorage, [485](#)
- PhilipsPrivateMRSyntheticImageStorage
 - gdcm::MediaStorage, [486](#)
- PhotometricInterpretation
 - gdcm::PhotometricInterpretation, [539](#)
- PixelData
 - gdcm::Bitmap, [210](#)
 - gdcm::PixmapReader, [552](#)
 - gdcm::PixmapWriter, [557](#)
- PixelFormat
 - gdcm::PixelFormat, [542](#)
- Pixmap
 - gdcm::Pixmap, [547](#)
- PixmapReader
 - gdcm::Bitmap, [210](#)
 - gdcm::PixmapReader, [551](#)
- PixmapToPixmapFilter
 - gdcm::PixmapToPixmapFilter, [553](#)
- PixmapWriter
 - gdcm::PixmapWriter, [556](#)
- PlanarConfiguration
 - gdcm::Bitmap, [210](#)
 - gdcm::ImageCodec, [415](#)
 - vtkGDCMImageReader, [835](#)
- pointer
 - gdcm::CodeString, [238](#)
 - gdcm::LO, [471](#)
 - gdcm::String, [676](#)
- PositronEmissionTomographyImageStorage
 - gdcm::UIDs, [743](#)
- Preamble
 - gdcm::Preamble, [560](#)
- PrepareWrite
 - gdcm::PixmapWriter, [556](#)
 - gdcm::SegmentWriter, [627](#)
 - gdcm::SurfaceWriter, [696](#)
- PrepareWritePointMacro
 - gdcm::SurfaceWriter, [696](#)
- Prepend
 - gdcm::Global, [386](#)
- PresentationLUTSOPClass
 - gdcm::UIDs, [741](#)
- PresentationContext
 - gdcm::PresentationContext, [562](#)
- PresentationContextAC
 - gdcm::network::PresentationContextAC, [563](#)
- PresentationContextArrayType
 - gdcm::network::AAssociateRQPDU, [141](#)
 - gdcm::PresentationContextGenerator, [565](#)
- PresentationContextGenerator
 - gdcm::PresentationContextGenerator, [565](#)
- PresentationContextRQ
 - gdcm::network::PresentationContextRQ, [567](#)
- PresentationDataValue
 - gdcm::network::PresentationDataValue, [569](#)
- PrimitiveData
 - gdcm::MeshPrimitive, [495](#)
- PrimitiveType
 - gdcm::MeshPrimitive, [495](#)
- PrimitivesData
 - gdcm::MeshPrimitive, [494](#)
- Print
 - gdcm::ApplicationEntity, [156](#)
 - gdcm::Attribute, [167](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, [173](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [180](#)
 - gdcm::BaseRootQuery, [197](#)
 - gdcm::Bitmap, [208](#)
 - gdcm::BoxRegion, [215](#)
 - gdcm::ByteValue, [222](#)
 - gdcm::CSAHeader, [259](#)
 - gdcm::Curve, [269](#)
 - gdcm::DataSet, [288](#)
 - gdcm::DictPrinter, [310](#)
 - gdcm::DirectionCosines, [315](#)
 - gdcm::Directory, [318](#)
 - gdcm::Element, [325](#)
 - gdcm::Element< TVR, VM::VM1_n >, [329](#)
 - gdcm::Element< VR::AS, VM::VM5 >, [336](#)
 - gdcm::Event, [346](#)
 - gdcm::Image, [396](#)
 - gdcm::LookupTable, [475](#)
 - gdcm::network::AAAbortPDU, [134](#)
 - gdcm::network::AAssociateACPDU, [137](#)
 - gdcm::network::AAssociateRJPDPU, [139](#)
 - gdcm::network::AAssociateRQPDU, [142](#)
 - gdcm::network::AbstractSyntax, [145](#)
 - gdcm::network::ApplicationContext, [154](#)
 - gdcm::network::AReleaseRPPDU, [158](#)
 - gdcm::network::AReleaseRQPDU, [159](#)
 - gdcm::network::AsynchronousOperationsWindow-Sub, [162](#)
 - gdcm::network::BasePDU, [194](#)
 - gdcm::network::ImplementationClassUIDSub, [433](#)
 - gdcm::network::ImplementationVersionNameSub, [434](#)
 - gdcm::network::MaximumLengthSub, [480](#)
 - gdcm::network::PDataTFPDU, [527](#)
 - gdcm::network::PresentationContextAC, [563](#)
 - gdcm::network::PresentationContextRQ, [568](#)
 - gdcm::network::PresentationDataValue, [569](#)
 - gdcm::network::RoleSelectionSub, [609](#)
 - gdcm::network::ServiceClassApplicationInformation, [641](#)
 - gdcm::network::SOPClassExtendedNegociationSub, [656](#)

- gdcm::network::TransferSyntaxSub, [727](#)
- gdcm::network::UserInformation, [808](#)
- gdcm::Object, [512](#)
- gdcm::Orientation, [514](#)
- gdcm::Overlay, [519](#)
- gdcm::PDBHeader, [531](#)
- gdcm::PersonName, [535](#)
- gdcm::PixelFormat, [544](#)
- gdcm::Pixmap, [548](#)
- gdcm::Preamble, [561](#)
- gdcm::PresentationContext, [562](#)
- gdcm::Printer, [572](#)
- gdcm::Region, [602](#)
- gdcm::Scanner, [616](#)
- gdcm::SegmentedPaletteColorLookupTable, [622](#)
- gdcm::SequenceOfFragments, [631](#)
- gdcm::SequenceOfItems, [636](#)
- gdcm::Sorter, [660](#)
- gdcm::TagPath, [715](#)
- gdcm::Testing, [719](#)
- gdcm::Version, [813](#)
- PrintJobSOPClass
 - gdcm::UIDs, [740](#)
- PrintQueueManagementSOPClassRetired
 - gdcm::UIDs, [741](#)
- PrintQueueSOPInstanceRetired
 - gdcm::UIDs, [741](#)
- PrintASCII
 - gdcm::ByteValue, [222](#)
- PrintAsPipeSeparatedString
 - gdcm::Tag, [712](#)
- PrintDataElement
 - gdcm::Printer, [572](#)
- PrintDataElement2
 - gdcm::DictPrinter, [310](#)
- PrintDataSet
 - gdcm::Printer, [572](#)
- PrintDataSet2
 - gdcm::DictPrinter, [310](#)
- PrintGroupLength
 - gdcm::ByteValue, [222](#)
- PrintHex
 - gdcm::ByteValue, [222](#)
- PrintSQ
 - gdcm::Printer, [572](#)
- PrintSelf
 - vtkGDCMImageReader, [832](#)
 - vtkGDCMImageWriter, [838](#)
 - vtkGDCMMedicalImageProperties, [841](#)
 - vtkGDCMPolyDataReader, [843](#)
 - vtkGDCMPolyDataWriter, [846](#)
 - vtkGDCMTesting, [849](#)
 - vtkGDCMThreadedImageReader, [852](#)
 - vtkGDCMThreadedImageReader2, [854](#)
 - vtkImageColorViewer, [860](#)
 - vtkImageMapToColors16, [864](#)
 - vtkImageMapToWindowLevelColors2, [867](#)
 - vtkImagePlanarComponentsToComponents, [869](#)
 - vtkImageRGBToYBR, [871](#)
 - vtkImageYBRToRGB, [873](#)
 - vtkLookupTable16, [875](#)
 - vtkRTStructSetProperties, [879](#)
- PrintStyle
 - gdcm::Printer, [573](#)
- PrintStyles
 - gdcm::Printer, [572](#)
- PrintTable
 - gdcm::network::ULTransitionTable, [798](#)
- PrintXML
 - gdcm::PrivateDict, [574](#)
- Printer
 - gdcm::Printer, [572](#)
- PrinterConfigurationRetrievalSOPClass
 - gdcm::UIDs, [740](#)
- PrinterConfigurationRetrievalSOPInstance
 - gdcm::UIDs, [740](#)
- PrinterSOPClass
 - gdcm::UIDs, [740](#)
- PrinterSOPInstance
 - gdcm::UIDs, [740](#)
- PrivateDict
 - gdcm::PrivateDict, [574](#)
- PrivateTag
 - gdcm::PrivateTag, [576](#)
- ProceduralEventLoggingSOPClass
 - gdcm::UIDs, [740](#)
- ProceduralEventLoggingSOPInstance
 - gdcm::UIDs, [740](#)
- ProcedureLogStorage
 - gdcm::UIDs, [742](#)
- Process
 - gdcm::Parser, [525](#)
- ProcessDataSet
 - gdcm::FileExplicitFilter, [364](#)
- ProcessPublicTag
 - gdcm::Scanner, [616](#)
- ProduceCharacterSetDataElement
 - gdcm::QueryFactory, [584](#)
- ProduceQuery
 - gdcm::QueryFactory, [585](#)
- ProductCharacteristicsQuerySOPClass
 - gdcm::UIDs, [744](#)
- ProgressEvent
 - gdcm::ProgressEvent, [578](#)
- PropertyCategory
 - gdcm::Segment, [620](#)
- PropertyType
 - gdcm::Segment, [620](#)

- PseudoColorSoftcopyPresentationStateStorageSOP-
Class
gdcm::UIDs, [742](#)
- PullPrintRequestSOPClassRetired
gdcm::UIDs, [741](#)
- PullStoredPrintManagementMetaSOPClassRetired
gdcm::UIDs, [741](#)
- Push
gdcm::TagPath, [715](#)
- PushBackFile
vtkGDCMMedicalImageProperties, [841](#)
- PythonFilter
gdcm::PythonFilter, [581](#)
- Quality
gdcm::JPEGCodec, [463](#)
- QueryFactory
gdcm::BaseRootQuery, [198](#)
gdcm::FindPatientRootQuery, [379](#)
gdcm::FindStudyRootQuery, [381](#)
gdcm::MovePatientRootQuery, [505](#)
gdcm::MoveStudyRootQuery, [507](#)
- RED
gdcm::LookupTable, [474](#)
- RFC2557MIMEencapsulation
gdcm::UIDs, [739](#)
- RGB
gdcm::PhotometricInterpretation, [539](#)
- RLE_COMPRESSION
vtkGDCMImageWriter, [837](#)
- RLELossless
gdcm::TransferSyntax, [725](#)
gdcm::UIDs, [739](#)
- ROI
gdcm::Overlay, [517](#)
- RTBeamsDeliveryInstructionStorageSupplement74-
FrozenDraft
gdcm::UIDs, [743](#)
- RTBeamsTreatmentRecordStorage
gdcm::UIDs, [743](#)
- RTBrachyTreatmentRecordStorage
gdcm::UIDs, [743](#)
- RTConventionalMachineVerificationSupplement74Frozen-
Draft
gdcm::UIDs, [743](#)
- RTDoseStorage
gdcm::MediaStorage, [485](#)
gdcm::UIDs, [743](#)
- RTImageStorage
gdcm::MediaStorage, [485](#)
gdcm::UIDs, [743](#)
- RTIonBeamsTreatmentRecordStorage
gdcm::MediaStorage, [486](#)
gdcm::UIDs, [743](#)
- RTIonMachineVerificationSupplement74FrozenDraft
gdcm::UIDs, [743](#)
- RTIonPlanStorage
gdcm::MediaStorage, [486](#)
gdcm::UIDs, [743](#)
- RTPlanStorage
gdcm::MediaStorage, [485](#)
gdcm::UIDs, [743](#)
- RTStructureSetStorage
gdcm::MediaStorage, [485](#)
gdcm::UIDs, [743](#)
- RTTreatmentSummaryRecordStorage
gdcm::MediaStorage, [486](#)
gdcm::UIDs, [743](#)
- RAWCodec
gdcm::RAWCodec, [594](#)
- README.txt, [1170](#)
- RGB2YBR
gdcm::ImageChangePhotometricInterpretation, [402](#)
- RGBPixelsToRGBPlanes
gdcm::ImageChangePlanarConfiguration, [405](#)
- RGBPlanesToRGBPixels
gdcm::ImageChangePlanarConfiguration, [405](#)
- RGBToRecommendedDisplayCIELab
gdcm::SurfaceHelper, [691](#), [692](#)
- RGBToRecommendedDisplayGrayscale
gdcm::SurfaceHelper, [692](#)
- RLECodec
gdcm::RLECodec, [607](#)
- RTStructSetProperties
vtkGDCMPolyDataReader, [844](#)
vtkGDCMPolyDataWriter, [847](#)
- RawDataStorage
gdcm::MediaStorage, [485](#)
gdcm::UIDs, [742](#)
- Read
gdcm::BasicOffsetTable, [202](#)
gdcm::ByteValue, [222](#)
gdcm::CommandDataSet, [243](#)
gdcm::CP246ExplicitDataElement, [249](#)
gdcm::CSAHeader, [260](#)
gdcm::DataElement, [277](#)
gdcm::DataSet, [288](#)
gdcm::Element, [325](#)
gdcm::Element< TVR, VM::VM1_n >, [329](#)
gdcm::EncodingImplementation< VR::VRASCII >, [341](#)
gdcm::EncodingImplementation< VR::VRBINARY >, [342](#)
gdcm::ExplicitDataElement, [351](#)
gdcm::ExplicitImplicitDataElement, [353](#)
gdcm::File, [357](#)
gdcm::FileMetaInformation, [368](#)
gdcm::Fragment, [383](#)

- gdcm::ImageReader, [424](#)
- gdcm::ImageRegionReader, [427](#)
- gdcm::ImplicitDataElement, [436](#)
- gdcm::Item, [449](#)
- gdcm::network::AAAbortPDU, [134](#)
- gdcm::network::AAAssociateACPDU, [137](#)
- gdcm::network::AAAssociateRJPDU, [139](#)
- gdcm::network::AAAssociateRQPDU, [142](#)
- gdcm::network::AbstractSyntax, [145](#)
- gdcm::network::ApplicationContext, [154](#)
- gdcm::network::AReleaseRPPDU, [158](#)
- gdcm::network::AReleaseRQPDU, [159](#)
- gdcm::network::AsynchronousOperationsWindowSub, [162](#)
- gdcm::network::BasePDU, [194](#)
- gdcm::network::ImplementationClassUIDSub, [433](#)
- gdcm::network::ImplementationVersionNameSub, [434](#)
- gdcm::network::MaximumLengthSub, [480](#)
- gdcm::network::PDataTFPDU, [527](#)
- gdcm::network::PresentationContextAC, [563](#)
- gdcm::network::PresentationContextRQ, [568](#)
- gdcm::network::PresentationDataValue, [569](#)
- gdcm::network::RoleSelectionSub, [609](#)
- gdcm::network::ServiceClassApplicationInformation, [641](#)
- gdcm::network::SOPClassExtendedNegociationSub, [656](#)
- gdcm::network::TransferSyntaxSub, [727](#)
- gdcm::network::UserInformation, [808](#)
- gdcm::PGXCodec, [538](#)
- gdcm::PixmapReader, [551](#)
- gdcm::PNMCodec, [559](#)
- gdcm::Preamble, [561](#)
- gdcm::Reader, [599](#)
- gdcm::SegmentReader, [625](#)
- gdcm::SequenceOfFragments, [631](#)
- gdcm::SequenceOfItems, [636](#)
- gdcm::StreamImageReader, [668](#)
- gdcm::SurfaceReader, [694](#)
- gdcm::TableReader, [707](#)
- gdcm::Tag, [713](#)
- gdcm::UNExplicitDataElement, [801](#)
- gdcm::UNExplicitImplicitDataElement, [803](#)
- gdcm::ValueIO, [812](#)
- gdcm::VL, [815](#)
- gdcm::VR, [824](#)
- gdcm::VR16ExplicitDataElement, [826](#)
- gdcm::VRVLSize< 0 >, [828](#)
- gdcm::VRVLSize< 1 >, [828](#)
- Read16
 - gdcm::VL, [816](#)
- ReadACRNEAImage
 - gdcm::ImageReader, [425](#)
- gdcm::PixmapReader, [551](#)
- ReadBacktrack
 - gdcm::Fragment, [383](#)
- ReadCompat
 - gdcm::FileMetaInformation, [368](#)
- ReadCompatInternal
 - gdcm::FileMetaInformation, [368](#)
- ReadComputeLength
 - gdcm::EncodingImplementation< VR::VRASCII >, [341](#)
 - gdcm::EncodingImplementation< VR::VRBINARY >, [342](#)
- ReadDataSet
 - gdcm::Reader, [599](#)
- ReadFiles
 - vtkGDCMThreadedImageReader, [852](#)
- ReadFromCommaSeparatedString
 - gdcm::PrivateTag, [576](#)
 - gdcm::Tag, [713](#)
- ReadFromPipeSeparatedString
 - gdcm::Tag, [713](#)
- ReadImage
 - gdcm::ImageReader, [425](#)
 - gdcm::PixmapReader, [551](#)
- ReadImageInformation
 - gdcm::StreamImageReader, [668](#)
- ReadImageInternal
 - gdcm::PixmapReader, [551](#)
- ReadInformation
 - gdcm::ImageRegionReader, [427](#)
- ReadInto
 - gdcm::network::PDataTFPDU, [527](#)
 - gdcm::network::PresentationDataValue, [569](#)
- ReadIntoBuffer
 - gdcm::ImageRegionReader, [427](#)
- ReadMetaInformation
 - gdcm::Reader, [599](#)
- ReadNested
 - gdcm::DataSet, [288](#)
- ReadNoSwap
 - gdcm::EncodingImplementation< VR::VRASCII >, [342](#)
 - gdcm::EncodingImplementation< VR::VRBINARY >, [343](#)
- ReadOrSkip
 - gdcm::DataElement, [277](#)
- ReadPointMacro
 - gdcm::SurfaceReader, [694](#)
- ReadPreValue
 - gdcm::CP246ExplicitDataElement, [250](#)
 - gdcm::DataElement, [277](#)
 - gdcm::ExplicitDataElement, [351](#)
 - gdcm::ExplicitImplicitDataElement, [353](#)
 - gdcm::Fragment, [383](#)

- gdcm::ImplicitDataElement, [436](#)
- gdcm::SequenceOfFragments, [631](#)
- gdcm::UNExplicitDataElement, [802](#)
- gdcm::UNExplicitImplicitDataElement, [804](#)
- gdcm::VR16ExplicitDataElement, [827](#)
- ReadPreamble
 - gdcm::Reader, [599](#)
- ReadSegment
 - gdcm::SegmentReader, [625](#)
- ReadSegments
 - gdcm::SegmentReader, [625](#)
- ReadSelectedTags
 - gdcm::DataSet, [288](#)
 - gdcm::Reader, [599](#)
- ReadSelectedTagsWithLength
 - gdcm::DataSet, [288](#)
- ReadSurface
 - gdcm::SurfaceReader, [694](#)
- ReadSurfaces
 - gdcm::SurfaceReader, [694](#)
- ReadUpToTag
 - gdcm::DataSet, [288](#)
 - gdcm::Reader, [599](#)
- ReadUpToTagWithLength
 - gdcm::DataSet, [288](#)
- ReadVM
 - gdcm::DictConverter, [305](#)
- ReadVR
 - gdcm::DictConverter, [305](#)
- ReadValue
 - gdcm::CP246ExplicitDataElement, [250](#)
 - gdcm::DataElement, [277](#)
 - gdcm::ExplicitDataElement, [351](#)
 - gdcm::ExplicitImplicitDataElement, [353](#)
 - gdcm::Fragment, [383](#)
 - gdcm::ImplicitDataElement, [436](#)
 - gdcm::SequenceOfFragments, [631](#)
 - gdcm::UNExplicitDataElement, [802](#)
 - gdcm::UNExplicitImplicitDataElement, [804](#)
 - gdcm::VR16ExplicitDataElement, [827](#)
- ReadWithLength
 - gdcm::CP246ExplicitDataElement, [250](#)
 - gdcm::DataElement, [277](#)
 - gdcm::DataSet, [288](#)
 - gdcm::ExplicitDataElement, [351](#)
 - gdcm::ExplicitImplicitDataElement, [353](#)
 - gdcm::ImplicitDataElement, [436](#)
 - gdcm::UNExplicitDataElement, [802](#)
 - gdcm::VR16ExplicitDataElement, [827](#)
- Reader
 - gdcm::Reader, [598](#)
- Readuint16
 - gdcm::DictConverter, [305](#)
- RealWorldValueMappingStorage
 - gdcm::UIDs, [742](#)
- RecommendedDisplayCIELabToRGB
 - gdcm::SurfaceHelper, [690](#), [691](#)
- RecurseDataSet
 - gdcm::Anonymizer, [151](#)
- red
 - gdcm::terminal, [131](#)
- reference
 - gdcm::CodeString, [238](#)
 - gdcm::LO, [471](#)
 - gdcm::String, [676](#)
- ReferenceFrameOfReferenceUID
 - vtkRTStructSetProperties, [879](#)
- ReferenceSeriesInstanceUID
 - vtkRTStructSetProperties, [879](#)
- ReferencedColorPrintManagementMetaSOPClassRetired
 - gdcm::UIDs, [740](#)
- ReferencedGrayscalePrintManagementMetaSOPClassRetired
 - gdcm::UIDs, [740](#)
- ReferencedImageBoxSOPClassRetired
 - gdcm::UIDs, [740](#)
- Region
 - gdcm::Region, [601](#)
- Register
 - gdcm::Object, [512](#)
- Remove
 - gdcm::Anonymizer, [151](#)
 - gdcm::DataSet, [288](#)
 - gdcm::FileAnonymizer, [359](#)
 - gdcm::Preamble, [561](#)
- RemoveAllObservers
 - gdcm::Subject, [682](#)
- RemoveDictEntry
 - gdcm::PrivateDict, [574](#)
- RemoveFile
 - gdcm::System, [703](#)
- RemoveGroupLength
 - gdcm::Anonymizer, [151](#)
- RemoveObserver
 - gdcm::Subject, [682](#)
- RemoveOverlay
 - gdcm::Pixmap, [548](#)
- RemovePrivateTags
 - gdcm::Anonymizer, [151](#)
- RemoveRetired
 - gdcm::Anonymizer, [152](#)
- Render
 - vtkImageColorViewer, [860](#)
- RenderWindow
 - vtkImageColorViewer, [862](#)
- Renderer
 - vtkImageColorViewer, [862](#)
- Replace

- gdcmm::Anonymizer, [152](#)
- gdcmm::CommandDataSet, [243](#)
- gdcmm::DataSet, [288](#)
- gdcmm::FileAnonymizer, [359](#)
- gdcmm::FileMetaInformation, [368](#)
- ReplaceEmpty
 - gdcmm::DataSet, [288](#)
- RequestData
 - vtkGDCMPolyDataReader, [843](#)
 - vtkImageMapToColors16, [865](#)
 - vtkImageMapToWindowLevelColors2, [867](#)
 - vtkImagePlanarComponentsToComponents, [869](#)
- RequestData_HemodynamicWaveformStorage
 - vtkGDCMPolyDataReader, [843](#)
- RequestData_RTStructureSetStorage
 - vtkGDCMPolyDataReader, [843](#)
- RequestDataCompat
 - vtkGDCMImageReader, [832](#)
 - vtkGDCMThreadedImageReader, [852](#)
- RequestInformation
 - vtkGDCMPolyDataReader, [844](#)
 - vtkGDCMThreadedImageReader2, [854](#)
 - vtkImageMapToColors16, [865](#)
 - vtkImageMapToWindowLevelColors2, [867](#)
- RequestInformation_HemodynamicWaveformStorage
 - vtkGDCMPolyDataReader, [844](#)
- RequestInformation_RTStructureSetStorage
 - vtkGDCMPolyDataReader, [844](#)
- RequestInformationCompat
 - vtkGDCMImageReader, [832](#)
- RequestPaddedCompositePixelCode
 - gdcmm::ImageCodec, [415](#)
- RequestPlanarConfiguration
 - gdcmm::ImageCodec, [415](#)
- Rescale
 - gdcmm::Rescaler, [604](#)
- RescaleFunctionIntoBestFit
 - gdcmm::Rescaler, [604](#)
- Rescaler
 - gdcmm::Rescaler, [604](#)
- reset
 - gdcmm::terminal, [131](#)
- ResetHandledDataSet
 - gdcmm::network::ULConnectionCallback, [792](#)
- RetrieveSOPInstanceUIDFromIndex
 - gdcmm::DirectoryHelper, [320](#)
- RetrieveSOPInstanceUIDFromZPosition
 - gdcmm::DirectoryHelper, [320](#)
- reverse
 - gdcmm::terminal, [131](#)
- reverse_iterator
 - gdcmm::CodeString, [238](#)
 - gdcmm::LO, [471](#)
 - gdcmm::String, [676](#)
- RoleSelectionSub
 - gdcmm::network::RoleSelectionSub, [609](#)
- SAGITTAL
 - gdcmm::Orientation, [514](#)
- SH
 - gdcmm::VR, [823](#)
- SIEMENS
 - gdcmm::Dicts, [311](#)
- SINGLEBIT
 - gdcmm::PixelFormat, [542](#)
- SL
 - gdcmm::VR, [823](#)
- SLICE_ORIENTATION_XY
 - vtkImageColorViewer, [859](#)
- SLICE_ORIENTATION_XZ
 - vtkImageColorViewer, [859](#)
- SLICE_ORIENTATION_YZ
 - vtkImageColorViewer, [859](#)
- SPM2AVG152PDFrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2AVG152T1FrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2AVG152T2FrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2AVG305T1FrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2BRAINMASKFrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2CSFFFrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2EPIFrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2FILT1FrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2GRAYFrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2PDFrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2PETFrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2SINGLESUBJT1FrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2SPECTFrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2T1FrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2T2FrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2TRANSMFrameofReference
 - gdcmm::UIDs, [739](#)
- SPM2WHITEFrameofReference
 - gdcmm::UIDs, [739](#)
- SQ

- gdcm::VR, [823](#)
- SS
 - gdcm::VR, [823](#)
- ST
 - gdcm::VR, [823](#)
- STATES_END
 - gdcm::Surface, [686](#)
- SURFACE
 - gdcm::Surface, [686](#)
- SV10
 - gdcm::CSAHeader, [258](#)
- SHA1
 - gdcm::SHA1, [647](#)
- SHComp
 - gdcm, [118](#)
- SOPClassExtendedNegociationSub
 - gdcm::network::SOPClassExtendedNegociationSub, [656](#)
- SOPInstanceUID
 - vtkRTStructSetProperties, [880](#)
- STATES
 - gdcm::Surface, [686](#)
- STComp
 - gdcm, [118](#)
- ScalarType
 - gdcm::PixelFormat, [542](#)
- Scale
 - vtkGDCMImageReader, [835](#)
- Scan
 - gdcm::Scanner, [616](#)
- Scanner
 - gdcm::Scanner, [614](#)
- SecondaryCaptureImageStorage
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- Segment
 - gdcm::Segment, [619](#)
- SegmentAlgorithmName
 - gdcm::Segment, [620](#)
- SegmentAlgorithmType
 - gdcm::Segment, [620](#)
- SegmentDescription
 - gdcm::Segment, [620](#)
- SegmentLabel
 - gdcm::Segment, [620](#)
- SegmentMap
 - gdcm::SegmentReader, [624](#)
- SegmentNumber
 - gdcm::Segment, [620](#)
- SegmentReader
 - gdcm::SegmentReader, [624](#)
- SegmentVector
 - gdcm::SegmentReader, [624](#)
 - gdcm::SegmentWriter, [627](#)
- SegmentWriter
 - gdcm::SegmentWriter, [627](#)
- Segmentation
 - gdcm::MediaStorage, [486](#)
- SegmentationStorage
 - gdcm::MediaStorage, [486](#)
 - gdcm::UIDs, [742](#)
- SegmentedPaletteColorLookupTable
 - gdcm::SegmentedPaletteColorLookupTable, [622](#)
- Segments
 - gdcm::SegmentReader, [625](#)
 - gdcm::SegmentWriter, [627](#)
- Selection
 - gdcm::Sorter, [661](#)
- SelectionMap
 - gdcm::Sorter, [659](#)
- Self
 - gdcm::AnonymizeEvent, [147](#)
 - gdcm::DataEvent, [281](#)
 - gdcm::DataSetEvent, [290](#)
 - gdcm::MemberCommand, [490](#)
 - gdcm::ProgressEvent, [578](#)
 - gdcm::SimpleMemberCommand, [649](#)
- SendEcho
 - gdcm::network::ULConnectionManager, [796](#)
 - gdcm::ServiceClassUser, [644](#)
- SendFind
 - gdcm::network::ULConnectionManager, [796](#)
 - gdcm::ServiceClassUser, [644](#)
- SendMove
 - gdcm::network::ULConnectionManager, [796](#)
 - gdcm::ServiceClassUser, [644](#)
- SendStore
 - gdcm::network::ULConnectionManager, [796](#)
 - gdcm::ServiceClassUser, [645](#)
- Separator
 - gdcm::ApplicationEntity, [156](#)
 - gdcm::PersonName, [536](#)
- SequenceLengthField
 - gdcm::SequenceOfItems, [637](#)
- SequenceOfFragments
 - gdcm::SequenceOfFragments, [630](#)
- SequenceOfItems
 - gdcm::SequenceOfItems, [635](#)
- SerieHelper
 - gdcm::SerieHelper, [639](#)
- SerieRestrictions
 - gdcm::SerieHelper, [639](#)
- Series
 - gdcm::Series, [641](#)
- SeriesInstanceUID
 - vtkRTStructSetProperties, [880](#)
- ServiceClassApplicationInformation

- gdcmm::network::ServiceClassApplicationInformation, 641
- ServiceClassUser
 - gdcmm::ServiceClassUser, 644
- Set
 - gdcmm::Attribute, 168
 - gdcmm::Attribute< Group, Element, TVR, VM::VM1 >, 173
 - gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >, 180
 - gdcmm::Element, 325
 - gdcmm::Element< TVR, VM::VM1_n >, 329
- SetAETitle
 - gdcmm::ServiceClassUser, 645
- SetAbstractSyntax
 - gdcmm::network::PresentationContextRQ, 568
 - gdcmm::PresentationContext, 562
- SetAlgorithmFamily
 - gdcmm::Surface, 688
- SetAlgorithmName
 - gdcmm::Surface, 688
- SetAlgorithmVersion
 - gdcmm::Surface, 688
- SetAnatomicRegion
 - gdcmm::Segment, 620
- SetArray
 - gdcmm::Element< TVR, VM::VM1_n >, 329
- SetAxisOfRotation
 - gdcmm::Surface, 688
- SetBitPosition
 - gdcmm::Overlay, 520
- SetBitSample
 - gdcmm::JPEGCodec, 463
- SetBitsAllocated
 - gdcmm::Overlay, 520
 - gdcmm::PixelFormat, 544
- SetBitsStored
 - gdcmm::PixelFormat, 544
- SetBlob
 - gdcmm::ApplicationEntity, 156
 - gdcmm::network::PresentationDataValue, 569
 - gdcmm::PersonName, 535
- SetBlueLUT
 - gdcmm::LookupTable, 475
- SetBufferLength
 - gdcmm::JPEGLSCCodec, 466
 - gdcmm::PNMCodec, 559
 - gdcmm::RLECodec, 608
- SetByteSwapTag
 - gdcmm::ByteSwapFilter, 218
- SetByteValue
 - gdcmm::Attribute, 168
 - gdcmm::Attribute< Group, Element, TVR, VM::VM1 >, 173
- gdcmm::Attribute< Group, Element, TVR, VM::VM1_n >, 180
- gdcmm::CSAElement, 255
- gdcmm::DataElement, 277
- SetByteValueNoSwap
 - gdcmm::Attribute, 168
 - gdcmm::Attribute< Group, Element, TVR, VM::VM1 >, 173
- SetCallbackFunction
 - gdcmm::MemberCommand, 491
 - gdcmm::SimpleMemberCommand, 650
- SetCalledAETitle
 - gdcmm::network::AAAssociateACPDU, 137
 - gdcmm::network::AAAssociateRQPDU, 142
 - gdcmm::ServiceClassUser, 645
- SetCallingAETitle
 - gdcmm::network::AAAssociateACPDU, 137
 - gdcmm::network::AAAssociateRQPDU, 142
- SetCenterOfRotation
 - gdcmm::Surface, 688
- SetChangePrivateTags
 - gdcmm::FileExplicitFilter, 364
- SetCheckFileMetaInformation
 - gdcmm::Writer, 884
- SetCipherType
 - gdcmm::CryptographicMessageSyntax, 251
- SetColor
 - gdcmm::Printer, 573
- SetColorLevel
 - vtkImageColorViewer, 860
- SetColorWindow
 - vtkImageColorViewer, 860
- SetColumns
 - gdcmm::Bitmap, 208
 - gdcmm::Overlay, 520
- SetCommand
 - gdcmm::network::PresentationDataValue, 569
- SetComponents
 - gdcmm::PersonName, 535
- SetCompressIconImage
 - gdcmm::ImageChangeTransferSyntax, 408
- SetComputeZSpacing
 - gdcmm::IPPSorter, 445
- SetCoordinateStartValue
 - gdcmm::Curve, 269
- SetCoordinateStepValue
 - gdcmm::Curve, 270
- SetCryptographicMessageSyntax
 - gdcmm::Anonymizer, 152
- SetCurve
 - gdcmm::Curve, 270
 - vtkGDCMImageReader, 832
- SetCurveDataDescriptor
 - gdcmm::Curve, 270

- SetCurveDescription
 - gdcm::Curve, [270](#)
- SetData
 - gdcm::DataEvent, [282](#)
- SetDataElement
 - gdcm::Bitmap, [208](#)
- SetDataSet
 - gdcm::File, [357](#)
 - gdcm::network::PresentationDataValue, [569](#)
- SetDataSetTransferSyntax
 - gdcm::FileMetaInformation, [369](#)
- SetDataValueRepresentation
 - gdcm::Curve, [270](#)
- SetDebug
 - gdcm::Trace, [721](#)
- SetDebugStream
 - gdcm::Trace, [721](#)
- SetDefaultTransferSyntax
 - gdcm::PresentationContextGenerator, [566](#)
- SetDerivationCodeSequenceCodeValue
 - gdcm::FileDerivation, [362](#)
- SetDerivationDescription
 - gdcm::FileDerivation, [362](#)
- SetDescription
 - gdcm::CSAHeaderDictEntry, [263](#)
 - gdcm::ModuleEntry, [501](#)
 - gdcm::Overlay, [520](#)
- SetDescriptor
 - gdcm::DICOMDIRGenerator, [300](#)
- SetDictName
 - gdcm::DictConverter, [305](#)
- SetDicts
 - gdcm::PythonFilter, [581](#)
 - gdcm::StringFilter, [679](#)
- SetDimension
 - gdcm::Bitmap, [208](#)
- SetDimensions
 - gdcm::Bitmap, [209](#)
 - gdcm::Curve, [270](#)
 - gdcm::ImageCodec, [414](#)
- SetDimensionsValue
 - gdcm::ImageHelper, [421](#)
- SetDirectionCosines
 - gdcm::Image, [396](#)
 - vtkGDCMImageWriter, [838](#)
- SetDirectionCosinesFromImageOrientationPatient
 - vtkGDCMImageWriter, [838](#)
- SetDirectionCosinesTolerance
 - gdcm::IPPSorter, [445](#)
- SetDirectionCosinesValue
 - gdcm::ImageHelper, [421](#)
- SetDirectory
 - gdcm::network::ULWritingCallback, [800](#)
 - gdcm::SerieHelper, [640](#)
- SetDisplayId
 - vtkImageColorViewer, [860](#)
- SetDomain
 - gdcm::BoxRegion, [215](#)
- SetDropDuplicatePositions
 - gdcm::IPPSorter, [445](#)
- SetElement
 - gdcm::Tag, [713](#)
- SetElementHandler
 - gdcm::Parser, [525](#)
- SetElementTag
 - gdcm::Tag, [713](#)
- SetElementXX
 - gdcm::DictEntry, [307](#)
- SetError
 - gdcm::Trace, [721](#)
- SetErrorStream
 - gdcm::Trace, [722](#)
- SetEvent
 - gdcm::network::ULEvent, [797](#)
- SetFile
 - gdcm::Anonymizer, [152](#)
 - gdcm::DICOMDIRGenerator, [300](#)
 - gdcm::FileDerivation, [362](#)
 - gdcm::FileExplicitFilter, [364](#)
 - gdcm::IconImageFilter, [390](#)
 - gdcm::Printer, [573](#)
 - gdcm::PythonFilter, [581](#)
 - gdcm::Reader, [599](#)
 - gdcm::SplitMosaicFilter, [664](#)
 - gdcm::StreamImageWriter, [672](#)
 - gdcm::StringFilter, [679](#)
 - gdcm::Validate, [810](#)
 - gdcm::Writer, [884](#)
- SetFileName
 - gdcm::Reader, [599](#)
 - gdcm::StreamImageReader, [668](#)
 - gdcm::StreamImageWriter, [672](#)
 - gdcm::Writer, [885](#)
 - vtkGDCMThreadedImageReader2, [854](#)
- SetFileNames
 - vtkGDCMImageReader, [832](#)
 - vtkGDCMImageWriter, [838](#)
 - vtkGDCMThreadedImageReader2, [854](#)
- SetFilePattern
 - vtkGDCMImageReader, [833](#)
- SetFilePrefix
 - vtkGDCMImageReader, [833](#)
- SetFilename
 - gdcm::TableReader, [707](#)
- SetFileNames
 - gdcm::DICOMDIRGenerator, [300](#)
- SetFiles
 - gdcm::FileSet, [375](#)

- SetFiniteVolume
 - gdcm::Surface, [688](#)
- SetForce
 - gdcm::ImageChangeTransferSyntax, [409](#)
 - gdcm::ImageFragmentSplitter, [418](#)
- SetForcePixelSpacing
 - gdcm::ImageHelper, [421](#)
- SetForceRescaleInterceptSlope
 - gdcm::ImageHelper, [421](#)
- SetFragmentSizeMax
 - gdcm::ImageFragmentSplitter, [418](#)
- SetFrameOrigin
 - gdcm::Overlay, [520](#)
- SetFromDataElement
 - gdcm::Attribute, [168](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, [173](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [180](#)
 - gdcm::Element, [325](#)
 - gdcm::Element< TVR, VM::VM1_n >, [329](#)
- SetFromDataSet
 - gdcm::Attribute, [168](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, [174](#)
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [180](#)
 - gdcm::MediaStorage, [488](#)
- SetFromFile
 - gdcm::MediaStorage, [488](#)
- SetFromHeader
 - gdcm::MediaStorage, [488](#)
- SetFromModality
 - gdcm::MediaStorage, [488](#)
- SetFromSourceImageSequence
 - gdcm::MediaStorage, [488](#)
- SetFromString
 - gdcm::DirectionCosines, [316](#)
- SetFromUID
 - gdcm::UIDs, [752](#)
- SetGreenLUT
 - gdcm::LookupTable, [475](#)
- SetGroup
 - gdcm::Curve, [270](#)
 - gdcm::Overlay, [520](#)
 - gdcm::Tag, [713](#)
- SetGroupXX
 - gdcm::DictEntry, [307](#)
- SetHeader
 - gdcm::File, [357](#)
- SetHighBit
 - gdcm::PixelFormat, [544](#)
- SetHostname
 - gdcm::ServiceClassUser, [645](#)
- SetIE
 - gdcm::IODEntry, [441](#)
- SetIconImage
 - gdcm::Pixmap, [548](#)
- SetImage
 - gdcm::PixmapWriter, [556](#)
 - gdcm::SplitMosaicFilter, [664](#)
- SetImplementationClassUID
 - gdcm::FileMetaInformation, [369](#)
- SetImplementationVersionName
 - gdcm::FileMetaInformation, [369](#)
- SetInput
 - gdcm::BitmapToBitmapFilter, [212](#)
 - gdcm::ImageConverter, [416](#)
 - vtkImageColorViewer, [860](#)
- SetInputConnection
 - vtkImageColorViewer, [860](#)
- SetInputFileName
 - gdcm::DictConverter, [305](#)
 - gdcm::FileAnonymizer, [359](#)
- SetIntercept
 - gdcm::Image, [396](#)
 - gdcm::Rescaler, [604](#)
- SetKey
 - gdcm::CSAElement, [255](#)
- SetKeyword
 - gdcm::DictEntry, [307](#)
- SetLUT
 - gdcm::Bitmap, [209](#)
 - gdcm::ImageCodec, [414](#)
 - gdcm::LookupTable, [475](#)
 - gdcm::SegmentedPaletteColorLookupTable, [622](#)
- SetLastElement
 - gdcm::ParseException, [522](#)
- SetLastFragment
 - gdcm::network::PresentationDataValue, [569](#)
- SetLength
 - gdcm::ByteValue, [222](#)
 - gdcm::Element< TVR, VM::VM1_2 >, [327](#)
 - gdcm::Element< TVR, VM::VM1_n >, [329](#)
 - gdcm::Element< TVR, VM::VM2_2n >, [331](#)
 - gdcm::Element< TVR, VM::VM2_n >, [332](#)
 - gdcm::Element< TVR, VM::VM3_3n >, [334](#)
 - gdcm::Element< TVR, VM::VM3_n >, [335](#)
 - gdcm::RLECodec, [608](#)
 - gdcm::SequenceOfFragments, [631](#)
 - gdcm::SequenceOfItems, [637](#)
 - gdcm::Value, [812](#)
- SetLengthToUndefined
 - gdcm::SequenceOfItems, [637](#)
- SetLoadMode
 - gdcm::SerieHelper, [640](#)
- SetLookupTable
 - vtkImageMapToColors16, [865](#)

- SetLossless
 - gdcm::JPEGCodec, [463](#)
 - gdcm::JPEGLSCoDec, [466](#)
- SetLossyError
 - gdcm::JPEGLSCoDec, [466](#)
- SetLossyFlag
 - gdcm::Bitmap, [209](#)
 - gdcm::ImageCodec, [414](#)
- SetManifold
 - gdcm::Surface, [688](#)
- SetMaxPDULength
 - gdcm::network::ULConnectionInfo, [793](#)
- SetMaxPDUSize
 - gdcm::network::ULConnection, [791](#)
- SetMaximumLength
 - gdcm::network::MaximumLengthSub, [480](#)
- SetMaximumPointDistance
 - gdcm::Surface, [688](#)
- SetMeanPointDistance
 - gdcm::Surface, [688](#)
- SetMedicalImageProperties
 - vtkGDCMImageReader, [833](#)
 - vtkGDCMImageWriter, [838](#)
 - vtkGDCMPolyDataWriter, [846](#)
- SetMergeModeToAbstractSyntax
 - gdcm::PresentationContextGenerator, [566](#)
- SetMergeModeToTransferSyntax
 - gdcm::PresentationContextGenerator, [566](#)
- SetMeshPrimitive
 - gdcm::Surface, [688](#)
- SetMessageHeader
 - gdcm::network::PresentationDataValue, [569](#)
- SetMinMaxForPixelType
 - gdcm::Rescaler, [604](#)
- SetName
 - gdcm::CSAElement, [255](#)
 - gdcm::CSAHeaderDictEntry, [263](#)
 - gdcm::DictEntry, [307](#)
 - gdcm::LODEntry, [441](#)
 - gdcm::Macro, [477](#)
 - gdcm::Module, [498](#)
 - gdcm::ModuleEntry, [501](#)
 - gdcm::network::AbstractSyntax, [145](#)
 - gdcm::network::ApplicationContext, [154](#)
 - gdcm::network::TransferSyntaxSub, [727](#)
 - gdcm::PDBelement, [529](#)
- SetNameFromUID
 - gdcm::network::AbstractSyntax, [145](#)
 - gdcm::network::TransferSyntaxSub, [727](#)
- SetNeedByteSwap
 - gdcm::Bitmap, [209](#)
 - gdcm::ImageCodec, [414](#)
- SetNeedOverlayCleanup
 - gdcm::ImageCodec, [414](#)
- SetNestedDataSet
 - gdcm::Item, [449](#)
- SetNoOfItems
 - gdcm::CSAElement, [255](#)
- SetNoSwap
 - gdcm::Element, [325](#)
 - gdcm::Element< TVR, VM::VM1_n >, [329](#)
- SetNumberOfCurves
 - gdcm::Pixmap, [548](#)
- SetNumberOfDimensions
 - gdcm::Bitmap, [209](#)
 - gdcm::ImageCodec, [414](#)
- SetNumberOfFilenames
 - gdcm::FilenameGenerator, [374](#)
- SetNumberOfFrames
 - gdcm::Overlay, [520](#)
- SetNumberOfInputPorts
 - vtkGDCMPolyDataWriter, [847](#)
- SetNumberOfItems
 - gdcm::SequenceOfItems, [637](#)
- SetNumberOfOverlays
 - gdcm::Pixmap, [548](#)
- SetNumberOfPoints
 - gdcm::Curve, [270](#)
- SetNumberOfResolutions
 - gdcm::JPEG2000Codec, [457](#)
- SetNumberOfSegments
 - gdcm::SegmentWriter, [627](#)
- SetNumberOfSurfacePoints
 - gdcm::Surface, [688](#)
- SetNumberOfSurfaces
 - gdcm::SurfaceWriter, [696](#)
- SetNumberOfTableValues
 - vtkLookupTable16, [875](#)
- SetNumberOfValues
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, [180](#)
- SetNumberOfVectors
 - gdcm::Surface, [688](#)
- SetObliquityThresholdCosineValue
 - gdcm::Orientation, [514](#)
- SetOffScreenRendering
 - vtkImageColorViewer, [860](#)
- SetOrigin
 - gdcm::Image, [396](#)
 - gdcm::Overlay, [520](#)
- SetOriginValue
 - gdcm::ImageHelper, [421](#)
- SetOutputDimensions
 - gdcm::IconImageGenerator, [392](#)
- SetOutputFileName
 - gdcm::DictConverter, [305](#)
 - gdcm::FileAnonymizer, [360](#)
- SetOutputFormatToLuminance

- vtkImageMapToColors16, [865](#)
- SetOutputFormatToLuminanceAlpha
 - vtkImageMapToColors16, [865](#)
- SetOutputFormatToRGB
 - vtkImageMapToColors16, [865](#)
- SetOutputFormatToRGBA
 - vtkImageMapToColors16, [865](#)
- SetOutputType
 - gdcm::DictConverter, [305](#)
- SetOutsideValuePixel
 - gdcm::IconImageGenerator, [392](#)
- SetOverlay
 - gdcm::Overlay, [520](#)
- SetOverlayVisibility
 - vtkImageColorViewer, [860](#)
- SetOwner
 - gdcm::PrivateTag, [576](#)
- SetPDU
 - gdcm::network::ULEvent, [797](#)
- SetParentId
 - vtkImageColorViewer, [860](#)
- SetPattern
 - gdcm::FilenameGenerator, [374](#)
- SetPermissions
 - gdcm::System, [703](#)
- SetPhotometricInterpretation
 - gdcm::Bitmap, [209](#)
 - gdcm::ImageChangePhotometricInterpretation, [402](#)
 - gdcm::ImageCodec, [414](#)
- SetPixelFormat
 - gdcm::Bitmap, [209](#)
 - gdcm::ImageCodec, [414](#)
 - gdcm::JPEGCodec, [463](#)
 - gdcm::Rescaler, [604](#)
- SetPixelMinMax
 - gdcm::IconImageGenerator, [392](#)
- SetPixelRepresentation
 - gdcm::PixelFormat, [544](#)
- SetPixmap
 - gdcm::IconImageGenerator, [392](#)
 - gdcm::PixmapWriter, [557](#)
- SetPlanarConfiguration
 - gdcm::Bitmap, [209](#)
 - gdcm::ImageChangePlanarConfiguration, [406](#)
 - gdcm::ImageCodec, [414](#)
- SetPointCoordinatesData
 - gdcm::Surface, [688](#)
- SetPointPositionAccuracy
 - gdcm::Surface, [689](#)
- SetPointsBoundingBoxCoordinates
 - gdcm::Surface, [689](#)
- SetPort
 - gdcm::ServiceClassUser, [645](#)
- SetPortSCP
 - gdcm::ServiceClassUser, [645](#)
- SetPosition
 - vtkImageColorViewer, [861](#)
- SetPreamble
 - gdcm::FileMetaInformation, [369](#)
- SetPrefix
 - gdcm::FilenameGenerator, [374](#)
- SetPresentationContextId
 - gdcm::network::PresentationContextAC, [563](#)
 - gdcm::network::PresentationContextRQ, [568](#)
 - gdcm::network::PresentationDataValue, [569](#)
 - gdcm::PresentationContext, [562](#)
- SetPresentationContexts
 - gdcm::network::ULConnection, [791](#)
 - gdcm::ServiceClassUser, [646](#)
- SetPrimitiveData
 - gdcm::MeshPrimitive, [495](#)
- SetPrimitiveType
 - gdcm::MeshPrimitive, [495](#)
- SetPrimitivesData
 - gdcm::MeshPrimitive, [495](#)
- SetPrivateCreator
 - gdcm::Tag, [713](#)
- SetProcessingAlgorithm
 - gdcm::Surface, [689](#)
- SetProgress
 - gdcm::ProgressEvent, [578](#)
- SetPropertyCategory
 - gdcm::Segment, [620](#)
- SetPropertyType
 - gdcm::Segment, [620](#)
- SetPurposeOfReferenceCodeSequenceCodeValue
 - gdcm::FileDerivation, [362](#)
- SetQuality
 - gdcm::JPEG2000Codec, [457](#)
 - gdcm::JPEGCodec, [463](#)
- SetRTStructSetProperties
 - vtkGDCMPolyDataWriter, [847](#)
- SetRate
 - gdcm::JPEG2000Codec, [457](#)
- SetReason
 - gdcm::network::AAAbortPDU, [134](#)
 - gdcm::network::PresentationContextAC, [564](#)
- SetRecommendedDisplayCIELabValue
 - gdcm::Surface, [689](#)
- SetRecommendedDisplayGrayscaleValue
 - gdcm::Surface, [689](#)
- SetRecommendedPresentationOpacity
 - gdcm::Surface, [689](#)
- SetRecommendedPresentationType
 - gdcm::Surface, [689](#)
- SetRecomputeItemLength
 - gdcm::FileExplicitFilter, [364](#)
- SetRecomputeSequenceLength

- gdcm::FileExplicitFilter, 364
- SetRedLUT
 - gdcm::LookupTable, 475
- SetRef
 - gdcm::IODEntry, 441
- SetRegion
 - gdcm::ImageRegionReader, 428
- SetRenderWindow
 - vtkImageColorViewer, 861
- SetRenderer
 - vtkImageColorViewer, 861
- SetRescaleInterceptSlopeValue
 - gdcm::ImageHelper, 421
- SetRetired
 - gdcm::DictEntry, 307
- SetReversible
 - gdcm::JPEG2000Codec, 457
- SetRoot
 - gdcm::UIDGenerator, 733
- SetRootDirectory
 - gdcm::DICOMDIRGenerator, 300
- SetRows
 - gdcm::Bitmap, 209
 - gdcm::Overlay, 520
- SetSamplesPerPixel
 - gdcm::PixelFormat, 544
- SetScalarType
 - gdcm::PixelFormat, 544
- SetSearchParameter
 - gdcm::BaseRootQuery, 197
- SetSegmentAlgorithmName
 - gdcm::Segment, 620
- SetSegmentAlgorithmType
 - gdcm::Segment, 620
- SetSegmentDescription
 - gdcm::Segment, 620
- SetSegmentLabel
 - gdcm::Segment, 620
- SetSegmentNumber
 - gdcm::Segment, 620
- SetSegments
 - gdcm::SegmentWriter, 627
- SetSize
 - vtkImageColorViewer, 861
- SetSlice
 - vtkImageColorViewer, 861
- SetSliceOrientation
 - vtkImageColorViewer, 861
- SetSliceOrientationToXY
 - vtkImageColorViewer, 861
- SetSliceOrientationToXZ
 - vtkImageColorViewer, 861
- SetSliceOrientationToYZ
 - vtkImageColorViewer, 861
- SetSlope
 - gdcm::Image, 396
 - gdcm::Rescaler, 605
- SetSortFunction
 - gdcm::Sorter, 660
- SetSource
 - gdcm::network::AAAbortPDU, 135
- SetSourceApplicationEntityTitle
 - gdcm::FileMetaInformation, 369
- SetSpacing
 - gdcm::Image, 396
- SetSpacingValue
 - gdcm::ImageHelper, 421
- SetState
 - gdcm::network::ULConnection, 791
- SetStream
 - gdcm::Reader, 600
 - gdcm::StreamImageReader, 669
 - gdcm::StreamImageWriter, 672
 - gdcm::Trace, 722
 - gdcm::Writer, 885
- SetStreamToFile
 - gdcm::Trace, 722
- SetStyle
 - gdcm::Printer, 573
- SetSurfaceComments
 - gdcm::Surface, 689
- SetSurfaceCount
 - gdcm::Segment, 620
- SetSurfaceNumber
 - gdcm::Surface, 689
- SetSurfaceProcessing
 - gdcm::Surface, 689
- SetSurfaceProcessingDescription
 - gdcm::Surface, 689
- SetSurfaceProcessingRatio
 - gdcm::Surface, 689
- SetSyngoDT
 - gdcm::CSAElement, 255
- SetTag
 - gdcm::AnonymizeEvent, 147
 - gdcm::DataElement, 277
- SetTargetPixelType
 - gdcm::Rescaler, 605
- SetTileSize
 - gdcm::JPEG2000Codec, 457
- SetTimeout
 - gdcm::network::ARTIMTimer, 161
 - gdcm::ServiceClassUser, 646
- SetToUndefined
 - gdcm::VL, 816
- SetTransferSyntax
 - gdcm::Bitmap, 210
 - gdcm::ImageChangeTransferSyntax, 409

- gdcm::network::PresentationContextAC, 564
- SetTuple
 - gdcm::network::RoleSelectionSub, 609
 - gdcm::network::ServiceClassApplicationInformation, 641
 - gdcm::network::SOPClassExtendedNegociationSub, 656
- SetType
 - gdcm::ModuleEntry, 501
 - gdcm::Overlay, 520
- SetTypeOfData
 - gdcm::Curve, 270
- SetUsage
 - gdcm::IODEntry, 441
- SetUseSeriesDetails
 - gdcm::SerieHelper, 640
- SetUseTargetPixelType
 - gdcm::Rescaler, 605
- SetUseVRUN
 - gdcm::FileExplicitFilter, 364
- SetUserCodec
 - gdcm::ImageChangeTransferSyntax, 409
- SetUserData
 - gdcm::Parser, 525
- SetUserInformation
 - gdcm::network::AAssociateRQPDU, 142
- SetVL
 - gdcm::DataElement, 278
- SetVLToUndefined
 - gdcm::DataElement, 278
- SetVM
 - gdcm::CSAElement, 255
 - gdcm::CSAHeaderDictEntry, 263
 - gdcm::DictEntry, 307
- SetVR
 - gdcm::CSAElement, 255
 - gdcm::CSAHeaderDictEntry, 263
 - gdcm::DataElement, 278
 - gdcm::DictEntry, 307
- SetValue
 - gdcm::Attribute, 169
 - gdcm::Attribute< Group, Element, TVR, VM::VM1 >, 174
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, 181
 - gdcm::CSAElement, 255
 - gdcm::DataElement, 277
 - gdcm::Element, 325
 - gdcm::Element< TVR, VM::VM1_n >, 329
 - gdcm::PDBElement, 529
- SetValues
 - gdcm::Attribute, 169
 - gdcm::Attribute< Group, Element, TVR, VM::VM1_n >, 181
- SetVectorAccuracy
 - gdcm::Surface, 689
- SetVectorCoordinateData
 - gdcm::Surface, 689
- SetVectorDimensionality
 - gdcm::Surface, 689
- SetWarning
 - gdcm::Trace, 722
- SetWarningStream
 - gdcm::Trace, 722
- SetWindowId
 - vtkImageColorViewer, 861
- SetWriteDataSetOnly
 - gdcm::Writer, 885
- SetZSpacingTolerance
 - gdcm::IPPSorter, 445
- setAttribute
 - gdcm::terminal, 131
- setbgcolor
 - gdcm::terminal, 131
- setfgcolor
 - gdcm::terminal, 131
- setmode
 - gdcm::terminal, 131
- SetupInteractor
 - vtkImageColorViewer, 861
- Shift
 - vtkGDCMImageReader, 835
- ShiftEnd
 - gdcm::ByteBuffer, 216
- ShowAbort
 - gdcm::SimpleSubjectWatcher, 651
- ShowAnonymization
 - gdcm::SimpleSubjectWatcher, 651
- ShowData
 - gdcm::SimpleSubjectWatcher, 652
- ShowDataSet
 - gdcm::SimpleSubjectWatcher, 652
- ShowIteration
 - gdcm::SimpleSubjectWatcher, 652
- ShowProgress
 - gdcm::SimpleSubjectWatcher, 652
- SimpleMemberCommand
 - gdcm::SimpleMemberCommand, 650
- SimpleSubjectWatcher
 - gdcm::SimpleSubjectWatcher, 651
- SingleSerieUIDFileSetHT
 - gdcm::SerieHelper, 640
- SingleSerieUIDFileSetmap
 - gdcm::SerieHelper, 639
- Size
 - gdcm::CodeString, 239
 - gdcm::DataSet, 289
 - gdcm::GroupDict, 388

- gdcm::network::AAAbortPDU, [135](#)
- gdcm::network::AAAssociateACPDU, [137](#)
- gdcm::network::AAAssociateRJPDU, [139](#)
- gdcm::network::AAAssociateRQPDU, [143](#)
- gdcm::network::AbstractSyntax, [145](#)
- gdcm::network::ApplicationContext, [154](#)
- gdcm::network::AReleaseRPPDU, [158](#)
- gdcm::network::AReleaseRQPDU, [159](#)
- gdcm::network::AsynchronousOperationsWindow-Sub, [162](#)
- gdcm::network::BasePDU, [194](#)
- gdcm::network::ImplementationClassUIDSub, [433](#)
- gdcm::network::ImplementationVersionNameSub, [434](#)
- gdcm::network::MaximumLengthSub, [480](#)
- gdcm::network::PDataTFPDU, [527](#)
- gdcm::network::PresentationContextAC, [564](#)
- gdcm::network::PresentationContextRQ, [568](#)
- gdcm::network::PresentationDataValue, [570](#)
- gdcm::network::RoleSelectionSub, [609](#)
- gdcm::network::ServiceClassApplicationInformation, [641](#)
- gdcm::network::SOPClassExtendedNegociationSub, [656](#)
- gdcm::network::TransferSyntaxSub, [727](#)
- gdcm::network::UserInformation, [808](#)
- size_type
 - gdcm::CodeString, [238](#)
 - gdcm::LO, [471](#)
 - gdcm::String, [676](#)
- SizeType
 - gdcm::DataSet, [285](#)
 - gdcm::FilenameGenerator, [373](#)
 - gdcm::IOD, [438](#)
 - gdcm::NestedModuleEntries, [509](#)
 - gdcm::network::AAAssociateACPDU, [137](#)
 - gdcm::network::AAAssociateRQPDU, [141](#)
 - gdcm::network::PDataTFPDU, [527](#)
 - gdcm::network::PresentationContextRQ, [567](#)
 - gdcm::PresentationContext, [562](#)
 - gdcm::PresentationContextGenerator, [565](#)
 - gdcm::SequenceOfFragments, [630](#)
 - gdcm::SequenceOfItems, [635](#)
- Slice
 - vtkImageColorViewer, [862](#)
- SliceOrientation
 - vtkImageColorViewer, [862](#)
- SmartPointer
 - gdcm::Object, [512](#)
 - gdcm::SmartPointer, [654](#)
- Sort
 - gdcm::IPPSorter, [445](#)
 - gdcm::Sorter, [660](#)
- SortFunc
 - gdcm::Sorter, [661](#)
- SortFunction
 - gdcm::Sorter, [659](#)
- Sorter
 - gdcm::Sorter, [660](#)
- SpacialFiducialsStorage
 - gdcm::MediaStorage, [485](#)
- SpacialRegistrationStorage
 - gdcm::MediaStorage, [485](#)
- Spacing
 - gdcm::Spacing, [662](#)
- SpacingType
 - gdcm::Spacing, [662](#)
- SpatialFiducialsStorage
 - gdcm::UIDs, [742](#)
- SpatialRegistrationStorage
 - gdcm::UIDs, [742](#)
- Spectroscopy
 - gdcm::Spectroscopy, [663](#)
- Split
 - gdcm::ImageFragmentSplitter, [418](#)
 - gdcm::SplitMosaicFilter, [664](#)
- SplitExtent
 - vtkGDCMThreadedImageReader2, [855](#)
- SplitMosaicFilter
 - gdcm::SplitMosaicFilter, [664](#)
- Squeeze
 - gdcm::ApplicationEntity, [156](#)
- StableSort
 - gdcm::Sorter, [660](#)
- StandaloneCurveStorage
 - gdcm::MediaStorage, [485](#)
- StandaloneCurveStorageRetired
 - gdcm::UIDs, [741](#)
- StandaloneModalityLUTStorage
 - gdcm::MediaStorage, [485](#)
- StandaloneModalityLUTStorageRetired
 - gdcm::UIDs, [742](#)
- StandaloneOverlayStorage
 - gdcm::MediaStorage, [485](#)
- StandaloneOverlayStorageRetired
 - gdcm::UIDs, [741](#)
- StandalonePETCurveStorageRetired
 - gdcm::UIDs, [743](#)
- StandaloneVOILUTStorage
 - gdcm::MediaStorage, [485](#)
- StandaloneVOILUTStorageRetired
 - gdcm::UIDs, [742](#)
- Start
 - gdcm::network::ARTIMTimer, [161](#)
- StartAssociation
 - gdcm::ServiceClassUser, [646](#)
- StartElement
 - gdcm::TableReader, [707](#)

- gdcmm::XMLDictReader, 887
- gdcmm::XMLPrivateDictReader, 889
- StartElementHandler
 - gdcmm::Parser, 524
- StartFilter
 - gdcmm::SimpleSubjectWatcher, 652
- StereometricRelationshipStorage
 - gdcmm::UIDs, 742
- Stop
 - gdcmm::network::ARTIMTimer, 161
- StopAssociation
 - gdcmm::ServiceClassUser, 646
- StopProtocol
 - gdcmm::network::ULConnection, 791
- StorageCommitmentPullModelSOPClassRetired
 - gdcmm::UIDs, 740
- StorageCommitmentPullModelSOPInstanceRetired
 - gdcmm::UIDs, 740
- StorageCommitmentPushModelSOPClass
 - gdcmm::UIDs, 740
- StorageCommitmentPushModelSOPInstance
 - gdcmm::UIDs, 740
- StorageServiceClass
 - gdcmm::UIDs, 740
- StoredPrintStorageSOPClassRetired
 - gdcmm::UIDs, 741
- StrCaseCmp
 - gdcmm::System, 703
- StrNCaseCmp
 - gdcmm::System, 703
- StrTokR
 - gdcmm::System, 703
- Stream
 - gdcmm::Writer, 885
- StreamImageReader
 - gdcmm::Reader, 600
 - gdcmm::StreamImageReader, 667
- StreamImageWriter
 - gdcmm::StreamImageWriter, 671
 - gdcmm::Writer, 885
- String
 - gdcmm::String, 677
- StringFilter
 - gdcmm::StringFilter, 678
- StructureSetDate
 - vtkRTStructSetProperties, 880
- StructureSetLabel
 - vtkRTStructSetProperties, 880
- StructureSetName
 - vtkRTStructSetProperties, 880
- StructureSetTime
 - vtkRTStructSetProperties, 880
- Study
 - gdcmm::Study, 680
- StudyComponentManagementSOPClass
 - gdcmm::MediaStorage, 485
- StudyComponentManagementSOPClassRetired
 - gdcmm::UIDs, 740
- StudyRootQueryRetrieveInformationModelFIND
 - gdcmm::UIDs, 743
- StudyRootQueryRetrieveInformationModelGET
 - gdcmm::UIDs, 743
- StudyRootQueryRetrieveInformationModelMOVE
 - gdcmm::UIDs, 743
- StudyInstanceUID
 - vtkRTStructSetProperties, 880
- Subject
 - gdcmm::Subject, 682
- SubstanceAdministrationLoggingSOPClass
 - gdcmm::UIDs, 740
- SubstanceAdministrationLoggingSOPInstance
 - gdcmm::UIDs, 740
- SubstanceApprovalQuerySOPClass
 - gdcmm::UIDs, 744
- Superclass
 - gdcmm::AnonymizeEvent, 147
 - gdcmm::DataEvent, 281
 - gdcmm::DataSetEvent, 290
 - gdcmm::LO, 471
 - gdcmm::ProgressEvent, 578
- Surface
 - gdcmm::Surface, 686
- SurfaceSegmentationStorage
 - gdcmm::MediaStorage, 486
 - gdcmm::UIDs, 745
- SurfaceCount
 - gdcmm::Segment, 620
- SurfaceReader
 - gdcmm::SurfaceReader, 694
- SurfaceVector
 - gdcmm::Segment, 619
- SurfaceWriter
 - gdcmm::SurfaceWriter, 696
- Surfaces
 - gdcmm::Segment, 620
- Swap
 - gdcmm::ByteSwap, 217
 - gdcmm::SwapperDoOp, 698
 - gdcmm::SwapperNoOp, 699
- SwapArray
 - gdcmm::SwapperDoOp, 698
 - gdcmm::SwapperNoOp, 699
- SwapCode
 - gdcmm::SwapCode, 698
- SwapCodeType
 - gdcmm::SwapCode, 697
- SwapFromSwapCodeIntoSystem
 - gdcmm::ByteSwap, 217

- SwapRange
 - gdcm::ByteSwap, [217](#)
- SwapRangeFromSwapCodeIntoSystem
 - gdcm::ByteSwap, [217](#)
- SyngoDTField
 - gdcm::CSAElement, [256](#)
- SyntaxError
 - gdcm::Parser, [524](#)
- SystemIsBigEndian
 - gdcm::ByteSwap, [217](#)
- SystemIsLittleEndian
 - gdcm::ByteSwap, [217](#)
- T1
 - gdcm::Type, [730](#)
- T1C
 - gdcm::Type, [730](#)
- T2
 - gdcm::Type, [730](#)
- T2C
 - gdcm::Type, [730](#)
- T3
 - gdcm::Type, [730](#)
- TM
 - gdcm::VR, [823](#)
- TRIANGLE
 - gdcm::MeshPrimitive, [494](#)
- TRIANGLE_FAN
 - gdcm::MeshPrimitive, [494](#)
- TRIANGLE_STRIP
 - gdcm::MeshPrimitive, [494](#)
- TS_END
 - gdcm::TransferSyntax, [725](#)
- TConstMemberFunctionPointer
 - gdcm::MemberCommand, [490](#)
- TMComp
 - gdcm, [118](#)
- TMemberFunctionPointer
 - gdcm::MemberCommand, [491](#)
 - gdcm::SimpleMemberCommand, [649](#)
- TS
 - gdcm::Bitmap, [211](#)
- TSName
 - gdcm::UIDs, [738](#)
- TSType
 - gdcm::TransferSyntax, [724](#)
 - gdcm::UIDs, [745](#)
- TYPETOENCODING
 - gdcm, [124](#)
 - gdcmVR.h, [1166](#)
- TYPETOLENGTH
 - gdcmVM.h, [1164](#)
- Table
 - gdcm::Table, [704](#)
- Table16
 - vtkLookupTable16, [875](#)
- TableEntry
 - gdcm::TableEntry, [705](#)
- TableReader
 - gdcm::TableReader, [706](#)
- TableRow
 - gdcm::network::TableRow, [708](#)
- Tag
 - gdcm::Tag, [710](#)
- tag
 - gdcm::Tag, [714](#)
- TagMismatchError
 - gdcm::Parser, [524](#)
- TagField
 - gdcm::DataElement, [279](#)
- TagPath
 - gdcm::TagPath, [715](#)
- TagToValue
 - gdcm::Scanner, [613](#)
- TagToValueValueType
 - gdcm::Scanner, [613](#)
- tags
 - gdcm::Tag, [714](#)
- TalairachBrainAtlasFrameofReference
 - gdcm::UIDs, [739](#)
- TestAbortOff
 - gdcm::SimpleSubjectWatcher, [652](#)
- TestAbortOn
 - gdcm::SimpleSubjectWatcher, [652](#)
- TestPBKDF2
 - gdcm::ASN1, [161](#)
- Testing
 - gdcm::Testing, [717](#)
- TestsList.txt, [1170](#)
- TextSRStorageTrialRetired
 - gdcm::UIDs, [742](#)
- ThreadedExecute
 - vtkImageRGBToYBR, [871](#)
 - vtkImageYBRToRGB, [873](#)
- ThreadedRequestData
 - vtkGDCMThreadedImageReader2, [855](#)
 - vtkImageMapToColors16, [865](#)
 - vtkImageMapToWindowLevelColors2, [867](#)
- to_string
 - gdcm, [124](#)
- ToPyObject
 - gdcm::PythonFilter, [581](#)
- ToString
 - gdcm::StringFilter, [679](#)
- ToStringPair
 - gdcm::StringFilter, [679](#)
- ToUnixSlashes
 - gdcm::Filename, [371](#)

- ToWindowsSlashes
 - gdcm::Filename, [371](#)
- ToshibaPrivateDataStorage
 - gdcm::MediaStorage, [485](#)
- Trace
 - gdcm::Trace, [721](#)
- TransferSyntax
 - gdcm::TransferSyntax, [725](#)
- TransferSyntaxArrayType
 - gdcm::PresentationContext, [562](#)
- TransferSyntaxStringsType
 - gdcm::UIDs, [738](#)
- TransferSyntaxSub
 - gdcm::network::TransferSyntaxSub, [727](#)
- Transition
 - gdcm::network::Transition, [728](#)
- transitions
 - gdcm::network::TableRow, [708](#)
- Trim
 - gdcm::String, [677](#)
- TrimInternal
 - gdcm::CodeString, [239](#)
- Truncate
 - gdcm::String, [677](#)
- TryJPEG2000Codec
 - gdcm::Bitmap, [210](#)
 - gdcm::ImageChangeTransferSyntax, [409](#)
- TryJPEG2000Codec2
 - gdcm::Bitmap, [210](#)
- TryJPEGCodec
 - gdcm::Bitmap, [210](#)
 - gdcm::ImageChangeTransferSyntax, [409](#)
- TryJPEGCodec2
 - gdcm::Bitmap, [210](#)
- TryJPEGLSCodec
 - gdcm::Bitmap, [210](#)
 - gdcm::ImageChangeTransferSyntax, [409](#)
- TryKAKADUCodec
 - gdcm::Bitmap, [210](#)
- TryPVRGCodec
 - gdcm::Bitmap, [210](#)
- TryRAWCodec
 - gdcm::Bitmap, [210](#)
 - gdcm::ImageChangeTransferSyntax, [409](#)
- TryRLECodec
 - gdcm::Bitmap, [210](#)
 - gdcm::ImageChangeTransferSyntax, [409](#)
- Type
 - gdcm::Element, [325](#)
 - gdcm::Element< TVR, VM::VM1_n >, [328](#)
 - gdcm::Type, [730](#)
 - gdcm::VL, [815](#)
- TypeType
 - gdcm::Type, [730](#)
- UI
 - gdcm::VR, [823](#)
- UINT12
 - gdcm::PixelFormat, [542](#)
- UINT16
 - gdcm::PixelFormat, [542](#)
- UINT32
 - gdcm::PixelFormat, [542](#)
- UINT8
 - gdcm::PixelFormat, [542](#)
- UL
 - gdcm::VR, [823](#)
- UN
 - gdcm::VR, [823](#)
- UNKNOWN
 - gdcm::PhotometricInterpretation, [539](#)
- UNKNOWN
 - gdcm::CSAHeader, [258](#)
 - gdcm::LookupTable, [474](#)
 - gdcm::Orientation, [514](#)
 - gdcm::PixelFormat, [542](#)
 - gdcm::Spacing, [662](#)
 - gdcm::Surface, [686](#)
 - gdcm::Type, [730](#)
- URI
 - gdcm::MediaStorage, [486](#)
- US
 - gdcm::VR, [823](#)
- US_SS
 - gdcm::VR, [823](#)
- US_SS_OW
 - gdcm::VR, [823](#)
- UT
 - gdcm::VR, [823](#)
- UIComp
 - gdcm, [118](#)
- UIDGenerator
 - gdcm::UIDGenerator, [732](#)
- ULAction
 - gdcm::network::ULAction, [754](#)
- ULBasicCallback
 - gdcm::network::ULBasicCallback, [788](#)
- ULConnection
 - gdcm::network::ULConnection, [790](#)
- ULConnectionCallback
 - gdcm::network::ULConnectionCallback, [792](#)
- ULConnectionInfo
 - gdcm::network::ULConnectionInfo, [793](#)
- ULConnectionManager
 - gdcm::network::ULConnectionManager, [796](#)
- ULEvent
 - gdcm::network::ULEvent, [797](#)
- ULTransitionTable
 - gdcm::network::ULTransitionTable, [798](#)

ULWritingCallback
 gdcmm::network::ULWritingCallback, [799](#)
UTComp
 gdcmm, [118](#)
uid_1_2_840_10008_15_0_3_1
 gdcmm::UIDs, [750](#)
uid_1_2_840_10008_15_0_3_10
 gdcmm::UIDs, [750](#)
uid_1_2_840_10008_15_0_3_11
 gdcmm::UIDs, [750](#)
uid_1_2_840_10008_15_0_3_12
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_13
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_14
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_15
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_16
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_17
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_18
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_19
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_2
 gdcmm::UIDs, [750](#)
uid_1_2_840_10008_15_0_3_20
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_21
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_22
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_23
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_24
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_25
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_26
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_27
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_28
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_29
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_3
 gdcmm::UIDs, [750](#)
uid_1_2_840_10008_15_0_3_30
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_31
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_3_4
 gdcmm::UIDs, [750](#)
uid_1_2_840_10008_15_0_3_5
 gdcmm::UIDs, [750](#)
uid_1_2_840_10008_15_0_3_6
 gdcmm::UIDs, [750](#)
uid_1_2_840_10008_15_0_3_7
 gdcmm::UIDs, [750](#)
uid_1_2_840_10008_15_0_3_8
 gdcmm::UIDs, [750](#)
uid_1_2_840_10008_15_0_3_9
 gdcmm::UIDs, [750](#)
uid_1_2_840_10008_15_0_4_1
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_4_2
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_4_3
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_4_4
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_4_5
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_4_6
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_4_7
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_15_0_4_8
 gdcmm::UIDs, [751](#)
uid_1_2_840_10008_1_1
 gdcmm::UIDs, [745](#)
uid_1_2_840_10008_1_2
 gdcmm::UIDs, [745](#)
uid_1_2_840_10008_1_20_1
 gdcmm::UIDs, [746](#)
uid_1_2_840_10008_1_20_1_1
 gdcmm::UIDs, [746](#)
uid_1_2_840_10008_1_20_2
 gdcmm::UIDs, [746](#)
uid_1_2_840_10008_1_20_2_1
 gdcmm::UIDs, [746](#)
uid_1_2_840_10008_1_2_1
 gdcmm::UIDs, [745](#)
uid_1_2_840_10008_1_2_1_99
 gdcmm::UIDs, [745](#)
uid_1_2_840_10008_1_2_2
 gdcmm::UIDs, [745](#)
uid_1_2_840_10008_1_2_4_100
 gdcmm::UIDs, [746](#)
uid_1_2_840_10008_1_2_4_50
 gdcmm::UIDs, [745](#)
uid_1_2_840_10008_1_2_4_51
 gdcmm::UIDs, [745](#)
uid_1_2_840_10008_1_2_4_52
 gdcmm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_53
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_54
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_55
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_56
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_57
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_58
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_59
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_60
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_61
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_62
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_63
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_64
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_65
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_66
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_70
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_80
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_81
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_90
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_91
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_92
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_93
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_94
gdcm::UIDs, [745](#)

uid_1_2_840_10008_1_2_4_95
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_2_5
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_2_6_1
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_2_6_2
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_3_10
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_40
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_40_1
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_42
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_42_1
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_1
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_10
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_11
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_12
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_13
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_14
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_15
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_16
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_17
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_18
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_2
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_3
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_4
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_5
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_6
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_7
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_8
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_1_9
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_2_1
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_4_2_2
gdcm::UIDs, [746](#)

uid_1_2_840_10008_1_9
gdcm::UIDs, [746](#)

uid_1_2_840_10008_2_16_4
gdcm::UIDs, [746](#)

uid_1_2_840_10008_2_6_1
gdcm::UIDs, [746](#)

uid_1_2_840_10008_3_1_1_1
gdcml::UIDs, [746](#)

uid_1_2_840_10008_3_1_2_1_1
gdcml::UIDs, [746](#)

uid_1_2_840_10008_3_1_2_1_4
gdcml::UIDs, [746](#)

uid_1_2_840_10008_3_1_2_2_1
gdcml::UIDs, [746](#)

uid_1_2_840_10008_3_1_2_3_1
gdcml::UIDs, [746](#)

uid_1_2_840_10008_3_1_2_3_2
gdcml::UIDs, [747](#)

uid_1_2_840_10008_3_1_2_3_3
gdcml::UIDs, [747](#)

uid_1_2_840_10008_3_1_2_3_4
gdcml::UIDs, [747](#)

uid_1_2_840_10008_3_1_2_3_5
gdcml::UIDs, [747](#)

uid_1_2_840_10008_3_1_2_5_1
gdcml::UIDs, [747](#)

uid_1_2_840_10008_3_1_2_5_4
gdcml::UIDs, [747](#)

uid_1_2_840_10008_3_1_2_5_5
gdcml::UIDs, [747](#)

uid_1_2_840_10008_3_1_2_6_1
gdcml::UIDs, [747](#)

uid_1_2_840_10008_4_2
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_1
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_14
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_15
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_16
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_16_376
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_17
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_17_376
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_18
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_18_1
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_2
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_22
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_23
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_24
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_24_1
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_25
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_26
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_27
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_29
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_30
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_31
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_32
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_33
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_4
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_4_1
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_4_2
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_9
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_1_9_1
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_4_1_1_1
gdcml::UIDs, [747](#)

uid_1_2_840_10008_5_1_4_1_1_10
gdcml::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_104_1
gdcml::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_104_2
gdcml::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_11
gdcml::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_11_1
gdcml::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_11_2
gdcml::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_11_3
gdcml::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_11_4
gdcml::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_128
gdcml::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_129
gdcml::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_12_1
gdcml::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_12_1_1
gdcml::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_12_2
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_12_2_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_12_3
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_13_1_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_13_1_2
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_13_1_3
gdcm::UIDs, [751](#)

uid_1_2_840_10008_5_1_4_1_1_1_1
gdcm::UIDs, [747](#)

uid_1_2_840_10008_5_1_4_1_1_1_1_1
gdcm::UIDs, [747](#)

uid_1_2_840_10008_5_1_4_1_1_1_2
gdcm::UIDs, [747](#)

uid_1_2_840_10008_5_1_4_1_1_1_2_1
gdcm::UIDs, [747](#)

uid_1_2_840_10008_5_1_4_1_1_1_3
gdcm::UIDs, [747](#)

uid_1_2_840_10008_5_1_4_1_1_1_3_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_2
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_20
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_2_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_3
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_3_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_4
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_481_1
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_481_2
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_481_3
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_481_4
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_481_5
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_481_6
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_481_7
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_481_8
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_481_9
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_4_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_4_2
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_5
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_6
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_66
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_66_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_66_2
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_66_3
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_66_4
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_66_5
gdcm::UIDs, [751](#)

uid_1_2_840_10008_5_1_4_1_1_67
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_6_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_6_2
gdcm::UIDs, [751](#)

uid_1_2_840_10008_5_1_4_1_1_7
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_77_1
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_1
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_1_1
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_2
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_2_1
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_3
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_4
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_4_1
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_5_1
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_5_2
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_5_3
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_5_4
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_77_1_6
gdcm::UIDs, [751](#)

uid_1_2_840_10008_5_1_4_1_1_77_2
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_7_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_7_2
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_7_3
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_7_4
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_8
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_88_1
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_88_11
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_88_2
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_88_22
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_88_3
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_88_33
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_88_4
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_88_40
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_88_50
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_88_59
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_88_65
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_88_67
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_1_9
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_9_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_9_1_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_9_1_2
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_9_1_3
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_9_2_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_9_3_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_1_9_4_1
gdcm::UIDs, [748](#)

uid_1_2_840_10008_5_1_4_1_2_1_1
gdcm::UIDs, [749](#)

uid_1_2_840_10008_5_1_4_1_2_1_2
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_1_2_1_3
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_1_2_2_1
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_1_2_2_2
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_1_2_2_3
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_1_2_3_1
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_1_2_3_2
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_1_2_3_3
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_31
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_32
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_32_1
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_32_2
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_32_3
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_33
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_34_1
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_34_2
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_34_3
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_34_4
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_34_4_1
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_34_4_2
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_34_4_3
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_34_4_4
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_34_5
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_37_1
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_37_2
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_37_3
gdcm::UIDs, [750](#)

uid_1_2_840_10008_5_1_4_38_1
gdcm::UIDs, [750](#)

- uid_1_2_840_10008_5_1_4_38_2
 - gdcm::UIDs, [750](#)
- uid_1_2_840_10008_5_1_4_38_3
 - gdcm::UIDs, [750](#)
- uid_1_2_840_10008_5_1_4_41
 - gdcm::UIDs, [750](#)
- uid_1_2_840_10008_5_1_4_42
 - gdcm::UIDs, [750](#)
- UltrasoundImageStorage
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- UltrasoundImageStorageRetired
 - gdcm::MediaStorage, [484](#)
 - gdcm::UIDs, [741](#)
- UltrasoundMultiFramedImageStorage
 - gdcm::MediaStorage, [484](#)
- UltrasoundMultiFramedImageStorageRetired
 - gdcm::MediaStorage, [484](#)
- UltrasoundMultiframeImageStorage
 - gdcm::UIDs, [741](#)
- UltrasoundMultiframeImageStorageRetired
 - gdcm::UIDs, [741](#)
- UnInstallPipeline
 - vtkImageColorViewer, [862](#)
- UnRegister
 - gdcm::Object, [512](#)
- UndefinedEntityError
 - gdcm::Parser, [524](#)
- underline
 - gdcm::terminal, [131](#)
- UnexpectedStateError
 - gdcm::Parser, [524](#)
- UnifiedProcedureStepEventSOPClass
 - gdcm::UIDs, [743](#)
- UnifiedProcedureStepPullSOPClass
 - gdcm::UIDs, [743](#)
- UnifiedProcedureStepPushSOPClass
 - gdcm::UIDs, [743](#)
- UnifiedProcedureStepWatchSOPClass
 - gdcm::UIDs, [743](#)
- UnifiedWorklistandProcedureStepSOPInstance
 - gdcm::UIDs, [743](#)
- UnifiedWorklistandProcedureStepServiceClass
 - gdcm::UIDs, [743](#)
- Unknown
 - gdcm::SwapCode, [697](#)
 - gdcm::TransferSyntax, [724](#)
- Unpack
 - gdcm::Unpacker12Bits, [804](#)
- Update
 - gdcm::Curve, [270](#)
 - gdcm::Overlay, [521](#)
- UpdateDisplayExtent
 - vtkImageColorViewer, [862](#)
- UpdateOrientation
 - vtkImageColorViewer, [862](#)
- UpdatePosition
 - gdcm::ByteBuffer, [216](#)
- Usage
 - gdcm::Usage, [806](#)
- UsageType
 - gdcm::Usage, [806](#)
- UseDictAlways
 - gdcm::PythonFilter, [581](#)
 - gdcm::StringFilter, [680](#)
- UserOption
 - gdcm::Usage, [806](#)
- UserInfoInformation
 - gdcm::network::UserInformation, [808](#)
- UserOrdering
 - gdcm::SerieHelper, [640](#)
- V
 - gdcm::Validate, [810](#)
- VERBOSE_STYLE
 - gdcm::Printer, [572](#)
- VERTEX
 - gdcm::MeshPrimitive, [494](#)
- VIEWType_END
 - gdcm::Surface, [686](#)
- VL16
 - gdcm::VR, [823](#)
- VL32
 - gdcm::VR, [823](#)
- VLEndoscopicImageStorage
 - gdcm::MediaStorage, [486](#)
 - gdcm::UIDs, [742](#)
- VLImageStorageTrialRetired
 - gdcm::UIDs, [742](#)
- VLMicroscopicImageStorage
 - gdcm::UIDs, [742](#)
- VLMultiframeImageStorageTrialRetired
 - gdcm::UIDs, [742](#)
- VLPhotographicImageStorage
 - gdcm::MediaStorage, [486](#)
 - gdcm::UIDs, [742](#)
- VLSlideCoordinatesMicroscopicImageStorage
 - gdcm::UIDs, [742](#)
- VLWholeSlideMicroscopyImageStorage
 - gdcm::MediaStorage, [486](#)
 - gdcm::UIDs, [745](#)
- VM0
 - gdcm::VM, [818](#)
- VM1
 - gdcm::VM, [818](#)
- VM10
 - gdcm::VM, [818](#)
- VM12

- gdcM::VM, [818](#)
- VM16
 - gdcM::VM, [818](#)
- VM18
 - gdcM::VM, [818](#)
- VM1_2
 - gdcM::VM, [819](#)
- VM1_3
 - gdcM::VM, [819](#)
- VM1_32
 - gdcM::VM, [819](#)
- VM1_4
 - gdcM::VM, [819](#)
- VM1_5
 - gdcM::VM, [819](#)
- VM1_8
 - gdcM::VM, [819](#)
- VM1_99
 - gdcM::VM, [819](#)
- VM1_n
 - gdcM::VM, [819](#)
- VM2
 - gdcM::VM, [818](#)
- VM24
 - gdcM::VM, [818](#)
- VM256
 - gdcM::VM, [819](#)
- VM28
 - gdcM::VM, [818](#)
- VM2_2n
 - gdcM::VM, [819](#)
- VM2_n
 - gdcM::VM, [819](#)
- VM3
 - gdcM::VM, [818](#)
- VM30_30n
 - gdcM::VM, [819](#)
- VM32
 - gdcM::VM, [818](#)
- VM35
 - gdcM::VM, [818](#)
- VM3_3n
 - gdcM::VM, [819](#)
- VM3_4
 - gdcM::VM, [819](#)
- VM3_n
 - gdcM::VM, [819](#)
- VM4
 - gdcM::VM, [818](#)
- VM47_47n
 - gdcM::VM, [819](#)
- VM4_4n
 - gdcM::VM, [819](#)
- VM5
 - gdcM::VM, [818](#)
- VM6
 - gdcM::VM, [818](#)
- VM6_6n
 - gdcM::VM, [819](#)
- VM7_7n
 - gdcM::VM, [819](#)
- VM8
 - gdcM::VM, [818](#)
- VM9
 - gdcM::VM, [818](#)
- VM99
 - gdcM::VM, [819](#)
- VM_END
 - gdcM::VM, [819](#)
- VMType
 - gdcM::Attribute, [165](#)
 - gdcM::Attribute< Group, Element, TVR, VM::VM1 >, [171](#)
- VOILUTBoxSOPClass
 - gdcM::UIDs, [741](#)
- VR_END
 - gdcM::VR, [823](#)
- VR_VM1
 - gdcM::VR, [823](#)
- VRALL
 - gdcM::VR, [823](#)
- VRASCII
 - gdcM::VR, [823](#)
- VRBINARY
 - gdcM::VR, [823](#)
- VT100
 - gdcM::terminal, [131](#)
- VIEWType
 - gdcM::Surface, [686](#)
- VL
 - gdcM::VL, [815](#)
- VM
 - gdcM::VM, [819](#)
- VMType
 - gdcM::VM, [818](#)
- VR
 - gdcM::VR, [823](#)
- VRBINARY
 - gdcM, [124](#)
- VRField
 - gdcM::CSAElement, [256](#)
 - gdcM::DataElement, [279](#)
- VRType
 - gdcM::VR, [822](#)
- VRTypeTemplateCase
 - gdcMVR.h, [1166](#)
- VTK_CMYK
 - vtkGDCMImageReader.h, [1172](#)

- VTK_LEGACY
 - vtkImageColorViewer, [862](#)
- VTK_LOOKUP_TABLE
 - vtkGDCMImageReader.h, [1172](#)
- VTK_YBR
 - vtkGDCMImageReader.h, [1172](#)
- Valid
 - gdcm::Preamble, [561](#)
- Validate
 - gdcm::PixelFormat, [545](#)
 - gdcm::Validate, [810](#)
- ValidateQuery
 - gdcm::BaseRootQuery, [197](#)
 - gdcm::FindPatientRootQuery, [379](#)
 - gdcm::FindStudyRootQuery, [381](#)
 - gdcm::MovePatientRootQuery, [504](#)
 - gdcm::MoveStudyRootQuery, [507](#)
- Validation
 - gdcm::Validate, [810](#)
- Value
 - gdcm::Value, [811](#)
- value
 - gdcm::SerieHelper::Rule, [610](#)
 - gdcm::STATIC_ASSERTION_FAILURE< true >, [666](#)
- value_type
 - gdcm::CodeString, [238](#)
 - gdcm::LO, [471](#)
 - gdcm::String, [676](#)
- ValueField
 - gdcm::DataElement, [279](#)
 - gdcm::PDBelement, [529](#)
- ValueLengthField
 - gdcm::DataElement, [279](#)
- ValueMultiplicityField
 - gdcm::CSAElement, [256](#)
- ValuePtr
 - gdcm::DataElement, [273](#)
- ValueType
 - gdcm::Scanner, [614](#)
- VerificationSOPClass
 - gdcm::UIDs, [738](#)
- Verify
 - gdcm::Defs, [295](#), [296](#)
 - gdcm::Macro, [477](#)
 - gdcm::Module, [498](#)
- Version
 - gdcm::Version, [813](#)
- Video
 - gdcm::MediaStorage, [486](#)
- VideoEndoscopicImageStorage
 - gdcm::MediaStorage, [485](#)
 - gdcm::UIDs, [742](#)
- VideoMicroscopicImageStorage
 - gdcm::UIDs, [742](#)
- VideoPhotographicImageStorage
 - gdcm::UIDs, [742](#)
- vtkGDCMImageWriter
 - JPEG2000_COMPRESSION, [837](#)
 - JPEG_COMPRESSION, [837](#)
 - JPEGLS_COMPRESSION, [837](#)
 - NO_COMPRESSION, [837](#)
 - RLE_COMPRESSION, [837](#)
- vtkImageColorViewer
 - SLICE_ORIENTATION_XY, [859](#)
 - SLICE_ORIENTATION_XZ, [859](#)
 - SLICE_ORIENTATION_YZ, [859](#)
- vtkBooleanMacro
 - vtkGDCMImageReader, [833](#)
 - vtkGDCMImageWriter, [838](#)
 - vtkGDCMThreadedImageReader, [852](#)
 - vtkGDCMThreadedImageReader2, [855](#)
 - vtkImageColorViewer, [862](#)
 - vtkImageMapToColors16, [865](#)
- vtkGDCMImageReader, [829](#)
 - ~vtkGDCMImageReader, [831](#)
 - ApplyInverseVideo, [834](#)
 - ApplyLookupTable, [834](#)
 - ApplyPlanarConfiguration, [834](#)
 - ApplyShiftScale, [834](#)
 - ApplyYBRToRGB, [834](#)
 - CanReadFile, [832](#)
 - Curve, [834](#)
 - DirectionCosines, [834](#)
 - ExecuteData, [832](#)
 - ExecuteInformation, [832](#)
 - FileNames, [834](#)
 - FillMedicalImageInformation, [832](#)
 - ForceRescale, [834](#)
 - GetDescriptiveName, [832](#)
 - GetFileExtensions, [832](#)
 - GetIconImage, [832](#)
 - GetOverlay, [832](#)
 - IconDataScalarType, [834](#)
 - IconImageDataExtent, [834](#)
 - IconNumberOfScalarComponents, [834](#)
 - ImageFormat, [834](#)
 - ImageOrientationPatient, [834](#)
 - ImagePositionPatient, [834](#)
 - LoadIconImage, [835](#)
 - LoadOverlays, [835](#)
 - LoadSingleFile, [832](#)
 - LossyFlag, [835](#)
 - MedicalImageProperties, [835](#)
 - New, [832](#)
 - NumberOfIconImages, [835](#)
 - NumberOfOverlays, [835](#)
 - PlanarConfiguration, [835](#)

- PrintSelf, [832](#)
- RequestDataCompat, [832](#)
- RequestInformationCompat, [832](#)
- Scale, [835](#)
- SetCurve, [832](#)
- SetFileNames, [832](#)
- SetFilePattern, [833](#)
- SetFilePrefix, [833](#)
- SetMedicalImageProperties, [833](#)
- Shift, [835](#)
- vtkBooleanMacro, [833](#)
- vtkGDCMImageReader, [831](#)
- vtkGetMacro, [833](#)
- vtkGetObjectMacro, [833](#)
- vtkGetStringMacro, [834](#)
- vtkGetVector3Macro, [834](#)
- vtkGetVector6Macro, [834](#)
- vtkSetMacro, [834](#)
- vtkSetVector6Macro, [834](#)
- vtkTypeRevisionMacro, [834](#)
- vtkGDCMImageReader, [831](#)
- vtkGDCMMedicalImageProperties, [841](#)
- vtkGDCMImageReader.h, [1170](#)
- VTK_CMYK, [1172](#)
- VTK_YBR, [1172](#)
- vtkGDCMImageWriter, [835](#)
- ~vtkGDCMImageWriter, [837](#)
- CompressionTypes, [837](#)
- GetDescriptiveName, [837](#)
- GetFileExtensions, [838](#)
- GetFileName, [838](#)
- New, [838](#)
- PrintSelf, [838](#)
- SetDirectionCosines, [838](#)
- SetDirectionCosinesFromImageOrientationPatient, [838](#)
- SetFileNames, [838](#)
- SetMedicalImageProperties, [838](#)
- vtkBooleanMacro, [838](#)
- vtkGDCMImageWriter, [837](#)
- vtkGetMacro, [838](#), [839](#)
- vtkGetObjectMacro, [839](#)
- vtkGetStringMacro, [839](#)
- vtkSetMacro, [839](#)
- vtkSetStringMacro, [839](#)
- vtkTypeRevisionMacro, [839](#)
- vtkGDCMImageWriter, [837](#)
- vtkGDCMMedicalImageProperties, [841](#)
- Write, [839](#)
- WriteGDCMData, [839](#)
- WriteSlice, [839](#)
- vtkGDCMImageWriter.h, [1172](#)
- vtkGDCMMedicalImageProperties, [840](#)
- ~vtkGDCMMedicalImageProperties, [841](#)
- Clear, [841](#)
- GetFile, [841](#)
- New, [841](#)
- PrintSelf, [841](#)
- PushBackFile, [841](#)
- vtkGDCMImageReader, [841](#)
- vtkGDCMImageWriter, [841](#)
- vtkGDCMMedicalImageProperties, [841](#)
- vtkTypeRevisionMacro, [841](#)
- vtkGDCMMedicalImageProperties, [841](#)
- vtkGDCMMedicalImageProperties.h, [1172](#)
- vtkGDCMPolyDataReader, [841](#)
- ~vtkGDCMPolyDataReader, [843](#)
- FileName, [844](#)
- FillMedicalImageInformation, [843](#)
- MedicalImageProperties, [844](#)
- New, [843](#)
- PrintSelf, [843](#)
- RTStructSetProperties, [844](#)
- RequestData, [843](#)
- RequestData_HemodynamicWaveformStorage, [843](#)
- RequestData_RTStructureSetStorage, [843](#)
- RequestInformation, [844](#)
- RequestInformation_HemodynamicWaveform-Storage, [844](#)
- RequestInformation_RTStructureSetStorage, [844](#)
- vtkGDCMPolyDataReader, [843](#)
- vtkGetObjectMacro, [844](#)
- vtkGetStringMacro, [844](#)
- vtkSetStringMacro, [844](#)
- vtkTypeRevisionMacro, [844](#)
- vtkGDCMPolyDataReader, [843](#)
- vtkGDCMPolyDataReader.h, [1173](#)
- vtkGDCMPolyDataWriter, [844](#)
- ~vtkGDCMPolyDataWriter, [846](#)
- InitializeRTStructSet, [846](#)
- MedicalImageProperties, [847](#)
- New, [846](#)
- PrintSelf, [846](#)
- RTStructSetProperties, [847](#)
- SetMedicalImageProperties, [846](#)
- SetNumberOfInputPorts, [847](#)
- SetRTStructSetProperties, [847](#)
- vtkGDCMPolyDataWriter, [846](#)
- vtkTypeRevisionMacro, [847](#)
- vtkGDCMPolyDataWriter, [846](#)
- WriteData, [847](#)
- WriteRTSTRUCTData, [847](#)
- WriteRTSTRUCTInfo, [847](#)
- vtkGDCMPolyDataWriter.h, [1174](#)
- vtkGDCMTesting, [847](#)
- ~vtkGDCMTesting, [849](#)
- GetGDCMDataRoot, [849](#)
- GetMD5MetaImage, [849](#)

- GetMHDMD5FromFile, 849
- GetNumberOfMD5MetalImages, 849
- GetRAWMD5FromFile, 849
- GetVTKDataRoot, 849
- MD5MetalImagesType, 849
- New, 849
- PrintSelf, 849
- vtkGDCMTesting, 849
- vtkTypeRevisionMacro, 850
- vtkGDCMTesting, 849
- vtkGDCMTesting.h, 1175
- vtkGDCMThreadedImageReader, 850
 - ~vtkGDCMThreadedImageReader, 852
 - ExecuteData, 852
 - ExecuteInformation, 852
 - New, 852
 - PrintSelf, 852
 - ReadFiles, 852
 - RequestDataCompat, 852
 - vtkBooleanMacro, 852
 - vtkGDCMThreadedImageReader, 851
 - vtkGetMacro, 852
 - vtkSetMacro, 852
 - vtkTypeRevisionMacro, 852
 - vtkGDCMThreadedImageReader, 851
- vtkGDCMThreadedImageReader.h, 1175
- vtkGDCMThreadedImageReader2, 852
 - ~vtkGDCMThreadedImageReader2, 854
 - GetFileName, 854
 - New, 854
 - PrintSelf, 854
 - RequestInformation, 854
 - SetFileName, 854
 - SetFileNames, 854
 - SplitExtent, 855
 - ThreadedRequestData, 855
 - vtkBooleanMacro, 855
 - vtkGDCMThreadedImageReader2, 854
 - vtkGetMacro, 855
 - vtkGetObjectMacro, 855
 - vtkGetVector3Macro, 855
 - vtkGetVector6Macro, 855
 - vtkSetMacro, 855
 - vtkSetVector3Macro, 855, 856
 - vtkSetVector6Macro, 856
 - vtkTypeRevisionMacro, 856
 - vtkGDCMThreadedImageReader2, 854
- vtkGDCMThreadedImageReader2.h, 1176
- vtkGetMacro
 - vtkGDCMImageReader, 833
 - vtkGDCMImageWriter, 838, 839
 - vtkGDCMThreadedImageReader, 852
 - vtkGDCMThreadedImageReader2, 855
 - vtkImageColorViewer, 862
 - vtkImageMapToColors16, 865
 - vtkImageMapToWindowLevelColors2, 867
- vtkGetObjectMacro
 - vtkGDCMImageReader, 833
 - vtkGDCMImageWriter, 839
 - vtkGDCMPolyDataReader, 844
 - vtkGDCMThreadedImageReader2, 855
 - vtkImageColorViewer, 862
 - vtkImageMapToColors16, 865
- vtkGetStringMacro
 - vtkGDCMImageReader, 834
 - vtkGDCMImageWriter, 839
 - vtkGDCMPolyDataReader, 844
 - vtkRTStructSetProperties, 879
- vtkGetVector3Macro
 - vtkGDCMImageReader, 834
 - vtkGDCMThreadedImageReader2, 855
- vtkGetVector6Macro
 - vtkGDCMImageReader, 834
 - vtkGDCMThreadedImageReader2, 855
- vtkImageColorViewer, 856
 - ~vtkImageColorViewer, 859
 - AddInput, 859
 - AddInputConnection, 859
 - FirstRender, 862
 - GetColorLevel, 859
 - GetColorWindow, 859
 - GetInput, 859
 - GetOffScreenRendering, 859
 - GetOverlayVisibility, 859
 - GetPosition, 859
 - GetSize, 860
 - GetSliceMax, 860
 - GetSliceMin, 860
 - GetSliceRange, 860
 - GetWindowName, 860
 - ImageActor, 862
 - InstallPipeline, 860
 - Interactor, 862
 - InteractorStyle, 862
 - New, 860
 - OverlayImageActor, 862
 - PrintSelf, 860
 - Render, 860
 - RenderWindow, 862
 - Renderer, 862
 - SetColorLevel, 860
 - SetColorWindow, 860
 - SetDisplayId, 860
 - SetInput, 860
 - SetInputConnection, 860
 - SetOffScreenRendering, 860
 - SetOverlayVisibility, 860
 - SetParentId, 860

- SetPosition, [861](#)
- SetRenderWindow, [861](#)
- SetRenderer, [861](#)
- SetSize, [861](#)
- SetSlice, [861](#)
- SetSliceOrientation, [861](#)
- SetSliceOrientationToXY, [861](#)
- SetSliceOrientationToXZ, [861](#)
- SetSliceOrientationToYZ, [861](#)
- SetWindowId, [861](#)
- SetupInteractor, [861](#)
- Slice, [862](#)
- SliceOrientation, [862](#)
- UnInstallPipeline, [862](#)
- UpdateDisplayExtent, [862](#)
- UpdateOrientation, [862](#)
- VTK_LEGACY, [862](#)
- vtkBooleanMacro, [862](#)
- vtkGetMacro, [862](#)
- vtkGetObjectMacro, [862](#)
- vtkImageColorViewer, [859](#)
- vtkTypeRevisionMacro, [862](#)
- vtkImageColorViewer, [859](#)
- WindowLevel, [863](#)
- vtkImageColorViewer.h, [1176](#)
- vtkImageMapToColors16, [863](#)
 - ~vtkImageMapToColors16, [864](#)
 - ActiveComponent, [865](#)
 - DataWasPassed, [865](#)
 - GetMTime, [864](#)
 - LookupTable, [865](#)
 - New, [864](#)
 - OutputFormat, [865](#)
 - PassAlphaToOutput, [865](#)
 - PrintSelf, [864](#)
 - RequestData, [865](#)
 - RequestInformation, [865](#)
 - SetLookupTable, [865](#)
 - SetOutputFormatToLuminance, [865](#)
 - SetOutputFormatToLuminanceAlpha, [865](#)
 - SetOutputFormatToRGB, [865](#)
 - SetOutputFormatToRGBA, [865](#)
 - ThreadedRequestData, [865](#)
 - vtkBooleanMacro, [865](#)
 - vtkGetMacro, [865](#)
 - vtkGetObjectMacro, [865](#)
 - vtkImageMapToColors16, [864](#)
 - vtkSetMacro, [865](#)
 - vtkTypeRevisionMacro, [865](#)
 - vtkImageMapToColors16, [864](#)
- vtkImageMapToColors16.h, [1177](#)
- vtkImageMapToWindowLevelColors2, [866](#)
 - ~vtkImageMapToWindowLevelColors2, [867](#)
 - Level, [868](#)
 - New, [867](#)
 - PrintSelf, [867](#)
 - RequestData, [867](#)
 - RequestInformation, [867](#)
 - ThreadedRequestData, [867](#)
 - vtkGetMacro, [867](#)
 - vtkImageMapToWindowLevelColors2, [867](#)
 - vtkSetMacro, [867](#), [868](#)
 - vtkTypeRevisionMacro, [868](#)
 - vtkImageMapToWindowLevelColors2, [867](#)
 - Window, [868](#)
- vtkImageMapToWindowLevelColors2.h, [1177](#)
- vtkImagePlanarComponentsToComponents, [868](#)
 - ~vtkImagePlanarComponentsToComponents, [869](#)
 - New, [869](#)
 - PrintSelf, [869](#)
 - RequestData, [869](#)
 - vtkImagePlanarComponentsToComponents, [869](#)
 - vtkTypeRevisionMacro, [870](#)
 - vtkImagePlanarComponentsToComponents, [869](#)
- vtkImagePlanarComponentsToComponents.h, [1178](#)
- vtkImageRGBToYBR, [870](#)
 - ~vtkImageRGBToYBR, [871](#)
 - New, [871](#)
 - PrintSelf, [871](#)
 - ThreadedExecute, [871](#)
 - vtkImageRGBToYBR, [871](#)
 - vtkTypeRevisionMacro, [871](#)
 - vtkImageRGBToYBR, [871](#)
- vtkImageRGBToYBR.h, [1178](#)
- vtkImageYBRToRGB, [871](#)
 - ~vtkImageYBRToRGB, [873](#)
 - New, [873](#)
 - PrintSelf, [873](#)
 - ThreadedExecute, [873](#)
 - vtkImageYBRToRGB, [873](#)
 - vtkTypeRevisionMacro, [873](#)
 - vtkImageYBRToRGB, [873](#)
- vtkImageYBRToRGB.h, [1179](#)
- vtkLookupTable16, [873](#)
 - ~vtkLookupTable16, [874](#)
 - Build, [874](#)
 - GetPointer, [875](#)
 - MapScalarsThroughTable2, [875](#)
 - New, [875](#)
 - PrintSelf, [875](#)
 - SetNumberOfTableValues, [875](#)
 - Table16, [875](#)
 - vtkLookupTable16, [874](#)
 - vtkTypeRevisionMacro, [875](#)
 - vtkLookupTable16, [874](#)
 - WritePointer, [875](#)
- vtkLookupTable16.h, [1179](#)
- vtkRTStructSetProperties, [875](#)

- ~vtkRTStructSetProperties, [877](#)
- AddContourReferencedFrameOfReference, [877](#)
- AddReferencedFrameOfReference, [878](#)
- AddStructureSetROI, [878](#)
- AddStructureSetROIObservation, [878](#)
- Clear, [878](#)
- DeepCopy, [878](#)
- GetContourReferencedFrameOfReferenceClassUID, [878](#)
- GetContourReferencedFrameOfReferenceInstanceUID, [878](#)
- GetNumberOfContourReferencedFrameOfReferences, [878](#)
- GetNumberOfReferencedFrameOfReferences, [878](#)
- GetNumberOfStructureSetROIs, [878](#)
- GetReferencedFrameOfReferenceClassUID, [878](#)
- GetReferencedFrameOfReferenceInstanceUID, [878](#)
- GetStructureSetObservationNumber, [878](#)
- GetStructureSetROIDescription, [878](#)
- GetStructureSetROIGenerationAlgorithm, [878](#)
- GetStructureSetROIName, [878](#)
- GetStructureSetROINumber, [878](#)
- GetStructureSetROIObservationLabel, [878](#)
- GetStructureSetROIRefFrameRefUID, [878](#)
- GetStructureSetRTROIInterpretedType, [878](#)
- Internals, [879](#)
- New, [878](#)
- PrintSelf, [879](#)
- ReferenceFrameOfReferenceUID, [879](#)
- ReferenceSeriesInstanceUID, [879](#)
- SOPInstanceUID, [880](#)
- SeriesInstanceUID, [880](#)
- StructureSetDate, [880](#)
- StructureSetLabel, [880](#)
- StructureSetName, [880](#)
- StructureSetTime, [880](#)
- StudyInstanceUID, [880](#)
- vtkGetStringMacro, [879](#)
- vtkRTStructSetProperties, [877](#)
- vtkSetStringMacro, [879](#)
- vtkTypeRevisionMacro, [879](#)
- vtkRTStructSetProperties, [877](#)
- vtkRTStructSetProperties.h, [1180](#)
- vtkSetMacro
 - vtkGDCMImageReader, [834](#)
 - vtkGDCMImageWriter, [839](#)
 - vtkGDCMThreadedImageReader, [852](#)
 - vtkGDCMThreadedImageReader2, [855](#)
 - vtkImageMapToColors16, [865](#)
 - vtkImageMapToWindowLevelColors2, [867](#), [868](#)
- vtkSetStringMacro
 - vtkGDCMImageWriter, [839](#)
 - vtkGDCMPolyDataReader, [844](#)
 - vtkRTStructSetProperties, [879](#)
- vtkSetVector3Macro
 - vtkGDCMThreadedImageReader2, [855](#), [856](#)
- vtkSetVector6Macro
 - vtkGDCMImageReader, [834](#)
 - vtkGDCMThreadedImageReader2, [856](#)
- vtkTypeRevisionMacro
 - vtkGDCMImageReader, [834](#)
 - vtkGDCMImageWriter, [839](#)
 - vtkGDCMMedicalImageProperties, [841](#)
 - vtkGDCMPolyDataReader, [844](#)
 - vtkGDCMPolyDataWriter, [847](#)
 - vtkGDCMTesting, [850](#)
 - vtkGDCMThreadedImageReader, [852](#)
 - vtkGDCMThreadedImageReader2, [856](#)
 - vtkImageColorViewer, [862](#)
 - vtkImageMapToColors16, [865](#)
 - vtkImageMapToWindowLevelColors2, [868](#)
 - vtkImagePlanarComponentsToComponents, [870](#)
 - vtkImageRGBToYBR, [871](#)
 - vtkImageYBRToRGB, [873](#)
 - vtkLookupTable16, [875](#)
 - vtkRTStructSetProperties, [879](#)
- WIREFRAME
 - gdcm::Surface, [686](#)
- WarningOff
 - gdcm::Trace, [722](#)
- WarningOn
 - gdcm::Trace, [722](#)
- Waveform
 - gdcm::Waveform, [880](#)
 - gdcm::MediaStorage, [486](#)
- WaveformStorageTrialRetired
 - gdcm::UIDs, [741](#)
- what
 - gdcm::Exception, [348](#)
- white
 - gdcm::terminal, [131](#)
- Window
 - vtkImageMapToWindowLevelColors2, [868](#)
- WindowLevel
 - vtkImageColorViewer, [863](#)
- Write
 - gdcm::ByteValue, [222](#)
 - gdcm::CommandDataSet, [243](#)
 - gdcm::CSAHeader, [260](#)
 - gdcm::DataElement, [278](#)
 - gdcm::DataSet, [289](#)
 - gdcm::Element, [325](#)
 - gdcm::Element< TVR, VM::VM1_n >, [329](#)
 - gdcm::EncodingImplementation< VR::VRASCII >, [342](#)
 - gdcm::EncodingImplementation< VR::VRBINARY >, [343](#)

- gdcm::ExplicitDataElement, [351](#)
- gdcm::File, [357](#)
- gdcm::FileAnonymizer, [360](#)
- gdcm::FileMetaInformation, [369](#)
- gdcm::Fragment, [383](#)
- gdcm::ImageWriter, [432](#)
- gdcm::ImplicitDataElement, [436](#)
- gdcm::Item, [449](#)
- gdcm::network::AAAbortPDU, [135](#)
- gdcm::network::AAAssociateACPDU, [137](#)
- gdcm::network::AAAssociateRJPDU, [139](#)
- gdcm::network::AAAssociateRQPDU, [143](#)
- gdcm::network::AbstractSyntax, [145](#)
- gdcm::network::ApplicationContext, [154](#)
- gdcm::network::AResultRPPDU, [158](#)
- gdcm::network::AResultRQPDU, [160](#)
- gdcm::network::AsynchronousOperationsWindow-Sub, [162](#)
- gdcm::network::BasePDU, [194](#)
- gdcm::network::ImplementationClassUIDSub, [433](#)
- gdcm::network::ImplementationUIDSub, [434](#)
- gdcm::network::ImplementationVersionNameSub, [434](#)
- gdcm::network::MaximumLengthSub, [480](#)
- gdcm::network::PDataTFPDU, [527](#)
- gdcm::network::PresentationContextAC, [564](#)
- gdcm::network::PresentationContextRQ, [568](#)
- gdcm::network::PresentationDataValue, [570](#)
- gdcm::network::RoleSelectionSub, [609](#)
- gdcm::network::ServiceClassApplicationInformation, [641](#)
- gdcm::network::SOPClassExtendedNegotiationSub, [656](#)
- gdcm::network::TransferSyntaxSub, [727](#)
- gdcm::network::UserInformation, [809](#)
- gdcm::PGXCodec, [538](#)
- gdcm::PixmapWriter, [557](#)
- gdcm::PNMCodec, [559](#)
- gdcm::Preamble, [561](#)
- gdcm::SegmentWriter, [627](#)
- gdcm::SequenceOfFragments, [632](#)
- gdcm::SequenceOfItems, [637](#)
- gdcm::StreamImageWriter, [672](#)
- gdcm::SurfaceWriter, [696](#)
- gdcm::Tag, [714](#)
- gdcm::ValueIO, [812](#)
- gdcm::VL, [816](#)
- gdcm::VR, [824](#)
- gdcm::VRVLSize< 0 >, [828](#)
- gdcm::VRVLSize< 1 >, [828](#)
- gdcm::Writer, [885](#)
- vtkGDCMImageWriter, [839](#)
- Write16
 - gdcm::VL, [816](#)
- WriteASCII
 - gdcm::Element< TVR, VM::VM1_n >, [329](#)
- WriteBuffer
 - gdcm::ByteValue, [223](#)
 - gdcm::SequenceOfFragments, [632](#)
- WriteBufferAsRGBA
 - gdcm::LookupTable, [475](#)
- WriteData
 - vtkGDCMPolyDataWriter, [847](#)
- WriteFooter
 - gdcm::DictConverter, [305](#)
- WriteGDCMData
 - vtkGDCMImageWriter, [839](#)
- WriteHeader
 - gdcm::DictConverter, [305](#)
- WriteHelpFile
 - gdcm::BaseRootQuery, [198](#)
- WriteImageInformation
 - gdcm::StreamImageWriter, [673](#)
- WriteImageSubregionRAW
 - gdcm::StreamImageWriter, [673](#)
- WritePointer
 - vtkLookupTable16, [875](#)
- WriteQuery
 - gdcm::BaseRootQuery, [198](#)
- WriteRTSTRUCTData
 - vtkGDCMPolyDataWriter, [847](#)
- WriteRTSTRUCTInfo
 - vtkGDCMPolyDataWriter, [847](#)
- WriteRawHeader
 - gdcm::StreamImageWriter, [673](#)
- WriteSlice
 - vtkGDCMImageWriter, [839](#)
- Writer
 - gdcm::Writer, [884](#)
- XML
 - gdcm::Printer, [572](#)
- XMLEncoding
 - gdcm::UIDs, [739](#)
- XRay3DAngiographicImageStorage
 - gdcm::MediaStorage, [486](#)
 - gdcm::UIDs, [742](#)
- XRay3DCraniofacialImageStorage
 - gdcm::UIDs, [742](#)
- XRayAngiographicBiPlaneImageStorageRetired
 - gdcm::MediaStorage, [485](#)
 - gdcm::UIDs, [742](#)
- XRayAngiographicImageStorage
 - gdcm::MediaStorage, [485](#)
 - gdcm::UIDs, [742](#)
- XRayRadiationDoseSR
 - gdcm::MediaStorage, [486](#)
- XRayRadiationDoseSRStorage

- gdcm::UIDs, [743](#)
- XRayRadiofluoroscopicImageStorage
 - gdcm::UIDs, [742](#)
- XRayRadiofluoroscopicImageStorage
 - gdcm::MediaStorage, [485](#)
- XMLDictReader
 - gdcm::XMLDictReader, [887](#)
- XMLPrivateDictReader
 - gdcm::XMLPrivateDictReader, [889](#)
- YBR_FULL
 - gdcm::PhotometricInterpretation, [539](#)
- YBR_FULL_422
 - gdcm::PhotometricInterpretation, [539](#)
- YBR_ICT
 - gdcm::PhotometricInterpretation, [539](#)
- YBR_PARTIAL_420
 - gdcm::PhotometricInterpretation, [539](#)
- YBR_PARTIAL_422
 - gdcm::PhotometricInterpretation, [539](#)
- YBR_RCT
 - gdcm::PhotometricInterpretation, [539](#)
- YES
 - gdcm::Surface, [686](#)
- YBR2RGB
 - gdcm::ImageChangePhotometricInterpretation, [403](#)
- yellow
 - gdcm::terminal, [131](#)
- ZEROED_OUT
 - gdcm::CSAHeader, [258](#)
- ZSpacing
 - gdcm::IPPSorter, [446](#)
- ZTolerance
 - gdcm::IPPSorter, [446](#)